



## RF Exposure Evaluation Declaration

---

**FCC ID:** T2C-RT30  
**IC:** 10741A-RT30  
**APPLICANT:** YEALINK(XIAMEN) NETWORK TECHNOLOGY  
CO.,LTD

**Application Type:** Certification  
**Product:** DECT Repeater  
**Model No.:** RT30  
**Brand Name:** YEALINK  
**FCC Classification:** Digital Transmission System (DTS)  
Unlicensed National Information Infrastructure (UNII)  
**Test Procedure(s):** KDB 447498 D01v06

Reviewed By : *Sunny Sun*  
( Sunny Sun )  
Approved By : *Marlinchen*  
( Marlin Chen )



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

---

## Revision History

Report No.	Version	Description	Issue Date	Note
1801RSU025-U2	Rev. 01	Initial Report	03-02-2018	Valid

## 1. PRODUCT INFORMATION

### 1.1. Equipment Description

Product Name	DECT Repeater
Model No.	RT30
Brand Name:	YEALINK

### 1.2. Product Specification Subjective to this Report

Frequency Range	1921.536 ~ 1928.448MHz
Number of Channels	5
Maximum Output Power	19.51dBm
Type of Modulation	Digital (Gaussian Frequency Shift Keying)
Antenna Gain	-1dBi

## 2. RF Exposure Evaluation

### 2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	f/1500	6
1500-100,000	--	--	1	30

f= Frequency in MHz

Calculation Formula:  $Pd = (Pout \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

r = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

## 2.2. Test Result of RF Exposure Evaluation

Product	DECT Repeater
Test Item	RF Exposure Evaluation

Test Mode	Frequency Band (MHz)	Maximum EIRP (dBm)	Safety Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit of Power Density (mW/cm <sup>2</sup> )
DECT	1921.536 ~ 1928.448	18.51	20	0.0141	1

The wireless device described within this report has been shown to be capable of compliance with basic restrictions related to human exposure to electromagnetic fields. The calculations shown in this report were made in accordance the procedures specified in the applied test specifications. The safety distance is 20cm.

\_\_\_\_\_ The End \_\_\_\_\_