



FCC PART 15.249


TEST REPORT

For

Vson Technology Co., Ltd.

5 Floor, A Building, Weixinda Xichen Industrial Park, Baoan District,
Shenzhen 518102, China

FCC ID: T2DV829

Report Type: Original Report	Product Type: Wireless Presenter
Test Engineer: <u>Jimmy Xiao</u> 	
Report Number: <u>RSZ111226004-00</u>	
Report Date: <u>2012-01-06</u>	
Reviewed By: Merry Zhao EMC Engineer	
Test Laboratory: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP*, or any agency of the Federal Government.

* This report contains data that are not covered by the NVLAP accreditation and are marked with an asterisk “★” (Rev.2)

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
TEST FACILITY	3
SYSTEM TEST CONFIGURATION.....	5
JUSTIFICATION	5
EQUIPMENT MODIFICATIONS	5
CONFIGURATION OF TEST SETUP	5
BLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS.....	6
FCC§15.203 - ANTENNA REQUIREMENT.....	7
APPLICABLE STANDARD	7
ANTENNA CONNECTOR CONSTRUCTION	7
FCC§15.205(A) §15.209(A) §15.249(A) §15.249(C) §15.249(D) §15.35 - RADIATED EMISSIONS	8
APPLICABLE STANDARD	8
MEASUREMENT UNCERTAINTY	8
TEST EQUIPMENT SETUP	8
EUT SETUP	9
TEST PROCEDURE	9
TEST EQUIPMENT LIST AND DETAILS.....	10
CORRECTED AMPLITUDE & MARGIN CALCULATION	10
TEST RESULTS SUMMARY	10
TEST DATA	10

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Vson Technology Co., Ltd.*'s product, model: V-829 (FCC ID: T2DV829), or the "EUT" as referred to in this report was a *Wireless Presenter*, which measures approximately: 10.0 cm (L) x 3.4 cm (W) x 1.1cm (H), rated input voltage: DC 3V battery.

** All measurement and test data in this report was gathered from production sample serial number: 1112084 (Assigned by BACL, Shenzhen). The EUT was received on 2011-12-26*

Objective

This report is prepared on behalf of *Vson Technology Co., Ltd.* in accordance with Part 2, Subpart J, and Part 15, Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.249 rules.

Related Submittal(s)/Grant(s)

No submittal(s).

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>

SYSTEM TEST CONFIGURATION

Justification

The system was configured for testing in an engineering mode.


Equipment Modifications

No modifications were made to the unit tested.

Configuration of Test Setup



Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207(a)	Conduction Emissions	N/A*
§15.209(a) §15.249(a) §15.249(c) §15.249(d)§15.35	Radiated Emissions	Compliance
§15.215(c)	20dB Bandwidth	Compliance

Note: N/A* The EUT was powered by battery only.

FCC§15.203 - ANTENNA REQUIREMENT

Applicable Standard

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used.

Antenna Connector Construction

The EUT has a PCB type antenna on board, which in accordance to section 15.203, is considered sufficient to comply with the provisions of this section.

Result: Compliant.

Please refer to the EUT internal photos.

FCC§15.205(a) §15.209(a) §15.249(a) §15.249(c) §15.249(d) §15.35 - RADIATED EMISSIONS

Applicable Standard

As per FCC§15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24.0–24.25 GHz	250	2500

As per FCC§15.249 (c), Field strength limits are specified at a distance of 3 meters.

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR 16-4-4, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is 4.0 dB.

Test Equipment Setup

The spectrum analyzer or receiver is set as:

Below 1000MHz:

RBW = 100 kHz / VBW = 300 kHz / Sweep = Auto


Above 1000MHz:

Peak: RBW = 1MHz / VBW = 1MHz / Sweep = Auto


Average: RBW = 1MHz / VBW = 10Hz / Sweep = Auto

EUT Setup

Below 1 GHz:



Above 1 GHz:



The radiated emission and out of band emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209 and FCC 15.249 limits.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The EUT is set 3 meter away from the testing antenna, which is varied from 1-4 meter, and the EUT is placed on a turntable, which is 0.8 meter above ground plane, the table shall be rotated for 360 degrees to find out the highest emission. The receiving antenna should be changed the polarization both of horizontal and vertical.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	HP8447D	2944A09795	2011-08-02	2012-08-01
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2011-03-11	2012-03-10
Mini-Circuits	Amplifier	ZVA-213+	T-E27H	2011-03-08	2012-03-07
Sunol Sciences	Horn Antenna	DRH-118	A052604	2011-05-05	2012-05-04
Rohde & Schwarz	Signal Analyzer	FSIQ 26	609358	2011-07-08	2012-07-07
Agilent	Spectrum Analyzer	8564E	3943A01781	2011-04-12	2012-04-11
the electro-Mechanics Co.	Horn Antenna	3116	9510-2270	2011-05-05	2012-05-04

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.209 & 15.249, with the worst margin reading of:

1.41 dB at 4864 MHz in the Horizontal polarization

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56%
ATM Pressure:	100.0 kPa

The testing was performed by Jimmy Xiao on 2011-12-27

Test Mode: Transmitting



Frequency 30MHz to 25 GHz:

Freq. (MHz)	Reading (dB μ V)	Detector QP/PK/Ave.	Direction Degree	Height (m)	Polar H/V	Ant. Loss (dB)	Cable loss (dB)	Amp. Gain (dB)	Corrected Amplitude (dB μ V/m)	FCC 15.249/15.209/15.205		
										Limit (dB μ V/m)	Margin (dB)	Comment
4864	58.52	PK	150	1.3	H	36.5	4.35	26.78	72.59	74	1.41*	Harmonic
7296	53.81	PK	160	1.8	H	39.1	5.19	26.62	71.48	74	2.52*	Harmonic
4864	55.67	PK	240	1.5	V	35.3	4.35	26.78	68.54	74	5.46	Harmonic
7296	52.03	PK	250	1.4	V	37.8	5.19	26.62	68.40	74	5.60	Harmonic
2432	95.56	PK	180	1.1	V	30.4	3.08	26.85	102.19	114	11.81	Fundament
2484.1	53.38	PK	330	1.2	V	30.3	3.14	26.85	59.97	74	14.03	Spurious
2389.5	53.14	PK	230	1.5	V	30.2	3.01	26.84	59.51	74	14.49	Spurious
7296	20.52	Ave.	160	1.8	H	39.1	5.19	26.62	38.19	54	15.81	Harmonic
7296	19.38	Ave.	250	1.4	V	37.8	5.19	26.62	35.75	54	18.25	Harmonic
2432	88.87	PK	230	1.2	H	30.4	3.08	26.85	95.50	114	18.5	Fundament
4864	21.34	Ave.	150	1.3	H	36.5	4.35	26.78	35.41	54	18.59	Harmonic
2484.1	48.14	PK	160	1.4	H	30.3	3.14	26.85	54.73	74	19.27	Spurious
4864	21.19	Ave.	240	1.5	V	35.3	4.35	26.78	34.06	54	19.94	Harmonic
2389.5	46.57	PK	240	1.1	H	30.2	3.01	26.84	52.94	74	21.06	Spurious
2389.5	22.17	Ave.	230	1.5	V	30.2	3.01	26.84	28.54	54	25.46	Spurious
2389.5	21.16	Ave.	240	1.1	H	30.2	3.01	26.84	27.53	54	26.47	Spurious
2484.1	19.49	Ave.	330	1.2	V	30.3	3.14	26.85	26.08	54	27.92	Spurious
2484.1	19.45	Ave.	160	1.4	H	30.3	3.14	26.85	26.04	54	27.96	Spurious
2432	33.64	Ave.	180	1.1	V	30.4	3.08	26.85	40.27	94	53.73	Fundament
2432	27.15	Ave.	230	1.2	H	30.4	3.08	26.85	33.78	94	60.22	Fundament

Note: The other data which below 20 dB to the limit was not recorded.

Band Edge:

Band Edge			Fundamental (2432MHz)	Attenuation (dB)	Limit (dB)
Left Side	2396.8 MHz	-54.65dBm	4.71dBm	59.36	\geq 50
Right Side	2490.7 MHz	-54.32dBm	4.71dBm	59.03	\geq 50

Band Edge, Left Side**Band Edge, Right Side********* END OF REPORT *******