

Test Number: 412-11
Issue Date: 10/21/2011

7. Measurement Data (continued)

7.10. Public Exposure to Radio Frequency Energy Levels (15.247(i) (1.1307 (b)(1)) RSS-GEN 5.5, RSS 102

Channel Frequency	MPE Distance (cm)	DUT Output Power (dBm)	DUT Antenna Gain (dBi)	Power Density		Limit (mW/cm ²)	Result
				(mW/cm ²)	(W/m ²)		
				(1)	(2)	(3)	(4)
2405	20	-21.94	2.1	0.00000208	0.00002083	1	Compliant
2440	20	-22.72	2.1	0.00000174	0.00001741	1	Compliant
2480	20	-22.94	2.1	0.00000165	0.00001655	1	Compliant

$$PD = \frac{OP + AG}{(4 \times \pi \times d^2)}$$

- **PD = Power Density (mW/cm²)**
- **OP = DUT Output Power (dBm)**
- **AG = DUT Antenna Gain (dBi)**
- **d = MPE Distance (cm)**

Reference CFR 2.1093(b): For purposes of this section, a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 2.5 centimeters of the body of the user.

1. Section 7.4 of this test report.
2. Data supplied by the client. Antenna specification data of worst case antenna used by the DUT.
3. Power density is calculated from field strength measurement and antenna gain.
4. Reference CFR 1.1310, Table 1: Limits for Maximum Permissible Exposure (MPE), Section (B): Limits for General Population/Uncontrolled Exposure.