



TEST REPORT

FCC PART 15 SUBPART B

FCC ID.....: **T37PL9164-4SW**
Report Reference No.....: **WE09120008**
 Compiled by
 (position+printed name+signature)..: File administrators Wenliang Li Wenliang Li
 Supervised by
 (position+printed name+signature)..: Test Engineer Cary Li Cary Li
 Approved by
 (position+printed name+signature)..: Manager Jimmy Li Jimmy Li
 Date of issue.....: Dec 24, 2009
Testing Laboratory Name: **Shenzhen Huatongwei International Inspection Co., Ltd**
 Address.....: Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China

Applicant's name.....: **ASOKA USA CORPORATION**
 Address.....: 2344-A Walsh Avenue, Santa Clara City, CA 95051

Test specification:
 Standard: **FCC Part 15B- Unintentional Radiators**
 TRF Originator.....: Shenzhen Huatongwei International Inspection CO., Ltd
 Master TRF.....: Dated 2006-06

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.
 This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Product name..... : **PlugLink AV 9164 Digital Power Center**
 Trade Mark: /
 Model/Type reference.....: PL9164-4SW
 Listed Models: /
Result..... : **Positive**

T E S T R E P O R T

Test Report No. :	WE09120008	Dec 24, 2009
		Date of issue

Equipment under Test : PlugLink AV 9164 Digital Power Center

Model /Type : PL9164-4SW

Listed Models : /

Applicant : ASOKA USA CORPORATION

Address : 2344-A Walsh Avenue, Santa Clara City, CA 95051

Test Result according to the standards on page 4:	Positive
----------------------------------------------------------	-----------------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

- 1. TEST STANDARDS 4**

- 2. SUMMARY 5**
 - 2.1. General Remarks 5
 - 2.2. Equipment Under Test 5
 - 2.3. Short description of the Equipment under Test (EUT) 5
 - 2.4. EUT operation mode 5
 - 2.5. EUT configuration 5
 - 2.6. Related Submittal(s) / Grant (s) 6
 - 2.7. Modifications 6

- 3. TEST ENVIRONMENT 7**
 - 3.1. Address of the test laboratory 7
 - 3.2. Test Facility 7
 - 3.3. Environmental conditions 8
 - 3.4. Configuration of Tested System 8
 - 3.5. Statement of the measurement uncertainty 9
 - 3.6. Equipments Used during the Test 9

- 4. TEST CONDITIONS AND RESULTS 10**
 - 4.1. Conducted Emissions Test 10
 - 4.2. Radiated Emission Test 13

- 5. TEST SETUP PHOTOS OF THE EUT 17**

- 6. EXTERNAL AND INTERNAL PHOTOS OF THE EUT 18**

1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15 Subpart B - Unintentional Radiators](#)

2. SUMMARY

2.1. General Remarks

Date of receipt of test sample : Dec 17, 2009

Testing commenced on : Dec 18, 2009

Testing concluded on : Dec 24, 2009

2.2. Equipment Under Test

Power supply system utilised

Power supply voltage : 120V / 60 Hz 115V / 60Hz
 12 V DC 24 V DC
 Other (specified in blank below)

/

2.3. Short description of the Equipment under Test (EUT)

PlugLink AV 9164 Digital Power Center.

For more details, refer to the user's manual of the EUT.

Serial number: Prototype

2.4. EUT operation mode

The EUT has been tested under typical operating condition.

2.5. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- supplied by the manufacturer

- supplied by the lab

Power Cable Length (m) : 1.5m
Unshield
Undetachable

Multimeter Manufacturer : /

Model No. : /

Cable Length (m) : /

Shield : /

2.6. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: **T37PL9164-4SW** filing to comply with the FCC Part 15, Subpart B Rules.

2.7. Modifications

No modifications were implemented to meet testing criteria.

3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Shenzhen Huatongwei International Inspection Co., Ltd
Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China
Phone: 86-755-26715686 Fax: 86-755-26748089

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 (2003) and CISPR Publication 22.

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L1225

Shenzhen Huatongwei International Inspection Co., Ltd has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories, Date of Registration: August 02, 2007. Valid time is until March 29, 2012.

A2LA-Lab Cert. No. 2243.01

Shenzhen Huatongwei International Inspection Co., Ltd, EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing. Valid time is from Aug 24, 2005 to Dec 30, 2009.

FCC-Registration No.: 662850

Shenzhen Huatongwei International Inspection Co., Ltd, EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 662850, Renewal date Jul 1, 2009.

IC-Registration No.: 5377

The 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377 on November Feb 13, 2009.

ACA

Shenzhen Huatongwei International Inspection Co., Ltd, EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

NEMKO-Aut. No.: ELA125

Shenzhen Huatongwei International Inspection Co., Ltd has been assessed the quality assurance system, the testing facilities, qualifications and testing practices of the relevant parts of the organization. The quality assurance system of the Laboratory has been validated against ISO/IEC 17025:2005 or equivalent. The laboratory also fulfils the conditions described in Nemko Document NLA-10, the Authorization is valid through Jul 7, 2011.

VCCI

The 3m Semi-anechoic chamber (12.2m×7.95m×6.7m) and Shielded Room (8m×4m×3m) of Shenzhen Huatongwei International Inspection Co., Ltd has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2484. Date of Registration: December 20, 2006. Valid time is until December 19, 2009.

Main Ports Conducted Interference Measurement of Shenzhen Huatongwei International Inspection Co., Ltd has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: C-2726. Date of Registration: December 20, 2006. Valid time is until December 19, 2009.

DNV

Shenzhen Huatongwei International Inspection Co Ltd has been found to comply with the requirements of DNV towards subcontractor of EMC and safety testing services in conjunction with the EMC and Low voltage Directives and in the voluntary field. The acceptance is based on a formal quality Audit and follow-ups according to relevant parts of ISO/IEC Guide 17025(2005), in accordance with the requirements of the DNV Laboratory Quality Manual towards subcontractors. Valid time is until 09 July, 2010.

3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	<u>15-35 ° C</u>
Humidity:	<u>30-70 %</u>
Atmospheric pressure:	<u>950-1050mbar</u>

3.4. Configuration of Tested System

Fig. 2-1 Configuration of Tested System




Table 2-1 Equipment Used in Tested System

No.	Product	Manufacturer	Model No.	Serial No.
1	PC 1	ASUS	I9100L	59NP00972
2	PC 2	IBM	1843-2XL	LV-BLH05 06/02
3	Coupler	ASOKO	/	/
4	Coupler	ASOKO	/	/
5	PlugLink AV 9164 Digital Power	ASOKO	PL9164-4SW	/

3.5. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Huatongwei laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.22dB	(1)
Radiated Emission	1~12.75GHz	4.35dB	(1)
Conducted Disturbance	0.15~30MHz	3.29dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.6. Equipments Used during the Test


AC Power Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	EMI TEST RECEIVER	ROHDE & SCHWARZ	ESCI	100106	2009/11
2	ARTIFICIAL MAINS	ROHDE & SCHWARZ	ESH2-Z5	100028	2009/11
3	PULSE LIMITER	ROHDE & SCHWARZ	ESHSZ2	100044	2009/11
4	EMI TEST SOFTWARE	ROHDE & SCHWARZ	ES-K1 1.71	N/A	2009/11

Radiated Emissions					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	ULTRA-BROADBAND ANTENNA	ROHDE & SCHWARZ	HL562	100015	2009/11
2	EMI TEST RECEIVER	ROHDE & SCHWARZ	ESI 26	100009	2009/11
3	RF TEST PANEL	ROHDE & SCHWARZ	TS / RSP	335015/ 0017	2009/11
4	TURNTABLE	ETS	2088	2149	2009/11
5	ANTENNA MAST	ETS	2075	2346	2009/11
6	EMI TEST SOFTWARE	ROHDE & SCHWARZ	ESK1	N/A	2009/11

4. TEST CONDITIONS AND RESULTS

4.1. Conducted Emissions Test

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4.
- 2 Support equipment, if needed, was placed as per ANSI C63.4.
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4 The EUT received the AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

Conducted Power Line Emission Limit

For unintentional device, according to § 15.107(a) Line Conducted Emission Limits is as following :

Frequency (MHz)	Maximum RF Line Voltage (dBµV)			
	CLASS A		CLASS B	
	Q.P.	Ave.	Q.P.	Ave.
0.15 - 0.50	79	66	66-56*	56-46*
0.50 - 5.00	73	60	56	46
5.00 - 30.0	73	60	60	50


* Decreasing linearly with the logarithm of the frequency

For intentional device, according to §15.207(a) Line Conducted Emission Limit is same as above table.

TEST RESULTS

EUT: PlugLink AV 9164 Digital Power Center
 Manufacturer: ASOKA
 Operating Condition: COMMUNICATION
 Test Site: 3# SHIELDED ROOM
 Operator: Cary
 Test Specification: AC 230V/50Hz
 Comment: M/N: PL9164-4SW
 Start of Test: 12/23/2009 / 9:30:45AM

SCAN TABLE: "Voltage (150K-30M) FIA"
 Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "ASO1219301_fin"

12/24/2009 9:23AM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.190500	40.70	10.2	64	23.3	QP	N	GND
0.388500	33.90	10.2	58	24.2	QP	N	GND
1.833000	30.30	10.3	56	25.7	QP	N	GND
12.669500	56.80	10.6	60	3.2	QP	N	GND
15.837500	55.10	10.7	60	4.9	QP	N	GND
19.550000	55.10	10.9	60	4.9	QP	N	GND

MEASUREMENT RESULT: "ASO1219301_fin2"

12/19/2009 2:35PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.312000	43.40	10.2	50	6.5	AV	N	GND
2.877500	27.30	10.4	46	18.7	AV	N	GND
4.965500	32.10	10.4	46	13.9	AV	N	GND
10.329500	45.30	10.6	50	4.7	AV	N	GND
10.370000	45.30	10.6	50	4.7	AV	N	GND
14.600000	44.40	10.7	50	5.6	AV	N	GND
18.668000	39.90	10.9	50	10.1	AV	N	GND


Remark:

- (1) Measuring frequencies from 0.15 MHz to the 30 MHz.
- (2) Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (3) The IF bandwidth of EMI Test Receiver was 9KHz for measuring from 0.15 MHz to 30 MHz

EUT: PlugLink AV 9164 Digital Power Center
 Manufacturer: ASOKA
 Operating Condition: COMMUNICATION
 Test Site: 3# SHIELDED ROOM
 Operator: Cary
 Test Specification: AC 120V/60Hz
 Comment: M/N: PL9164-4SW
 Start of Test: 12/19/2009 / 2:37:02PM

SCAN TABLE: "Voltage (150K-30M) FIA"

Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "ASO1219302_fin"

12/19/2009 3:05PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.357000	45.20	10.2	59	13.6	QP	L1	GND
0.955500	32.00	10.3	56	24.0	QP	L1	GND
1.239000	32.20	10.3	56	23.8	QP	L1	GND
6.446000	53.40	10.4	60	6.6	QP	L1	GND
7.620500	54.00	10.5	60	6.0	QP	L1	GND
15.518000	49.30	10.7	60	10.7	QP	L1	GND

MEASUREMENT RESULT: "ASO1219302_fin2"

12/19/2009 3:05PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.312000	39.10	10.2	50	10.8	AV	L1	GND
0.361500	39.30	10.2	49	9.4	AV	L1	GND
2.202500	38.20	10.4	46	7.8	AV	L1	GND
2.801000	33.30	10.4	46	12.7	AV	L1	GND
7.647500	41.70	10.5	50	8.3	AV	L1	GND
12.350000	42.50	10.6	50	7.5	AV	L1	GND


Remark:

- (1) Measuring frequencies from 0.15 MHz to the 30 MHz.
- (2) Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (3) The IF bandwidth of EMI Test Receiver was 9KHz for measuring from 0.15 MHz to 30MHz


4.2. Radiated Emission Test

TEST CONFIGURATION


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



TEST PROCEDURE

- 1 The EUT was placed on a turn table which is 0.8m above ground plane.
- 2 Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

RADIATION LIMIT

For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Distance (Meters)	Radiated (dBµV/m)	Radiated (µV/m)
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.


TEST RESULTS

Operation Mode: Communication Temperature: 24 C Humidity: 68 % RH Polarity: Ver.

EUT: PlugLink AV 9164 Digital Power Center
 Manufacturer: ASOKA
 Operating Condition: COMMUNICATION
 Test Site: 3M CHAMBER
 Operator: Cary
 Test Specification: AC 120V/60Hz
 Comment: M/N:PL9164-4SW
 Start of Test: 12/19/2009 / 10:10:58PM

SWEEP TABLE: "test (30M-1G)"

Start Frequency	Stop Frequency	Detector	Meas. Time	IF Bandw.	Field Strength Transducer
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz	HL562 09



MEASUREMENT RESULT: "AS01219401_red"

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
101.920000	34.00	-13.7	43.5	9.5	QP	100.0	291.00	VERTICAL
125.250000	33.30	-13.4	43.5	10.2	QP	100.0	237.00	VERTICAL
140.801000	34.20	-15.3	43.5	8.8	QP	100.0	89.00	VERTICAL
300.452000	38.40	-0.9	46.0	7.6	QP	100.0	223.00	VERTICAL
875.591100	39.40	0.6	46.0	6.6	QP	100.0	190.00	VERTICAL
900.861000	40.00	1.7	46.0	6.0	QP	100.0	345.00	VERTICAL

Remark:


- (1) Measuring frequencies from 30 MHz to the 1 GHz.
- (2) * denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.
- (3) Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (4) The IF bandwidth of EMI Test Receiver was 120KHz for measuring from 30 MHz to 1 GHz and 1 MHz for measuring above 1 GHz

Operation Mode: Communication Temperature: 24 C Humidity: 68 % RH Polarity: Hor.

EUT: PlugLink AV 9164 Digital Power Center
 Manufacturer: ASOKA
 Operating Condition: COMMUNICATION
 Test Site: 3M CHAMBER
 Operator: Cary
 Test Specification: AC 120V/60Hz
 Comment: M/N:PL9164-4SW
 Start of Test: 12/19/2009 / 10:10:58PM

SWEEP TABLE: "test (30M-1G)"

Start Frequency	Stop Frequency	Detector	Meas. Time	IF Bandw.	Field Strength Transducer
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz	HL562 09



MEASUREMENT RESULT: "AS01219402_red"

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
300.929000	40.10	-11.9	46.0	4.5	QP	100.0	247.00	HORIZONTAL
335.190000	44.50	-10.4	46.0	6.4	QP	100.0	268.00	HORIZONTAL
372.124000	43.70	-9.2	46.0	6.8	QP	100.0	275.00	HORIZONTAL
626.452000	39.70	-0.9	46.0	5.8	QP	100.0	314.00	HORIZONTAL
776.591000	39.30	0.6	46.0	6.7	QP	100.0	33.00	HORIZONTAL
926.132000	40.00	2.5	46.0	6.0	QP	100.0	301.00	HORIZONTAL

Remark:

- (1) Measuring frequencies from 30 MHz to the 1 GHz.
- (2) * denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.
- (3) Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (4) The IF bandwidth of EMI Test Receiver was 120KHz for measuring from 30 MHz to 1 GHz and 1 MHz for measuring above 1 GHz