



# FCC RF Test Report

**APPLICANT** : Cellon Communications Technology Co., Ltd.  
**EQUIPMENT** : GSM/GPRS/EDGE(Downlink Only)  
850/900/1800/1900 UMTS900/2100 mobile phone  
**BRAND NAME** : Claro / Digicel/ekt / enspire / 2degrees / Movistar  
**MODEL NAME** : C8646, 8646  
**MARKETING NAME** : 8646, C8646, 8646CA, 8646EN, 8646CO, 8646GT,  
8646CL, 8646TL, 8646NZ  
**FCC ID** : T38C8646  
**STANDARD** : FCC 47 CFR Part 2, 22(H), 24(E)  
**CLASSIFICATION** : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on May 14, 2013 and completely tested on May 19, 2013. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.

Reviewed by:

Jones Tsai / Manager



**SPORTON INTERNATIONAL (SHENZHEN) INC.**  
No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.C.



## TABLE OF CONTENTS

<b>REVISION HISTORY.....</b>	<b>3</b>
<b>SUMMARY OF TEST RESULT .....</b>	<b>4</b>
<b>1 GENERAL DESCRIPTION.....</b>	<b>5</b>
1.1    Applicant.....	5
1.2    Manufacturer .....	5
1.3    Feature of Equipment Under Test.....	5
1.4    Product Specification of Equipment Under Test .....	5
1.5    Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator .....	6
1.6    Testing Site .....	6
1.7    Applied Standards .....	6
<b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....</b>	<b>7</b>
2.1    Test Mode.....	7
2.2    Connection Diagram of Test System .....	8
2.3    Support Unit used in test configuration and system.....	8
2.4    Measurement Results Explanation Example .....	9
<b>3 TEST RESULT.....</b>	<b>10</b>
3.1    Conducted Output Power Measurement.....	10
3.2    Peak-to-Average Ratio .....	12
3.3    Effective Radiated Power and Effective Isotropic Radiated Power Measurement .....	16
3.4    99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	19
3.5    Band Edge Measurement.....	27
3.6    Conducted Spurious Emission Measurement.....	32
3.7    Field Strength of Spurious Radiated Measurement .....	38
3.8    Frequency Stability for Temperature and Voltage Measurement .....	45
<b>4 LIST OF MEASURING EQUIPMENT.....</b>	<b>49</b>
<b>5 UNCERTAINTY OF EVALUATION.....</b>	<b>50</b>

### APPENDIX A. PHOTOGRAPHS OF EUT

### APPENDIX B. SETUP PHOTOGRAPHS



# REVISION HISTORY



## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	N/A	PASS	-
3.2	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.3	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
3.3	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.4	§2.1049 §22.917(b) §24.238(b)	99% Occupied Bandwidth and 26dB Bandwidth	N/A	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a)	Band Edge Measurement	< 43+10log <sub>10</sub> (P[Watts])	PASS	-
3.6	§2.1051 §22.917(a) §24.238(a)	Conducted Spurious Emission	< 43+10log <sub>10</sub> (P[Watts])	PASS	-
3.7	§2.1053 §22.917(a) §24.238(a)	Field Strength of Spurious Radiated	< 43+10log <sub>10</sub> (P[Watts])	PASS	Under limit 19.79 dB at 1672.000 MHz
3.8	§2.1055 §22.355 §24.235	Frequency Stability for Temperature and Voltage	< 2.5 ppm	PASS	-



## 1 General Description

### 1.1 Applicant

**Cellon Communications Technology Co., Ltd.**

11f, Skyworth C Buuiling, Gaoxin S.Ave.1., Hi-Tech Industrial Park, Nanshan.Shenzhen

### 1.2 Manufacturer

**Cellon Communications Technology Co., Ltd.**

11f, Skyworth C Buuiling, Gaoxin S.Ave.1., Hi-Tech Industrial Park, Nanshan.Shenzhen

### 1.3 Feature of Equipment Under Test

Product Feature	
<b>Equipment</b>	GSM/GPRS/EDGE(Downlink Only) 850/900/1800/1900 UMTS900/2100 mobile phone
<b>Brand Name</b>	Claro / Digicel/ekt / enspire / 2degrees / Movistar
<b>Model Name</b>	C8646, 8646
<b>Marketing Name</b>	8646, C8646, 8646CA, 8646EN, 8646CO, 8646GT, 8646CL, 8646TL, 8646NZ
<b>FCC ID</b>	T38C8646
<b>EUT supports Radios application</b>	GSM/GPRS/WLAN 11bgn/Bluetooth EDR
<b>HW Version</b>	P2
<b>SW Version</b>	C8646_Latam_Digicel_00.15
<b>EUT Stage</b>	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

### 1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
<b>Tx Frequency</b>	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz
<b>Rx Frequency</b>	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz
<b>Maximum Output Power to Antenna</b>	GSM850 : 32.21 dBm GSM1900 : 29.92 dBm
<b>Antenna Type</b>	Fixed Internal Antenna
<b>Type of Modulation</b>	GSM / GPRS: GMSK



## 1.5 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (%, Hz, ppm)	Emission Designator
Part 22	GSM850 GSM	GMSK	0.4360	0.04 ppm	248KGXW
Part 24	GSM1900 GSM	GMSK	0.6931	0.03 ppm	250KGXW

## 1.6 Testing Site

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.		
Test Site Location	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.C. TEL: +86-755- 3320-2398		
Test Site No.	Sporton Site No.		FCC/IC Registration No.
	TH01-SZ	03CH01-SZ	831040/4086F-1

## 1.7 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC 47 CFR Part 2, 22(H), 24(E)
- ANSI / TIA / EIA-603-C-2004
- FCC KDB 971168 D01 Power Meas. License Digital Systems v01

### Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

### 2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 9000 MHz for GSM850.
2. 30 MHz to 19000 MHz for GSM1900.


Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	■ GSM Link	■ GSM Link
GSM 1900	■ GSM Link	■ GSM Link

**Note:** The maximum power levels are GSM mode for GMSK link, only these modes were used for all tests.

The conducted power tables are as follows:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	<b>824.2</b>	<b>836.4</b>	<b>848.8</b>	<b>1850.2</b>	<b>1880.0</b>	<b>1909.8</b>
GSM	32.17	<b>32.21</b>	32.11	<b>29.92</b>	29.67	29.46
GPRS 8	32.16	32.20	32.10	29.89	29.64	29.45
GPRS 10	29.50	29.47	29.42	28.34	28.14	28.03
GPRS 11	27.52	27.46	27.36	26.37	26.18	26.05
GPRS 12	26.51	26.45	26.39	24.86	24.64	24.53

## 2.2 Connection Diagram of Test System



## 2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	System Simulator	Agilent	E5515C	N/A	N/A	Unshielded, 1.8 m
3.	DC Power Supply	TOPWORD	3303DR	N/A	N/A	Unshielded, 1.8 m



## 2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

### 3 Test Result

#### 3.1 Conducted Output Power Measurement

##### 3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


##### 3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

##### 3.1.3 Test Procedures

1. The transmitter output port was connected to base station.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.  
The path loss was compensated to the results for each measurement.
3. Set EUT at maximum power through base station.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

##### 3.1.4 Test Setup





### 3.1.5 Test Result of Conducted Output Power

Cellular Band			
Modes	GSM850 (GSM)		
Channel	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8
Conducted Power (dBm)	32.17	32.21	32.11
Conducted Power (Watts)	1.65	1.66	1.63

PCS Band			
Modes	GSM1900 (GSM)		
Channel	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8
Conducted Power (dBm)	29.92	29.67	29.46
Conducted Power (Watts)	0.98	0.93	0.88

**Note:** maximum burst average power for GSM.

## 3.2 Peak-to-Average Ratio

### 3.2.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


### 3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

### 3.2.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and System Simulator via power divider.
2. For GSM operating modes:
  - a. Set EUT in maximum power output.
  - b. Set the RBW = 1MHz, VBW = 3MHz, Peak detector in spectrum analyzer for first trace.
  - c. Set the RBW = 1MHz, VBW = 3MHz, RMS detector in spectrum analyzer for second trace.
  - d. The wanted burst signal is triggered by spectrum analyzer, and measured respectively the peak level and Mean level without burst-off time, after system simulator synchronized with the spectrum analyzer.
3. Record the deviation as Peak to Average Ratio.

### 3.2.4 Test Setup






### 3.2.5 Test Result of Peak-to-Average Ratio

PCS Band			
Modes	GSM1900 (GSM)		
Channel	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8
Peak-to-Average Ratio (dB)	0.30	0.30	0.31


### 3.2.6 Test Result (Plots) of Peak-to-Average Ratio

Band :	GSM 1900	Test Mode :	GSM Link
--------	----------	-------------	----------

#### Peak-to-Average Ratio on Channel 512 (1850.2 MHz)




#### Peak-to-Average Ratio on Channel 661 (1880.0 MHz)





## Peak-to-Average Ratio on Channel 810 (1909.8 MHz)



Date: 16.MAY.2013 15:54:33



### 3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

#### 3.3.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v01. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.


#### 3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.3.3 Test Procedures

1. The EUT was placed on a turntable with 1.5 meter height in a fully anechoic chamber.
2. The EUT was set at 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. GSM operating modes: Set RBW= 1MHz, VBW= 3MHz, RMS detector over burst;  
UMTS operating modes: Set RBW= 100 KHz, VBW= 300 KHz, RMS detector over frame, and use channel power option with bandwidth=5MHz, per section 4.0 of KDB 971168 D01.
4. The table was rotated 360 degrees to determine the position of the highest radiated power.
5. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
6. Taking the record of maximum ERP/EIRP.
7. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
8. The conducted power at the terminal of the dipole antenna is measured.
9. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
10.  $ERP/EIRP = Ps + Et - Es + Gs = Ps + Rt - Rs + Gs$   
Ps (dBm) : Input power to substitution antenna.  
Gs (dBi or dBd) : Substitution antenna Gain.  
 $Et = Rt + AF$   
 $Es = Rs + AF$   
AF (dB/m) : Receive antenna factor  
Rt : The highest received signal in spectrum analyzer for EUT.  
Rs : The highest received signal in spectrum analyzer for substitution antenna.

### 3.3.4 Test Setup





### 3.3.5 Test Result of ERP

GSM850 (GSM) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-20.69	-48.12	0.00	-1.08	26.35	0.4312
836.40	-20.95	-48.28	0.00	-0.93	26.40	0.4360
848.80	-21.39	-48.35	0.00	-0.76	26.20	0.4166

Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-36.14	-47.97	0.00	-1.08	10.75	0.0119
836.40	-35.97	-48.01	0.00	-0.93	11.11	0.0129
848.80	-36.12	-48.05	0.00	-0.76	11.17	0.0131

### 3.3.6 Test Result of EIRP

GSM1900 (GSM) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-26.12	-51.88	0.00	1.96	27.72	0.5915
1880.00	-27.89	-52.99	0.00	2.00	27.10	0.5129
1909.80	-28.73	-54.28	0.00	1.98	27.53	0.5659

Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-25.68	-52.13	0.00	1.96	28.41	0.6931
1880.00	-27.35	-53.17	0.00	2.00	27.82	0.6058
1909.80	-28.05	-54.13	0.00	1.98	28.06	0.6401

## 3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

### 3.4.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


### 3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

### 3.4.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The 99% occupied bandwidth and 26 dB bandwidth of the middle channel for the highest RF powers were measured.

### 3.4.4 Test Setup





### 3.4.5 Test Result of 99% Occupied Bandwidth and 26dB Bandwidth


Cellular Band			
Modes	GSM850 (GSM)		
Channel	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8
99% OBW (KHz)	246.00	244.00	248.00
26dB BW (KHz)	314.00	312.00	316.00

PCS Band			
Modes	GSM1900 (GSM)		
Channel	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8
99% OBW (KHz)	246.00	250.00	250.00
26dB BW (KHz)	320.00	316.00	312.00

### 3.4.6 Test Result (Plots) of 99% Occupied Bandwidth and 26dB Bandwidth


<b>Band :</b>	GSM 850	<b>Test Mode :</b>	GSM Link
---------------	---------	--------------------	----------

#### 99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)




Date: 16.MAY.2013 20:47:54


#### 26dB Bandwidth Plot on Channel 128 (824.2 MHz)




Date: 16.MAY.2013 20:35:32

**99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)**



Date: 16.MAY.2013 20:45:07

**26dB Bandwidth Plot on Channel 189 (836.4 MHz)**


Date: 16.MAY.2013 20:33:11


**99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)**


Date: 16.MAY.2013 20:39:23


**26dB Bandwidth Plot on Channel 251 (848.8 MHz)**


Date: 16.MAY.2013 20:37:02


<b>Band :</b>	GSM 1900	<b>Test Mode :</b>	GSM Link
---------------	----------	--------------------	----------

**99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)**



Date: 16.MAY.2013 21:36:44

**26dB Bandwidth Plot on Channel 512 (1850.2 MHz)**



Date: 16.MAY.2013 21:23:00

**99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)**



Date: 16.MAY.2013 21:34:45

**26dB Bandwidth Plot on Channel 661 (1880.0 MHz)**


Date: 16.MAY.2013 21:24:45

**99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)**


Date: 16.MAY.2013 21:28:40

**26dB Bandwidth Plot on Channel 810 (1909.8 MHz)**


Date: 16.MAY.2013 21:26:17

## 3.5 Band Edge Measurement

### 3.5.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.


### 3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

### 3.5.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The band edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100.
4. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
5. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
 $= P(W) - [43 + 10\log(P)]$  (dB)  
 $= [30 + 10\log(P)]$  (dBm) -  $[43 + 10\log(P)]$  (dB)  
 $= -13$  dBm.


### 3.5.4 Test Setup



### 3.5.5 Test Result (Plots) of Conducted Band Edge

<b>Band :</b>	GSM850	<b>Test Mode :</b>	GSM Link
<b>Correction Factor :</b>	0.23dB	<b>Maximum 26dB Bandwidth :</b>	0.316MHz
<b>Band Edge :</b>	-16.68dBm	<b>Measurement Value :</b>	-16.91dBm

**Lower Band Edge Plot on Channel 128 (824.2 MHz)**




Date: 16.MAY.2013 20:51:39

1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW}/\text{RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

For example,  $-16.91\text{dBm} + 0.23\text{dB} = -16.68\text{dBm}$


<b>Band :</b>	GSM850	<b>Test Mode :</b>	GSM Link
<b>Correction Factor :</b>	0.23dB	<b>Maximum 26dB Bandwidth :</b>	0.316MHz
<b>Band Edge :</b>	-17.03dBm	<b>Measurement Value :</b>	-17.26dBm

**Higher Band Edge Plot on Channel 251 (848.8 MHz)**


Date: 16.MAY.2013 21:04:18

1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW}/\text{RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


<b>Band :</b>	GSM1900	<b>Test Mode :</b>	GSM Link
<b>Correction Factor :</b>	0.28dB	<b>Maximum 26dB Bandwidth :</b>	0.320MHz
<b>Band Edge :</b>	-17.87dBm	<b>Measurement Value :</b>	-18.15dBm

**Lower Band Edge Plot on Channel 512 (1850.2 MHz)**


Date: 16.MAY.2013 21:18:24

1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW}/\text{RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

<b>Band :</b>	GSM1900	<b>Test Mode :</b>	GSM Link
<b>Correction Factor :</b>	0.28dB	<b>Maximum 26dB Bandwidth :</b>	0.320MHz
<b>Band Edge :</b>	-18.40dBm	<b>Measurement Value :</b>	-18.68dBm

**Higher Band Edge Plot on Channel 810 (1909.8 MHz)**


Date: 16.MAY.2013 21:11:53

1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW}/\text{RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

## 3.6 Conducted Spurious Emission Measurement

### 3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10<sup>th</sup> harmonic.


### 3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

### 3.6.3 Test Procedures

1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
 $= P(W) - [43 + 10\log(P)]$  (dB)  
 $= [30 + 10\log(P)]$  (dBm) -  $[43 + 10\log(P)]$  (dB)  
 $= -13$  dBm.


### 3.6.4 Test Setup



### 3.6.5 Test Result (Plots) of Conducted Spurious Emission


<b>Band :</b>	GSM850	<b>Channel :</b>	CH189
<b>Test Mode :</b>	GSM Link	<b>Frequency :</b>	836.4 MHz

**Conducted Spurious Emission Plot between 30MHz ~ 1GHz**




Date: 16.MAY.2013 22:04:20


**Conducted Spurious Emission Plot between 1GHz ~ 3GHz**



Date: 16.MAY.2013 22:28:32


**Conducted Spurious Emission Plot between 3GHz ~ 7GHz**


Date: 16.MAY.2013 22:30:59


**Conducted Spurious Emission Plot between 7GHz ~ 9GHz**


Date: 16.MAY.2013 22:32:16


<b>Band :</b>	GSM1900	<b>Channel :</b>	CH661
<b>Test Mode :</b>	GSM Link	<b>Frequency :</b>	1880.0 MHz

**Conducted Spurious Emission Plot between 30MHz ~ 1GHz**



Date: 16.MAY.2013 21:44:56

**Conducted Spurious Emission Plot between 1GHz ~ 3GHz**


Date: 16.MAY.2013 21:49:40

**Conducted Spurious Emission Plot between 3GHz ~ 7GHz**



Date: 16.MAY.2013 21:54:51

**Conducted Emission Plot between 7GHz ~ 13.6GHz**


Date: 16.MAY.2013 21:56:16



## Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 16.MAY.2013 21:57:40



## 3.7 Field Strength of Spurious Radiated Measurement

### 3.7.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

### 3.7.2 Measuring Instruments


See list of measuring instruments of this test report.

### 3.7.3 Test Procedures


1. The EUT was placed on a rotatable wooden table with 0.8 meter above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
11. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
 $= P(W) - [43 + 10\log(P)]$  (dB)  
 $= [30 + 10\log(P)]$  (dBm) -  $[43 + 10\log(P)]$  (dB)  
 $= -13$  dBm.
12. EIRP (dBm) = S.G. Power - Tx Cable Loss + Tx Antenna Gain
13. ERP (dBm) = EIRP - 2.15


### 3.7.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz




**For radiated emissions above 1GHz****3.7.5 Test Results of Radiated Emissions (9 KHz ~ 30 MHz)**

The low frequency, which started from 9 KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.




## 3.7.6 Test Result of Field Strength of Spurious Radiated

Band :	GSM850			Temperature :	24~25°C																																																				
Test Mode :	GSM Link			Relative Humidity :	54~56%																																																				
Test Engineer :	John Zheng			Polarization :	Horizontal																																																				
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.																																																								
 <p>Level (dBm)</p> <p>Date: 2013-05-19</p> <p>-13dBm</p> <p>Frequency (MHz)</p> <p>1672, 2510, 3345, 4182</p> <p>Site : 03CH01-SZ Condition : -13dBm HF_EIRP_H_130101 HORIZONTAL Project : (FG) 351403</p> <p>Plane : H</p> <table border="1"><thead><tr><th>Frequency (MHz)</th><th>ERP (dBm)</th><th>Limit (dBm)</th><th>Over Limit (dB)</th><th>SPA Reading (dBm)</th><th>S.G. Power (dBm)</th><th>TX Cable loss (dB)</th><th>TX Antenna Gain (dBi)</th><th>Polarization (H/V)</th><th>Result</th></tr></thead><tbody><tr><td>1672</td><td>-32.79</td><td>-13</td><td>-19.79</td><td>-49.64</td><td>-35.76</td><td>0.88</td><td>6.00</td><td>H</td><td>Pass</td></tr><tr><td>2510</td><td>-35.62</td><td>-13</td><td>-22.62</td><td>-60.49</td><td>-38.23</td><td>1.08</td><td>5.84</td><td>H</td><td>Pass</td></tr><tr><td>3345</td><td>-55.52</td><td>-13</td><td>-42.52</td><td>-66.12</td><td>-59.89</td><td>1.14</td><td>7.66</td><td>H</td><td>Pass</td></tr><tr><td>4182</td><td>-55.84</td><td>-13</td><td>-42.84</td><td>-70.60</td><td>-61.11</td><td>1.37</td><td>8.79</td><td>H</td><td>Pass</td></tr></tbody></table>								Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result	1672	-32.79	-13	-19.79	-49.64	-35.76	0.88	6.00	H	Pass	2510	-35.62	-13	-22.62	-60.49	-38.23	1.08	5.84	H	Pass	3345	-55.52	-13	-42.52	-66.12	-59.89	1.14	7.66	H	Pass	4182	-55.84	-13	-42.84	-70.60	-61.11	1.37	8.79	H	Pass
Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result																																																
1672	-32.79	-13	-19.79	-49.64	-35.76	0.88	6.00	H	Pass																																																
2510	-35.62	-13	-22.62	-60.49	-38.23	1.08	5.84	H	Pass																																																
3345	-55.52	-13	-42.52	-66.12	-59.89	1.14	7.66	H	Pass																																																
4182	-55.84	-13	-42.84	-70.60	-61.11	1.37	8.79	H	Pass																																																



Band :	GSM850	Temperature :	24~25°C
Test Mode :	GSM Link	Relative Humidity :	54~56%
Test Engineer :	John Zheng	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ  
Condition : -13DBM HF\_EIRP\_V\_130101 VERTICAL  
Project : (FG) 351403

Plane : H

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-35.14	-13	-22.14	-49.17	-38.11	0.88	6.00	V	Pass
2510	-36.41	-13	-23.41	-58.94	-39.02	1.08	5.84	V	Pass
3345	-56.97	-13	-43.97	-68.80	-61.34	1.14	7.66	V	Pass
4182	-55.67	-13	-42.67	-70.89	-60.94	1.37	8.79	V	Pass



Band :	GSM1900	Temperature :	24~25°C
Test Mode :	GSM Link	Relative Humidity :	54~56%
Test Engineer :	John Zheng	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-SZ  
Condition : -13DBM HF\_EIRP\_H\_130101 HORIZONTAL  
Project : (FG) 351403

Plane : H

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-57.77	-13	-44.77	-69.92	-64.51	1.28	8.02	H	Pass
5640	-52.51	-13	-39.51	-70.50	-60.93	1.58	10.00	H	Pass
7520	-49.57	-13	-36.57	-71.51	-59.89	1.78	12.10	H	Pass
9400	-51.26	-13	-38.26	-73.38	-62.04	2.22	13.00	H	Pass



Band :	GSM1900			Temperature :	24~25°C					
Test Mode :	GSM Link			Relative Humidity :	54~56%					
Test Engineer :	John Zheng			Polarization :	Vertical					
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.									
<p>Level (dBm)</p> <p>Date: 2013-05-19</p> <p>-10.0</p> <p>-20.0</p> <p>-30.0</p> <p>-40.0</p> <p>-50.0</p> <p>-60.0</p> <p>-70.0</p> <p>-80.0</p> <p>-90.0</p> <p>-100</p> <p>30 1000. 3000. 5000. 7000. 9000. 11000. 13000. 15000. 17000. 19000</p> <p>Frequency (MHz)</p> <p>13DBM</p> <p>1 2 3 4</p>										
Site	: 03CH01-SZ									
Condition	: -13DBM HF_EIRP_V_130101 VERTICAL									
Project	: (FG) 351403									
Plane	: H									
Frequency	EIRP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result	
( MHz )	( dBm )	( dBm )	( dB )	Reading (dBm)	Power (dBm)	loss ( dB )	Gain (dBi)	( H/V )		
3760	-54.29	-13	-41.29	-69.32	-61.03	1.28	8.02	V	Pass	
5640	-54.39	-13	-41.39	-71.47	-62.81	1.58	10	V	Pass	
7520	-49.33	-13	-36.33	-71.58	-59.65	1.78	12.1	V	Pass	
9400	-48.87	-13	-35.87	-72.49	-59.65	2.22	13	V	Pass	



## 3.8 Frequency Stability for Temperature and Voltage Measurement

### 3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5\text{ppm}$ ) of the center frequency.

### 3.8.2 Measuring Instruments

See list of measuring instruments of this test report.


### 3.8.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to  $-30^\circ\text{C}$  and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in  $10^\circ\text{C}$  step up to  $50^\circ\text{C}$ . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.
4. If the EUT cannot be turned on at  $-30^\circ\text{C}$ , the testing lowest temperature will be raised in  $10^\circ\text{C}$  step until the EUT can be turned on.

### 3.8.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at  $25\pm 5^\circ\text{C}$  and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

### 3.8.5 Test Setup





## 3.8.6 Test Result of Temperature Variation

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	GSM		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-24	-0.03	PASS
-20	-23	-0.03	
-10	-27	-0.03	
0	-26	-0.03	
10	-30	-0.04	
20	-32	-0.04	
30	-31	-0.04	
40	-32	-0.04	
50	-33	-0.04	
55	-33	-0.04	

**Note:** The manufacturer declared that the EUT could work properly at temperature 55°C.

Band :	GSM 1900	Channel :	661
Limit (ppm) :	2.5	Frequency :	1880.0 MHz

Temperature (°C)	GSM		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-29	-0.02	PASS
-20	-37	-0.02	
-10	-38	-0.02	
0	-45	-0.02	
10	-49	-0.03	
20	-55	-0.03	
30	-56	-0.03	
40	-58	-0.03	
50	-59	-0.03	
55	-61	-0.03	

**Note:** The manufacturer declared that the EUT could work properly at temperature 55°C.



### 3.8.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GSM	3.8	-30	-0.04	2.5	PASS
		BEP	-32	-0.04		
		4.35	-31	-0.04		
GSM 1900 CH661	GSM	3.8	-51	-0.03		
		BEP	-50	-0.03		
		4.35	-53	-0.03		

**Note:**

1. Normal Voltage = 3.8V.
2. Battery End Point (BEP) = 3.5 V.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP30	101400	9kHz~30GHz	Mar. 28, 2013	May 16, 2013	Mar. 27, 2014	Conducted (TH01-SZ)
System Simulator	R&S	CMU200	100954	GSM	Jun. 14, 2012	May 16, 2013	Jun. 13, 2013	Conducted (TH01-SZ)
DC Power Supply	TOPWORD	3303DR	N/A714621	N/A	Mar. 28, 2013	May 16, 2013	Mar. 27, 2014	Conducted (TH01-SZ)
Thermal Chamber	Hongzhan	LP-150U	HD20120425	N/A	Mar. 28, 2013	May 16, 2013	Mar. 27, 2014	Conducted (TH01-SZ)
ESCI TEST Receiver	R&S	ESCI	100724	9K-3GHz	Mar. 28, 2013	May 19, 2013	Mar. 27, 2014	Radiation (03CH01-SZ)
Spectrum Analyzer	R&S	FSP30	101362	9kHz~30GHz	Oct. 11, 2012	May 19, 2013	Oct. 10, 2013	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS Lindgren	3117	00119436	1GHz~18GHz	Oct. 12, 2012	May 19, 2013	Oct. 11, 2013	Radiation (03CH01-SZ)
Bilog Antenna	SCHAFFNER	CBL6112B	2614	30Mhz~2Ghz	Nov. 03, 2012	May 19, 2013	Nov. 02, 2013	Radiation (03CH01-SZ)
Amplifier	ADVANTEST	BB525C	E9007003	9K-3000MHz GAIN 30db	Mar. 28, 2013	May 19, 2013	Mar. 27, 2014	Radiation (03CH01-SZ)
Amplifier	Yiai	AV3860B	04030	2GHz~26.5GHz	Mar. 28, 2013	May 19, 2013	Mar. 27, 2014	Radiation (03CH01-SZ)
SHF-EHF-Horn	Schwarzbeck	BBHA9170	BBHA9170249	14Ghz~40Ghz	Nov. 23, 2012	May 19, 2013	Nov. 22, 2013	Radiation (03CH01-SZ)
Loop Antenna	R&S	HFH2-Z2	100321	9KHZ-30MHZ	Oct. 22, 2012	May 19, 2013	Oct. 21, 2013	Radiation (03CH01-SZ)
System Simulator	Agilent	E5515C	MY50264168	GSM/WCDMA /CDMA2000	Oct. 09, 2012	May 19, 2013	Oct. 08, 2013	Radiation (03CH01-SZ)



## 5 Uncertainty of Evaluation

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2U <sub>c</sub> (y))	2.54
--	------

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2U <sub>c</sub> (y))	4.72
--	------



## **Appendix A. Photographs of EUT**

Please refer to Sporton report number EP351403 as below.