

RF Exposure Evaluation declaration

Product Name : Philips 900/1800/1900
Model No. : Xenium9@9m
FCC ID. : T38CT9A9M

Applicant : Cellon Communications Technology (Shenzhen) Co.,Ltd.
Address : 13/F, Skyworth C Building, Gaoxin S.Ave1, Hi-Tech Industrial Park, Nanshan, Shenzhen, China

Date of Receipt : 2006/09/18
Issued Date : 2006/09/28
Report No. : 069S017

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of QuieTek Corporation.

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm^2

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm^2 . If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product : Philips 900/1800/1900
Test Item : RF Exposure Evaluation
Test Site : AC-3
Test Mode : Transmitter

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is -5.7 dBi or 0.27 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 2.5 cm (mW/cm ²)
0	2402.00	0.3055	0.0010
39	2441.00	0.2831	0.0010
78	2480.00	0.2576	0.0009

The power density P_d (4th column) at a distance of 2.5 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².