



NVLAP LAB CODE 200707-0



FCC PART 22 H/24 E MEASUREMENT AND TEST REPORT

For

Cellon Communications Technology (Shenzhen) Co.,Ltd.

13/F, Skyworth C Building, Gaoxin S.Ave1, Hi-Tech Industrial Park,

Nanshan, Shenzhen, Guangdong 518057, China

FCC ID: T38UT2001

Report Type: Original Report	Product Type: GSM&GPRS Dual Band Mobile Phone
Test Engineer:	<u>Kvass Yang</u> <i>Kvass. Yang</i>
Report Number:	<u>RSZ09040201</u>
Report Date:	<u>2009-05-06</u>
Reviewed By:	<u>Simon Mo</u> <i>simon mo</i> EMC Engineer
Prepared By:	Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, NIST, or any agency of the Federal Government.

* This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "*" (Rev.2)

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
EUT PHOTO	4
OBJECTIVE	5
RELATED SUBMITTAL(S)/GRANT(S).....	5
TEST METHODOLOGY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION	6
JUSTIFICATION	6
EQUIPMENT MODIFICATIONS	6
CONFIGURATION OF TEST SETUP	6
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
§1.1307& §2.1093 - RF EXPOSURE.....	8
APPLICABLE STANDARD	8
TEST RESULT	8
§2.1047 - MODULATION CHARACTERISTIC	9
§ 2.1046, § 22.913 (A) & § 24.232 (C) - RF OUTPUT POWER.....	10
APPLICABLE STANDARD	10
TEST PROCEDURE	10
TEST EQUIPMENT LIST AND DETAILS.....	10
TEST DATA	11
§2.1049, §22.917, §22.905 & §24.238 - OCCUPIED BANDWIDTH	20
APPLICABLE STANDARDS.....	20
TEST PROCEDURE	20
TEST EQUIPMENT LIST AND DETAILS.....	20
TEST DATA	20
§2.1051, §22.917(A) & §24.238(A) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS	24
APPLICABLE STANDARDS.....	24
TEST PROCEDURE	24
TEST EQUIPMENT LIST AND DETAILS.....	24
TEST DATA	24
§2.1053, §22.917& §24.238 - SPURIOUS RADIATED EMISSIONS	31
APPLICABLE STANDARDS.....	31
TEST PROCEDURE	31
TEST EQUIPMENT LIST AND DETAILS.....	31
TEST DATA	32
§22.917(A) & §24.238(A) - BAND EDGES.....	34
APPLICABLE STANDARDS.....	34
TEST PROCEDURE	34
TEST EQUIPMENT LIST AND DETAILS.....	34

TEST DATA	34
§2.1055, §22.355 & §24.235 - FREQUENCY STABILITY	40
APPLICABLE STANDARD	40
TEST PROCEDURE	40
TEST EQUIPMENT LIST AND DETAILS.....	41
TEST DATA	41
DECLARATION LETTER	43

GENERAL INFORMATION

Product Description for Equipment Under Test (EUT)

The Cellon Communications Technology (Shenzhen) Co.,Ltd.'s product, model number: C2001 or the "EUT" as referred to in this report is a GSM&GPRS Dual Band Mobile Phone, which measures approximately: 9.7 cm L x 4.3 cm W x 1.4 cm H, rated input voltage: DC 3.7V battery.

Frequency Range:

Cellular Band: 824-849 MHz (TX), 869-894 MHz (RX)

PCS Band: 1850-1910 MHz (TX), 1930-1990 MHz (RX)

Modulation Mode: GMSK

Transmitter Output Power:

Cellular Band: 33±2 dBm

PCS Band: 30±2 dBm

** All measurement and test data in this report was gathered from production sample serial number: IMEI: 359668020004421 (Assigned by the applicant). The EUT was received on 2009-04-02.*

***Note:** The series products, model C2001, C640, C640/8, C640/9, C640/8R, C640/8S, C640/9R, C640/9S, we select C2001 to test, there is no electrical change has been made to the equipment, which was explained in the attached Declaration Letter.

EUT Photo



Please see additional photos in Exhibit B&C

Objective

This type approval report is prepared on behalf of *Cellon Communications Technology (Shenzhen) Co., Ltd.* in accordance with Part 2, Subpart J, Part 22 Subpart H, and Part 24 Subpart E of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC rules for output power, modulation characteristic, occupied bandwidth, and spurious emission at antenna terminal, spurious radiated emission, frequency stability, band edge and radiated margin.

Related Submittal(s)/Grant(s)

No related submittal(s).

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-part J as well as the following parts:

Part 22 Subpart H - Public Mobile Services
Part 24 Subpart E - Personal Communication Services

Applicable Standards: TIA/EIA 603-C, ANSI C63.4-2003.

All radiated and conducted emissions measurements were performed at Bay Area Compliance Laboratories Corp. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp.(Shenzhen) to collect test data is located in the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 21, 2007. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



NVLAP LAB CODE 200707-0

The current scope of accreditations can be found at
<http://ts.nist.gov/Standards/scopes/2007070.htm>

SYSTEM TEST CONFIGURATION

Justification


The EUT was configured for testing according to TIA/EIA-603-C.

The final qualification test was performed with the EUT operating at normal mode.


Equipment Modifications

No modifications were made to the EUT.

Configuration of Test Setup



Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307, §2.1093	RF Exposure (SAR)	Compliant *
§2.1046; § 22.913 (a) § 24.232 (c)	RF Output Power	Compliant
§ 2.1047	Modulation Characteristics	N/A
§ 2.1049 § 22.905 § 22.917 § 24.238	99% & -26 dB Occupied Bandwidth	Compliant
§ 2.1051, § 22.917 (a) § 24.238 (a)	Spurious Emissions at Antenna Terminal	Compliant
§ 2.1053 § 22.917 (a) § 24.238 (a)	Field Strength of Spurious Radiation	Compliant
§ 22.917 (a) § 24.238 (a)	Out of band emission, Band Edge	Compliant
§ 2.1055 § 22.355 § 24.235	Frequency stability vs. temperature Frequency stability vs. voltage	Compliant

Note: * SAR report released by BACL, Report Number: RSZ09040201-SAR

§1.1307& §2.1093 - RF EXPOSURE

Applicable Standard

§1.1307 and §2.1093.

Test Result

Compliance

The EUT is a portable device and thus requires SAR evaluation; please refer to BACL SAR Report: RSZ09040201-SAR.

§2.1047 - MODULATION CHARACTERISTIC

According to FCC § 2.1047(d), Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

§ 2.1046, § 22.913 (a) & § 24.232 (c) - RF OUTPUT POWER

Applicable Standard


According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC §2.1046 and §24.232 (C), in no case may the peak output power of a base station transmitter exceed 2 watt EIRP.

Test Procedure

Conducted method:

The RF output of the transmitter was connected to the wireless test set and the wireless communication test set through sufficient attenuation.



Radiated method:

TIA 603-C section 2.2.17

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Horn Antenna	DRH-118	A052604	2008-09-25	2009-09-25
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2009-03-11	2010-03-11
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2008-08-28	2009-08-27
HP	Preamplifier	8449B	3008A00277	2008-09-12	2009-09-11
HP	Signal Generator	HP8657A	2849U00982	2008-10-16	2009-10-16
HP	Amplifier	HP8447D	2944A09795	2008-08-02	2009-08-02
HP	Synthesized Sweeper	8341B	2624A00116	2008-11-07	2009-11-06
COM POWER	Dipole Antenna	AD-100	041000	2008-09-25	2009-09-25
A.H. System	Horn Antenna	SAS-200/571	135	2008-05-17	2009-05-17
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	1100.0008.02	2008-09-26	2009-09-25

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Kvass Yang on 2009-04-12.

Conducted Power

Cellular Band (Part 22H)

Mode	Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Part 22H Limit (dBm)
GSM	Low	824.2	31.97	1.574	38.45
	Middle	836.6	31.79	1.510	38.45
	High	848.8	31.84	1.528	38.45
GPRS	Low	824.2	31.95	1.567	38.45
	Middle	836.6	31.81	1.517	38.45
	High	848.8	31.85	1.531	38.45

PCS Band (Part 24E)

Mode	Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Part 24E Limit (dBm)
GSM	Low	1850.2	28.31	0.678	33
	Middle	1880.0	28.34	0.682	33
	High	1909.8	28.44	0.698	33
GPRS	Low	1850.2	28.33	0.681	33
	Middle	1880.0	28.36	0.685	33
	High	1909.8	28.46	0.701	33

Radiated Power (ERP and EIRP)

Cellular Band (Part 22H)

GSM:

Indicated		Table Angle Degree	Test Antenna		Substituted					Absolute Level (dBm)	FCC Part 22H	
Frequency (MHz)	S.A. Amp. (dBμV/m)		Height (m)	Polar (H/V)	Frequency (MHz)	S.G. Level (dBm)	Polar (H/V)	Ant. Gain Cord. (dBi)	Cable Loss (dB)		Limit (dBm)	Result
Low Channel												
824.2	93.89	213	1.2	H	824.2	27.96	H	0	0.9	27.06	38.45	Pass
824.2	99.53	1670	1.8	V	824.2	29.72	V	0	0.9	28.82	38.45	Pass
Middle Channel												
836.6	96.86	114	1.5	H	836.6	29.31	H	0	0.9	28.41	38.45	Pass
836.6	102.21	110	1.7	V	836.6	30.12	V	0	0.9	29.22	38.45	Pass
High Channel												
848.8	93.29	211	1.6	H	848.8	27.42	H	0	0.9	26.52	38.45	Pass
848.8	100.94	882	1.7	V	848.8	29.94	V	0	0.9	29.04	38.45	Pass

GPRS:

Indicated		Table Angle Degree	Test Antenna		Substituted					Absolute Level (dBm)	FCC Part 22H	
Frequency (MHz)	S.A. Amp. (dBμV/m)		Height (m)	Polar (H/V)	Frequency (MHz)	S.G. Level (dBm)	Polar (H/V)	Ant. Gain Cord. (dBi)	Cable Loss (dB)		Limit (dBm)	Result
Low Channel												
824.2	96.78	114	1.0	H	824.2	29.24	H	0	0.9	28.34	38.45	Pass
824.2	98.11	67	1.8	V	824.2	29.63	V	0	0.9	28.73	38.45	Pass
Middle Channel												
836.6	98.12	116	1.0	H	836.6	29.63	H	0	0.9	28.73	38.45	Pass
836.6	100.59	235	1.7	V	836.6	29.94	V	0	0.9	29.04	38.45	Pass
High Channel												
848.8	97.27	111	1.5	H	848.8	29.32	H	0	0.9	28.42	38.45	Pass
848.8	99.72	273	1.75	V	848.8	29.75	V	0	0.9	28.85	38.45	Pass

PCS Band (Part 24E)

GSM:

Indicated		Table Angle Degree	Test Antenna		Substituted					Absolute Level (dBm)	FCC Part 24E	
Frequency (MHz)	S.A. Amp. (dBμV/m)		Height (m)	Polar (H/V)	Frequency (MHz)	S.G. Level (dBm)	Polar (H/V)	Ant. Gain Cord. (dBi)	Cable Loss (dB)		Limit (dBm)	Result
Low Channel												
1850.2	87.95	19	1.6	H	1850.2	19.67	H	6.2	1.02	24.85	33	Pass
1850.2	88.41	84	2.0	V	1850.2	20.01	V	6.2	1.02	25.19	33	Pass
Middle Channel												
1880	87.74	42	1.8	H	1880	19.62	H	6.2	1.03	24.79	33	Pass
1880	89.29	321	2.0	V	1880	21.35	V	6.2	1.03	26.52	33	Pass
High Channel												
1909.8	82.84	69	1.9	H	1909.8	17.78	H	6.2	1.03	22.95	33	Pass
1909.8	86.63	271	1.2	V	1909.8	19.32	V	6.2	1.03	24.49	33	Pass

GPRS:


Indicated		Table Angle Degree	Test Antenna		Substituted					Absolute Level (dBm)	FCC Part 24E	
Frequency (MHz)	S.A. Amp. (dBμV/m)		Height (m)	Polar (H/V)	Frequency (MHz)	S.G. Level (dBm)	Polar (H/V)	Ant. Gain Cord. (dBi)	Cable Loss (dB)		Limit (dBm)	Result
Low Channel												
1850.2	86.04	211	2.0	H	1850.2	18.89	H	6.2	1.02	24.07	33	Pass
1850.2	87.44	250	1.7	V	1850.2	19.45	V	6.2	1.02	24.63	33	Pass
Middle Channel												
1880	82.94	353	1.3	H	1880	17.29	H	6.2	1.03	22.46	33	Pass
1880	86.28	12	1.0	V	1880	18.91	V	6.2	1.03	24.08	33	Pass
High Channel												
1909.8	85.11	201	2.0	H	1909.8	18.72	H	6.2	1.03	23.89	33	Pass
1909.8	85.17	253	1.7	V	1909.8	18.73	V	6.2	1.03	23.90	33	Pass

Plots of Conducted Output Power


Cellular Band (Part 22H)

GSM:


Low Channel



Middle Channel




High Channel




GPRS:


Low Channel



Middle Channel





High Channel




PCS Band (Part 24E)

GSM:


Low Channel**Middle Channel**

High Channel




GPRS:


Low Channel



Middle Channel



High Channel



§2.1049, §22.917, §22.905 & §24.238 - OCCUPIED BANDWIDTH


Applicable Standards

CFR 47 §2.1049, §22.917, §22.905 and §24.238.

Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 30 kHz (Cellular /PCS) and the 26 dB & 99% bandwidth was recorded.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100224	2008-10-16	2009-10-16
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	1100.0008.02	2008-06-21	2009-06-21

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56%
ATM Pressure:	100.0kPa

The testing was performed by Kvass Yang on 2009-04-12.

GMSK Modulation:

Cellular Band (Part 22H)

Channel	Frequency (MHz)	99% Bandwidth (kHz)	26 dB Bandwidth (kHz)
190	836.6	246.0	332.0


PCS Band (Part 24E)

Channel	Frequency (MHz)	99% Bandwidth (kHz)	26 dB Bandwidth (kHz)
661	1880.0	246.0	330.0


Please refer to the following plots.

OBW of Cellular Band (Part 22H)

99% Bandwidth




26 dB Bandwidth




OBW of PCS Band (Part 24E)

99% Bandwidth



26 dB Bandwidth



§2.1051, §22.917(a) & §24.238(a) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS


Applicable Standards

CFR 47 §2.1051, §22.917(a) and §4.238(a).

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100 kHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2008-05-09	2009-05-09
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	1100.0008.02	2008-06-21	2009-06-21

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions


Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Kvass Yang on 2009-04-15.


Please refer to the following plots.



Cellular Band (Part 22H)

30 – 1000 MHz - Middle Channel (GSM)

Fundamental test
with band stop filter


1 – 10 GHz - Middle Channel (GSM)




PCS Band (Part24E)**30 – 1000 MHz - Middle Channel (GSM)****1 - 1.9 GHz - Middle Channel (GSM)**

Fundamental test
with band stop filter

1.9 – 20 GHz - Middle Channel (GSM)



30 – 1000 MHz - Middle Channel (GPRS)



Ref Lvl 0 dBm

Marker 1 [T1] 1.66733467 GHz

RBW 1 MHz

RF Att 10 dB

VBW 3 MHz

SWT 52 ms

Unit dBm

4 dB Offset

-D1 -13 dBm

1MAX



-42.88 dBm

Start 1 GHz


900 MHz

Stop 10 GHz

Date: 15.APR.2009 22:35:30

PCS Band (Part24E)**30 – 1000 MHz - Middle Channel (GPRS)****1 – 1.9 GHz - Middle Channel (GPRS)**

1.9 – 20 GHz - Middle Channel (GPRS)



§2.1053, §22.917& §24.238 - SPURIOUS RADIATED EMISSIONS

Applicable Standards

CFR 47 § 2.1053, §22.917 and § 24.238.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = 10 lg (TXpwr in Watts/0.001) – the absolute level

Spurious attenuation limit in dB = 43 + 10 Log₁₀ (power out in Watts)

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Horn Antenna	DRH-118	A052604	2008-09-25	2009-09-25
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2009-03-11	2010-03-11
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2008-08-28	2009-08-27
HP	Preamplifier	8449B	3008A00277	2008-09-12	2009-09-11
HP	Signal Generator	HP8657A	2849U00982	2008-10-16	2009-10-16
HP	Amplifier	HP8447D	2944A09795	2008-08-02	2009-08-02
HP	Synthesized Sweeper	8341B	2624A00116	2008-11-07	2009-11-06
COM POWER	Dipole Antenna	AD-100	041000	2008-09-25	2009-09-25
A.H. System	Horn Antenna	SAS-200/571	135	2008-05-17	2009-05-17
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	1100.0008.02	2008-06-21	2009-06-21

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Kvass Yang on 2009-04-16.

Below 1 GHz:

Cellular Band (GSM)

Indicated		Table Angle Degree	Test Antenna		Substituted				Absolute Level (dBm)	Limit (dBm)	Margin (dB)
Frequency (MHz)	S.A. Reading (dBμV)		Height (m)	Polar (H/V)	Frequency (MHz)	Level (dBm)	Ant. Gain (dBi)	Cable Loss (dB)			
Middle Channel											
545.32	47.75	134	1.8	H	545.32	-53.23	0	0.68	-53.91	-13	40.91
765.34	46.49	75	1.9	H	765.34	-53.98	0	0.76	-54.74	-13	41.74
543.21	45.70	120	1.5	V	543.21	-54.12	0	0.68	-54.80	-13	41.80
764.26	44.32	225	1.4	V	764.26	-55.41	0	0.76	-56.17	-13	43.17

PCS Band (GSM)

Indicated		Table Angle Degree	Test Antenna		Substituted				Absolute Level (dBm)	Limit (dBm)	Margin (dB)
Frequency (MHz)	S.A. Reading (dBuV)		Height (m)	Polar (H/V)	Frequency (MHz)	Level (dBm)	Ant. Gain (dBi)	Cable Loss (dB)			
Middle Channel											
763.40	47.35	102	1.3	V	763.40	-51.23	0	0.76	-51.99	-13	38.99
705.52	45.14	0	1.2	V	705.52	-53.67	0	0.70	-54.37	-13	41.37
765.32	43.10	77	1.6	H	765.32	-55.47	0	0.76	-56.23	-13	43.23
709.25	42.32	158	1.8	H	709.25	-56.78	0	0.70	-57.48	-13	44.48

Above 1 GHz:

Cellular Band (GSM)

Indicated		Table Angle Degree	Test Antenna		Substituted				Absolute Level (dBm)	Limit (dBm)	Margin (dB)
Frequency (MHz)	S.A. Reading (dBμV)		Height (m)	Polar (H/V)	Frequency (MHz)	Level (dBm)	Ant. Gain (dBi)	Cable Loss (dB)			
Middle Channel											
1673.2	58.42	281	1.0	V	1673.2	-36.20	6.2	0.94	-30.94	-13	17.94
1673.2	54.39	57	1.0	H	1673.2	-37.32	6.2	0.94	-32.06	-13	19.06
2509.8	48.19	0	1.2	V	2509.8	-53.34	7.3	1.19	-47.23	-13	34.23
2509.8	46.78	125	1.6	H	2509.8	-56.07	7.3	1.19	-49.96	-13	36.96
3346.6	47.51	232	1.0	V	3346.6	-55.34	6.7	1.38	-50.02	-13	37.02
3346.6	45.13	147	1.5	H	3346.6	-59.46	6.7	1.38	-54.14	-13	41.14

PCS Band (GSM)

Indicated		Table Angle Degree	Test Antenna		Substituted				Absolute Level (dBm)	Limit (dBm)	Margin (dB)
Frequency (MHz)	S.A. Reading (dBμV)		Height (m)	Polar (H/V)	Frequency (MHz)	Level (dBm)	Ant. Gain (dBi)	Cable Loss (dB)			
Middle Channel											
3760	60.10	231	2.0	H	3760	-44.21	6.9	1.47	-38.78	-13	25.78
3760	57.551	205	2.0	V	3760	-46.52	6.9	1.47	-41.09	-13	28.09
5640	46.43	213	1.9	V	5640	-56.09	8.3	1.76	-49.55	-13	36.55
7520	45.32	164	2.2	H	7520	-55.12	7.6	2.09	-49.61	-13	36.61
7520	44.16	0	1.4	V	7520	-56.23	7.6	2.09	-50.72	-13	37.72
5640	44.56	261	1.8	H	5640	-57.34	8.3	1.76	-50.8	-13	37.8

§22.917(a) & §24.238(a) - BAND EDGES

Applicable Standards


According to § 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency, RBW set to 10 kHz.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100224	2008-11-07	2009-11-06
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	1100.0008.02	2008-06-21	2009-06-21

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Kvass Yang on 2009-04-22.

Please refer to the following tables and plots.

Cellular Band (Part 22H)

GSM:

Frequency (MHz)	Emission (dBm)	Limit (dBm)
824	-13.81	-13
849	-14.91	-13

GPRS:

Frequency (MHz)	Emission (dBm)	Limit (dBm)
824	-13.11	-13
849	-13.75	-13


PCS Band (Part 24E)

GSM:


Frequency (MHz)	Emission (dBm)	Limit (dBm)
1850	-17.88	-13
1910	-22.76	-13

GPRS:

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1850	-17.65	-13
1910	-21.94	-13


Cellular Band, Lowest Channel (GSM)

Date: 22.APR.2009 22:02:57

Cellular Band, Highest Channel (GSM)


Date: 22.APR.2009 21:59:52

Cellular Band, Lowest Channel (GPRS)




Date: 22.APR.2009 22:11:29

Cellular Band, Highest Channel (GPRS)




Date: 22.APR.2009 22:12:52

PCS Band, Lowest Channel (GSM)




Date: 22.APR.2009 22:06:52

PCS Band, Highest Channel (GSM)




Date: 22.APR.2009 22:07:51

PCS Band, Lowest Channel (GPRS)



Date: 22.APR.2009 22:33:41

PCS Band, Highest Channel (GPRS)



Date: 22.APR.2009 22:34:33

§2.1055, §22.355 & §24.235 - FREQUENCY STABILITY

Applicable Standard

CFR47 § 2.1055 (a), § 2.1055 (d), §22.355, §24.235

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929.	5.0	N/A	N/A
929 to 960.	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: An external variable DC power supply was connected to the battery terminals of the equipment under test. The voltage was set to 115% of the nominal value and was then decreased until the transmitter light no longer illuminated; i.e., the battery end point. The output frequency was recorded for each battery voltage.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
WUHUAN	Temperature & Humidity Chamber	HTP205	20021115	2008-12-28	2009-12-28
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	1100.0008.02	2008-06-21	2009-06-21

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Kvass Yang on 2009-04-22.

Cellular Band:

Middle Channel, fo = 836.6 MHz				
Temperature (°C)	Power Supplied (Vdc)	Frequency Error		Limit (ppm)
		(Hz)	(ppm)	
-30	3.7	-15	-0.0179	2.5
	3.3	-12	-0.0143	2.5
-20	3.7	-15	-0.0179	2.5
	3.3	-13	-0.0155	2.5
-10	3.7	-14	-0.0167	2.5
	3.3	-13	-0.0155	2.5
0	3.7	-13	-0.0155	2.5
	3.3	-16	-0.0191	2.5
10	3.7	-15	-0.0179	2.5
	3.3	-12	-0.0143	2.5
20	3.7	-12	-0.0143	2.5
	3.3	-12	-0.0143	2.5
30	3.7	-14	-0.0167	2.5
	3.3	-12	-0.0143	2.5
40	3.7	-18	-0.0215	2.5
	3.3	-13	-0.0155	2.5
55	3.7	-13	-0.0155	2.5
	3.3	-13	-0.0155	2.5

PCS Band:

Middle Channel, fo = 1880.0 MHz				
Temperature (°C)	Power Supplied (Vdc)	Frequency Error		Limit (ppm)
		(Hz)	(ppm)	
-30	3.7	-30	-0.016	2.5
	3.3	-33	-0.0176	2.5
-20	3.7	-17	-0.009	2.5
	3.3	-20	-0.0106	2.5
-10	3.7	-20	-0.0106	2.5
	3.3	-17	-0.009	2.5
0	3.7	-18	-0.0096	2.5
	3.3	-16	-0.0085	2.5
10	3.7	-17	-0.009	2.5
	3.3	-15	-0.008	2.5
20	3.7	-18	-0.0096	2.5
	3.3	-17	-0.009	2.5
30	3.7	-17	-0.009	2.5
	3.3	-16	-0.0085	2.5
40	3.7	-17	-0.009	2.5
	3.3	-16	-0.0085	2.5
55	3.7	-18	-0.0096	2.5
	3.3	-19	-0.0101	2.5

DECLARATION LETTER



Cellon Communications Technology (Shenzhen) Co., Ltd.
13/F, Skyworth C Building, Gaoxin S.Ave1, Hi-Tech Industrial Park, Nanshan
518057 China

Product Similarity Declaration

To Whom It May Concern,

We, Cellon Communications Technology (Shenzhen) Co., Ltd., hereby declare that our GSM&GPRS Dual Band Mobile Phone, Model Number: C640, C640/8, C640/9, C640/8R, C640/8S, C640/9R, C640/9S are electrically identical with the Model Number: C2001 that was certified by BACL. They are named differently due to marketing purposes.

Please contact me if you have any question.

Signature:

Maggie.xu 2007.4.20

Typed or Printed Name: Maggie.xu

Title: Manager

Company Name: Cellon Communications Technology (Shenzhen) Co., Ltd.

******* END OF REPORT *******