



166 South Carter, Genoa City, WI 53128

Manufacturer: CentraLite Systems, Inc.
Model Tested: 3130
Project Number: 6685

RF Exposure Compliance

Company: Centralite
Model: 3130
Formal Name: 3 Series Smart Switch

Rule Part: CFR 47 Part 1.1307(b)
CFR 47 Part 2.1093

Test Procedure: FCC 447498 D01 RF Exposure Guidance v05r02
4.3. General SAR test reduction and exclusion guidance
4.3.1. Standalone SAR test exclusion considerations

Limits: The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

$f(\text{GHz})$ is the RF channel transmit frequency in GHz.

Power and distance are rounded to the nearest mW and mm before calculation.

The result is rounded to one decimal place for comparison.

When the minimum *test separation distance* is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Output Power: This is a portable device. The maximum peak conducted output power measured 8.74 dBm. $8.74 \text{ dBm} = 7.48 \text{ mW}$

Exclusion threshold: $[7 \text{ mW} / 5 \text{ mm}] \times [\sqrt{2.440 \text{ GHz}}] = 2.2$

Results: **2.2 is ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.**
SAR measurement is not necessary.