

MPE EVALUATION

TEST REPORT

For

Vehicle Radio

Model Name: 5188, 588, TWR MR-150V (136-174 MHz)

Trade Name: --

FCC ID: T4K5188V1

Report No.: SZAGC013080601E9

Date of Issue: Jun.20, 2008

Prepared For

Qixiang Electron Science & Technology Co., Ltd.

Qixiang Building, Tangxi Industrial Zone, Luojiang District,

Quanzhou 362011, Fujian Province, China

TEL: 86-595-2265 6926

FAX: 86-595-2265 6927

Prepared By

Shenzhen Attestation of Global Compliance Science & Technology Co., Ltd

Suite B11/B12, 4F, Huafeng Mall, Chuangye 2nd Road,

25 District, Bao'an, Shenzhen

TEL: 86-755-2974 2358

FAX: 86-755-2600 8484

TABLE OF CONTENTS

1. DESCRIPTION	3
2. ANTENNA INFORMATION.....	3
3. TEST SITE.....	3
4. MEASUREMENT SYSTEM.....	4
5. MEASUREMENT UNCERTAINTY.....	4
6. METHOD OF MEASUREMENT	4
6.1 MPE MEASUREMENTS MADE ON TRUNK MOUNTED ANTENNAS	4
6.1.1 External vehicle MPE measurement.....	4
6.2 MPE MEASUREMENTS MADE ON CENTER ROOF MOUNTED ANTENNAS	5
6.3 PRESENTATION OF RESULT	6
8. CONCLUSION.....	11

1. DESCRIPTION

5188 Mobile Radio are Compatible, Conventional radio system operation.

The operation and functions for the **ST-5188** Series radios are described in this manual.

5188 has a compact size with a various features in range of 136 MHz ~ 174 MHz.

5188 has a various features shown as below.

- Wideband frequency separation,
- 25 kHz/ 12.5KHz channel spacing
- On / Off hook function, Talk Around
- Scanning, Priority Scanning
- Look Back, Scan list editing
- CTCSS / CDDCS (Conventional operation), Busy channel lockout
- Time-out timer

2. ANTENNA INFORMATION

Whip Antenna for vehicle: 136 ~ 174 MHz,

1/4 wave 3.5 dBi antenna gain

3. TEST SITE

The test site (WorldStandardizationCertification&TestingCo., Ltd.) used to collect the radiated data is located on the address of 1-2/F, Dachong Keji Building, No.28 of Tonggu Road, Nanshan District, Shenzhen, 518057, China

The registration number is 989301. The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2003.

4. MEASUREMENT SYSTEM

- Automobile: Hyundai Verna (2000)
- E-Field Survey Meter & Probe - NARDA Model EMC 20 (100kHz~3GHz)
- Calibration due date: 2009-05
- Antennas - (1/4 wave 3 dBi)

5. MEASUREMENT UNCERTAINTY

The information below presents an estimate of the possible errors that are associated with the measurement system.

Description	Error
NARDA Survey Meter:	± 4%
Repeatability Accuracy:	± 7%

6. METHOD OF MEASUREMENT

6.1 MPE MEASUREMENTS MADE ON TRUNK MOUNTED ANTENNAS

6.1.1 EXTERNAL VEHICLE MPE MEASUREMENT

(Antenna mounted in trunk center)

With the survey meter and probe, take ten (10) measurements, at the standard test distance of 60 cm to the antenna, from the back of the vehicle in a vertical line and then average the results. These measurements are taken and recorded at every twenty (20) centimeters over a range starting at twenty (20) centimeters above ground and ending at 2.0 meters.

6.1.2 INTERNAL VEHICLE MPE MEASUREMENT

(Antenna mounted in trunk center)

While rotating survey meter probe through 180 degrees to ensure that the highest level is found, scan the inside of the vehicle, both front and back seating areas, for the highest level in each location. After the highest level is found, scan vertically making two (2) additional measurements within an area approximately 40 cm wide (representing the width of a person) so as to have a total of three (3) measured points as indicated below that will be averaged.

- a) Head area
- b) Chest area
- c) Lower Trunk area

6.2 MPE MEASUREMENTS MADE ON CENTER ROOF MOUNTED ANTENNAS

6.2.1 EXTERNAL VEHICLE MPE MEASUREMENT

With the survey meter and probe, take ten (10) measurements, at the standard test distance of 60 cm from the vehicle-mounted antenna, in a vertical line and then average the results. These measurements are taken and recorded at every twenty (20) centimeters over a range starting at twenty (20) centimeters above ground and ending at 2.0 meters; this would be representative of a person standing next to a vehicle during a mobile radio transmission.

6.2.2 INTERNAL VEHICLE MPE MEASUREMENT

While rotating survey meter probe through 180 degrees to ensure that the highest level is found, scan the inside of the vehicle, both front and back seating areas, for the highest level in each location. After the highest level is found, scan vertically making two (2) additional measurements within an area approximately 40 cm wide (representing the width of a person) so as to have a total of three (3) measured points as indicated below that will be averaged.

- a) Head area
- b) Chest area
- c) Lower Trunk area

6.3 PRESENTATION OF RESULT

Power Density= The maximum value of all the measure points / 2 (The Duty Cycle of 50% was considered by deviding the maximum value by 2 and Expressed in mW/ cm²)

7. TEST RESULT

According to §1.1310 and §2.1091 RF exposure is calculated.

Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minute)
Limits for Occupational / Controlled Exposure				
0.3 – 3.0	614	1.63	(100)*	6
3.0 – 30	1842/f	4.89/f	(900/f)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100 000	/	/	5	6

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minute)
Limits for General population / Uncontrolled Exposure				
0.3 – 3.0	614	1.63	(100)*	30
3.0 – 30	842/f	2.19/f	(180/f)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100 000	/	/	1.0	30

F = Frequency in MHz

* = Plane-wave equivalent power density

Limit for Occupational / Controlled Exposure: 1.0

Limit for General Population / Uncontrolled Exposure: 0.2

External Vehicle MPE Assessment At Bottom Channel					
Antenna Location	Antenna / Gain	Meas. Distance (cm)	E/H Field	Calibration Factor	Power. Density (mW/cm ²)
Trunk	Whip/3	60	E	1	0.102
Measurement Grid					
Test Position	Height	Test Value (mW/cm ²)	Test Position	Height (cm)	Test Value (mW/cm ²)
1	20	0.07	6	120	0.10
2	40	0.07	7	140	0.11
3	60	0.10	8	160	0.10
4	80	0.11	9	180	0.11
5	100	0.15	10	200	0.10

External Vehicle MPE Assessment At Middle Channel					
Antenna Location	Antenna / Gain	Meas. Distance (cm)	E/H Field	Calibration Factor	Power. Density (mW/cm ²)
Trunk	Whip/3	60	E	1	0.088
Measurement Grid					
Test Position	Height	Test Value (mW/cm ²)	Test Position	Height (cm)	Test Value (mW/cm ²)
1	20	0.08	6	120	0.09
2	40	0.09	7	140	0.08
3	60	0.08	8	160	0.08
4	80	0.10	9	180	0.09
5	100	0.10	10	200	0.09

External Vehicle MPE Assessment At Top Channel					
Antenna Location	Antenna / Gain	Meas. Distance (cm)	E/H Field	Calibration Factor	Power. Density (mW/cm ²)
Trunk	Whip/3	60	E	1	0.086
Measurement Grid					
Test Position	Height	Test Value (mW/cm ²)	Test Position	Height (cm)	Test Value (mW/cm ²)
1	20	0.07	6	120	0.09
2	40	0.09	7	140	0.08
3	60	0.08	8	160	0.09
4	80	0.09	9	180	0.08
5	100	0.10	10	200	0.09

Internal Vehicle MPE Assessment At Bottom Channel					
Antenna Location	Antenna / Gain	Meas. Distance (cm)	E/H Field	Calibration Factor	Power Density HigherLevel (mW/cm ²)
Trunk	Whip/3	Highest Reading	E	1	0.10
Measurement Grid					
Test Position	Test Value (mW/cm ²)		Test Value (mW/cm ²)		controlled Limit
Front	0.09		0.08		0.20
Back	0.10		0.10		0.20

Internal Vehicle MPE Assessment At Middle Channel					
Antenna Location	Antenna / Gain	Meas. Distance (cm)	E/H Field	Calibration Factor	Power Density HigherLevel (mW/cm ²)
Trunk	Whip/3	Highest Reading	E	1	0.11
Measurement Grid					
Test Position	Test Value (mW/cm ²)		Test Value (mW/cm ²)		controlled Limit
Front	0.09		0.10		0.20
Back	0.10		0.11		0.20

Internal Vehicle MPE Assessment At Middle Channel					
Antenna Location	Antenna / Gain	Meas. Distance (cm)	E/H Field	Calibration Factor	Power Density HigherLevel (mW/cm ²)
Trunk	Whip/3	Highest Reading	E	1	0.11
Measurement Grid					
Test Position	Test Value (mW/cm ²)		Test Value (mW/cm ²)		controlled Limit
Front	0.09		0.09		0.20
Back	0.10		0.11		0.20

8. CONCLUSION

The measurement results complies with the FCC Limit per 47 CFR 2.1091 (b) for the Uncontrolled RF Exposure.