



**CONFORMANCE TEST REPORT
FOR
FCC 47 CFR, Part 15 Subpart C**

Report No.: 08-06-MAS-097

Client: **Caron Autosound Ltd.**
 Product: **Bluetooth A2DP Speaker with Handsfree**
 Model: **BTS-10**
 FCC ID: **T4PBTS1020080519**
 Manufacturer/supplier: **Grandunion Electronics (Shenzhen) Company Limited.**

Date test item received: 2008/06/10
 Date test campaign completed: 2008/06/23
 Date of issue: 2008/06/27


The test result only corresponds to the tested sample. It is not permitted to copy this report, in part or in full, without the permission of the test laboratory.

Total number of pages of this test report: 55 pages

Total number of pages of photos: External photos 2 pages

Internal photos 3 pages

Setup photos 1 pages

Test Engineer	Checked By	Approved By
 Ivan Tsai	 David You	 Joe Hsieh

ELECTRONICS TESTING CENTER, TAIWAN
 NO.8, LANE 29, WENMING RD.,
 LESHAN TSUEN, GUISHAN SHIANG,
 TAOYUAN COUNTY, TAIWAN 33383,
 R.O.C.TAIWAN, R.O.C.

TEL: (03) 3276170~4
 INT: +886-3-3276170~4
 FAX: (03) 3276188
 INT: +886-3-3276188



Client : Caron Autosound Ltd.
Address : Rm 1610-1611, 16/F, Metropole Square, 2 On Yiu Street, Shatin, Hong Kong
Manufacturer : Grandunion Electronics (Shenzhen) Company Limited.
Address : Zheng Keng Industrial Area, Bantian, Buji Town, Shenzhen City, China
EUT : Bluetooth A2DP Speaker with Handsfree
Trade name : ----
Model No. : BTS-10
Power Source : 3Vdc from USB or Battery
Regulations applied : FCC 47 CFR, Part 15 Subpart C (2007)

The testing described in this report has been carried out to the best of our knowledge and ability, and our responsibility is limited to the exercise of reasonable care. This certification is not intended to believe the sellers from their legal and/or contractual obligations.

The compliance test is only certified for the test equipment and the results of the testing report relate only to the item tested. The compliance test of this report was conducted in accordance with the appropriate standards. It's not intention to assure the quality and performance of the product. This report shall not be reproduced except in full, without the approval of ETC. This report must not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.

Laboratory Introduction: Electronics Testing Center, Taiwan is recognized, filed and mutual recognition arrangement as following:

- ① ISO9001: TÜV Product Service
- ② ISO/IEC 17025: BSMI, CNLA, DGT, NVLAP, CCIBLAC, UL, Compliance
- ③ Filing: FCC, Industry Canada, VCCI
- ④ MRA: Australia, Hong Kong, New Zealand, Singapore, USA, Japan, Korea, China, APLAC through CNLA
- ⑤ FCC Registration Number: 90588, 91094, 91095



NVLAP Lab Code 200133-0

Table of Contents	Page
1 GENERAL INFORMATION.....	5
1.1 Product Description.....	5
1.2 Characteristics of Device.....	5
1.3 Test Methodology.....	5
1.4 Modification List of EUT.....	5
1.5 Test Facility.....	5
2 PROVISIONS APPLICABLE	6
2.1 Definition.....	6
2.2 Requirement for Compliance	7
2.3 Restricted Bands of Operation.....	9
2.4 Labeling Requirement	9
2.5 User Information.....	10
3. SYSTEM TEST CONFIGURATION	11
3.1 Justification	11
3.2 Devices for Tested System	11
4 RADIATED EMISSION MEASUREMENT.....	12
4.1 Applicable Standard	12
4.2 Measurement Procedure	12
4.3 Measuring Instrument.....	14
4.4 Radiated Emission Data	15
4.5 Field Strength Calculation.....	18
5 CONDUCTED EMISSION MEASUREMENT	19
6 ANTENNA REQUIREMENT.....	20
6.1 Standard Applicable	20
6.2 Antenna Construction and Directional Gain	20
7 20dB EMISSION BANDWIDTH MEASUREMENT.....	21
7.1 Standard Applicable	21
7.2 Measurement Procedure	21
7.3 Measurement Equipment.....	21
7.4 Measurement Data.....	22
8 OUTPUT POWER MEASUREMENT	26
8.1 Standard Applicable	26
8.2 Measurement Procedure	26

8.3 Measurement Equipment.....	26
8.4 Measurement Data.....	27
9 OUT-OF-BAND RF CONDUCTED SPURIOUS EMISSION MEASUREMENT.....	31
9.1 Standard Applicable	31
9.2 Measurement Procedure	31
9.3 Measurement Equipment.....	31
9.4 Measurement Data.....	32
10 NUMBER OF HOPPING CHANNELS	38
10.1 Standard Applicable	38
10.2 Measurement Procedure	38
10.3 Measurement Equipment.....	38
10.4 Measurement Data.....	38
11 HOPPING CHANNEL CARRIER FREQUENCY SEPARATED	42
11.1 Standard Applicable	42
11.2 Measurement Procedure	42
11.3 Measurement Equipment.....	42
11.4 Measurement Data.....	43
12 DWELL TIME.....	47
12.1 Standard Applicable	47
12.2 Measurement Procedure	47
12.3 Measurement Equipment.....	47
12.4 Measurement Data.....	47

1 GENERAL INFORMATION

1.1 Product Description

- a) Type of EUT : Bluetooth A2DP Speaker with Handsfree
- b) Trade Name : ----
- c) Model No. : BTS-10
- d) FCC ID : T4PBTS1020080519
- e) Type of Modulation: GFSK
- f) Frequency Range : 2402MHz ~ 2480MHz

1.2 Characteristics of Device

The EUT is a Bluetooth A2DP Speaker with Handsfree based on the Bluetooth technology. Bluetooth is a short-range radio link intended to be a cable replacement between portable or fixed electronic devices. Bluetooth operates in the unlicensed ISM Band at 2.4GHz. In this band, 79 RF channels spaced 1MHz apart are defined. The rated output power is 3.8 dBm (2.399 mW).

1.3 Test Methodology

All testing were performed according to the procedures in ANSI C63.4 (2003) an FCC CFR 47 Part 2 and Part 15.

1.4 Modification List of EUT

N/A

1.5 Test Facility

The semi-anechoic chamber and conducted measurement facility used to collect the radiated and conducted data are located inside the Building at No.8, Lane 29, Wen-ming Road, Lo-shan Tsun, Kweishan Hsiang, Taoyuan, Taiwan, R.O.C.

This site has been accreditation as a FCC filing site.

2 PROVISIONS APPLICABLE

2.1 Definition

Unintentional radiator:

A device that intentionally generates and radio frequency energy for use within the device, or that sends radio frequency signals by conduction to associated equipment via connecting wiring, but which is not intended to emit RF energy by radiation or induction.

Class A Digital Device:

A digital device which is marketed for use in commercial or business environment; exclusive of a device which is market for use by the general public, or which is intended to be used in the home.

Class B Digital Device :

A digital device which is marketed for use in a residential environment notwithstanding use in a commercial, business or industrial environment. Example of such devices that are marketed for the general public.

Note : A manufacturer may also qualify a device intended to be marketed in a commercial, business, or industrial environment as a Class B digital device, and in fact is encouraged to do so, provided the device complies with the technical specifications for a Class B Digital Device. In the event that a particular type of device has been found to repeatedly cause harmful interference to radio communications, the Commission may classify such a digital device as a Class B Digital Device, Regardless of its intended use.

Intentional radiator:

A device that intentionally generates and emits radio frequency energy by radiation or induction.

2.2 Requirement for Compliance

(1) Conducted Emission Requirement

For unintentional device, according to §15.107(a) Line Conducted Emission Limits is as following:

Frequency MHz	Quasi Peak dB μ V	Average dB μ V
0.15 - 0.5	66-56*	56-46*
0.5 - 5.0	56	46
5.0 - 30.0	60	50

*Decreases with the logarithm of the frequency.

For intentional device, according to §15.207(a) Line Conducted Emission Limits is same as above table.

(2) Radiated Emission Requirement

For unintentional device, according to §15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency MHz	Distance Meters	Radiated dB μ V/m	Radiated μ V/m
30 - 88	3	40.0	100
88 - 216	3	43.5	150
216 - 960	3	46.0	200
above 960	3	54.0	500

For intentional device, according to §15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

(3) Antenna Requirement

According to §15.247 (b), if Receiving antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(4) 20dB Bandwidth Requirement

According to 15.247(a)(1), for frequency hopping systems, hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW.

(5) Output Power Requirement

For frequency hopping systems, according to 15.247(1), operating in the 2400-2483.5MHz band employing at least 75 hopping channels. The maximum peak output power of the transmitter shall not exceed 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(6) 100 kHz Bandwidth of Frequency Band Edges Requirement

According to 15.247(c), if any 100 kHz bandwidth outside these frequency bands, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be either at least 20 dB below that in any 100 kHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified in §15.209(a), whichever results in the lesser attenuation.

(7) Number of Hopping Channels

According to 15.247(b)(1), for frequency hopping systems, operating in the 2400-2483.5MHz band employing at least 75 hopping channels.

(8) Channel Carrier Frequencies Separation

According to 15.247(a)(1)(iii), the frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25kHz or the 20dB bandwidth of hopping channel, whichever is greater.

(9) Dwell Time

According to 15.247(a)(1)(iii), frequency hopping system in the 2400-2483.5MHz band employing at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 second multiplied by the number of hopping channels employed.

(10) Power Spectral Density

According to 15.247(d), for bluetooth device, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

2.3 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below :

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42-16.423	399.9-410	4.5-5.25
0.495 - 0.505 **	16.69475 - 16.69525	608-614	5.35-5.46
2.1735 - 2.1905	16.80425 - 16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475 - 156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2655-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

2.4 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device :

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

2.5 User Information

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual.

The Federal Communications Commission Radio Frequency Interference Statement includes the following paragraph.

This equipment has been tested and found to comply with the limits for a Class B Digital Device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instruction may cause harmful interference to radio communication. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio / TV technician for help.

To comply with the FCC RF exposure compliance requirement, this device and its antenna must not be co-located or operating to conjunction with any other antenna or transmitter.

3. SYSTEM TEST CONFIGURATION

3.1 Justification


For the purposes of this test report ancillary equipment is defined as equipment which is used in conjunction with the EUT to provide operational and control features to the EUT during the test. Notebook PC was used to control the RF channel under the highest, middle and lowest frequency and transmit the maximum RF power. Customer would not use it. But never the less ancillary equipment can influence the test results..

3.2 Devices for Tested System

Device	Manufacture	Model	Cable Description
*Bluetooth A2DP Speaker with Handsfree	Grandunion Electronics (Shenzhen) Company Limited.	BTS-10	----
Notebook PC	HP	nx6320	70cm*1, Unshielded Power Line
Test Jig	N/A	N/A	40cm*1, Unshielded Signal Line
Power Supply	GW	GPC-3030D	1.8m*1, Unshielded Power Line

Remark

1. “*” means equipment under test.



Note: An HP notebook performs the control test mode. The notebook removes away after the control command is ready.

4 RADIATED EMISSION MEASUREMENT

4.1 Applicable Standard

For unintentional radiator, the radiated emission shall comply with §15.109(a).

For intentional radiators, according to §15.247 (a), operation under this provision is limited to frequency hopping and digitally modulated, and the out band emission shall be comply with §15.247 (c)

4.2 Measurement Procedure

A. Final Measurement

1. Setup the configuration per figure 1 and 2 for frequencies measured below and above 1 GHz respectively. Turn on EUT and make sure that it is in continuous operating function.
2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a semi-anechoic chamber to determine the accurate frequencies of higher emissions and then each selected frequency is precisely measured. As the same purpose, for emission measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
3. For emission measured below and above 1 GHz, set the spectrum analyzer on a 120 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0 ° to 360 ° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading. A RF test receiver is also used to confirm emissions measured.

Figure 1 : Frequencies measured below 1 GHz configuration





Figure 2 : Frequencies measured above 1 GHz configuration



4.3 Measuring Instrument

The following instrument are used for radiated emissions measurement :

Equipment	Manufacturer	Model No.	Next Cal. Due
EMI Test Receiver	R&S	ESIB7	07/23/2008
Spectrum Analyzer	Rohde & Schwarz	FSU46	11/23/2008
Horn Antenna	EMCO	3115	06/12/2009
BiLog Antenna	Schaffner	CBL 6112B	07/04/2008
Horn Antenna	COM-POWER	AH-118	04/20/2009
Preamplifier	Hewlett-Packard	8449B	09/20/2008
SYNESIZED SWEEPER	AGILENT	83640B	09/21/2008

Measuring instrument setup in measured frequency band when specified detector function is used :

Frequency Band (MHz)	Instrument	Function	Resolution Bandwidth	Video Bandwidth
30 to 1000	RF Test Receiver	Quasi-Peak	120 kHz	300 kHz
	RF Test Receiver	Peak	120 kHz	300 kHz
Above 1000	Spectrum Analyzer	Peak	1 MHz	1 MHz
	Spectrum Analyzer	Average	1 MHz	10 Hz

4.4 Radiated Emission Data

4.4.1 RF Portion

a) Channel 0

Operation Mode : Transmitting

Fundamental Frequency : 2402 MHz

Test Date : Jun. 23, 2008

Temperature : 20°C

Humidity : 60%

Frequency (MHz)	Reading (dBUV)				Factor (dB) Corr.	Result @3m (dBUV/m) Peak Ave (H/V Max.)		Limit @3m (dBUV/m) Peak Ave.	
	H Peak	H Ave	V Peak	V Ave		Peak	Ave	Peak	Ave.
1201.000	---	---	---	---	-12.9	---	---	74.0	54.0
4804.000	---	---	---	---	0.5	---	---	74.0	54.0
12010.000	---	---	---	---	10.5	---	---	74.0	54.0
16216.000	---	---	---	---	13.3	---	---	74.0	54.0

b) Channel 39

Fundamental Frequency : 2441 MHz

Frequency (MHz)	Reading (dBUV)				Factor (dB) Corr.	Result @3m (dBUV/m) Peak Ave (H/V Max.)		Limit @3m (dBUV/m) Peak Ave.	
	H Peak	H Ave	V Peak	V Ave		Peak	Ave	Peak	Ave.
1220.500	---	---	---	---	-12.9	---	---	74.0	54.0
4882.000	---	---	---	---	0.5	---	---	74.0	54.0
7323.000	---	---	---	---	3.7	---	---	74.0	54.0
12205.000	---	---	---	---	5.8	---	---	74.0	54.0
19528.000	---	---	---	---	13.3	---	---	74.0	54.0

c) Channel 78

Fundamental Frequency : 2480 MHz


Frequency (MHz)	Reading (dBUV)				Factor (dB) Corr.	Result @3m (dBUV/m) Peak Ave (H/V Max.)		Limit @3m (dBUV/m) Peak Ave.	
	H Peak	H Ave	V Peak	V Ave		Peak	Ave	Peak	Ave.
1240.000	---	---	---	---	-12.9	---	---	74.0	54.0
4960.000	---	---	---	---	0.5	---	---	74.0	54.0
7440.000	---	---	---	---	3.7	---	---	74.0	54.0
12400.000	---	---	---	---	5.8	---	---	74.0	54.0
19840.000	---	---	---	---	13.3	---	---	74.0	54.0
22320.000	---	---	---	---	13.5	---	---	74.0	54.0

Note :


1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. Item “Margin” referred to Average limit while there is only peak result.
4. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.

4.4.2 Other Emission

A. below 1GHz



EUT : Bluetooth A2DP Speaker with Handsfree	Model : BTS-10	Status : Operation Mode	
Condition : Vertical	Date : 2008/6/23	Temp. : 20°C	Humi. : 60%



	Freq (MHz)	QP Level (dBuV)	Factor (dB/m)	QP Result (dBuV/m)	QP Limit (dBuV/m)	QP Margin (dB)
1	30.000	17.8	19.7	37.5	40.0	-2.5
2	203.006	24.0	12.7	36.7	43.5	-6.8
3	309.920	28.2	17.2	45.4	46.0	-0.6
4	407.114	22.4	20.2	42.6	46.0	-3.4
5	473.206	19.6	21.6	41.2	46.0	-4.8
6	663.707	17.6	24.5	42.1	46.0	-3.9

B. above 1GHz

Frequency (MHz)	Ant Pol H / V	Reading (dBuV) Peak	Correct Factor (dB)	Duty Factor (dB)	Result @3m (dBuV/m) Peak AVG	Limit @3m (dBuV/m) Peak AVG	Margins (dB)
Radiated emission frequencies above 1 GHz to 12.5 GHz were too low to be measured.							

Note:

1. Place of Measurement: Measuring site of the ETC.
2. If the data table appeared symbol of "***" means the value was too low to be measured.
3. The estimated measurement uncertainty of the result measurement is
 - ±4.6dB (30MHz ≤ f < 300MHz).
 - ±4.4dB (300MHz ≤ f < 1000MHz).
 - ±4.1dB (1GHz ≤ f ≤ 18GHz).

4.4.3 Radiated Measurement at Bandedge with Fundamental Frequencies

(A)

Channel 0

Operation Mode : Transmitting

Fundamental Frequency : 2402 MHz

Test Date : Jun. 23, 2008

Temperature : 20°C

Humidity : 60%

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m) Peak Ave (H/V Max.)		Limit @3m (dBuV/m) Peak Ave.	
	H Peak	V Ave	H Peak	V Ave		Peak	Ave	Peak	Ave.
2390.000	26.17	15.41	25.39	14.62	30.3	56.47	45.71	74.0	54.0

Note:

The result is the highest value of radiated emission from restrict band of 2310 ~2390 MHz.

(B)

Channel 78

Operation Mode : Transmitting

Fundamental Frequency : 2480 MHz

Test Date : Jun. 23, 2008

Temperature : 20°C

Humidity : 60%

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m) Peak Ave (H/V Max.)		Limit @3m (dBuV/m) Peak Ave.	
	H Peak	V Ave	H Peak	V Ave		Peak	Ave	Peak	Ave.
2483.500	25.84	14.92	25.66	13.87	30.3	56.14	45.22	74.0	54.0

Note:

The result is the highest value of radiated emission from restrict band of 2483.5 ~2500 MHz.

4.5 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor, High Pass Filter Loss(if used) and Cable Loss, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation calculation is as follows:

$$\mathbf{Result = Reading + Corrected Factor}$$

where

$$\text{Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$

5 CONDUCTED EMISSION MEASUREMENT

This EUT is excused from investigation of conducted emission, for it is powered by battery only. According to §15.207 (d), measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines.

6 ANTENNA REQUIREMENT

6.1 Standard Applicable

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to §15.247 (b), if Receiving antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

6.2 Antenna Construction and Directional Gain

The antennas fix on the PCB. The peak gain of antenna used is -0.833 dBi.

7 20dB EMISSION BANDWIDTH MEASUREMENT


7.1 Standard Applicable

According to 15.247(a)(1), for frequency hopping systems, hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of hopping channel, whichever is greater.

7.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. The setup of the EUT as shown in figure 3. Turn on the EUT and connect it to measurement instrument. Then set it to any convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Figure 3: Emission bandwidth measurement configuration.



7.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Next Cal. Due
Spectrum Analyzer	Agilent	8564EC	10/10/2008

7.4 Measurement Data


Test Date : Jun. 10, 2008

Temperature : 20°C

Humidity : 60%

Channel	Frequency (MHz)	20 dB Bandwidth (MHz)	Chart
0	2402	0.750	Page 23
39	2441	0.820	Page 24
78	2480	0.950	Page 25


Note: Please refer to page 23 to page 25 for chart.



Test Request: (-28.7dBm)

Mkr	Frequency (MHz)	Level (dBm)
1	2402.005	-8.7
2	2401.600	-32.8
3	2402.350	-29.8


		ΔFrequency (MHz)	ΔLevel (dB)
1	Mkr 3 - Mkr 2	0.750	3.0



Test Request: (-30.16dBm)

Mkr	Frequency (MHz)	Level (dBm)
1	2441.015	-10.2
2	2440.600	-34.7
3	2441.420	-30.3

		ΔFrequency (MHz)	ΔLevel (dB)
1	Mkr 3 - Mkr 2	0.820	4.4



Test Request: (-32.0dBm)

Mkr	Frequency (MHz)	Level (dBm)
1	2480.015	-12.0
2	2479.490	-33.5
3	2480.440	-32.2

		△Frequency (MHz)	△Level (dB)
1	Mkr 3 - Mkr 2	0.950	1.3

8 OUTPUT POWER MEASUREMENT

8.1 Standard Applicable

For frequency hopping system, according to 15.247(b), the maximum peak output power of the transmitter shall not exceed 1 Watt. If Receiving antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

8.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. The setup of the EUT as shown in figure 3. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz and VBW to 3 MHz.
4. Measure the highest amplitude appearing on spectral display and record the level to calculate result data.
5. Repeat above procedures until all frequencies measured were complete.

8.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Next Cal. Due
Spectrum Analyzer	Agilent	8564EC	10/10/2008

8.4 Measurement Data


Test Date : Jun. 10, 2008

Temperature : 20°C

Humidity : 60%

Channel	Frequency (MHz)	Reading (dBm)	Cable Loss (dB)	Maximum Peak Output Power (dBm)	Maximum Peak Output Power (mW)	FCC Limit (mW)	Chart
0	2402	-6.2	10.0	3.8	2.399	1000	Page 28
39	2441	-7.5	10.0	2.5	1.778	1000	Page 29
78	2480	-9.7	10.0	0.3	1.072	1000	Page 30

Note: Please refer to page 28 to page 30 for chart.




Test Request: (30dBm)

	Freq (MHz)	PK Level (dBm)	Factor (dB)	PK Result (dBm)	PK Limit (dBm)	PK Margin (dB)
1	2401.842	-6.2	10.0	3.8	30.0	-26.2



Test Request: (30dBm)

	Freq (MHz)	PK Level (dBm)	Factor (dB)	PK Result (dBm)	PK Limit (dBm)	PK Margin (dB)
1	2440.875	-7.5	10.0	2.5	30.0	-27.5



Test Request: (30dBm)

	Freq (MHz)	PK Level (dBm)	Factor (dB)	PK Result (dBm)	PK Limit (dBm)	PK Margin (dB)
1	2480.050	-9.7	10.0	0.3	30.0	-29.7

9 OUT-OF-BAND RF CONDUCTED SPURIOUS EMISSION MEASUREMENT

9.1 Standard Applicable

According to 15.247(c), if any 100 kHz bandwidth outside these frequency bands, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be either at least 20 dB below that in any 100 kHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified in §15.209(a), whichever results in the lesser attenuation.

9.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. The setup of the EUT as shown in figure 3. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

9.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Next Cal. Due
Spectrum Analyzer	Agilent	8564EC	10/10/2008

9.4 Measurement Data

Test Date : Jun. 10, 2008


Temperature : 20°C

Humidity : 60%

Channel	Test Frequency Range	Note	Chart
0	2350 MHz - 2450 MHz	Lower Band Edge	Page 33
78	2433.5 MHz - 2533.5 MHz	Upper Band Edge	Page 34
0	30 MHz - 25 GHz		Page 35
39	30 MHz - 25 GHz		Page 36
78	30 MHz - 25 GHz		Page 37

Note: Please refer to page 33 to page 37 for chart.


EUT : Bluetooth A2DP Speak with handsfree	Model : BTS-10	Status : Bluetooth-CH00-Band Edge	
Condition : RF Conduction	Date : 2008/6/10	Temp. : 20°C	Humi. : 60%
RBW: 100 kHz	VBW: 300 kHz	SWP: 50ms	ATTEN: 10dB



Test Request: (-26.3dBm)

Mkr	Frequency (MHz)	Level (dBm)
1	2401.333	-6.3
2	2399.500	-57.7


	Δ Frequency (MHz)	Δ Level (dB)
1	Mkr 1 - Mkr 2	51.4



Test Request: (-29.7dBm)

Mkr	Frequency (MHz)	Level (dBm)
1	2480.833	-9.7
2	2484.833	-58.8


		ΔFrequency (MHz)	ΔLevel (dB)
1	Mkr 1 - Mkr 2	-4.000	49.1



Test Request: (-28.0dBm)

		△Frequency (MHz)	△Level (dB)
1	Mkr 1 - Mkr 2	790.716	53.7


EUT : Bluetooth A2DP Speak with handsfree	Model : BTS-10	Status : Bluetooth-CH39-BandEdge_All	
Condition : RF Conduction	Date : 2008/6/10	Temp. : 20°C	Humi. : 60%
RBW: 100 kHz	VBW: 300 kHz	SWP: 6300ms	ATTEN: 10dB



Test Request: (-28.8dBm)

		Δ Frequency (MHz)	Δ Level (dB)
1	Mkr 1 - Mkr 2	790.717	52.7

EUT : Bluetooth A2DP Speak with handsfree	Model : BTS-10	Status : Bluetooth-CH78-BandEdge_All	
Condition : RF Conduction	Date : 2008/6/10	Temp. : 20°C	Humi. : 60%
RBW: 100 kHz	VBW: 300 kHz	SWP: 6300ms	ATTEN: 10dB



Test Request: (-30.8dBm)

		Δ Frequency (MHz)	Δ Level (dB)
1	Mkr 1 - Mkr 2	832.334	50.5

10 NUMBER of HOPPING CHANNELS

10.1 Standard Applicable

According to 15.247(b)(1), for frequency hopping systems, operating in the 2400-2483.5MHz band employing at least 75 hopping channels

10.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. The setup of the EUT as shown in figure 3. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set EUT to hopping operating mode and set spectrum analyzer maximum to measure the number of hopping channels.

10.3 Measurement Equipment


Equipment	Manufacturer	Model No.	Next Cal. Due
Spectrum Analyzer	Agilent	8564EC	10/10/2008


10.4 Measurement Data


Test Date : Jun. 10, 2008 Temperature : 20°C Humidity : 60%

Number of hopping channels = 79 channels

Note: Please refer to page 39 to page 41 for chart.







11 HOPPING CHANNEL CARRIER FREQUENCY SEPARATED

11.1 Standard Applicable

According to 15.247(a)(1), the frequency hopping system shall have hopping channel carrier frequencies separated by minimum of 25kHz or the 20dB bandwidth of hopping channel, whichever is greater.

11.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. The setup of the EUT as shown in figure 3. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any measurement frequency within its operating range and make sure the instrument is operated in its linear range.
3. Set spectrum analyzer maximum hold to measure channel carrier frequency , then adjust channel carrier frequency to adjacent channel.
4. Repeat above procedure until all measured frequencies were complete.

11.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Next Cal. Due
Spectrum Analyzer	Agilent	8564EC	10/10/2008

11.4 Measurement Data


Test Date : Jun. 10, 2008

Temperature : 20°C

Humidity : 60%

Channel	Frequency (MHz)	Hopping Channel Carrier Frequency Separated (MHz)	Chart
0	2402	0.990	Page 44
39	2441	1.005	Page 45
78	2480	1.015	Page 46


Note: Please refer to page 44 to page 46 for chart.



Test Request: None

Mkr	Frequency (MHz)	Level (dBm)
1	2402.000	-6.8
2	2402.990	-7.3


		ΔFrequency (MHz)	ΔLevel (dB)
1	Mkr 1 - Mkr 2	-0.990	0.5



Test Request: None

Mkr	Frequency (MHz)	Level (dBm)
1	2441.030	-8.0
2	2442.035	-8.3

		ΔFrequency (MHz)	ΔLevel (dB)
1	Mkr 1 - Mkr 2	-1.005	0.3



Test Request: None

Mkr	Frequency (MHz)	Level (dBm)
1	2479.025	-11.0
2	2480.040	-10.5

		ΔFrequency (MHz)	ΔLevel (dB)
1	Mkr 1 - Mkr 2	-1.015	-0.5

12 Dwell Time

12.1 Standard Applicable

According to 15.247(a)(1)(iii), frequency hopping system in the 2400-2483.5MHz band employing at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 second multiplied by the number of hopping channels employed.

12.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. The setup of the EUT as shown in figure 3.

12.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Next Cal. Due
Spectrum Analyzer	Agilent	8564EC	10/10/2008

12.4 Measurement Data

Test Date : Jun. 10, 2008

Temperature : 20°C


Humidity : 60%

13.4.1 DH1

Test period=0.4(second/channel)× 79 channel=31.6sec

2402MHz dwell time= 420.0 us× $\frac{800}{79}$ ×31.6 = 134.40 ms


Note: Please refer to page 48 to page 49 for chart.



Test Request: None

Mkr	Time (ms)	Level (dBm)
1	0.297	-7.8
2	0.717	-8.3

	Mkr 1 - Mkr 2	ΔTime (ms)	ΔLevel (dB)
1	Mkr 1 - Mkr 2	-0.420	0.5




12.4.2 DH3

Test period=0.4(second/channel)× 79 channel=31.6sec

2441MHz dwell time= $1.677 \text{ ms} \times \frac{400}{79} \times 31.6 = 268.32 \text{ ms}$


Note: Please refer to page 51 to page 52 for chart.



Test Request: None

Mkr	Time (ms)	Level (dBm)
1	0.290	-10.0
2	1.967	-9.2

	△Time (ms)	△Level (dB)
1	Mkr 1 - Mkr 2	-0.8




12.4.3 DH5

Test period=0.4(second/channel)× 79 channel=31.6sec

$$2480\text{MHz dwell time} = 2.920 \text{ ms} \times \frac{260}{79} \times 31.6 = 303.68 \text{ ms}$$

Note: Please refer to page 54 to page 55 for chart.



Test Request: None

Mkr	Time (ms)	Level (dBm)
1	0.680	-10.5
2	3.600	-10.0

	Mkr 1 - Mkr 2	ΔTime (ms)	ΔLevel (dB)
1	Mkr 1 - Mkr 2	-2.920	-0.5

EUT : Bluetooth A2DP Speak with handsfree	Model : BTS-10	Status : Bluetooth-CH78-DH5-DwellTime-Peroid	
Condition : RF Conduction	Date : 2008/6/10	Temp. : 20°C	Humi. : 60%
Center Freq.: 2480MHz	RBW: 1000 kHz	VBW: 1000 kHz	ATTEN: 10dB

