



FCC Radio Test Report

FCC ID: T58WF2505R

This report concerns (check one): Original Grant Class II Change

Issued Date : Apr. 11, 2014
Project No. : 1403C216
Equipment : 150Mbps wireless N high power USB Adapter
Model Name : WF2505
Applicant : NETIS SYSTEMS CO., LTD
Address : 4F&5F R&D Building, Oriental Cyberport, High-Tech Industrial Park, Nanshan, Shenzhen, China.

Tested by: Neutron Engineering Inc. EMC Laboratory
Date of Receipt: Mar. 28, 2014
Date of Test: Mar. 25, 2014~ Apr. 10, 2014

Testing Engineer : David Mao
(David Mao)

Technical Manager : Leo Hung
(Leo Hung)

Authorized Signatory : Steven Lu
(Steven Lu)

Neutron Engineering Inc.

No.3, Jinshagang 1st Road, ShiXia,
Dalang Town, Dong Guan, China.

TEL: 0769-8318-3000

FAX: 0769-8319-6000



Declaration

Neutron represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (**NML**) of **R.O.C.**, or National Institute of Standards and Technology (**NIST**) of **U.S.A.**

Neutron's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **Neutron** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **Neutron** issued reports.

Neutron's reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **Neutron-self**, extracts from the test report shall not be reproduced except in full with **Neutron's** authorized written approval.

Neutron's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.



Table of Contents	Page
1 . CERTIFICATION	6
2 . SUMMARY OF TEST RESULTS	7
2.1 TEST FACILITY	8
2.2 MEASUREMENT UNCERTAINTY	8
3 . GENERAL INFORMATION	9
3.1 GENERAL DESCRIPTION OF EUT	9
3.2 DESCRIPTION OF TEST MODES	11
3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	12
3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	13
3.5 DESCRIPTION OF SUPPORT UNITS	14
4 . EMC EMISSION TEST	15
4.1 CONDUCTED EMISSION MEASUREMENT	15
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS	15
4.1.2 TEST PROCEDURE	15
4.1.3 DEVIATION FROM TEST STANDARD	15
4.1.4 TEST SETUP	16
4.1.5 EUT OPERATING CONDITIONS	16
4.1.6 EUT TEST CONDITIONS	16
4.1.7 TEST RESULTS	16
4.2 RADIATED EMISSION MEASUREMENT	19
4.2.1 RADIATED EMISSION LIMITS	19
4.2.2 TEST PROCEDURE	20
4.2.3 DEVIATION FROM TEST STANDARD	20
4.2.4 TEST SETUP	21
4.2.5 EUT OPERATING CONDITIONS	22
4.2.6 EUT TEST CONDITIONS	22
4.2.7 TEST RESULTS (9K~ 30MHZ)	23
4.2.8 TEST RESULTS (BETWEEN 30 – 1000 MHZ)	24
4.2.9 TEST RESULTS (ABOVE 1000 MHZ)	31
5 . BANDWIDTH TEST	60
5.1 APPLIED PROCEDURES	60
5.1.1 TEST PROCEDURE	60
5.1.2 DEVIATION FROM STANDARD	60
5.1.3 TEST SETUP	60
5.1.4 EUT OPERATION CONDITIONS	60
5.1.5 EUT TEST CONDITIONS	60
5.1.6 TEST RESULTS	61
6 . MAXIMUM OUTPUT POWER TEST	69



Table of Contents	Page
6.1 APPLIED PROCEDURES / LIMIT	69
6.1.1 TEST PROCEDURE	69
6.1.2 DEVIATION FROM STANDARD	69
6.1.3 TEST SETUP	69
6.1.4 EUT OPERATION CONDITIONS	69
6.1.5 EUT TEST CONDITIONS	69
6.1.6 TEST RESULTS	70
7 . ANTENNA CONDUCTED SPURIOUS EMISSION	71
7.1 APPLIED PROCEDURES / LIMIT	71
7.1.1 TEST PROCEDURE	71
7.1.2 DEVIATION FROM STANDARD	71
7.1.3 TEST SETUP	71
7.1.4 EUT OPERATION CONDITIONS	71
7.1.5 EUT TEST CONDITIONS	71
7.1.6 TEST RESULTS	72
8 . POWER SPECTRAL DENSITY TEST	92
8.1 APPLIED PROCEDURES / LIMIT	92
8.1.1 TEST PROCEDURE	92
8.1.2 DEVIATION FROM STANDARD	92
8.1.3 TEST SETUP	92
8.1.4 EUT OPERATION CONDITIONS	92
8.1.5 EUT TEST CONDITIONS	92
8.1.6 TEST RESULTS	93
9 . MEASUREMENT INSTRUMENTS LIST	101
10 . EUT TEST PHOTO	103



REPORT ISSUED HISTORY

Issued No.	Description	Issued Date
NEI-FCCP-1-1403C216	Original Issue.	Apr. 11, 2014



1. CERTIFICATION

Equipment : 150Mbps wireless N high power USB Adapter
Brand Name : netis
Model Name : WF2505
Applicant : NETIS SYSTEMS CO., LTD
Date of Test : Mar. 25, 2014~ Apr. 10, 2014
Test Item : ENGINEERING SAMPLE
Standard(s) : FCC Part15, Subpart C(15.247) / ANSI C63.4-2009

The above equipment has been tested and found compliance with the requirement of the relative standards by Neutron Engineering Inc. EMC Laboratory.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. NEI-FCCP-1-1403C216) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).



2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

Applied Standard(s): FCC Part15 (15.247) , Subpart C				
Standard(s)	Section	Test Item	Judgment	Remark
	FCC			
	15.207	Conducted Emission	PASS	
	15.247(d)	Antenna conducted Spurious Emission	PASS	
	15.247(a)(2)	6dB Bandwidth	PASS	
	15.247(b)(3)	Peak Output Power	PASS	
	15.247(e)	Power Spectral Density	PASS	
	15.203	Antenna Requirement	PASS	
	15.209/15.205	Transmitter Radiated Emissions	PASS	

NOTE:

- (1) "N/A" denotes test is not applicable in this test report.
- (2) The test follows FCC KDB Publication No. 558074 D01 DTS Meas Guidance v03r01 (Measurement Guidelines of DTS)



2.1 TEST FACILITY

The test facilities used to collect the test data in this report is **DG-C02/DG-CB03** at the location of No.3,Jinshagang 1st Road, ShiXia, Dalang Town, Dong Guan, China.523792
 Neutron's test firm number for FCC: 319330

2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

A. Conducted Measurement :

Test Site	Method	Measurement Frequency Range	U , (dB)	NOTE
DG-C02	CISPR	150 KHz ~ 30MHz	1.94	

B. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	Ant. H / V	U , (dB)	NOTE
DG-CB03	CISPR	9KHz~30MHz	V	3.79	
		9KHz~30MHz	H	3.57	
		30MHz ~ 200MHz	V	3.82	
		30MHz ~ 200MHz	H	3.60	
		200MHz ~ 1,000MHz	V	3.86	
		200MHz ~ 1,000MHz	H	3.94	
		1GHz~18GHz	V	3.12	
		1GHz~18GHz	H	3.68	
		18GHz~40GHz	V	4.15	
		18GHz~40GHz	H	4.14	



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	150Mbps wireless N high power USB Adapter	
Brand Name	netis	
Model Name	WF2505	
Model Difference	N/A	
Product Description	Operation Frequency	2412~2462 MHz
	Modulation Technology	802.11b:DSSS 802.11g:OFDM 802.11n:OFDM
	Bit Rate of Transmitter	802.11b: 11/5.5/2/1 Mbps 802.11g: 54/48/36/24/18/12/9/6 Mbps 802.11n up to 150 Mbps
	Output Power (Max.)	802.11b: 16.91dBm 802.11g: 17.55 dBm 802.11n(20MHz): 18.99 dBm 802.11n(40MHz): 19.21 dBm
Power Source	Supplied from USB port.	
Power Rating	DC 5V	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2. Channel List:

CH 01 – CH 11 for 802.11b, 802.11g, 802.11n(20MHz) CH 03 – CH 09 for 802.11n(40MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

3. Table for Filed Antenna:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	<i>RF link</i>	RF21S00001A	Dipole	R-SMA	5.24



3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX B MODE CHANNEL 01/06/11
Mode 2	TX G MODE CHANNEL 01/06/11
Mode 3	TX N-20MHZ MODE CHANNEL 01/06/11
Mode 4	TX N-40MHZ MODE CHANNEL 03/06/09
Mode 5	TX MODE

The EUT system operated these modes were found to be the worst case during the pre-scanning test as following:

For Conducted Test	
Final Test Mode	Description
Mode 5	TX MODE

For Radiated Test	
Final Test Mode	Description
Mode 1	TX B MODE CHANNEL 01/06/11
Mode 2	TX G MODE CHANNEL 01/06/11
Mode 3	TX N-20MHZ MODE CHANNEL 01/06/11
Mode 4	TX N-40MHZ MODE CHANNEL 03/06/09

Note:

- (1) The measurements are performed at the high, middle, low available channels.
- (2) 802.11b mode: DBPSK (1Mbps)
 802.11g mode: OFDM (6Mbps)
 802.11n HT20 mode : BPSK (6.5Mbps)
 802.11n HT40 mode : BPSK (6.5Mbps)
 For radiated emission tests, the highest output powers were set for final test.
- (3) For radiated below 1G test, the 802.11b is found to be the worst case and recorded.



3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING


During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of WLAN

Test software version	GUI_Demo_01.05.29_8192		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b DSSS	5	4	4
IEEE 802.11g OFDM	0F	0F	0F
IEEE 802.11n (20MHz)	0C	0C	0D
Frequency (MHz)	2422 MHz	2437 MHz	2452 MHz
IEEE 802.11n (40MHz)	0D	0D	0D




3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted TX Mode:



Radiated TX Mode:



- C-1 Parallel Cable
- C-2 RS232 Cable
- C-3 D-Sub Cable
- C-4 USB Cable
- C-5 USB Cable
- C-6 USB Cable



3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
E-1	USB Keyboard	Dell	L100	DOC	CNORH659658907 1T08NE	
E-2	Notebook	Lenovo	E46L	DOC	EB22953770	
E-3	PC	Dell 755	DCSM	DOC	8PWN82X	
E-4	Modem	ACEEX	DM-1414V	IFAXDM141 4	0603002131	
E-5	Printer	SII	DPU-414	DOC	3018507 B	
E-6	LCD monitor	Dell	E177FPc	DOC	CNOFJ179-64180- 6AG-1WNS	
E-7	USB Mouse	Dell	MO56UOA	DOC	FQJ000BS	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	YES	NO	1.5m	
C-2	YES	NO	1.5m	
C-3	YES	YES	1.5m	
C-4	YES	NO	1.5m	
C-5	YES	NO	1.5m	
C-6	YES	NO	1.5m	



4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

Frequency (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz


4.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

4.1.6 EUT TEST CONDITIONS

Temperature: 18°C
 Relative Humidity: 55%
 Test Voltage: AC 120V/60Hz

4.1.7 TEST RESULTS


Remark:

- (1) All readings are QP Mode value unless otherwise stated AVG in column of 'Note'. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform. In this case, a "*" marked in AVG Mode column of Interference Voltage Measured.
- (2) Measuring frequency range from 150KHz to 30MHz.



Test Mode : TX MODE

Line




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.1930	34.44	9.65	44.09	63.91	-19.82	peak	
2	0.4781	27.67	9.70	37.37	56.37	-19.00	peak	
3 *	1.7242	33.47	9.81	43.28	56.00	-12.72	peak	
4	2.0094	32.67	9.84	42.51	56.00	-13.49	peak	
5	2.8727	28.74	9.86	38.60	56.00	-17.40	peak	
6	23.2422	28.05	10.29	38.34	60.00	-21.66	peak	



Test Mode : TX MODE

Neutral



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.1930	26.05	9.71	35.76	63.91	-28.15	peak	
2	0.5720	30.33	9.74	40.07	56.00	-15.93	peak	
3	0.8610	30.17	9.76	39.93	56.00	-16.07	peak	
4	2.0094	34.48	9.86	44.34	56.00	-11.66	peak	
5 *	2.0094	30.90	9.86	40.76	46.00	-5.24	AVG	
6	2.3922	34.35	9.88	44.23	56.00	-11.77	peak	
7	2.3922	30.60	9.88	40.48	46.00	-5.52	AVG	
8	2.8687	33.86	9.88	43.74	56.00	-12.26	peak	



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 RADIATED EMISSION LIMITS (Frequency Range 9KHz-1000MHz)

20dB in any 100 KHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

Frequency (MHz)	(dBuV/m) (at 3 meters)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9KHz~90KHz for PK/AVG detector
Start ~ Stop Frequency	90KHz~110KHz for QP detector
Start ~ Stop Frequency	110KHz~490KHz for PK/AVG detector
Start ~ Stop Frequency	490KHz~30MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector



4.2.2 TEST PROCEDURE


- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.2.3 DEVIATION FROM TEST STANDARD


No deviation

4.2.4 TEST SETUP


(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1 GHz



(C) For radiated emissions below 30MHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

4.2.6 EUT TEST CONDITIONS

Temperature: 21°C

Relative Humidity: 55%

Test Voltage: AC 120V/60Hz



4.2.7 TEST RESULTS (9K~ 30MHZ)

Test Mode : TX Mode 2412MHz

Freq. (MHz)	Ant. 0°/90°	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
0.0094	0°	68.35	24.30	92.65	128.11	-35.46	AV
0.0094	0°	72.35	24.30	96.65	148.11	-51.46	PK
0.0136	0°	70.35	24.30	94.65	124.93	-30.28	AV
0.0136	0°	79.35	24.30	103.65	144.93	-41.28	PK
0.0244	0°	56.36	24.02	80.38	119.86	-39.48	AV
0.0244	0°	60.12	24.02	84.14	139.86	-55.72	PK
0.0326	0°	61.36	23.50	84.86	117.34	-32.48	AV
0.0326	0°	65.38	23.50	88.88	137.34	-48.46	PK
0.5680	0°	18.72	20.02	38.74	72.52	-33.78	QP
1.7536	0°	18.95	19.52	38.47	69.54	-31.07	QP

Freq. (MHz)	Ant. 0°/90°	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
0.0093	90°	76.35	24.30	100.65	128.21	-27.56	AVG
0.0093	90°	82.36	24.30	106.66	148.21	-41.55	PK
0.0235	90°	56.38	24.08	80.46	120.18	-39.72	AVG
0.0235	90°	59.35	24.08	83.43	140.18	-56.75	PK
0.0317	90°	57.35	23.56	80.91	117.58	-36.67	AVG
0.0317	90°	58.35	23.56	81.91	137.58	-55.67	PK
0.0429	90°	59.35	22.85	82.20	114.96	-32.76	AVG
0.0429	90°	63.35	22.85	86.20	134.96	-48.76	PK
0.4911	90°	17.45	19.82	37.27	73.78	-36.51	QP
1.7156	90°	18.63	19.53	38.16	69.54	-31.38	QP

Remark:

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (2) Distance extrapolation factor = 40 log (specific distance / test distance) (dB);
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor.




4.2.8 TEST RESULTS (BETWEEN 30 – 1000 MHZ)

Remark:

- (1) Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode or Peak Mode with Detector BW=120KHz ; SPA setting in RBW=120KHz, VBW =120KHz, Swp. Time = 0.3 sec./MHz.
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- (3) Measuring frequency range from 30MHz to 1000MHz.
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not show in table.




Test Mode: TX B MODE CHANNEL 01



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	32.9100	46.18	-23.00	23.18	40.00	-16.82	peak	
2		167.7400	38.91	-17.72	21.19	43.50	-22.31	peak	
3		278.3200	39.10	-16.12	22.98	46.00	-23.02	peak	
4		487.8400	38.86	-16.24	22.62	46.00	-23.38	peak	
5		746.8300	32.66	-7.10	25.56	46.00	-20.44	peak	
6		980.6000	31.91	-5.44	26.47	54.00	-27.53	peak	



Test Mode: TX B MODE CHANNEL 01




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	112.4500	41.45	-24.07	17.38	43.50	-26.12	peak	
2	167.7400	42.55	-20.26	22.29	43.50	-21.21	peak	
3	242.4300	49.23	-22.91	26.32	46.00	-19.68	peak	
4	415.0900	37.95	-12.83	25.12	46.00	-20.88	peak	
5 *	695.4200	36.72	-9.52	27.20	46.00	-18.80	peak	
6	976.7200	33.97	-4.96	29.01	54.00	-24.99	peak	



Test Mode: TX B MODE CHANNEL 06

Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	32.9100	46.18	-23.00	23.18	40.00	-16.82	peak	
2		156.1000	41.75	-19.02	22.73	43.50	-20.77	peak	
3		278.3200	42.10	-16.12	25.98	46.00	-20.02	peak	
4		431.5800	39.08	-15.80	23.28	46.00	-22.72	peak	
5		709.0000	35.58	-10.28	25.30	46.00	-20.70	peak	
6		833.1600	34.39	-10.03	24.36	46.00	-21.64	peak	



Test Mode: TX B MODE CHANNEL 06

Horizontal




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1 *	155.1300	48.09	-22.09	26.00	43.50	-17.50	peak	
2	242.4300	48.23	-22.91	25.32	46.00	-20.68	peak	
3	415.0900	36.95	-12.83	24.12	46.00	-21.88	peak	
4	695.4200	36.72	-9.52	27.20	46.00	-18.80	peak	
5	791.4500	32.00	-8.61	23.39	46.00	-22.61	peak	
6	976.7200	33.47	-4.96	28.51	54.00	-25.49	peak	



Test Mode: TX B MODE CHANNEL 11


Vertical



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	71.7100	46.63	-26.54	20.09	40.00	-19.91	peak	
2	167.7400	39.91	-17.72	22.19	43.50	-21.31	peak	
3	278.3200	39.10	-16.12	22.98	46.00	-23.02	peak	
4	487.8400	37.86	-16.24	21.62	46.00	-24.38	peak	
5	709.0000	36.08	-10.28	25.80	46.00	-20.20	peak	
6 *	833.1600	36.39	-10.03	26.36	46.00	-19.64	peak	



Test Mode: TX B MODE CHANNEL 11



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	95.9600	43.41	-26.18	17.23	43.50	-26.27	peak	
2	167.7400	40.55	-20.26	20.29	43.50	-23.21	peak	
3 *	242.4300	47.23	-22.91	24.32	46.00	-21.68	peak	
4	415.0900	34.95	-12.83	22.12	46.00	-23.88	peak	
5	695.4200	33.22	-9.52	23.70	46.00	-22.30	peak	
6	944.7100	29.86	-5.67	24.19	46.00	-21.81	peak	



4.2.9 TEST RESULTS (ABOVE 1000 MHZ)

Remark:

- (1) All readings are Peak unless otherwise stated QP in column of 『Note 』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency;"H" denotes spurious frequency;"E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission.
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:
"X" - denotes Laid on Table; "Y" - denotes Vertical Stand; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



Test Mode : TX B MODE 2412MHz

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		Note
		Peak	AV		Peak	AV	Peak	AV	
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2390.00	V	24.53	14.19	34.09	58.62	48.28	74.00	54.00	X/E
2411.20	V	70.46	68.35	34.16	104.62	102.51			X/F
4824.00	V	37.30	28.21	6.43	43.73	34.64	74.00	54.00	X/H

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		Note
		Peak	AV		Peak	AV	Peak	AV	
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2390.00	H	22.54	13.64	34.16	56.70	47.80	74.00	54.00	X/E
2411.20	H	61.18	59.13	34.16	95.34	93.29			X/F
4824.00	H	38.37	28.20	6.43	44.80	34.63	74.00	54.00	X/H

Test Mode : TX B MODE 2437MHz

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		Note
		Peak	AV		Peak	AV	Peak	AV	
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2436.20	V	67.90	65.80	34.23	102.13	100.03			X/F
4874.00	V	41.02	30.21	6.58	47.60	36.79	74.00	54.00	X/H

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		Note
		Peak	AV		Peak	AV	Peak	AV	
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2438.00	H	60.49	58.32	34.23	94.72	92.55			X/F
4874.00	H	36.00	25.65	6.58	42.58	32.23	74.00	54.00	X/H



Test Mode : TX B MODE 2462MHz

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		Note
		Peak	AV		Peak	AV	Peak	AV	
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2463.00	V	67.52	65.51	34.31	101.83	99.82			X/F
2483.50	V	23.65	13.80	34.37	58.02	48.17	74.00	54.00	X/E
4924.00	V	43.49	35.27	6.72	50.21	41.99	74.00	54.00	X/H

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		Note
		Peak	AV		Peak	AV	Peak	AV	
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2463.80	H	57.59	55.35	34.31	91.90	89.66			X/F
2483.50	H	23.34	13.49	34.37	57.71	47.86	74.00	54.00	X/E
4924.00	H	36.15	28.27	6.72	42.87	34.99	74.00	54.00	X/H





TX CH01 (Above 1000 MHz, Vertical)







TX CH01 (Above 1000 MHz, Horizontal)







TX CH06 (Above 1000 MHz, Vertical)







TX CH06 (Above 1000 MHz, Horizontal)







TX CH11 (Above 1000 MHz, Vertical)





TX CH11 (Above 1000 MHz, Horizontal)





Test Mode : TX G MODE 2412MHz

Freq. (MHz)	Ant.Pol. H/V	Reading (dBuV)		Ant./CF CF(dB)	Act. (dBuV/m)		Limit (dBuV/m)		Note
		Peak	AV		Peak	AV	Peak	AV	
2390.00	V	25.68	15.80	34.09	59.77	49.89	74.00	54.00	X/E
2410.90	V	72.92	64.32	34.16	107.08	98.48			X/F
4824.00	V	36.56	27.14	6.43	42.99	33.57	74.00	54.00	X/H

Freq. (MHz)	Ant.Pol. H/V	Reading (dBuV)		Ant./CF CF(dB)	Act. (dBuV/m)		Limit (dBuV/m)		Note
		Peak	AV		Peak	AV	Peak	AV	
2390.00	H	22.44	14.08	34.09	56.53	48.17	74.00	54.00	X/E
2410.80	H	64.20	56.46	34.16	98.36	90.62			X/F
4824.00	H	32.56	23.50	6.43	38.99	29.93	74.00	54.00	X/H

Test Mode : TX G MODE 2437MHz

Freq. (MHz)	Ant.Pol. H/V	Reading (dBuV)		Ant./CF CF(dB)	Act. (dBuV/m)		Limit (dBuV/m)		Note
		Peak	AV		Peak	AV	Peak	AV	
2438.40	V	72.98	64.01	34.23	107.21	98.24			X/F
4874.00	V	43.85	39.50	27.14	6.58	66.64	74.00	54.00	X/H

Freq. (MHz)	Ant.Pol. H/V	Reading (dBuV)		Ant./CF CF(dB)	Act. (dBuV/m)		Limit (dBuV/m)		Note
		Peak	AV		Peak	AV	Peak	AV	
2435.90	H	61.88	51.83	34.22	96.10	86.05			X/F
4874.00	H	40.25	30.56	6.58	46.83	37.14	74.00	54.00	X/H



Test Mode : TX G MODE 2462MHz

Freq. (MHz)	Ant.Pol. H/V	Reading (dBuV)		Ant./CF CF(dB)	Act. (dBuV/m)		Limit (dBuV/m)		Note
		Peak	AV		Peak	AV	Peak	AV	
2463.20	V	72.21	62.27	34.29	106.50	96.56			X/F
2483.50	V	24.15	14.87	34.37	58.52	49.24	74.00	54.00	X/E
4924.00	V	39.28	30.65	6.70	45.98	37.35	74.00	54.00	X/H

Freq. (MHz)	Ant.Pol. H/V	Reading (dBuV)		Ant./CF CF(dB)	Act. (dBuV/m)		Limit (dBuV/m)		Note
		Peak	AV		Peak	AV	Peak	AV	
2457.30	H	63.24	53.20	34.29	97.53	87.49			X/F
2483.50	H	23.32	13.74	34.37	57.69	48.11	74.00	54.00	X/E
4924.00	H	38.21	29.35	6.70	44.91	36.05	74.00	54.00	X/H




TX CH01 (Above 1000 MHz, Vertical)






TX CH01 (Above 1000 MHz, Horizontal)

120.0 dBuV/m





80.0 dBm






TX CH06 (Above 1000 MHz, Vertical)






TX CH06 (Above 1000 MHz, Horizontal)

120.0 dBuV/m




80.0 dBm






TX CH11 (Above 1000 MHz, Vertical)

120.0 dBuV/m




80.0 dBm






TX CH11 (Above 1000 MHz, Horizontal)

120.0 dBuV/m



80.0 dBm





Test Mode : TX N-20M MODE 2412MHz

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		Note
		Peak	AV		Peak	AV	Peak	AV	
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2390.00	V	25.91	14.90	34.09	60.00	48.99	74.00	54.00	X/E
2410.00	V	71.42	61.38	34.16	105.58	95.54			X/F
4824.00	V	40.78	30.65	6.43	47.21	37.08	74.00	54.00	X/H

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		Note
		Peak	AV		Peak	AV	Peak	AV	
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2390.00	H	23.29	13.79	34.09	57.38	47.88	74.00	54.00	X/E
2406.30	H	62.58	52.25	34.14	96.72	86.39			X/F
4824.00	H	41.56	31.44	6.43	47.99	37.87	74.00	54.00	X/H

Test Mode : TX N-20M MODE 2437MHz

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		Note
		Peak	AV		Peak	AV	Peak	AV	
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2442.80	V	71.50	60.84	34.23	105.73	95.07			X/F
4874.00	V	42.65	33.45	6.58	49.23	40.03	74.00	54.00	X/H

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		Note
		Peak	AV		Peak	AV	Peak	AV	
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2440.20	H	60.45	49.72	34.23	94.68	83.95			X/F
4874.00	H	42.35	31.42	6.58	48.93	38.00	74.00	54.00	X/H



Test Mode : TX N-20M MODE 2462MHz

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		Note
		Peak	AV		Peak	AV	Peak	AV	
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2465.00	V	71.21	60.37	34.31	105.52	94.68			X/F
2483.50	V	25.00	14.63	34.37	59.37	49.00	74.00	54.00	X/E
4924.00	V	44.65	32.25	6.70	51.35	38.95	74.00	54.00	X/H

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		Note
		Peak	AV		Peak	AV	Peak	AV	
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2459.70	H	61.39	50.16	34.31	95.70	84.47			X/F
2483.50	H	23.66	13.62	34.37	58.03	47.99	74.00	54.00	X/E
4924.00	H	44.78	32.11	6.70	51.48	38.81	74.00	54.00	X/H




TX CH01 (Above 1000 MHz, Vertical)






TX CH01 (Above 1000 MHz, Horizontal)

120.0 dBuV/m




80.0 dBm






TX CH06 (Above 1000 MHz, Vertical)

120.0 dBuV/m




80.0 dBm






TX CH06 (Above 1000 MHz, Horizontal)

110.0 dBuV/m





80.0 dBm







TX CH11 (Above 1000 MHz, Vertical)





TX CH11 (Above 1000 MHz, Horizontal)





Test Mode : TX N-40M MODE 2422MHz

Freq. (MHz)	Ant.Pol. H/V	Reading (dBuV)		Ant./CF CF(dB)	Act. (dBuV/m)		Limit (dBuV/m)		Note
		Peak	AV		Peak	AV	Peak	AV	
2390.00	V	28.61	16.39	34.09	62.70	50.48	74.00	54.00	X/E
2431.20	V	67.34	55.27	34.21	101.55	89.48			X/F
4844.00	V	40.89	30.26	6.50	47.39	36.76	74.00	54.00	X/H

Freq. (MHz)	Ant.Pol. H/V	Reading (dBuV)		Ant./CF CF(dB)	Act. (dBuV/m)		Limit (dBuV/m)		Note
		Peak	AV		Peak	AV	Peak	AV	
2390.00	H	24.39	14.08	34.09	58.48	48.17	74.00	54.00	X/E
2416.00	H	59.36	46.64	34.17	93.53	80.81			X/F
4844.00	H	40.21	33.21	6.50	46.71	39.71	74.00	54.00	X/H

Test Mode : TX N-40M MODE 2437MHz

Freq. (MHz)	Ant.Pol. H/V	Reading (dBuV)		Ant./CF CF(dB)	Act. (dBuV/m)		Limit (dBuV/m)		Note
		Peak	AV		Peak	AV	Peak	AV	
2424.80	V	69.01	56.37	34.19	103.20	90.56			X/F
4874.00	V	40.17	31.25	6.58	46.75	37.83	74.00	54.00	X/H

Freq. (MHz)	Ant.Pol. H/V	Reading (dBuV)		Ant./CF CF(dB)	Act. (dBuV/m)		Limit (dBuV/m)		Note
		Peak	AV		Peak	AV	Peak	AV	
2421.00	H	60.74	47.57	34.18	94.92	81.75			X/F
4874.00	H	39.56	27.14	6.58	46.14	33.72	74.00	54.00	X/H



Test Mode : TX N-40M MODE 2452MHz

Freq. (MHz)	Ant.Pol. H/V	Reading (dBuV)		Ant./CF CF(dB)	Act. (dBuV/m)		Limit (dBuV/m)		Note
		Peak	AV		Peak	AV	Peak	AV	
2436.20	V	66.58	53.67	34.27	100.85	87.94			X/F
2483.50	V	25.47	14.99	34.37	59.84	49.36	74.00	54.00	X/E
4904.00	V	38.98	27.22	6.67	45.65	33.89	74.00	54.00	X/H

Freq. (MHz)	Ant.Pol. H/V	Reading (dBuV)		Ant./CF CF(dB)	Act. (dBuV/m)		Limit (dBuV/m)		Note
		Peak	AV		Peak	AV	Peak	AV	
2435.80	H	59.63	47.12	34.27	93.90	81.39			X/F
2483.50	H	23.59	13.79	34.37	57.96	48.16	74.00	54.00	X/E
4904.00	H	39.51	28.54	6.67	46.18	35.21	74.00	54.00	X/H





TX CH03 (Above 1000 MHz, Vertical)







TX CH03 (Above 1000 MHz, Horizontal)






TX CH06 (Above 1000 MHz, Vertical)






TX CH06 (Above 1000 MHz, Horizontal)

120.0 dBuV/m




80.0 dBm






TX CH09 (Above 1000 MHz, Vertical)

120.0 dBuV/m




80.0 dBm






TX CH09 (Above 1000 MHz, Horizontal)

120.0 dBuV/m



80.0 dBm





5. BANDWIDTH TEST

5.1 Applied procedures

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	2400-2483.5	PASS

5.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100KHz, VBW=300KHz, Sweep time = 2.5 ms.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.


5.1.5 EUT TEST CONDITIONS



Temperature: 25°C
Relative Humidity: 55%
Test Voltage: AC 120V/60Hz



5.1.6 TEST RESULTS


Test Mode : TX B Mode_CH01/06/11










Test Mode: TX G Mode_CH01/06/11










Test Mode : TX N-20MHz Mode_CH01/06/11









Test Mode : TX N-40MHz Mode_CH03/06/09







6. MAXIMUM OUTPUT POWER TEST

6.1 Applied procedures / limit

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Maximum Output Power	1 Watt or 30dBm	2400-2483.5	PASS

6.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the power meter and antenna output port as show in the block diagram below,
- b. The maximum peak conducted output power was performed in accordance with method 9.1.3 of FCC KDB 558074 D01 DTS Meas Guidance v03r01.

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing. Transmit output power was measured while the host equipment supply voltage was varied from 85 % to 115 % of the nominal rated supply voltage. No change in transmit output power was observed.

6.1.5 EUT TEST CONDITIONS

Temperature: 25°C
 Relative Humidity: 55%
 Test Voltage: AC 120V/60Hz



6.1.6 TEST RESULTS

Test Mode : TX B Mode

Test Channel	Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)	Limit (Watt)
CH01	2412	16.91	30	1
CH06	2437	16.52	30	1
CH11	2462	16.33	30	1

Test Mode : TX G Mode

Test Channel	Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)	Limit (Watt)
CH01	2412	17.35	30	1
CH06	2437	17.55	30	1
CH11	2462	17.51	30	1

Test Mode : TX N-20M Mode

Test Channel	Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)	Limit (Watt)
CH01	2412	18.91	30	1
CH06	2437	18.98	30	1
CH11	2462	18.99	30	1

Test Mode : TX N-40M Mode

Test Channel	Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)	Limit (Watt)
CH03	2422	19.01	30	1
CH06	2437	19.21	30	1
CH09	2452	19.18	30	1



7. ANTENNA CONDUCTED SPURIOUS EMISSION

7.1 Applied procedures / limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

7.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100KHz, VBW=300KHz, Sweep time = Auto.

7.1.2 DEVIATION FROM STANDARD

No deviation.

7.1.3 TEST SETUP



7.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

7.1.5 EUT TEST CONDITIONS

Temperature: 25°C
Relative Humidity: 55%
Test Voltage: AC 120V/60Hz



7.1.6 TEST RESULTS

Test Mode :	TX B Mode
-------------	-----------

