






EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name. :	WF2780
Temperature:	25 °C	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX N40 Mode /CH151, CH159		










EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name. :	WF2780
Temperature:	25 °C	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX AC 20 Mode /CH149, CH157, CH165		









EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name. :	WF2780
Temperature:	25 °C	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX AC 40 Mode /CH151, CH159		







EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name. :	WF2780
Temperature:	25 °C	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX AC 80 Mode /CH155		







**6. MAXIMUM OUTPUT POWER TEST**

**6.1 Applied procedures / limit**

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Maximum Output Power	1 watt or 30dBm	5725 - 5825	PASS

**6.1.1 MEASUREMENT INSTRUMENTS LIST**

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	P-series Power meter	Agilent	N1911A	MY45100473	Apr. 25, 2014
2	Wireband Power sensor	Agilent	N1921A	MY51100041	Apr. 25, 2014

Remark: "N/A" denotes no model name, serial no. or calibration specified.  
 All calibration period of Equipment List is One Year.

**6.1.2 TEST PROCEDURE**

- a. The EUT was directly connected to the power meter and antenna output port as show in the block diagram below,
- b. The maximum peak conducted output power was performed in accordance with method 9.1.3 of FCC KDB 558074 D01 DTS Meas Guidance v03r01(A,N20,N40 mode) and 662911 D01 Multiple Transmitter Output v01r02(N20,N40 mode)

**6.1.3 DEVIATION FROM STANDARD**

No deviation.

**6.1.4 TEST SETUP**



**6.1.5 EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.



**6.1.6 TEST RESULTS**

EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	25 °C	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX A Mode /CH149, CH157, CH165		

ANT 6				
Test Channel	Frequency (MHz)	Maximum Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
CH149	5745 MHz	12.89	30	1
CH157	5785 MHz	12.69	30	1
CH165	5825 MHz	12.45	30	1



EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	25 °C	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX N20 Mode /CH149, CH157, CH165		

ANT 6				
Test Channel	Frequency (MHz)	Maximum Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
CH149	5745 MHz	12.88	30	1
CH157	5785 MHz	12.71	30	1
CH165	5825 MHz	12.75	30	1

ANT 7				
Test Channel	Frequency (MHz)	Maximum Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
CH149	5745 MHz	12.71	30	1
CH157	5785 MHz	12.53	30	1
CH165	5825 MHz	12.83	30	1

ANT 6 + ANT 7				
Test Channel	Frequency (MHz)	Maximum Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
CH149	5745 MHz	15.81	30	1
CH157	5785 MHz	15.63	30	1
CH165	5825 MHz	15.80	30	1

Note: The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers (2T2R). All transmit signals are completely uncorrelated.



EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	25 °C	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX N40 Mode /CH151, CH159		

ANT 6				
Test Channel	Frequency (MHz)	Maximum Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
CH151	5755 MHz	12.64	30	1
CH159	5795 MHz	12.48	30	1

ANT 7				
Test Channel	Frequency (MHz)	Maximum Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
CH151	5755 MHz	12.72	30	1
CH159	5795 MHz	12.57	30	1

ANT 6 + ANT 7				
Test Channel	Frequency (MHz)	Maximum Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
CH151	5755 MHz	15.69	30	1
CH159	5795 MHz	15.54	30	1

Note: The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers (2T2R). all transmit signals are completely uncorrelated.



EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	25 °C	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX AC 20 Mode /CH149, CH157, CH165		

ANT 6				
Test Channel	Frequency (MHz)	Maximum Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
CH149	5745 MHz	12.88	30	1
CH157	5785 MHz	12.70	30	1
CH165	5825 MHz	12.51	30	1

ANT 7				
Test Channel	Frequency (MHz)	Maximum Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
CH149	5745 MHz	12.71	30	1
CH157	5785 MHz	12.53	30	1
CH165	5825 MHz	12.85	30	1

ANT 6 + ANT 7				
Test Channel	Frequency (MHz)	Maximum Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
CH149	5745 MHz	15.81	30	1
CH157	5785 MHz	15.63	30	1
CH165	5825 MHz	15.69	30	1

Note: The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers (2T2R). all transmit signals are completely uncorrelated.



## Neutron Engineering Inc.

EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	25 °C	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX AC 40 Mode /CH151, CH159		

ANT 6				
Test Channel	Frequency (MHz)	Maximum Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
CH151	5755 MHz	12.64	30	1
CH159	5795 MHz	12.48	30	1

ANT 7				
Test Channel	Frequency (MHz)	Maximum Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
CH151	5755 MHz	12.72	30	1
CH159	5795 MHz	12.57	30	1

ANT 6 + ANT 7				
Test Channel	Frequency (MHz)	Maximum Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
CH151	5755 MHz	15.69	30	1
CH159	5795 MHz	15.54	30	1

Note: The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers (2T2R). all transmit signals are completely uncorrelated.



## Neutron Engineering Inc.

EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	25 °C	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX AC 80 Mode /CH155		

ANT 6				
Test Channel	Frequency (MHz)	Maximum Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
CH155	5795 MHz	12.65	30	1

ANT 7				
Test Channel	Frequency (MHz)	Maximum Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
CH155	5795 MHz	12.42	30	1

ANT 6 + ANT 7				
Test Channel	Frequency (MHz)	Maximum Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
CH155	5755 MHz	15.55	30	1

Note: The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers (2T2R). all transmit signals are completely uncorrelated.



**7. ANTENNA CONDUCTED SPURIOUS EMISSION**

**7.1 Applied procedures / limit**

20dB in any 100 KHz bandwidth outside the operating frequency band, In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

**LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)**

Frequency (MHz)	(dBuV/m) (at 3 meters)	
	Peak	Average
Above 1000	74	54

**7.1.1 MEASUREMENT INSTRUMENTS LIST**

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov. 11, 2014

Remark: "N/A" denotes no model name, serial no. or calibration specified.  
All calibration period of Equipment List is One Year.

**7.1.2 TEST PROCEDURE**

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting : RBW= 100KHz, VBW=300KHz, Sweep time =20 ms.


**7.1.3 DEVIATION FROM STANDARD**

No deviation.





#### 7.1.4 TEST SETUP





#### 7.1.5 EUT OPERATION CONDITIONS



The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.







**7.1.6 TEST RESULTS**

EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	25 °C	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX A Mode /CH149, CH157, CH165		

















**Neutron Engineering Inc.**



EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	25 °C	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX N20Mode /CH149, CH157, CH165 / ANT 6		

















EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	25 °C	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX N20 Mode /CH149, CH157, CH165 / ANT 7		







Date: 26.MAR.2014 01:53:36



Date: 26.MAR.2014 02:02:39

















EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	25 °C	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX N40 Mode /CH151, CH159 / ANT 6		















**Neutron Engineering Inc.**

EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	25 °C	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX N40 Mode /CH151, CH159 / ANT 7		

















## Neutron Engineering Inc.

EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	25 °C	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX AC 20 Mode /CH149, CH157, CH165 / ANT 6		



















EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	25 °C	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX AC 20 Mode /CH149, CH157, CH165 / ANT 7		



















EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	25 °C	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX AC 40 Mode /CH151, CH159 / ANT 6		















**Neutron Engineering Inc.**

EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	25 °C	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX AC 40 Mode /CH151, CH159 / ANT 7		















EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	25 °C	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX AC 80 Mode /CH155 / ANT 6		









EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	25 °C	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX AC N80 Mode /CH155 / ANT 7		







**8. POWER SPECTRAL DENSITY TEST**

**8.1 Applied procedures / limit**

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(e)	Power Spectral Density	8 dBm (in any 3KHz)	5745 - 5825	PASS

**8.1.1 MEASUREMENT INSTRUMENTS LIST**

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov. 11, 2014

Remark: "N/A" denotes no model name, serial no. or calibration specified.  
 All calibration period of Equipment List is One Year.


**8.1.2 TEST PROCEDURE**

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting : RBW=3KHz, VBW=10KHz, Sweep time = auto.
- c. The power spectral density was performed in accordance with method 10.2 of FCC KDB 558074 D01 DTS Meas Guidance v03r01 (A, N20, N40 mode) and 662911 D01 Multiple Transmitter Output v01r02. (N20,N40 mode)

**8.1.3 DEVIATION FROM STANDARD**

No deviation.

**8.1.4 TEST SETUP**




**8.1.5 EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.





**8.1.6 TEST RESULTS**

EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	23 °C	Relative Humidity:	51 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX A Mode /CH149, CH157, CH165		













EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	23 °C	Relative Humidity:	51 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX N20 Mode /CH149, CH157, CH165 / ANT 6		









EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	23 °C	Relative Humidity:	51 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX N20 Mode /CH149, CH157, CH165 / ANT 7		








EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	23 °C	Relative Humidity:	51 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX N20 Mode /CH149, CH157, CH165		


ANT 6 + ANT 7			
Test Channel	Frequency (MHz)	Power Density (dBm)	LIMIT (dBm)
CH149	5745 MHz	-24.26	8
CH157	5785 MHz	-25.01	8
CH165	5825 MHz	-24.66	8

Note: The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers (2T2R). all transmit signals are completely uncorrelated.



EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	23 °C	Relative Humidity:	51 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX N40 Mode /CH151, CH159 / ANT 6		











EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	23 °C	Relative Humidity:	51 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX N40 Mode /CH151, CH159 / ANT 7		








EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	23 °C	Relative Humidity:	51 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX N40 Mode /CH151, CH159		



ANT 6+ANT 7			
Test Channel	Frequency (MHz)	Power Density (dBm)	LIMIT (dBm)
CH151	5755 MHz	-26.57	8
CH159	5795 MHz	-26.43	8

Note: The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers (2T2R). all transmit signals are completely uncorrelated.




EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	23 °C	Relative Humidity:	51 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX AC 20 Mode /CH149, CH157, CH165 / ANT 6		









EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	23 °C	Relative Humidity:	51 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX AC 20 Mode /CH149, CH157, CH165 / ANT 7		







EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	23 °C	Relative Humidity:	51 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX AC 20 Mode /CH149, CH157, CH165		


ANT 6 + ANT 7			
Test Channel	Frequency (MHz)	Power Density (dBm)	LIMIT (dBm)
CH149	5745 MHz	-24.64	8
CH157	5785 MHz	-25.26	8
CH165	5825 MHz	-25.70	8


Note: The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers (2T2R). all transmit signals are completely uncorrelated.






EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	23 °C	Relative Humidity:	51 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX AC 40 Mode /CH151, CH159 / ANT 6		








EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	23 °C	Relative Humidity:	51 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX AC 40 Mode /CH151, CH159 / ANT 7		








EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	23 °C	Relative Humidity:	51 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX AC 40 Mode /CH151, CH159		

ANT 6 + ANT 7			
Test Channel	Frequency (MHz)	Power Density (dBm)	LIMIT (dBm)
CH151	5755 MHz	-30.45	8
CH159	5795 MHz	-30.68	8

Note: The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers (2T2R). all transmit signals are completely uncorrelated.




EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	23 °C	Relative Humidity:	51 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX AC 80 Mode /CH155 / ANT 6		





EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	23 °C	Relative Humidity:	51 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX AC 80 Mode /CH155 / ANT 7		





EUT:	AC1200 Wireless Dual Band Gigabit Router	Model Name :	WF2780
Temperature:	23 °C	Relative Humidity:	51 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX AC 80 Mode /CH155		

ANT 6 + ANT 7			
Test Channel	Frequency (MHz)	Power Density (dBm)	LIMIT (dBm)
CH155	5775 MHz	-32.88	8

Note: The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers (2T2R). all transmit signals are completely uncorrelated.







**9. EUT TEST PHOTO**

**Conducted Measurement Photos**





**Radiated Measurement Photos  
30M~1000MHz**



**Radiated Measurement Photos  
Above 1000MHz**

