



## Maximum Permissible Exposure

### 1. Introduction

In this document, we try to prove the safety of radiation harmfulness to the human body for our product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The Gain of the antenna used in this product is measured in a Fully Anechoic Chamber (FAC) calibrated for antenna measurement in MLT, and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis transmission formula is a far field assumption, the calculated result of that is an over-prediction for near field power density. We will take that as the worst case to specify the safety range.

### 2. Description of EUT

EUT	: MODULE 802.11g Wireless Ethernet PCI card
Applicant	: March Networks Corporation Suite 530, Tower B 555 Legget Drive Kanata, ON K2K 2X3 CANADA
Manufacturer	: Gemtek Technology Co., Ltd. No.1 Jen-Ai Road, HsinChu Industrial Park, HuKou Hsiang, HsinChu Hsien,Taiwan, R.O.C.
Model No	: 17037
FCC ID	: T5L17037

### 3. Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance with the antenna should be included in users manual. So, this device is classified as Mobile Device.



# MAX LIGHT

## MEASUREMENT REPORT

2/2

### 4. Friis Formula

Friis transmission formula :  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

$P_d$  = power density in  $mW/cm^2$

$P_{out}$  = output power to antenna in Mw

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm

### 5. Test Result:

#### 802.11b

Max RF Power (dBm)	TX Antenna Gain (dBi)	Testing Result (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
17.11	3.0	0.0068	1

#### 802.11g

Max RF Power (dBm)	TX Antenna Gain (dBi)	Testing Result (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
13.46	3.0	0.0053	1

#### 802.11 Super g

Max RF Power (dBm)	TX Antenna Gain (dBi)	Testing Result (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
12.93	3.0	0.0051	1