



ANSI/IEEE Std. C95.1-1992

in accordance with the requirements of
FCC Report and Order: ET Docket 93-62



FCC TEST REPORT

For

Rugged Tablet PC

Trade Name: DAP

Model: M9020

Issued to

DAP Technologies LTD
4535 Boul. Wilfrid-Hamel,
Suite 100, Quebec

Issued by

Compliance Certification Services Inc.

No.11, Wugong 6th Rd., Wugu Dist.,
New Taipei City 24891,
Taiwan. (R.O.C.)

<http://www.ccsrf.com>

service@ccsrf.com

Issued Date: 2013/09/06



***Note:** This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.*



Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	2013/09/06	Initial Issue	ALL	Scott Hsu
01	2013/9/11	Revise Antenna Spec	6	Scott Hsu
02	2013/9/26	Revise Antenna Type	6	Scott Hsu
03	2013/10/17	Revise Highest Reported 1-g SAR of Column name, FCC Rule Parts, Simultaneous Transmission Check and Highest Reported SAR of Summary of Highest SAR Values.	6,18,115	Scott Hsu



Table Of Contents

1	Certificate of Compliance (SAR Evaluation)	5
2	Description of Equipment Under Test	6
3	Requirements for Compliance Testing Defined	7
3.1	Requirements for Compliance Testing Defined by the FCC	7
4	Dosimetric Assessment System	8
4.1	Measurement System Diagram	9
4.2	System Components	10
5	Evaluation Procedures	13
6	SAR Measurement Procedures	15
6.1	Normal SAR Test Procedure	15
7	Device Under Test	17
7.1	Band Interface	17
7.2	Simultaneous Transmission	18
8	Summary of Test Configurations	19
8.1	Body Test Exclusion Thresholds	19
8.2	Body Exposure Conditions for WWAN for Main Antenna	19
8.3	Body Exposure Conditions for WWAN for Aux Antenna	20
8.4	Body Exposure Conditions for Wi-Fi for Main Antenna	20
8.5	Body Exposure Conditions for Wi-Fi for Aux Antenna	20
9	KDB 941225 D05 SAR for LTE Devices V02	21
10	Measurement Uncertainty	25
11	Exposure Limit	26
12	Tissue Dielectric Properties	27
12.1	Test Liquid Confirmation	27
12.2	Typical Composition of Ingredients for Liquid Tissue Phantoms	28
12.3	Simulating Liquids Parameter Check Results	29
13	System Performance Check	31
13.1	System Performance Check Results	32
14	RF Output Power Measurement	33
14.1	GSM850	33
14.2	GPRS1900	34
14.3	WCDMA Band II	35
14.4	WCDMA Band IV	39
14.5	WCDMA Band V	43
14.6	CDMA BC0	47



14.7	CDMA BC 1	48
14.8	LTE Transmit Power	49
14.9	LTE Band 2	50
14.9.1	Spectrum Plots for the Test RB allocations	56
14.10	LTE Band 4	60
14.10.1	Spectrum Plots for the Test RB allocations	66
14.11	LTE Band 5	70
14.11.1	Spectrum Plots for the Test RB allocations	74
14.12	LTE Band 13	78
14.12.1	Spectrum Plots for the Test RB allocations	80
14.13	LTE Band 17	84
14.13.1	Spectrum Plots for the Test RB allocations	86
14.14	LTE Band 25	90
14.14.1	Spectrum Plots for the Test RB allocations	96
14.15	Wi-Fi (2.4 GHz Band)	100
14.16	Wi-Fi (5 GHz Band)	101
15	SAR Measurements Results	105
15.1	Summary of Highest SAR Values	115
16	Antenna Locations & Separation Distances	116
17	Schematic of Bumpers	117
18	Equipment List & Calibration Status	118
19	Facilities	119
20	Reference	119
21	Attachments	120



1 Certificate of Compliance (SAR Evaluation)

Applicant DAP Technologies LTD
4535 Boul. Wilfrid-Hamel, Suite 100, Quebec

Equipment Under Test: Rugged Tablet PC

Trade Name: DAP

Model Number: M9020

Date of Test: August 14 ~ September 5 , 2013

Device Category: PORTABLE DEVICES

Exposure Category: GENERAL POPULATION/UNCONTROLLED EXPOSURE

Applicable Standards	
FCC	<ul style="list-style-type: none"> ● IEEE 1528 2003 ● KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r01 ● KDB 447498 D01 General RF Exposure Guidance v05r01 ● KDB 616217 D04 SAR for laptop and tablets v01r01 ● KDB 248227 D01 SAR measurement for 802 11 a b g v01r02 ● KDB 941225 D05 SAR for LTE Devices v02r02
Limit	
1.6 W/kg	
Test Result	
Pass	

The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved by:

Alex Wu
Section Manager
Compliance Certification Services Inc.

Tested by:

Scott Hsu
SAR Engineer
Compliance Certification Services Inc.



2 DESCRIPTION OF EQUIPMENT UNDER TEST

Product		Rugged Tablet PC			
Trade Name		DAP			
Model Number		M9020			
Transmitters		GSM & UMTS & LTE			
		Wi-Fi & Bluetooth			
Modulation Technique		GPRS:GMSK			
		WCDMA:BPSK			
		CDMA:QPSK			
		LTE:QPSK/16QAM			
		802.11a: Orthogonal Frequency Division Multiplexing (OFDM)			
		802.11b: Direct Sequence Spread Spectrum(DSSS)			
		802.11g: Orthogonal Frequency Division Multiplexing (OFDM)			
Antenna Specification		WWAN	Brand name	Brito	
			Parts Number	397000300007	
			Type	MONOPILE	
		Note: The antenna specification are same between Main and Aux.			
		WLAN	Brand name	PENSON	
			Parts Number	Main:39700030000E	
				Aux:39700030000F	
Type	Dipole				
FCC Rule Parts	Band	Frequency Range	Highest Reported 1-g SAR		
22	GSM850	824 - 849 MHz	0.143 W/kg (Edge4)		
24	GSM1900	1850 - 1910 MHz	1.318 W/kg (Edge4)		
24	WCDMA Band II	1850 - 1910 MHz	1.310 W/kg (Edge4)		
27	WCDMA Band IV	1710 - 1755 MHz	0.920 W/kg (Edge4)		
22	WCDMA Band V	824 - 849 MHz	0.107 W/kg (Edge4)		
22	CDMA BC0	824 - 849 MHz	0.114 W/kg (Edge4)		
24	CDMA BC1	1850 - 1910 MHz	1.447 W/kg (Edge4)		
24	LTE Band 2	1850 - 1910 MHz	1.317 W/kg (Edge4)		
27	LTE Band 4	1710 - 1755 MHz	0.897 W/kg (Edge4)		
22	LTE Band 5	824 - 849 MHz	0.119 W/kg (Edge4)		
27	LTE Band 13	777 - 787 MHz	0.061 W/kg (Rear/Bottom)		
27	LTE Band 17	704 - 716 MHz	0.058 W/kg (Rear/Bottom)		
24	LTE Band 25	1850 - 1910 MHz	1.347 W/kg (Edge4)		
15.247	2.4GHz	2412 - 2462 MHz	0.983 W/kg (Edge1)		
	5.8GHz	5725 - 5850 MHz	1.184W/kg (Edge2)		
15.407	5.2GHz	5150 - 5250 MHz	0.504 W/kg (Rear/Bottom)		
	5.3GHz	5250 - 5350 MHz	0.616 W/kg (Rear/Bottom)		
	5.5GHz	5500 - 5700 MHz	0.876 W/kg (Edge2)		
Rechargeable Li-polymer Battery–alternate		Brand: DAP Model: M9020-BTR Rating: 7.4V 3100mAH			

Remark: The sample selected for test was prototype that approximated to production product and was provided by manufacturer



3 Requirements for Compliance Testing Defined

3.1 Requirements for Compliance Testing Defined by the FCC


The US Federal Communications Commission has released the report and order "Guidelines for Evaluating the Environmental Effects of RF Radiation", ET Docket No. 93-62 in August 1996 [1]. The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 W/kg for an uncontrolled environment and 8.0 mW/g for an occupational/controlled environment as recommended by the ANSI/IEEE standard C95.1-1992 [6].



4 Dosimetric Assessment System

These measurements were performed with the automated near-field scanning system DASY4/DAST5 from Schmid & Partner Engineering AG (SPEAG). The system is based on a high precision robot (working range greater than 0.9 m) which positions the probes with a positional repeatability of better than ± 0.02 mm. Special E- and H-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines to the data acquisition unit. The SAR measurements were conducted with the dosimetric probe EX3DV4-SN: 3665 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe has been calibrated according to the procedure with accuracy of better than $\pm 10\%$. The spherical isotropy was evaluated with the procedure and found to be better than ± 0.25 dB. The phantom used was the SAM Twin Phantom as described in FCC supplement C, IEEE 1528 2003.

4.1 Measurement System Diagram



The DASY4/DASY5 system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot (Stäubli RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to the DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows 2000 or Windows XP.
- DASY4/DASY5 software.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand and right-hand usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing validating the proper functioning of the system.



4.2 System Components

DASY4/DASY5 Measurement Server



The DASY4/DASY5 measurement server is based on a PC/104 CPU board with a 166MHz low-power Pentium, 32MB chip disk and 64MB RAM. The necessary circuits for communication with either the DAE3 electronic box as well as the 16-bit AD-converter system for optical detection and digital I/O interface are contained on the DASY4/DASY5 I/O-board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation.



The PC-operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with two expansion slots which are reserved for future applications. Please note that the expansion slots do not have a standardized pinout and therefore only the expansion cards provided by SPEAG can be inserted. Expansion cards from any other supplier could seriously damage the measurement server. Calibration: No calibration required.

Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE4) consists of a highly sensitive electrometer grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock. The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection. The input impedance of the DAE4 box is 200M Ω ; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



EX3DV4 Isotropic E-Field Probe for Dosimetric Measurements

- Construction:** Symmetrical design with triangular core
Built-in shielding against static charges
PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
- Calibration:** Basic Broad Band Calibration in air: 10-3000 MHz.
Conversion Factors (CF) for HSL 900 and HSL 1800
CF-Calibration for other liquids and frequencies upon request.
- Frequency:** 10 MHz to > 6 GHz; Linearity: ± 0.2 dB (30 MHz to 3 GHz)
- Directivity:** ± 0.3 dB in HSL (rotation around probe axis)
 ± 0.5 dB in HSL (rotation normal to probe axis)
- Dynamic Range:** 10 μ W/g to > 100 mW/g; Linearity: ± 0.2 dB
(noise: typically < 1 μ W/g)



REV. 05



Dimensions: Overall length: 330 mm (Tip: 20 mm)
Tip diameter: 2.5 mm (Body: 12 mm)
Distance from probe tip to dipole centers: 1 mm

Application: High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%.



Interior of probe


SAM Phantom (V4.0)

Construction: The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528-2003, CENELEC 50361 and IEC 62209. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot.

Shell Thickness: 2 ± 0.2 mm

Filling Volume: Approx. 25 liters

Dimensions: Height: 810mm; Length: 1000mm; Width: 500mm



SAM Phantom (ELI4)

Construction: Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with the latest draft of the standard IEC 62209 Part II and all known tissue simulating liquids. ELI4 has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is supported by software version DASY4/DASY5 and higher and is compatible with all SPEAG dosimetric probes and dipoles

Shell Thickness: 2.0 ± 0.2 mm (sagging: <1%)

Filling Volume: Approx. 25 liters

Dimensions: Major ellipse axis: 600 mm

Minor axis: 400 mm 500mm





Device Holder for SAM Twin Phantom

Construction: In combination with the Twin SAM Phantom V4.0 or Twin SAM, the Mounting Device (made from POM) enables the rotation of the mounted transmitter in spherical coordinates, whereby the rotation point is the ear opening. The devices can be easily and accurately positioned according to IEC, IEEE, CENELEC, FCC or other specifications. The device holder can be locked at different phantom locations (left head, right head, and flat phantom).



System Validation Kits for SAM Phantom (V4.0)

Construction: Symmetrical dipole with 1/4 balun Enables measurement of feedpoint impedance with NWA Matched for use near flat phantoms filled with brain simulating solutions Includes distance holder and tripod adaptor.

Frequency: 850, 1800, 1900, 2450, 5200, 5300, 5500, 5800 MHz

Return loss: > 20 dB at specified validation position

Power capability: > 100 W ($f < 1\text{GHz}$); > 40 W ($f > 1\text{GHz}$)

Dimensions: D835V2: dipole length: 161 mm; overall height: 340 mm
D1800V2: dipole length: 72.5 mm; overall height: 300 mm
D1900V2: dipole length: 67.7 mm; overall height: 300 mm
D2450V2: dipole length: 51.5 mm; overall height: 290 mm
D5GHzV2: dipole length: 20.6 mm; overall height: 300 mm



System Validation Kits for ELI4 phantom

Construction: Symmetrical dipole with 1/4 balun Enables measurement of feedpoint impedance with NWA Matched for use near flat phantoms filled with brain simulating solutions Includes distance holder and tripod adaptor.

Frequency: 850, 1800, 1900, 2450, 5200, 5300, 5500, 5800 MHz

Return loss: > 20 dB at specified validation position

Power capability: > 100 W ($f < 1\text{GHz}$); > 40 W ($f > 1\text{GHz}$)

Dimensions: D835V2: dipole length: 161 mm; overall height: 340 mm
D1800V2: dipole length: 72.5 mm; overall height: 300 mm
D1900V2: dipole length: 67.7 mm; overall height: 300 mm
D2450V2: dipole length: 51.5 mm; overall height: 290 mm
D5GHzV2: dipole length: 20.6 mm; overall height: 300 mm





5 Evaluation Procedures

Data Evaluation

The DASYS4/DASYS5 post processing software (SEMCAD) automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	$Norm_i, a_{i0}, a_{i1}, a_{i2}$
	- Conversion factor	$ConvF_i$
	- Diode compression point	dcp_i
Device parameters:	- Frequency	f
	- Crest factor	cf
Media parameters:	- Conductivity	σ
	- Density	ρ

These parameters must be set correctly in the software. They can be found in the component documents or be imported into the software from the configuration files issued for the DASYS components. In the direct measuring mode of the multi-meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

with	V_i	= Compensated signal of channel i	(i = x, y, z)
	U_i	= Input signal of channel i	(i = x, y, z)
	cf	= Crest factor of exciting field	(DASY parameter)
	dcp_i	= Diode compression point	(DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes:

$$E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$

H-field probes:

$$H_i = \sqrt{V_i} \cdot \frac{a_{i10} + a_{i11}f + a_{i12}f^2}{f}$$

with	V_i	= Compensated signal of channel i	(i = x, y, z)
	$Norm_i$	= Sensor sensitivity of channel i	(i = x, y, z)

$\mu V/(V/m)^2$ for E0field Probes

$ConvF$	= Sensitivity enhancement in solution
a_{ij}	= Sensor sensitivity factors for H-field probes
f	= Carrier frequency (GHz)
E_i	= Electric field strength of channel i in V/m
H_i	= Magnetic field strength of channel i in A/m



The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with

- SAR = local specific absorption rate in W/kg
- E_{tot} = total field strength in V/m
- σ = conductivity in [mho/m] or [Siemens/m]
- ρ = equivalent tissue density in g/cm³

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.

The power flow density is calculated assuming the excitation field as a free space field.

$$P_{pwe} = \frac{E_{tot}^2}{377} \quad \text{or} \quad P_{pwe} = H_{tot}^2 \cdot 37.7$$

with

- P_{pwe} = Equivalent power density of a plane wave in mW/cm²
- E_{tot} = total electric field strength in V/m
- H_{tot} = total magnetic field strength in A/m



6 SAR Measurement Procedures

6.1 Normal SAR Test Procedure

- **Power Reference Measurement**

The reference and drift jobs are useful jobs for monitoring the power drift of the device under test in the batch process. Both jobs measure the field at a specified reference position, at a selectable distance from the phantom surface. The reference position can be either the selected section's grid reference point or a user point in this section. The reference job projects the selected point onto the phantom surface, orients the probe perpendicularly to the surface, and approaches the surface using the selected detection method.

- **Area Scan**

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a finer measurement around the hot spot. The sophisticated interpolation routines implemented in DASY4/DASY5 software can find the maximum locations even in relatively coarse grids. The scan area is defined by an editable grid. This grid is anchored at the grid reference point of the selected section in the phantom. When the area scan's property sheet is brought-up, the grid resolution has to less than 15 mm by 15 mm at frequency $\leq 2\text{GHz}$; the grid resolution has to less than 12mm by 12 mm at frequency between 2GHz to 4GHz; grid resolution has to less than 10 mm by 10 mm at frequency between 4GHz to 6GHz.

According to KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r01

	$\leq 3 \text{ GHz}$	$> 3 \text{ GHz}$
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	$5 \pm 1 \text{ mm}$	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5 \text{ mm}$
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$	$\leq 2 \text{ GHz}: \leq 15 \text{ mm}$ $2 - 3 \text{ GHz}: \leq 12 \text{ mm}$	$3 - 4 \text{ GHz}: \leq 12 \text{ mm}$ $4 - 6 \text{ GHz}: \leq 10 \text{ mm}$
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be \leq the corresponding x or y dimension of the test device with at least one measurement point on the test device.	



- Zoom Scan**

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The default zoom scan measures points in accordance with the frequency can be divided into three parts. (1)The zoom scan volume was set to 5x5x7 points at frequency ≤ 2 GHz. (2) The zoom scan volume was set to 7x7x7 points at frequency between 2GHz to 4GHz (3) The zoom scan volume was set to 7x7x12 points at frequency between 4GHz to 6GHz. The measures points within a cube whose base faces are centered around the maximum found in a preceding area scan job within the same procedure. If the preceding Area Scan job indicates more than one maximum, the number of Zoom Scans has to be enlarged accordingly.

According to KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r01

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{Zoom}, \Delta y_{Zoom}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm	3 – 4 GHz: ≤ 5 mm 4 – 6 GHz: ≤ 4 mm
Maximum zoom scan spatial resolution, normal to phantom surface	Uniform grid: $\Delta z_{Zoom}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{Zoom}(1)$: between 1 st two points losest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Maximum zoom scan volume	x, y, z	≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm	

- Power Drift Measurement**

The drift job measures the field at the same location as the most recent reference job within the same procedure, and with the same settings. The drift measurement gives the field difference in dB from the reading conducted within the last reference measurement. Several drift measurements are possible for one reference measurement. This allows a user to monitor the power drift of the device under test within a batch process. In the properties of the Drift job, the user can specify a limit for the drift and have DASY4/DASY5 software stop the measurements if this limit is exceeded.

- Z-Scan**

The Z Scan job measures points along a vertical straight line. The line runs along the Z-axis of a one-dimensional grid. A user can anchor the grid to the current probe location. As with any other grids, the local Z-axis of the anchor location establishes the Z-axis of the grid.



7 Device Under Test

7.1 Band Interface

Tx Frequency Bands	<ul style="list-style-type: none">• GSM850: 824 - 849 MHz• GSM1900: 1850 - 1910 MHz• W-CDMA Band II: 1850 - 1910 MHz• W-CDMA Band IV: 1710 - 1755 MHz• W-CDMA Band V: 824 - 849 MHz• CDMA BC 0: 824 – 849 MHz• CDMA BC 1: 1850 – 1910 MHz• CDMA BC 10: 817.9 – 823.1 MHz• LTE Band 2: 1850 – 1910 MHz• LTE Band 4: 1710 – 1755 MHz• LTE Band 5: 824 – 849 MHz• LTE Band 13: 777 – 787 MHz• LTE Band 17: 704 – 716 MHz• LTE Band 25: 1850 – 1915 MHz• 802.11a/b/g/n: 2412 - 2462 MHz 5180 – 5825 MHz
Mode	<ul style="list-style-type: none">• GSM/GPRS/EGPRS• UMTS Rel 99• HSDPA (Rel 5, CAT 24)• HSUPA (Rel 6, CAT 7)• HSPA+ (Rel 7, CAT 7)• DC-HSPA+ (Rel 8, CAT 24)• LTE(Rel 8, CAT3)• 802.11a/b/g/n HT20/HT40



7.2 Simultaneous Transmission

No.	Conditions	Body SAR	Hotspot
1	GPRS850 + WiFi 2.4GHz	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
2	GPRS1900 + WiFi 2.4GHz	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
3	WCDMA Band V + WiFi 2.4GHz	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
4	WCDMA Band II + WiFi 2.4GHz	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
5	CDMA + WiFi 2.4GHz	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
6	LTE Band 2 + WiFi 2.4GHz	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
7	LTE Band 4 + WiFi 2.4GHz	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
8	LTE Band 5 + WiFi 2.4GHz	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
9	LTE Band 13 + WiFi 2.4GHz	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
10	LTE Band 17 + WiFi 2.4GHz	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
11	LTE Band 25 + WiFi 2.4GHz	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
12	GPRS850 + WiFi 5GHz	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
13	GPRS1900 + WiFi 5GHz	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
14	WCDMA Band V + WiFi 5GHz z	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
15	WCDMA Band II + WiFi 5GHz	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
16	CDMA + WiFi 5GHz	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
17	LTE Band 2 + WiFi 5GHz	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
18	LTE Band 4 + WiFi 5GHz	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
19	LTE Band 5 + WiFi 5GHz	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
20	LTE Band 13 + WiFi 5GHz	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
21	LTE Band 17 + WiFi 5GHz	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
22	LTE Band 25 + WiFi 5GHz	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

: The Product can simultaneously transmit

: The Product can't simultaneously transmit



8 Summary of Test Configurations

8.1 Body Test Exclusion Thresholds

The following SAR test exclusion Thresholds based on KDB 447498 D01 General RF Exposure Guidance v05r01) 4.3.1)

Band	Test Configurations	Antenna-to-edge/surface	Power Target (dBm)	Power Tolerance (dBm)	Calculate Power (mW)	Test Exclusion Power Threshold(mW)	SAR Required
GSM850	Edge 4	10.7mm	32	1	1995.26	35	Yes
GSM1900	Edge 4	10.7mm	29	1	1000	23	Yes
WCDMA Band II	Edge 4	10.7mm	23	1	251.18	24	Yes
WCDMA Band V	Edge 4	10.7mm	23	1	251.18	35	Yes
CDMA(BC0)	Edge 4	10.7mm	24	1	316.22	35	Yes
CDMA(BC1)	Edge 4	10.7mm	24	1	316.22	23	Yes
LTE Band 2	Edge 4	10.7mm	23	1	251.18	23	Yes
LTE Band 4	Edge 4	10.7mm	23	1	251.18	24	Yes
LTE Band 5	Edge 4	10.7mm	23	1	251.18	35	Yes
LTE Band 13	Edge 4	10.7mm	23	1	251.18	35	Yes
LTE Band 17	Edge 4	10.7mm	23	1	251.18	35	Yes
LTE Band 25	Edge 4	10.7mm	23	1	251.18	23	Yes
WiFi 2.4GHz	Edge 1	5.7mm	13.5	1.5	31.62	21	Yes
WiFi 5GHz	Edge 1	5.7mm	13.5	1.5	31.62	14	Yes

8.2 Body Exposure Conditions for WWAN for Main Antenna

Test Configurations	Antenna-to-edge/surface	SAR Required	Note
Front	5.8 mm	No	SAR is not required
Rear	35.4 mm	Yes	SAR is required
Edge 1	24.5 mm	No	This is not the most conservative antenna-to-user distance at edge mode
Edge 2	210.4 mm	No	This is not the most conservative antenna-to-user distance at edge mode
Edge 3	90 mm	No	This is not the most conservative antenna-to-user distance at edge mode
Edge 4	10.7 mm	Yes	This is most conservative antenna-to-user distance at edge mode



8.3 Body Exposure Conditions for WWAN for Aux Antenna

Test Configurations	Antenna-to-edge/surface	SAR Required	Note
Front	5.8 mm	No	The Antenna is used for receive only
Rear	35.4 mm	No	The Antenna is used for receive only
Edge 1	24.5 mm	No	The Antenna is used for receive only
Edge 2	7.1 mm	No	The Antenna is used for receive only
Edge 3	90 mm	No	The Antenna is used for receive only
Edge 4	214 mm	No	The Antenna is used for receive only

8.4 Body Exposure Conditions for Wi-Fi for Main Antenna

Test Configurations	Antenna-to-edge/surface	SAR Required	Note
Front	7.3 mm	No	SAR is not required
Rear	32 mm	Yes	SAR is required
Edge 1	5.7 mm	Yes	This is most conservative antenna-to-user distance at edge mode
Edge 2	92.2 mm	No	This is not the most conservative antenna-to-user distance at edge mode
Edge 3	164 mm	No	This is not the most conservative antenna-to-user distance at edge mode
Edge 4	92.2 mm	No	This is not the most conservative antenna-to-user distance at edge mode

8.5 Body Exposure Conditions for Wi-Fi for Aux Antenna

Test Configurations	Antenna-to-edge/surface	SAR Required	Note
Front	7.3 mm	No	SAR is not required
Rear	32 mm	Yes	SAR is required
Edge 1	123.3mm	No	This is not the most conservative antenna-to-user distance at edge mode
Edge 2	8.7 mm	Yes	This is most conservative antenna-to-user distance at edge mode
Edge 3	32.8 mm	No	This is not the most conservative antenna-to-user distance at edge mode
Edge 4	221.1mm	No	This is not the most conservative antenna-to-user distance at edge mode



9 KDB 941225 D05 SAR for LTE Devices V02

Item	Description	Information						
1	Identify the operating frequency range of each LTE transmission band used by the device	Band 2						
		TX:1850 – 1910 MHz						
		Band 4						
		TX:1710 – 1755 MHz						
		Band 5						
		TX:824 – 849 MHz						
		Band 13						
		TX:777 – 787 MHz						
		Band 17						
		TX:704 – 716 MHz						
2	Identify the channel bandwidths used in each LTE band; 1.4, 3, 5, 10, 15, 20 MHz etc.	Band 2						
		TX:1850 – 1915 MHz						
		Band 4						
		TX:1710 – 1755 MHz						
		Band 5						
		TX:824 – 849 MHz						
		Band 13						
		TX:777 – 787 MHz						
3	Identify the high, middle and low (H, M, L) channel numbers and channel frequencies for each LTE bandwidth and frequency band	Band 2						
		TX:1850 – 1915 MHz						
		Band 4						
		TX:1710 – 1755 MHz						
		Band 5						
		TX:824 – 849 MHz						
		Band 13						
		TX:777 – 787 MHz						
		Band 17						
		TX:704 – 716 MHz						
		Band 25						
		TX:1850 – 1915 MHz						
		Band	1.4MHz	3 MHz	5 MHz	10 MHz	15MHz	20 MHz
		Band2	✓	✓	✓	✓	✓	✓
		Band4	✓	✓	✓	✓	✓	✓
		Band5	✓	✓	✓	✓	✗	✗
		Band13	✗	✗	✓	✓	✗	✗
		Band17	✗	✗	✓	✓	✗	✗
		Band25	✓	✓	✓	✓	✓	✓
		Band 2	Channel Bandwidth					
			1.4MHz	3MHz	5MHz	10MHz	15MHz	20MHz
		Low	18607/ 1850.7	18615/ 1851.5	18625/ 1852.5	18650/ 1855	18675/ 1857.5	18700/ 1860
Mid	18900/1 1880	18900/1 880	18900/ 1880	18900/ 1880	18900/ 1880	18900/ 1880		
High	19192/ 1909.2	19184/ 1908.4	19175/1 907.5	19150/1 905	19125/ 1902.5	19100/ 1900		
Band 4	Channel Bandwidth							
	1.4MHz	3MHz	5MHz	10MHz	15MHz	20MHz		
Low	19957/ 1710.7	19965/1 711.5	19975/1 712.5	20000/ 1715	20025/ 1717.5	20050/ 1720		
Mid	20175/ 1732.5	20175/ 1732.5	20175/1 732.5	20175/ 1732.5	20175/ 1732.5	20175/ 1732.5		
High	20392/ 1754.2	20384/ 1753.4	20375/ 1752.5	20350/1 750	20325/ 1747.5	20300/ 1745		
Band 5	Channel Bandwidth							
	1.4MHz	3MHz	5MHz	10MHz	15MHz	20MHz		
Low	20407/ 824.7	20415/ 825.5	20425/ 826.5	20450/8 29				
Mid	20525/ 836.5	20525/ 836.5	20525/8 36.5	20525/ 836.5				
High	20642/ 848.2	20643/ 847.4	20625/ 846.5	20600/8 44				



KDB 941225 D05 SAR for LTE Devices V02 (Continued)

Item	Description	Information																																		
3	Identify the high, middle and low (H, M, L) channel numbers and channel frequencies for each LTE bandwidth and frequency band	<table border="1"> <thead> <tr> <th rowspan="2">Band 13</th> <th colspan="6">Channel Bandwidth</th> </tr> <tr> <th>1.4MHz</th> <th>3MHz</th> <th>5MHz</th> <th>10MHz</th> <th>15MHz</th> <th>20MHz</th> </tr> </thead> <tbody> <tr> <td>Low</td> <td></td> <td></td> <td>23205/ 779.5</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Mid</td> <td></td> <td></td> <td>23230/ 782</td> <td>23230/ 782</td> <td></td> <td></td> </tr> <tr> <td>High</td> <td></td> <td></td> <td>23255/ 784.5</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Band 13	Channel Bandwidth						1.4MHz	3MHz	5MHz	10MHz	15MHz	20MHz	Low			23205/ 779.5				Mid			23230/ 782	23230/ 782			High			23255/ 784.5			
		Band 13		Channel Bandwidth																																
			1.4MHz	3MHz	5MHz	10MHz	15MHz	20MHz																												
		Low			23205/ 779.5																															
		Mid			23230/ 782	23230/ 782																														
		High			23255/ 784.5																															
		<table border="1"> <thead> <tr> <th rowspan="2">Band 17</th> <th colspan="6">Channel Bandwidth</th> </tr> <tr> <th>1.4MHz</th> <th>3MHz</th> <th>5MHz</th> <th>10MHz</th> <th>15MHz</th> <th>20MHz</th> </tr> </thead> <tbody> <tr> <td>Low</td> <td></td> <td></td> <td>23755/ 706.5</td> <td>23780/ 709</td> <td></td> <td></td> </tr> <tr> <td>Mid</td> <td></td> <td></td> <td>23790/ 710</td> <td>23790/ 710</td> <td></td> <td></td> </tr> <tr> <td>High</td> <td></td> <td></td> <td>23825/ 713.5</td> <td>23800/ 711</td> <td></td> <td></td> </tr> </tbody> </table>	Band 17	Channel Bandwidth						1.4MHz	3MHz	5MHz	10MHz	15MHz	20MHz	Low			23755/ 706.5	23780/ 709			Mid			23790/ 710	23790/ 710			High			23825/ 713.5	23800/ 711		
		Band 17		Channel Bandwidth																																
			1.4MHz	3MHz	5MHz	10MHz	15MHz	20MHz																												
		Low			23755/ 706.5	23780/ 709																														
		Mid			23790/ 710	23790/ 710																														
		High			23825/ 713.5	23800/ 711																														
		<table border="1"> <thead> <tr> <th rowspan="2">Band 25</th> <th colspan="6">Channel Bandwidth</th> </tr> <tr> <th>1.4MHz</th> <th>3MHz</th> <th>5MHz</th> <th>10MHz</th> <th>15MHz</th> <th>20MHz</th> </tr> </thead> <tbody> <tr> <td>Low</td> <td>26047/ 1850.7</td> <td>26055/ 1851.5</td> <td>26065/ 1852.5</td> <td>26090/ 1855</td> <td>26115/ 1857.5</td> <td>26140/ 1860</td> </tr> <tr> <td>Mid</td> <td>26365/ 1882.5</td> <td>26365/ 1882.5</td> <td>26365/ 1882.5</td> <td>26365/ 1882.5</td> <td>26365/1 882.5</td> <td>26365/ 1882.5</td> </tr> <tr> <td>High</td> <td>26682/ 1914.2</td> <td>26674/ 1913.4</td> <td>26665/1 912.5</td> <td>26640/ 1910</td> <td>26615/1 907.5</td> <td>26590/ 1905</td> </tr> </tbody> </table>	Band 25	Channel Bandwidth						1.4MHz	3MHz	5MHz	10MHz	15MHz	20MHz	Low	26047/ 1850.7	26055/ 1851.5	26065/ 1852.5	26090/ 1855	26115/ 1857.5	26140/ 1860	Mid	26365/ 1882.5	26365/ 1882.5	26365/ 1882.5	26365/ 1882.5	26365/1 882.5	26365/ 1882.5	High	26682/ 1914.2	26674/ 1913.4	26665/1 912.5	26640/ 1910	26615/1 907.5	26590/ 1905
		Band 25		Channel Bandwidth																																
1.4MHz	3MHz		5MHz	10MHz	15MHz	20MHz																														
Low	26047/ 1850.7	26055/ 1851.5	26065/ 1852.5	26090/ 1855	26115/ 1857.5	26140/ 1860																														
Mid	26365/ 1882.5	26365/ 1882.5	26365/ 1882.5	26365/ 1882.5	26365/1 882.5	26365/ 1882.5																														
High	26682/ 1914.2	26674/ 1913.4	26665/1 912.5	26640/ 1910	26615/1 907.5	26590/ 1905																														
4	Specify the UE category and uplink modulations used	<p>UE Category: 3</p> <p>Uplink Modulations: QPSK, 16QAM</p>																																		
5	Descriptions of the LTE transmitter and antenna implementation; and also identify whether it is a standalone transmitter operating independently of other wireless transmitters in the device or sharing hardware components and/or antenna(s) with other transmitters etc	<ul style="list-style-type: none"> ● The Main antenna is used for LTE and other wireless modes (GPRS/EGPRS/UMTS/CDMA) for both Transmit and Receive. ● The Main antenna is used for LTE and other wireless modes (GPRS/EGPRS/UMTS/CDMA) for Receive only. 																																		
6	Identify the LTE voice/data requirements in each operating mode and exposure condition with respect to head and body test configurations, antenna locations, handset flip-cover or slide positions, antenna diversity conditions etc.	<p>Data only device.</p> <p>Exposure Conditions:</p> <ul style="list-style-type: none"> ● Body – Rear side, Edge 1, Edge 2, Edge 3, Edge 4 of DUT at separation distance of 0 cm from the flat phantom 																																		



KDB 941225 D05 SAR for LTE Devices V02 (Continued)

Item	Description	Information																																						
7	<p>Identify if Maximum Power Reduction(MPR) is implemented as an optional or permanent feature, i.e., built-in by design:</p> <ol style="list-style-type: none"> MPR may be considered during SAR testing only when the maximum output power is permanently limited by the MPR implemented within the device, according to the RB (resource block) configurations specified in 3GPP/LTE standards. Regardless of network requirements, only those RB configurations allowed (see 3GPP standards) for the channel bandwidth and modulation combinations may be tested with MPR active. Configurations with RB allocations less than the RB thresholds required by 3GPP must be tested without MPR. A-MPR (additional MPR) must be disabled during SAR testing. 	<p>As per 3GPP 36.101 v9.11.0 (2012-03), Release 9</p> <p>Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3</p> <table border="1" data-bbox="724 443 1426 607"> <thead> <tr> <th rowspan="2">Modulation</th> <th colspan="6">Channel bandwidth / Transmission bandwidth (N_{RB})</th> <th rowspan="2">MPR (dB)</th> </tr> <tr> <th>1.4 MHz</th> <th>3.0 MHz</th> <th>5 MHz</th> <th>10 MHz</th> <th>15 MHz</th> <th>20 MHz</th> </tr> </thead> <tbody> <tr> <td>QPSK</td> <td>> 5</td> <td>> 4</td> <td>> 8</td> <td>> 12</td> <td>> 16</td> <td>> 18</td> <td>≤ 1</td> </tr> <tr> <td>16 QAM</td> <td>≤ 5</td> <td>≤ 4</td> <td>≤ 8</td> <td>≤ 12</td> <td>≤ 16</td> <td>≤ 18</td> <td>≤ 1</td> </tr> <tr> <td>16 QAM</td> <td>> 5</td> <td>> 4</td> <td>> 8</td> <td>> 12</td> <td>> 16</td> <td>> 18</td> <td>≤ 2</td> </tr> </tbody> </table> <p>MPR is permanently built-in by design</p> <p>A-MPR was disabled</p>	Modulation	Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1	16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1	16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2
Modulation	Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)																																	
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz																																		
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1																																	
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1																																	
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2																																	
8	<p>When power reduction is required for one or more LTE modes to satisfy SAR compliance for simultaneous transmission or other equipment certification and operating requirements, maximum average conducted output power measurement results for each power reduction mode applicable to the simultaneous voice/data transmission configurations for such wireless configurations and frequency bands are required.</p>	<p>No.</p>																																						



KDB 941225 D05 SAR for LTE Devices V02 (Continued)

Item	Description	Information
9	Based on the design specifications and other information available to the manufacturer, through measurement and analysis during product development, when the maximum output power for different RB allocations and RB offset conditions within a channel bandwidth, modulation, or across the channels in a frequency band varies by more than 1 dB.	Refer to Section 14.
10	The maximum average conducted output power should be measured for the required test channels, for each channel bandwidth and uplink modulation, in each frequency band, using the following configurations to support the SAR test reduction and exclusion applied in the evaluation: <ol style="list-style-type: none">1. 100% RB allocation2. 1 RB and also 50% RB allocation, offset to the upper and lower edges of each required test channel and also to the middle of the channel bandwidth	Refer to Section 14.
11	Spectrum plots should be included in SAR reports to demonstrate the tested RB allocations have been established correctly at the maximum output power conditions.	Refer to Section 14.



10 Measurement Uncertainty

Measurement uncertainty for 300 MHz to 3 GHz averaged over 1 gram

Uncertainty Component	Uncertainty	Prob.	Div.	C_i (10g)	Std. Unc.(1-g)	V_i or V_{eff}
Measurement System						
Probe Calibration ($k=1$)	6.00	Normal	1	1	6.00	∞
Probe Isotropy	7.60	Rectangular	$\sqrt{3}$	0.7	3.07	∞
Boundary Effect	0.65	Rectangular	$\sqrt{3}$	1	0.38	∞
Linearity	4.70	Rectangular	$\sqrt{3}$	1	2.71	∞
System Detection Limit	1.00	Rectangular	$\sqrt{3}$	1	0.58	∞
Readout Electronics	0.30	Normal	1	1	0.30	∞
Response Time	0.80	Rectangular	$\sqrt{3}$	1	0.46	∞
Integration Time	2.60	Rectangular	$\sqrt{3}$	1	1.50	∞
RF Ambient Conditions	3.00	Rectangular	$\sqrt{3}$	1	1.73	∞
RF Ambient Reflections	3.00	Rectangular	$\sqrt{3}$	1	1.73	∞
Probe Positioner Mechanical Tolerance	0.40	Rectangular	$\sqrt{3}$	1	0.23	∞
Probe Positioning with respect to Phantom Shell	2.90	Rectangular	$\sqrt{3}$	1	1.67	∞
Extrapolation, interpolation and integration Algorithms for Max. SAR Evaluation	2.00	Rectangular	$\sqrt{3}$	1	1.15	∞
Test sample Related						
Test sample Positioning	3.70	Normal	1	1	3.7	89
Device Holder Uncertainty	3.40	Normal	1	1	3.4	5
Output Power Variation - SAR drift measurement	5.00	Rectangular	$\sqrt{3}$	1	2.89	∞
Phantom and Tissue Parameters						
Phantom Uncertainty (shape and thickness tolerances)	7.50	Rectangular	$\sqrt{3}$	1	4.33	∞
Liquid Conductivity - deviation from target values	4.14	Rectangular	$\sqrt{3}$	0.64	1.53	∞
Liquid Conductivity - measurement uncertainty	-4.28	Normal	1	0.64	-2.74	39
Liquid Permittivity - deviation from target values	3.92	Rectangular	$\sqrt{3}$	0.6	1.36	∞
Liquid Permittivity - measurement uncertainty	-4.29	Normal	1	0.6	-2.57	39
Temp. Unc. - Conductivity	1.70	Rectangular	$\sqrt{3}$	0.78	0.77	∞
Temp. Unc. - Permittivity	0.30	Rectangular	$\sqrt{3}$	0.23	0.04	∞
		RSS			11.72	611
Expanded Uncertainty U, Coverage Factor = 2, > 95 % Confidence =		$k=2$				23.43%
Expanded Uncertainty U, Coverage Factor = 2, > 95 % Confidence =		$k=2$				1.83dB

Measurement uncertainty for 3 to 6 GHz averaged over 1 gram

Uncertainty Component	Uncertainty	Prob.	Div.	C_i (10g)	Std. Unc.(1-g)	V_i or V_{eff}
Measurement System						
Probe Calibration ($k=1$)	6.55	Normal	1	1	6.55	∞
Probe Isotropy	7.60	Rectangular	$\sqrt{3}$	0.7	3.07	∞
Boundary Effect	2.00	Rectangular	$\sqrt{3}$	1	1.15	∞
Linearity	4.70	Rectangular	$\sqrt{3}$	1	2.71	∞
System Detection Limit	1.00	Rectangular	$\sqrt{3}$	1	0.58	∞
Readout Electronics	0.30	Normal	1	1	0.30	∞
Response Time	0.80	Rectangular	$\sqrt{3}$	1	0.46	∞
Integration Time	2.60	Rectangular	$\sqrt{3}$	1	1.50	∞
RF Ambient Conditions	3.00	Rectangular	$\sqrt{3}$	1	1.73	∞
RF Ambient Reflections	3.00	Rectangular	$\sqrt{3}$	1	1.73	∞
Probe Positioner Mechanical Tolerance	0.80	Rectangular	$\sqrt{3}$	1	0.46	∞
Probe Positioning with respect to Phantom Shell	6.70	Rectangular	$\sqrt{3}$	1	3.87	∞
Extrapolation, interpolation and integration Algorithms for Max. SAR Evaluation	4.00	Rectangular	$\sqrt{3}$	1	2.31	∞
Test sample Related						
Test sample Positioning	3.70	Normal	1	1	3.7	89
Device Holder Uncertainty	3.40	Normal	1	1	3.4	5
Output Power Variation - SAR drift measurement	5.00	Rectangular	$\sqrt{3}$	1	2.89	∞
Phantom and Tissue Parameters						
Phantom Uncertainty (shape and thickness tolerances)	7.90	Rectangular	$\sqrt{3}$	1	4.56	∞
Liquid Conductivity - deviation from target values	5.00	Rectangular	$\sqrt{3}$	0.64	1.85	∞
Liquid Conductivity - measurement uncertainty	-3.88	Normal	1	0.64	-2.48	39
Liquid Permittivity - deviation from target values	5.00	Rectangular	$\sqrt{3}$	0.6	1.73	∞
Liquid Permittivity - measurement uncertainty	-2.09	Normal	1	0.6	-1.25	39
Temp. Unc. - Conductivity	1.70	Rectangular	$\sqrt{3}$	0.78	0.77	∞
Temp. Unc. - Permittivity	0.30	Rectangular	$\sqrt{3}$	0.23	0.04	∞
		RSS			12.63	611
Expanded Uncertainty U, Coverage Factor = 2, > 95 % Confidence =		$k=2$				25.26%
Expanded Uncertainty U, Coverage Factor = 2, > 95 % Confidence =		$k=2$				1.96dB



11 Exposure Limit

(A). Limits for Occupational/Controlled Exposure (W/kg)

<u>Whole-Body</u>	<u>Partial-Body</u>	<u>Hands, Wrists, Feet and Ankles</u>
0.4	8.0	2.0

(B). Limits for General Population/Uncontrolled Exposure (W/kg)

<u>Whole-Body</u>	<u>Partial-Body</u>	<u>Hands, Wrists, Feet and Ankles</u>
0.08	1.6	4.0

NOTE: **Whole-Body SAR** is averaged over the entire body, **partial-body SAR** is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. **SAR for hands, wrists, feet and ankles** is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Population/Uncontrolled Environments:

are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Occupational/Controlled Environments:

are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

NOTE
GENERAL POPULATION/UNCONTROLLED EXPOSURE
PARTIAL BODY LIMIT
1.6 W/kg



12 Tissue Dielectric Properties

12.1 Test Liquid Confirmation

Simulating Liquids Parameter Check

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values

The relative permittivity and conductivity of the tissue material should be within $\pm 5\%$ of the values given in the table below. $\pm 5\%$ may not be easily achieved at certain frequencies.

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in IEEE 1528 2003 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in IEEE 1528 2003 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations and extrapolated according to the head parameters specified in IEEE 1528 2003

Target Frequency (MHz)	Head		Body	
	ϵ_r	σ (S/m)	ϵ_r	σ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800 – 2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5000	36.2	4.45	49.3	5.07
5100	36.1	4.55	49.1	5.18
5200	36.0	4.66	49.0	5.30
5300	35.9	4.76	48.9	5.42
5400	35.8	4.86	48.7	5.53
5500	35.6	4.96	48.6	5.65
5600	35.5	5.07	48.5	5.77
5700	35.4	5.17	48.3	5.88
5800	35.3	5.27	48.2	6.00



12.2 Typical Composition of Ingredients for Liquid Tissue Phantoms

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% by weight)	Frequency (MHz)									
	450		835		915		1900		2450	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	41.45	52.4	41.05	56.0	54.9	40.4	62.7	73.2
Salt (NaCl)	3.95	1.49	1.45	1.4	1.35	0.76	0.18	0.5	0.5	0.04
Sugar	56.32	46.78	56.0	45.0	56.5	41.76	0.0	58.0	0.0	0.0
HEC	0.98	0.52	1.0	1.0	1.0	1.21	0.0	1.0	0.0	0.0
Bactericide	0.19	0.05	0.1	0.1	0.1	0.27	0.0	0.1	0.0	0.0
Triton X-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	36.8	0.0
DGBE	0.0	0.0	0.0	0.0	0.0	0.0	44.92	0.0	0.0	26.7
Dielectric Constant	43.42	58.0	42.54	56.1	42.0	56.8	39.9	54.0	39.8	52.5
Conductivity (S/m)	0.85	0.83	0.91	0.95	1.0	1.07	1.42	1.45	1.88	1.78

alt: 99⁺% Pure Sodium Chloride

Sugar: 98⁺% Pure Sucrose

Water: De-ionized, 16 MΩ⁺ resistivity

HEC: Hydroxy thyl Cellulose

DGBE: 99⁺% Di(ethylene glycol) butyl ether, [2-(2-butoxyethoxy)ethanol]

Triton X-100 (ultra-pure): Polyethylene glycol mono [4-(1, 1, 3, 3-tetramethylbutyl)phenyl]ether

Simulating Liquids for 5 GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	78
Mineral oil	11
Emulsifiers	9
Additives and Salt	2



12.3 Simulating Liquids Parameter Check Results

Date	Band	Freq(MHz)	Measured			Standard		Δ		Limit
			e' (εr)	e''	σ	e' (εr)	σ	e' (εr)	σ	±5
2013/8/14	Body 900	824.2	55.27	21.09	0.97	55.24	0.97	0.05%	-0.35%	±5
		836.6	55.16	21.06	0.98	55.20	0.97	-0.07%	0.80%	±5
		848.8	55.02	21.03	0.99	55.16	0.99	-0.25%	0.57%	±5
2013/8/15	Body 1800	1712.4	52.83	15.21	1.45	53.53	1.46	-1.31%	-1.17%	±5
		1732.4	52.58	15.24	1.47	53.48	1.48	-1.69%	-0.69%	±5
		1752.6	52.64	15.35	1.49	53.43	1.49	-1.47%	0.31%	±5
2013/8/15	Body 1900	1850.2	51.62	14.19	1.46	53.30	1.52	-3.15%	-4.01%	±5
		1880	51.58	14.24	1.49	53.30	1.52	-3.22%	-2.12%	±5
		1909.8	51.39	14.23	1.51	53.30	1.52	-3.58%	-0.66%	±5
2013/8/16	Body 750	779.5	53.77	22.97	0.99	55.42	0.97	-2.98%	3.00%	±5
		782	53.77	22.91	1.00	55.41	0.97	-2.95%	3.04%	±5
		784.5	53.76	22.85	1.00	55.40	0.97	-2.95%	3.10%	±5
2013/8/16	Body 900	826.4	55.78	21.05	0.97	55.24	0.97	0.99%	-0.31%	±5
		836.6	55.68	21.02	0.98	55.20	0.97	0.88%	0.59%	±5
		846.6	55.59	20.99	0.99	55.17	0.98	0.76%	0.40%	±5
2013/8/19	Body 1800	1710.2	53.40	15.22	1.45	53.54	1.46	-0.26%	-1.20%	±5
		1747.6	53.34	15.21	1.48	53.44	1.49	-0.19%	-0.69%	±5
		1784.8	53.18	15.29	1.52	53.34	1.51	-0.31%	0.38%	±5
2013/8/20	Body 1900	1850.2	51.70	14.15	1.45	53.30	1.52	-3.01%	-4.29%	±5
		1880	51.61	14.21	1.48	53.30	1.52	-3.18%	-2.34%	±5
		1909.8	51.46	14.25	1.51	53.30	1.52	-3.46%	-0.52%	±5
2013/8/29	Body 2450	2412	50.58	14.18	1.90	52.75	1.91	-4.11%	-0.68%	±5
		2437	50.52	14.30	1.94	52.72	1.94	-4.16%	-0.11%	±5
		2442	50.51	14.31	1.94	52.71	1.94	-4.17%	-0.06%	±5
		2462	50.45	14.38	1.97	52.68	1.97	-4.24%	0.02%	±5
		2472	50.42	14.42	1.98	52.67	1.98	-4.28%	-0.04%	±5
2013/8/30	Body 5000	5180	49.07	17.68	5.09	49.07	5.25	0.01%	-3.13%	±5
		5200	49.07	17.67	5.10	49.04	5.28	0.05%	-3.28%	±5
		5300	48.94	17.76	5.23	48.88	5.41	0.12%	-3.33%	±5
		5500	48.69	17.98	5.49	48.64	5.62	0.10%	-2.29%	±5
		5600	48.50	18.07	5.62	48.47	5.76	0.07%	-2.38%	±5
		5700	48.37	18.15	5.75	48.33	5.88	0.08%	-2.24%	±5
		5800	48.25	18.24	5.88	48.23	5.97	0.03%	-1.55%	±5
2013/9/2	Body 5000	5825	48.25	18.23	5.90	48.20	6.00	0.09%	-1.66%	±5
		5180	49.49	18.07	5.20	49.07	5.25	0.86%	-1.02%	±5
		5200	49.52	18.07	5.22	49.04	5.28	0.97%	-1.07%	±5
		5300	49.31	18.15	5.34	48.88	5.41	0.88%	-1.23%	±5
		5500	49.02	18.32	5.60	48.64	5.62	0.78%	-0.44%	±5
		5600	48.86	18.44	5.74	48.47	5.76	0.80%	-0.41%	±5
		5700	48.71	18.57	5.88	48.33	5.88	0.79%	-0.02%	±5
5800	48.57	18.69	6.02	48.23	5.97	0.70%	0.86%	±5		
5825	48.60	18.68	6.05	48.20	6.00	0.84%	0.75%	±5		



Date	Band	Freq(MHz)	Measured			Standard		Δ		Limit
			e' (εr)	e''	σ	e' (εr)	σ	e' (εr)	σ	±5
2013/9/3	Body 5000	5180	48.38	18.50	5.32	49.07	5.25	-1.39%	1.33%	±5
		5200	48.29	18.49	5.34	49.04	5.28	-1.54%	1.22%	±5
		5300	48.18	18.61	5.48	48.88	5.41	-1.44%	1.28%	±5
		5500	47.88	18.96	5.79	48.64	5.62	-1.56%	3.00%	±5
		5600	47.60	19.07	5.93	48.47	5.76	-1.79%	3.00%	±5
		5700	47.40	19.12	6.05	48.33	5.88	-1.93%	2.96%	±5
		5800	47.23	19.18	6.18	48.23	5.97	-2.09%	3.50%	±5
		5825	47.22	19.23	6.22	48.20	6.00	-2.04%	3.73%	±5
2013/9/4	Body 5000	5180	48.49	17.59	5.06	49.07	5.25	-1.19%	-3.65%	±5
		5200	48.43	17.58	5.08	49.04	5.28	-1.25%	-3.77%	±5
		5300	48.33	17.66	5.20	48.88	5.41	-1.12%	-3.88%	±5
		5500	48.10	17.91	5.47	48.64	5.62	-1.11%	-2.70%	±5
		5600	47.88	17.98	5.59	48.47	5.76	-1.22%	-2.90%	±5
		5700	47.71	18.03	5.71	48.33	5.88	-1.29%	-2.92%	±5
		5800	47.59	18.08	5.82	48.23	5.97	-1.34%	-2.45%	±5
		5825	47.56	18.10	5.86	48.20	6.00	-1.32%	-2.40%	±5
2013/9/5	Body 5000	5180	48.62	17.78	5.12	49.07	5.25	-0.91%	-2.58%	±5
		5200	48.56	17.78	5.14	49.04	5.28	-0.99%	-2.63%	±5
		5300	48.46	17.87	5.26	48.88	5.41	-0.85%	-2.75%	±5
		5500	48.23	18.13	5.54	48.64	5.62	-0.84%	-1.51%	±5
		5600	48.01	18.20	5.66	48.47	5.76	-0.96%	-1.67%	±5
		5700	47.83	18.25	5.78	48.33	5.88	-1.04%	-1.70%	±5
		5800	47.71	18.31	5.90	48.23	5.97	-1.08%	-1.20%	±5
		5825	47.67	18.32	5.93	48.20	6.00	-1.09%	-1.19%	±5



13 System Performance Check

The system performance check is performed prior to any usage of the system in order to guarantee reproducible results. The system performance check verifies that the system operates within its specifications. The system performance check results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

System Performance Check Measurement Conditions

- The measurements were performed in the flat section of the SAM twin phantom filled with Body simulating liquid of the following parameters.
- The DASY4/DASY5 system with an E-field probe EX3DV4 SN:3665 was used for the measurements.
- The dipole was mounted on the small tripod so that the dipole feed point was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 15 mm (below 1 GHz) and 10 mm (above 1 GHz) from dipole center to the simulating liquid surface.
- The coarse grid with a grid spacing of 10mm was aligned with the dipole.
- Special 7x7x7 fine cube was chosen for cube integration (dx=dy= 5 mm, dz= 5 mm).
- Distance between probe sensors and phantom surface was set to 3.0 mm.
- The dipole input power (forward power) was 100 mW±3%.
- The results are normalized to 1 W input power.

Reference SAR Values for System Performance Check

The reference SAR values can be obtained from the calibration certificate of system validation dipoles

System Dipole	Serial No.	Cal. Date	Freq. (MHz)	Target SAR Values (W/kg)		
				1g/10g	Head	Body
D750V3	1020	10/26/2012	750	1g	8.37	8.75
				10g	5.53	5.78
D835V2	4d015	03/18/2013	850	1g	9.61	9.59
				10g	6.26	6.31
D1800V2	2d062	02/12/2013	1800	1g	38.7	38.5
				10g	20.3	20.3
D1900V2	5d056	02/13/2013	1900	1g	40.1	40.4
				10g	21.0	21.5
D2450V2	728	05/02/2012	2450	1g	53.5	51.1
				10g	25.0	23.9
D5GHzV2	1004	11/16/2012	5200	1g	77.8	71.8
				10g	22.1	20.1
D5GHzV2	1004	11/16/2012	5300	1g	83.9	75.4
				10g	24.0	21.2
D5GHzV2	1004	11/16/2012	5600	1g	83.3	78.8
				10g	23.6	21.8
D5GHzV2	1004	11/16/2012	5800	1g	79.8	73.5
				10g	22.7	20.4



13.1 System Performance Check Results

Date	System Dipole			Parameters	Target	Measured	Deviation[%]	Limited[%]
	Type	Serial No.	Liquid					
2013/8/14	D835V2	4d015	Body	1g SAR:	9.59	9.69	1.04	± 5
				10g SAR:	6.31	6.42	1.74	± 5
2013/8/15	D1800V2	2d062	Body	1g SAR:	38.50	38.60	0.26	± 5
				10g SAR:	20.30	20.40	0.49	± 5
2013/8/15	D1900V2	5d056	Body	1g SAR:	40.40	39.90	-1.24	± 5
				10g SAR:	21.50	21.20	-1.40	± 5
2013/8/16	D835V2	4d015	Body	1g SAR:	9.59	9.57	-0.21	± 5
				10g SAR:	6.31	6.34	0.48	± 5
2013/8/16	D750V3	1020	Body	1g SAR:	8.75	8.33	-4.80	± 5
				10g SAR:	5.78	5.55	-3.98	± 5
2013/8/19	D1800V2	2d062	Body	1g SAR:	38.50	39.10	1.56	± 5
				10g SAR:	20.30	20.70	1.97	± 5
2013/8/20	D1900V2	5d056	Body	1g SAR:	40.40	40.40	0.00	± 5
				10g SAR:	21.50	21.40	-0.47	± 5
2013/8/29	D2450V2	728	Body	1g SAR:	51.10	52.20	2.15	± 5
				10g SAR:	23.90	24.50	2.51	± 5
2013/8/30	D5GHzV2 (5.2GHz)	1004	Body	1g SAR:	71.80	74.00	3.06	± 5
				10g SAR:	20.10	21.00	4.48	± 5
2013/8/30	D5GHzV2 (5.3GHz)	1004	Body	1g SAR:	75.40	73.00	-3.18	± 5
				10g SAR:	21.20	20.70	-2.36	± 5
2013/9/2	D5GHzV2 (5.6GHz)	1004	Body	1g SAR:	78.80	77.30	-1.90	± 5
				10g SAR:	21.80	21.70	-0.46	± 5
2013/9/3	D5GHzV2 (5.6GHz)	1004	Body	1g SAR:	78.80	81.10	2.92	± 5
				10g SAR:	21.80	22.80	4.59	± 5
2013/9/4	D5GHzV2 (5.8GHz)	1004	Body	1g SAR:	73.50	72.10	-1.90	± 5
				10g SAR:	20.40	20.40	0.00	± 5
2013/9/5	D5GHzV2 (5.8GHz)	1004	Body	1g SAR:	73.50	71.10	-3.27	± 5
				10g SAR:	20.40	20.40	0.00	± 5



14 RF Output Power Measurement

14.1 GSM850

GMSK (GPRS) Mode Coding scheme : CS-1

Target Power: 32 dBm

Tolerance: +/- 1 dBm

Band	Slot	Channel No.	Frequency (MHz)	Average power(dBm)	Frame Avg Pwr
GPRS 850	1	128	824.2	32.1	23.1
		190	836.6	32.2	23.1
		251	848.8	32.1	23.1
GPRS 850	2	128	824.2	32.0	26.0
		190	836.6	32.1	26.0
		251	848.8	32.1	26.0

EGPRS850

8PSK (EGPRS) Mode Coding scheme : MCS-5

Target Power: 27 dBm

Tolerance: +/- 1 dBm

Band	Slot	Channel No.	Frequency (MHz)	Average power(dBm)	Frame Avg Pwr
EGPRS 850	1	128	824.2	26.9	17.9
		190	836.6	27.0	17.9
		251	848.8	27.0	18.0
EGPRS 850	2	128	824.2	26.7	20.7
		190	836.6	26.8	20.8
		251	848.8	26.8	20.8
EGPRS 850	3	128	824.2	26.6	22.3
		190	836.6	26.6	22.4
		251	848.8	26.7	22.4
EGPRS 850	4	128	824.2	26.4	23.4
		190	836.6	26.5	23.5
		251	848.8	26.5	23.5



14.2 GPRS1900

GMSK (GPRS) Mode Coding scheme : CS-1

Target Power: 29 dBm

Tolerance: +/- 1 dBm

Band	Slot	Channel No.	Frequency (MHz)	Average power(dBm)	Frame Avg Pwr
GPRS 1900	1	512	1850.2	29.6	20.6
		661	1880.0	29.4	20.4
		810	1909.8	29.5	20.4
GPRS 1900	2	512	1850.2	29.5	23.4
		661	1880.0	29.5	23.5
		810	1909.8	29.4	23.3

EGPRS1900

8PSK (EGPRS) Mode Coding scheme : MCS-5

Target Power: 26 dBm

Tolerance: +/- 1 dBm

Band	Slot	Channel No.	Frequency (MHz)	Average power(dBm)	Frame Avg Pwr
EGPRS 1900	1	512	1850.2	25.6	16.5
		661	1880.0	25.6	16.5
		810	1909.8	25.5	16.4
EGPRS 1900	2	512	1850.2	25.5	19.4
		661	1880.0	25.5	19.4
		810	1909.8	25.4	19.4
EGPRS 1900	3	512	1850.2	25.4	21.1
		661	1880.0	25.3	21.1
		810	1909.8	25.2	20.9
EGPRS 1900	4	512	1850.2	25.2	22.2
		661	1880.0	25.3	22.2
		810	1909.8	25.1	22.1



14.3 WCDMA Band II

Target Power: 23 dBm

Tolerance: +/- 1 dBm

Release 99

The following tests were completed according to the test requirements outlined in section 5.2 of the 3GPP TS34.121-1 V8.5.0 specification. The EUT supports power Class 3, which has a nominal maximum output power of 24 dBm (+1.7/-3.7) 12.2kps RMC is used for this testing. Power control set to All bits up. A summary of these settings are illustrated below:

Mode	Subtest	Rel99
WCDMA General Settings	Loopback Mode	Test Mode 1
	Rel99 RMC	12.2kbps RMC
	Power Control Algorithm	Algorithm2
	β_c/β_d	8/15

Output power table

Band	Data Rate or Sub-test	UL/DL Channel No.	Frequency(MHz)	Average power(dBm)
WCDMA Band II	---	9262/9662	1852.4	23.1
		9400/9800	1880.0	23.0
		9538/9983	1907.6	23.0



HSDPA

Target Power: 23 dBm

Tolerance: +/- 1 dBm

The following 4 Sub-tests were completed according to Release 6 procedures in section 5.2 of 3GPP TS34.121. A summary of these settings are illustrated below:

	Mode	HSDPA	HSDPA	HSDPA	HSDPA
	Subtest	1	2	3	4
W-CDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set1			
	Power Control Algorithm	Algorithm 2			
	β_c	2/15	12/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	Bd (SF)	64			
	β_c/β_d	2/15	12/15	8/15	4/15
	β_{hs}	4/15	24/15	30/15	30/15
	CM (dB)	0	1	1.5	1.5
HSDPA Specific Settings	D_{ACK}	8			
	D_{NAK}	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback (Table 5.2B.4)	4ms			
	CQI Repetition Factor (Table 5.2B.4)	2			
	$A_{hs} = \beta_{hs}/\beta_c$	30/15			

Output power table

Band	Data Rate or Sub-test	UL/DL Channel No.	Frequency(MHz)	Average power(dBm)
HSDPA II	1	9262/9662	1852.4	22.4
		9400/9800	1880.0	22.4
		9538/9983	1907.6	22.5
	2	9262/9662	1852.4	22.6
		9400/9800	1880.0	22.6
		9538/9983	1907.6	22.6
	3	9262/9662	1852.4	22.1
		9400/9800	1880.0	22.0
		9538/9983	1907.6	22.2
	4	9262/9662	1852.4	22.1
		9400/9800	1880.0	22.2
		9538/9983	1907.6	22.2



HSPA (HSDPA & HSUPA)

The following 5 Sub-tests were completed according to Release 6 procedures in section 5.2 of 3GPP TS34.121. A summary of these settings are illustrated below:

	Mode	HSPA	HSPA	HSPA	HSPA	HSPA
	Subtest	1	2	3	4	5
W-CDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2kbps RMC				
	HSDPA FRC	H-Set1				
	HSUPA Test	HSUPA Loopback				
	Power Control Algorithm	Algorithm2				
	β_c	11/15	6/15	15/15	2/15	15/15
	β_d	15/15	15/15	9/15	15/15	15/15
	β_{ec}	209/225	12/15	30/15	2/15	24/15
	β_c/β_d	11/15	6/15	9/15	2/15	15/15
	β_{hs}	22/15	12/15	30/15	4/15	30/15
	β_{ed}	1309/225	94/75	47/15	56/75	134/15
	CM (dB)	1	3	2	3	1
MPR (dB)	0	2	1	2	0	
HSDPA Specific Settings	DACK	8				
	DNAK	8				
	DCQI	8				
	Ack-nack repetition factor	3				
	CQI Feedback (Table 5.2B.4)	4ms				
	CQI Repetition Factor (Table 5.2B.4)	2				
	A _{hs} = β_{hs}/β_c	30/15				
HSUPA Specific Settings	D E-DPCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	AG Index	20	12	15	17	21
	ETFCI (from 34.121 Table C.11.1.3)	75	67	92	71	81
	Associated Max UL Data Rate kbps	242.1	174.9	482.8	205.8	308.9
	Reference E_TFCIs	E-TFCI 11	E-TFCI 11		E-TFCI 11	
		E-TFCI PO 4	E-TFCI PO 4		E-TFCI PO 4	
		E-TFCI 67	E-TFCI 92		E-TFCI 67	
		E-TFCI PO 18	E-TFCI PO 18		E-TFCI PO 18	
		E-TFCI 71			E-TFCI 71	
		E-TFCI PO 23			E-TFCI PO 23	
		E-TFCI 75			E-TFCI 75	
		E-TFCI PO 26			E-TFCI PO 26	
E-TFCI 81			E-TFCI 81			
E-TFCI PO 27			E-TFCI PO 27			



Output power table

Band	Data Rate or Sub-test	UL/DL Channel No.	Frequency(MHz)	Average power(dBm)
HSUPA II	1	9262/9662	1852.4	22.1
		9400/9800	1880.0	22.4
		9538/9983	1907.6	22.4
	2	9262/9662	1852.4	20.6
		9400/9800	1880.0	20.4
		9538/9983	1907.6	20.7
	3	9262/9662	1852.4	21.5
		9400/9800	1880.0	21.8
		9538/9983	1907.6	21.4
	4	9262/9662	1852.4	21.3
		9400/9800	1880.0	21.5
		9538/9983	1907.6	21.4
	5	9262/9662	1852.4	22.5
		9400/9800	1880.0	22.5
		9538/9983	1907.6	22.5



14.4 WCDMA Band IV

Target Power: 23dBm

Tolerance: +/- 1 dBm

Release 99

The following tests were completed according to the test requirements outlined in section 5.2 of the 3GPP TS34.121-1 V8.5.0 specification. The EUT supports power Class 3, which has a nominal maximum output power of 24 dBm (+1.7/-3.7) 12.2kps RMC is used for this testing. Power control set to All bits up. A summary of these settings are illustrated below:

Mode	Subtest	Rel99
WCDMA General Settings	Loopback Mode	Test Mode 1
	Rel99 RMC	12.2kbps RMC
	Power Control Algorithm	Algorithm2
	β_c/β_d	8/15

Output power table

Band	Data Rate or Sub-test	UL/DL Channel No.	Frequency(MHz)	Average power(dBm)
WCDMA Band V	---	1312/1537	1712.4	22.9
		1413/1638	1732.6	22.8
		1513/1738	1752.6	23.0



HSDPA

Target Power: 23dBm

Tolerance: +/- 1 dBm

The following 4 Sub-tests were completed according to Release 6 procedures in section 5.2 of 3GPP TS34.121. A summary of these settings are illustrated below:

	Mode	HSDPA	HSDPA	HSDPA	HSDPA
	Subtest	1	2	3	4
W-CDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set1			
	Power Control Algorithm	Algorithm 2			
	β_c	2/15	12/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	Bd (SF)	64			
	β_c/β_d	2/15	12/15	8/15	4/15
	β_{hs}	4/15	24/15	30/15	30/15
	CM (dB)	0	1	1.5	1.5
HSDPA Specific Settings	D_{ACK}	8			
	D_{NAK}	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback (Table 5.2B.4)	4ms			
	CQI Repetition Factor (Table 5.2B.4)	2			
	$A_{hs} = \beta_{hs}/\beta_c$	30/15			

Output power table

Band	Data Rate or Sub-test	UL/DL Channel No.	Frequency(MHz)	Average power(dBm)
HSDPA IV	1	1312/1537	1712.4	22.7
		1413/1638	1732.6	22.6
		1513/1738	1752.6	22.7
	2	1312/1537	1712.4	22.8
		1413/1638	1732.6	22.7
		1513/1738	1752.6	22.7
	3	1312/1537	1712.4	22.2
		1413/1638	1732.6	22.1
		1513/1738	1752.6	22.1
	4	1312/1537	1712.4	21.9
		1413/1638	1732.6	22.0
		1513/1738	1752.6	22.2



HSPA (HSDPA & HSUPA)

The following 5 Sub-tests were completed according to Release 6 procedures in section 5.2 of 3GPP TS34.121. A summary of these settings are illustrated below:

	Mode	HSPA	HSPA	HSPA	HSPA	HSPA
	Subtest	1	2	3	4	5
W-CDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2kbps RMC				
	HSDPA FRC	H-Set1				
	HSUPA Test	HSUPA Loopback				
	Power Control Algorithm	Algorithm2				
	β_c	11/15	6/15	15/15	2/15	15/15
	β_d	15/15	15/15	9/15	15/15	15/15
	β_{ec}	209/225	12/15	30/15	2/15	24/15
	β_c/β_d	11/15	6/15	9/15	2/15	15/15
	β_{hs}	22/15	12/15	30/15	4/15	30/15
	β_{ed}	1309/225	94/75	47/15	56/75	134/15
	CM (dB)	1	3	2	3	1
MPR (dB)	0	2	1	2	0	
HSDPA Specific Settings	DACK	8				
	DNAK	8				
	DCQI	8				
	Ack-nack repetition factor	3				
	CQI Feedback (Table 5.2B.4)	4ms				
	CQI Repetition Factor (Table 5.2B.4)	2				
	A _{hs} = β_{hs}/β_c	30/15				
HSUPA Specific Settings	D E-DPCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	AG Index	20	12	15	17	21
	ETFCI (from 34.121 Table C.11.1.3)	75	67	92	71	81
	Associated Max UL Data Rate kbps	242.1	174.9	482.8	205.8	308.9
	Reference E_TFCIs	E-TFCI 11	E-TFCI 11		E-TFCI 11	
		E-TFCI PO 4	E-TFCI PO 4		E-TFCI PO 4	
		E-TFCI 67	E-TFCI 92		E-TFCI 67	
		E-TFCI PO 18	E-TFCI PO 18		E-TFCI PO 18	
		E-TFCI 71			E-TFCI 71	
		E-TFCI PO 23			E-TFCI PO 23	
		E-TFCI 75			E-TFCI 75	
		E-TFCI PO 26			E-TFCI PO 26	
E-TFCI 81			E-TFCI 81			
E-TFCI PO 27			E-TFCI PO 27			



Output power table

Band	Data Rate or Sub-test	UL/DL Channel No.	Frequency(MHz)	Average power(dBm)
HSUPA IV	1	1312/1537	1712.4	22.1
		1413/1638	1732.6	22.4
		1513/1738	1752.6	22.3
	2	1312/1537	1712.4	20.5
		1413/1638	1732.6	20.6
		1513/1738	1752.6	20.3
	3	1312/1537	1712.4	21.7
		1413/1638	1732.6	21.3
		1513/1738	1752.6	21.7
	4	1312/1537	1712.4	21.6
		1413/1638	1732.6	21.3
		1513/1738	1752.6	21.5
	5	1312/1537	1712.4	22.3
		1413/1638	1732.6	22.4
		1513/1738	1752.6	22.6



14.5 WCDMA Band V

Target Power: 23dBm

Tolerance: +/- 1 dBm

Release 99

The following tests were completed according to the test requirements outlined in section 5.2 of the 3GPP TS34.121-1 V8.5.0 specification. The EUT supports power Class 3, which has a nominal maximum output power of 24 dBm (+1.7/-3.7) 12.2kps RMC is used for this testing. Power control set to All bits up. A summary of these settings are illustrated below:

Mode	Subtest	Rel99
WCDMA General Settings	Loopback Mode	Test Mode 1
	Rel99 RMC	12.2kbps RMC
	Power Control Algorithm	Algorithm2
	β_c/β_d	8/15

Output power table

Band	Data Rate or Sub-test	UL/DL Channel No.	Frequency(MHz)	Average power(dBm)
WCDMA Band V	---	4132/4157	826.4	22.8
		4182/4407	836.4	22.8
		4233/4458	846.6	22.9



HSDPA

Target Power: 23dBm

Tolerance: +/- 1 dBm

The following 4 Sub-tests were completed according to Release 6 procedures in section 5.2 of 3GPP TS34.121. A summary of these settings are illustrated below:

	Mode	HSDPA	HSDPA	HSDPA	HSDPA
	Subtest	1	2	3	4
W-CDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set1			
	Power Control Algorithm	Algorithm 2			
	β_c	2/15	12/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	Bd (SF)	64			
	β_c/β_d	2/15	12/15	8/15	4/15
	β_{hs}	4/15	24/15	30/15	30/15
	CM (dB)	0	1	1.5	1.5
HSDPA Specific Settings	D_{ACK}	8			
	D_{NAK}	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback (Table 5.2B.4)	4ms			
	CQI Repetition Factor (Table 5.2B.4)	2			
	$A_{hs} = \beta_{hs}/\beta_c$	30/15			

Output power table

Band	Data Rate or Sub-test	UL/DL Channel No.	Frequency(MHz)	Average power(dBm)
HSDPA V	1	4132/4157	826.4	22.3
		4182/4407	836.4	22.2
		4233/4458	846.6	22.2
	2	4132/4157	826.4	22.3
		4182/4407	836.4	22.2
		4233/4458	846.6	22.2
	3	4132/4157	826.4	21.8
		4182/4407	836.4	21.7
		4233/4458	846.6	21.8
	4	4132/4157	826.4	21.8
		4182/4407	836.4	21.7
		4233/4458	846.6	21.7



HSPA (HSDPA & HSUPA)

The following 5 Sub-tests were completed according to Release 6 procedures in section 5.2 of 3GPP TS34.121. A summary of these settings are illustrated below:

	Mode	HSPA	HSPA	HSPA	HSPA	HSPA
	Subtest	1	2	3	4	5
W-CDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2kbps RMC				
	HSDPA FRC	H-Set1				
	HSUPA Test	HSUPA Loopback				
	Power Control Algorithm	Algorithm2				
	β_c	11/15	6/15	15/15	2/15	15/15
	β_d	15/15	15/15	9/15	15/15	15/15
	β_{ec}	209/225	12/15	30/15	2/15	24/15
	β_c/β_d	11/15	6/15	9/15	2/15	15/15
	β_{hs}	22/15	12/15	30/15	4/15	30/15
	β_{ed}	1309/225	94/75	47/15	56/75	134/15
	CM (dB)	1	3	2	3	1
MPR (dB)	0	2	1	2	0	
HSDPA Specific Settings	DACK	8				
	DNAK	8				
	DCQI	8				
	Ack-nack repetition factor	3				
	CQI Feedback (Table 5.2B.4)	4ms				
	CQI Repetition Factor (Table 5.2B.4)	2				
	A _{hs} = β_{hs}/β_c	30/15				
HSUPA Specific Settings	D E-DPCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	AG Index	20	12	15	17	21
	ETFCI (from 34.121 Table C.11.1.3)	75	67	92	71	81
	Associated Max UL Data Rate kbps	242.1	174.9	482.8	205.8	308.9
	Reference E_TFCIs	E-TFCI 11	E-TFCI 11		E-TFCI 11	
		E-TFCI PO 4	E-TFCI PO 4		E-TFCI PO 4	
		E-TFCI 67	E-TFCI 92		E-TFCI 67	
		E-TFCI PO 18	E-TFCI PO 18		E-TFCI PO 18	
		E-TFCI 71			E-TFCI 71	
		E-TFCI PO 23			E-TFCI PO 23	
		E-TFCI 75			E-TFCI 75	
		E-TFCI PO 26			E-TFCI PO 26	
	E-TFCI 81			E-TFCI 81		
E-TFCI PO 27			E-TFCI PO 27			



Output power table

Band	Data Rate or Sub-test	UL/DL Channel No.	Frequency(MHz)	Average power(dBm)
HSUPA V	1	4132/4157	826.4	22.1
		4182/4407	836.4	22.2
		4233/4458	846.6	22.2
	2	4132/4157	826.4	20.5
		4182/4407	836.4	20.1
		4233/4458	846.6	20.1
	3	4132/4157	826.4	21.3
		4182/4407	836.4	21.0
		4233/4458	846.6	21.1
	4	4132/4157	826.4	21.5
		4182/4407	836.4	21.1
		4233/4458	846.6	21.2
	5	4132/4157	826.4	22.5
		4182/4407	836.4	22.2
		4233/4458	846.6	22.3



14.6 CDMA BC0

1xRTT

Target Power: 24dBm

Tolerance: +/- 1 dBm

This procedure assumes the Agilent 8960 Test Set has the following applications installed and with valid license.

<u>Application</u>	<u>Rev, License</u>
CDMA2000 Mobile Test	B.13.08, L

- Call Setup > Shift & Preset
- Cell Info > Cell Parameters > System ID (SID) > 387 for BC0
> Network ID (NID) > 65535
- Protocol Rev > 6 (IS-2000-0)
- Radio Config (RC) > Please see following table or details
- FCH Service Option (SO) Setup > Please see following table or details
- Traffic Data Rate > Full
- TDSO SCH Info > F-SCH Parameters > F-SCH Data Rate > 153.6 kbps
> R-SCH Parameters > R-SCH Data Rate > 153.6 kbps
- Rvs Power Ctrl > Active bits
- Rvs Power Ctrl > All Up bits (Maximum TxPout)

Output power table

Band	Mode	UL/DL Channel No.	Frequency(MHz)	Average power(dBm)
BC0	RC1 SO55 (Loopback)	1013	824.70	24.2
		384	836.52	24.4
		777	848.31	24.0
	RC3 SO55 (Loopback)	1013	824.70	24.1
		384	836.52	24.3
		777	848.31	23.7
	RC3 SO32 ((+F-SCH))	1013	824.70	24.1
		384	836.52	24.3
		777	848.31	23.9



14.7 CDMA BC 1

1xRTT

Target Power: 24dBm 、 23.5dBm(channel:1175)

Tolerance: +/- 1 dBm

This procedure assumes the Agilent 8960 Test Set has the following applications installed and with valid license.

Application Rev, License
CDMA2000 Mobile Test B.13.08, L

- Call Setup > Shift & Preset
● Cell Info > Cell Parameters > System ID (SID) > 387 for BC1
> Network ID (NID) > 65535
● Protocol Rev > 6 (IS-2000-0)
● Radio Config (RC) > Please see following table or details
● FCH Service Option (SO) Setup > Please see following table or details
● Traffic Data Rate > Full
● TDSO SCH Info > F-SCH Parameters > F-SCH Data Rate > 153.6 kbps
> R-SCH Parameters > R-SCH Data Rate > 153.6 kbps
● Rvs Power Ctrl > Active bits
● Rvs Power Ctrl > All Up bits (Maximum TxPout)

Output power table

Table with 5 columns: Band, Mode, UL/DL Channel No., Frequency(MHz), Average power(dBm). Rows include BC1 with modes RC1 SO55 (Loopback) and RC3 SO55 (Loopback) and RC3 SO32 ((+F-SCH)) across channel numbers 25, 600, and 1175.



14.8 LTE Transmit Power

The following tests were conducted according to the test requirements outlined in section 6.2 of the 3GPP TS36.101 specification.

UE Power Class: 3 (23 +/- 1dBm). The allowed Maximum Power Reduction (MPR) for the maximum output power due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1 of the 3GPP TS36.101.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3

Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

The allowed A-MPR values specified below in Table 6.2.4.-1 of 3GPP TS36.101 are in addition to the allowed MPR requirements. All the measurements below were performed with A-MPR disabled, by using Network Signaling Value of "NS_01".

Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)

Network Signalling value	Requirements (sub-clause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks (N_{RB})	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.5-1	1.4, 3, 5, 10, 15, 20	Table 5.6-1	NA
NS_03	6.6.2.2.1	2, 4, 10, 23, 25, 35, 36	3	>5	≤ 1
			5	>6	≤ 1
			10	>6	≤ 1
			15	>8	≤ 1
			20	>10	≤ 1
NS_04	6.6.2.2.2	41	5	>6	≤ 1
			10, 15, 20	See Table 6.2.4-4	
NS_05	6.6.3.3.1	1	10,15,20	≥ 50	≤ 1
NS_06	6.6.2.2.3	12, 13, 14, 17	1.4, 3, 5, 10	Table 5.6-1	n/a
NS_07	6.6.2.2.3	13	10	Table 6.2.4-2	Table 6.2.4-2
	6.6.3.3.2				
NS_08	6.6.3.3.3	19	10, 15	> 44	≤ 3
NS_09	6.6.3.3.4	21	10, 15	> 40	≤ 1
				> 55	≤ 2
NS_10		20	15, 20	Table 6.2.4-3	Table 6.2.4-3
NS_11	6.6.2.2.1	23 ¹	1.4, 3, 5, 10	Table 6.2.4-5	Table 6.2.4-5
..					
NS_32	-	-	-	-	-

Note 1: Applies to the lower block of Band 23, i.e. a carrier placed in the 2000-2010 MHz region.



14.9 LTE Band 2

Output power table

Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average power(dBm)		
2	20	18700	1860.0	QPSK	1	0	0	23.0		
					1	49	0	23.1		
					1	99	0	22.8		
					50	0	1	22.4		
					50	24	1	22.3		
					50	49	1	22.3		
				16QAM	100	0	1	22.3		
					1	0	1	22.2		
					1	49	1	22.1		
					1	99	1	22.1		
					50	0	2	21.1		
					50	24	2	21.2		
		18900	1880.0	QPSK	1880.0	QPSK	1	0	0	23.1
							1	49	0	22.9
							1	99	0	22.7
							50	0	1	22.6
							50	24	1	22.4
							50	49	1	22.3
				16QAM	100	0	1	22.2		
					1	0	1	22.2		
					1	49	1	22.2		
					1	99	1	22.3		
					50	0	2	21.6		
					50	24	2	21.2		
		19100	1900.0	QPSK	1900.0	QPSK	50	49	2	21.1
							100	0	2	21.1
							1	0	0	22.9
							1	49	0	23.1
							1	99	0	23.1
							50	0	1	22.4
16QAM	50			24	1	22.3				
	50			49	1	22.3				
	100			0	1	22.1				
	1			0	1	22.1				
	1			49	1	22.2				
	1			99	1	22.3				
50	0	2	21.1							
50	24	2	21.1							
50	49	2	21.1							
100	0	2	21.0							



Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average power(dBm)
2	15	18675	1857.5	QPSK	1	0	0	23.0
					1	37	0	23.1
					1	74	0	23.0
					36	0	1	22.1
					36	18	1	22.4
					36	35	1	22.3
					75	0	1	22.1
				16QAM	1	0	1	22.1
					1	37	1	22.3
					1	74	1	22.1
					36	0	2	21.1
					36	18	2	21.1
					36	35	2	21.2
					75	0	2	21.1
		18900	1880.0	QPSK	1	0	0	23.4
					1	37	0	22.9
					1	74	0	22.8
					36	0	1	22.6
					36	18	1	22.5
					36	35	1	22.5
					75	0	1	22.4
				16QAM	1	0	1	22.7
					1	37	1	22.6
					1	74	1	22.5
					36	0	2	21.5
					36	18	2	21.5
					36	35	2	21.5
					75	0	2	21.4
		19125	1902.5	QPSK	1	0	0	22.9
					1	37	0	23.2
1	74				0	23.2		
36	0				1	22.1		
36	18				1	22.0		
36	35				1	22.0		
75	0				1	22.1		
16QAM	1			0	1	22.0		
	1			37	1	22.4		
	1			74	1	22.4		
	36			0	2	21.1		
	36			18	2	21.0		
	36			35	2	21.1		
	75			0	2	21.0		



Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average power(dBm)
2	10	18650	1855.0	QPSK	1	0	0	23.0
					1	24	0	23.1
					1	49	0	23.1
					25	0	1	22.1
					25	12	1	22.0
					25	24	1	22.1
				16QAM	50	0	1	22.0
					1	0	1	22.0
					1	24	1	22.2
					1	49	1	22.2
					25	0	2	21.2
					25	12	2	21.1
					25	24	2	21.1
					50	0	2	21.0
		18900	1880.0	QPSK	1	0	0	23.5
					1	24	0	23.4
					1	49	0	23.4
					25	0	1	22.8
					25	12	1	22.8
					25	24	1	22.7
				16QAM	50	0	1	22.7
					1	0	1	22.8
					1	24	1	22.8
					1	49	1	22.7
					25	0	2	21.8
					25	12	2	21.9
					25	24	2	21.8
					50	0	2	21.7
		19150	1905.0	QPSK	1	0	0	23.0
					1	24	0	23.1
1	49				0	23.2		
25	0				1	22.1		
25	12				1	22.0		
25	24				1	22.0		
16QAM	50			0	1	22.0		
	1			0	1	22.1		
	1			24	1	22.2		
	1			49	1	22.2		
	25			0	2	21.0		
	25			12	2	21.1		
	25			24	2	21.1		
	50			0	2	21.1		



Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average power(dBm)
2	5	18625	1852.5	QPSK	1	0	0	23.1
					1	12	0	23.2
					1	24	0	23.1
					12	0	1	22.1
					12	6	1	22.1
					12	11	1	22.2
					25	0	1	22.1
				16QAM	1	0	1	22.2
					1	12	1	22.3
					1	24	1	22.2
					12	0	2	21.3
					12	6	2	21.3
					12	11	2	21.3
					25	0	2	21.2
		18900	1880.0	QPSK	1	0	0	23.6
					1	12	0	23.1
					1	24	0	22.9
					12	0	1	22.8
					12	6	1	22.7
					12	11	1	22.7
					25	0	1	22.6
				16QAM	1	0	1	22.7
					1	12	1	22.3
					1	24	1	22.1
					12	0	2	21.7
					12	6	2	21.7
					12	11	2	21.6
					25	0	2	21.6
		19175	1907.5	QPSK	1	0	0	23.1
					1	12	0	23.1
1	24				0	23.2		
12	0				1	22.2		
12	6				1	22.2		
12	11				1	22.2		
25	0				1	22.1		
16QAM	1			0	1	22.0		
	1			12	1	22.4		
	1			24	1	22.3		
	12			0	2	21.2		
	12			6	2	21.2		
	12			11	2	21.2		
	25			0	2	21.1		



Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average power(dBm)
2	3	18615	1851.5	QPSK	1	0	0	23.0
					1	7	0	23.1
					1	14	0	23.0
					8	0	1	22.1
					8	4	1	22.0
					8	7	1	22.1
				15	0	1	22.0	
				16QAM	1	0	1	22.1
					1	7	1	22.2
					1	14	1	22.1
					8	0	2	21.1
					8	4	2	21.1
					8	7	2	21.1
				15	0	2	21.1	
				18900	1880.0	QPSK	1	0
		1	7				0	23.1
		1	14				0	22.9
		8	0				1	22.5
		8	4				1	22.4
		8	7				1	22.4
		15	0			1	22.3	
		16QAM	1			0	1	22.3
			1			7	1	22.3
			1			14	1	22.2
			8			0	2	21.2
			8			4	2	21.4
			8			7	2	21.3
		15	0			2	21.3	
		19184	1908.4			QPSK	1	0
				1	7		0	23.2
1	14			0	23.2			
8	0			1	22.1			
8	4			1	22.2			
8	7			1	22.3			
15	0			1	22.2			
16QAM	1			0	1	22.2		
	1			7	1	22.3		
	1			14	1	22.3		
	8			0	2	21.2		
	8			4	2	21.2		
	8			7	2	21.3		
15	0			2	21.2			




Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average power(dBm)
2	1.4	18607	1850.7	QPSK	1	0	0	22.7
					1	2	0	22.7
					1	5	0	22.8
					3	0	1	22.7
					3	1	1	22.7
					3	2	1	22.7
				16QAM	6	0	1	21.7
					1	0	1	21.9
					1	2	1	21.8
					1	5	1	21.8
					3	0	2	21.8
					3	1	2	21.7
					3	2	2	21.7
					6	0	2	20.8
		18900	1880.0	QPSK	1	0	0	22.7
					1	2	0	22.7
					1	5	0	22.8
					3	0	1	22.7
					3	1	1	22.6
					3	2	1	22.6
				16QAM	6	0	1	21.7
					1	0	1	21.9
					1	2	1	21.8
					1	5	1	21.9
					3	0	2	21.7
					3	1	2	21.7
		19192	1909.2	QPSK	3	2	2	21.7
					3	2	2	21.7
					6	0	2	20.7
					1	0	0	22.9
1	2				0	23.0		
1	5				0	23.1		
3	0				1	22.8		
16QAM	3			1	1	22.9		
	3			2	1	22.9		
	6			0	1	22.0		
	1			0	1	21.9		
	1			2	1	22.0		
	1			5	1	22.0		
	3			0	2	21.8		
3	1	2	21.8					
3	2	2	21.8					
6	0	2	21.0					




14.9.1 Spectrum Plots for the Test RB allocations

20MHz Band Width: Ch 18900, RB Size=1; RB Offset = 0




20MHz Band Width: Ch 18900, RB Size=1; RB Offset = 49






20MHz Band Width: Ch 18900, RB Size=1; RB Offset = 99




20MHz Band Width: Ch 18900, RB Size=50; RB Offset = 0






20MHz Band Width: Ch 18900, RB Size=50; RB Offset = 24




20MHz Band Width: Ch 18900, RB Size=50; RB Offset = 49





20MHz Band Width: Ch 18900, RB Size=100; RB Offset = 0





14.10 LTE Band 4

Output power table

Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average power(dBm)		
4	20	20050	1720.0	QPSK	1	0	0	23.7		
					1	49	0	23.5		
					1	99	0	23.6		
					50	0	1	23.0		
					50	24	1	22.7		
					50	49	1	22.7		
				16QAM	100	0	1	22.7		
					1	0	1	22.7		
					1	49	1	22.8		
					1	99	1	22.7		
					50	0	2	21.8		
					50	24	2	21.7		
		20175	1732.5	QPSK	1732.5	QPSK	50	49	2	21.7
							100	0	2	21.7
							1	0	0	23.8
							1	49	0	23.8
							1	99	0	23.8
							50	0	1	22.9
				16QAM	50	24	1	22.9		
					50	49	1	22.9		
					100	0	1	23.1		
					1	0	1	23.0		
					1	49	1	23.0		
					1	99	1	22.8		
20300	1745.0	QPSK	1745.0	QPSK	50	0	2	21.9		
					50	24	2	21.9		
					50	49	2	21.9		
					100	0	2	21.8		
					1	0	0	23.9		
					1	49	0	23.8		
		16QAM	1	99	0	23.5				
			50	0	1	22.9				
			50	24	1	22.9				
			50	49	1	22.9				
			100	0	1	23.0				
			1	0	1	22.8				
16QAM	1	49	1	22.8						
	1	99	1	22.4						
	50	0	2	22.0						
	50	24	2	21.9						
	50	49	2	21.9						
	100	0	2	22.0						



Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average power(dBm)	
4	15	20025	1717.5	QPSK	1	0	0	23.4	
					1	37	0	23.6	
					1	74	0	23.4	
					36	0	1	22.5	
					36	18	1	22.6	
					36	35	1	22.5	
				16QAM	75	0	1	22.5	
					1	0	1	22.6	
					1	37	1	22.5	
					1	74	1	22.5	
					36	0	2	21.5	
					36	18	2	21.6	
		20175	1732.5	QPSK	1732.5	36	35	2	21.5
						75	0	2	21.5
						1	0	0	23.7
						1	37	0	23.8
						1	74	0	23.7
						36	0	1	22.7
				16QAM	36	18	1	22.7	
					36	35	1	22.7	
					75	0	1	22.7	
					1	0	1	22.6	
					1	37	1	22.7	
					1	74	1	22.8	
		20325	1747.5	QPSK	1747.5	36	0	2	21.8
						36	18	2	21.7
						36	35	2	21.7
						75	0	2	21.7
						1	0	0	23.8
						1	37	0	23.7
				16QAM	1	74	0	23.6	
					36	0	1	22.9	
					36	18	1	22.8	
					36	35	1	22.8	
					75	0	1	22.8	
					1	0	1	22.9	
16QAM	1	37	1	23.9					
	1	74	1	22.8					
	36	0	2	21.9					
	36	18	2	21.8					
	36	35	2	21.8					
	75	0	2	21.8					



Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average power(dBm)
4	10	20000	1715.0	QPSK	1	0	0	23.4
					1	24	0	23.5
					1	49	0	23.5
					25	0	1	22.5
					25	12	1	22.5
					25	24	1	22.5
					50	0	1	22.4
				16QAM	1	0	1	22.6
					1	24	1	22.6
					1	49	1	22.5
					25	0	2	21.5
					25	12	2	21.5
					25	24	2	21.5
					50	0	2	21.4
		20175	1732.5	QPSK	1	0	0	23.6
					1	24	0	23.7
					1	49	0	23.6
					25	0	1	22.7
					25	12	1	22.7
					25	24	1	22.6
					50	0	1	22.6
				16QAM	1	0	1	22.8
					1	24	1	22.8
					1	49	1	22.8
					25	0	2	21.6
					25	12	2	21.7
					25	24	2	21.7
					50	0	2	21.6
		20350	1750.0	QPSK	1	0	0	23.6
					1	24	0	23.7
1	49				0	23.5		
25	0				1	22.7		
25	12				1	22.7		
25	24				1	22.7		
50	0				1	22.7		
16QAM	1			0	1	22.9		
	1			24	1	22.8		
	1			49	1	22.6		
	25			0	2	21.7		
	25			12	2	21.7		
	25			24	2	21.8		
	50			0	2	21.7		



Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average power(dBm)
4	5	19975	1712.5	QPSK	1	0	0	23.6
					1	12	0	23.6
					1	24	0	23.6
					12	0	1	22.6
					12	6	1	22.6
					12	11	1	22.7
					25	0	1	22.6
				16QAM	1	0	1	22.7
					1	12	1	22.7
					1	24	1	22.7
					12	0	2	21.6
					12	6	2	22.6
					12	11	2	22.6
					25	0	2	22.6
		20175	1732.5	QPSK	1	0	0	23.6
					1	12	0	23.7
					1	24	0	23.7
					12	0	1	22.7
					12	6	1	22.7
					12	11	1	22.6
					25	0	1	22.6
				16QAM	1	0	1	22.7
					1	12	1	22.7
					1	24	1	22.8
					12	0	2	21.8
					12	6	2	21.8
					12	11	2	21.8
					25	0	2	21.7
		20375	1752.5	QPSK	1	0	0	23.7
					1	12	0	23.8
1	24				0	23.6		
12	0				1	22.8		
12	6				1	22.9		
12	11				1	22.8		
25	0				1	22.7		
16QAM	1			0	1	22.8		
	1			12	1	22.8		
	1			24	1	22.7		
	12			0	2	21.7		
	12			6	2	21.7		
	12			11	2	21.7		
	25			0	2	21.7		



Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average power(dBm)
4	3	19965	1711.5	QPSK	1	0	0	23.6
					1	7	0	23.6
					1	14	0	23.6
					8	0	1	22.7
					8	4	1	22.7
					8	7	1	22.7
					15	0	1	22.6
				16QAM	1	0	1	22.6
					1	7	1	22.8
					1	14	1	22.7
					8	0	2	21.8
					8	4	2	21.7
					8	7	2	21.6
					15	0	2	21.6
					20175	1732.5	QPSK	1
		1	7	0				23.8
		1	14	0				23.8
		8	0	1				22.8
		8	4	1				22.8
		8	7	1				22.8
		15	0	1				22.7
		16QAM	1	0			1	22.7
			1	7			1	22.8
			1	14			1	22.8
			8	0			2	21.7
			8	4			2	21.7
			8	7			2	21.8
			15	0			2	21.8
			20384	1753.4			QPSK	1
		1			7	0		23.7
1	14	0			23.7			
8	0	1			22.8			
8	4	1			22.8			
8	7	1			22.8			
15	0	1			22.7			
16QAM	1	0			1	22.6		
	1	7			1	22.6		
	1	14			1	22.5		
	8	0			2	21.8		
	8	4			2	21.7		
	8	7			2	21.8		
	15	0			2	21.8		
	15	0			2	21.8		




Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average power(dBm)
4	1.4	19957	1710.7	QPSK	1	0	0	23.5
					1	2	0	23.5
					1	5	0	23.5
					3	0	1	23.3
					3	1	1	23.3
					3	2	1	23.4
					6	0	1	22.5
				16QAM	1	0	1	22.6
					1	2	1	22.6
					1	5	1	22.7
					3	0	2	22.4
					3	1	2	22.2
					3	2	2	22.4
					6	0	2	21.6
		20175	1732.5	QPSK	1	0	0	23.6
					1	2	0	23.6
					1	5	0	23.7
					3	0	1	23.3
					3	1	1	23.4
					3	2	1	23.4
					6	0	1	22.7
				16QAM	1	0	1	22.8
					1	2	1	22.8
					1	5	1	22.7
					3	0	2	22.3
					3	1	2	22.4
					3	2	2	22.4
					6	0	2	21.9
		20392	1754.2	QPSK	1	0	0	23.5
					1	2	0	23.4
1	5				0	23.4		
3	0				1	23.3		
3	1				1	23.3		
3	2				1	23.3		
6	0				1	22.6		
16QAM	1			0	1	22.5		
	1			2	1	22.5		
	1			5	1	22.5		
	3			0	2	22.4		
	3			1	2	22.4		
	3			2	2	22.2		
	6			0	2	21.6		




14.10.1 Spectrum Plots for the Test RB allocations

20MHz Band Width: Ch 20175, RB Size=1; RB Offset = 0




20MHz Band Width: Ch 20175, RB Size=1; RB Offset = 49






20MHz Band Width: Ch 20175, RB Size=1; RB Offset = 99




20MHz Band Width: Ch 20175, RB Size=50; RB Offset = 0






20MHz Band Width: Ch 20175, RB Size=50; RB Offset = 24




20MHz Band Width: Ch 20175, RB Size=50; RB Offset = 49





20MHz Band Width: Ch 20175, RB Size=100; RB Offset = 0





14.11 LTE Band 5

Output power table

Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average power(dBm)
5	10	20450	829.0	QPSK	1	0	0	23.5
					1	24	0	23.5
					1	49	0	23.5
					25	0	1	22.6
					25	12	1	22.6
					25	24	1	22.7
					50	0	1	22.5
				16QAM	1	0	1	22.7
					1	24	1	22.7
					1	49	1	22.7
					25	0	2	21.6
					25	12	2	21.6
					25	24	2	21.6
					50	0	2	21.5
		20525	836.5	QPSK	1	0	0	23.4
					1	24	0	23.5
					1	49	0	23.7
					25	0	1	22.5
					25	12	1	22.5
					25	24	1	22.4
					50	0	1	22.4
				16QAM	1	0	1	22.6
					1	24	1	22.7
					1	49	1	22.7
					25	0	2	21.6
					25	12	2	21.5
					25	24	2	21.5
					50	0	2	21.5
		20600	844.0	QPSK	1	0	0	23.4
					1	24	0	23.2
1	49				0	23.2		
25	0				1	22.4		
25	12				1	22.4		
25	24				1	22.5		
50	0				1	22.5		
16QAM	1			0	1	22.5		
	1			24	1	22.2		
	1			49	1	22.3		
	25			0	2	21.5		
	25			12	2	21.5		
	25			24	2	21.6		
	50			0	2	21.5		



Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average power(dBm)
5	5	20425	826.5	QPSK	1	0	0	23.6
					1	12	0	23.5
					1	24	0	23.4
					12	0	1	22.7
					12	6	1	22.7
					12	11	1	22.7
					25	0	1	22.6
				16QAM	1	0	1	22.8
					1	12	1	22.7
					1	24	1	22.7
					12	0	2	21.7
					12	6	2	21.7
					12	11	2	21.7
					25	0	2	21.7
		20525	836.5	QPSK	1	0	0	23.7
					1	12	0	23.7
					1	24	0	23.6
					12	0	1	22.7
					12	6	1	22.7
					12	11	1	22.7
					25	0	1	22.7
				16QAM	1	0	1	22.8
					1	12	1	22.9
					1	24	1	22.7
					12	0	2	21.9
					12	6	2	21.7
					12	11	2	21.7
					25	0	2	21.7
		20625	846.5	QPSK	1	0	0	23.2
					1	12	0	23.4
1	24				0	23.3		
12	0				1	22.4		
12	6				1	22.4		
12	11				1	22.5		
25	0				1	22.4		
16QAM	1			0	1	22.5		
	1			12	1	22.7		
	1			24	1	22.6		
	12			0	2	21.5		
	12			6	2	21.5		
	12			11	2	21.5		
	25			0	2	21.5		



Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average power(dBm)
5	3	20415	825.5	QPSK	1	0	0	23.6
					1	7	0	23.7
					1	14	0	23.4
					8	0	1	22.8
					8	4	1	22.7
					8	7	1	22.7
					15	0	1	22.7
				16QAM	1	0	1	22.8
					1	7	1	22.8
					1	14	1	22.7
					8	0	2	21.8
					8	4	2	21.7
					8	7	2	21.7
					15	0	2	21.8
					20525	836.5	QPSK	1
		1	7	0				23.7
		1	14	0				23.5
		8	0	1				22.8
		8	4	1				22.7
		8	7	1				22.6
		15	0	1				22.6
		16QAM	1	0			1	22.8
			1	7			1	22.8
			1	14			1	22.7
			8	0			2	22.8
			8	4			2	21.6
			8	7			2	21.7
			15	0			2	21.6
			20634	847.4			QPSK	1
		1			7	0		23.4
1	14	0			23.2			
8	0	1			22.5			
8	4	1			22.5			
8	7	1			22.5			
15	0	1			22.5			
16QAM	1	0			1	22.5		
	1	7			1	22.7		
	1	14			1	22.4		
	8	0			2	21.6		
	8	4			2	21.5		
	8	7			2	21.5		
	15	0			2	21.4		




Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average power(dBm)
5	1.4	20407	824.7	QPSK	1	0	0	23.5
					1	2	0	23.5
					1	5	0	23.6
					3	0	1	23.5
					3	1	1	23.5
					3	2	1	23.5
					6	0	1	22.6
				16QAM	1	0	1	22.8
					1	2	1	22.9
					1	5	1	22.9
					3	0	2	22.7
					3	1	2	22.6
					3	2	2	22.7
					6	0	2	21.6
		20525	836.5	QPSK	1	0	0	23.4
					1	2	0	23.4
					1	5	0	23.4
					3	0	1	23.3
					3	1	1	23.3
					3	2	1	23.3
					6	0	1	22.4
				16QAM	1	0	1	22.6
					1	2	1	22.5
					1	5	1	22.4
					3	0	2	22.4
					3	1	2	22.4
					3	2	2	22.5
					6	0	2	21.4
		20642	848.2	QPSK	1	0	0	23.2
					1	2	0	23.2
1	5				0	23.1		
3	0				1	22.8		
3	1				1	22.8		
3	2				1	22.8		
6	0				1	22.3		
16QAM	1			0	1	22.3		
	1			2	1	22.2		
	1			5	1	22.2		
	3			0	2	22.1		
	3			1	2	22.1		
	3			2	2	22.2		
	6			0	2	22.1		




14.11.1 Spectrum Plots for the Test RB allocations

10MHz Band Width: Ch 20525, RB Size=1; RB Offset = 0




10MHz Band Width: Ch 20525, RB Size=1; RB Offset = 24






10MHz Band Width: Ch 20525, RB Size=1; RB Offset = 49




10MHz Band Width: Ch 20525, RB Size=25; RB Offset = 0






10MHz Band Width: Ch 20525, RB Size=25; RB Offset = 12



10MHz Band Width: Ch 20525, RB Size=25; RB Offset = 24





10MHz Band Width: Ch 20525, RB Size=50; RB Offset = 0





14.12 LTE Band 13

Output power table

Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average power(dBm)
13	10	23230	782.0	QPSK	1	0	0	23.1
					1	24	0	23.4
					1	49	0	23.3
					25	0	1	22.2
					25	12	1	22.5
					25	24	1	22.4
					50	0	1	22.2
				16QAM	1	0	1	22.3
					1	24	1	22.4
					1	49	1	22.4
					25	0	2	21.1
					25	12	2	21.4
					25	24	2	21.3
					50	0	2	21.3




Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average power(dBm)
13	5	23205	779.5	QPSK	1	0	0	23.2
					1	12	0	23.3
					1	24	0	23.4
					12	0	1	22.3
					12	6	1	22.3
					12	11	1	22.4
					25	0	1	22.3
				16QAM	1	0	1	22.3
					1	12	1	22.5
					1	24	1	22.4
					12	0	2	21.3
					12	6	2	21.3
					12	11	2	21.3
					25	0	2	21.3
		23230	752.0	QPSK	1	0	0	23.2
					1	12	0	23.4
					1	24	0	23.4
					12	0	1	22.4
					12	6	1	22.5
					12	11	1	22.5
					25	0	1	22.3
				16QAM	1	0	1	22.1
					1	12	1	22.4
					1	24	1	22.5
					12	0	2	21.5
					12	6	2	21.5
					12	11	2	21.7
					25	0	2	21.5
		23255	784.5	QPSK	1	0	0	23.4
					1	12	0	23.6
1	24				0	23.2		
12	0				1	22.5		
12	6				1	22.4		
12	11				1	22.6		
25	0				1	22.5		
16QAM	1			0	1	22.5		
	1			12	1	22.8		
	1			24	1	22.3		
	12			0	2	21.5		
	12			6	2	21.5		
	12			11	2	21.6		
	25			0	2	21.5		




14.12.1 Spectrum Plots for the Test RB allocations

10MHz Band Width: Ch 23230, RB Size=1; RB Offset = 0




10MHz Band Width: Ch 23230, RB Size=1; RB Offset = 24






10MHz Band Width: Ch 23230, RB Size=1; RB Offset = 49




10MHz Band Width: Ch 23230, RB Size=25; RB Offset = 0






10MHz Band Width: Ch 23230, RB Size=25; RB Offset = 12



10MHz Band Width: Ch 23230, RB Size=25; RB Offset = 24





10MHz Band Width: Ch 23230, RB Size=50; RB Offset = 0

LTE Measurement - V3.0.30 - TX Measurement

Multi Evaluation PRACH SRS

Mode: FDD Freq.: 782.0 MHz Ref. Level: 41.00 dBm Bandwidth: 10.0 MHz Cyclic Prefix: Normal Meas Subfr.: 0

Spectrum Emission Mask

Detected Allocation NoRB: 50 OffsetRB: 0

	Current	Average	Extreme	StdDev	
OBW	8.880 MHz	8.880 MHz	8.880 MHz	0.000 MHz	
TX Power	22.17 dBm	22.16 dBm	22.06 dBm	22.22 dBm	0.02 dBm

Statistic Count Out of Tolerance Detected Modulation Detected Channel Type View Filter Throughput

100/100 0.00 % QPSK PUSCH 100.0 %

Connection Established
PS: RRC State: Connected

Cell Setup ... Connection Setup ... DL Error Insertion ... TPC ... Power ... Enable CQI Reporting Config ...

LTE

Multi Evaluation RUN

RF Settings

Trigger

Display

Marker

Signaling Parameter

LTE Signaling ON



14.13 LTE Band 17

Output power table

Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average power(dBm)
17	10	23790	710.0	QPSK	1	0	0	23.3
					1	24	0	23.6
					1	49	0	22.8
					25	0	1	22.5
					25	12	1	22.4
					25	24	1	22.4
					50	0	1	22.3
				16QAM	1	0	1	22.3
					1	24	1	22.3
					1	49	1	22.3
					25	0	2	21.3
					25	12	2	21.4
					25	24	2	21.3
					50	0	2	21.3




Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average power(dBm)
17	5	23755	706.5	QPSK	1	0	0	23.4
					1	12	0	23.5
					1	24	0	23.3
					12	0	1	22.5
					12	6	1	22.5
					12	11	1	22.6
					25	0	1	22.4
				16QAM	1	0	1	22.5
					1	12	1	22.6
					1	24	1	22.5
					12	0	2	21.5
					12	6	2	21.6
					12	11	2	21.6
					25	0	2	21.5
		23790	710.0	QPSK	1	0	0	23.4
					1	12	0	23.6
					1	24	0	23.0
					12	0	1	22.5
					12	6	1	22.6
					12	11	1	22.5
					25	0	1	22.6
				16QAM	1	0	1	22.8
					1	12	1	22.8
					1	24	1	22.4
					12	0	2	21.5
					12	6	2	21.6
					12	11	2	21.5
					25	0	2	21.4
		23825	713.5	QPSK	1	0	0	23.1
					1	12	0	23.2
1	24				0	22.9		
12	0				1	22.3		
12	6				1	22.4		
12	11				1	22.3		
25	0				1	22.2		
16QAM	1			0	1	22.1		
	1			12	1	22.0		
	1			24	1	21.9		
	12			0	2	21.2		
	12			6	2	21.1		
	12			11	2	21.2		
	25			0	2	21.1		




14.13.1 Spectrum Plots for the Test RB allocations

10MHz Band Width: Ch 23790, RB Size=1; RB Offset = 0




10MHz Band Width: Ch 23790, RB Size=1; RB Offset = 24






10MHz Band Width: Ch 23790, RB Size=1; RB Offset = 49




10MHz Band Width: Ch 23790, RB Size=25; RB Offset = 0






10MHz Band Width: Ch 23790, RB Size=25; RB Offset = 12




10MHz Band Width: Ch 23790, RB Size=25; RB Offset = 24





10MHz Band Width: Ch 23790, RB Size=50; RB Offset = 0





14.14 LTE Band 25

Output power table

Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average power(dBm)		
25	20	26140	1860.0	QPSK	1	0	0	23.0		
					1	49	0	23.0		
					1	99	0	22.9		
					50	0	1	22.3		
					50	24	1	22.3		
					50	49	1	22.2		
		16QAM	100	0	1	22.3				
			1	0	1	22.3				
			1	49	1	22.3				
			1	99	1	22.1				
			50	0	2	21.2				
			50	24	2	21.1				
		26365	1882.5	QPSK	1882.5	QPSK	50	49	2	21.1
							100	0	2	21.1
							1	0	0	23.1
							1	49	0	22.9
							1	99	0	22.7
							50	0	1	22.4
	16QAM	50	24	1	22.2					
		50	49	1	22.2					
		100	0	1	22.2					
		1	0	1	22.1					
		1	49	1	22.0					
		1	99	1	21.5					
	26590	1905.0	QPSK	1905.0	QPSK	50	0	2	21.2	
						50	24	2	21.3	
						50	49	2	21.2	
100						0	2	21.3		
1						0	0	23.0		
1						49	0	22.9		
16QAM	1	99	0	22.8						
	50	0	1	22.2						
	50	25	1	22.2						
	50	49	1	22.2						
	100	0	1	22.1						
	1	0	1	21.9						
26590	1905.0	16QAM	1905.0	16QAM	1	49	1	22.1		
					1	99	1	22.0		
					50	0	2	21.2		
					50	24	2	21.2		
					50	49	2	21.2		
					100	0	2	21.3		



Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average power(dBm)
25	15	26115	1857.5	QPSK	1	0	0	22.9
					1	37	0	22.9
					1	74	0	22.8
					36	0	1	22.0
					36	18	1	22.0
					36	35	1	21.9
					75	0	1	21.9
				16QAM	1	0	1	22.1
					1	37	1	22.2
					1	74	1	22.0
					36	0	2	21.0
					36	18	2	21.0
					36	35	2	20.9
					75	0	2	20.9
		26365	1882.5	QPSK	1	0	0	22.9
					1	37	0	22.9
					1	74	0	22.5
					36	0	1	22.1
					36	18	1	22.1
					36	35	1	22.1
					75	0	1	22.0
				16QAM	1	0	1	22.0
					1	37	1	21.9
					1	74	1	21.7
					36	0	2	21.0
					36	18	2	21.0
					36	35	2	21.0
75	0				2	20.9		
26615	1907.5	QPSK	1	0	0	22.7		
			1	37	0	22.9		
			1	74	0	22.9		
			36	0	1	21.8		
			36	18	1	21.9		
			36	35	1	21.8		
			75	0	1	21.7		
		16QAM	1	0	1	21.9		
			1	37	1	22.3		
			1	74	1	22.1		
			36	0	2	20.8		
			36	18	2	20.8		
			36	35	2	20.8		
			75	0	2	20.7		



Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average power(dBm)
25	10	26090	1855.0	QPSK	1	0	0	23.0
					1	24	0	22.9
					1	49	0	22.8
					25	0	1	22.2
					25	12	1	22.1
					25	24	1	22.1
					50	0	1	22.1
				16QAM	1	0	1	22.1
					1	24	1	22.0
					1	49	1	22.1
					25	0	2	21.2
					25	12	2	21.1
					25	24	2	21.0
					50	0	2	21.0
		26365	1882.5	QPSK	1	0	0	22.9
					1	24	0	23.0
					1	49	0	22.6
					25	0	1	22.0
					25	12	1	22.1
					25	24	1	22.1
					50	0	1	22.0
				16QAM	1	0	1	22.0
					1	24	1	22.1
					1	49	1	21.7
					25	0	2	21.1
					25	12	2	21.2
					25	24	2	21.1
					50	0	2	21.0
		26640	1910.0	QPSK	1	0	0	22.9
					1	24	0	22.9
1	49				0	22.8		
25	0				1	22.0		
25	12				1	21.9		
25	24				1	22.0		
50	0				1	21.9		
16QAM	1			0	1	22.0		
	1			24	1	22.0		
	1			49	1	21.9		
	25			0	2	21.1		
	25			12	2	21.0		
	25			24	2	21.0		
	50			0	2	20.9		



Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average power(dBm)
25	5	26065	1852.5	QPSK	1	0	0	23.1
					1	12	0	23.1
					1	24	0	22.9
					12	0	1	22.2
					12	6	1	22.3
					12	11	1	22.2
					25	0	1	22.2
				16QAM	1	0	1	22.3
					1	12	1	22.4
					1	24	1	22.1
					12	0	2	21.3
					12	6	2	21.1
					12	11	2	21.2
					25	0	2	21.1
		26365	1882.5	QPSK	1	0	0	23.0
					1	12	0	23.1
					1	24	0	22.9
					12	0	1	22.2
					12	6	1	22.1
					12	11	1	22.2
					25	0	1	22.1
				16QAM	1	0	1	22.1
					1	12	1	22.2
					1	24	1	22.1
					12	0	2	21.0
					12	6	2	21.1
					12	11	2	21.2
					25	0	2	21.0
		26665	1912.5	QPSK	1	0	0	22.8
					1	12	0	22.9
1	24				0	22.8		
12	0				1	22.9		
12	6				1	21.8		
12	11				1	22.0		
25	0				1	21.8		
16QAM	1			0	1	22.0		
	1			12	1	22.1		
	1			24	1	21.9		
	12			0	2	21.0		
	12			6	2	21.0		
	12			11	2	21.0		
	25			0	2	20.9		



Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average power(dBm)
25	3	26055	1851.5	QPSK	1	0	0	23.2
					1	7	0	23.2
					1	14	0	23.0
					8	0	1	22.3
					8	4	1	22.3
					8	7	1	22.3
					15	0	1	22.2
				16QAM	1	0	1	22.4
					1	7	1	22.3
					1	14	1	22.2
					8	0	2	21.2
					8	4	2	21.3
					8	7	2	21.3
					15	0	2	21.2
		26365	1882.5	QPSK	1	0	0	23.1
					1	7	0	23.0
					1	14	0	22.9
					8	0	1	22.3
					8	4	1	22.2
					8	7	1	22.2
					15	0	1	22.1
				16QAM	1	0	1	22.0
					1	7	1	22.2
					1	14	1	22.1
					8	0	2	21.1
					8	4	2	21.1
					8	7	2	21.1
					15	0	2	21.1
		26675	1913.4	QPSK	1	0	0	22.8
					1	7	0	23.0
1	14				0	22.7		
8	0				1	22.0		
8	4				1	22.1		
8	7				1	22.0		
15	0				1	22.0		
16QAM	1			0	1	22.0		
	1			7	1	22.1		
	1			14	1	22.0		
	8			0	2	21.0		
	8			4	2	21.0		
	8			7	2	21.1		
	15			0	2	21.0		




Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Start	MPR	Average power(dBm)		
25	1.4	26047	1850.7	QPSK	1	0	0	22.9		
					1	2	0	22.9		
					1	5	0	22.8		
					3	0	1	22.9		
					3	1	1	22.9		
					3	2	1	22.8		
				16QAM	6	0	1	21.9		
					1	0	1	21.9		
					1	2	1	21.9		
					1	5	1	21.9		
					3	0	2	21.9		
					3	1	2	21.9		
		26365	1882.5	QPSK	1882.5	QPSK	3	2	2	21.8
							6	0	2	21.0
							1	0	0	22.7
							1	2	0	22.7
							1	5	0	22.6
							3	0	1	22.6
				16QAM	3	1	1	22.7		
					3	2	1	22.6		
					6	0	1	21.8		
					1	0	1	22.0		
					1	2	1	21.9		
					1	5	1	22.0		
		26682	1914.2	QPSK	1914.2	QPSK	3	0	2	21.9
							3	1	2	21.9
							3	2	2	21.8
							6	0	2	20.8
							1	0	0	22.8
							1	2	0	22.8
16QAM	1			5	0	22.7				
	3			0	1	22.8				
	3			1	1	22.8				
	3			2	1	22.7				
	6			0	1	21.8				
	1			0	1	22.0				
16QAM	1	2	1	22.0						
	1	5	1	22.0						
	3	0	2	22.0						
	3	1	2	22.1						
	3	2	2	21.9						
	6	0	2	20.8						




14.14.1 Spectrum Plots for the Test RB allocations

20MHz Band Width: Ch 26365, RB Size=1; RB Offset = 0




20MHz Band Width: Ch 26365, RB Size=1; RB Offset = 49






20MHz Band Width: Ch 26365, RB Size=1; RB Offset = 99




20MHz Band Width: Ch 26365, RB Size=50, RB Offset = 0






20MHz Band Width: Ch 26365, RB Size=50, RB Offset = 24



20MHz Band Width: Ch 26365, RB Size=50, RB Offset = 49





20MHz Band Width: Ch 26365, RB Size=100, RB Offset = 0

LTE Measurement - V3.0.30 - TX Measurement

Multi Evaluation PRACH SRS

Mode: FDD Freq: 1882.5 MHz Ref. Level: 41.00 dBm Bandwidth: 20.0 MHz Cyclic Prefix: Normal Meas Subfr.: 0

Spectrum Emission Mask

Detected Allocation NoRB: 100 OffsetRB: 0

	Current	Average	Extreme	StdDev
OBW	17.775 MHz	12.180 MHz	17.790 MHz	4.295 MHz
TX Power	22.21 dBm	22.22 dBm	22.08 dBm 22.33 dBm	0.06 dBm

Statistic Count Out of Tolerance Detected Modulation Detected Channel Type View Filter Throughput

100/100 0.00 % QPSK PUSCH 100.0 %

Connection Established
PS: RRC State: Connected

Cell Setup ... Connection Setup ... DL Error Insertion ... TPC ... Power ... Enable CQI Reporting Config ...

LTE

Multi Evaluation RUN

RF Settings

Trigger

Display

Marker

Signaling Parameter

LTE Signaling ON



14.15 Wi-Fi (2.4 GHz Band)

Required Test Channels per KDB 248227 D01

Mode	Band (GHz)	Freq. (MHz)	Ch #	Default Test Channels	
				802.11b	802.11g
802.11 b/g	2.4	2412	1 [#]	✓	▽
		2437	6	✓	▽
		2462	11 [#]	✓	▽

Notes

✓ = “default test channels”

▽ = possible 802.11g channels with maximum average output ¼ dB the “default test channels”

= when output power is reduced for channel 1 and /or 11 to meet restricted band requirements

the highest output channels closest to each of these channels should be tested.

The indicated Wi-Fi target powers in the following table are absolute maximums.

Output power table

Band (GHz)	Mode	Data rate (Mbps)	Ch #	Freq. (MHz)	Target Pwr (dBm)			Tune-up Tolerance (dBm)	Maximum Tune-up Pwr (dBm)	Avg. Pwr (dBm)		
					Main	Aux	Total			Main	Aux	Total
2.4	802.11b	1	1	2412	12.5			±1.5	14.0	13.7		
			6	2437	12.5			±1.5	14.0	13.9		
			11	2462	12.5			±1.5	14.0	13.9		
	802.11g	6	1	2412	12.0			±1.5	13.5	13.3		
			6	2437	12.5			±1.5	14.0	13.6		
			11	2462	12.0			±1.5	13.5	12.7		
	802.11n HT20	MCS8	1	2412	7.5	7.5	10.5	±1.5	12.0	8.8	8.7	11.8
			6	2437	10.5	10.5	13.5	±1.5	15.0	11.8	11.9	14.9
			11	2462	7.5	7.5	10.5	±1.5	12.0	9.0	8.9	12.0
	802.11n HT40	MCS8	3	2412	7.0	7.0	10.0	±1.5	11.5	8.5	7.8	11.2
			6	2437	7.0	7.0	10.0	±1.5	11.5	8.5	7.9	11.2
			9	2462	5.5	5.5	8.5	±1.5	10.0	7.0	6.7	9.9

Note(s):

SAR is not required for 802.11g/HT40 channels when the maximum average output power is less than 1/4 dB higher than that measured on the corresponding 802.11b channels per KDB 248227 D01



14.16 Wi-Fi (5 GHz Band)

Required Test Channels per KDB 248227 D01

Mode	Band (GHz)	Freq. (MHz)	Ch #	Default Test Channels			
				§15.247		UNII	
802.11a	UNII	5180	36			✓	
		5200	40				*
		5220	44				*
		5240	48			✓	
		5260	52			✓	
		5280	56				*
		5300	60				*
		5320	64			✓	
		5500	100				*
		5520	104			✓	
		5540	108				*
		5560	112				*
		5580	116			✓	
		5600	120				*
		5620	124			✓	
		5640	128				*
		5660	132				*
		5680	136			✓	
	5700	140				*	
		UNII or §15.247	5745	149	✓		✓
	5765		153		*		*
	5785		157	✓			*
	5805		161		*	✓	
	§15.247	5825	165	✓			

Notes

✓ = "default test channels"

* = possible 802.11a channels with maximum average output > the "default test channels"

The indicated Wi-Fi target powers in the following table are absolute maximums



Wi-Fi 5.2GHz Band:

Band (GHz)	Mode	Data rate (Mbps)	Ch #	Freq. (MHz)	Target Pwr (dBm)			Tune-up Tolerance (dBm)	Maximum Tune-up Pwr (dBm)	Avg. Pwr (dBm)		
					Main	Aux	Total			Main	Aux	Total
5.2	802.11a	6	36	5180	9.5			± 1.5	11.0	10.8		
			40	5200	9.5			± 1.5	11.0	10.7		
			44	5220	9.5			± 1.5	11.0	10.6		
			48	5240	9.5			± 1.5	11.0	10.7		
	802.11n (HT20)	MCS8	36	5180	4.5	4.5	7.5	± 1.5	9.0	5.8	4.4	8.2
			40	5200	4.5	4.5	7.5	± 1.5	9.0	6.3	5.3	8.8
			44	5220	4.5	4.5	7.5	± 1.5	9.0	6.4	5.0	8.8
			48	5240	4.5	4.5	7.5	± 1.5	9.0	6.3	5.3	8.8
	802.11n (HT40)	MCS8	38	5190	4.5	4.5	7.5	± 1.5	9.0	5.8	5.8	8.8
			46	5230	4.5	4.5	7.5	± 1.5	9.0	5.8	5.7	8.8

Note(s):

SAR is not required for 802.11n HT20/HT40 channels when the maximum average output power is less than 1/4 dB higher than that measured on the corresponding 802.11a channels per KDB 248227 D01

Wi-Fi 5.3GHz Band:

Band (GHz)	Mode	Data rate (Mbps)	Ch #	Freq. (MHz)	Target Pwr (dBm)			Tune-up Tolerance (dBm)	Maximum Tune-up Pwr (dBm)	Avg. Pwr (dBm)		
					Main	Aux	Total			Main	Aux	Total
5.3	802.11a	6	52	5260	10.5			± 1.5	12.0	11.9		
			56	5280	10.5			± 1.5	12.0	12.0		
			60	5300	11.5			± 1.5	13.0	12.8		
			64	5320	9.5			± 1.5	11.0	11.0		
	802.11n (HT20)	MCS8	52	5260	4.5	4.5	7.5	± 1.5	9.0	5.8	4.9	8.4
			56	5280	7.5	7.5	10.5	± 1.5	12.0	9.6	7.3	11.6
			60	5300	8.0	8.0	11.0	± 1.5	12.5	9.7	8.5	12.2
			64	5320	8.0	8.0	11.0	± 1.5	12.5	9.7	8.8	12.3
	802.11n (HT40)	MCS8	54	5270	4.5	4.5	7.5	± 1.5	9.0	6.2	5.8	9.0
			62	5310	6.0	6.0	9.0	± 1.5	10.5	8.0	6.4	10.3

Note(s):

SAR is not required for 802.11n HT20/HT40 channels when the maximum average output power is less than 1/4 dB higher than that measured on the corresponding 802.11a channels per KDB 248227 D01



Wi-Fi 5.5GHz Band:

Band (GHz)	Mode	Data rate (Mbps)	Ch #	Freq. (MHz)	Target Pwr (dBm)			Tune-up Tolerance (dBm)	Maximum Tune-up Pwr (dBm)	Avg. Pwr (dBm)		
					Main	Aux	Total			Main	Aux	Total
5.5	802.11a	6	100	5500	12.0			± 1.5	13.5	13.2		
			104	5520	11.0			± 1.5	12.5	12.2		
			108	5540	11.0			± 1.5	12.5	12.2		
			112	5560	11.0			± 1.5	12.5	12.1		
			116	5580	11.0			± 1.5	12.5	12.1		
			120	5600	11.0			± 1.5	12.5	12.2		
			124	562	11.0			± 1.5	12.5	12.2		
			128	5640	11.0			± 1.5	12.5	12.3		
			132	5660	11.0			± 1.5	12.5	12.4		
			136	5680	11.0			± 1.5	12.5	12.5		
			140	5700	11.5			± 1.5	13.0	12.7		
	802.11n (HT20)	MCS8	100	5500	9.0	9.0	12.0	± 1.5	13.5	10.7	9.6	13.2
			104	5520	8.5	8.5	11.5	± 1.5	13.0	10.5	9.5	13.0
			108	5540	8.5	8.5	11.5	± 1.5	13.0	10.6	9.2	13.0
			112	5560	8.5	8.5	11.5	± 1.5	13.0	10.3	9.1	12.8
			116	5580	8.5	8.5	11.5	± 1.5	13.0	10.3	8.7	12.6
			120	5600	8.5	8.5	11.5	± 1.5	13.0	10.6	9.3	13.0
			124	5620	9.5	9.5	12.5	± 1.5	14.0	11.8	9.3	13.7
			128	5640	9.5	9.5	12.5	± 1.5	14.0	11.5	9.4	13.6
			132	5660	9.5	9.5	12.5	± 1.5	14.0	11.3	9.5	13.5
			136	5680	9.5	9.5	12.5	± 1.5	14.0	11.2	9.6	13.5
			140	5700	9.5	9.5	12.5	± 1.5	14.0	11.6	9.8	13.8
	802.11n (HT40)	MCS8	102	5510	9.0	9.0	12.0	± 1.5	13.5	11.0	9.4	13.3
			118	5550	9.0	9.0	12.0	± 1.5	13.5	11.1	9.3	13.3
			134	5670	9.5	9.5	12.5	± 1.5	14.0	11.6	9.7	13.8

Note(s):

SAR is not required for 802.11n HT40 channels when the maximum average output power is less than 1/4 dB higher than that measured on the corresponding 802.11a channels per KDB 248227 D01



Wi-Fi 5.8GHz Band:

Band (GHz)	Mode	Data rate (Mbps)	Ch #	Freq. (MHz)	Target Pwr (dBm)			Tune-up Tolerance (dBm)	Maximum Tune-up Pwr (dBm)	Avg. Pwr (dBm)		
					Main	Aux	Total			Main	Aux	Total
5.8	802.11a	6	149	5745	12.0			± 1.5	13.5	13.2		
			153	5765	12.0			± 1.5	13.5	13.5		
			157	5785	12.0			± 1.5	13.5	13.2		
			161	5805	12.5			± 1.5	14.0	13.9		
			165	5825	12.5			± 1.5	14.0	14.0		
	802.11n (HT20)	MCS8	149	5745	10.0	10.0	13.0	± 1.5	14.5	11.8	10.3	14.1
			153	5765	10.0	10.0	13.0	± 1.5	14.5	11.9	10.6	14.3
			157	5785	10.0	10.0	13.0	± 1.5	14.5	11.8	10.6	14.3
			161	5805	10.5	10.5	13.5	± 1.5	15.0	12.1	11.1	14.6
			165	5825	10.5	10.5	13.5	± 1.5	15.0	12.2	11.1	14.7
	802.11n (HT40)	MCS8	151	5755	9.5	9.5	12.5	± 1.5	14.0	10.6	10.9	13.8
			159	5795	9.5	9.5	12.5	± 1.5	14.0	11.2	9.8	13.6

Note(s):

SAR is not required for 802.11n HT40 channels when the maximum average output power is less than 1/4 dB higher than that measured on the corresponding 802.11a channels per KDB 248227 D01



15 SAR Measurements Results

GSM850:

Mode	Slot	Test Position	Channel	Freq. (MHz)	Dist. (mm)	Power (dBm)		Measured 1g SAR (W/kg)	Reported SAR(W/kg)	Note
						Tune up limit	Measured			
GPRS 850	2	Edge 4	128	824.2	0					
			190	836.6	0	33.0	32.1	0.115	0.143	
			251	848.8	0					
		Rear	128	824.2	0					
			190	836.6	0	33.0	32.1	0.035	0.043	
			251	848.8	0					

GSM1900:

Mode	Slot	Test Position	Channel	Freq. (MHz)	Dist. (mm)	Power (dBm)		Measured 1g SAR (W/kg)	Reported SAR(W/kg)	Note
						Tune up limit	Measured			
GPRS 1900	2	Edge 4	512	1850.2	0	30.0	29.5	0.843	0.955	1
			661	1880.0	0	30.0	29.5	0.970	1.083	
			810	1909.8	0	30.0	29.4	1.140	1.318	1
			810	1909.8	0	30.0	29.4	1.140	1.309	2
		Rear	512	1850.2	0					
			661	1880.0	0	30.0	29.5	0.141	0.157	
			810	1909.8	0					

Note(s):

- Testing of other required channels within the operating mode of a frequency band is required when the reported 1-g SAR for the mid-band or highest output power channel. ≥ 0.8 W/kg and transmission band ≤ 100 MHz (Per KDB 447498 D01 v05r01 section 4.3.3)
- Repeated measurements are required only when the measured SAR is ≥ 0.80 W/kg. If the measured SAR values are < 1.45 W/kg with $\leq 20\%$ variation, only one repeated measurement is required to reaffirm that the results are not expected to have substantial variations, which may introduce significant compliance concerns. (Per KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r01)
 - Original SAR = 1.14 W/kg, therefore two times repeat SAR is required.
 - Repeat SAR = 1.14 W/kg < 1.45 W/kg
 - SAR variation= 0.0% $< 20\%$



WCDMA Band II:

Mode	Test Position	Channel	Freq. (MHz)	Dist. (mm)	Power (dBm)		Measured 1g SAR (W/kg)	Reported SAR(W/kg)	Note
					Tune up limit	Measured			
Rel 99 RMC 12.2Kbps	Edge 4	9262	1852.4	0	24.0	23.1	0.896	1.095	
		9400	1880.0	0	24.0	23.0	0.914	1.151	1
		9538	1907.6	0	24.0	23.0	1.040	1.297	1
	Rear	9538	1907.6	0	24.0	23.0	1.050	1.310	2
		9262	1852.4	0	24.0	23.1	0.123	0.150	
		9400	1880.0	0					
		9538	1907.6	0					

Note(s):

- Testing of other required channels within the operating mode of a frequency band is required when the reported 1-g SAR for the mid-band or highest output power channel. ≥ 0.8 W/kg and transmission band ≤ 100 MHz (Per KDB 447498 D01 v05r01 section 4.3.3)
- Repeated measurements are required only when the measured SAR is ≥ 0.80 W/kg. If the measured SAR values are < 1.45 W/kg with $\leq 20\%$ variation, only one repeated measurement is required to reaffirm that the results are not expected to have substantial variations, which may introduce significant compliance concerns. (Per KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r01)
 - Original SAR = 1.04 W/kg, therefore two times repeat SAR is required.
 - Repeat SAR = 1.05 W/kg < 1.45 W/kg
 - SAR variation= 0.95% $< 20\%$

WCDMA Band IV:

Mode	Test Position	Channel	Freq. (MHz)	Dist. (mm)	Power (dBm)		Measured 1g SAR (W/kg)	Reported SAR(W/kg)	Note
					Tune up limit	Measured			
Rel 99 RMC 12.2Kbps	Edge 4	1312	1712.4	0					
		1413	1732.6	0					
		1513	1752.6	0	24.0	23.0	0.724	0.920	
	Rear	1312	1712.4	0					
		1413	1732.6	0					
		1513	1752.6	0	24.0	23.0	0.107	0.136	

WCDMA Band V:

Mode	Test Position	Channel	Freq. (MHz)	Dist. (mm)	Power (dBm)		Measured 1g SAR (W/kg)	Reported SAR(W/kg)	Note
					Tune up limit	Measured			
Rel 99 RMC 12.2Kbps	Edge 4	4132	826.4	0					
		4183	836.6	0					
		4233	846.6	0	24.0	22.9	0.083	0.107	
	Rear	4132	826.4	0					
		4183	836.6	0					
		4233	846.6	0	24.0	22.9	0.042	0.054	



CDMA BC0:

Mode	Test Position	Channel	Freq. (MHz)	Dist. (mm)	Power (dBm)		Measured 1g SAR (W/kg)	Reported SAR(W/kg)	Note
					Tune up limit	Measured			
CDMA BC0	Edge 4	1013	824.7	0					
		384	836.5	0	25.0	24.4	0.098	0.114	
		777	848.3	0					
	Rear	1013	824.7	0					
		384	836.5	0	25.0	24.4	0.046	0.053	
		777	848.3	0					

CDMA BC1:

Mode	Test Position	Channel	Freq. (MHz)	Dist. (mm)	Power (dBm)		Measured 1g SAR (W/kg)	Reported SAR(W/kg)	Note
					Tune up limit	Measured			
CDMA BC1	Edge 4	25	1851.3	0	25.0	24.7	1.350	1.447	
		25	1851.3	0	25.0	24.7	1.310	1.404	2
		600	1880.0	0	25.0	24.7	1.350	1.447	1
		1175	1908.8	0	24.5	24.5	1.270	1.264	1
	Rear	25	1851.3	0	25.0	24.7	0.164	0.176	
		600	1880.0	0					
		1175	1908.8	0					

Note(s):

1. Testing of other required channels within the operating mode of a frequency band is required when the reported 1-g SAR for the mid-band or highest output power channel. ≥ 0.8 W/kg and transmission band ≤ 100 MHz (Per KDB 447498 D01 v05r01 section 4.3.3)
2. Repeated measurements are required only when the measured SAR is ≥ 0.80 W/kg. If the measured SAR values are < 1.45 W/kg with $\leq 20\%$ variation, only one repeated measurement is required to reaffirm that the results are not expected to have substantial variations, which may introduce significant compliance concerns. (Per KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r01)
 - 2.1 Original SAR = 1.35 W/kg, therefore two times repeat SAR is required.
 - 2.2 Repeat SAR = 1.31 W/kg < 1.45 W/kg
 - 2.3 SAR variation= 3.0 % $< 20\%$



LTE Band 2 (20MHz Bandwidth):

Mode	Test Position	Channel	Freq. (MHz)	Dist. (mm)	UL RB Allocation	UL RB Start	MPR	Power (dBm)		Measured 1g SAR (W/kg)	Reported SAR(W/kg)	Note
								Tune up limit	Measured			
QPSK	Edge4	18900	1880.0	0	1	0	0	24.0	23.1	1.070	1.316	
		18700	1860.0	0	1	0	0	24.0	23.0	1.010	1.272	1
		19100	1900.0	0	1	0	0	24.0	22.9	1.020	1.314	1
		18900	1880.0	0	50	0	1	24.0	22.6	0.918	1.267	
		18700	1860.0	0	50	0	1	24.0	22.4	0.784	1.133	1
		19100	1900.0	0	50	0	1	24.0	22.4	0.834	1.205	1
		18900	1880.0	0	100	0	1	24.0	22.2	0.870	1.317	2
		18700	1860.0	0	100	0	1	24.0	22.3	0.796	1.177	2
		19100	1900.0	0	100	0	1	24.0	22.1	0.835	1.293	2
		18900	1880.0	0	1	0	0	24.0	23.1	1.070	1.316	3
QPSK	Rear	18900	1880.0	0	1	0	0	24.0	23.1	0.125	0.154	
		18900	1880.0	0	50	0	1	24.0	22.6	0.115	0.159	

Note(s):

- When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. (Per KDB 941225 D05 v02r02 section 5.2.1)
- The highest reported SAR for 1 RB and 50% RB allocation are ≥ 0.8 W/kg, SAR is required of 100% RB. (Per KDB 941225 D05 v02r02 section 5.2.3)
- Repeated measurements are required only when the measured SAR is ≥ 0.80 W/kg. If the measured SAR values are < 1.45 W/kg with $\leq 20\%$ variation, only one repeated measurement is required to reaffirm that the results are not expected to have substantial variations, which may introduce significant compliance concerns. (Per KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r01)
 - Original SAR = 1.07 W/kg, therefore two times repeat SAR is required.
 - Repeat SAR = 1.07 W/kg < 1.45 W/kg
 - SAR variation= 0.0 % $< 20\%$



LTE Band 4 (20MHz Bandwidth):

Mode	Test Position	Channel	Freq. (MHz)	Dist. (mm)	UL RB Allocation	UL RB Start	MPR	Power (dBm)		Measured 1g SAR (W/kg)	Reported SAR(W/kg)	Note
								Tune up limit	Measured			
QPSK	Edge4	20300	1745.0	0	1	0	0	24.0	23.9	0.860	0.880	
		20050	1720.0	0	1	0	0	24.0	23.7	0.769	0.824	1
		20175	1732.5	0	1	0	0	24.0	23.8	0.816	0.854	1
		20050	1720.0	0	50	0	1	24.0	23.0	0.601	0.757	
		20175	1732.5	0	50	0	1	24.0	22.9	0.643	0.828	1
		20300	1745.5	0	50	0	1	24.0	22.9	0.680	0.876	1
		20300	1745.0	0	100	0	1	24.0	23.0	0.668	0.841	2
		20050	1720.0	0	100	0	1	24.0	22.7	0.620	0.836	2
		20175	1732.5	0	100	0	1	24.0	23.1	0.657	0.808	2
		20300	1745.0	0	1	0	0	24.0	23.9	0.877	0.897	3
QPSK	Rear	20300	1745.0	0	1	0	0	24.0	23.9	0.092	0.094	
		20050	1720.0	0	50	0	1	24.0	22.6	0.086	0.119	

Note(s):

1. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. (Per KDB 941225 D05 v02r02 section 5.2.1)
2. The highest reported SAR for 1 RB and 50% RB allocation are ≥ 0.8 W/kg, SAR is required of 100% RB. (Per KDB 941225 D05 v02r02 section 5.2.3)
3. Repeated measurements are required only when the measured SAR is ≥ 0.80 W/kg. If the measured SAR values are < 1.45 W/kg with $\leq 20\%$ variation, only one repeated measurement is required to reaffirm that the results are not expected to have substantial variations, which may introduce significant compliance concerns. (Per KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r01)
 - 3.1 Original SAR = 0.860 W/kg, therefore two times repeat SAR is required.
 - 3.2 Repeat SAR = 0.877 W/kg < 1.45 W/kg
 - 3.3 SAR variation= 1.9 % $< 20\%$



LTE Band 5 (10MHz Bandwidth):

Mode	Test Position	Channel	Freq. (MHz)	Dist. (mm)	UL RB Allocation	UL RB Start	MPR	Power (dBm)		Measured 1g SAR (W/kg)	Reported SAR(W/kg)	Note
								Tune up limit	Measured			
QPSK	Edge4	20525	836.5	0	1	49	0	24.0	23.7	0.099	0.106	
		20450	829.0	0	25	24	1	24.0	22.6	0.086	0.119	
QPSK	Rear	20525	836.5	0	1	49	0	24.0	23.7	0.052	0.056	
		20450	829.0	0	25	24	1	24.0	22.6	0.045	0.062	

LTE Band 13 (10MHz Bandwidth):

Mode	Test Position	Channel	Freq. (MHz)	Dist. (mm)	UL RB Allocation	UL RB Start	MPR	Power (dBm)		Measured 1g SAR (W/kg)	Reported SAR(W/kg)	Note
								Tune up limit	Measured			
QPSK	Edge4	23230	782.0	0	1	24	0	24.0	23.4	0.050	0.057	
		23230	782.0	0	25	12	1	24.0	22.5	0.042	0.059	
QPSK	Rear	23230	782.0	0	1	24	0	24.0	23.4	0.053	0.061	
		23230	782.0	0	25	12	1	24.0	22.5	0.037	0.052	

LTE Band 17 (10MHz Bandwidth):

Mode	Test Position	Channel	Freq. (MHz)	Dist. (mm)	UL RB Allocation	UL RB Start	MPR	Power (dBm)		Measured 1g SAR (W/kg)	Reported SAR(W/kg)	Note
								Tune up limit	Measured			
QPSK	Edge4	23790	710.0	0	1	24	0	24.0	23.6	0.043	0.047	
		23790	710.0	0	25	0	1	24.0	22.5	0.034	0.048	
QPSK	Rear	23790	710.0	0	1	24	0	24.0	23.6	0.053	0.058	
		23790	710.0	0	25	0	1	24.0	22.5	0.035	0.049	



LTE Band 25 (20MHz Bandwidth):

Mode	Test Position	Channel	Freq. (MHz)	Dist. (mm)	UL RB Allocation	UL RB Start	MPR	Power (dBm)		Measured 1g SAR (W/kg)	Reported SAR(W/kg)	Note
								Tune up limit	Measured			
QPSK	Edge4	26365	1882.5	0	1	0	0	24.0	23.1	1.030	1.267	
		26140	1860.0	0	1	0	0	24.0	23.0	1.000	1.259	1
		26590	1905.0	0	1	0	0	24.0	23.0	1.040	1.309	1
		26365	1882.5	0	50	0	1	24.0	22.4	0.793	1.146	
		26140	1860.0	0	50	0	1	24.0	22.3	0.755	1.117	1
		26590	1905.0	0	50	0	1	24.0	22.2	0.813	1.231	1
		26365	1882.5	0	100	0	2	24.0	22.2	0.800	1.211	2
		26140	1860.0	0	100	0	2	24.0	22.3	0.764	1.130	2
		26590	1905.0	0	100	0	2	24.0	22.1	0.828	1.282	2
		26590	1905.0	0	1	0	0	24.0	23.0	1.070	1.347	3
QPSK	Rear	26365	1882.5	0	1	0	0	24.0	23.1	0.117	0.144	
		26365	1882.5	0	50	0	1	23.0	21.9	0.100	0.129	

Note(s):

1. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. (Per KDB 941225 D05 v02r02 section 5.2.1)
2. The highest reported SAR for 1 RB and 50% RB allocation are ≥ 0.8 W/kg, SAR is required of 100% RB. (Per KDB 941225 D05 v02r02 section 5.2.3)
3. Repeated measurements are required only when the measured SAR is ≥ 0.80 W/kg. If the measured SAR values are < 1.45 W/kg with $\leq 20\%$ variation, only one repeated measurement is required to reaffirm that the results are not expected to have substantial variations, which may introduce significant compliance concerns. (Per KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r01)
 - 3.1 Original SAR = 1.04 W/kg, therefore two times repeat SAR is required.
 - 3.2 Repeat SAR = 1.07 W/kg < 1.45 W/kg
 - 3.3 SAR variation= 2.8 % $< 20\%$



Wi-Fi (2.4GHz Band):

Band	Mode	Test Position	Channel	Freq. (MHz)	Chain	Dist. (mm)	Power (dBm)		Measured 1g SAR (W/kg)	Reported SAR(W/kg)	Note
							Tune up limit	Measured			
2.4GHz	802.11b	Edge 1	1	2412	0	0	14.0	13.7	0.818	0.877	1
			6	2437	0	0	14.0	13.9	0.922	0.943	
			11	2462	0	0	14.0	13.9	0.961	0.983	1
			11	2462	0	0	14.0	13.9	0.952	0.974	2
	802.11n HT20	Rear	6	2437	0	0	14.0	13.9	0.088	0.090	
		Edge 1	6	2437	0	0	15.0	14.9	0.572	0.585	
		Edge 2	6	2437	1	0	15.0	14.9	0.240	0.246	
	Rear	6	2437	0+1	0	15.0	14.9	0.034	0.035		

Note(s):

1. Testing of other required channels within the operating mode of a frequency band is required when the reported 1-g SAR for the mid-band or highest output power channel. ≥ 0.8 W/kg and transmission band ≤ 100 MHz (Per KDB 447498 D01 v05r01 section 4.3.3)
2. Repeated measurements are required only when the measured SAR is ≥ 0.80 W/kg. If the measured SAR values are < 1.45 W/kg with $\leq 20\%$ variation, only one repeated measurement is required to reaffirm that the results are not expected to have substantial variations, which may introduce significant compliance concerns. (Per KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r01)
 - 2.1 Original SAR = 0.961 W/kg, therefore two times repeat SAR is required.
 - 2.2 Repeat SAR = 0.952W/kg < 1.45 W/kg
 - 2.3 SAR variation= 0.9% $< 20\%$



Wi-Fi (5.2GHz Band):

Band	Mode	Test Position	Channel	Freq. (MHz)	Chain	Dist. (mm)	Power (dBm)		Measured 1g SAR (W/kg)	Reported SAR(W/kg)	Note
							Tune up limit	Measured			
5.2GHz	802.11a	Edge1	36	5180	0	0	11.0	10.8	0.234	0.245	
			48	5240	0	0	11.0	10.7	0.298	0.319	
		Rear	36	5180	0	0	11.0	10.8	0.415	0.435	
			48	5240	0	0	11.0	10.7	0.470	0.504	

Wi-Fi (5.3GHz Band):

Band	Mode	Test Position	Channel	Freq. (MHz)	Chain	Dist. (mm)	Power (dBm)		Measured 1g SAR (W/kg)	Reported SAR(W/kg)	Note
							Tune up limit	Measured			
5.3GHz	802.11a	Edge1	56	5280	0	0	12.0	12.0	0.548	0.548	
			60	5300	0	0	13.0	12.8	0.588	0.616	
		Rear	56	5280	0	0	12.0	12.0	0.383	0.383	
			60	5300	0	0	13.0	12.8	0.356	0.373	

Wi-Fi (5.5GHz Band):

Band	Mode	Test Position	Channel	Freq. (MHz)	Chain	Dist. (mm)	Power (dBm)		Measured 1g SAR (W/kg)	Reported SAR(W/kg)	Note
							Tune up limit	Measured			
5.5GHz	802.11a	Edge1	100	5500	0	0	13.5	13.2	0.688	0.737	
			120	5600	0	0	12.5	12.2	0.532	0.570	
			128	5640	0	0	12.5	12.3	0.487	0.510	
			140	5700	0	0	13.0	12.7	0.429	0.460	
		Rear	100	5500	0	0	13.5	13.2	0.473	0.507	
			120	5600	0	0	12.5	12.2	0.481	0.515	
			128	5640	0	0	12.5	12.3	0.497	0.520	
			140	5700	0	0	13.0	12.7	0.364	0.390	
	802.11n HT20	Edge1	100	5500	0+1	0	13.5	13.2	0.779	0.835	
			120	5600	0+1	0	13.0	13.0	0.477	0.477	
			124	5620	0+1	0	14.0	13.7	0.480	0.514	
			140	5700	0+1	0	14.0	13.8	0.425	0.445	
		Edge2	100	5500	0+1	0	13.5	13.2	0.774	0.829	
			120	5600	0+1	0	13.0	13.0	0.732	0.732	
			124	5620	0+1	0	14.0	13.7	0.781	0.837	
			140	5700	0+1	0	14.0	13.8	0.836	0.875	
		Rear	140	5700	0+1	0	14.0	13.8	0.837	0.876	1
			100	5500	0+1	0	13.5	13.2	0.615	0.659	
			120	5600	0+1	0	13.0	13.0	0.525	0.525	
			124	5620	0+1	0	14.0	13.7	0.511	0.548	
			140	5700	0+1	0	14.0	13.8	0.524	0.549	

Note(s):

- 1 Repeated measurements are required only when the measured SAR is ≥ 0.80 W/kg. If the measured SAR values are < 1.45 W/kg with $\leq 20\%$ variation, only one repeated measurement is required to reaffirm that the results are not expected to have substantial variations, which may introduce significant compliance concerns. (Per KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r01)
 - 1.1 Original SAR = 0.836 W/kg, therefore two times repeat SAR is required.
 - 1.2 Repeat SAR = 0.837W/kg < 1.45 W/kg
 - 1.3 SAR variation= 0.1% $< 20\%$



Wi-Fi (5.8GHz Band):

Band	Mode	Test Position	Channel	Freq. (MHz)	Chain	Dist. (mm)	Power (dBm)		Measured 1g SAR (W/kg)	Reported SAR(W/kg)	Note
							Tune up limit	Measured			
5.8GHz	802.11a	Edge1	153	5765	0	0	13.5	13.5	0.611	0.611	
			161	5805	0	0	14.0	13.9	0.725	0.742	
			165	5825	0	0	14.0	14.0	0.778	0.778	
		Rear	153	5765	0	0	13.5	13.5	0.394	0.394	
			161	5805	0	0	14.0	13.9	0.507	0.519	
			165	5825	0	0	14.0	14.0	0.482	0.482	
	802.11n HT20	Edge1	153	5765	0+1	0	14.5	14.3	0.534	0.559	
			161	5805	0+1	0	15.0	14.6	0.449	0.492	
			165	5825	0+1	0	15.0	14.7	0.527	0.565	
		Edge2	153	5765	0+1	0	14.5	14.3	0.953	0.998	
			161	5805	0+1	0	15.0	14.6	1.020	1.118	
			165	5825	0+1	0	15.0	14.7	0.955	1.023	
		Rear	161	5805	0+1	0	15.0	14.6	1.080	1.184	1
			153	5765	0+1	0	14.5	14.3	0.545	0.571	
			161	5805	0+1	0	15.0	14.6	0.461	0.505	
			165	5825	0+1	0	15.0	14.7	0.545	0.584	

Note(s):

- 1 Repeated measurements are required only when the measured SAR is ≥ 0.80 W/kg. If the measured SAR values are < 1.45 W/kg with $\leq 20\%$ variation, only one repeated measurement is required to reaffirm that the results are not expected to have substantial variations, which may introduce significant compliance concerns. (Per KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r01)1.1 Original SAR = 1.02 W/kg, therefore two times repeat SAR is required.
 - 1.2 Repeat SAR = 1.08 W/kg < 1.45 W/kg
 - 1.3 SAR variation= 5.5% $< 20\%$




15.1 Summary of Highest SAR Values

Results for highest reported SAR values for each frequency band and mode

Technology/Band	Test configuration	Mode	Highest Reported 1g-SAR (W/kg)
GSM850	Edge4	GPRS 2slot	0.143
GSM1900	Edge4	GPRS 2slot	1.318
W-CDMA (UMTS) Band II	Edge4	12.2 Kbps	1.310
WCDMA (UMTS) band IV	Edge4	12.2 Kbps	0.920
WCDMA (UMTS) band V	Edge4	12.2 Kbps	0.107
CDMA BC0	Edge4	RC1 SO55	0.114
CDMA BC1	Edge4	RC1 SO55	1.447
LTE band 2	Edge4	QPSK BW20	1.317
LTE band 4	Edge4	QPSK BW20	0.897
LTE band 5	Edge4	QPSK BW10	0.119
LTE band 13	Rear	QPSK BW10	0.061
LTE band 17	Rear	QPSK BW10	0.058
LTE band 25	Edge4	QPSK BW20	1.347
WiFi 2.4 GHz	Edge1	802.11b	0.983
WiFi 5.2 GHz	Rear	802.11a	0.504
WiFi 5.3 GHz	Edge1	802.11a	0.616
WiFi 5.5 GHz	Edge2	802.11n HT20	0.876
WiFi 5.8 GHz	Edge2	802.11n HT20	1.184




16 Antenna Locations & Separation Distances



Unit: mm

17 Schematic of Bumpers

According to KDB 616217)4.1), the bumpers thickness is less than 5mm. Therefore the bumpers cannot be removed for SAR testing.





18 Equipment List & Calibration Status

Name of Equipment	Manufacturer	Type/Model	Serial Number	Calibration Cycle(year)	Calibration Due
S-Parameter Network Analyzer	Agilent	E8358A	MY46213916	1	06/03/2014
Electronic Probe kit	Hewlett Packard	85070D	N/A	N/A	N/A
Power Meter	Anritsu	ML2495A	GB41291611	1	09/18/2013
Power Sensor	Anritsu	MA2411B	MY41091956	1	09/18/2013
Spectrum Analyzer	Agilent	E4446A	US42510252	1	12/09/2013
Wireless Communication Test Set	Agilent	E5515C 8960	MY48363204	1	09/12/2013
Radio Communication Analyzer	Anritsu	MT8820C	6200938900	1	05/30/2014
Data Acquisition Electronics (DAE)	SPEAG	DAE4	877	1	03/11/2014
Dosimetric E-Field Probe	SPEAG	EX3DV4	3665	1	05/06/2014
750 MHz System Validation Dipole	SPEAG	D750V3	1020	1	10/25/2013
835 MHz System Validation Dipole	SPEAG	D835V2	4d015	1	03/17/2014
1800 MHz System Validation Dipole	SPEAG	D1800V2	2d062	1	02/11/2014
1900 MHz System Validation Dipole	SPEAG	D1900V2	5d056	1	02/12/2014
2450 MHz System Validation Dipole	SPEAG	D2450V2	728	1	05/01/2014
5 GHz System Validation Dipole	SPEAG	D5GHzV2	1004	1	11/15/2013
Robot	Staubli	RX60L	F02/5T69A1/A/01	N/A	N/A
Amplifier	Mini-Circuit	ZVE-8G	665500309	N/A	N/A
Amplifier	Mini-Circuit	ZHL-1724HLN	D072602#2	N/A	N/A



19 Facilities

All measurement facilities used to collect the measurement data are located at

- No. 81-1, Lane 210, Bade Rd. 2, Luchu Hsiang, Taoyuan Hsien, Taiwan, R.O.C.
- No.11, Wugong 6th Rd., Wugu Dist., New Taipei City 24891, Taiwan. (R.O.C.)
- No. 199, Chunghsen Road, Hsintien City, Taipei Hsien, Taiwan, R.O.C.

20 Reference

- [1] Federal Communications Commission, \Report and order: Guidelines for evaluating the environmental effects of radiofrequency radiation", Tech. Rep. FCC 96-326, FCC, Washington, D.C. 20554, 1996.
- [2] David L. Means Kwok Chan, Robert F. Cleveland, \Evaluating compliance with FCC guidelines for human exposure to radiofrequency electromagnetic fields", Tech. Rep., Federal Communication Commission, Office of Engineering & Technology, Washington, DC, 1997.
- [3] Thomas Schmid, Oliver Egger, and Niels Kuster, \Automated E-field scanning system for dosimetric assessments", IEEE Transactions on Microwave Theory and Techniques, vol. 44, pp. 105{113, Jan. 1996.
- [4] Niels Kuster, Ralph Kastle, and Thomas Schmid, \Dosimetric evaluation of mobile communications equipment with known precision", IEEE Transactions on Communications, vol. E80-B, no. 5, pp. 645{652, May 1997.
- [5] CENELEC, \Considerations for evaluating of human exposure to electromagnetic fields (EMFs) from mobile telecommunication equipment (MTE) in the frequency range 30MHz - 6GHz", Tech. Rep., CENELEC, European Committee for Electrotechnical Standardization, Brussels, 1997.
- [6] ANSI, ANSI/IEEE C95.1-1992: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz, The Institute of Electrical and Electronics Engineers, Inc., New York, NY 10017, 1992.
- [7] Katja Pokovic, Thomas Schmid, and Niels Kuster, \Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies", in ICECOM '97, Dubrovnik, October 15{17, 1997, pp. 120{124.
- [8] Katja Pokovic, Thomas Schmid, and Niels Kuster, \E-field probe with improved isotropy in brain simulating liquids", in Proceedings of the ELMAR, Zadar, Croatia, 23{25 June, 1996, pp. 172{175.
- [9] Volker Hombach, Klaus Meier, Michael Burkhardt, Eberhard Kuhn, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 900 MHz", IEEE Transactions on Microwave Theory and Techniques, vol. 44, no. 10, pp. 1865{1873, Oct. 1996.
- [10] Klaus Meier, Ralf Kastle, Volker Hombach, Roger Tay, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 1800 MHz", IEEE Transactions on Microwave Theory and Techniques, Oct. 1997, in press.
- [11] W. Gander, Computermathematik, Birkhaeuser, Basel, 1992.
- [12] W. H. Press, S. A. Teukolsky, W. T. Vetterling, and B. P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second Edition, Cambridge University Press, 1992. Dosimetric Evaluation of Sample device, month 1998 9
- [13] NIS81 NAMAS, \The treatment of uncertainty in EMC measurement", Tech. Rep., NAMAS Executive, National Physical Laboratory, Teddington, Middlesex, England, 1994.
- [14] Barry N. Taylor and Christ E. Kuyatt, \Guidelines for evaluating and expressing the uncertainty of NIST measurement results", Tech. Rep., National Institute of Standards and Technology, 1994. Dosimetric Evaluation of Sample device, month 1998 10



21 Attachments

Exhibit	Content
1	System Performance Check Plots
2	SAR test plots for GPRS 850
3	SAR test plots for GPRS 1900
4	SAR test plots for WCDMA Band II
5	SAR test plots for WCDMA Band IV
6	SAR test plots for WCDMA Band V
7	SAR test plots for CDMA BC0
8	SAR test plots for CDMA BC1
9	SAR test plots for LTE Band 2
10	SAR test plots for LTE Band 4
11	SAR test plots for LTE Band 5
12	SAR test plots for LTE Band 13
13	SAR test plots for LTE Band 17
14	SAR test plots for LTE Band 25
15	SAR test plots for Wi-Fi 2.4GHz Band
16	SAR test plots for Wi-Fi 5 GHz Band
17	SAR_Probe_EX3DV4_sn3665
18	SAR_DAE4_sn877
19	SAR_Dipole_D750v3_sn1020
20	SAR_Dipole_D835v2_sn4d015
21	SAR_Dipole_D1800v2_sn2d062
22	SAR_Dipole_D1900v2_sn5d056
23	SAR_Dipole_D2450v2_sn728
24	SAR_Dipole_D5GHzv2_sn1004
25	T130724W02-SF PHOTOS

END OF REPORT