



The University of Michigan
Radiation Laboratory
3228 EECS Building
Ann Arbor, MI 48109-2122
Tel: (734) 764-0500

Measured Radio Frequency Emissions
From

EnTire TPM Transmitter
Model(s): 218898-101, 218898-102, and 218898-103

Report No. 415031-341
November 7, 2006

Copyright © 2006

For:
EnTire Solutions, LLC
24175 Research Drive
Farmington Hills, MI 48335-2642

Contact: Timothy Regnerus
Tel: (248) 426-3999
Fax: (248) 478-7241
PO: Verbal

Measurements made by: Valdis V. Liepa

Tests supervised by:
Report approved by:

Valdis V. Liepa
Valdis V. Liepa
Research Scientist

Test Report Prepared by: Joseph D. Brunett

Summary

Tests for compliance with FCC Regulations Part 15, Subpart C, and Industry Canada RSS-210/GEN, were performed on EnTire Solutions, LLC model(s) 218898-101, 218898-102, 218898-103. This device is subject to the Rules and Regulations as a Transmitter.

In testing completed on October 2, 2006, the device tested in the worst case met the allowed FCC specifications for radiated emissions by 1.4 dB (see p. 6). Besides harmonics, there were no other significant spurious emissions found; emissions from digital circuitry were negligible. The conducted emission tests do not apply, since the device is powered from a 12 VDC battery.

1. Introduction

EnTire Solutions, LLC models 218898-101, 218898-102, and 218898-103 were tested for compliance with FCC Regulations, Part 15, adopted under Docket 87-389, April 18, 1989 as subsequently amended, and with Industry Canada RSS-210/Gen, Issue 6, September 2005. The tests were performed at the University of Michigan Radiation Laboratory Willow Run Test Range following the procedures described in ANSI C63.4-2003 "Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz". The Site description and attenuation characteristics of the Open Area Test Site are on file with FCC Laboratory, Columbia, Maryland (FCC Reg. No: 91050) and with Industry Canada, Ottawa, ON (File Ref. No: IC 2057).

2. Equipment Used

The pertinent test equipment commonly used in our facility for measurements is listed in Table 2.1 below. The middle column identifies the specific equipment used in these tests.

Table 2.1 Test Equipment.

Test Instrument	Eqpt. Used	Manufacturer/Model
Spectrum Analyzer (0.1-1500 MHz)		Hewlett-Packard, 182T/8558B
Spectrum Analyzer (9kHz-22GHz)	X	Hewlett-Packard 8593A SN: 3107A01358
Spectrum Analyzer (9kHz-26GHz)	X	Hewlett-Packard 8593E, SN: 3412A01131
Spectrum Analyzer (9kHz-26GHz)		Hewlett-Packard 8563E, SN: 3310A01174
Spectrum Analyzer (9kHz-40GHz)		Hewlett-Packard 8564E, SN: 3745A01031
Power Meter		Hewlett-Packard, 432A
Power Meter		Anritsu, ML4803A/MP
Harmonic Mixer (26-40 GHz)		Hewlett-Packard 11970A, SN: 3003A08327
Harmonic Mixer (40-60 GHz)		Hewlett-Packard 11970U, SN: 2332A00500
Harmonic Mixer (75-110 GHz)		Hewlett-Packard 11970W, SN: 2521A00179
Harmonic Mixer (140-220 GHz)		Pacific Millimeter Prod., GMA, SN: 26
S-Band Std. Gain Horn		S/A, Model SGH-2.6
C-Band Std. Gain Horn		University of Michigan, NRL design
XN-Band Std. Gain Horn		University of Michigan, NRL design
X-Band Std. Gain Horn		S/A, Model 12-8.2
X-band horn (8.2- 12.4 GHz)		Narda 640
X-band horn (8.2- 12.4 GHz)		Scientific Atlanta , 12-8.2, SN: 730
K-band horn (18-26.5 GHz)		FXR, Inc., K638KF
Ka-band horn (26.5-40 GHz)		FXR, Inc., U638A
U-band horn (40-60 GHz)		Custom Microwave, HO19
W-band horn(75-110 GHz)		Custom Microwave, HO10
G-band horn (140-220 GHz)		Custom Microwave, HO5R
Bicone Antenna (30-250 MHz)	X	University of Michigan, RLBC-1
Bicone Antenna (200-1000 MHz)	X	University of Michigan, RLBC-2
Dipole Antenna Set (30-1000 MHz)	X	University of Michigan, RLDP-1,-2,-3
Dipole Antenna Set (30-1000 MHz)		EMCO 2131C, SN: 992
Active Rod Antenna (30 Hz-50 MHz)		EMCO 3301B, SN: 3223
Active Loop Antenna (30 Hz-50 MHz)		EMCO 6502, SN:2855
Ridge-horn Antenna (300-5000 MHz)	X	University of Michigan
Amplifier (5-1000 MHz)	X	Avantek, A11-1, A25-1S
Amplifier (5-4500 MHz)	X	Avantek
Amplifier (4.5-13 GHz)		Avantek, AFT-12665
Amplifier (6-16 GHz)		Trek
Amplifier (16-26 GHz)		Avantek
LISN Box		University of Michigan
Signal Generator		Hewlett-Packard 8657B

3. Configuration and Identification of Device Under Test (DUT)

3.1 Design and Identification of the Device

The DUT was designed and manufactured by EnTire Solutions, LLC, 24175 Research Drive, Farmington Hills, MI 48335-2642. It is identified as:

EnTire Solutions, LLC TPMS Transmitter
Model(s): 218898-101, 218898-102, 218898-103
FCC ID: T7B-2T
IC: 6484A-2T

3.2 Models

There are three versions/models of the DUT. The only difference between the 218898-101 and 218898-102 models is a variation in the length of the valve stem, the -101 has a short stem and the -102 has a longer stem. The model 218898-103 is electrically identical to the 218898-101. The only difference being that its RF message transmission rate has changed from 1 min to 1 min 40s during normal operation. Transmissions are the same format and data size and contains the same number of RF messages for all three devices.

3.3 Modes of Operation

The DUT periodically transmits tire pressure data. The device is also capable of being automatically actuated (via LF interrogation) either by in-vehicle LF initiators or by trained personnel during servicing. Per FCC correspondence, service modes fall under FCC part 15.231(a)(5). Figure 6.1 demonstrates compliance with both 15.231(a)(2) and (5). A list of all operating modes is included in the Description of Operation exhibit.

3.4 EMI/EMC Relevant Modifications

There were no modifications made to the DUT by this laboratory.

4. Regulatory Limits

The DUT tested falls under the category of an Intentional Radiators and the Digital Devices. For FCC, it is subject to Part 15, Subpart C (Section 15.231(a),(c), & (e), 15.209) and Subpart A (Section 15.33). For Industry Canada it is subject to RSS-210 (2.6, 2.7). The applicable testing frequencies with corresponding emission limits are given in Tables 4.1 and 4.2 below.

4.1 Radiated Emission Limits

Table 4.1. General Radiated Emission Limits (FCC: 15.33, 15.35, 15.209; IC: RSS-210, 2.7 Table 2)
(Digital Class B)

Freq. (MHz)	E _{lim} (3m) μ V/m	E _{lim} dB(μ V/m)
30-88	100	40.0
88-216	150	43.5
216-960	200	46.0
960-2000	500	54.0

Note: Average readings apply above 1000 MHz (1 MHz BW)
Quasi-Peak readings apply to 1000 MHz (120 kHz BW)

Table 4.2. Radiated Emission Limits (FCC: 15.231(e), 15.205(a); IC: RSS-210; 2.7 Table 5).
 (Transmitter)

Frequency (MHz)	Fundamental Ave. E _{lim} (3m)		Spurious** Ave. E _{lim} (3m)	
	(μ V/m)	dB (μ V/m)	(μ V/m)	dB (μ V/m)
260.0-470.0	1500-5000*		150-500	
315.0	2417	67.7	241.7	47.7
433.9	4399	72.9	439.9	52.9
322-335.4	Restricted Bands			
399.9-410			200	46.0
608-614				
960-1240	Restricted Bands			
1300-1427				
1435-1626.5				
1660-1710			500	54.0
1718.9-1722.2				
2200-2300				

* Linear interpolation, formula: $E = -2833.2 + 16.67*f$ (MHz)

** Measure up to tenth harmonic; 120 kHz RBW up to 1 GHz, 1 MHz RBW above 1 GHz

4.3 Exemptions

For devices operating in transportation vehicles, digital emissions are exempt (FCC 15.103(a), IC correspondence) and need not be reported.

4.4 Power Line Conducted Emission Limits

The power line conducted emission limits and tests do not apply here, as the DUT is powered by a 12 VDC battery.

4.5 Supply Voltage Variation

Measurements of the variation in the fundamental radiated emission shall be performed with the supply voltage varied between 85% and 115% of the nominal rated value. For battery operated equipment, the equipment tests shall be performed using a new battery.

5. Test Procedures

5.1 Semi-Anechoic Chamber Radiated Emission Testing

To become familiar with the emission behavior of the DUT, the DUT was first studied and measured in a shielded semi-anechoic chamber. In the chamber is set-up similar to that of an outdoor 3-meter site, with a turntable, antenna mast, and a ground plane. Instrumentation includes spectrum analyzers and other equipment as needed.

In testing for radiated emissions, a transmitter was provided by the manufacturer that is capable of repeated emissions. It was placed on the test table flat, on its side, and on its end. In the chamber we studied and recorded all the emissions using a Bicone antenna up to 300 MHz and a ridged horn antenna above 200 MHz. The measurements made in the chamber below 1 GHz are used for pre-test evaluation only. The measurements made above 1 GHz are used in pre-test evaluation and in final compliance assessment. We note that for the horn antenna, the antenna pattern is directive and the measurement is essentially that of free space (no ground reflection). Consequently, it is not essential to measure the DUT for both antenna polarizations, as long as the DUT is measured on all three of its major axis. In the chamber we also recorded the spectrum and modulation characteristics of the carrier. These data are presented in subsequent sections.

5.2 Open Area Test Site (OATS) Radiated Emission Testing

After the chamber measurements are complete, emissions are re-measured on the outdoor 3-meter open area test site at the fundamental and harmonics up to 1 GHz using tuned dipoles and/or a high frequency biconical antenna. The DUT is placed on the test table flat, on its side, and on its end, and worst case emissions are recorded. Photographs included in this filing show the DUT on the OATS.

5.3 Field Calculation for Radiated Emission Measurements

To convert the dBm's measured on the spectrum analyzer to dB(μ V/m), we use expression

$$E_3(\text{dB}\mu\text{V/m}) = 107 + P_R + K_A - K_G$$

where P_R = power recorded on spectrum analyzer, dB, measured at 3m
 K_A = antenna factor, dB/m
 K_G = pre-amplifier gain, including cable loss, dB

When presenting the data, at each frequency the highest measured emission under all of the possible orientations is given. Computations and results are given in Table 5.1. There we see that the DUT meets the limit by 1.4 dB.

5.4 Power Line Conducted Emission Testing

These tests do not apply, since the DUT is powered from a 12 VDC battery.

6. Test Results

6.1 Correction For Pulse Operation

When the transmitter is activated, it can, in the worst case, transmit 3 datasets (words) of Manchester encoded data in any given 100 ms window. Each word consists of two wakeup pulses, the first 0.195 ms in duration, the second 0.490 ms in duration. Following the wakeup pulses, 69 Manchester ASK encoded data pulses are sent, each with an on-time of no more than 0.102 ms. See Figure 6.1. Computing the duty factor results in:

$$K_E = 3 \times ((0.195 \text{ ms} + 0.490 \text{ ms} + 69 \times 0.102 \text{ ms}) / 100 \text{ ms}) = 0.23 \text{ or } -12.7 \text{ dB.}$$

6.2 Emission Spectrum

Using the ridge-horn antenna and DUT placed in its aperture, emission spectrum was recorded and is shown in Figure 6.2. We note that in scanning from 30 MHz to 4.5 GHz using Bicone and the ridge horn antennas, there were no other significant spurious emissions observed.

6.3 Bandwidth of the Emission Spectrum

The measured spectrum of the signal is shown in Figure 6.3. The allowed (-20 dB, 99%) bandwidth is 0.25% of 315 MHz, or 787.25 kHz. From the plot we see that the -20 dB bandwidth is 55.0 kHz, and the center frequency is 315.075 MHz.

6.4 Effect of Supply Voltage Variation and Test Battery Voltages

The DUT has been designed to be powered by a 12 VDC battery. For this test, the battery was replaced by a laboratory variable power supply. Relative power radiated was measured at the fundamental as the voltage was varied from 2 to 4 volts. The emission variation is shown in Figure 6.4.

Batteries:	before testing	$V_{oc} = 3.29 \text{ V}$
	after testing	$V_{oc} = 3.03 \text{ V}$
Ave. current from batteries		$I = 9.5 \text{ mA (cw)}$

Table 5.1 Highest Emissions Measured

Radiated Emission - RF											EnTire T7B-2T
#	Freq. MHz	Ant. Used	Ant. Pol.	Pr dBm	Det. Used	Ka dB/m	Kg dB	E3*	E3lim	Pass dB	Comments
1	Long Stem										
2	315.0	Dip	H	-23.9	Pk	18.6	22.7	66.3	67.7	1.4	flat
3	315.0	Dip	V	-30.4	Pk	18.6	22.7	59.8	67.7	7.9	end
4	630.0	Dip	H	-61.3	Pk	24.4	19.7	37.7	47.7	10.0	side
5	630.0	Dip	V	-59.7	Pk	24.4	19.7	39.3	47.7	8.4	end
6	945.0	Dip	H	-69.3	Pk	28.8	17.8	36.1	47.7	11.6	end
7	945.0	Dip	V	-70.2	Pk	28.8	17.8	35.2	47.7	12.5	flat
8	1260.0	Horn	H	-43.1	Pk	20.6	28.0	43.8	54.0	10.2	side
9	1575.0	Horn	H	-55.0	Pk	21.5	28.0	32.8	54.0	21.2	end
10	1890.0	Horn	H	-45.1	Pk	22.2	28.0	43.4	54.0	10.6	flat
11	2205.0	Horn	H	-52.2	Pk	23.0	28.1	37.0	54.0	17.0	end
12	2520.0	Horn	H	-52.3	Pk	23.9	28.3	37.6	54.0	16.4	end
13	2835.0	Horn	H	-48.7	Pk	24.8	28.2	42.2	54.0	11.8	end
14	3150.0	Horn	H	-53.9	Pk	25.8	27.9	38.3	54.0	15.7	end
15											
16	Short Stem										
17	315.0	Dip	H	-28.1	Pk	18.6	22.7	62.1	67.7	5.6	flat
18	315.0	Dip	V	-32.3	Pk	18.6	22.7	57.9	67.7	9.8	end
19	630.0	Dip	H	-60.3	Pk	24.4	19.7	38.7	47.7	9.0	side
20	630.0	Dip	V	-60.8	Pk	24.4	19.7	38.2	47.7	9.5	end
21	945.0	Dip	H	-67.2	Pk	28.8	17.8	38.2	47.7	9.5	end
22	945.0	Dip	V	-70.8	Pk	28.8	17.8	34.6	47.7	13.1	flat
23	1260.0	Horn	H	-42.8	Pk	20.6	28.0	44.1	54.0	9.9	flat
24	1575.0	Horn	H	-54.3	Pk	21.5	28.0	33.5	54.0	20.5	side
25	1890.0	Horn	H	-43.6	Pk	22.2	28.0	44.9	54.0	9.1	flat
26	2205.0	Horn	H	-51.5	Pk	23.0	28.1	37.7	54.0	16.3	end
27	2520.0	Horn	H	-53.6	Pk	23.9	28.3	36.3	54.0	17.7	end
28	2835.0	Horn	H	-48.8	Pk	24.8	28.2	42.1	54.0	11.9	end
29	3150.0	Horn	H	-55.6	Pk	25.8	27.9	36.6	54.0	17.4	end
30											
31	* Includes 12.7 dB duty factor										
32											
Digital Radiated Emissions*											
#	Freq. kHz	Ant. Used	Ant. Pol.	Pr dBm	Det. Used	Ka dB/m	Kg dB	E3	E3lim	Pass dB	Comments
6											
7	Digital emissions more than 20 dB below FCC/IC Class B Limit.										
8											
9	* For devices used in transportation vehicles, digital emissions are exempt from FCC regulations per FCC 15										

Meas. 10/02/2006; U of Mich.




Figure 6.1(a).

Transmissions modulation characteristics: (top) transmission repetition > 10 s
 (center) four word transmission, (bottom) expanded word.

University of Michigan Radiation Laboratory
FCC Part 15, IC RSS-210/GEN - Test Report No. 415031-341




Figure 6.1(b). Transmissions modulation characteristics: (top) wake pulse 1, (center) wake pulse 2, (bottom) Manchester pulse.




Figure 6.2. Emission spectrum of the DUT (pulsed emission).
The amplitudes are only indicative (not calibrated).




Figure 6.3. Measured bandwidth of the DUT (pulsed emission).





Figure 6.4.

Relative emissions at 315.0 MHz vs. supply voltage.
(pulsed emission)



DUT on OATS



DUT on OATS (close-up)