

<b>FCC TEST REPORT</b> <b>FCC 47 CFR Part 15C</b> <b>Industry Canada RSS-210</b> <b>Digital transmission systems operating within the 2400 – 2483.5 MHz band</b>	
<b>Report Reference No.</b> .....	G0M-1502-4538-TFC247BL-V01
<b>Testing Laboratory</b> .....	Eurofins Product Service GmbH
Address.....	Storkower Str. 38c 15526 Reichenwalde Germany
Accreditation .....	<div style="display: flex; justify-content: center; align-items: center;">   </div> <p style="text-align: center; margin-top: 5px;">                     A2LA Accredited Testing Laboratory, Certificate No.: 1983.01                      FCC Filed Test Laboratory, Reg.-No.: 96970                      IC OATS Filing assigned code: 3470A                 </p>
<b>Applicant's name</b> .....	Panasonic Industrial Devices Europe GmbH
Address.....	Zeppelinstr. 19 21337 Lüneburg GERMANY
<b>Test specification:</b>	
Standard .....	47 CFR Part 15C KDB Publication No. 558074 RSS-210, Issue 8, 2010-12 RSS-Gen, Issue 4, 2014-11 ANSI C63.4:2009
Test scope.....	complete Radio compliance test
<b>Equipment under test (EUT):</b>	
Product description	Bluetooth Smart Module
Model No.	ENW89847A1KF
Additional Model(s)	None
Brand Name(s)	PAN1760
Hardware version	01
Firmware / Software version	01
	FCC-ID: T7V1760                      IC: 216Q-1760
<b>Test result</b>	<b>Passed</b>

**Possible test case verdicts:**

- neither assessed nor tested .....: N/N
- required by standard but not appl. to test object.....: N/A
- required by standard but not tested.....: N/T
- not required by standard for the test object .....: N/R
- test object does meet the requirement.....: P (Pass)
- test object does not meet the requirement.....: F (Fail)

**Testing:**

Test Lab Temperature.....: 20 – 23 °C

Test Lab Humidity .....: 32 – 38 %

Date of receipt of test item .....: 2015-02-24

Date (s) of performance of tests .....: 2015-03-02 – 2015-03-03

Compiled by .....: Wilfried Treffke

Tested by (+ signature).....: Wilfried Treffke *W. Treff*

(Responsible for Test) .....

Approved by (+ signature) .....: Christian Weber *C. Weber*

Date of issue .....: 2015-05-11

Total number of pages .....: 78

**General remarks:**

**The test results presented in this report relate only to the object tested.**

**The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.**

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

**Additional comments:**

---

---

## Version History

Version	Issue Date	Remarks	Revised by
01	2015-05-11	Initial Release	

---



## REPORT INDEX

<b>1</b>	<b>EQUIPMENT (TEST ITEM) DESCRIPTION</b>	<b>5</b>
1.1	Photos – Equipment External	6
1.2	Photos – Equipment internal	7
1.3	Photos – Test setup	8
1.4	Supporting Equipment Used During Testing	9
1.5	Test Modes	10
1.6	Test Equipment Used During Testing	11
1.7	Sample emission level calculation	13
<b>2</b>	<b>RESULT SUMMARY</b>	<b>14</b>
<b>3</b>	<b>TEST CONDITIONS AND RESULTS</b>	<b>15</b>
3.1	Test Conditions and Results – Occupied Bandwidth	15
3.2	Test Conditions and Results – 6 dB Bandwidth	19
3.3	Test Conditions and Results – Maximum peak conducted power	23
3.4	Test Conditions and Results – Power spectral density	24
3.5	Test Conditions and Results – AC power line conducted emissions	25
3.6	Test Conditions and Results – Band edge compliance	28
3.7	Test Conditions and Results – Conducted spurious emissions	31
3.8	Test Conditions and Results – Transmitter radiated emissions	35
3.9	Test Conditions and Results – Receiver radiated emissions	37
ANNEX A	Transmitter radiated spurious emissions	39
ANNEX B	Receiver radiated spurious emissions	71


## 1 Equipment (Test item) Description

<b>Description</b>	Bluetooth Smart Module	
<b>Model</b>	ENW89847A1KF	
<b>Additional Model(s)</b>	None	
<b>Brand Name(s)</b>	PAN1760	
<b>Serial number</b>	None	
<b>Hardware version</b>	01	
<b>Software / Firmware version</b>	01	
<b>FCC-ID</b>	T7V1760	
<b>IC</b>	216Q-1760	
<b>Equipment type</b>	Radio module	
<b>Radio type</b>	Transceiver	
<b>Radio technology</b>	Bluetooth 4.0 Low Energy	
<b>Operating frequency range</b>	2402 - 2480 MHz	
<b>Assigned frequency band</b>	2400 - 2483.5 MHz	
<b>Main test frequencies</b>	F <sub>LOW</sub>	2402 MHz
	F <sub>MID</sub>	2440 MHz
	F <sub>HIGH</sub>	2480 MHz
<b>Spreading</b>	Frequency Hopping	
<b>Modulations</b>	GFSK	
<b>Number of channels</b>	40	
<b>Channel spacing</b>	2MHz	
<b>Number of antennas</b>	1	
<b>Antenna</b>	Type	integrated
	Model	ANT2012L
	Manufacturer	Yageo
	Gain	2.7 dBi (manufacturer declaration)
<b>Manufacturer</b>	Panasonic Industrial Devices Europe GmbH Zeppelinstr. 19 21337 Lüneburg GERMANY	
<b>Power supply</b>	V <sub>NOM</sub>	3.3VDC
	V <sub>MIN</sub>	N/R
	V <sub>MAX</sub>	N/R
<b>AC/DC-Adaptor</b>	none	



1.1 Photos – Equipment External



1.2 Photos – Equipment internal



1.3 Photos – Test setup





#### 1.4 Supporting Equipment Used During Testing

Product Type*	Device	Manufacturer	Model No.	Comments
None				
<p><b>*Note:</b> Use the following abbreviations:</p> <p style="padding-left: 40px;">AE : Auxiliary/Associated Equipment, or</p> <p style="padding-left: 40px;">SIM : Simulator (Not Subjected to Test)</p> <p style="padding-left: 40px;">CABL : Connecting cables</p>				

**1.5 Test Modes**

Mode #	Description	
Transmit	General conditions:	EUT powered by via USB.
	Radio conditions:	Mode = standalone transmit Spreading = Hopping stopped (single hopping channel) Modulation = GFSK Data rate = 1 Mbps Duty cycle = 100 % Power level = Maximum
Receive	General conditions:	EUT powered by via USB.
	Radio conditions:	Mode = standalone receive Spreading = On Modulation = GFSK
AC-Powerline	General conditions:	EUT powered by commercial Laptop
	Radio conditions:	Mode = Transmit Spreading = On

**1.6 Test Equipment Used During Testing**

<b>Measurement Software</b>			
Description	Manufacturer	Name	Version
EMC Test Software	Dare Instruments	Radimation	2014.1.15

<b>Occupied Bandwidth</b>					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Spectrum Analyzer	R&S	FSP 30	EF00312	2015-02	2016-02

<b>6dB Bandwidth</b>					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Spectrum Analyzer	R&S	FSP 30	EF00312	2015-02	2016-02

<b>Maximum peak conducted power</b>					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Spectrum Analyzer	R&S	FSP 30	EF00312	2015-02	2016-02

<b>Power spectral density</b>					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Spectrum Analyzer	R&S	FSP 30	EF00312	2015-02	2016-02

<b>Band edge compliance</b>					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Spectrum Analyzer	R&S	FSP 30	EF00312	2015-02	2016-02

<b>Conducted spurious emissions</b>					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Spectrum Analyzer	R&S	FSP 30	EF00312	2015-02	2016-02

<b>Radiated spurious emissions</b>					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Semi-anechoic chamber	Frankonia	AC 1	EF00062	-	-
Spectrum Analyzer	R&S	FSIQ26	EF00242	2014-03	2015-03
Biconical Antenna	R&S	HK 116	EF00012	2013-02	2016-02
LPD Antenna	R&S	HL 223	EF00187	2014-03	2017-03
LPD Antenna	R&S	HL 025	EF00327	2013-02	2016-02

AC powerline conducted emissions					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
AMN	R&S	ESH2-Z5	EF00182	2014-11	2016-11
EMI Test Receiver	R&S	ESCS 30	EF00295	2014-10	2015-10

## 1.7 Sample emission level calculation

The following is a description of terms and a sample calculation, as appears in the radiated emissions data table. The numbers used in the calculation are for example only. There is no direct correlation to the specific data taken for the product described in this document:

Reading:

This is the reading obtained on the spectrum analyzer in dB $\mu$ V. Any external preamplifiers used are taken into account through internal analyzer settings.

A.F.:

This is the antenna factor for the receiving antenna. It is a conversion factor, which converts electric fields strengths to voltages, which can be measured directly on the spectrum analyzer. It is treated as a loss in dB. Cable losses have been included with the A.F. to simplify the calculations. The antenna factor is used in calculations as follows:

$$\text{Reading on Analyzer (dB}\mu\text{V)} + \text{A.F. (dB)} = \text{Net field strength (dB}\mu\text{V/m)}$$

Net:

This is the net field strength measurement (as shown above).

Limit:

This is the FCC Class B radiated emission limit (in units of dB $\mu$ V/m). The FCC limits are given in units of  $\mu$ V/m. The following formula is used to convert the units of  $\mu$ V/m to dB $\mu$ V/m:

$$\text{Limit (dB}\mu\text{V/m)} = 20 * \log (\mu\text{V/m})$$

Margin:

This is the margin of compliance below the FCC limit. The units are given in dB. A negative margin indicates the emission was below the limit. A positive margin indicates that the emission exceeds the limit.

Example only:


$$\begin{array}{rclcl} \text{Reading} & + & \text{AF} & = & \text{Net Reading} & : & \text{Net reading - FCC limit} & = & \text{Margin} \\ 21.5 \text{ dB}\mu\text{V} & + & 26 \text{ dB} & = & 47.5 \text{ dB}\mu\text{V/m} & : & 47.5 \text{ dB}\mu\text{V/m} - 57.0 \text{ dB}\mu\text{V/m} & = & -9.5 \text{ dB} \end{array}$$

## 2 Result Summary

FCC 47 CFR Part 15C, IC RSS-210				
Product Specific Standard Section	Requirement – Test	Reference Method	Result	Remarks
RSS-Gen 6.6	Occupied Bandwidth	RSS-Gen 6.6	N/R	Informational only
FCC § 15.247(a)(2) IC RSS-210 § A8.2	6dB Bandwidth	KDB Publication No. 558074	PASS	
FCC § 15.247(b)(3) IC RSS-210 § A8.4	Maximum peak conducted power	KDB Publication No. 558074	PASS	
FCC § 15.247(e) IC RSS-210 § A8.2	Power spectral density	KDB Publication No. 558074	PASS	
47 CFR 15.207 RSS-Gen 7.2.4	AC power line conducted emissions	KDB Publication No. 558074 / ANSI C63.4	PASS	
FCC § 15.247(d) IC RSS-210 § A8.5	Band edge compliance	KDB Publication No. 558074	PASS	
FCC § 15.247(d) IC RSS-210 § A8.5	Conducted spurious emissions	KDB Publication No. 558074	PASS	
FCC § 15.247(d) FCC § 15.209 IC RSS-210 A8.5 IC RSS-Gen 6.13	Transmitter radiated spurious emissions	KDB Publication No. 558074 / ANSI C 63.4	PASS	
IC RSS-Gen 4 7.1	Receiver radiated spurious emissions	ANSI C 63.4	PASS	
<b>Remarks:</b>				

### 3 Test Conditions and Results

#### 3.1 Test Conditions and Results – Occupied Bandwidth


Occupied Bandwidth acc. to IC RSS-Gen		Verdict: PASS	
Test according to measurement reference	Reference Method		
	RSS-Gen 6.6		
Test frequency range	Tested frequencies		
	$F_{LOW} / F_{MID} / F_{HIGH}$		
<b>Limits</b>			
None (Informational only)			
<b>Test setup</b>			
			
<b>Test procedure</b>			
<ol style="list-style-type: none"> <li>1. EUT set to test mode (Communication tester is used if needed)</li> <li>2. Span set to at least twice the emission spectrum</li> <li>3. Resolution bandwidth set to 1 % of span</li> <li>4. Occupied Bandwidth (99 %) measurement with spectrum analyzer built in measurement function</li> </ol>			
<b>Test results</b>			
Channel	Frequency [MHz]	Mode	Occupied Bandwidth [kHz]
$F_{LOW}$	2402	Transmit	1012
$F_{MID}$	2440	Transmit	1011
$F_{HIGH}$	2480	Transmit	1017
Comments:			

Occupied Bandwidth – F<sub>Low</sub>

Occupied Bandwidth acc. to RSS-Gen

Project Number: G0M-1502-4538

Applicant: Panasonic Industrial Devices Europe GmbH  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Wilfried Treffke  
 Test Conditions: Tnom / Vnom  
 Mode: Tx, BT-LE, 2402 MHz, modulated  
 Test Date: 2015-03-02  
 Verdict: NONE (INFORMATION ONLY)  
 Note 1: A spectrum analyzer with an integrated 99% power bandwidth function is used  
 Note 2: OBW= 1.012 MHz




Occupied bandwidth: 1012 KHz  
 Date: 2.MAR.2015 12:28:00



**Occupied Bandwidth – F<sub>MID</sub>**
**Occupied Bandwidth acc. to RSS-Gen**

Project Number: G0M-1502-4538

Applicant: Panasonic Industrial Devices Europe GmbH  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Wilfried Treffke  
 Test Conditions: Tnom / Vnom  
 Mode: Tx, BT-LE, 2440 MHz, modulated  
 Test Date: 2015-03-02  
 Verdict: NONE (INFORMATION ONLY)  
 Note 1: A spectrum analyzer with an integrated 99% power bandwidth function is used  
 Note 2: OBW= 1.011 MHz




Occupied bandwidth: 1011 KHz  
 Date: 2.MAR.2015 12:32:00

Occupied Bandwidth – F<sub>HIGH</sub>

Occupied Bandwidth acc. to RSS-Gen


Project Number: G0M-1502-4538

Applicant: Panasonic Industrial Devices Europe GmbH  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Wilfried Treffke  
 Test Conditions: Tnom / Vnom  
 Mode: Tx, BT-LE, 2480 MHz, modulated  
 Test Date: 2015-03-02  
 Verdict: NONE (INFORMATION ONLY)  
 Note 1: A spectrum analyzer with an integrated 99% power bandwidth function is used  
 Note 2: OBW= 1.017 MHz



Occupied bandwidth: 1017 KHz  
 Date: 2.MAR.2015 12:35:21

**3.2 Test Conditions and Results – 6 dB Bandwidth**


<b>6dB Bandwidth acc. to FCC 15.247 / IC RSS-210</b>				<b>Verdict: PASS</b>	
EUT requirement rule parts and clause	Reference				
	FCC 15.247(a)(2) / IC RSS-210 A8.2				
Test according to measurement reference	Reference Method				
	FCC KDB Publication No. 558074				
Test frequency range	Tested frequencies				
	$F_{LOW} / F_{MID} / F_{HIGH}$				
<b>Limits</b>					
≥ 500kHz					
<b>Test setup</b>					
					
<b>Test procedure</b>					
<ol style="list-style-type: none"> <li>1. EUT set to test mode</li> <li>2. Span set to at least twice the emission spectrum</li> <li>3. Detector set to peak and max hold and RBW is set to 100 kHz</li> <li>4. Envelope peak value of emission spectrum is selected</li> <li>5. Marker on envelope of spectrum is set to level of -6 dB to the left of the peak</li> <li>6. Marker on envelope of spectrum is set to level of -6 dB to the right of the peak</li> <li>7. 6 dB Bandwidth is determined by marker frequency separation</li> </ol>					
<b>Test results</b>					
Channel	Frequency [MHz]	Mode	6 dB Bandwidth [kHz]	Limit [kHz]	Result
$F_{LOW}$	2402	Transmit	692.1	500	PASS
$F_{MID}$	2440	Transmit	668.0	500	PASS
$F_{HIGH}$	2480	Transmit	682.4	500	PASS
Comments:					

6 dB Bandwidth – F<sub>Low</sub>

**Minimum 6 dB Bandwidth acc. to FCC 15.247**

Project Number: G0M-1502-4538

Applicant: Panasonic Industrial Devices Europe GmbH  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Wilfried Treffke  
 Test Conditions: Tnom / Vnom  
 Mode: Tx, BT-LE, 2402 MHz, modulated  
 Test Date: 2015-03-02  
 Verdict: PASS  
 Note 1: Procedure 8.1 DTS (558074 D01 Meas Guidance)  
 Note 2: Minimum 6 dB Bandwidth conducted




6 dB bandwidth: 692.1 KHz > 500 KHz;      verdict: PASS  
 Date: 2.MAR.2015 12:43:46

6 dB Bandwidth – F<sub>MID</sub>

**Minimum 6 dB Bandwidth acc. to FCC 15.247**

Project Number: G0M-1502-4538

Applicant: Panasonic Industrial Devices Europe GmbH  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Wilfried Treffke  
 Test Conditions: Tnom / Vnom  
 Mode: Tx, BT-LE, 2440 MHz, modulated  
 Test Date: 2015-03-02  
 Verdict: PASS  
 Note 1: Procedure 8.1 DTS (558074 D01 Meas Guidance)  
 Note 2: Minimum 6 dB Bandwidth conducted




6 dB bandwidth: 668 KHz > 500 KHz; verdict: PASS  
 Date: 2.MAR.2015 12:46:00

**6 dB Bandwidth – F<sub>HIGH</sub>**
**Minimum 6 dB Bandwidth acc. to FCC 15.247**


Project Number: G0M-1502-4538

Applicant: Panasonic Industrial Devices Europe GmbH  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Wilfried Treffke  
 Test Conditions: Tnom / Vnom  
 Mode: Tx, BT-LE, 2480 MHz, modulated  
 Test Date: 2015-03-02  
 Verdict: PASS  
 Note 1: Procedure 8.1 DTS (558074 D01 Meas Guidance)  
 Note 2: Minimum 6 dB Bandwidth conducted




6 dB bandwidth: 682.4 KHz > 500 KHz;      verdict: PASS  
 Date: 2.MAR.2015 12:48:59

**3.3 Test Conditions and Results – Maximum peak conducted power**

<b>Maximum peak conducted power acc. to FCC 15.247 / IC RSS-210</b>				<b>Verdict: PASS</b>			
EUT requirement rule parts and clause		Reference					
		FCC 15.247(b)(3) / IC RSS-210 A8.4					
Test according to measurement reference		Reference Method					
		FCC KDB Publication No. 558074					
Test frequency range		Tested frequencies					
		$F_{LOW} / F_{MID} / F_{HIGH}$					
Measurement mode		Peak					
Maximum antenna gain		2.7 dBi $\Rightarrow$ Limit correction = 0 dB					
<b>Limits</b>							
1 W (30 dBm)							
The conducted output power limit specified above is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in the table, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.							
<b>Test setup</b>							
							
<b>Test procedure</b>							
<ol style="list-style-type: none"> <li>1. EUT set to test mode (Communication tester is used if needed)</li> <li>2. Center frequency set to test channel center frequency</li> <li>3. Span set to twice the 20 dB bandwidth and detector to peak and max hold</li> <li>4. Resolution bandwidth is set to 3 MHz</li> <li>5. Peak conducted power is determined from peak of spectrum envelope</li> </ol>							
<b>Test results</b>							
Channel	Frequency [MHz]	Voltage	Mode	Peak power [dBm]	Peak power [mW]	Limit [dBm]	Margin [dB]
$F_{LOW}$	2402	$V_{nom} = 3.3V$	Transmit	-3.0	0.50	30	-33.00
$F_{MID}$	2440	$V_{nom} = 3.3V$	Transmit	-2.4	0.58	30	-32.40
$F_{HIGH}$	2480	$V_{nom} = 3.3V$	Transmit	-2.0	0.63	30	-32.00
Comment:							

**3.4 Test Conditions and Results – Power spectral density**

Power spectral density acc. to FCC 15.247 / IC RSS-210				Verdict: PASS		
EUT requirement rule parts and clause	Reference					
	FCC 15.247(e) / IC RSS-210 A8.2					
Test according to measurement reference	Reference Method					
	FCC KDB Publication No. 558074					
Test frequency range	Tested frequencies					
	$F_{LOW} / F_{MID} / F_{HIGH}$					
Measurement mode	Peak					
<b>Limits</b>						
8 dBm / 3 kHz						
<b>Test setup</b>						
						
<b>Test procedure</b>						
<ol style="list-style-type: none"> <li>1. EUT set to test mode (Communication tester is used if needed)</li> <li>2. Center frequency set to test channel center frequency</li> <li>3. Span is set large enough to capture maximum emissions in passband, RBW is set to 3kHz</li> <li>4. Peak power density is determined from peak emission of envelope</li> </ol>						
<b>Test results</b>						
Channel	Frequency [MHz]	Test mode	Peak frequency [MHz]	Peak power density [dBm/100kHz]	Limit [dBm/3kHz]	Margin [dB]
$F_{LOW}$	2402	Transmit	2401.990	-3.08	8.0	-11.08
$F_{MID}$	2440	Transmit	2439.986	-2.52	8.0	-10.52
$F_{HIGH}$	2480	Transmit	2479.986	-2.18	8.0	-10.18
Comments:						



**3.5 Test Conditions and Results – AC power line conducted emissions**


<b>Power line conducted emissions acc. to FCC 47 CFR 15.207 / IC RSS-Gen</b>		<b>Verdict: PASS</b>		
Test according referenced standards	Reference Method			
	ANSI C63.4			
Fully configured sample scanned over the following frequency range	Frequency range			
	0.15 MHz to 30 MHz			
Points of Application	Application Interface			
AC Mains	LISN			
EUT test mode	AC power line			
<b>Limits and results</b>				
Frequency [MHz]	Quasi-Peak [dB $\mu$ V]	Result	Average [dB $\mu$ V]	Result
0.15 to 5	66 to 56*	PASS	56 to 46*	PASS
0.5 to 5	56	PASS	46	PASS
5 to 30	60	PASS	50	PASS
Comments: * Limit decreases linearly with the logarithm of the frequency.				

**Conducted Emissions**
**EMI voltage test in the ac-mains according to FCC 15B**

Project number: G0M-1502-4538

Manufacturer: Panasonic Industrial Devices Europe GmbH  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Klein  
 Test Conditions: Tnom: 23°C, Unom: 5V USB from Notebook with 120V AC/DC-Adapter  
 LISN: ESH2-Z5 N  
 Mode: Permanent TX @ 2419MHz  
 Test Date: 2015-03-10  
 Note:

Index 15




Frequency	Quasi-Peak	Quasi-Peak Limit	Quasi-Peak Difference	Quasi-Peak Status
156,75 kHz	60,39 dBµV	65,63 dBµV	-5,25 dB	Pass
240 kHz	53,21 dBµV	62,1 dBµV	-8,89 dB	Pass
Frequency	Average	Average Limit	Average Difference	Average Status
156,75 kHz	33,35 dBµV	55,63 dBµV	-22,29 dB	Pass
240 kHz	22,74 dBµV	52,1 dBµV	-29,36 dB	Pass

**Conducted Emissions**
**EMI voltage test in the ac-mains according to FCC 15B**

Project number: G0M-1502-4538


Manufacturer: Panasonic Industrial Devices Europe GmbH  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Klein  
 Test Conditions: Tnom: 23°C, Unom: 5V USB from Notebook with 120V AC/DC-Adapter  
 LISN: ESH2-Z5 L  
 Mode: Permanent TX @ 2419MHz  
 Test Date: 2015-03-10  
 Note:

Index 16



Frequency	Quasi-Peak	Quasi-Peak Limit	Quasi-Peak Difference	Quasi-Peak Status
172,5 kHz	62,41 dBµV	64,84 dBµV	-2,43 dB	Pass
294,45 kHz	52,58 dBµV	60,4 dBµV	-7,82 dB	Pass
Frequency	Average	Average Limit	Average Difference	Average Status
172,5 kHz	31,99 dBµV	54,84 dBµV	-22,85 dB	Pass
294,45 kHz	46,37 dBµV	50,4 dBµV	-4,03 dB	Pass


**3.6 Test Conditions and Results – Band edge compliance**

<b>Band-edge compliance acc. to FCC 15.247 / IC RSS-210</b>				<b>Verdict: PASS</b>	
EUT requirement rule parts and clause	Reference				
	FCC 15.247(d) / IC RSS-210 A8.5				
Test according to measurement reference	Reference Method				
	FCC KDB Publication No. 558074				
Test frequency range	Tested frequencies				
	$F_{LOW} / F_{HIGH}$				
Measurement mode	Peak				
<b>Limits</b>					
Limit			Condition		
$\leq -20$ dB / 100 kHz			Peak power measurement detector = Peak		
$\leq -30$ dB / 100 kHz			Peak power measurement detector = RMS		
<b>Test setup</b>					
					
<b>Test procedure</b>					
<ol style="list-style-type: none"> <li>EUT set to test mode (Communication tester is used if needed)</li> <li>Span set around lower band edge and detector is set to peak and max hold</li> <li>Resolution bandwidth is set to 100 kHz</li> <li>Markers are set to peak emission levels within frequency band and outside frequency band</li> <li>Band edge attenuation is determined from level difference</li> </ol>					
<b>Test results</b>					
Channel	Frequency [MHz]	Mode	Level [dBc]	Limit [dBc]	Margin [dB]
$F_{LOW}$	2402	Transmit	-41.4	-20	-21.40
$F_{HIGH}$	2480	Transmit	-47.8	-20	-27.80
Comments:					

**Band-edge compliance F<sub>Low</sub>**
**Band-edge compliance acc. to FCC 15.247**

Project Number: G0M-1502-4538

Applicant: Panasonic Industrial Devices Europe GmbH  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Wilfried Treffke  
 Test Conditions: Tnom / Vnom  
 Mode: Tx, BT-LE, 2402 MHz, modulated  
 Test Date: 2015-03-02  
 Verdict: PASS  
 Note 1: 20 dB down method (558074 D01 Meas Guidance)  
 Note 2: lower Band-edge, conducted measurement




Limit: Marker Delta value >20 dB; Result: PASS  
 Date: 2.MAR.2015 13:30:36

**Band-edge compliance F<sub>HIGH</sub>**
**Band-edge compliance acc. to FCC 15.247**

Project Number: G0M-1502-4538


Applicant: Panasonic Industrial Devices Europe GmbH  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Wilfried Treffke  
 Test Conditions: Tnom / Vnom  
 Mode: Tx, BT-LE, 2480 MHz, modulated  
 Test Date: 2015-03-02  
 Verdict: PASS  
 Note 1: 20 dB down method (558074 D01 Meas Guidance)  
 Note 2: upper Band-edge, conducted measurement



Limit: Marker Delta value &gt;20 dB; Result: PASS

Date: 2.MAR.2015 13:33:08

**3.7 Test Conditions and Results – Conducted spurious emissions**


<b>Conducted spurious emissions acc. to FCC 15.247 / IC RSS-210</b>				<b>Verdict: PASS</b>			
EUT requirement rule parts and clause		Reference					
		FCC 15.247(d) / IC RSS-210 A8.5					
Test according to measurement reference		Reference Method					
		FCC KDB Publication No. 558074					
Test frequency range		Tested frequencies					
		10 MHz – 10 <sup>th</sup> Harmonic					
Measurement mode		Peak					
<b>Limits</b>							
Limit				Condition			
≤ -20 dB / 100 kHz				Peak power measurement detector = Peak			
≤ -30 dB /100 kHz				Peak power measurement detector = RMS			
<b>Test setup</b>							
							
<b>Test procedure</b>							
<ol style="list-style-type: none"> <li>1. EUT set to test mode (Communication tester is used if needed)</li> <li>2. Span it set according to measurement range</li> <li>3. Resolution bandwidth is set to 100 kHz and detector to peak and max hold</li> <li>4. Markers are set to peak emission levels within frequency band</li> <li>5. Emission level is determined by second marker on emission peak</li> <li>6. Attenuation is determined from level difference</li> </ol>							
<b>Test results</b>							
Channel	Frequency [MHz]	Mode	Emission [MHz]	Emission Level [dBm]	Peak power [dBm]	Limit [dBm]	Margin [dB]
F <sub>LOW</sub>	2402	Peak	4800.7	-28.7	-3.9	-23.9	-04.80
F <sub>MID</sub>	2440	Peak	4884.8	-27.1	-3.5	-23.5	-03.60
F <sub>HIGH</sub>	2480	Peak	4968.8	-32.0	-2.4	-22.4	-09.60
Comments:							

Conducted spurious emissions – F<sub>Low</sub>

Spurious Emissions acc. to FCC 15.247

Project Number: G0M-1502-4538

Applicant: Panasonic Industrial Devices Europe GmbH  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Wilfried Treffke  
 Test Conditions: Tnom / Vnom  
 Mode: Tx, BT-LE, 2402 MHz, modulated  
 Test Date: 2015-03-02  
 Verdict: PASS  
 Note 1: Spurious in non-restricted frequency bands (558074 D01 Meas Guidance)  
 Note 2: conducted measurement






Conducted spurious emissions – F<sub>MID</sub>

Spurious Emissions acc. to FCC 15.247

Project Number: G0M-1502-4538


Applicant: Panasonic Industrial Devices Europe GmbH  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Wilfried Treffke  
 Test Conditions: Tnom / Vnom  
 Mode: Tx, BT-LE, 2440 MHz, modulated  
 Test Date: 2015-03-02  
 Verdict: PASS  
 Note 1: Spurious in non-restricted frequency bands (558074 D01 Meas Guidance)  
 Note 2: conducted measurement




**Conducted spurious emissions – F<sub>HIGH</sub>**
**Spurious Emissions acc. to FCC 15.247**

Project Number: G0M-1502-4538

Applicant: Panasonic Industrial Devices Europe GmbH  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Wilfried Treffke  
 Test Conditions: Tnom / Vnom  
 Mode: Tx, BT-LE, 2480 MHz, modulated  
 Test Date: 2015-03-02  
 Verdict: PASS  
 Note 1: Spurious in non-restricted frequency bands (558074 D01 Meas Guidance)  
 Note 2: conducted measurement




3.8 Test Conditions and Results – Transmitter radiated emissions

Transmitter radiated emissions acc. to FCC 47 CFR 15.247 / IC RSS-210				Verdict: PASS	
Test according referenced standards		Reference Method			
		FCC 15.247(d) / IC RSS-210 A8.5			
Test according to measurement reference		Reference Method			
		FCC KDB Publication No. 558074 / ANSI C63.4			
Test frequency range		Tested frequencies			
		30 MHz – 10 <sup>th</sup> Harmonic			
Limits					
Frequency range [MHz]	Detector	Limit [ $\mu$ V/m]	Limit [dB $\mu$ V/m]	Limit Distance [m]	
30 – 88	Quasi-Peak	100	40	3	
88 – 216	Quasi-Peak	150	43.5	3	
216 – 960	Quasi-Peak	200	46	3	
960 – 1000	Quasi-Peak	500	54	3	
> 1000	Average	500	54	3	
<p>Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).</p> <p>When average radiated emission measurements are specified, including average emission measurements below 1000 MHz, there also is a limit on the peak level of the radio frequency emissions. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test.</p>					
Test setup					
 <p>The diagram illustrates the test setup. A Semi-anechoic Chamber is shown with a Ground Plane at the bottom. Inside the chamber, an Amplifier Matrix is connected to a Measurement Receiver. The Equipment Under Test (EUT) is placed on a Turn table within the chamber. A vertical antenna is positioned to the left of the chamber, connected to the Amplifier Matrix. The chamber is labeled 'Semi-anechoic Chamber' and the ground plane is labeled 'Ground Plane'. The EUT is labeled 'EUT' and the turn table is labeled 'Turn table'. The Amplifier Matrix is labeled 'Amplifier Matrix' and the Measurement Receiver is labeled 'Measurement Receiver'.</p>					

Test procedure									
1. EUT set to test mode (Communication tester is used if needed) 2. Span it set according to measurement range 3. Resolution bandwidth below 1 GHz is set according to CISPR 16 with peak/quasi-peak detector and RBW of 1 MHz with peak/average detector is used above 1 GHz 4. Markers are set to peak emission levels within restricted bands									
Test results									
Channel	Frequency [MHz]	Mode	Emission [MHz]	Level [dB $\mu$ V/m]	Det.	Pol.	Limit [dB $\mu$ V/m]	Limit dist. [m]*	Margin [dB]
F <sub>LOW</sub>	2402	Transmit	2389	51.94	pk	hor	74.00	3	-22.06
F <sub>LOW</sub>	2402	Transmit	2389	27.89	RMS	hor	54.00	3	-26.11
F <sub>LOW</sub>	2402	Transmit	2389	47.86	pk	ver	74.00	3	-26.14
F <sub>LOW</sub>	2402	Transmit	2389	27.20	RMS	ver	54.00	3	-26.80
F <sub>LOW</sub>	2402	Transmit	4803	47.83	pk	hor	74.00	3	-26.17
F <sub>LOW</sub>	2402	Transmit	4803	39.59	avg	hor	54.00	3	-14.41
F <sub>MID</sub>	2440	Transmit	4879	42.02	pk	ver	74.00	3	-31.98
F <sub>MID</sub>	2440	Transmit	4879	34.29	avg	ver	54.00	3	-19.71
F <sub>MID</sub>	2440	Transmit	4880	47.98	pk	hor	74.00	3	-26.02
F <sub>MID</sub>	2440	Transmit	4880	41.42	avg	hor	54.00	3	-12.58
F <sub>MID</sub>	2440	Transmit	7319	49.74	pk	hor	74.00	1	-24.26
F <sub>MID</sub>	2440	Transmit	7319	40.54	avg	hor	54.00	1	-13.46
F <sub>MID</sub>	2440	Transmit	7319	45.64	pk	ver	74.00	1	-28.36
F <sub>MID</sub>	2440	Transmit	7319	35.75	avg	ver	54.00	1	-18.25
F <sub>MID</sub>	2440	Transmit	12200	49.81	pk	hor	74.00	1	-24.19
F <sub>MID</sub>	2440	Transmit	12200	38.59	avg	hor	54.00	1	-15.41
F <sub>HIGH</sub>	2480	Transmit	2483.5	55.12	pk	hor	74.00	3	-18.88
F <sub>HIGH</sub>	2480	Transmit	2483.5	38.07	RMS	hor	54.00	3	-15.93
F <sub>HIGH</sub>	2480	Transmit	2492.5	55.55	pk	hor	74.00	3	-18.45
F <sub>HIGH</sub>	2480	Transmit	2492.5	28.72	RMS	hor	54.00	3	-25.28
F <sub>HIGH</sub>	2480	Transmit	2492.5	50.15	pk	ver	74.00	3	-23.85
F <sub>HIGH</sub>	2480	Transmit	2492.5	28.69	RMS	ver	54.00	3	-25.31
F <sub>HIGH</sub>	2480	Transmit	7439	53.55	pk	hor	74.00	1	-20.45
F <sub>HIGH</sub>	2480	Transmit	7439	45.06	avg	hor	54.00	1	-08.94
F <sub>HIGH</sub>	2480	Transmit	7440	53.46	pk	ver	74.00	1	-20.54
F <sub>HIGH</sub>	2480	Transmit	7440	44.94	avg	ver	54.00	1	-09.06
Comments: * Physical distance between EUT and measurement antenna.									

**3.9 Test Conditions and Results – Receiver radiated emissions**

Receiver radiated emissions acc. to IC RSS-210			Verdict: PASS	
Test according referenced standards	Reference Method			
	IC RSS-210 A8.5			
Test according to measurement reference	Reference Method			
	ANSI C63.4			
Test frequency range	Tested frequencies			
	30 MHz – 3 <sup>th</sup> Harmonic			
EUT test mode	Receive			
Limits				
Frequency range [MHz]	Detector	Limit [ $\mu\text{V}/\text{m}$ ]	Limit [ $\text{dB}\mu\text{V}/\text{m}$ ]	Limit Distance [m]
30 – 88	Quasi-Peak	100	40	3
88 – 216	Quasi-Peak	150	43.5	3
216 – 960	Quasi-Peak	200	46	3
960 – 1000	Quasi-Peak	500	54	3
> 1000	Average	500	54	3
Test setup				
				

**Test procedure**

1. EUT set to receive mode (Communication tester is used if needed)
2. Span it set according to measurement range
3. Resolution bandwidth below 1 GHz is set according to CISPR 16 with peak/quasi-peak detector and RBW of 1 MHz with peak/average detector is used above 1 GHz
4. Markers are set to peak emission levels

**Test results**

Channel	Frequency [MHz]	Emission [MHz]	Emission Level [dB $\mu$ V/m]	Pol.	Det.	Limit [dB $\mu$ V/m]	Margin [dB $\mu$ V/m]
F <sub>MID</sub>	2442	854.4	23.35	ver	pk	46.00	-22.65 dB
F <sub>MID</sub>	2442	7416	48.93	ver	pk	53.98	-05.05 dB
F <sub>MID</sub>	2442	7968	49.22	hor	pk	53.98	-04.76 dB

Comments:


## ANNEX A Transmitter radiated spurious emissions

### Spurious emissions according to FCC 15.247

Project number: G0M-1502-4538

Applicant:	Panasonic Industrial Devices
EUT Name:	Bluetooth Smart Module
Model:	ENW89847A1KF
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 25°C, Vnom: 5.0 V DC
Antenna:	Rohde & Schwarz HK 116, Horizontal
Measurement distance:	3 m
Mode:	TX; BT-LE; 2402 MHz
Test Date:	2015-03-04
Note:	

Index 1




**Spurious emissions according to FCC 15.247**

Project number: G0M-1502-4538

Applicant:	Panasonic Industrial Devices
EUT Name:	Bluetooth Smart Module
Model:	ENW89847A1KF
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 25°C, Vnom: 5.0 V DC
Antenna:	Rohde & Schwarz HK 116, Vertical
Measurement distance:	3 m
Mode:	TX; BT-LE; 2402 MHz
Test Date:	2015-03-04
Note:	

Index 2






**Spurious emissions according to FCC 15.247**

Project number: G0M-1502-4538

Applicant:	Panasonic Industrial Devices
EUT Name:	Bluetooth Smart Module
Model:	ENW89847A1KF
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 25°C, Vnom: 5.0 V DC
Antenna:	Rohde & Schwarz HL 223, Horizontal
Measurement distance:	3 m
Mode:	TX; BT-LE; 2402 MHz
Test Date:	2015-03-04
Note:	

Index 3




**Spurious emissions according to FCC 15.247**

Project number: G0M-1502-4538

Applicant:	Panasonic Industrial Devices
EUT Name:	Bluetooth Smart Module
Model:	ENW89847A1KF
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 25°C, Vnom: 5.0 V DC
Antenna:	Rohde & Schwarz HL 223, Vertical
Measurement distance:	3 m
Mode:	TX; BT-LE; 2402 MHz
Test Date:	2015-03-04
Note:	

Index 4




**Spurious emissions according to FCC 15.247**

Project number: GOM-1502-4538

Applicant: Panasonic Industrial Devices  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Treffke  
 Test Conditions: Tnom: 25°C, Vnom: 5.0 V DC  
 Antenna: Schwarzbeck BBHA 9120D, Horizontal  
 Measurement distance: 3 m  
 Mode: TX; BT-LE; 2402 MHz  
 Test Date: 2015-03-04  
 Note:

Index 5




**Spurious emissions according to FCC 15.247**

Project number: GOM-1502-4538

Applicant: Panasonic Industrial Devices  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Treffke  
 Test Conditions: Tnom: 25°C, Vnom: 5.0 V DC  
 Antenna: Schwarzbeck BBHA 9120D, Horizontal  
 Measurement distance: 3 m  
 Mode: TX; BT-LE; 2402 MHz  
 Test Date: 2015-03-04  
 Note: lower bandedge

Index 6



Frequency	Peak	Peak Limit	Peak Difference	Peak Status
2.389 GHz	51.94 dBµV/m	74 dBµV/m	-22.06 dB	Pass


Frequency	RMS	RMS Limit	RMS Difference	RMS Status
2.389 GHz	27.89 dBµV/m	54 dBµV/m	-26.11 dB	Pass

**Spurious emissions according to FCC 15.247**

Project number: G0M-1502-4538

Applicant: Panasonic Industrial Devices  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Treffke  
 Test Conditions: Tnom: 25°C, Vnom: 5.0 V DC  
 Antenna: Schwarzbeck BBHA 9120D, Vertical  
 Measurement distance: 3 m  
 Mode: TX; BT-LE; 2402 MHz  
 Test Date: 2015-03-04  
 Note:

Index 7




**Spurious emissions according to FCC 15.247**

Project number: GOM-1502-4538

Applicant: Panasonic Industrial Devices  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Treffke  
 Test Conditions: Tnom: 25°C, Vnom: 5.0 V DC  
 Antenna: Schwarzbeck BBHA 9120D, Vertical  
 Measurement distance: 3 m  
 Mode: TX; BT-LE; 2402 MHz  
 Test Date: 2015-03-04  
 Note: lower bandedge

Index 8



Frequency	Peak	Peak Limit	Peak Difference	Peak Status
2.389 GHz	47.86 dBµV/m	74 dBµV/m	-26.14 dB	Pass


Frequency	RMS	RMS Limit	RMS Difference	RMS Status
2.389 GHz	27.2 dBµV/m	54 dBµV/m	-26.8 dB	Pass

**Spurious emissions according to FCC 15.247**

Project number: G0M-1502-4538

Applicant: Panasonic Industrial Devices  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Treffke  
 Test Conditions: Tnom: 25°C, Vnom: 5.0 V DC  
 Antenna: Schwarzbeck BBHA 9120D, Horizontal  
 Measurement distance: 1 m converted to 3m  
 Mode: TX; BT-LE; 2402 MHz  
 Test Date: 2015-03-04  
 Note:

Index 17




Frequency	Peak	Peak Limit	Peak Difference	Status
4.803 GHz	47.83 dBµV/m	74 dBµV/m	-26.17 dB	Pass
Frequency	Average	Average Limit	Average Difference	Average Status
4.803 GHz	39.59 dBµV/m	54 dBµV/m	-14.41 dB	Pass

**Spurious emissions according to FCC 15.247**

Project number: GOM-1502-4538

Applicant:	Panasonic Industrial Devices
EUT Name:	Bluetooth Smart Module
Model:	ENW89847A1KF
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 25°C, Vnom: 5.0 V DC
Antenna:	Schwarzbeck BBHA 9120D, Vertical
Measurement distance:	1 m converted to 3m
Mode:	TX; BT-LE; 2402 MHz
Test Date:	2015-03-04
Note:	

Index 18






**Spurious emissions according to FCC 15.247**

Project number: G0M-1502-4538

Applicant:	Panasonic Industrial Devices
EUT Name:	Bluetooth Smart Module
Model:	ENW89847A1KF
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 25°C, Vnom: 5.0 V DC
Antenna:	Schwarzbeck BBHA 9120D, Horizontal
Measurement distance:	1 m converted to 3m
Mode:	TX; BT-LE; 2402 MHz
Test Date:	2015-03-04
Note:	

Index 25




**Spurious emissions according to FCC 15.247**

Project number: G0M-1502-4538

Applicant:	Panasonic Industrial Devices
EUT Name:	Bluetooth Smart Module
Model:	ENW89847A1KF
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 25°C, Vnom: 5.0 V DC
Antenna:	Schwarzbeck BBHA 9120D, Vertical
Measurement distance:	1 m converted to 3m
Mode:	TX; BT-LE; 2402 MHz
Test Date:	2015-03-04
Note:	

Index 27




**Spurious emissions according to FCC 15.247**

Project number: G0M-1502-4538

Applicant:	Panasonic Industrial Devices
EUT Name:	Bluetooth Smart Module
Model:	ENW89847A1KF
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 25°C, Vnom: 5.0 V DC
Antenna:	Rohde & Schwarz HL 025, Horizontal
Measurement distance:	1 m converted to 3m
Mode:	TX; BT-LE; 2402 MHz
Test Date:	2015-03-04
Note:	

Index 26




**Spurious emissions according to FCC 15.247**

Project number: G0M-1502-4538

Applicant:	Panasonic Industrial Devices
EUT Name:	Bluetooth Smart Module
Model:	ENW89847A1KF
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 25°C, Vnom: 5.0 V DC
Antenna:	Rohde & Schwarz HL 025, Vertical
Measurement distance:	1 m converted to 3m
Mode:	TX; BT-LE; 2402 MHz
Test Date:	2015-03-04
Note:	

Index 28




**Spurious emissions according to FCC 15.247**

Project number: GOM-1502-4538

Applicant: Panasonic Industrial Devices  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Treffke  
 Test Conditions: Tnom: 25°C, Vnom: 5.0 V DC  
 Antenna: Schwarzbeck BBHA 9120D, Horizontal  
 Measurement distance: 3 m  
 Mode: TX; BT-LE; 2440 MHz  
 Test Date: 2015-03-04  
 Note:

Index 11




**Spurious emissions according to FCC 15.247**

Project number: G0M-1502-4538

Applicant: Panasonic Industrial Devices  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Treffke  
 Test Conditions: Tnom: 25°C, Vnom: 5.0 V DC  
 Antenna: Schwarzbeck BBHA 9120D, Vertical  
 Measurement distance: 3 m  
 Mode: TX; BT-LE; 2440 MHz  
 Test Date: 2015-03-04  
 Note:

Index 12




**Spurious emissions according to FCC 15.247**

Project number: G0M-1502-4538

Applicant: Panasonic Industrial Devices  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Treffke  
 Test Conditions: Tnom: 25°C, Vnom: 5.0 V DC  
 Antenna: Schwarzbeck BBHA 9120D, Horizontal  
 Measurement distance: 1 m converted to 3m  
 Mode: TX; BT-LE; 2440 MHz  
 Test Date: 2015-03-04  
 Note:

Index 21



Frequency	Peak	Peak Limit	Peak Difference	Status
4.88 GHz	47.98 dBµV/m	74 dBµV/m	-26.02 dB	Pass
7.319 GHz	49.74 dBµV/m	74 dBµV/m	-24.26 dB	Pass


Frequency	Average	Average Limit	Average Difference	Average Status
4.88 GHz	41.42 dBµV/m	54 dBµV/m	-12.58 dB	Pass
7.319 GHz	40.54 dBµV/m	54 dBµV/m	-13.46 dB	Pass

**Spurious emissions according to FCC 15.247**

Project number: G0M-1502-4538

Applicant: Panasonic Industrial Devices  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Treffke  
 Test Conditions: Tnom: 25°C, Vnom: 5.0 V DC  
 Antenna: Schwarzbeck BBHA 9120D, Vertical  
 Measurement distance: 1 m converted to 3m  
 Mode: TX; BT-LE; 2440 MHz  
 Test Date: 2015-03-04  
 Note:

Index 22



Frequency	Peak	Peak Limit	Peak Difference	Status
4.879 GHz	42.02 dBµV/m	74 dBµV/m	-31.98 dB	Pass
7.319 GHz	45.64 dBµV/m	74 dBµV/m	-28.36 dB	Pass

Frequency	Average	Average Limit	Average Difference	Average Status
4.879 GHz	34.29 dBµV/m	54 dBµV/m	-19.71 dB	Pass
7.319 GHz	35.75 dBµV/m	54 dBµV/m	-18.25 dB	Pass

Test Report No.: G0M-1502-4538-TFC247BL-V01

 Eurofins Product Service GmbH  
 Storkower Str. 38c, D-15526 Reichenwalde, Germany




**Spurious emissions according to FCC 15.247**

Project number: G0M-1502-4538

Applicant: Panasonic Industrial Devices  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Treffke  
 Test Conditions: Tnom: 25°C, Vnom: 5.0 V DC  
 Antenna: Schwarzbeck BBHA 9120D, Horizontal  
 Measurement distance: 1 m converted to 3m  
 Mode: TX; BT-LE; 2440 MHz  
 Test Date: 2015-03-04  
 Note:

Index 29




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
12.2 GHz	49.81 dBµV/m	74 dBµV/m	-24.19 dB	Pass
Frequency	Average	Average Limit	Average Difference	Average Status
12.2 GHz	38.59 dBµV/m	54 dBµV/m	-15.41 dB	Pass

**Spurious emissions according to FCC 15.247**

Project number: G0M-1502-4538

Applicant:	Panasonic Industrial Devices
EUT Name:	Bluetooth Smart Module
Model:	ENW89847A1KF
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 25°C, Vnom: 5.0 V DC
Antenna:	Schwarzbeck BBHA 9120D, Vertical
Measurement distance:	1 m converted to 3m
Mode:	TX; BT-LE; 2440 MHz
Test Date:	2015-03-04
Note:	

Index 31




**Spurious emissions according to FCC 15.247**

Project number: G0M-1502-4538

Applicant:	Panasonic Industrial Devices
EUT Name:	Bluetooth Smart Module
Model:	ENW89847A1KF
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 25°C, Vnom: 5.0 V DC
Antenna:	Rohde & Schwarz HL 025, Horizontal
Measurement distance:	1 m converted to 3m
Mode:	TX; BT-LE; 2440 MHz
Test Date:	2015-03-04
Note:	

Index 30




**Spurious emissions according to FCC 15.247**

Project number: G0M-1502-4538

Applicant:	Panasonic Industrial Devices
EUT Name:	Bluetooth Smart Module
Model:	ENW89847A1KF
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 25°C, Vnom: 5.0 V DC
Antenna:	Rohde & Schwarz HL 025, Vertical
Measurement distance:	1 m converted to 3m
Mode:	TX; BT-LE; 2440 MHz
Test Date:	2015-03-04
Note:	

Index 32




**Spurious emissions according to FCC 15.247**

Project number: GOM-1502-4538

Applicant: Panasonic Industrial Devices  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Treffke  
 Test Conditions: Tnom: 25°C, Vnom: 5.0 V DC  
 Antenna: Schwarzbeck BBHA 9120D, Horizontal  
 Measurement distance: 3 m  
 Mode: TX; BT-LE; 2480 MHz  
 Test Date: 2015-03-04  
 Note:

Index 13




**Spurious emissions according to FCC 15.247**

Project number: G0M-1502-4538

Applicant: Panasonic Industrial Devices  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Treffke  
 Test Conditions: Tnom: 25°C, Vnom: 5.0 V DC  
 Antenna: Schwarzbeck BBHA 9120D, Horizontal  
 Measurement distance: 3 m  
 Mode: TX; BT-LE; 2480 MHz  
 Test Date: 2015-03-04  
 Note: upper bandedge

Index 14



Frequency	Peak	Peak Limit	Peak Difference	Peak Status
2.4835 GHz	55.12 dBµV/m	74 dBµV/m	-18.88 dB	Pass
2.4925 GHz	55.55 dBµV/m	74 dBµV/m	-18.45 dB	Pass


Frequency	RMS	RMS Limit	RMS Difference	RMS Status
2.4835 GHz	38.07 dBµV/m	54 dBµV/m	-15.93 dB	Pass
2.4925 GHz	28.72 dBµV/m	54 dBµV/m	-25.28 dB	Pass

**Spurious emissions according to FCC 15.247**

Project number: GOM-1502-4538

Applicant: Panasonic Industrial Devices  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Treffke  
 Test Conditions: Tnom: 25°C, Vnom: 5.0 V DC  
 Antenna: Schwarzbeck BBHA 9120D, Vertical  
 Measurement distance: 3 m  
 Mode: TX; BT-LE; 2480 MHz  
 Test Date: 2015-03-04  
 Note:

Index 15




**Spurious emissions according to FCC 15.247**

Project number: G0M-1502-4538

Applicant: Panasonic Industrial Devices  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Treffke  
 Test Conditions: Tnom: 25°C, Vnom: 5.0 V DC  
 Antenna: Schwarzbeck BBHA 9120D, Vertical  
 Measurement distance: 3 m  
 Mode: TX; BT-LE; 2480 MHz  
 Test Date: 2015-03-04  
 Note: upper bandedge

Index 16



Frequency	Peak	Peak Limit	Peak Difference	Peak Status
2.4925 GHz	50.15 dBµV/m	74 dBµV/m	-23.85 dB	Pass
Frequency	RMS	RMS Limit	RMS Difference	RMS Status
2.4925 GHz	28.69 dBµV/m	54 dBµV/m	-25.31 dB	Pass




**Spurious emissions according to FCC 15.247**

Project number: G0M-1502-4538

Applicant: Panasonic Industrial Devices  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Treffke  
 Test Conditions: Tnom: 25°C, Vnom: 5.0 V DC  
 Antenna: Schwarzbeck BBHA 9120D, Horizontal  
 Measurement distance: 1 m converted to 3m  
 Mode: TX; BT-LE; 2480 MHz  
 Test Date: 2015-03-04  
 Note:

Index 23




Frequency	Peak	Peak Limit	Peak Difference	Status
7.439 GHz	53.55 dBµV/m	74 dBµV/m	-20.45 dB	Pass
Frequency	Average	Average Limit	Average Difference	Average Status
7.439 GHz	45.06 dBµV/m	54 dBµV/m	-8.94 dB	Pass

**Spurious emissions according to FCC 15.247**

Project number: G0M-1502-4538

Applicant: Panasonic Industrial Devices  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Treffke  
 Test Conditions: Tnom: 25°C, Vnom: 5.0 V DC  
 Antenna: Schwarzbeck BBHA 9120D, Vertical  
 Measurement distance: 1 m converted to 3m  
 Mode: TX; BT-LE; 2480 MHz  
 Test Date: 2015-03-04  
 Note:

Index 24




Frequency	Peak	Peak Limit	Peak Difference	Status
7.44 GHz	53.46 dBµV/m	74 dBµV/m	-20.54 dB	Pass
Frequency	Average	Average Limit	Average Difference	Average Status
7.44 GHz	44.94 dBµV/m	54 dBµV/m	-9.06 dB	Pass

**Spurious emissions according to FCC 15.247**

Project number: G0M-1502-4538

Applicant:	Panasonic Industrial Devices
EUT Name:	Bluetooth Smart Module
Model:	ENW89847A1KF
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 25°C, Vnom: 5.0 V DC
Antenna:	Schwarzbeck BBHA 9120D, Horizontal
Measurement distance:	1 m converted to 3m
Mode:	TX; BT-LE; 2480 MHz
Test Date:	2015-03-04
Note:	

Index 33




**Spurious emissions according to FCC 15.247**

Project number: G0M-1502-4538

Applicant:	Panasonic Industrial Devices
EUT Name:	Bluetooth Smart Module
Model:	ENW89847A1KF
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 25°C, Vnom: 5.0 V DC
Antenna:	Schwarzbeck BBHA 9120D, Vertical
Measurement distance:	1 m converted to 3m
Mode:	TX; BT-LE; 2480 MHz
Test Date:	2015-03-04
Note:	

Index 35




**Spurious emissions according to FCC 15.247**

Project number: G0M-1502-4538

Applicant:	Panasonic Industrial Devices
EUT Name:	Bluetooth Smart Module
Model:	ENW89847A1KF
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 25°C, Vnom: 5.0 V DC
Antenna:	Rohde & Schwarz HL 025, Horizontal
Measurement distance:	1 m converted to 3m
Mode:	TX; BT-LE; 2480 MHz
Test Date:	2015-03-04
Note:	

Index 34




**Spurious emissions according to FCC 15.247**

Project number: G0M-1502-4538

Applicant:	Panasonic Industrial Devices
EUT Name:	Bluetooth Smart Module
Model:	ENW89847A1KF
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 25°C, Vnom: 5.0 V DC
Antenna:	Rohde & Schwarz HL 025, Vertical
Measurement distance:	1 m converted to 3m
Mode:	TX; BT-LE; 2480 MHz
Test Date:	2015-03-04
Note:	

Index 36




## ANNEX B Receiver radiated spurious emissions

### Spurious emissions according to RSS-GEN

Project number: G0M-1502-4538

Applicant:	Panasonic Industrial Devices
EUT Name:	Bluetooth Smart Module
Model:	ENW89847A1KF
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 25°C, Vnom: 5.0 V DC
Antenna:	Rohde & Schwarz HK 116, Horizontal
Measurement distance:	3 m
Mode:	RX; BT-LE; 2440 MHz
Test Date:	2015-03-04
Note:	

Index 7




**Spurious emissions according to RSS-GEN**

Project number: G0M-1502-4538

Applicant:	Panasonic Industrial Devices
EUT Name:	Bluetooth Smart Module
Model:	ENW89847A1KF
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 25°C, Vnom: 5.0 V DC
Antenna:	Rohde & Schwarz HK 116, Vertical
Measurement distance:	3 m
Mode:	RX; BT-LE; 2440 MHz
Test Date:	2015-03-04
Note:	

Index 8






**Spurious emissions according to RSS-GEN**

Project number: G0M-1502-4538

Applicant:	Panasonic Industrial Devices
EUT Name:	Bluetooth Smart Module
Model:	ENW89847A1KF
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 25°C, Vnom: 5.0 V DC
Antenna:	Rohde & Schwarz HL 223, Horizontal
Measurement distance:	3 m
Mode:	RX; BT-LE; 2440 MHz
Test Date:	2015-03-04
Note:	

Index 5




**Spurious emissions according to RSS-GEN**

Project number: GOM-1502-4538

Applicant: Panasonic Industrial Devices  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Treffke  
 Test Conditions: Tnom: 25°C, Vnom: 5.0 V DC  
 Antenna: Rohde & Schwarz HL 223, Vertical  
 Measurement distance: 3 m  
 Mode: RX; BT-LE; 2440 MHz  
 Test Date: 2015-03-04  
 Note:

Index 6




Frequency	Peak	Peak Limit	Peak Difference	Status
854.4 MHz	23.35 dBµV/m	46 dBµV/m	-22.65 dB	Pass

**Spurious emissions according to RSS-GEN**

Project number: G0M-1502-4538

Applicant:	Panasonic Industrial Devices
EUT Name:	Bluetooth Smart Module
Model:	ENW89847A1KF
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 25°C, Vnom: 5.0 V DC
Antenna:	Schwarzbeck BBHA 9120D, Horizontal
Measurement distance:	3 m
Mode:	RX; BT-LE; 2440 MHz
Test Date:	2015-03-04
Note:	

Index 9




**Spurious emissions according to RSS-GEN**

Project number: G0M-1502-4538

Applicant:	Panasonic Industrial Devices
EUT Name:	Bluetooth Smart Module
Model:	ENW89847A1KF
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 25°C, Vnom: 5.0 V DC
Antenna:	Schwarzbeck BBHA 9120D, Vertical
Measurement distance:	3 m
Mode:	RX; BT-LE; 2440 MHz
Test Date:	2015-03-04
Note:	

Index 11




**Spurious emissions according to RSS-GEN**

Project number: GOM-1502-4538

Applicant: Panasonic Industrial Devices  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Treffke  
 Test Conditions: Tnom: 25°C, Vnom: 5.0 V DC  
 Antenna: Schwarzbeck BBHA 9120D, Horizontal  
 Measurement distance: 3 m  
 Mode: RX; BT-LE; 2440 MHz  
 Test Date: 2015-03-04  
 Note:

Index 10




Frequency	Peak	Peak Limit	Peak Difference	Status
7.968 GHz	49.22 dBµV/m	53.98 dBµV/m	-4.76 dB	Pass

**Spurious emissions according to RSS-GEN**

Project number: GOM-1502-4538

Applicant: Panasonic Industrial Devices  
 EUT Name: Bluetooth Smart Module  
 Model: ENW89847A1KF  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Treffke  
 Test Conditions: Tnom: 25°C, Vnom: 5.0 V DC  
 Antenna: Schwarzbeck BBHA 9120D, Vertical  
 Measurement distance: 3 m  
 Mode: RX; BT-LE; 2440 MHz  
 Test Date: 2015-03-04  
 Note:

Index 12



Frequency	Peak	Peak Limit	Peak Difference	Status
7.416 GHz	48.93 dBµV/m	53.98 dBµV/m	-5.05 dB	Pass