



Test report No:
 NIE: 63175RRF.005


Test Report

USA FCC Part 15.247, 15.209 CANADA RSS-247, RSS-Gen

Radio Frequency Devices. Operation within the bands 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz.

Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices.

General Requirements and Information for the Certification of Radio Apparatus.

(*) Identification of item tested	Automotive Infotainment System
(*) Trademark	BMW
(*) Model and /or type reference	MGU21
Other identification of the product	HW version: 1.3 SW version: 20w27.4-1-15 FCC ID: T8GMGU21 IC: 6434A-MGU21
(*) Features	USB 2.0 (including support for Apple Devices), Bluetooth, WLAN Modul 2.4 / 5 GHz, GNSS, AR-CAM input, Video-out APIX3, CAN, 100Base-T1 and 1000Base-T1
Applicant	HARMAN BECKER AUTOMOTIVE SYSTEMS GMBH BECKER-GOERING-STR. 16; 76307 KARLSBAD, GERMANY
Test method requested, standard	USA FCC Part 15.247 (10-1-19) Edition: Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz. USA FCC Part 15.209 (10-1-19) Edition: Radiated emission limits; general requirements. CANADA RSS-247 Issue 2 (February 2017). CANADA RSS-Gen Issue 5 Amendment 1 (March 2019). Guidance for Performing Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid Systems Devices Operating Under Section 15.247 of the FCC Rules. 558074 D01 Meas Guidance v05r02 dated April 2, 2019. ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.
Summary	IN COMPLIANCE
Approved by (name / position & signature)	José Carlos Luque RF Lab. Supervisor 
Date of issue	2020-09-04
Report template No	FDT08_22 (*) "Data provided by the client"

Index

Competences and guarantees	3
General conditions.....	3
Uncertainty.....	3
Data provided by the client	3
Usage of samples	3
Test sample description.....	5
Identification of the client	6
Testing period and place	7
Document history.....	7
Environmental conditions	7
Remarks and comments.....	8
Testing verdicts.....	9
Summary	9
Appendix A: Test results. Bluetooth EDR (GFSK, Pi/4-DQPSK, 8DPSK)	10
Appendix B: Test results. 802.11 bgn20 1x1.....	78

Competences and guarantees

DEKRA Testing and Certification S.A.U. is a testing laboratory accredited by the National Accreditation Body (ENAC -Entidad Nacional de Acreditación), to perform the tests indicated in the Certificate No. 51/LE 147.

DEKRA Testing and Certification is a FCC-recognized accredited testing laboratory with appropriate scope of accreditation that include testing performed in this test report.

DEKRA Testing and Certification is an ISED-recognized accredited testing laboratory with appropriate scope of accreditation that include testing performed in this test report.

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification S.A.U. has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification S.A.U. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification S.A.U. at the time of performance of the test.

DEKRA Testing and Certification S.A.U. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification S.A.U.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification S.A.U.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification S.A.U. and the Accreditation Bodies.

Uncertainty

Uncertainty (factor $k=2$) was calculated according to the DEKRA Testing and Certification S.A.U. internal document PODT000.

Data provided by the client

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item tested", "Trademark", "Model and/or type reference tested").
2. The sample of the model MGU21 is an automotive infotainment System.

MGU Head-Unit. The main functionalities are: Navigation, USB, voice recognition and several interfaces to the vehicle and Bluetooth / WLAN.

The Head-unit provides different interfaces like: AR-CAM input, Videoout APIX3 (for the connection of an external Display), 3 USB interfaces (including support for Apple devices), CAN, 100Base-T1 and 1000Base-T1.

DEKRA Testing and Certification S.A.U. declines any responsibility with respect to the information provided by the client and that may affect the validity of result.

Usage of samples

Samples undergoing test have been selected by: The client.

- Sample S/01 is composed of the following elements:

Control N°	Description	Model	Serial N°	Date of reception
63175C/001	Automotive infotainment System	MGU21	B382C00L7512617	2020/05/25

Auxiliary elements used with the Sample S/01:

Control N°	Description	Model	Serial N°	Date of reception
63175C/010	OABR Cable	--	--	2020/05/25
63175C/021	SMA Adapter Cable	--	--	2020/05/25
63175C/017	Ethernet Cable	--	--	2020/05/25
63175C/003	OABR Converter Board	--	--	2020/05/25
63175C/006	Ethernet/USB Adapter	EU-4306	EU430685MA02183	2020/05/25

Sample S/01 has undergone the following test(s): All Conducted tests indicated in the Appendix A.

- Sample S/02 is composed of the following elements:

Control N°	Description	Model	Serial N°	Date of reception
63175C/001	Automotive infotainment System	MGU21	B382C00L7512617	2020/05/25

Auxiliary elements used with the Sample S/02:

Control N°	Description	Model	Serial N°	Date of reception
63175C/003	OABR Converter Board	--	--	2020/05/25
63175C/008	Power Cable DC for OABR board	--	--	2020/05/25
63175C/010	OABR Cable	--	--	2020/05/25
63175C/013	APIX Cable	--	--	2020/05/25
63175C/018	Power Cable DC for headunit	--	--	2020/05/25
63175C/027	GNSS Antenna	Magma AA.171	171TT17311936	2020/06/02

Sample S/02 has undergone the following test(s): All Radiated tests indicated in the Appendix B.

Test sample description

Ports..... :	Port name and description	Cable					
		Specified max length [m]	Attached during test	Shielded	Coupled to patient ⁽³⁾		
	BT/WIFI connector – CONM 4POL ROS BMW209-40MT1-A PCN2944		<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>		
	USB1 connector – CONM-SM 4POL ROS D4S20Y-40MA5-B		<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>		
	USB2 connector – CONM-SM 4POL ROS D4S20Y-40MA5-C		<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>		
	USB3 connector – CONM-SM 4POL ROS D4S20Y-40MA5-E		<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>		
	APIX3 connector – CONM-SM 4+2POL ROS 99S22A-40MA5-D		<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
	Car Main-connector – CONM 16POL TYC 2300483-s		<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
	AR-CAM connector – CONM 1POL ROS 59S2FT-40MA5-K		<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>		
	Ethernet BroadR-Reach , 100 BASE-T1		<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
	Ethernet , 1000 BASE-T1		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
GNSS connector		<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>			
Supplementary information to the ports..... :							
Rated power supply	Voltage and Frequency		Reference poles				
			L1	L2	L3	N	PE
	<input type="checkbox"/>	AC:	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	AC:	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	DC:					
<input type="checkbox"/>	DC:						
Rated Power							
Clock frequencies.....							
Other parameters							
Software version	20w27.4-1-15						
Hardware version	1.3						

Dimensions in cm (W x H x D)			
Mounting position	<input type="checkbox"/>	Table top equipment	
	<input type="checkbox"/>	Wall/Ceiling mounted equipment	
	<input type="checkbox"/>	Floor standing equipment	
	<input type="checkbox"/>	Hand-held equipment	
	<input checked="" type="checkbox"/>	Other: automotive dashboard	
Modules/parts	Module/parts of test item	Type	Manufacturer
Accessories (not part of the test item)	Description	Type	Manufacturer
Documents as provided by the applicant	Description	File name	Issue date

⁽³⁾ Only for Medical Equipment

Identification of the client

HARMAN BECKER AUTOMOTIVE SYSTEMS GMBH
 BECKER-GOERING-STR. 16; 76307 KARLSBAD, GERMANY

Testing period and place

Test Location	DEKRA Testing and Certification S.A.U.
Date (start)	2020-06-05
Date (finish)	2020-08-03

Document history

Report number	Date	Description
63175RRF.005	2020-09-04	First release

Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar

In the semianechoic chamber, the following limits were not exceeded during the test.

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar

In the chamber for conducted measurements, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar

Remarks and comments

The tests have been performed by the technical personnel: Alfonso Gutiérrez, Javier Miguel Nadales, José Gabriel Pendón, Nicolás Salguero, Verónica García, Daniel Mejías, Antonio Ruiz and Miguel Ángel Torres.

Used instrumentation:

Conducted Measurements:

		Last Calibration	Due Calibration
1.	Shielded Room ETS LINDGREN S101	N.A.	N.A.
2.	DC Power Supply 40V/40A Rohde & Schwarz NGPE40	N.A.	N.A.
3.	Digital Multimeter FLUKE 179	2019/09	2020/09
4.	Signal and Spectrum Analyzer 10 Hz - 40 GHz ROHDE AND SCHWARZ FSV40	2019/09	2021/09

Radiated Measurements:

		Last Calibration	Due Calibration
1.	Semianechoic Absorber Lined Chamber FRANKONIA SAC-3	N.A.	N.A.
2.	Shielded Room FRANKONIA	N.A.	N.A.
3.	Biconical/Log Antenna 30 MHz - 6 GHz ETS LINDGREN 3142E	2018/07	2021/07
4.	RF Pre-amplifier 40 dB, 10 MHz - 6 GHz BONN ELEKTRONIK BLNA 0160-01N	2019/09	2020/09
5.	EMI Test Receiver 20Hz-26.5GHz ROHDE AND SCHWARZ ESU26	2020/05	2022/05
6.	Horn Antenna 1-18GHz SCHWARZBECK MESS- ELEKTRONIK BBHA 9120 D	2018/06	2021/06
7.	Broadband Horn Antenna 18 - 40 GHz SCHWARZBECK MESS-ELEKTRONIK BBHA 9170	2018/07	2021/07
8.	Pre-amplifier, G>55dB 1-18GHz NARDA AMF-7D-01001800-22-10P	2020/05	2021/05
9.	Low Noise Amplifier G>30dB, 18 - 40 GHz BONN ELEKTRONIK BLMA 1840-1M	2019/02	2021/02
10.	EMI Test Receiver 20Hz-40GHz ROHDE AND SCHWARZ ESU40	2019/09	2021/09
11.	DC Power Supply 150V/22A, AGILENT TECHNOLOGIES N8740A	N.A.	N.A.
12.	Digital Multimeter FLUKE 179	2020/06	2021/06

Testing verdicts

Not applicable:	N/A
Pass:	P
Fail:	F
Not measured:	N/M

Summary

1. Bluetooth EDR

FCC PART 15 PARAGRAPH / RSS-247			
Requirement – Test case		Verdict	Remark
15.247 (a) (1) / RSS-247 5.1. (b)	20 dB Bandwidth and Carrier frequency separation	P	
15.247 (a)(1)(iii) / RSS-247 Clause 5.1 (d)	Number of hopping channels	P	
15.247 (a)(1)(iii) / RSS-247 Clause 5.1 (d)	Time of occupancy (Dwell Time)	P	
15.247 (b) / RSS-247 5.4. (b)	Maximum peak output power and antenna gain	P	
15.247 (d) / RSS-247 5.5.	Band-edge emissions compliance (Transmitter)	P	
15.247 (d) / RSS-247 5.5.	Emission limitations radiated (Transmitter)	P	
<u>Supplementary information and remarks:</u> None.			

2. WLAN 2.4 GHz (802.11 b/g/n20 1x1).

FCC PART 15 PARAGRAPH / RSS-247			
Requirement – Test case		Verdict	Remark
15.247 (a) (2) / RSS-247 5.2. (a)	6 dB Bandwidth	P	
15.247 (b) / RSS-247 5.4. (d)	Maximum output power and antenna gain	P	
15.247 (d) / RSS-247 5.5.	Band-edge emissions compliance (Transmitter)	P	
15.247 (e) / RSS-247 5.2. (b)	Power spectral density	P	
15.247 (d) / RSS-247 5.5.	Emission limitations radiated (Transmitter)	P	
<u>Supplementary information and remarks:</u> None.			

Appendix A: Test results. Bluetooth EDR (GFSK, Pi/4-DQPSK, 8DPSK)

INDEX

TEST CONDITIONS	12
FCC 15.247 (a) (1) / RSS-247 5.1. (b) 20 dB Bandwidth and Carrier frequency separation	15
FCC 15.247 (a)(1)(iii) / RSS-247 5.1 (d) Number of hopping channels	25
FCC 15.247 (a)(1)(iii) / RSS-247 5.1 (d) Time of occupancy (Dwell Time).....	28
FCC 15.247 (b) / RSS-247 5.4 (b) Maximum peak output power and antenna gain	34
FCC 15.247 (d) / RSS-247 5.5. Band-edge emissions compliance (Transmitter)	40
FCC 15.247 (d) / RSS-247 5.5. Emission limitations radiated. (Transmitter).....	47

TEST CONDITIONS

POWER SUPPLY (V):

V nominal:	12 Vdc.
Type of Power Supply:	DC External (Car Battery).

ANTENNA:

Type of Antenna:	External antenna.
Maximum Declared Antenna Gain:	-6.2 dBi (Antenna gain plus antenna cable loss).

TEST FREQUENCIES:

Low Channel:	2402 MHz
Middle Channel:	2441 MHz
High Channel:	2480 MHz

CONDUCTED MEASUREMENTS:

The equipment under test was set up in a shielded room and it is connected to the spectrum analyser using a low loss RF cable. The reading of the spectrum analyser is corrected taking into account the cable loss.



The DC supply voltage is applied using an external calibrated power supply with a multimeter.

RADIATED MEASUREMENTS:


All radiated tests were performed in a semi-anechoic chamber. The measurement antenna (Bilog antenna for the range between 30 MHz to 1000 MHz) and 1 GHz-18 GHz Double ridge horn antenna is situated at a distance of 3 m and a distance of 1m for the frequency range 17 GHz-26 GHz (18 GHz-40 GHz horn antenna).

For radiated emissions in the range 17 GHz-26 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.


The equipment under test was set up on a non-conductive platform above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height (Bilog antenna and Double ridge horn antenna) was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.


Radiated measurements setup from 30 MHz to 1 GHz:



Radiated measurements setup from 1 GHz to 17 GHz:



Radiated measurements setup $f > 17$ GHz:



FCC 15.247 (a) (1) / RSS-247 5.1. (b) 20 dB Bandwidth and Carrier frequency separation

SPECIFICATION:

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

RESULTS:

- **GFSK**

	Low Channel 2402 MHz	Middle Channel 2441 MHz	High Channel 2480 MHz
20 dB Spectrum Bandwidth (kHz)	938.901	938.34	935.68
99% Bandwidth (kHz)	883.2	881.7	880.8
Measurement uncertainty (kHz)	<±3.64		

- **Pi/4 DQPSK**

	Low Channel 2402 MHz	Middle Channel 2441 MHz	High Channel 2480 MHz
20 dB Spectrum Bandwidth (kHz)	1355.97	1355.17	1356.1
99% Bandwidth (kHz)	1224.6	1209	1210.2
Measurement uncertainty (kHz)	<±3.64		


- **8DPSK**

	Low Channel 2402 MHz	Middle Channel 2441 MHz	High Channel 2480 MHz
20 dB Spectrum Bandwidth (kHz)	1310.5	1039.87	1319.202
99% Bandwidth (kHz)	1207.2	1205.7	1208.7
Measurement uncertainty (kHz)	<±3.64		


Verdict: PASS

• **GFSK – Bandwidths**


- Low Channel:



- Middle Channel:




- High Channel:



Carrier frequency separation - GFSK

Carrier frequency separation: 976.17 kHz




The hopping channel carrier frequencies are separated by a minimum two-thirds of the 20 dB bandwidth of the hopping channel.


Verdict: PASS

• Pi/4 DQPSK – Bandwidths


- Low Channel:



- Middle Channel:




- High Channel:



Carrier frequency separation - Pi/4 DQPSK

Carrier frequency separation: 974.37 kHz




The hopping channel carrier frequencies are separated by a minimum two-thirds of the 20 dB bandwidth of the hopping channel.


Verdict: PASS

• 8DPSK – Bandwidths


- Low Channel:



- Middle Channel:




- High Channel:



Carrier frequency separation - 8DPSK

Carrier frequency separation: 997.8 kHz



The hopping channel carrier frequencies are separated by a minimum two-thirds of the 20 dB bandwidth of the hopping channel.

Verdict: PASS

FCC 15.247 (a)(1)(iii) / RSS-247 5.1 (d) Number of hopping channels



SPECIFICATION:

Frequency hopping system in the 2400-2483.5 MHz band shall use at least 15 channels.

RESULTS:

The number of hopping channels is 79 for all three modes.



- **GFSK – Number of hopping channels**



Total number of hopping channels: 79

Verdict: PASS



- Pi/4 DQPSK – Number of hopping channels



Total number of hopping channels: 79

Verdict: PASS

- 8DPSK – Number of hopping channels



Total number of hopping channels: 79

Verdict: PASS

FCC 15.247 (a)(1)(iii) / RSS-247 5.1 (d) Time of occupancy (Dwell Time)

SPECIFICATION:


The average time of occupancy on any channel shall not be greater than 0.4 seconds (400 ms) within a period of 0.4 seconds multiplied by the number of hopping channels employed = $0.4 \times 79 = 31.6$ seconds.

RESULTS:

- **GFSK (packet type DH5) – Time of Occupancy (Dwell Time)**


- Transmit Time per Hop:

2.85758 ms



▪ Time of Occupancy:

Nº of hops on spectrum analyzer	8
Nº of hops over the period	84.26666667
Average Time of Occupancy	240.7987413 ms




Measurement uncertainty (ms)	<±0.546
------------------------------	---------

Verdict: PASS

• Pi/4 DQPSK (packet type 2DH5) – Time of Occupancy (Dwell Time)


- Transmit Time per Hop:

2.8776 ms



Time of Occupancy:

Nº of hops on spectrum analyzer	11
Nº of hops over the period	115.8666667
Average Time of Occupancy	333.41792 ms




Measurement uncertainty (ms)	<±0.546
------------------------------	---------

Verdict: PASS

• 8DPSK (packet type 3DH5) – Time of Occupancy (Dwell Time)


- Transmit Time per Hop:

2.87938 ms



Time of Occupancy:

Nº of hops on spectrum analyzer	11
Nº of hops over the period	115.8666667
Average Time of Occupancy	333.6241627 ms



Measurement uncertainty (ms)	<±0.546
------------------------------	---------

Verdict: PASS

FCC 15.247 (b) / RSS-247 5.4 (b) Maximum peak output power and antenna gain

SPECIFICATION:

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 hopping channels: 1 watt (30 dBm). The e.i.r.p. shall not exceed 4 W (RSS-247).

RESULTS:

The EIRP power (dBm) is calculated by adding the maximum declared antenna gain to the measured conducted power.

Maximum Declared Antenna Gain: -6.2 dBi

The maximum directional gain of the antenna is less than 6 dBi and therefore the maximum output power is not required to be reduced from the stated values.

- **GFSK (1 Mbps)**

Peak Conducted Output Power	Low Channel 2402 MHz	Middle Channel 2441 MHz	High Channel 2480 MHz
Maximum Conducted Power (dBm)	8.35	8.08	8.54
Maximum EIRP Power (dBm)	2.15	1.88	2.34
Measurement uncertainty (dB)	<±2.57		

- **Pi/4 DQPSK (2 Mbps)**

Peak Conducted Output Power	Low Channel 2402 MHz	Middle Channel 2441 MHz	High Channel 2480 MHz
Maximum Conducted Power (dBm)	6.87	6.86	7.07
Maximum EIRP Power (dBm)	0.67	0.66	0.87
Measurement uncertainty (dB)	<±2.57		

- **8DPSK (3 Mbps)**

Peak Conducted Output Power	Low Channel 2402 MHz	Middle Channel 2441 MHz	High Channel 2480 MHz
Maximum Conducted Power (dBm)	7.32	7.27	7.49
Maximum EIRP Power (dBm)	1.12	1.07	1.29
Measurement uncertainty (dB)	<±2.57		


Verdict: PASS

- GFSK – Peak Output Power


- Low Channel:



- Middle Channel:




- High Channel:




• Pi/4 DQPSK – Peak Output Power

- Low Channel:



- Middle Channel:




- High Channel:




- 8DPSK – Peak Output Power

- Low Channel:



- Middle Channel:



- High Channel:

