



FCC LISTED, REGISTRATION
 NUMBER: 720267

Informe de ensayo nº:
 Test report No:

ISED LISTED REGISTRATION
 NUMBER 4621A-2

NIE: 55472RRF.005A1

Test report (Modification 1)

**USA FCC Part 15.247, 15.209
 CANADA RSS-247, RSS-Gen**

Radio Frequency Devices. Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and
 5725 - 5850 MHz.

Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt
 Local Area Network (LE-LAN) Devices.

General Requirements for Compliance of Radio Apparatus.

Identificación del objeto ensayado.....: Identification of item tested	Automotive infotainment System
Marca Trademark	BMW
Modelo y/o referencia tipo Model and /or type reference	MGU RSE
Other identification of the product	FCC ID: T8GMGURSE IC: 6434A-MGURSE
Final HW version	1.1.5
Final SW version	18w15.3-1
Características Features	KLEER, USB Type C, HDMI/MHL
Solicitante Applicant	HARMAN BECKER AUTOMOTIVE SYSTEMS GMBH BECKER-GOERING-STR. 16; 76307 KARLSBAD GERMANY
Método de ensayo solicitado, norma.....: Test method requested, standard	USA FCC Part 15.247 10-1-17 Edition: Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz. USA FCC Part 15.209 10-1-17 Edition: Radiated emission limits; general requirements. CANADA RSS-247 Issue 2 (February 2017). CANADA RSS-Gen Issue 4 (November 2014). Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 558074 D01 DTS Meas Guidance v04 dated 05/04/2017. ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.
Resultado.....: Summary	IN COMPLIANCE
Aprobado por (nombre / cargo y firma) Approved by (name / position & signature)	A. Llamas RF Lab. Manager
Fecha de realización Date of issue	2018-07-27

Formato de informe No.: FDT11_20
Report template No

Index

Competences and guarantees.....	4
General conditions.....	4
Uncertainty	4
Usage of samples.....	5
Test sample description	5
Identification of the client	5
Testing period.....	5
Environmental conditions.....	6
Modifications to the reference test report.....	7
Remarks and comments.....	7
Testing verdicts	8
Appendix A – Test results	9

Competences and guarantees

DEKRA Testing and Certification is a testing laboratory accredited by the National Accreditation Body (ENAC - Entidad Nacional de Acreditación), to perform the tests indicated in the Certificate No. 51/LE 147.

DEKRA Testing and Certification is a laboratory with a measurement facility in compliance with the requirements of Section 2.948 of the FCC rules and has been added to the list of facilities whose measurements data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Registration Number: 720267.

DEKRA Testing and Certification is a laboratory with a measurement site in compliance with the requirements of RSS 212, Issue 1 (Provisional) and has been added to the list of filed sites of the Canadian Certification and Engineering Bureau. Reference File Number: ISED 4621A-2.

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification at the time of performance of the test.

DEKRA Testing and Certification is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification..
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification and the Accreditation Bodies.

Uncertainty

Uncertainty (factor $k=2$) was calculated according to the DEKRA Testing and Certification internal document PODT000.

Usage of samples

Samples undergoing test have been selected by: **the client**

Sample S/01 is composed of the following elements:

Control N°	Description	Model	Serial N°	Date of reception
55472/390	Automotive infotainment System	MGU RSE	B326K10H7512319	2018-05-14

1. Sample S/01 has undergone following test(s).
All radiated tests indicated in appendix A.

Sample S/02 is composed of the following elements:

Control N°	Description	Model	Serial N°	Date of reception
55472/387	Automotive infotainment System	MGU RSE	B326K+0H751228	2018-05-14

1. Sample S/02 has undergone following test(s).
All conducted tests indicated in appendix A.

Test sample description

The test sample consists of an automotive unit to be installed in cars with the following features: KLEER, USB Type C, HDMI/MHL.

Identification of the client

HARMAN BECKER AUTOMOTIVE SYSTEMS GMBH
BECKER-GOERING-STR. 16; 76307 KARLSBAD GERMANY

Testing period

The performed test started on 2018-05-16 and finished on 2018-06-12.

The tests have been performed at DEKRA Testing and Certification.

Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %
Shielding effectiveness	> 100 dB
Electric insulation	> 10 k Ω
Reference resistance to earth	< 1 Ω

In the semianechoic chamber, the following limits were not exceeded during the test.

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar
Shielding effectiveness	> 100 dB
Electric insulation	> 10 k Ω
Reference resistance to earth	< 1 Ω
Normal site attenuation (NSA)	< ± 4 dB at 10 m distance between item under test and receiver antenna, (30 MHz to 1000 MHz)
Field homogeneity	More than 75% of illuminated surface is between 0 and 6 dB (26 MHz to 1000 MHz).

In the chamber for conducted measurements, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar
Shielding effectiveness	> 100 dB
Electric insulation	> 10 k Ω
Reference resistance to earth	< 1 Ω

Modifications to the reference test report

It was introduced the following modifications in respect to the test report number 55472RRF.005 related with the same samples, in the next clauses and sub-clauses:

Clauses / Sub-clauses	Modification	Justification
Test Conditions	Added the sentence with the chips that can be operating at the same time.	TCB request
Test Conditions/ Radiated Measurements	The sentence to determine the worst case was modified to clarify how it was chosen the worst case of radiated spurious emission.	TCB request
Section 15.247 Subclause (d) / RSS-247 5.5. Emission limitations radiated (Transmitter) / Results / Kleer 1	Added the sentence to clarify how it was chosen the worst case of radiated spurious emission.	TCB request
Section 15.247 Subclause (d) / RSS-247 5.5. Emission limitations radiated (Transmitter) / Results / Kleer 2	Added the sentence to clarify how it was chosen the worst case of radiated spurious emission.	TCB request
Section 15.247 Subclause (b) / RSS-247 5.4. (d). Maximum output power and antenna gain / Results	Added the table with the sum of fundamentals when the chips is operating at the same time.	TCB request

This modification test report cancels and replaces the test report 55472RF.005.

Remarks and comments

1: The tests have been performed by the technical personnel: José Alberto Aranda, Miguel Ángel Torres and Gonzalo Rueda.

2: Used instrumentation:

Conducted Measurements

	Last Cal. date	Cal. due date
1. Spectrum Analyzer Agilent PSA E4440A	2017/10	2019/10
2. DC power supply R&S NGPE 40/40	2018/02	2021/02

Radiated Measurements

	Last Cal. date	Cal. due date
1. Semianechoic Absorber Lined Chamber ETS FACT3 200STP	N.A.	N.A.
2. BiconicalLog antenna ETS LINDGREN 3142E	2017/04	2020/04
3. Multi Device Controller EMCO 2090	N.A.	N.A.
4. Double-ridge Guide Horn antenna 1-18 GHz SCHWARZBECK BBHA 9120 D	2016/11	2019/11
5. Broadband Horn antenna 18-40 GHz SCHWARZBECK BBHA 9170	2017/03	2020/03
6. EMI Test Receiver R&S ESR7	2016/07	2018/07
7. Spectrum analyser Rohde & Schwarz FSW50	2018/02	2020/02
8. RF pre-amplifier 30 MHz-6 GHz Bonn Elektronik BLNA 0360-01N	2017/07	2018/07
9. RF pre-amplifier 1-18 GHz Bonn Elektronik BLMA 0118-1M	2018/03	2019/03
10. RF pre-amplifier 18-40 GHz NARDA JS44-18004000-33-8P	2018/02	2019/02

Testing verdicts

Not applicable	N/A
Pass	P
Fail	F
Not measured	N/M

FCC PART 15 PARAGRAPH / RSS-247		VERDICT			
		NA	P	F	NM
Section 15.247 Subclause (a) (2) / RSS-247 5.2. (a)	6 dB Bandwidth		P		
Section 15.247 Subclause (b) / RSS-247 5.4. (d)	Maximum output power and antenna gain		P		
Section 15.247 Subclause (d) / RSS-247 5.5.	Emission limitations conducted (Transmitter)		P		
Section 15.247 Subclause (d) / RSS-247 5.5.	Band-edge emissions compliance (Transmitter)		P		
Section 15.247 Subclause (e) / RSS-247 5.2. (b)	Power spectral density		P		
Section 15.247 Subclause (d) / RSS-247 5.5.	Emission limitations radiated (Transmitter)		P		

Appendix A – Test results

INDEX

TEST CONDITIONS	11
Occupied Bandwidth	13
Section 15.247 Subclause (a) (2) / RSS-247 5.2. (a). 6 dB Bandwidth	17
Section 15.247 Subclause (b) / RSS-247 5.4. (d). Maximum output power and antenna gain	21
Section 15.247 Subclause (d) / RSS-247 5.5. Emission limitations conducted (Transmitter).....	26
Section 15.247 Subclause (d) / RSS-247 5.5. Band-edge emissions compliance (Transmitter).....	31
Section 15.247 Subclause (e) / RSS-247 5.2. (b) Power spectral density	35
Section 15.247 Subclause (d) / RSS-247 5.5. Emission limitations radiated (Transmitter)	39

TEST CONDITIONS

Power supply (V):

$$V_{\text{nominal}} = 12 \text{ Vdc}$$

Type of power supply = External power supply (Battery).

Type of antenna= Integral antenna.

Declared Gain for antenna (maximum) = 4.4 dBi

TEST FREQUENCIES:

Lowest channel: 2403 MHz

Middle channel: 2443 MHz

Highest channel: 2478 MHz

The equipment under tests has two different KLEER chips with two different RF outputs (KLEER1 and KLEER2) which can transmit simultaneously.

CONDUCTED MEASUREMENTS

The equipment under test was set up in a shielded room and it is directly connected to the spectrum analyzer.



The DC supply voltage is applied using an external calibrated power supply.

RADIATED MEASUREMENTS

All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m for the frequency range 30 MHz-1000 MHz (30 MHz-1000 MHz Bilog antenna) and at a distance of 1m for the frequency range 1 GHz-25 GHz (1 GHz-18 GHz Double ridge horn antenna and 18 GHz-40 GHz horn antenna).


For radiated emissions in the range 1 GHz-25 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.

The equipment under test was set up on a non-conductive platform above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.


Measurements were made in both horizontal and vertical planes of polarization.

The test was performed with the equipment transmitting first with only KLEER1 chip activated and with KLEER2 chip activated separately and repeated with both chips (KLEER1+KLEER2) transmitting simultaneously to check the impact of the co-location of the other radio interfaces. The results and plots below show the worst results obtained.

Radiated measurements setup $f < 1$ GHz



Radiated measurements setup $f > 1$ GHz



Occupied Bandwidth

RESULTS

(see next plots).

KLEER 1


	Lowest frequency 2403 MHz	Middle frequency 2443 MHz	Highest frequency 2478 MHz
99% bandwidth (MHz)	2.949	2.947	2.934
-26 dBc bandwidth (MHz)	5.199	5.209	5.239
Measurement uncertainty (kHz)	<± 5.00		

KLEER 2


	Lowest frequency 2403 MHz	Middle frequency 2443 MHz	Highest frequency 2478 MHz
99% bandwidth (MHz)	2.932	2.905	2.920
-26 dBc bandwidth (MHz)	5.030	5.119	5.031
Measurement uncertainty (kHz)	<± 5.00		

KLEER 1


Lowest Channel



Middle Channel




Highest channel




KLEER 2


Lowest Channel



Middle Channel



Highest channel



Section 15.247 Subclause (a) (2) / RSS-247 5.2. (a). 6 dB Bandwidth

SPECIFICATION

The minimum 6 dB bandwidth shall be at least 500 kHz.

RESULTS

6 dB Bandwidth (see next plots).

KLEER 1

	Lowest frequency 2403 MHz	Middle frequency 2443 MHz	Highest frequency 2478 MHz
6 dB Spectrum bandwidth (kHz)	1852	1892	1852
Measurement uncertainty (kHz)	<±11.51		

KLEER 2


	Lowest frequency 2403 MHz	Middle frequency 2443 MHz	Highest frequency 2478 MHz
6 dB Spectrum bandwidth (kHz)	1912	1682	1772
Measurement uncertainty (kHz)	<±11.51		

Verdict: PASS


6 dB BANDWIDTH.

KLEER 1


Lowest Channel



Middle Channel




Highest Channel




KLEER 2


Lowest Channel



Middle Channel



Highest Channel



Section 15.247 Subclause (b) / RSS-247 5.4. (d). Maximum output power and antenna gain

SPECIFICATION

For systems using digital modulation in the 2400-2483.5 MHz band: 1 watt (30 dBm).
 The e.i.r.p. shall not exceed 4 W (36 dBm) (Canada).

RESULTS

The maximum peak conducted output power was measured using the method according to point 9.1.1. of Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 558074 D01 DTS Meas Guidance v04 dated 05/04/2017.

The EIRP power (dBm) is calculated by adding the declared maximum antenna gain to the measured conducted power.

MAXIMUM OUTPUT POWER. See next plots.

Maximum declared antenna gain port (Kleer 1): 4.4 dBi.

Maximum declared antenna gain port (Kleer 2): 4.4 dBi.

KLEER 1

	Lowest frequency 2403 MHz	Middle frequency 2443 MHz	Highest frequency 2478 MHz
Maximum conducted power (dBm)	2.62	2.95	2.88
Maximum EIRP power (dBm)	7.02	7.35	7.28
Measurement uncertainty (dB)	<±0.78		

KLEER 2

	Lowest frequency 2403 MHz	Middle frequency 2443 MHz	Highest frequency 2478 MHz
Maximum conducted power (dBm)	2.66	2.55	2.31
Maximum EIRP power (dBm)	7.06	6.95	6.71
Measurement uncertainty (dB)	<±0.78		

The maximum directional gain of the antenna is less than 6 dBi and therefore the maximum output power is not required to be reduced from the stated values.

KLEER 1+KLEER 2

Frequency	Maximum conducted output power (dBm). Kleer 1	Maximum conducted output power (dBm). Kleer 2	Maximum conducted output power (dBm). Kleer1 + Kleer 2	Maximum e.i.r.p. (dBm). Kleer 1+Kleer 2
2403 MHz	2.62	2.66	5.65	10.05
2443 MHz	2.95	2.55	5.76	10.16
2478 MHz	2.88	2.31	5.61	10.01


NOTE: This table contains the sum of the fundamentals of interfaces Kleer 1 and Kleer 2.

Verdict: PASS


CONDUCTED PEAK POWER.

KLEER 1


Lowest frequency



Middle frequency




Highest frequency




KLEER 2


Lowest frequency



Middle frequency



Highest frequency



Section 15.247 Subclause (d) / RSS-247 5.5. Emission limitations conducted (Transmitter)

SPECIFICATION

In any 100 kHz bandwidth outside the frequency band in which the digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required shall be 30 dB instead of 20 dB.

RESULTS:

KLEER 1

Reference Level Measurement

	Lowest frequency 2403 MHz	Middle frequency 2443 MHz	Highest frequency 2478 MHz
Reference Level Measurement (dBm)	0.23	0.21	0.78
Measurement uncertainty (dB)	<±0.78		

Lowest frequency 2403 MHz:
All peaks are more than 20 dB below the limit

Middle frequency 2443 MHz:
All peaks are more than 20 dB below the limit

Highest frequency 2478 MHz:
All peaks are more than 20 dB below the limit

KLEER 2

Reference Level Measurement

	Lowest frequency 2403 MHz	Middle frequency 2443 MHz	Highest frequency 2478 MHz
Reference Level Measurement (dBm)	0.09	0.65	0.14
Measurement uncertainty (dB)	<±0.78		

Lowest frequency 2403 MHz:

All peaks are more than 20 dB below the limit

Middle frequency 2443 MHz:

All peaks are more than 20 dB below the limit

Highest frequency 2478 MHz:


All peaks are more than 20 dB below the limit

Measurement uncertainty (dB): < 2.03

Verdict: PASS


KLEER 1

Lowest frequency




Note: The peak shown in the plot above the limit is the carrier frequency.

Middle frequency



Note: The peak shown in the plot above the limit is the carrier frequency.


Highest frequency



Note: The peak shown in the plot above the limit is the carrier frequency.


KLEER 2

Lowest frequency




Note: The peak shown in the plot above the limit is the carrier frequency.

Middle frequency



Note: The peak shown in the plot above the limit is the carrier frequency.

Highest frequency



Note: The peak shown in the plot above the limit is the carrier frequency.

Section 15.247 Subclause (d) / RSS-247 5.5. Band-edge emissions compliance (Transmitter)

SPECIFICATION

In any 100 kHz bandwidth outside the frequency band in which the digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required shall be 30 dB instead of 20 dB.


RESULTS:

Note: Radiated measurements were used to show compliance with the limits in the restricted bands 2.31-2.39 GHz and 2.4835-2.5 GHz.

KLEER 1

1. LOW FREQUENCY SECTION. CONDUCTED.


See next plot.



Verdict: PASS

2. HIGH FREQUENCY SECTION. CONDUCTED.

See next plot.




Measurement uncertainty (dB)	< ±2.03
------------------------------	---------

Verdict: PASS

KLEER 2

1. LOW FREQUENCY SECTION. CONDUCTED.


See next plot.



Verdict: PASS

2. HIGH FREQUENCY SECTION. CONDUCTED.

See next plot.



Measurement uncertainty (dB)	< ± 2.03
------------------------------	--------------

Verdict: PASS

Section 15.247 Subclause (e) / RSS-247 5.2. (b) Power spectral density

SPECIFICATION

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

RESULTS

The maximum power spectral density level in the fundamental emission was measured using the method PKPSD (Peak PSD) according to point 10.2. of Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 558074 D01 DTS Meas Guidance v04 dated 05/04/2017.

Power spectral density (see next plots).

KLEER 1

	Lowest frequency 2403 MHz	Middle frequency 2443 MHz	Highest frequency 2478 MHz
Power spectral density (dBm)	0.32	0.46	0.51
Measurement uncertainty (dB)	<±0.78		

KLEER 2


	Lowest frequency 2403 MHz	Middle frequency 2443 MHz	Highest frequency 2478 MHz
Power spectral density (dBm)	0.22	0.53	-0.24
Measurement uncertainty (dB)	<±0.78		

Verdict: PASS


POWER SPECTRAL DENSITY

KLEER 1


Lowest Channel



Middle Channel




Highest Channel




KLEER 2


Lowest Channel



Middle Channel



Highest Channel



Section 15.247 Subclause (d) / RSS-247 5.5. Emission limitations radiated (Transmitter)

SPECIFICATION

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c) / RSS-Gen):

Frequency Range (MHz)	Field strength ($\mu\text{V/m}$)	Field strength ($\text{dB}\mu\text{V/m}$)	Measurement distance (m)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	30
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 25000	500	54	3

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

RSS-247. Attenuation below the general field strength limits specified in RSS-Gen is not required.

RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-1000 MHz and at distance of 1m for the frequency range 1 GHz-25 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

Frequency range 30 MHz-1000 MHz.

The spurious signals detected do not depend on the operating channel and KLEER chain.

Spurious frequency (MHz)	Polarization	Detector	Emission Level (dB μ V/m)	Measurement Uncertainty (dB)
48.026	V	Quasi-Peak	20.80	± 3.88
151.008	V	Quasi-Peak	24.10	± 3.88
258.387	H	Quasi-Peak	31.02	± 3.88
281.440	H	Quasi-Peak	31.48	± 3.88
297.284	H	Quasi-Peak	36.29	± 3.88
359.881	H	Quasi-Peak	30.54	± 3.88

Frequency range 1 GHz-25 GHz

The results in the next tables show the maximum measured levels in the 1-25 GHz range including the restricted bands 2.31-2.39 GHz and 2.4835-2.5 GHz (see next plots).

Spurious signals with peak levels above the average limit (54 dB μ V/m at 3 m) are measured with average detector for checking compliance with the average limit.

KLEER 1

The equipment with only KLEER1 chip activated is the worst case than with both chips (KLEER1+KLEER2) transmitting simultaneously.

1. CHANNEL: LOWEST (2403 MHz).

Spurious frequency (GHz)	Polarization	Detector	Emission Level (dB μ V/m)	Measurement Uncertainty (dB)
2.18457	H	Peak	53.53	± 3.70
4.00000	V	Peak	37.38	± 3.70
4.80577	V	Peak	47.40	± 3.70
7.20910	V	Peak	49.75	± 3.70

2. CHANNEL: MIDDLE (2443 MHz).

Spurious frequency (GHz)	Polarization	Detector	Emission Level (dB μ V/m)	Measurement Uncertainty (dB)
2.21620	H	Peak	51.75	± 3.70
4.00030	V	Peak	37.03	± 3.70
4.87623	V	Peak	49.06	± 3.70
7.31410	V	Peak	46.88	± 3.70

3. CHANNEL: HIGHEST (2478 MHz).

Spurious frequency (GHz)	Polarization	Detector	Emission Level (dB μ V/m)	Measurement Uncertainty (dB)
2.48361	H	Peak	55.49	± 3.70
		Avg	42.43	± 3.70
4.00000	V	Peak	36.55	± 3.70
4.95603	V	Peak	49.63	± 3.70
7.31410	V	Peak	46.88	± 3.70

Verdict: PASS

KLEER 2

The equipment with only KLEER2 chip activated is the worst case than with both chips (KLEER1+KLEER2) transmitting simultaneously.

1. CHANNEL: LOWEST (2403 MHz).

Spurious frequency (GHz)	Polarization	Detector	Emission Level (dB μ V/m)	Measurement Uncertainty (dB)
3.99983	V	Peak	43.78	± 3.70
4.50010	H	Peak	40.30	± 3.70
4.80483	V	Peak	56.98	± 3.70
		Avg	50.56	± 3.70
5.99950	H	Peak	47.34	± 3.70
7.20723	V	Peak	49.13	± 3.70
9.00017	H	Peak	51.28	± 3.70
9.61430	V	Peak	51.49	± 3.70

2. CHANNEL: MIDDLE (2443 MHz).


Spurious frequency (GHz)	Polarization	Detector	Emission Level (dB μ V/m)	Measurement Uncertainty (dB)
3.99983	V	Peak	42.95	± 3.70
4.88463	V	Peak	51.57	± 3.70
5.99997	H	Peak	47.46	± 3.70
7.32763	V	Peak	45.09	± 3.70
8.99970	H	Peak	51.01	± 3.70

3. CHANNEL: HIGHEST (2478 MHz).

Spurious frequency (GHz)	Polarization	Detector	Emission Level (dB μ V/m)	Measurement Uncertainty (dB)
2.48356	H	Peak	57.19	± 3.70
		Avg	46.59	± 3.70
3.99983	V	Peak	43.33	± 3.70
4.50010	H	Peak	40.41	± 3.70
4.79877	H	Peak	44.86	± 3.70
4.95510	H	Peak	55.66	± 3.70
		Avg	46.85	± 3.70
6.00043	H	Peak	47.20	± 3.70
9.00017	H	Peak	52.02	± 3.70
9.90970	V	Peak	51.13	± 3.70

Verdict: PASS

FREQUENCY RANGE 30 MHz-1000 MHz.




(This plot is valid for all three channels and for both KLEER 1 and KLEER 2).

KLEER 1


FREQUENCY RANGE 1 GHz to 3 GHz.

CHANNEL: Lowest (2403 MHz).




Note: The peak shown in the plot above the limit is the carrier frequency.

CHANNEL: Middle (2443 MHz).



Note: The peak shown in the plot above the limit is the carrier frequency.


CHANNEL: Highest (2478 MHz).




Note: The peak shown in the plot above the limit is the carrier frequency.

FREQUENCY RANGE 3 GHz to 17 GHz.


CHANNEL: Lowest (2403 MHz).




CHANNEL: Middle (2443 MHz).



CHANNEL: Highest (2478 MHz).




FREQUENCY RANGE 17 GHz to 26 GHz.




(This plot is valid for all three channels).

FREQUENCY RANGE 2.31 GHz to 2.39 GHz. (RESTRICTED BAND)


CHANNEL: Lowest (2403 MHz).



CHANNEL: Middle (2443 MHz).




CHANNEL: Highest (2478 MHz).




FREQUENCY RANGE 2.4835 GHz to 2.5 GHz. (RESTRICTED BAND).


CHANNEL: Lowest (2403 MHz).



CHANNEL: Middle (2443 MHz).




CHANNEL: Highest (2478 MHz).



KLEER 2


FREQUENCY RANGE 1 GHz to 3 GHz.

CHANNEL: Lowest (2403 MHz).




Note: The peak shown in the plot above the limit is the carrier frequency.

CHANNEL: Middle (2443 MHz).



Note: The peak shown in the plot above the limit is the carrier frequency.


CHANNEL: Highest (2478 MHz).




Note: The peak shown in the plot above the limit is the carrier frequency.

FREQUENCY RANGE 3 GHz to 17 GHz.


CHANNEL: Lowest (2403 MHz).




CHANNEL: Middle (2443 MHz).



CHANNEL: Highest (2478 MHz).




FREQUENCY RANGE 17 GHz to 26 GHz.




(This plot is valid for all three channels).

FREQUENCY RANGE 2.31 GHz to 2.39 GHz. (RESTRICTED BAND)


CHANNEL: Lowest (2403 MHz).



CHANNEL: Middle (2443 MHz).




CHANNEL: Highest (2478 MHz).




FREQUENCY RANGE 2.4835 GHz to 2.5 GHz. (RESTRICTED BAND).

CHANNEL: Lowest (2403 MHz).



CHANNEL: Middle (2443 MHz).



CHANNEL: Highest (2478 MHz).

