



Test report No:
 NIE: 60268RRF.012A1

Partial Test report

USA FCC Part 15.247, 15.407, 15.209

CANADA RSS-247, RSS-Gen

Radio Frequency Devices.

Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz.

Unlicensed National Information Infrastructure (U-NII) Devices:
 General technical requirements.

Radiated emission limits; general requirements.

Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs)
 and Licence-Exempt Local Area Network (LE-LAN) Devices.

General Requirements and Information for the Certification of Radio
 Apparatus.

| | |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| (*) Identification of item tested | Automotive Infotainment System |
| (*) Trademark | Mercedes-Benz |
| (*) Model and /or type reference | NTG7 HIGH |
| Other identification of the product | HW version: D5 SW version: E17.100 FCC ID: T8GNTG7HIGH IC: 6434A-NTG7HIGH |
| (*) Features | FM/AM/DAB/DVBT USB, Bluetooth, WLAN, GNSS. |
| Applicant | HARMAN BECKER AUTOMOTIVE SYSTEMS GMBH BECKER-GOERING-STR. 16; 76307 KARLSBAD GERMANY |
| Test method requested, standard | USA FCC Part 15.407 (10-1-19) Edition: Unlicensed National Information Infrastructure (U-NII) Devices. General technical requirements. Band U-NII-3 (5725 MHz – 5850 MHz). USA FCC Part 15.247 (10-1-19) Edition: Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz. USA FCC Part 15.209 (10-1-19) Edition: Radiated emission limits; general requirements. CANADA RSS-247 Issue 2 (February 2017). CANADA RSS-Gen Issue 5 (March 2019) -Transmitter out of band radiated emissions with simultaneous transmissions Guidance for Performing Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid Systems Devices Operating Under Section 15.247 of the FCC Rules. 558074 D01 Meas Guidance v05r02 dated April 2, 2019. Guidance for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices 789033 D02 General U-NII Test Procedures New Rules v02r01 dated Dec 14, 2017. |

| | |
|-------------------------------------------|---------------------------------------------------------------------------------------|
| | ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices. |
| Summary | IN COMPLIANCE |
| Approved by (name / position & signature) | Jose Carlos Luque RF Lab. Supervisor |
| Date of issue | 2020-08-13 |
| Report template No | FDT08_22 (* "Data provided by the client") |

Index

| | |
|------------------------------------|---|
| Competences and guarantees | 4 |
| General conditions | 4 |
| Uncertainty..... | 4 |
| Data provided by the client | 4 |
| Usage of samples | 4 |
| Test sample description..... | 5 |
| Identification of the client | 6 |
| Testing period and place | 6 |
| Document history..... | 6 |
| Environmental conditions | 7 |
| Remarks and comments..... | 7 |
| Testing verdicts..... | 8 |
| Summary | 8 |
| Appendix A: Test results..... | 9 |

Competences and guarantees

DEKRA Testing and Certification is a testing laboratory accredited by the National Accreditation Body (ENAC - Entidad Nacional de Acreditación), to perform the tests indicated in the Certificate No. 51/LE 147.

DEKRA Testing and Certification is a FCC-recognized accredited testing laboratory with appropriate scope of accreditation that include testing performed in this test report.

DEKRA Testing and Certification is an ISED-recognized accredited testing laboratory with appropriate scope of accreditation that include testing performed in this test report.

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification at the time of performance of the test.

DEKRA Testing and Certification is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification and the Accreditation Bodies.

Uncertainty

Uncertainty (factor k=2) was calculated according to the DEKRA Testing and Certification internal document PODT000.

Data provided by the client

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item tested", "Trademark", "Model and/or type reference tested").
2. The sample of the model NTG7 HIGH is an Automotive head unit to be installed in cars with the following features: FM/AM/DAB/DVBT, USB, Bluetooth, WLAN and GNSS.

DEKRA Testing and Certification S.A.U. declines any responsibility with respect to the information provided by the client and that may affect the validity of result.

Usage of samples

Samples undergoing test have been selected by: The client.

- Sample S/01 is composed of the following elements:

| Control Nº | Description | Model | Serial Nº | Date of reception |
|------------|----------------------------------------------|-----------|----------------|-------------------|
| 60268/302 | Mercedes-Benz Automotive infotainment System | NTG7 HIGH | HBM609LS000001 | 2020/02/26 |

Auxiliary elements used with the sample S/01:

| Control Nº | Description | Model | Serial Nº | Date of reception |
|------------|--------------------------|-------|-----------|-------------------|
| 60268/308 | RF Harness | -- | -- | 2020/02/26 |
| 60268/122 | RF Cable with 4 Antennas | -- | -- | 2019/09/30 |

Sample S/01 has undergone the following test(s): All RADIATED tests indicated in Appendixes A.

Test sample description

| Ports..... : | Port name and description | Cable | | | |
|-----------------------------------------------|-------------------------------------|---------------------------------------------------------------|-------------------------------------|-------------------------------------|-----------------------------------|
| | | Specified max length [m] | Attached during test | Shielded | Coupled to patient ⁽³⁾ |
| | Car Connector A | >3m ^(x1) | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| | Car Connector B | >3m ^(x1) | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| | Display Connector CID/PIP / RVC | >3m ^(x1) | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| | USB Connector | <3m ^(x2) | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| | Eth Connector | >3m ^(x1) | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| | BT/WLAN-Antenna | >3m ^(x1) | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| | FM/AM, TV/SDARS Ant | >3m ^(x1) | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| | GNSS Antenna | >3m ^(x1) | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| Supplementary information to the ports..... : | | | | | |
| Rated power supply | Voltage and Frequency | | | | |
| | <input checked="" type="checkbox"/> | DC: 12V Car battery / attenuator (9,5-15,5V normal operation) | | | |

| | | | |
|-----------------------------------------------|-------------------------------------|----------------------------|--------------|
| Rated Power | 9,5-15,5V normal operation | | |
| Clock frequencies..... | See schematics | | |
| Other parameters | See Technical Description | | |
| Software version | E17.100 | | |
| Hardware version | D5 | | |
| Dimensions in cm (W x H x D) | 182 x 78 x 160 mm | | |
| Mounting position | <input checked="" type="checkbox"/> | Other: automotive headunit | |
| Modules/parts..... | Module/parts of test item | Type | Manufacturer |
| | N/A | - | |
| Accessories (not part of the test item) | Description | Type | Manufacturer |
| | Display | - | LG. |
| | HARMANeco RasPi | - | HBAS |
| | Cable harness | - | HBAS |
| | BT/WLAN-Antenna | - | Hirschmann |
| Documents as provided by the applicant..... | Description | File name | Issue date |
| | Technical Description | | |

⁽³⁾ Only for Medical Equipment

Identification of the client

HARMAN BECKER AUTOMOTIVE SYSTEMS GMBH
 BECKER-GOERING-STR. 16; 76307 KARLSBAD GERMANY

Testing period and place

| | |
|---------------|----------------------------------------|
| Test Location | DEKRA Testing and Certification S.A.U. |
| Date (start) | 2020-03-26 |
| Date (finish) | 2020-03-27 |

Document history

| Report number | Date | Description |
|----------------|------------|-------------------------------------------------------------------------------------------------------------------|
| 60268RRF.012 | 2020-05-25 | First release |
| 60268RRF.012A1 | 2020-08-13 | First modification due to typos. This modification test report cancels and replaces the test report 60268RRF.012. |

Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

| | |
|-------------------|-------------------------------------|
| Temperature | Min. = 15 °C Max. = 35 °C |
| Relative humidity | Min. = 20 % Max. = 75 % |
| Air pressure | Min. = 860 mbar Max. = 1060 mbar |

In the semianechoic chamber, the following limits were not exceeded during the test.

| | |
|-------------------|-------------------------------------|
| Temperature | Min. = 15 °C Max. = 35 °C |
| Relative humidity | Min. = 20 % Max. = 75 % |
| Air pressure | Min. = 860 mbar Max. = 1060 mbar |

Remarks and comments

The tests have been performed by the technical personnel: Miguel Ángel Torres.

Used instrumentation:

Radiated Measurements:

| | Last Calibration | Due Calibration |
|-----------------------------------------------------------------------------|------------------|-----------------|
| 1. Semianechoic Absorber Lined Chamber ETS LINDGREN FACT 3 200 STP | N.A. | N.A. |
| 2. Shielded Room ETS LINDGREN S101 | N.A. | N.A. |
| 3. Biconical/Log Antenna 30MHz - 6GHz ETS LINDGREN 3142E | 2017/09 | 2020/09 |
| 4. RF Pre-amplifier 40 dB, 10 MHz - 6 GHz BONN ELEKTRONIK BLNA 0160-01N | 2020/02 | 2021/02 |
| 5. EMI Test Receiver 7 GHz ROHDE AND SCHWARZ ESR7 | 2018/10 | 2020/10 |
| 6. DC Power Supply 30V/5A KEYSIGHT TECHNOLOGIES U8002A | N.A. | N.A. |
| 7. Digital Multimeter, FLUKE 175 | 2019/10 | 2020/10 |
| 8. Horn antenna 1-18 GHz SCHWARZBECK MESS-ELEKTRONIK BBHA 9120 D | 2018/01 | 2021/01 |
| 9. Broadband Horn antenna 18 - 40 GHz SCHWARZBECK MESS-ELEKTRONIK BBHA 9170 | 2018/07 | 2021/07 |
| 10. RF Pre-amplifier G>30dB, 1-18GHz BONN ELEKTRONIK BLMA 0118-3A | 2019/11 | 2020/11 |
| 11. Low Noise Amplifier G>30dB, 18 - 40 GHz BONN ELEKTRONIK BLMA 1840-1M | 2019/02 | 2021/02 |
| 12. Signal and Spectrum Analyzer ROHDE AND SCHWARZ FSV40 | 2019/10 | 2021/10 |

Testing verdicts

| | |
|-----------------|-----|
| Not applicable: | N/A |
| Pass: | P |
| Fail: | F |
| Not measured: | N/M |

Summary

| FCC PART 15 PARAGRAPH / RSS-247 | | |
|----------------------------------------------------------------------------------------------------------------------------------------------------------|---------|--------|
| Requirement – Test case | Verdict | Remark |
| FCC 15.209 (a), 15.247 (d), 15.407 (b) / RSS-Gen 8.9, RSS-247 5.5, 6.2.1.2, 6.2.2.2, 6.2.3.2 & 6.2.4.2: - Emission limitations radiated (Transmitter) | P | (1) |
| <u>Supplementary information and remarks:</u> | | |
| (1) Only co-location radiated spurious emission test was requested. | | |

Appendix A: Test results.

INDEX

| | |
|----------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| TEST CONDITIONS | 11 |
| FCC 15.209 (a), 15.247 (d), 15.407 (b) / RSS-Gen 8.9, RSS-247 5.5, 6.2.1.2, 6.2.2.2, 6.2.3.2 & 6.2.4.2 Emission limitations radiated (Transmitter) | 16 |

TEST CONDITIONS

POWER SUPPLY (V):

Vnominal: 12 Vdc
 Type of Power Supply: External DC (Vehicle battery).

ANTENNA:

Bluetooth EDR:

Type of Antenna: External antenna.
 Maximum Declared Antenna Gain: +1.8 dBi (Antenna gain plus antenna cable loss).

802.11 bgn SISO:

Type of Antenna: External antenna.
 Maximum Declared Antenna Gain: +2.4 dBi (Antenna gain plus antenna cable loss).

802.11 a20 / n2040 / ac2040 / ac80:

Type of Antenna: External antenna.
 Maximum Declared Antenna Gain: +2.5 dBi. (Antenna gain plus antenna cable loss).

RADIOS AND CHANNELS TESTED:

| Bluetooth EDR / FHSS | | |
|----------------------|-------------------------|-------------------------|
| Mode: | Basic Rate (GFSK - DH5) | |
| Channel Spacing: | 1 MHz | |
| Frequency Range: | 2402 MHz to 2480 MHz | |
| Transmit Channels | Channel | Channel Frequency (MHz) |
| | Middle: 38 | 2440 |

| WLAN 2.4 GHz (IEEE 802.11 b/g/n20) / DTS | | |
|------------------------------------------|-------------------------------------|-------------------------|
| Mode: | 802.11 b SISO: 1, 2, 5.5 & 11 Mbps. | |
| Channel Spacing: | 20 MHz | |
| Frequency Range: | 2412 MHz to 2472 MHz | |
| Transmit Channels | Channel | Channel Frequency (MHz) |
| | Middle: 6 | 2437 |

| WLAN 5 GHz (IEEE 802.11 a20/n2040/ac204080) / U-NII-1 | | |
|-------------------------------------------------------|------------------------------------------------------|-------------------------|
| Mode: | 802.11 a20 SISO: 6, 9, 12, 18, 24, 36, 48 & 54 Mbps. | |
| Frequency Range: | 5150 MHz to 5250 MHz | |
| Channel Spacing: | 20 MHz | |
| Transmit Channels | Channel | Channel Frequency (MHz) |
| | Middle: 40 | 5200 |

| | | |
|-------------------|-------------------------------------------------------|-------------------------|
| | WLAN 5 GHz (IEEE 802.11 a20/n2040/ac204080) / U-NII-3 | |
| Mode: | 802.11 ac20 SISO: 6, 9, 12, 18, 24, 36, 48 & 54 Mbps. | |
| Frequency Range: | 5725 MHz to 5850 MHz | |
| Channel Spacing: | 20 MHz | |
| Transmit Channels | Channel | Channel Frequency (MHz) |
| | Middle: 157 | 5785 |

The test set-up was made in accordance to the general provisions of FCC DTS Measurement 558074 D01 DTS Meas Guidance v05r2 dated April 2, 2019 and FCC Unlicensed National Information Infrastructure (U-NII) Devices 789033 D02 General U-NII Test Procedures New Rules v02r01 dated Dec 14, 2017.

The EUT was tested in the following operating mode:

- Continuous transmission with a modulated carrier at maximum power in all required channels selecting the supported data rates/modulations types.

During transmitter test the EUT was being controlled by the SW tool to operate in a continuous transmit mode on the test channel as required and in each of the different modulation modes.

Selected Transmission Mode for each Radio:

The following configurations were selected based on preliminary testing that identified those corresponding to the worst cases:

* Bluetooth Basic Rate: Transmitter radiated spurious emissions tests were performed with the EUT transmitting in Basic Rate mode because its power is higher than EDR mode.

* WLAN 2.4 GHz: Transmitter radiated spurious emissions tests were performed with the EUT transmitting in 802.11 b / 1Mbps mode configuration as this mode was found as the worst case for spurious emissions than all the other 2.4 GHz WLAN SISO modes.

* WLAN 5 GHz U-NII-1 band: Transmitter radiated spurious emissions tests were performed with the EUT transmitting in 802.11 a20 / 6Mbps mode configuration as these modes were found as the worst case for spurious emissions than all the other 5 GHz WLAN U-NII-1 band SISO modes.

* WLAN 5 GHz U-NII-3 band: Transmitter radiated spurious emissions tests were performed with the EUT transmitting in 802.11 ac20 / 6Mbps mode configuration as these modes were found as the worst case for spurious emissions than all the other 5 GHz WLAN U-NII-3 band SISO modes.

TESTED SIMULTANEOUS TRANSMISSION MODES:

* **Co-location Bluetooth, WLAN 2.4 GHz, WLAN 5 GHz U-NII-1 band**, with the EUT configured to simultaneously transmit three signals at maximum output power:

Bluetooth Basic Rate in DH5 mode, WLAN 2.4GHz in 802.11 b / 1 Mbps, WLAN 5GHz in 802.11 a20 / 6 Mbps.

* **Co-location Bluetooth, WLAN 2.4 GHz, WLAN 5 GHz U-NII-3 band**, with the EUT configured to simultaneously transmit three signals at maximum output power:

Bluetooth Basic Rate in DH5 mode, WLAN 2.4GHz in 802.11 b / 1 Mbps, WLAN 5GHz in 802.11 ac20 / MCS0.


RADIATED MEASUREMENTS

All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m. The EUT was placed at a height of 80 cm above the reference ground plane in the center of the chamber turntable to perform the measurements below 1GHz and The EUT was placed at a height of 1.5 meters above the test chamber floor in the center of the chamber turntable to perform the measurements above 1GHz. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.


Measurements were made in both horizontal and vertical planes of polarization.

The final measured value, for the given emission, in the tables below incorporates the calibrated antenna factor, preamplifier gain (if used) and cable losses.


Radiated measurements setup 30 MHz < f < 1 GHz:



Radiated measurements setup $f > 1$ GHz up to 17 GHz:



Radiated measurements setup $f > 17$ GHz up to 40 GHz:



FCC 15.209 (a), 15.247 (d), 15.407 (b) / RSS-Gen 8.9, RSS-247 5.5, 6.2.1.2, 6.2.2.2, 6.2.3.2 & 6.2.4.2 Emission limitations radiated (Transmitter)

SPECIFICATION:

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), appearing outside of the band 13.110 MHz - 14.010 MHz band must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c) / RSS-Gen):

| Frequency Range (MHz) | Field strength ($\mu\text{V/m}$) | Field strength ($\text{dB}\mu\text{V/m}$) | Measurement distance (m) |
|-----------------------|------------------------------------|---------------------------------------------|--------------------------|
| 0.009-0.490 | 2400/F(kHz) | - | 300 |
| 0.490-1.705 | 24000/F(kHz) | - | 30 |
| 1.705 - 30.0 | 30 | 29.54 | 30 |
| 30 - 88 | 100 | 40 | 3 |
| 88 - 216 | 150 | 43.5 | 3 |
| 216 - 960 | 200 | 46 | 3 |
| 960 - 40000 | 500 | 54 | 3 |

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

RSS-247. Attenuation below the general field strength limits specified in RSS-Gen is not required.

RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-40 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

Test performed on the following worst cases in all relevant tests channels:

• **Mode Bluetooth EDR, 802.11 b, 802.11 a20 U-NII-1.**

Bluetooth EDR: Middle Channel (2440 MHz). GFSK.
 802.11 b: BW=20 MHz, Middle Channel (2437 MHz), 1Mbps.
 802.11 a20: BW=20 MHz, Middle Channel (5200 MHz), 6Mbps.

LIMIT: The spurious frequencies were measured at 3 meter. The limit of the test is determined by:

| Frequency Range | Detector | Limit at 3m (dBµV/m) |
|--------------------|-----------|------------------------------------|
| 30 MHz to 88 MHz | Quasi-PK | 40 dBµV/m |
| 88 MHz to 216 MHz | Quasi -PK | 43.5 dBµV/m |
| 216 MHz to 960 MHz | Quasi -PK | 46 dBµV/m |
| 960 MHz to 1 GHz | Quasi -PK | 54 dBµV/m |
| 1 GHz to 26 GHz | PK | 74 dBµV/m |
| 26 to 40 GHz | PK | 68.23 dBµV/m (*) OR 74 dBµV/m (**) |
| 1 to 40 GHz | AVG | 54 dBµV/m (**) |

(*) Radiated emissions which fall in the non-restricted bands.

(**) Radiated emissions which fall in the restricted bands, as defined in §15.205(a).

Frequency range 30 MHz - 1 GHz

The spurious emissions below 1 GHz do not depend on either the operating channel or the modulation mode selected in the EUT.

Spurious frequencies detected at less than 20 dB below the limit:

| Spurious frequency (MHz) | Emission Level (dBµV/m) | Limit (dBµV/m) | Polarization | Detector | Measurement Uncertainty (dB) |
|--------------------------|-------------------------|----------------|--------------|------------|------------------------------|
| 45.698 | 32.1 | 40 | V | Quasi-peak | <± 5.08 |
| 125.012 | 35.6 | 43.5 | V | Quasi-peak | <± 5.08 |
| 250.012 | 30.4 | 46 | V | Quasi-peak | <± 5.08 |
| 375.019 | 30.6 | 46 | H | Quasi-peak | <± 5.08 |
| 477.716 | 33.1 | 46 | H | Quasi-peak | <± 5.08 |
| 625.014 | 31 | 46 | V | Quasi-peak | <± 5.08 |
| 720.01 | 34.1 | 46 | H | Quasi-peak | <± 5.08 |


Frequency range 1 - 40 GHz

Spurious frequencies detected at less than 20 dB below the limit:


| Spurious frequency (GHz) | Emission Level (dBµV/m) | Limit (dBµV/m) | Polarization | Detector | Measurement Uncertainty (dB) |
|--------------------------|-------------------------|----------------|--------------|----------|------------------------------|
| 5.6341 | 51.15 | 74 | H | Peak | <± 4.11 |
| 7.3095 | 39.53 | 74 | H | Peak | <± 4.11 |
| 10.4005 | 60.55 | 74 | H | Peak | <± 5.13 |
| | 47.5 | 54 | | AVG | |

Verdict: PASS

FREQUENCY RANGE 30 MHz - 1 GHz




FREQUENCY RANGE 1 – 7 GHz




The peaks above the highest limit are the Bluetooth EDR, WLAN 2.4 GHz and WLAN 5 GHz carrier frequencies.

FREQUENCY RANGE 7 - 17 GHz



FREQUENCY RANGE 17 - 40 GHz



• **Mode Bluetooth EDR, 802.11 b, 802.11 ac20 U-NII-3.**

Bluetooth EDR: Middle Channel (2440 MHz). GFSK.
 802.11 b: BW=20 MHz, Middle Channel (2437 MHz), 1Mbps.
 802.11 ac20 : BW=20 MHz, Middle Channel (5785 MHz), MCS0.

LIMIT: The spurious frequencies were measured at 3 meter. The limit of the test is determined by:

| Frequency Range | Detector | Limit at 3m (dBµV/m) |
|--------------------|-----------|------------------------------------|
| 30 MHz to 88 MHz | Quasi-PK | 40 dBµV/m |
| 88 MHz to 216 MHz | Quasi -PK | 43.5 dBµV/m |
| 216 MHz to 960 MHz | Quasi -PK | 46 dBµV/m |
| 960 MHz to 1 GHz | Quasi -PK | 54 dBµV/m |
| 1 GHz to 26 GHz | PK | 74 dBµV/m |
| 26 to 40 GHz | PK | 68.23 dBµV/m (*) OR 74 dBµV/m (**) |
| 1 to 40 GHz | AVG | 54 dBµV/m (**) |

(*) Radiated emissions which fall in the non-restricted bands.

(**) Radiated emissions which fall in the restricted bands, as defined in §15.205(a).

Frequency range 30 MHz - 1 GHz

The spurious emissions below 1 GHz do not depend on either the operating channel or the modulation mode selected in the EUT.

Spurious frequencies detected at less than 20 dB below the limit:

| Spurious frequency (MHz) | Emission Level (dBµV/m) | Limit (dBµV/m) | Polarization | Detector | Measurement Uncertainty (dB) |
|--------------------------|-------------------------|----------------|--------------|------------|------------------------------|
| 500.014 | 27.2 | 46 | V | Quasi-peak | <± 5.08 |
| 625.014 | 29.3 | 46 | V | Quasi-peak | <± 5.08 |


Frequency range 1 - 40 GHz

Spurious frequencies detected at less than 20 dB below the limit:


| Spurious frequency (GHz) | Emission Level (dBµV/m) | Limit (dBµV/m) | Polarization | Detector | Measurement Uncertainty (dB) |
|--------------------------|-------------------------|----------------|--------------|----------|------------------------------|
| 5.6363 | 52.15 | 74 | H | Peak | <± 4.11 |
| 7.3125 | 40.54 | 74 | V | Peak | <± 4.11 |
| 11.56983 | 51.69 | 74 | H | Peak | <± 5.13 |

Verdict: PASS

FREQUENCY RANGE 30 MHz - 1 GHz




FREQUENCY RANGE 1 – 7 GHz



The peaks above the highest limit are the Bluetooth EDR, WLAN 2.4 GHz and WLAN 5 GHz carrier frequencies.

FREQUENCY RANGE 7 - 17 GHz



FREQUENCY RANGE 17 - 40 GHz

