

Test report No:  
 NIE: 60268RAN.004A3

## Assessment report

### RF EXPOSURE REPORT ACCORDING TO FCC 47 CFR Part 2.1091 ISED RSS-102 Issue 5:2015

(*) Identification of item under evaluation	Automotive infotainment System
(*) Trademark	Mercedes-Benz
(*) Model and /or type reference	NTG7 PREMIUM
Other identification of the product	FCC ID: T8GNTG7PRE IC: 6434A-NTG7PRE HW Version: D4 SW Version: E17
(*) Features	FM/AM/DAB/DVBT USB, Bluetooth, WLAN, GNSS
Manufacturer	HARMAN BECKER AUTOMOTIVE SYSTEMS GMBH BECKER-GOERING-STR. 16 76307 KARLSBAD GERMANY
Test method requested, standard	FCC 47 CFR Part 2.1091 Radiofrequency radiation exposure evaluation: mobile devices. ISED RSS-102 Issue 5 (2015-03) – Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) IEEE Std C95.3™ -2002 (R2008). IEEE Recommended Practice for Measurements and Computations of Radio Frequency Electromagnetic Fields With Respect to Human Exposure to Such Fields, 100 kHz–300 GHz
Summary	IN COMPLIANCE
Approved by (name / position & signature)	Miguel Lacave Antennas Lab Manager
Date of issue	2019-12-17
Report template No	FAN36_01 (*) "Data provided by the client"

## Index

Competences and guarantees .....	3
General conditions .....	3
Data provided by the client.....	3
Identification of the client.....	3
Document history .....	4
General description of the device under evaluation.....	4
RF Exposure Assessment result and verdict.....	5
Appendix A: FCC RF Exposure information .....	7
FCC RF Exposure evaluation .....	8
FCC MPE Evaluation .....	9
Appendix B: ISED RF Exposure information .....	10
ISED RF Exposure evaluation for mobile devices.....	11
ISED MPE Evaluation .....	12

## Competences and guarantees

---

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification S.A.U. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification at the time of performance of the test.

DEKRA Testing and Certification S.A.U. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Assessment Report apply only to the particular item under test established in this document.

**IMPORTANT:** No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification S.A.U.

## General conditions

---

1. This report is only referred to the item that has undergone the assessment.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification S.A.U.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification S.A.U. and the Accreditation Bodies

## Data provided by the client

---

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item tested", "Trademark", "Model and/or type reference tested").
2. Maximum output power and maximum antenna gain information.
3. The sample consists of an automotive head unit to be installed in cars with the following features: FM/AM/DAB/DVBT, USB, Bluetooth, WLAN and GNSS.

DEKRA Testing and Certification S.A.U. declines any responsibility with respect to the information provided by the client and that may affect the validity of results.

## Identification of the client

---

Harman Becker Automotive Systems GmbH  
Becker Göring Strasse 16.  
76307. Karlsbad.  
Germany.

## Document history

Report number	Date	Description
60268RAN.004	2019-10-18	First release
60268RAN.004A1	2019-11-07	Second release. Updated antenna gain values.
60268RAN.004A2	2019-12-04	Third release. Added 5.1GHz frequency band.
60268RAN.004A3	2019-12-17	Fourth release. Updated simultaneous transmission conditions.

## General description of the device under evaluation

The device under evaluation consists of an automotive head unit to be installed in cars with the following features: FM/AM/DAB/DVBT, USB, Bluetooth, WLAN and GNSS.

According to the manufacturer, during its normal use, the separation distance between the device and the body of nearby users will be greater than 20 cm. In order to perform the assessment a conservative evaluation distance of 20 cm has been used.

The equipment specifications declared by the manufacturer for each supported technology and band are:

Technology / Mode	Band	Frequency (MHz)	Maximum Conducted Output Power (dBm)	Antenna peak gain (dBi)	Cable loss (dBm)	Maximum E.I.R.P. (dBm)	Maximum E.I.R.P. (mW)
WLAN 1 (SISO/MIMO)	2.4 GHz	2412 - 2484	10.00	3.00	0.60	12.40	17.38
WLAN 2 (MIMO)	2.4 GHz	2412 - 2484	10.00	3.00	0.80	12.20	16.60
WLAN 3 (SISO)	5.1 & 5.7 GHz	5150 - 5825	14.00	4.50	2.00	16.50	44.67
WLAN 4 (MIMO)	5.1 & 5.7 GHz	5150 - 5825	14.00	4.50	1.30	17.20	52.48
WLAN 5 (MIMO)	5.1 & 5.7 GHz	5150 - 5825	14.00	4.50	1.00	17.50	56.23
Bluetooth	2.4 GHz	2402 - 2480	10.00	3.00	1.20	11.80	15.14

**Table 1:** Equipment specifications

## RF Exposure Assessment result and verdict

### FCC assessment:

Limits for Maximum Permissible Exposure (MPE) to comply with FCC 47 CFR § 2.1091 are defined in “§1.1310 Radiation Exposure limits, paragraph (e)”:

Technology / Mode	Band	Frequency (MHz)	Distance (cm)	Power density (mW/cm <sup>2</sup> )	FCC General Population Limit (mW/cm <sup>2</sup> )	Verdict
WLAN 1 (SISO/MIMO)	2.4 GHz	2412 - 2484	20.00	0.00	1.00	<b>Pass</b>
WLAN 2 (MIMO)	2.4 GHz	2412 - 2484	20.00	0.00	1.00	<b>Pass</b>
WLAN 3 (SISO)	5.1 & 5.7 GHz	5150 - 5825	20.00	0.01	1.00	<b>Pass</b>
WLAN 4 (MIMO)	5.1 & 5.7 GHz	5150 - 5825	20.00	0.01	1.00	<b>Pass</b>
WLAN 5 (MIMO)	5.1 & 5.7 GHz	5150 - 5825	20.00	0.01	1.00	<b>Pass</b>
Bluetooth	2.4 GHz	2402 - 2480	20.00	0.00	1.00	<b>Pass</b>

**Table 2:** Assessment result and verdict

### Simultaneous Transmission assessment:

The device supports simultaneous transmission for the following technology combinations:

1. WLAN 2.4 GHz MIMO and WLAN 5 GHz SISO and Bluetooth
2. WLAN 2.4 GHz MIMO and Bluetooth
3. WLAN 5 GHz MIMO and Bluetooth

Simultaneous technologies and modes	Result	Limit	Verdict
WLAN 1 (2.4 GHz MIMO) + WLAN 2 (2.4 GHz MIMO) + WLAN 3 (5 GHz SISO)	0.02	1	<b>Pass</b>
WLAN 1 (2.4 GHz MIMO) + WLAN 2 (2.4 GHz MIMO) + Bluetooth	0.01	1	<b>Pass</b>
WLAN 4 (5 GHz MIMO) + WLAN 5 (5 GHz MIMO) + Bluetooth	0.02	1	<b>Pass</b>

**Table 3:** Simultaneous Transmission assessment

**ISED assessment:**

Limits for RF Field Strength to comply with RSS-102 Issue 5 are defined in “Health Canada’s RF exposure guideline, Safety code 6”:

Technology / Mode	Band	Frequency (MHz)	Distance (cm)	Power density (W/m <sup>2</sup> )	ISED General Public Limit (W/m <sup>2</sup> )	Verdict
WLAN 1 (SISO/MIMO)	2.4 GHz	2412 - 2484	20.00	0.03	5.37	<b>Pass</b>
WLAN 2 (MIMO)	2.4 GHz	2412 - 2484	20.00	0.03	5.37	<b>Pass</b>
WLAN 3 (SISO)	5.1 & 5.7 GHz	5150 - 5825	20.00	0.09	9.01	<b>Pass</b>
WLAN 4 (MIMO)	5.1 & 5.7 GHz	5150 - 5825	20.00	0.10	9.01	<b>Pass</b>
WLAN 5 (MIMO)	5.1 & 5.7 GHz	5150 - 5825	20.00	0.11	9.01	<b>Pass</b>
Bluetooth	2.4 GHz	2402 - 2480	20.00	0.03	5.35	<b>Pass</b>

**Table 4:** Assessment result and verdict

Simultaneous Transmission assessment:

The device supports simultaneous transmission for the following technology combinations:

1. WLAN 2.4 GHz SISO/MIMO and WLAN 5 GHz SISO and Bluetooth
2. WLAN 2.4 GHz SISO/MIMO and Bluetooth
3. WLAN 5 GHz MIMO and Bluetooth

Simultaneous technologies and modes	Result	Limit	Verdict
WLAN 1 (2.4 GHz MIMO) + WLAN 2 (2.4 GHz MIMO) + WLAN 3 (5 GHz SISO)	0.03	1	<b>Pass</b>
WLAN 1 (2.4 GHz MIMO) + WLAN 2 (2.4 GHz MIMO) + Bluetooth	0.02	1	<b>Pass</b>
WLAN 4 (5 GHz MIMO) + WLAN 5 (5 GHz MIMO) + Bluetooth	0.03	1	<b>Pass</b>

**Table 5:** Simultaneous Transmission assessment

## Appendix A: FCC RF Exposure information

## FCC RF Exposure evaluation

Devices operating in standalone mobile device exposure conditions may contain a single transmitter or multiple transmitters that do not transmit simultaneously. A minimum test separation distance  $\geq 20$  cm is required between the antenna and radiating structures of the device and nearby persons to apply mobile device exposure limits. The distance must be at least 20 cm and fully supported by the operating and installation configurations of the transmitter and its antenna(s), according to the source-based time-averaged maximum power requirements of § 2.1091(d)(2). In cases where cable losses or other attenuations are applied to determine compliance, the most conservative operating configurations and exposure conditions must be evaluated. The minimum test separation distance required for a device to comply with mobile device exposure conditions must be clearly identified in the installation and operating instructions, for all installation and exposure conditions, to enable users and installers to comply with RF exposure requirements. For mobile devices that have the potential to operate in portable device exposure conditions, similar to the configurations described in § 2.1091(d)(4), a KDB inquiry is required to determine the SAR test requirements for demonstrating compliance.

When a device qualifies for the categorical exclusion provision of § 2.1091(c), the minimum test separation distance may be estimated, when applicable, by simple calculations according to plane-wave equivalent conditions, to ensure the transmitter and its antenna(s) can operate in manners that meet or exceed the estimated distance. The source-based time-averaged maximum radiated power, according to the maximum antenna gain, must be applied to calculate the field strength and power density required to establish the minimum test separation distance. When the estimated test separation distance becomes overly conservative and does not support compliance, MPE measurement or computational modeling may be used to determine the required minimum separation distance.

According to §1.1310 Radiofrequency radiation exposure limits, paragraph (e), the limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields are:

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3–3.0	614	1.63	* 100	6
3.0–30	1842/f	4.89/f	* 900/f <sup>2</sup>	6
30–300	61.4	0.163	1.0	6
300–1,500			f/300	6
1,500–100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34	614	1.63	* 100	30
1.34–30	824/f	2.19/f	* 180/f <sup>2</sup>	30
30–300	27.5	0.073	0.2	30
300–1,500			f/1500	30
1,500–100,000			1.0	30

f = frequency in MHz \* = Plane-wave equivalent power density



## FCC MPE Evaluation

Each supported transmission technology will be evaluated to determine if it is in compliance with limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields.

In order to perform the assessment, the following equations have been used for the calculations; these equations are accurate in the far-field of an antenna and will over-predict power density in the near field, where they could be used for making a "worst case" or conservative prediction:

$$\text{Power density: } S[mW / cm^2] = \frac{P_{E.I.R.P.}[mW]}{4\pi R[cm]^2}$$

$$\text{Minimum compliance distance: } R_{\min}[cm] = \sqrt{\frac{P_{E.I.R.P.}[mW]}{4\pi S[mW / cm^2]}}$$

Where:

$S$  = power density

$P_{E.I.R.P.}$  = Equivalent isotropically radiated power

$R$  = distance to the center of radiation of the antenna (evaluation distance)

$R_{\min}$  = distance to the center of radiation of the antenna

### **Multiple frequencies assessment**

When multiple sources are introduced into an environment, it becomes necessary to address the sources interdependently, since each source will contribute some percentage of the maximum exposure toward the total exposure at a fixed location. The sum of the ratios of the exposure from each source to the corresponding maximum exposure for the frequency of each source must be evaluated.

The exposure complies with the maximum permissible exposure if the sum of the ratios is less than unity:

$$\sum_{i=1}^n \frac{S_i}{MPE_i} < 1$$

Where

$S_i$  is the power flux density of each source;

$MPE_i$  is the power flux density basic restriction of each source.

## Appendix B: ISED RF Exposure information

## ISED RF Exposure evaluation for mobile devices

According to RSS-102 Issue 5, Paragraph “4. Exposure Limits”, Industry of Canada has adopted the RF field strength limits established in Health Canada’s RF exposure guideline, Safety code 6:

**Table 4: RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)**

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m <sup>2</sup> )	Reference Period (minutes)
0.003-10 <sup>-21</sup>	83	90	-	Instantaneous*
0.1-10	-	0.73/ <i>f</i>	-	6**
1.1-10	87/ <i>f</i> <sup>0.5</sup>	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ <i>f</i> <sup>0.25</sup>	0.1540/ <i>f</i> <sup>0.25</sup>	8.944/ <i>f</i> <sup>0.5</sup>	6
48-300	22.06	0.05852	1,291	6
300-6000	3.142 <i>f</i> <sup>0.3417</sup>	0.008335 <i>f</i> <sup>0.3417</sup>	0.02619 <i>f</i> <sup>0.6834</sup>	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ <i>f</i> <sup>1.2</sup>
150000-300000	0.158 <i>f</i> <sup>0.5</sup>	4.21 x 10 <sup>-4</sup> <i>f</i> <sup>0.5</sup>	6.67 x 10 <sup>-5</sup> <i>f</i>	616000/ <i>f</i> <sup>1.2</sup>
Note: <i>f</i> is frequency in MHz. *Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).				

**Table 6: RF Field Strength Limits for Controlled Use Devices (Controlled Environment)**

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m <sup>2</sup> )	Reference Period (minutes)
0.003-10 <sup>23</sup>	170	180	-	Instantaneous*
0.1-10	-	1.6/ <i>f</i>	-	6**
1.29-10	193/ <i>f</i> <sup>0.5</sup>	-	-	6**
10-20	61.4	0.163	10	6
20-48	129.8/ <i>f</i> <sup>0.25</sup>	0.3444/ <i>f</i> <sup>0.25</sup>	44.72/ <i>f</i> <sup>0.5</sup>	6
48-100	49.33	0.1309	6.455	6
100-6000	15.60 <i>f</i> <sup>0.25</sup>	0.04138 <i>f</i> <sup>0.25</sup>	0.6455 <i>f</i> <sup>0.5</sup>	6
6000-15000	137	0.364	50	6
15000-150000	137	0.364	50	616000/ <i>f</i> <sup>1.2</sup>
150000-300000	0.354 <i>f</i> <sup>0.5</sup>	9.40 x 10 <sup>-4</sup> <i>f</i> <sup>0.5</sup>	3.33 x 10 <sup>-4</sup> <i>f</i>	616000/ <i>f</i> <sup>1.2</sup>
Note: <i>f</i> is frequency in MHz. *Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).				

## ISED MPE Evaluation

---

Each supported transmission technology will be evaluated to determine if it is in compliance with RSS-102 Issue 5, RF Field Strength Limits for devices used by the General Public.

In order to perform the assessment, the following equations have been used for the calculations; these equations are accurate in the far-field of an antenna and will over-predict power density in the near field, where they could be used for making a "worst case" or conservative prediction:

$$\text{Power density: } S[W/m^2] = \frac{P_{E.I.R.P.}[W]}{4\pi R[m]^2}$$

$$\text{Minimum compliance distance: } R_{\min}[m] = \sqrt{\frac{P_{E.I.R.P.}[W]}{4\pi S[W/m^2]}}$$

Where:

$S$  = power density

$P_{E.I.R.P.}$  = Equivalent isotropically radiated power

$R$  = distance to the center of radiation of the antenna (evaluation distance)

$R_{\min}$  = distance to the center of radiation of the antenna

### **Multiple frequencies assessment**

When multiple sources are introduced into an environment, it becomes necessary to address the sources interdependently, since each source will contribute some percentage of the maximum exposure toward the total exposure at a fixed location. The sum of the ratios of the exposure from each source to the corresponding maximum exposure for the frequency of each source must be evaluated.

The exposure complies with the maximum permissible exposure if the sum of the ratios is less than unity:

$$\sum_{i=1}^n \frac{S_i}{MPE_i} < 1$$

Where

$S_i$  is the power flux density of each source;

$MPE_i$  is the power flux density basic restriction of each source.