

Test report No:  
NIE: 76930RAN.002A1

## Assessment report

### RF EXPOSURE REPORT ACCORDING TO FCC 47 CFR Part 2.1091; FCC 47 CFR Part 1.1307 FCC 47 CFR Part 1.1310

(*) Identification of item under evaluation	Telematic control unit with wireless technologies, used in automotive industry
(*) Trademark	VW AG
(*) Model and /or type reference	ConBox-High
(*) Derived model not evaluated	ConBox High RD
(*) Other identification of the product	HW version: 043 SW version: 0595 FCC ID: T8GP114 IC: 6434A-P114
(*) Features	GSM, UMTS, LTE, GNSS, Wi-Fi, BTLE, BT_EDR
(*) Manufacturer	HARMAN BECKER AUTOMOTIVE SYSTEMS GMBH BECKER-GOERING-STR. 16 76307, KARLSBAD, GERMANY
Test method requested, standard	FCC 47 CFR Part 2.1091 Radiofrequency radiation exposure evaluation: mobile devices. FCC 47 CFR Part 1.1307: Actions that may have a significant environmental effect, for which Environmental Assessments (EAs) must be prepared. FCC 47 CFR Part 1.1310: Radiofrequency radiation exposure limits.
Summary	IN COMPLIANCE
Approved by (name / position & signature)	Miguel Lacave Antennas Lab Manager
Date of issue	2024-01-29
Report template No	FAN36_02 (*) "Data provided by the client"

# Index

Competences and guarantees .....	3
General conditions .....	3
Data provided by the client.....	3
Identification of the client.....	5
Document history .....	5
Appendix A: FCC RF Exposure assessment result .....	6
General description of the device under evaluation .....	7
Evaluation Results.....	10
Appendix B: FCC RF Exposure information .....	12
RF Exposure determination of exemption.....	13
RF Exposure evaluation .....	15

## Competences and guarantees

---

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification, S.A.U. has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification, S.A.U. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification, S.A.U. at the time of performance of the test.

DEKRA Testing and Certification, S.A.U. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Assessment Report apply only to the particular item under test established in this document.

**IMPORTANT:** No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification, S.A.U.

## General conditions

---

1. This report is only referred to the item that has undergone the assessment.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification, S.A.U.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification, S.A.U. and the Accreditation Bodies

## Data provided by the client

---

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item under evaluation", "Trademark", "Model and/or type reference", "Derived model not evaluated", "General description of the device", "Other identification of the product").
2. Maximum output power, maximum antenna gain and use distance information.
3. The device under evaluation consists of a Telematic control unit with wireless technologies, used in automotive industry.
4. Derived model not evaluated. These models have been declared by the supplier of the sample as being the same as the model under evaluation.

**HARMAN Becker Automotive Systems GmbH**

Becker-Goering-Str. 16  
76307 Karlsbad, Germany



## Declaration of Comparability

**HARMAN BECKER**  
**Automotive Systems GmbH**

**Becker-Göring-Str. 16**  
**D-76307 Karlsbad, Germany**

To whom it may concern:

We, Harman Becker Automotive Systems GmbH, hereby declares that our products:

**ConBox-High** and **ConBox High RD** are equipped with the same NAD module (for each variant listed below) and the cellular part is identical between these TCU's.

Also, the test results are valid and representative for both projects as long as there are no modifications which may request additional tests.

ConBox Variant: A970, A971, A973, A974, A975, A976, A977, A978, A979, A980, A981, A982, A983, A984, P114, P115, P119

Sincerely,

i.v. 

---

By: Iulian-George Stoica  
Title: Principal Engineer, Quality Engineering  
e-mail: [iulian.stoica@harman.com](mailto:iulian.stoica@harman.com)  
Telephone: +40799 306 699  
Company: Harman Becker Automotive Systems GmbH

i.v. 

---

By: Olteanu Marius  
Title: Regulatory Product Compliance Expert  
e-mail: [marius.olteanu@harman.com](mailto:marius.olteanu@harman.com)

DEKRA Testing and Certification S.A.U. declines any responsibility with respect to the information provided by the client and that may affect the validity of results.

## Identification of the client

---

HARMAN BECKER AUTOMOTIVE SYSTEMS GMBH  
BECKER-GOERING-STR. 16  
76307, KARLSBAD, GERMANY

## Document history

---

Report number	Date	Description
76930RAN.002	2023-12-19	First release
76930RAN.002A1	2024-01-29	Second release. LTE Band 38 has been removed and LTE Band 28 has been included in the RF exposure evaluation This test report cancels and replaces report 76930RAN.002.

## Appendix A: FCC RF Exposure assessment result

## General description of the device under evaluation

---

Table 1 shows information used for the RF Evaluation, taking into account the following declared specifications for the device:

**Description and technologies:** the device under evaluation consists of a Telematic control unit with wireless technologies, used in automotive industry with the following features: GSM, UMTS, LTE, GNSS, Wi-Fi, BTLE, BT\_EDR.

The device under evaluation has four cellular communications ports, to which it is possible to connect several antennas. The worst-case antenna for each port has been considered to perform the RF exposure evaluation. Additionally, it has an internal backup cellular antenna, which has been also evaluated.

**Evaluation Distance:** according to the manufacturer, during its normal use, the separation distance between the radiating structures of the device and nearby users will be greater than 30 cm. In order to perform the assessment a conservative evaluation distance of 30 cm has been used.

**Maximum output power:**

- Values corresponding to cellular maximum output power have been declared by the device manufacturer (maximum output power values stated in manufacturer's technical description document).
- Values corresponding to BTEDR conducted output power have been measured and stated into 7Layers GmbH test report num. MDE\_HARMAN\_1736\_FCCa\_Rev1.
- Values corresponding to 802.11 b/g/n and BTLE conducted output power have been measured and stated into 7Layers GmbH test report num. MDE\_HARMAN\_1736\_FCCb\_rev1.
- Values corresponding to 802.11 a/n/ac conducted output power have been measured and stated into 7Layers GmbH test report num. MDE\_HARMAN\_1736\_FCCc\_rev2.

**Antennas:** the device supports several antennas for the GSM, UMTS, LTE, GNSS, Wi-Fi, BTLE, BT\_EDR transmitting technologies:

- "4M0.035.507.A" antenna for cellular transmissions in the external antenna port 1.
- "36a.035.502.A" antenna for cellular transmissions in the external antenna port 2.
- "4M0.035.504.A" antenna for cellular transmissions in the external antenna port 3.
- "Audi DDA Gen2 MLB BK roof" antenna for cellular transmissions in the external antenna port 4.
- "Internal Backup" antenna for cellular transmissions.
- "WLAN P1518 C5 10k" BT Wi-Fi antenna, for BTEDR, BTLE, 2.4 GHz and 5GHz transmissions.

Values corresponding to antennas gain have been declared by the device manufacturer (maximum peak gain stated in antenna manufacturer's datasheet).

The following table shows the information provided above:

Technology / Mode	Operating Band	Frequency under evaluation (MHz)	Maximum Conducted Output Power (Incl. Tune-Up) (dBm)	Duty Cycle (%)	Time Averaged Conducted Power (dBm)	Cellular Internal Antenna peak gain (dBi)	Antenna 1 peak gain (dBi)	Antenna 2 peak gain (dBi)	Antenna 3 peak gain (dBi)	Antenna 4 peak gain (dBi)	BT_WLAN External Antenna peak gain (dBi)	Maximum Averaged E.R.P (dBm)	Maximum Averaged E.R.P (mW)	Maximum Averaged E.I.R.P (dBm)	Maximum Averaged E.I.R.P (mW)
GSM	850	824 - 849	35.00	12.50	25.97	-0.10	4.50	5.50	-0.46	8.00	-	31.82	1520.23	33.97	2494.08
GPRS 1TX	850	824 - 849	35.00	12.50	25.97	-0.10	4.50	5.50	-0.46	8.00	-	31.82	1520.23	33.97	2494.08
GPRS 2TX	850	824 - 849	35.00	25.00	28.98	-0.10	4.50	5.50	-0.46	8.00	-	34.83	3040.47	36.98	4988.16
GPRS 3TX	850	824 - 849	33.20	37.50	28.94	-0.10	4.50	5.50	-0.46	8.00	-	34.79	3013.22	36.94	4943.46
GPRS 4TX	850	824 - 849	32.00	50.00	28.99	-0.10	4.50	5.50	-0.46	8.00	-	34.84	3047.68	36.99	5000.00
EGPRS 1TX	850	824 - 849	30.00	12.50	20.97	-0.10	4.50	5.50	-0.46	8.00	-	26.82	480.74	28.97	788.70
EGPRS 2TX	850	824 - 849	30.00	25.00	23.98	-0.10	4.50	5.50	-0.46	8.00	-	29.83	961.48	31.98	1577.39
EGPRS 3TX	850	824 - 849	28.20	37.50	23.94	-0.10	4.50	5.50	-0.46	8.00	-	29.79	952.86	31.94	1563.26
EGPRS 4TX	850	824 - 849	27.00	50.00	23.99	-0.10	4.50	5.50	-0.46	8.00	-	29.84	963.76	31.99	1581.14
GSM	1900	1850 - 1910	32.00	12.50	22.97	4.40	6.50	5.50	0.80	8.00	-	28.82	761.92	30.97	1250.00
GPRS 1TX	1900	1850 - 1910	32.00	12.50	22.97	4.40	6.50	5.50	0.80	8.00	-	28.82	761.92	30.97	1250.00
GPRS 2TX	1900	1850 - 1910	32.00	25.00	25.98	4.40	6.50	5.50	0.80	8.00	-	31.83	1523.84	33.98	2500.00
GPRS 3TX	1900	1850 - 1910	30.20	37.50	25.94	4.40	6.50	5.50	0.80	8.00	-	31.79	1510.19	33.94	2477.60
GPRS 4TX	1900	1850 - 1910	29.00	50.00	25.99	4.40	6.50	5.50	0.80	8.00	-	31.84	1527.46	33.99	2505.94
EGPRS 1TX	1900	1850 - 1910	29.00	12.50	19.97	4.40	6.50	5.50	0.80	8.00	-	25.82	381.87	27.97	626.48
EGPRS 2TX	1900	1850 - 1910	29.00	25.00	22.98	4.40	6.50	5.50	0.80	8.00	-	28.83	763.73	30.98	1252.97
EGPRS 3TX	1900	1850 - 1910	27.20	37.50	22.94	4.40	6.50	5.50	0.80	8.00	-	28.79	756.89	30.94	1241.74
EGPRS 4TX	1900	1850 - 1910	26.00	50.00	22.99	4.40	6.50	5.50	0.80	8.00	-	28.84	765.54	30.99	1255.94
UMTS	II	1850 - 1910	25.00	100.00	25.00	4.40	6.50	5.50	0.80	8.00	-	30.85	1216.19	33.00	1995.26
UMTS	IV	1710 - 1755	25.00	100.00	25.00	2.70	6.50	5.50	1.36	8.00	-	30.85	1216.19	33.00	1995.26
UMTS	V	824 - 849	25.00	100.00	25.00	-0.10	4.50	5.50	-0.46	8.00	-	30.85	1216.19	33.00	1995.26



Technology / Mode	Operating Band	Frequency under evaluation (MHz)	Maximum Conducted Output Power (Incl. Tune-Up) (dBm)	Duty Cycle (%)	Time Averaged Conducted Power (dBm)	Cellular Internal Antenna peak gain (dBi)	Antenna 1 peak gain (dBi)	Antenna 2 peak gain (dBi)	Antenna 3 peak gain (dBi)	Antenna 4 peak gain (dBi)	BT_WLAN External Antenna peak gain (dBi)	Maximum Averaged E.R.P (dBm)	Maximum Averaged E.R.P (mW)	Maximum Averaged E.I.R.P (dBm)	Maximum Averaged E.I.R.P (mW)
LTE	2	1850 - 1910	25.00	100.00	25.00	4.40	-	-	-	8.00	-	30.85	1216.19	33.00	1995.26
LTE	4	1710 - 1755	25.00	100.00	25.00	2.70	-	-	-	8.00	-	30.85	1216.19	33.00	1995.26
LTE	5	824 - 849	25.00	100.00	25.00	-0.10	-	-	-	8.00	-	30.85	1216.19	33.00	1995.26
LTE	7	2500 - 2570	25.00	100.00	25.00	4.30	-	-	-	8.00	-	30.85	1216.19	33.00	1995.26
LTE	12	699 - 716	25.00	100.00	25.00	-3.20	-	-	-	8.00	-	30.85	1216.19	33.00	1995.26
LTE	13	777 - 787	25.00	100.00	25.00	-3.20	-	-	-	8.00	-	30.85	1216.19	33.00	1995.26
LTE	28	703 - 748	25.00	100.00	25.00	4.30	-	-	-	8.00	-	30.85	1216.19	33.00	1995.26
LTE	66	1710 - 1780	25.00	100.00	25.00	2.70	-	-	-	8.00	-	30.85	1216.19	33.00	1995.26
802.11b/g/n	2.4 GHz	2412 - 2484	12.60	100.00	12.60	-	-	-	-	-	0.11	10.56	11.38	12.71	18.66
802.11a/n/ac	U-NII-1	5150 - 5250	14.90	100.00	14.90	-	-	-	-	-	1.99	14.74	29.79	16.89	48.87
802.11a/n/ac	U-NII-3	5725 - 5850	11.50	100.00	11.50	-	-	-	-	-	2.38	11.73	14.89	13.88	24.43
Bluetooth	2.4 GHz	2400 - 2483.5	10.20	100.00	10.20	-	-	-	-	-	0.11	8.16	6.55	10.31	10.74
BTLE	2.4 GHz	2400 - 2483.5	-1.70	100.00	-1.70	-	-	-	-	-	0.11	-3.74	0.42	-1.59	0.69

Table 1: Equipment specifications

## Evaluation Results

### RF Exposure Exemption evaluation:

Technology / Mode	Operating Band	Frequency under evaluation (MHz)	Distance (cm)	Time Averaged Conducted Power (mW)	Maximum Averaged E.R.P (mW)	§ 1.1307(b)(3).i.(B) Exposure Limit (mW)	Verdict for exemption § 1.1307(b)(3).i
GSM/GPRS	850	824 - 849	30.00	N/A	3047.68	1680.96	MPE required
GSM/GPRS	1900	1850 - 1910	30.00	N/A	1527.46	3060.00	MPE required (sim.TX)
UMTS	II	1850 - 1910	30.00	N/A	1216.19	3060.00	MPE required (sim.TX)
UMTS	IV	1710 - 1755	30.00	N/A	1216.19	3060.00	MPE required (sim.TX)
UMTS	V	824 - 849	30.00	N/A	1216.19	1680.96	MPE required (sim.TX)
LTE	2	1850 - 1910	30.00	N/A	1216.19	3060.00	MPE required (sim.TX)
LTE	4	1710 - 1755	30.00	N/A	1216.19	3060.00	MPE required (sim.TX)
LTE	5	824 - 849	30.00	N/A	1216.19	1680.96	MPE required (sim.TX)
LTE	7	2500 - 2570	30.00	N/A	1216.19	3060.00	MPE required (sim.TX)
LTE	12	699 - 716	30.00	N/A	1216.19	1425.96	MPE required (sim.TX)
LTE	13	777 - 787	30.00	N/A	1216.19	1585.08	MPE required (sim.TX)
LTE	28	703 - 748	30.00	N/A	1216.19	1434.12	MPE required (sim.TX)
LTE	66	1710 - 1780	30.00	N/A	1216.19	3060.00	MPE required (sim.TX)
802.11b/g/n	2.4 GHz	2412 - 2484	30.00	18.20	22.13	N/A	MPE required (sim.TX)
802.11a/n/ac	U-NII-1	5150 - 5250	30.00	30.90	59.57	N/A	MPE required (sim.TX)
802.11a/n/ac	U-NII-3	5725 - 5850	30.00	N/A	27.23	14.89	MPE required (sim.TX)
Bluetooth	2.4 GHz	2400 - 2483.5	30.00	10.47	12.74	N/A	MPE required (sim.TX)
BTLE	2.4 GHz	2400 - 2483.5	30.00	0.68	0.82	N/A	MPE required (sim.TX)

**Table 2:** FCC Exemption Evaluation Results

The device fails to comply with applicable §1.1307(b)(3).i. exemption limits, so Maximum Permissible Exposure (MPE) evaluation is necessary to demonstrate compliance.

**RF Exposure MPE evaluation:**

Technology / Mode	Operating Band	Frequency under evaluation (MHz)	Distance (cm)	Power density (mW/cm <sup>2</sup> )	FCC General Population Limit (mW/cm <sup>2</sup> )	Verdict
GSM/GPRS	850.00	824 - 849	30.00	0.44	0.55	Pass
GSM/GPRS	1900.00	1850 - 1910	30.00	0.22	1.00	Pass
UMTS	II	1850 - 1910	30.00	0.18	1.00	Pass
UMTS	IV	1710 - 1755	30.00	0.18	1.00	Pass
UMTS	V	824 - 849	30.00	0.18	0.55	Pass
LTE	2.00	1850 - 1910	30.00	0.18	1.00	Pass
LTE	4.00	1710 - 1755	30.00	0.18	1.00	Pass
LTE	5.00	824 - 849	30.00	0.18	0.55	Pass
LTE	7.00	2500 - 2570	30.00	0.18	1.00	Pass
LTE	12.00	699 - 716	30.00	0.18	0.47	Pass
LTE	13.00	777 - 787	30.00	0.18	0.52	Pass
LTE	28.00	703 - 748	30.00	0.18	1.00	Pass
LTE	66.00	1710 - 1780	30.00	0.18	0.47	Pass
802.11b/g/n	2.4 GHz	2412 - 2484	30.00	0.00	1.00	Pass
802.11a/n/ac	U-NII-1	5150 - 5250	30.00	0.00	1.00	Pass
802.11a/n/ac	U-NII-3	5725 - 5850	30.00	0.00	1.00	Pass
Bluetooth	2.4 GHz	2400 - 2483.5	30.00	0.00	1.00	Pass
BTLE	2.4 GHz	2400 - 2483.5	30.00	0.00	1.00	Pass

**Table 3: FCC Evaluation Results**

The computed value(s) are below the limit(s), so these modes meet the requirements stated in FCC 47 CFR Part 1.1310.

**Simultaneous transmission assessment:**

Simultaneous technologies and modes	Result ( $\sum$ of Pout/Pmax ratios)	Verdict ( $\sum \leq 1$ )
GPRS 4TX 850 + 802.11b/g/n 2.4 GHz + 802.11a/n/ac U-NII-1 + Bluetooth 2.4 GHz	0.81	Pass

**Table 4: Simultaneous Transmission assessment**

## Appendix B: FCC RF Exposure information

## RF Exposure determination of exemption

According to FCC 47 CFR §1.1307 (b)(3) Determination of exemption:

(i) For single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2), a single RF source is exempt if:

(A) The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);

(B) Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold  $P_{th}$  (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P_{th}$  is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

$d$  = the separation distance (cm);

(C) Or using Table 1 and the minimum separation distance ( $R$  in meters) from the body of a nearby person for the frequency ( $f$  in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply,  $R$  must be at least  $\lambda/2\pi$ , where  $\lambda$  is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of  $\lambda/4$  or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

TABLE 1 TO §1.1307(b)(3)(i)(C)—SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$ .
1.34-30	$3,450 R^2/f^2$ .
30-300	$3.83 R^2$ .
300-1,500	$0.0128 R^2 f$ .
1,500-100,000	$19.2R^2$ .

(ii) For multiple RF sources: Multiple RF sources are exempt if:

(A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).

(B) in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(B) of this section for P<sub>th</sub>, including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

P<sub>i</sub> = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

P<sub>th,i</sub> = the exemption threshold power (P<sub>th</sub>) according to paragraph (b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i.

ERP<sub>j</sub> = the ERP of fixed, mobile, or portable RF source j.

ERP<sub>th,j</sub> = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least λ/2π according to the applicable formula of paragraph (b)(3)(i)(C) of this section.

Evaluated<sub>k</sub> = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

Exposure Limit<sub>k</sub> = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from §1.1310 of this chapter.

The available maximum time-averaged power or effective radiated power (ERP), can be calculated using the following formula to assess compliance with the Exemption Limits:

$$P_{E.I.R.P.} = P_T + G_T - L_C$$

Where:

P<sub>T</sub> = transmitter time-averaged output power (including Duty Cycle and tune-up tolerance, if applicable)

G<sub>T</sub> = gain of the transmitting antenna

L<sub>C</sub> = signal attenuation in the connecting cable between the transmitter and the antenna if applicable

$$P_{E.R.P.} = P_{E.I.R.P.} - 2.15 \text{ dB}$$

## RF Exposure evaluation

Limits for Maximum Permissible Exposure (MPE) for RF sources are defined in FCC 47 CFR “§1.1310 Radiation Exposure limits, paragraph (e)”:

TABLE 1 TO §1.1310(E)(1)—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(i) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
<b>(ii) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

f = frequency in MHz. \* = Plane-wave equivalent power density.

Each supported transmission technology will be evaluated to determine if it is in compliance with limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields.

In order to perform the assessment, the following equations have been used for the calculations; these equations are accurate in the far-field of an antenna and will over-predict power density in the near field, where they could be used for making a "worst-case" or conservative prediction:

$$\text{Power density: } S[mW/cm^2] = \frac{P_{E.I.R.P.}[mW]}{4\pi R[cm]^2}$$

Where:

$S$  = power density

$P_{E.I.R.P.}$  = Equivalent isotropically radiated power

$R$  = distance to the center of radiation of the antenna (evaluation distance)

$$P_{E.I.R.P.} = P_T + G_T - L_C$$

Where:

$P_T$  = transmitter time-averaged output power (including Duty Cycle and tune-up tolerance, if applicable)

$G_T$  = gain of the transmitting antenna

$L_C$  = signal attenuation in the connecting cable between the transmitter and the antenna if applicable