

Test report No:
 NIE: 62486RRF.002

Partial Test Report

Reference Standard:
 USA FCC Part 22 & 90
 CANADA RSS-132

(*) Identification of item tested	Telematic control unit with wireless technologies, used in automotive industry
(*) Trademark	BMW
(*) Model and /or type reference	WAVE-11-HIGH-R1
Other identification of the product	HW version: D3 SW version: 20512H.001_047_009 FCC ID: T8GWAVE11HIGHR1 IC: 6434A-WAVE11HIGHR1
(*) Features	GSM, UMTS, LTE, 5G, GNSS
Applicant	HARMAN BECKER AUTOMOTIVE SYSTEMS GMBH BECKER-GOERING-STR. 16; 76307 KARLSBAD GERMANY
Test method requested, standard	USA FCC Part 22 (10-1-19 Edition). USA FCC Part 90 (10-1-19 Edition). CANADA RSS-132 Issue 3, Jan. 2013. - Radiated emissions. ANSI C63.26 - 2015. KDB 971168 D01 Power Meas License Digital Systems v03r01, April. 2018.
Approved by (name / position & signature)	José Carlos Luque RF Lab. Supervisor
Date of issue	2021-02-02
Report template No	FDT08_23 (*) "Data provided by the client"

Index

Competences and guarantees	3
General conditions	3
Uncertainty	3
Data provided by the client.....	3
Usage of samples	4
Test sample description	4
Identification of the client.....	6
Testing period and place.....	6
Document history	6
Environmental conditions	7
Remarks and comments	7
Testing verdicts.....	8
Summary	9
Appendix A: Test results for FCC Part 22 & 90 / RSS-132	11

Competences and guarantees

DEKRA Testing and Certification S.A.U. is a testing laboratory accredited by the National Accreditation Body (ENAC -Entidad Nacional de Acreditación), to perform the tests indicated in the Certificate No. 51/LE 147.

DEKRA Testing and Certification is a FCC-recognized accredited testing laboratory with appropriate scope of accreditation that include testing performed in this test report.

DEKRA Testing and Certification is an ISED-recognized accredited testing laboratory with appropriate scope of accreditation that include testing performed in this test report.

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification S.A.U. has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification S.A.U. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification S.A.U. at the time of performance of the test.

DEKRA Testing and Certification S.A.U. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document. **IMPORTANT:** No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification S.A.U.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification S.A.U.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification S.A.U. and the Accreditation Bodies.

Uncertainty

Uncertainty (factor $k=2$) was calculated according to the DEKRA Testing and Certification S.A.U. internal document PODT000.

Data provided by the client

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item tested", "Trademark", "Model and/or type reference tested").
2. The sample of the model WAVE-11-HIGH-R1 is a Telematics control unit with wireless technologies, used in automotive, equipped with 2 modems, OEM and customer. The project name WAVE has the meaning "Wireless Access in Vehicular Environment" and thus describes the key features of this device as Communication and Data Interface. This unit was designed for automotive usage and contains the following features: GSM, UMTS, LTE, 5G, and GNSS.

DEKRA Testing and Certification S.A.U. declines any responsibility with respect to the information provided by the client and that may affect the validity of results.

Usage of samples

Samples undergoing test have been selected by: The client.

- Sample S/01 is composed of the following elements:

Control Nº	Description	Model	Serial Nº	Date of reception
62486E/106	Telematic Control Unit	WAVE-11-HIGH-R1	B392160L4900519	2020/09/28
62486E/014	Antenna DA Wave 5G US	DA05DI20	--	2020/09/22
62486E/024	Antenna Box	AB01-I20-01	--	2020/09/22
62486E/025	Antenna Box	AB01-I20-01	--	2020/09/22
62486E/026	Antenna Box	AB01-I20-01	--	2020/09/22
62486E/027	Antenna Box	AB01-I20-01	--	2020/09/22
62486E/122	RF Harness	--	--	2020/09/28
62486E/061	Harness 20 pol	--	--	2020/09/22

Auxiliary elements used with the Sample S/01:

Control Nº	Description	Model	Serial Nº	Date of reception
62486E/110	Battery Li-ion	11FR1580-2	--	2020/09/28
62486E/044	Antenna ground planes for roof	--	--	2020/09/22
62486E/048	RF Cable for 4-Fakra	--	--	2020/09/22
62486E/057	OABR Cable	--	--	2020/09/22
62486E/066	OABR 1000 BaseT Converter	--	--	2020/09/22
62486E/069	I-Box OABR Adapter	--	--	2020/09/22
62486E/072	Ethernet Cable	--	--	2020/09/22
62486E/090	Speaker	FR7	--	2020/09/28
62486E/097	SOS Pulser (E-Call)	9385	11224	2020/09/28

Sample S/01 has undergone the following test(s): The Radiated tests indicated in the Appendix A.

Test sample description

Ports..... :	Port name and description	Cable					
		Specified max length [m]	Attached during test	Shielded	Coupled to patient ⁽³⁾		
	RF connector – code D violet (trunk/roof)	Port not used for SOP2021 (it has V2X interfaces and gateway for SDARS signal towards another ECU)	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>		
	RF connector – code C blue (trunk/roof)	>5m	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>		
	NanoMQS 20pol	>5m	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
	NanoMQS 10pol	>8m	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
	HDBT MATenet 2-Pol (Roof/Trunk)	>5m	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
	Antenna Connector grey (Roof)	<0.5m	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>		
Supplementary information to the ports..... :							
Rated power supply	Voltage and Frequency		Reference poles				
			L1	L2	L3	N	PE
	<input type="checkbox"/>	AC:	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	AC:	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
	<input checked="" type="checkbox"/>	DC: 12V car battery / attenuator (4,5 V ≤ UB ≤ 18 V; UB typical: 12 V)					
<input type="checkbox"/>	DC:						
Rated Power	12V DC						
Clock frequencies.....	25MHz;26MHz;32,768kHz;49,58MHz;						
Other parameters	See Technical description						
Software version	20512H.001_047_009						
Hardware version	D3						

Dimensions in cm (W x H x D)	160x18x112 mm		
Mounting position	<input type="checkbox"/>	Table top equipment	
	<input type="checkbox"/>	Wall/Ceiling mounted equipment	
	<input type="checkbox"/>	Floor standing equipment	
	<input type="checkbox"/>	Hand-held equipment	
	<input checked="" type="checkbox"/>	Other: automotive telematics control unit	
Modules/parts	Module/parts of test item	Type	Manufacturer
Accessories (not part of the test item)	Description	Type	Manufacturer
	Cable Harness	-	
	2G/3G4G/5G Antenna	-	Hirschmann/ Molex
	E-CALL button/LED	-	
	SOS Loudspeaker	-	
	Wake-up unit Box	-	
Documents as provided by the applicant	Description	File name	Issue date
	Technical Description		

⁽³⁾ Only for Medical Equipment

Identification of the client

HARMAN BECKER AUTOMOTIVE SYSTEMS GMBH
 BECKER-GOERING-STR. 16, 76307 KARLSBAD, GERMANY

Testing period and place

Test Location	DEKRA Testing and Certification S.A.U.
Date (start)	2020-10-28
Date (finish)	2020-11-06

Document history

Report number	Date	Description
62486RRF.002	2021-02-02	First release.

Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %

In the semianechoic chamber, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %

Remarks and comments

The tests have been performed by the technical personnel: José Manuel Jiménez, Alfonso Gutiérrez, Pablo Redondo, Nicolás Salguero, Cristina Calle, Miguel Manuel López and Verónica García.

Used instrumentation:

Radiated Measurements:

	Last Calibration	Due Calibration
1. Semianechoic Absorber Lined Chamber ETS LINDGREN FACT 3 200 STP	N.A.	N.A.
2. Shielded Room ETS LINDGREN S101	N.A.	N.A.
3. Multi-device Controller EMCO 2090	N.A.	N.A.
4. Antenna Mast ETS LINDGREN 2175 MiniMast	N.A.	N.A.
5. Field Probe Positioner MATURO FPP 2.3-M	N.A.	N.A.
6. Ethernet Temperature and Humidity Logger HW GROUP HWg-STE	2020/04	2021/04
7. Horn Antenna 1-18 GHz SCHWARZBECK MESS-ELEKTRONIK BBHA 9120 D	2018/01	2021/01
8. Biconical/Log Antenna 30MHz - 6GHz ETS LINDGREN 3142E	2020/04	2023/04
9. RF Preamplifier G>30dB, 1-18 GHz BONN ELEKTRONIK BLMA 0118-3A	2020/10	2021/10
10. Signal and Spectrum Analyzer 10 Hz - 40 GHz ROHDE AND SCHWARZ FSV40	2019/10	2021/10
11. EMI Test Receiver 7 GHz ROHDE AND SCHWARZ ESR7	2018/10	2020/10
12. Wideband Radio Communication Tester ROHDE AND SCHWARZ CMW500	2020/07	2021/07
13. Horn Antenna 1-18 GHz, SCHWARZBECK BBHA 9120 D	2018/01	2021/01
14. High Pass Filter 1000 MHz, WAINWRIGHT WHKS 1000-10SS	2020/06	2021/06
15. High Pass Filter 3 - 18 GHz TEMSTRON / TEMWELL ST-3GA2833-HS	2020/05	2021/05
16. DC Power Supply 30V/5A KEYSIGHT TECHNOLOGIES U8002A	N.A.	N.A.
17. Digital Multimeter, FLUKE 175	2020/11	2021/11
18. Hybrid Bilog Antenna 30MHz-6GHz SUNOL SCIENCES CORPORATION JB6	2018/10	2021/10
19. High Pass Filter 1.1 - 8 GHz, WAINWRIGHT INSTRUMENTS WHK10-990-1100-8000-40SS	2019/06	2021/06
20. Horn Antenna 1-18 GHz SCHWARZBECK MESS-ELEKTRONIK BBHA 9120 D	2019/11	2022/11
21. RF Preamplifier, 40 dB ,1-18 GHz BONN ELEKTRONIK BLMA 0118-1M	2020/05	2021/05
22. Spectrum Analyzer ROHDE AND SCHWARZ FSW50	2020/07	2022/07
23. EMI Test Receiver 7 GHz ROHDE AND SCHWARZ ESR7	2019/10	2021/10
24. Wideband Radio Communication Tester ROHDE AND SCHWARZ CMW500	2020/04	2021/04
25. Wideband Radio Communication Tester ROHDE AND SCHWARZ CMW500	2020/09	2021/09
26. High Pass Filter 1.1 - 8 GHz, WAINWRIGHT INSTRUMENTS WHK10-990-1100-8000-40SS	2019/11	2020/11

Testing verdicts

Not applicable:	N/A
Pass:	P
Fail:	F
Not measured:	N/M

Summary

FCC PART 22 / RSS-132 PARAGRAPH		
Requirement – Test case	Verdict	Remark
FCC 22.913 / RSS-132 5.4: RF output power	N/M	(1)
FCC 2.1047 / RSS-132 5.2: Modulation characteristics	N/M	(1)
FCC 22.355 / RSS-132 5.3: Frequency stability	N/M	(1)
FCC 2.1049: Occupied Bandwidth	N/M	(1)
FCC 22.917 / RSS-132 5.5: Spurious emissions at antenna terminals	N/M	(1)
FCC 22.917 / RSS-132 5.5: Radiated emissions	P	(2)
<u>Supplementary information and remarks:</u>		
<p>(1) Test not requested. Radiated emissions test only requested.</p> <p>(2) The 62486RRF.001 contains the results of the pre-testing to determine the worst case of the setting of the antennas:</p> <ul style="list-style-type: none"> · Conf #1: MIMO1 Port -> Int BuA Antenna / MIMO2 Port -> MIMO2 Antenna / Antennenbox for NAD#2. · Conf #2: MIMO1 Port -> Int BuA Antenna / MIMO2 Port -> MIMO2 Antenna / FSA antenna for NAD#2. · Conf #3: MIMO1 Port -> MIMO1 Antenna / MIMO2 Port -> MIMO2 Antenna / Antennenbox for NAD#2. · Conf #4: MIMO1 Port -> MIMO2 Antenna / MIMO2 Port -> MIMO2 Antenna / FSA antenna for NAD#2. 		

FCC PART 90 PARAGRAPH		
Requirement – Test case	Verdict	Remark
FCC 90.635 (b): RF output power	N/M	(1)
FCC 2.1047: Modulation characteristics	N/M	(1)
FCC 90.213 Frequency stability	N/M	(1)
FCC 2.1049: Occupied Bandwidth	N/M	(1)
FCC 90.691 Spurious emissions at antenna terminals (Emission mask requirements for EA-based systems)	N/M	(1)
FCC 90.691: Radiated emissions	P	(2)
<p><u>Supplementary information and remarks:</u></p> <p>(1) Test not requested. Radiated emissions test only requested.</p> <p>(2) The 62486RRF.001 contains the results of the pre-testing to determine the worst case of the setting of the antennas:</p> <ul style="list-style-type: none"> · Conf #1: MIMO1 Port -> Int BuA Antenna / MIMO2 Port -> MIMO2 Antenna / Antennenbox for NAD#2. · Conf #2: MIMO1 Port -> Int BuA Antenna / MIMO2 Port -> MIMO2 Antenna / FSA antenna for NAD#2. · Conf #3: MIMO1 Port -> MIMO1 Antenna / MIMO2 Port -> MIMO2 Antenna / Antennenbox for NAD#2. · Conf #4: MIMO1 Port -> MIMO2 Antenna / MIMO2 Port -> MIMO2 Antenna / FSA antenna for NAD#2. 		

Appendix A: Test results for FCC Part 22 & 90 / RSS-132

INDEX

TEST CONDITIONS	13
Radiated emissions	15

TEST CONDITIONS

POWER SUPPLY (V):

Vnominal: 12 Vdc
 Type of Power Supply: External DC (vehicle battery).

The module with the highest antenna gain has been tested using the worst case obtained for conducted output power. And the other module has been tested using an adjacent channel with a setting that would allow communication in the same band to both modules simultaneously.

TEST FREQUENCIES:

2G Band 850 MHz. GPRS and EDGE modulations. MIMO 2x2 (configuration 3):

Module NAD1		Module NAD2	
Low Channel (128)	824.2 MHz	Adjacent channel to Low Channel (130)	824.6 MHz
Middle Channel (190)	836.6 MHz	Adjacent channel to Middle Channel (192)	837 MHz
High Channel (251)	848.8 MHz	Adjacent channel to High Channel (249)	848.4 MHz

3G Band V. WCDMA and HSUPA modulations. MIMO 2x2 (configuration 3):

Module NAD1		Module NAD2	
Low Channel (4132)	826.4 MHz	Adjacent channel to Low Channel (4157)	831.4 MHz
Middle Channel (4182)	836.4 MHz	Adjacent channel to Middle Channel (4207)	841.4 MHz
High Channel (4233)	846.6 MHz	Adjacent channel to High Channel (4208)	841.6 MHz

LTE Band 5 (824-849 MHz). QPSK and 16QAM modulations. MIMO 2x2 (configuration 3):

	Channel (Frequency)			
	BW = 1.4 MHz	BW = 3 MHz	BW=5 MHz	BW=10 MHz
Low	20407 (824.70 MHz)	20415 (825.50 MHz)	20425 (826.50 MHz)	20450 (829.00 MHz)
Middle	20525 (836.50 MHz)	20525 (836.50 MHz)	20525 (836.50 MHz)	20525 (836.50 MHz)
High	20643 (848.30 MHz)	20635 (847.50 MHz)	20625 (846.50 MHz)	20600 (844.00 MHz)

Module NAD1		Module NAD2	
Low Channel (20425)	826.5 MHz	Adjacent channel to Low Channel (20475)	831.5 MHz
Middle Channel (20525)	836.5 MHz	Adjacent channel to Middle Channel (20575)	841.5 MHz
High Channel (20625)	846.5 MHz	Adjacent channel to High Channel (20575)	841.5 MHz

LTE Band 26 (sub-band 824-849 MHz). QPSK and 16QAM modulations. MIMO 2x2 (configuration 3):

	Channel (Frequency)				
	BW = 1.4 MHz	BW = 3 MHz	BW = 5 MHz	BW = 10 MHz	BW = 15 MHz
Low	26797 (824.70 MHz)	26805 (825.50 MHz)	26815 (826.50 MHz)	26840 (829.00 MHz)	26865 (831.50 MHz)
Middle	26915 (836.50 MHz)	26915 (836.50 MHz)	26915 (836.50 MHz)	26915 (836.50 MHz)	26915 (836.50 MHz)
High	27033 (848.30 MHz)	27025 (847.50 MHz)	27015 (846.50 MHz)	26990 (844.00 MHz)	26965 (841.50 MHz)

NOTE: LTE Band 26 sub-band 824-849 MHz is completely included in LTE Band 5, so the channels of Band 5 were tested to give conformity to the assigned block.

LTE Band 26 (sub-band 814-824 MHz). QPSK and 16QAM modulations. MIMO 2x2 (configuration 3):

	Channel (Frequency)				
	BW = 1.4 MHz	BW = 3 MHz	BW = 5 MHz	BW = 10 MHz	BW = 15 MHz
Low	26697 (814.70 MHz)	26705 (815.5 MHz)	26715 (816.5 MHz)	N/A	26765 (821.5 MHz)
Middle	26740 (819 MHz)	26740 (819 MHz)	26740 (819 MHz)	26740 (819 MHz)	N/A
High	26783 (823.30 MHz)	26775 (822.50 MHz)	26765 (821.50 MHz)	N/A	N/A

Module NAD1		Module NAD2	
Low Channel (26705)	815.5 MHz	Adjacent channel to Low Channel (26735)	818.5 MHz
Middle Channel (26740)	819 MHz	Adjacent channel to Middle Channel (26770)	822 MHz
High Channel (26775)	822.5 MHz	Adjacent channel to High Channel (26745)	819.5 MHz

Radiated emissions

SPECIFICATION:

FCC §22.917:

RSS-132. Clause 5.5:

The power of emissions shall be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. P in watts.

FCC §2.1051, §90.691:

Emission mask requirements for EA-based systems:

For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

METHOD:

The measurement was performed with the EUT inside an anechoic chamber. The spectrum was scanned from 30 MHz to at least the 10th harmonic of the High frequency generated within the equipment.

The EUT was placed on a 1 meter high non-conductive stand at a 3 meter distance from the measuring antenna.

Detected emissions were maximized at each frequency by rotating the EUT and adjusting the measuring antenna height and polarization. The maximum field strength (dB μ V/m) is measured and recorded.

The maximum field strength (dB μ V/m) of each detected emission at less than 20 dB respect to the limit is converted to an equivalent EIRP level (dBm) according to ANSI C63.26 with the formula:

$$\text{EIRP (dBm)} = E \text{ (dB}\mu\text{V/m)} + 20 \log(D) - 104.8; \text{ where } D \text{ is the measurement distance (in the far field region) in m.}$$
$$D = 3 \text{ m}$$

Measurement Limit:

According to specification. the power of emissions shall be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. P in Watts.


At P_o transmitting power. the specified minimum attenuation becomes $43+10\log (P_o)$. and the level in dBm relative P_o becomes:

$$P_o \text{ (dBm)} - [43 + 10 \log (P_o \text{ in mWatts}) - 30] = - 13 \text{ dBm}$$


A resolution bandwidth / video bandwidth of 100 kHz / 300 kHz or higher were used for frequencies below 1 GHz and 1 MHz / 3 MHz for frequencies above 1 GHz.

TEST SETUP:

Radiated measurements below 1 GHz:



Radiated measurements above 1 GHz up to 10 GHz:



RESULTS:

2G Band 850 MHz:

GPRS and EDGE modulations: A preliminary scan determined the GPRS modulation as the worst case. The following results are the ones of the worst case.

- LOW CHANNEL:

Frequency range 30 MHz - 1 GHz

No spurious frequencies at less than 20 dB below the limit.

Frequency range 1 - 10 GHz

No spurious frequencies at less than 20 dB below the limit.

- MIDDLE CHANNEL:

Frequency range 30 MHz - 1 GHz

No spurious frequencies at less than 20 dB below the limit.

Frequency range 1 - 10 GHz

No spurious frequencies at less than 20 dB below the limit.

- HIGH CHANNEL:

Frequency range 30 MHz - 1 GHz

Spurious frequencies at less than 20 dB below the limit:

Spurious frequency (MHz)	E.I.R.P (dBm)	Polarization	Detector	Measurement Uncertainty (dB)
812.289	-32.88	V	Peak	<± 5.08

Frequency range 1 - 10 GHz

Spurious frequencies at less than 20 dB below the limit:


Spurious frequency (GHz)	E.I.R.P (dBm)	Polarization	Detector	Measurement Uncertainty (dB)
2.5453	-27.04	H	Peak	<± 5.13

Measurement Uncertainty (dB): <± 5.08 for $f \geq 30$ MHz up to 1 GHz
<± 5.13 for $f \geq 1$ GHz up to 8.5 GHz

Verdict: PASS


FREQUENCY RANGE 30 MHz - 1 GHz (worst case):

- Low Channel:




The peak above the limit is the carrier frequency.

- Middle Channel:



The peak above the limit is the carrier frequency.



- High Channel:





The peak above the limit is the carrier frequency.

FREQUENCY RANGE 1 - 10 GHz (worst case):



- Low Channel:



- Middle Channel:



- High Channel:



3G Band V:

WCDMA and HSUPA modulations: A preliminary scan determined the WCDMA modulation as the worst case. The following results are the ones of the worst case.

- LOW CHANNEL:

Frequency range 30 MHz - 1 GHz:

No spurious frequencies at less than 20 dB below the limit.

Frequency range 1 – 8.5 GHz:

Spurious frequencies at less than 20 dB below the limit:

Spurious frequency (GHz)	E.I.R.P (dBm)	Polarization	Detector	Measurement Uncertainty (dB)
1.00013	-23.44	V	Peak	<± 5.13

- MIDDLE CHANNEL:

Frequency range 30 MHz - 1 GHz:

No spurious frequencies at less than 20 dB below the limit.

Frequency range 1 – 8.5 GHz:

Spurious frequencies at less than 20 dB below the limit:

Spurious frequency (GHz)	E.I.R.P (dBm)	Polarization	Detector	Measurement Uncertainty (dB)
1.0063	-23.26	H	Peak	<± 5.13

- HIGH CHANNEL:

Frequency range 30 MHz - 1 GHz:

No spurious frequencies at less than 20 dB below the limit.

Frequency range 1 – 8.5 GHz:

Spurious frequencies at less than 20 dB below the limit:


Spurious frequency (GHz)	E.I.R.P (dBm)	Polarization	Detector	Measurement Uncertainty (dB)
1.00163	-22.83	H	Peak	<± 5.13

Measurement Uncertainty (dB): <± 5.08 for f ≥ 30 MHz up to 1 GHz
 <± 5.13 for f ≥ 1 GHz up to 10 GHz

Verdict: PASS


FREQUENCY RANGE 30 MHz - 1 GHz (worst case):

- Low Channel:




The peak above the limit is the carrier frequency. The peaks at 871.4MHz and 876.4MHz correspond to the downlink signals.

- Middle Channel:



The peak above the limit is the carrier frequency. The peak at 886.4MHz corresponds to the downlink signal.


- High Channel:




The peak above the limit is the carrier frequency. The peak at 886.6MHz corresponds to the downlink signal.

FREQUENCY RANGE 1 - 8.5 GHz (worst case):


- Low Channel:



- Middle Channel:



- High Channel:



824-849 MHz (LTE Band 5 and this sub-band of the LTE Band 26):

QPSK and QAM modulations: A preliminary scan determined the QPSK modulation, Nominal Bandwidth 5 MHz, Resource Block Size 1, Resource Block Offset 0 as the worst case. The following results are the ones of the worst case.

- LOW CHANNEL:

Frequency range 30 MHz - 1 GHz:

Spurious frequencies at less than 20 dB below the limit:

Spurious frequency (MHz)	E.I.R.P (dBm)	Polarization	Detector	Measurement Uncertainty (dB)
820.2105	-22.29	V	Peak	<± 4.99

Frequency range 1 - 8.5 GHz:

No spurious frequencies at less than 20 dB below the limit.

- MIDDLE CHANNEL:

Frequency range 30 MHz - 1 GHz:

No spurious frequencies at less than 20 dB below the limit.

Frequency range 1 - 8.5 GHz:

No spurious frequencies at less than 20 dB below the limit.

- HIGH CHANNEL:

Frequency range 30 MHz - 1 GHz:

Spurious frequencies at less than 20 dB below the limit:

Spurious frequency (MHz)	E.I.R.P (dBm)	Polarization	Detector	Measurement Uncertainty (dB)
851.3475	-30.36	V	Peak	<± 4.99

Frequency range 1 - 8.5 GHz:


No spurious frequencies at less than 20 dB below the limit.

Measurement Uncertainty (dB): <± 4.99 for f ≥ 30 MHz up to 1 GHz
<± 4.98 for f ≥ 1 GHz up to 10 GHz

Verdict: PASS


FREQUENCY RANGE 30 MHz - 1 GHz (worst case):

- Low Channel:




The peak above the limit is the carrier frequency. The peaks at 871MHz and 876MHz correspond to the downlink signals.

- Middle Channel:



The peak above the limit is the carrier frequency. The peaks at 881MHz and 886MHz correspond to the downlink signals.


- High Channel:




The peak above the limit is the carrier frequency. The peaks at 891MHz and 886MHz correspond to the downlink signals.

FREQUENCY RANGE 1 - 8.5 GHz (worst case):


- Low Channel:



- Middle Channel:



- High Channel:



814-824 MHz (Sub-band of the LTE Band 26):

QPSK and QAM modulations: A preliminary scan determined the QPSK modulation, Nominal Bandwidth 3 MHz, Resource Block Size 1, Resource Block Offset 0 as the worst case to maintain the two modules with established communication.

The following results are the ones of the worst case.

- LOW CHANNEL:

Frequency range 30 MHz - 1 GHz:

Spurious frequencies at less than 20 dB below the limit:

Spurious frequency (MHz)	E.I.R.P (dBm)	Polarization	Detector	Measurement Uncertainty (dB)
811.707	-27.99	V	Peak	<± 4.99

Frequency range 1 - 8.5 GHz:

No spurious frequencies at less than 20 dB below the limit.

- MIDDLE CHANNEL:

Frequency range 30 MHz - 1 GHz:

No spurious frequencies at less than 20 dB below the limit.

Frequency range 1 - 8.5 GHz:

No spurious frequencies at less than 20 dB below the limit.

- HIGH CHANNEL:

Frequency range 30 MHz - 1 GHz:

No spurious frequencies at less than 20 dB below the limit.

Frequency range 1 - 8.5 GHz:


No spurious frequencies at less than 20 dB below the limit.

Measurement Uncertainty (dB): <± 4.99 for f ≥ 30 MHz up to 1 GHz
<± 4.98 for f ≥ 1 GHz up to 10 GHz

Verdict: PASS


FREQUENCY RANGE 30 MHz - 1 GHz (worst case):

- Low Channel:




The peak above the limit is the carrier frequency. The peaks at 860.5MHz and 863.5MHz correspond to the downlink signals.

- Middle Channel:



The peak above the limit is the carrier frequency. The peaks at 864MHz and 867MHz correspond to the downlink signals.


- High Channel:




The peak above the limit is the carrier frequency. The peaks at 864.5MHz and 867.5MHz correspond to the downlink signals.

FREQUENCY RANGE 1 - 8.5 GHz (worst case):

- Low Channel:



- Middle Channel:



- High Channel:

