


Test report No:
 NIE: 62486RRF.007

Partial Test Report

Reference Standard:
 USA FCC Part 27
 CANADA RSS-139, RSS-199

(*) Identification of item tested	Telematic control unit with wireless technologies, used in automotive industry
(*) Trademark	BMW
(*) Model and /or type reference	WAVE-11-HIGH-R1 Type: B392
Other identification of the product	HW version: D3 SW version: 20512H.001_047_009 FCC ID: T8GWAVE11HIGHR1 IC: 6434A-WAVE11HIGHR1
(*) Features	GSM, UMTS, LTE, 5G, GNSS
Applicant	HARMAN BECKER AUTOMOTIVE SYSTEMS GMBH BECKER-GOERING-STR. 16; 76307 KARLSBAD GERMANY
Test method requested, standard	USA FCC Part 27 (10-1-19 Edition). CANADA RSS-139 Issue 3, Jul. 2015. CANADA RSS-199 Issue 3, Dec. 2016. - Radiated emissions. ANSI C63.26-2015. KDB 971168 D01 Power Meas License Digital Systems v03r01, April. 2018.
Approved by (name / position & signature)	Rafael López EMC Consumer & RF Lab. Manager  2021.10.29 12:44:44 +02'00'
Date of issue	2021-10-29
Report template No	FDT08_23 (*) "Data provided by the client"

Index

Competences and guarantees	3
General conditions	3
Uncertainty.....	3
Data provided by the client	3
Usage of samples	4
Test sample description.....	4
Identification of the client	7
Testing period and place	7
Document history.....	7
Environmental conditions	8
Remarks and comments.....	9
Testing verdicts.....	9
Summary	10
Appendix A: Test results for FCC Part 27 / RSS-139, RSS-199	11

Competences and guarantees

DEKRA Testing and Certification S.A.U. is a testing laboratory accredited by the National Accreditation Body (ENAC -Entidad Nacional de Acreditación), to perform the tests indicated in the Certificate No. 51/LE 147.

DEKRA Testing and Certification is a FCC-recognized accredited testing laboratory with appropriate scope of accreditation that include testing performed in this test report.

DEKRA Testing and Certification is an ISED-recognized accredited testing laboratory with appropriate scope of accreditation that include testing performed in this test report.

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification S.A.U. has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification S.A.U. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification S.A.U. at the time of performance of the test.

DEKRA Testing and Certification S.A.U. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document. **IMPORTANT:** No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification S.A.U.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification S.A.U.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification S.A.U. and the Accreditation Bodies.

Uncertainty

Uncertainty (factor $k=2$) was calculated according to the DEKRA Testing and Certification S.A.U. internal document PODT000.

Data provided by the client

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item tested", "Trademark", "Model and/or type reference tested").
2. The sample of the model WAVE-11-HIGH-R1, type B392, is a Telematics control unit with wireless technologies, used in automotive, equipped with 2 modems, OEM and customer. The project name WAVE has the meaning "Wireless Access in Vehicular Environment" and thus describes the key features of this device as Communication and Data Interface. This unit was designed for automotive usage and contains the following features: GSM, UMTS, LTE, 5G, and GNSS.

DEKRA Testing and Certification S.A.U. declines any responsibility with respect to the information provided by the client and that may affect the validity of results.

Usage of samples

Samples undergoing test have been selected by: The client.

- Sample S/01 is composed of the following elements:

Control N°	Description	Model	Serial N°	Date of reception
62486E/105	Telematic Control Unit	WAVE-11-HIGH-R1 (type B392)	B392120L4900533	2020/09/28
62486E/012	Antenna DA WAVE HIGH 5G US	DA05DI20	--	2020/09/22
62486E/036	Antenna Box	AB01-I20-01	--	2020/09/22
62486E/037	Antenna Box	AB01-I20-01	--	2020/09/22
62486E/038	Antenna Box	AB01-I20-01	--	2020/09/22
62486E/039	Antenna Box	AB01-I20-01	--	2020/09/22
62486E/060	Harness 20 pol	--	--	2020/09/22

Auxiliary elements used with the Sample S/01:

Control N°	Description	Model	Serial N°	Date of reception
62486E/109	Battery Li-ion	11FR1580-2	--	2020/09/28
62486E/042	Antenna ground planes for roof	--	--	2020/09/22
62486E/045	RF Cable for 4-Fakra	--	--	2020/09/22
62486E/056	OABR Cable	--	--	2020/09/22
62486E/064	OABR 1000 BaseT Converter	--	--	2020/09/22
62486E/067	I-Box OABR Adapter	--	--	2020/09/22
62486E/071	Ethernet Cable	--	--	2020/09/22
62486E/090	Speaker	FR7	--	2020/09/28
62486E/097	SOS Pulser (E-Call)	9385	11224	2020/09/28

Sample S/01 has undergone the following test(s): The Radiated tests for the sub-range 1-18 GHz of the LTE Band CA_7C, the sub-ranges 30 MHz - 1 GHz and 1-3 GHz of the LTE Band CA_41C, the LTE Band CA_66B indicated in the Appendix A.

- Sample S/02 is composed of the following elements:

Control N°	Description	Model	Serial N°	Date of reception
62486E/304	Telematic Control Unit	WAVE-11-HIGH-R1 (type B392)	B392I+0L4900520	2020/11/10
62486E/012	Antenna DA WAVE HIGH 5G US	DA05DI20	--	2020/09/22
62486E/036	Antenna Box	AB01-I20-01	--	2020/09/22
62486E/037	Antenna Box	AB01-I20-01	--	2020/09/22
62486E/038	Antenna Box	AB01-I20-01	--	2020/09/22
62486E/039	Antenna Box	AB01-I20-01	--	2020/09/22
62486E/060	Harness 20 pol	--	--	2020/09/22

Auxiliary elements used with the Sample S/02:

Control N°	Description	Model	Serial N°	Date of reception
62486E/109	Battery Li-ion	11FR1580-2	--	2020/09/28
62486E/042	Antenna ground planes for roof	--	--	2020/09/22
62486E/045	RF Cable for 4-Fakra	--	--	2020/09/22
62486E/056	OABR Cable	--	--	2020/09/22
62486E/064	OABR 1000 BaseT Converter	--	--	2020/09/22
62486E/067	I-Box OABR Adapter	--	--	2020/09/22
62486E/071	Ethernet Cable	--	--	2020/09/22
62486E/090	Speaker	FR7	--	2020/09/28
62486E/097	SOS Pulser (E-Call)	9385	11224	2020/09/28

Sample S/02 has undergone the following test(s): The Radiated tests for the sub-ranges 30 MHz - 1 GHz and 18-27 GHz of the LTE Band CA_7C, the sub-range 3-27 GHz of the LTE Band CA_41C, the LTE Band CA_66C indicated in the Appendix A.

Test sample description

Ports..... :	Port name and description	Cable					
		Specified max length [m]	Attached during test	Shielded	Coupled to patient ⁽³⁾		
	RF connector –code D violet trunk/roof)	Port not used for SOP2021 (it has V2X interfaces and gateway for SDARS signal towards another ECU)	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>		
	RF connector – code C blue (trunk/roof)	>5m	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>		
	NanoMQS 20pol	>5m	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
	NanoMQS 10pol	>8m	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
	HDBT MATenet 2-Pol (Roof/Trunk)	>5m	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
	Antenna Connector grey (Roof)	<0.5m	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>		
Supplementary information to the ports..... :							
Rated power supply	Voltage and Frequency		Reference poles				
			L1	L2	L3	N	PE
	<input type="checkbox"/>	AC:	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	AC:	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
	<input checked="" type="checkbox"/>	DC: 12V car battery / attenuator (4,5 V ≤ UB ≤ 18 V; UB typical: 12 V)					
<input type="checkbox"/>	DC:						
Rated Power	12V DC						
Clock frequencies.....	25MHz;26MHz;32,768kHz;49,58MHz;						
Other parameters	See Technical description						
Software version	D3						
Hardware version	20512H.001_047_009						

Dimensions in cm (W x H x D)	160x18x112 mm		
Mounting position	<input type="checkbox"/>	Table top equipment	
	<input type="checkbox"/>	Wall/Ceiling mounted equipment	
	<input type="checkbox"/>	Floor standing equipment	
	<input type="checkbox"/>	Hand-held equipment	
	<input checked="" type="checkbox"/>	Other: automotive telematics control unit	
Modules/parts	Module/parts of test item	Type	Manufacturer
Accessories (not part of the test item)	Description	Type	Manufacturer
	Cable Harness	-	
	2G/3G4G/5G Antenna	-	Hirschmann/ Molex
	E-CALL button/LED	-	
	SOS Loudspeaker	-	
	Wake-up unit Box	-	
Documents as provided by the applicant	Description	File name	Issue date
	Technical Description		

⁽³⁾ Only for Medical Equipment

Identification of the client

HARMAN BECKER AUTOMOTIVE SYSTEMS GMBH
 BECKER-GOERING-STR. 16, 76307 KARLSBAD, GERMANY

Testing period and place

Test Location	DEKRA Testing and Certification S.A.U.
Date (start)	2020-11-11
Date (finish)	2021-01-11

Document history

Report number	Date	Description
62486RRF.007	2021-02-02	First release.
62486RRF.007A1	2021-10-29	First modification due to include LTE band 38 (completely included in band 41). This modification test report cancels and replaces the test report 62486RRF.007

Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar

In the semianechoic chamber, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar

Remarks and comments

The tests have been performed by the technical personnel: Nicolás Salguero, Miguel Manuel López, Pablo Redondo, Cristina Calle, Alfonso Gutiérrez.

Used instrumentation:

Radiated Measurements

	Last Calibration	Due Calibration
1. Semianechoic Absorber Lined Chamber ETS LINDGREN FACT 3 200 STP	N.A.	N.A.
2. Shielded Room ETS LINDGREN S101	N.A.	N.A.
3. Multi-device Controller EMCO 2090	N.A.	N.A.
4. Antenna Mast ETS LINDGREN 2175 MiniMast	N.A.	N.A.
5. Field Probe Positioner MATURO FPP 2.3-M	N.A.	N.A.
6. Biconical/Log Antenna 30 MHz - 6 GHz ETS LINDGREN 3142E	2020/04	2023/04
7. Horn Antenna 1-18 GHz SCHWARZBECK MESS-ELEKTRONIK BBHA 9120 D	2019/11	2022/11
8. Horn Antenna 18 - 40 GHz SCHWARZBECK MESS-ELEKTRONIK BBHA 9170	2020/05	2023/05
9. Preamplifier G>40dB 10MHz-6GHz, BONN ELEKTRONIK, BLNA 0160-01N	2020/02	2021/02
10. RF Preamplifier, 40 dB ,1-18 GHz BONN ELEKTRONIK BLMA 0118-1M	2020/05	2021/05
11. Low Noise Amplifier G>30dB, 18 - 40 GHz BONN ELEKTRONIK BLMA 1840-1M	2019/02	2021/02
12. EMI Test Receiver 7 GHz ROHDE AND SCHWARZ ESR7	2019/10	2021/10
13. Spectrum Analyzer ROHDE AND SCHWARZ FSW50	2020/07	2022/07
14. Signal and Spectrum Analyzer 10 Hz - 40 GHz ROHDE AND SCHWARZ FSV40	2019/10	2021/10
15. Wideband Radio Communication Tester ROHDE AND SCHWARZ CMW500	2020/07	2021/07
16. Wideband Radio Communication Tester ROHDE AND SCHWARZ CMW500	2020/09	2021/09
17. Low Pass Filter DC - 1 GHz WAINWRIGHT INSTRUMENTS WLK1000-6SS	2020/07	2022/07
18. High Pass Filter 3 - 18 GHz TEMSTRON / TEMWELL ST-3GA2833-HS	2020/05	2021/05
19. Attenuator 3dB, 2W, DC-18GHz, TECHNIWAVE TWTS2G	2020/01	2021/01
20. DC Power Supply, 30V/5A KEYSIGHT TECHNOLOGIES U8002A	N.A.	N.A.
21. Digital Multimeter FLUKE 175	2020/11	2021/11

Testing verdicts

Not applicable:	N/A
Pass:	P
Fail:	F
Not measured:	N/M

Summary

FCC PART 27 / RSS-139, RSS-199 PARAGRAPH		
Requirement – Test case	Verdict	Remark
FCC 27.50 / RSS-139 6.5., RSS-199 4.4.: RF output power	N/M	(1)
FCC 2.1047 / RSS-139 6.2., RSS-199 4.1.: Modulation characteristics	N/M	(1)
FCC 27.54 / RSS-139 6.4., RSS-199 4.3.: Frequency stability	N/M	(1)
FCC 2.1049 / RSS-139 6.4., RSS-199 4.3.: Occupied Bandwidth	N/M	(1)
FCC 27.53 / RSS-139 6.6., RSS-199 4.5.: Spurious emissions at antenna terminals	N/M	(1)
FCC 27.53 / RSS-139 6.6., RSS-199 4.5.: Radiated emissions	P	(2)
<u>Supplementary information and remarks:</u>		
<p>(1) Test not requested. Radiated emissions test only requested.</p> <p>(2) The 62486RRF.001 contains the results of the pre-testing to determine the worst case of the setting of the antennas.</p> <ul style="list-style-type: none"> · Conf #1: MIMO1 Port -> Int BuA Antenna / MIMO2 Port -> MIMO2 Antenna / Antennenbox for NAD#2. · Conf #2: MIMO1 Port -> Int BuA Antenna / MIMO2 Port -> MIMO2 Antenna / FSA antenna for NAD#2. · Conf #3: MIMO1 Port -> MIMO1 Antenna / MIMO2 Port -> MIMO2 Antenna / Antennenbox for NAD#2. · Conf #4: MIMO1 Port -> MIMO2 Antenna / MIMO2 Port -> MIMO2 Antenna / FSA antenna for NAD#2. 		

Appendix A: Test results for FCC Part 27 / RSS-139, RSS-199

INDEX

TEST CONDITIONS	13
Radiated emissions	19

TEST CONDITIONS

POWER SUPPLY (V):

Vnominal: 12 Vdc
 Type of Power Supply: External DC (vehicle battery).

The module with the highest antenna gain has been tested using the worst case obtained for conducted output power. And the other module has been tested using an adjacent channel with a setting that would allow communication in the same band to both modules simultaneously.

LTE Band CA_7C + LTE Band 7. QPSK and QAM modulations. CARRIER AGGREGATION & MIMO 2x2 (configuration 3):

LTE Band 7:

	Channel (Frequency)			
	BW = 5 MHz	BW = 10 MHz	BW = 15 MHz	BW = 20 MHz
Low	20775 (2502.5 MHz)	20800 (2505.0 MHz)	20825 (2507.5 MHz)	20850 (2510.0 MHz)
Middle	21100 (2535.0 MHz)	21100 (2535.0 MHz)	21100 (2535.0 MHz)	21100 (2535.0 MHz)
High	21425 (2567.5 MHz)	21400 (2565.0 MHz)	21375 (2562.5 MHz)	21350 (2560.0 MHz)

LTE Band CA_7C:

Range	CC-Combo / N _{RB_agg} [RB]	CC1 Note1					CC2 Note1				
		BW [RB]	N _{UL}	f _{UL} [MHz]	N _{DL}	f _{DL} [MHz]	BW [RB]	N _{UL}	f _{UL} [MHz]	N _{DL}	f _{DL} [MHz]
Low	50+100	50	20805	2505.5	2805	2625.5	100	20949	2519.9	2949	2639.9
		100	20850	2510	2850	2630	50	20994	2524.4	2994	2644.4
	75+50	75	20825	2507.5	2825	2627.5	50	20945	2519.5	2945	2639.5
	75+75	75	20825	2507.5	2825	2627.5	75	20975	2522.5	2975	2642.5
	75+100	75	20828	2507.8	2828	2627.8	100	20999	2524.9	2999	2644.9
		100	20850	2510	2850	2630	75	21021	2527.1	3021	2647.1
Mid	50+100	50	21006	2525.6	3006	2645.6	100	21150	2540	3150	2660
		100	21051	2530.1	3051	2650.1	50	21195	2544.5	3195	2664.5
	75+50	75	21051	2530.1	3051	2650.1	50	21171	2542.1	3171	2662.1
	75+75	75	21025	2527.5	3025	2647.5	75	21175	2542.5	3175	2662.5
	75+100	75	21003	2525.3	3003	2645.3	100	21174	2542.4	3174	2662.4
		100	21026	2527.6	3026	2647.6	75	21197	2544.7	3197	2664.7
High	50+100	50	21206	2545.6	3206	2665.6	100	21350	2560	3350	2680
		100	21251	2550.1	3251	2670.1	50	21395	2564.5	3395	2684.5
	75+50	75	21277	2552.7	3277	2672.7	50	21397	2564.7	3397	2684.7
	75+75	75	21225	2547.5	3225	2667.5	75	21375	2562.5	3375	2682.5
	75+100	75	21179	2542.9	3179	2662.9	100	21350	2560	3350	2680
		100	21201	2545.1	3201	2665.1	75	21372	2562.2	3372	2682.2
100+100	100	21152	2540.2	3152	2660.2	100	21350	2560	3350	2680	

Note 1: Carriers in increasing frequency order.

TEST FREQUENCIES:

Module NAD2								Module NAD1		
Carrier Aggregation Intra-band. Test frequencies for CA 7C.								LTE Band 7		
CA 7C: Band 7 with 2 contiguous intra-band CC (PCC+SCC), 1 RB										
Channel	NRB	PCC			SCC1			BW (MHz)	EARFCN	Freq. (MHz)
		BW (MHz)	EARFCN	Freq. (MHz)	BW (MHz)	EARFCN	Freq. (MHz)			
Low	100+100	20	20850	2510	20	21048	2529.8	10	Adjacent channel to SCC1 (21200)	2545
Middle	100+100	20	21001	2525.1	20	21199	2544.9	10	Adjacent channel to SCC1 (21350)	2560
High	100+100	20	21152	2540.2	20	21350	2560	10	Adjacent channel to PCC (20900)	2515

LTE Band CA_41C + LTE Band 41. QPSK and QAM modulations. CARRIER AGGREGATION & MIMO 2x2 (configuration 3):

LTE Band 41:

	Channel (Frequency)			
	BW = 5 MHz	BW = 10 MHz	BW = 15 MHz	BW = 20 MHz
Low	39675 (2498.50 MHz)	39700 (2501.00 MHz)	39725 (2503.50 MHz)	39750 (2506.00 MHz)
Middle	40620 (2593.00 MHz)	40620 (2593.00 MHz)	40620 (2593.00 MHz)	40620 (2593.00 MHz)
High	41565 (2687.50 MHz)	41540 (2685.00 MHz)	41515 (2682.50 MHz)	41490 (2680.00 MHz)

LTE Band CA_41C:

Range	CC-Combo / N _{RB,agg} [RB]	CC1 Note1			CC2 Note1		
		BW [RB]	N _{UL/DL}	f _{UL/DL} [MHz]	BW [RB]	N _{UL/DL}	f _{UL/DL} [MHz]
Low	25+100	25	39683	2499.3	100	39800	2511
		100	39750	2506	25	39867	2517.7
	50+75	50	39703	2501.3	75	39823	2513.3
		75	39725	2503.5	50	39845	2515.5
	50+100	50	39705	2501.5	100	39849	2515.9
		100	39750	2506	50	39894	2520.4
	75+75	75	39725	2503.5	75	39875	2518.5
		75+100	75	39728	2503.8	100	39899
	100+100	100	39750	2506	75	39921	2523.1
		100	39750	2506	100	39948	2525.8
Mid	25+100	25	40528	2583.8	100	40645	2595.5
		100	40595	2590.5	25	40712	2602.2
	50+75	50	40549	2585.9	75	40669	2597.9
		75	40571	2588.1	50	40691	2600.1
	50+100	50	40526	2583.6	100	40670	2598.0
		100	40571	2588.1	50	40715	2602.5
	75+75	75	40545	2585.5	75	40695	2600.5
		75+100	75	40523	2583.3	100	40694
	100+100	100	40546	2585.6	75	40717	2602.7
		100	40521	2583.1	100	40719	2602.9
High	25+100	25	41373	2668.3	100	41490	2680
		100	41440	2675	25	41557	2686.7
	50+75	50	41395	2670.5	75	41515	2682.5
		75	41417	2672.7	50	41537	2684.7
	50+100	50	41346	2665.6	100	41490	2680
		100	41391	2670.1	50	41535	2684.5
	75+75	75	41365	2667.5	75	41515	2682.5
		75+100	75	41319	2662.9	100	41490
	100+100	100	41341	2665.1	75	41512	2682.2
		100	41292	2660.2	100	41490	2680

Note 1: Carriers in increasing frequency order.
 Note 2: This test frequency is applicable only for intra-band contiguous CA which requires channel spacing to be less than nominal channel spacing.

TEST FREQUENCIES:

Module NAD2								Module NAD1		
Carrier Aggregation Intra-band. Test frequencies for CA 41C.								LTE Band 41		
CA 41C: Band 41 with 2 contiguous intra-band CC (PCC+SCC), 1 RBlock.										
Channel	NRB	PCC			SCC1			BW (MHz)	EARFCN	Freq. (MHz)
		BW (MHz)	EARFCN	Freq. (MHz)	BW (MHz)	EARFCN	Freq. (MHz)			
Low	100+25	20	39750	2506	5	39867	2517.7	20	Adjacent channel to SCC1 (39950)	2526
Middle	100+25	20	40595	2590.5	5	40712	2602.2	20	Adjacent channel to PCC (40390)	2570
High	100+25	20	41440	2675	5	41557	2686.7	20	Adjacent channel to PCC (41190)	2650

LTE Band CA_66B + LTE Band 66. QPSK and QAM modulations. CARRIER AGGREGATION & MIMO 2x2 (configuration 3):

LTE Band 66:

	Channel (Frequency)					
	BW = 1.4 MHz	BW = 3 MHz	BW = 5 MHz	BW = 10 MHz	BW = 15 MHz	BW = 20 MHz
Low	131979 (1710.7 MHz)	131987 (1711.5 MHz)	131997 (1712.5 MHz)	132022 (1715.0 MHz)	132047 (1717.5 MHz)	132072 (1720.0 MHz)
Middle	132322 (1745.0 MHz)	132322 (1745.0 MHz)	132322 (1745.0 MHz)	132322 (1745.0 MHz)	132322 (1745.0 MHz)	132322 (1745.0 MHz)
High	132665 (1779.3 MHz)	132657 (1778.5 MHz)	132647 (1777.5 MHz)	132622 (1775.0 MHz)	132597 (1772.5 MHz)	132572 (1770.0 MHz)

LTE Band CA_66B:

Range	CC-Combo / NRB_agg [RB]	CC1 Note1					CC2 Note1				
		BW [RB]	N _{UL}	f _{UL} [MHz]	N _{DL}	f _{DL} [MHz]	BW [RB]	N _{UL}	f _{UL} [MHz]	N _{DL}	f _{DL} [MHz]
Low	25+25	25	131997	1712.5	66461	2112.5	25	132045	1717.3	66509	2117.3
	25+50	25	132000	1712.8	66464	2112.8	50	132072	1720	66536	2120
		50	132022	1715	66486	2115	25	132094	1722.2	66558	2122.2
	25+75	25	132002	1713	66466	2113	75	132095	1722.3	66559	2122.3
		75	132047	1717.5	66511	2117.5	25	132140	1726.8	66604	2126.8
50+50	50	132022	1715	66486	2115	50	132121	1724.9	66585	2124.9	
Mid	25+25	25	132398	1752.6	66862	2152.6	25	132446	1757.4	66910	2157.4
	25+50	25	132375	1750.3	66839	2150.3	50	132447	1757.5	66911	2157.5
		50	132397	1752.5	66861	2152.5	25	132469	1759.7	66933	2159.7
	25+75	25	132353	1748.1	66817	2148.1	75	132446	1757.4	66910	2157.4
		75	132398	1752.6	66862	2152.6	25	132491	1761.9	66955	2161.9
50+50	50	132373	1750.1	66837	2150.1	50	132472	1760	66936	2160	
High ²	25+25	25	132647	1777.5	67111	2177.5	25	NA	NA	67159	2182.3
	25+50	25	132647	1777.5	67111	2177.5	50	NA	NA	67183	2184.7
		50	132622	1775	67086	2175	25	NA	NA	67158	2182.2
	25+75	25	132647	1777.5	67111	2177.5	75	NA	NA	67204	2186.8
		75	132597	1772.5	67061	2172.5	25	NA	NA	67154	2181.8
50+50	50	132622	1775	67086	2175	50	NA	NA	67185	2184.9	
High ³	25+25	25	132599	1772.7	67063	2172.7	25	132647	1777.5	67111	2177.5
	25+50	25	132550	1767.8	67014	2167.8	50	132622	1775	67086	2175
		50	132572	1770	67036	2170	25	132644	1777.2	67108	2177.2
	25+75	25	132504	1763.2	66968	2163.2	75	132597	1772.5	67061	2172.5
		75	132549	1767.7	67013	2167.7	25	132642	1777	67106	2177
50+50	50	132523	1765.1	66987	2165.1	50	132622	1775	67086	2175	

Note 1: Carriers in increasing frequency order.
Note 2: Applicable for intra-band contiguous CA without UL CA.
Note 3: Applicable for intra-band contiguous CA with UL CA.

TEST FREQUENCIES:

Module NAD2								Module NAD1		
Carrier Aggregation Intra-band. Test frequencies for CA_66B.								LTE Band 66		
CA_66B: Band 66 with 2 contiguous intra-band CC (PCC+SCC), 1 Block.										
Channel	NRB	PCC			SCC1			BW (MHz)	EARFCN	Freq. (MHz)
		BW (MHz)	EARFCN	Freq. (MHz)	BW (MHz)	EARFCN	Freq. (MHz)			
Low	25+50	5	132000	1712.80	10	132072	1720	3	Adjacent channel to SCC1 (132122)	1725
Middle	25+50	5	132375	1750.3	10	132447	1757.5	3	Adjacent channel to PCC (132272)	1740
High	25+50	5	132550	1767.8	10	132622	1775	3	Adjacent channel to PCC (132472)	1760

LTE Band CA_66C + LTE Band 66. QPSK and QAM modulations. CARRIER AGGREGATION & MIMO 2x2 (configuration 3):

LTE Band 66:

	Channel (Frequency)					
	BW = 1.4 MHz	BW = 3 MHz	BW = 5 MHz	BW = 10 MHz	BW = 15 MHz	BW = 20 MHz
Low	131979 (1710.7 MHz)	131987 (1711.5 MHz)	131997 (1712.5 MHz)	132022 (1715.0 MHz)	132047 (1717.5 MHz)	132072 (1720.0 MHz)
Middle	132322 (1745.0 MHz)	132322 (1745.0 MHz)	132322 (1745.0 MHz)	132322 (1745.0 MHz)	132322 (1745.0 MHz)	132322 (1745.0 MHz)
High	132665 (1779.3 MHz)	132657 (1778.5 MHz)	132647 (1777.5 MHz)	132622 (1775.0 MHz)	132597 (1772.5 MHz)	132572 (1770.0 MHz)

LTE Band CA_66C:

Range	CC-Combo / NRB ₄₀₀ [RB]	CC1 Note1					CC2 Note1				
		BW [RB]	NUL	f _{UL} [MHz]	N _{DL}	f _{DL} [MHz]	BW [RB]	NUL	f _{UL} [MHz]	N _{DL}	f _{DL} [MHz]
Low	50+75	50	132025	1715.3	66489	2115.3	75	132145	1727.3	66609	2127.3
		75	132047	1717.5	66511	2117.5	50	132167	1729.5	66631	2129.5
	50+100	50	132027	1715.5	66491	2115.5	100	132171	1729.9	66635	2129.9
		100	132072	1720	66536	2120	50	132216	1734.4	66680	2134.4
	75+75	75	132047	1717.5	66511	2117.5	75	132197	1732.5	66681	2132.5
		75	132050	1717.8	66514	2117.8	100	132221	1734.9	66685	2134.9
	75+100	100	132072	1720	66536	2120	75	132243	1737.1	66707	2137.1
		100+25	100	132072	1720	66536	2120	25	132189	1731.7	66653
	100+100	25	132005	1713.3	66489	2113.3	100	132122	1725.0	66586	2125.0
		100	132072	1720	66536	2120	100	132270	1739.8	66734	2139.8
Mid	50+75	50	132351	1747.9	66815	2147.9	75	132471	1759.9	66935	2159.9
		75	132373	1750.1	66837	2150.1	50	132493	1762.1	66957	2162.1
	50+100	50	132328	1745.6	66792	2145.6	100	132472	1760	66936	2160
		100	132373	1750.1	66837	2150.1	50	132517	1764.5	66981	2164.5
	75+75	75	132347	1747.5	66811	2147.5	75	132497	1762.5	66961	2162.5
		75	132325	1745.3	66789	2145.3	100	132496	1762.4	66960	2162.4
	75+100	100	132348	1747.6	66812	2147.6	75	132519	1764.7	66983	2164.7
		100+25	100	132387	1752.5	66861	2152.5	25	132514	1764.2	66978
	100+100	25	132330	1745.8	66794	2145.8	100	132447	1757.5	66911	2157.5
		100	132323	1745.1	66787	2145.1	100	132521	1764.9	66985	2164.9
High ²	50+75	50	132622	1775	67086	2175	75	NA	NA	67206	2187
		75	132597	1772.5	67061	2172.5	50	NA	NA	67181	2184.5
	50+100	50	132622	1775	67086	2175	100	NA	NA	67230	2189.4
		100	132572	1770	67036	2170	50	NA	NA	67180	2184.4
	75+75	75	132597	1772.5	67061	2172.5	75	NA	NA	67211	2187.5
		75+100	75	132597	1772.5	67061	2172.5	100	NA	NA	67232
	100+25	100	132572	1770	67036	2170	75	NA	NA	67207	2187.1
		100	132572	1770	67036	2170	25	NA	NA	67153	2181.7
	100+100	25	132647	1777.5	67111	2177.5	100	NA	NA	67228	2189.2
		100	132572	1770	67036	2170	100	NA	NA	67234	2189.8
High ³	50+75	50	132477	1760.5	66941	2160.5	75	132597	1772.5	67061	2172.5
		75	132499	1762.7	66963	2162.7	50	132619	1774.7	67083	2174.7
	50+100	50	132428	1755.6	66892	2155.6	100	132572	1770	67036	2170
		100	132473	1760.1	66937	2160.1	50	132617	1774.5	67081	2174.5
	75+75	75	132447	1757.5	66911	2157.5	75	132597	1772.5	67061	2172.5
		75+100	75	132401	1752.9	66885	2152.9	100	132572	1770	67036
	100+25	100	132423	1755.1	66887	2155.1	75	132594	1772.2	67058	2172.2
		100	132522	1765	66986	2165	25	132639	1776.7	67103	2176.7
	100+100	25	132455	1758.3	66919	2158.3	100	132572	1770.0	67036	2170.0
		100	132374	1750.2	66838	2150.2	100	132572	1770	67036	2170

Note 1: Carriers in increasing frequency order.
 Note 2: Applicable for intra-band contiguous CA without UL CA.
 Note 3: Applicable for intra-band contiguous CA with UL CA.

TEST FREQUENCIES:

Module NAD2								Module NAD1		
Carrier Aggregation Intra-band. Test frequencies for CA 66C.								LTE Band 66		
CA_66C: Band 66 with 2 contiguous intra-band CC (PCC+SCC), 1 Block.										
Channel	NRB	PCC			SCC1			BW (MHz)	EARFCN	Freq. (MHz)
		BW (MHz)	EARFCN	Freq. (MHz)	BW (MHz)	EARFCN	Freq. (MHz)			
Low	75+50	15	132047	1717.5	10	132167	1729.5	3	Adjacent channel to SCC1 (132252)	1738
Middle	75+50	15	132373	1750.1	10	132493	1762.1	3	Adjacent channel to PCC (132252)	1738
High	75+50	15	132499	1762.7	10	132619	1774.7	3	Adjacent channel to PCC (132392)	1752

LTE Band 38:

Channel (Frequency. MHz)		
Lowest	Middle	Highest
2570	2595	2620

NOTE: Band 38 is completely included in band 41, so the channels of band 41 have been tested to give conformity to the assigned block:

LTE Band 41

Channel (Frequency. MHz)		
Lowest	Middle	Highest
2496	2593	2690

Radiated emissions

SPECIFICATION:

1. LTE Band 7 and LTE Band 41. FCC §2.1053 & §27.53 (m) (4) / RSS-199 Issue 3 Clause 4.5 (b).

FCC §27.53 (m) (4):

(m) For BRS and EBS stations, the power of any emissions outside the licensee's frequency bands of operation shall be attenuated below the transmitter power (P) measured in watts in accordance with the standards below. If a licensee has multiple contiguous channels, out-of-band emissions shall be measured from the upper and lower edges of the contiguous channels.

(4) For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

RSS-199 Issue 3 Clause 4.5 (b):

4.5. In the 1 MHz band immediately outside and adjacent to the channel edge, the unwanted emission power shall be measured with a resolution bandwidth of at least 1% of the occupied bandwidth for base station and fixed subscriber equipment, and 2% for mobile subscriber equipment. Beyond the 1 MHz band, a resolution bandwidth of 1 MHz shall be used. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full required measurement bandwidth of 1 MHz, or 1% or 2% of the occupied bandwidth, as applicable.

Equipment shall comply with the following unwanted emission limits:

(b) for mobile subscriber equipment, the power of any unwanted emissions measured as above shall be attenuated (in dB) below the transmitter power, P (dBW), by at least:

- i. $40 + 10 \log_{10} p$ from the channel edges to 5 MHz away
- ii. $43 + 10 \log_{10} p$ between 5 MHz and X MHz from the channel edges, and
- iii. $55 + 10 \log_{10} p$ at X MHz and beyond from the channel edges

In addition, the attenuation shall not be less than $43 + 10 \log_{10} p$ on all frequencies between 2490.5 MHz and 2496 MHz, and $55 + 10 \log_{10} p$ at or below 2490.5 MHz.

In (b), p is the transmitter power measured in watts and X is 6 MHz or the equipment occupied bandwidth, whichever is greater.

LTE Band 7 and LTE Band 41 MEASUREMENT LIMIT:

On all frequencies between the channel edge and 5 megahertz from the channel edge:

At P_o transmitting power, the specified minimum attenuation becomes $40 + 10 \log (P_o)$, and the level in dBm relative P_o becomes:

$$P_o \text{ (dBm)} - [40 + 10 \log (P_o \text{ in mwatts}) - 30] = -10 \text{ dBm}$$

On all frequencies between 5 megahertz and X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section; and between 2490.5 MHz and 2496 MHz:

At P_o transmitting power, the specified minimum attenuation becomes $43 + 10 \log (P_o)$, and the level in dBm relative P_o becomes:

$$P_o \text{ (dBm)} - [43 + 10 \log (P_o \text{ in mwatts}) - 30] = -13 \text{ dBm}$$

On all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section; and below 2490.5 MHz: