

# Farpointe Data, Inc. RF Exposure Exhibit

**SCOPE OF WORK**

EMC TESTING – Mobile-Ready Contactless Proximity Card Reader: PB 3500

**REPORT NUMBER**

104449567MPK-001B

**ISSUE DATE**

October 29, 2020

**PAGES**

9

**DOCUMENT CONTROL NUMBER**

Non-Specific Radio Report Shell Rev. December 2017 MPK  
© 2017 INTERTEK



## RF Exposure Exhibit (mobile devices)

Report Number: 104449567MPK-001B

Project Number: G104449567

Issue Date: October 29, 2020

Product Designation: Mobile-Ready Contactless Proximity Card

Model Tested: PB 3500

FCC ID: T8I-CONEKT4

IC: 6504A-CONEKT4

to

47CFR 2.1091

RSS-102 Issue 5

for

Farpointe Data, Inc.

**Tested by:**

Intertek  
1365 Adams Court  
Menlo Park, CA 94025 USA

**Client:**

Farpointe Data, Inc.  
2195 Zanker Road  
San Jose, CA 95131 USA

**Report prepared by:**



**Anderson Soungpanya / Project Engineer**

**Report reviewed by:**



**Krishna Vemuri / EMC Manager**

*This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.*

<b>Report No. 104449567MPK-001B</b>	
<b>Equipment Under Test:</b>	Mobile-Ready Contactless Proximity Card Reader
<b>Trade Name:</b>	Farpointe Data, Inc.
<b>Model(s) Tested:</b>	PB 3500
<b>Applicant:</b>	Farpointe Data, Inc.
<b>Contact:</b>	Kirk Bierach
<b>Address:</b>	Farpointe Data, Inc. 2195 Zanker Road San Jose, CA 95131
<b>Country:</b>	USA
<b>Tel. Number:</b>	(408) 731-8700
<b>Email:</b>	kirk.bierach@farpointedata.com
<b>Applicable Regulation:</b>	47CFR 2.1091 RSS-102 Issue 5

## TABLE OF CONTENTS

<i>Farpointe Data, Inc.</i> .....	<b>1</b>
<b>1.0 RF Exposure Summary</b> .....	<b>5</b>
<b>2.0 RF Exposure Limits</b> .....	<b>5</b>
<b>3.0 Test Results (Mobile Configuration)</b> .....	<b>7</b>
<b>4.0 Document History</b> .....	<b>9</b>

**1.0 RF Exposure Summary**

Test	Reference FCC	Reference Industry Canada	Result
Radio frequency Radiation Exposure Evaluation	47 CFR§2.1091	RSS-102 Issue 5	Complies

**2.0 RF Exposure Limits**

In this document, we evaluate the RF Exposure to human body due the intentional transmission from the transmitter (EUT). The limits for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 and RSS-102 are followed.

**2.1 FCC Limits**

According to FCC 1.1310 table 1: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (minutes)
<b>(A)Limits For Occupational / Control Exposures</b>				
0.3 – 3.0	614	1.63	*100	6
3.0 – 30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300 - 1500	...	...	F/300	6
1500 - 100,000	...	...	5	6
<b>(B)Limits For General Population / Uncontrolled Exposure</b>				
0.3 – 1.34	614	1.63	*100	30
1.34 – 30	824/f	2.19/f	*180/f <sup>2</sup>	30
30 – 300	27.5	0.073	0.2	30
300 - 1500	...	...	F/1500	30
1500 - 100,000	...	...	1.0	30

F = Frequency in MHz

\* = plane wave equivalent density

## 2.2 Industry Canada Limits

According to RSS-102, Industry Canada has adopted the SAR and RF field strength limits established in Health Canada's RF exposure guideline, Safety Code 6.

<b>Table 4: RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)</b>				
Frequency Range	Electric Field	Magnetic Field	Power Density	Reference Period
(MHz)	(V/m rms)	(A/m rms)	(W/m <sup>2</sup> )	(minutes)
0.003-10	83	90	-	Instantaneous*
0.1-10	-	0.73/ f	-	6**
1.1-10	87/ f <sup>0.5</sup>	-	-	6**
10-20	27.46	0.0728	-2	6
20-48	58.07/ f <sup>0.25</sup>	0.1540/ f <sup>0.25</sup>	8.944/ f <sup>0.5</sup>	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 f <sup>0.3417</sup>	0.008335 f <sup>0.3417</sup>	0.02619 f <sup>0.6834</sup>	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ f <sup>1.2</sup>
150000-300000	0.158 f <sup>0.5</sup>	4.21 x 10 <sup>-4</sup> f <sup>0.5</sup>	6.67 x 10 <sup>-5</sup> f	616000/f <sup>1.2</sup>
Note: f is frequency in MHz. * Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).				

**3.0 Test Results (Mobile Configuration)**

**3.1 Classification**

Radio is installed inside a mobile host device. The antenna of the product, under normal use condition, is at least 20 cm away from the body of the user and accessible to the end user. Warning statement to the user for keeping at least 20 cm or more separation distance with the antenna should be included in user’s manual.

**3.2 EIRP calculations**

The Mobile-Ready Contactless Proximity Card Reader, Model: PB 3500 consists of two radios: 125 kHz RFID and Bluetooth.

**3.3 Maximum RF Power**

**Mobile-Ready Contactless Proximity Card Reader, Model: PB 3500:**

Frequency Range (MHz)	RF Output (dBm)	Antenna Gain <sup>1</sup> (dBi)	Note
2402-2480	1.97	2.1	Conducted power measurements were taken from 104449567MPK-001

<sup>1</sup>As declared by the manufacturer.

**3.4 RF Exposure Calculation**

**3.4.1 RF Exposure calculation for Bluetooth, Mobile-Ready Contactless Proximity Card Reader, Model: PB 3500:**

Calculations for this report are based on highest power measured for each band.

Frequency Range (MHz)	EIRP (dBm)	EIRP (mW)	Power Density (mW/cm <sup>2</sup> ) @20 cm	FCC Limit (mW/cm <sup>2</sup> )	Results
2402-2480	4.07	2.553	0.000508	1	Complies

Note: Antenna gains below 0 are considered as 0dBi.

Frequency Range (MHz)	EIRP (dBm)	EIRP (mW)	Power Density (W/m <sup>2</sup> ) @20 cm	RSS Limit (W/m <sup>2</sup> )	Results
2402-2480	4.07	2.553	0.00508	5.47	Complies

Note: Antenna gains below 0 are considered as 0dBi.

**Power Density Calculation**

The Power Density can be calculated using the formula

$$S = \text{EIRP} / 4\pi D^2$$

Where: S is Power Density in mW/cm<sup>2</sup>

D is the distance from the antenna in cm.



**4.0 Document History**

<b>Revision/ Job Number</b>	<b>Writer Initials</b>	<b>Reviewers Initials</b>	<b>Date</b>	<b>Change</b>
1.0/ G104274811	AS	KV	October 29, 2020	Original document