



America

**Choose certainty.
Add value.**

Report On

Application for Grant of Equipment Authorization of the
Microchip Technology Inc.
LoRa PCIE Radio Card – Model LG9271

FCC Part 15 Subpart C §15.247
IC RSS-247 Issue 1 May 2015

Report No. TP72122013.100

February 2017





REPORT ON Radio Testing of the
Microchip Technology, Inc.
Model LG9271

TEST REPORT NUMBER TP72122013.100

PREPARED FOR Microchip Technology, Inc.
450 Holger Way
San Jose CA 95134

CONTACT PERSON Carlos Ribeiro
Apps and Hardware Manager
(513) 870-8542
Carlos.Ribeiro@microchip.com


PREPARED BY Steve Hoke
Name
Authorized Signatory
Title: Senior EMC Engineer


APPROVED BY Pete Walsh
Name
Authorized Signatory
Title: Tampa Service Line Manager

DATED 14. February 2017



Revision History

TP72122013.100 Microchip Technology, Inc. Model LG9271					
DATE	OLD REVISION	NEW REVISION	REASON	PAGES AFFECTED	APPROVED BY
14. February 2017	Initial Release				Pete Walsh



CONTENTS

Section	Page No
1	REPORT SUMMARY 5
1.1	Introduction 6
1.2	Brief Summary of Results 7
1.3	Product Information 8
1.4	EUT Test Configuration 9
1.5	Deviations from the Standard 11
1.6	Modification Record 11
1.7	Test Methodology 11
1.8	Test Facility Location 11
2	TEST DETAILS 12
2.1	Peak Output Power 13
2.2	Conducted Emissions 16
2.3	99% Emission Bandwidth 18
2.4	Minimum 6 dB RF Bandwidth 21
2.5	Out-Of-Band Emissions - Conducted 24
2.6	Band-Edge Compliance of RF Conducted Emissions 27
2.7	Spurious Radiated Emissions 29
2.8	Power Spectral Density 35
3	TEST EQUIPMENT USED 39
3.1	Test Equipment Used 40
3.2	Measurement Uncertainty 41
4	DIAGRAM OF TEST SETUP 44
4.1	Test Setup Diagram 45
5	ACCREDITATION, DISCLAIMERS AND COPYRIGHT 47
5.1	Accreditation, Disclaimers and Copyright 48



SECTION 1

1REPORT SUMMARY

Radio Testing of the
Microchip Technology, Inc.
Model LG9271



1.1 INTRODUCTION

The information contained in this report is intended to show verification of Microchip Technology, Inc. Model LG9271 to the requirements of FCC Part 15 Subpart C §15.247 and IC RSS-247 Issue 1 May 2015.

Objective	To perform Radio Testing to determine the Equipment Under Test's (EUT's) compliance with the Test Specification, for the series of tests carried out.
Manufacturer	Microchip Technology, Inc.
Model Number(s)	LG9271
FCC ID Number	T9JLG9271
IC Number	6514A-LG9271
Serial Number(s)	None
Number of Samples Tested	1
Test Specification/Issue/Date	<ul style="list-style-type: none">• FCC Part 15 Subpart C §15.247• IC RSS-247 Issue 1 May 2015. Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices.• IC RSS-Gen Issue 4, November 2014 - General Requirements for Compliance of Radio Apparatus.• 558074 D01 DTS Meas Guidance v03r03, (June 09, 2015) Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247.
Start of Test	29. November, 2016
Finish of Test	03. January 2017
Name of Engineer(s)	Steven Hoke
Related Document(s)	None. Supporting documents for EUT certification are separate exhibits.



1.2 BRIEF SUMMARY OF RESULTS

A brief summary of the tests carried out in accordance with FCC Part 15 Subpart C §15.247 with cross-reference to the corresponding IC RSS standard is shown below.

Section	§15.247 Spec Clause	RSS	Test Description	Result	Comments/ Base Standard
2.1	§15.247(b)(3)	RSS-247 5.4(4)	Peak Output Power	Compliant	
2.2	§15.207(a)	RSS-Gen 8.8	Conducted Emissions	N/A	
2.3		RSS-Gen 6.6	99% Emission Bandwidth	Compliant	
2.4	§15.247(a)(2)	RSS-247 5.2(1)	Minimum 6 dB RF Bandwidth	Compliant	
2.5	§15.247(d)	RSS-247 5.5	Out-of-Band Emissions - Conducted	Compliant	
2.6	§15.247(d)	RSS-247 5.5	Band-edge Compliance of RF Conducted Emissions	Compliant	
2.7	§15.247(d)	RSS-Gen 8.9 and 8.10	Spurious Radiated Emissions	Compliant	
2.7		RSS-Gen 7.1	Receiver Spurious Emissions	Compliant	
2.8	§15.247(d)	RSS-Gen 8.9 and 8.10	Radiated Band Edge Measurements	Compliant	
2.9	§15.247(e)	RSS-247 5.2(2)	Power Spectral Density for Digitally Modulated Device	Compliant	

N/A Not performed. EUT is an RF Module.



1.3 PRODUCT INFORMATION

1.3.1 Technical Description

The Equipment Under Test (EUT) was a Microchip Technology, Inc. Model LG9271. It was mounted and tested on the provided Occam Technology Group host as detailed in this filing.

1.3.2 EUT General Description

EUT Description	PCIE Radio Card (915 MHz version)
Model Number(s)	LG9271
Rated Voltage	3.3 to 5VDC
Mode Verified	LoRa
Capability	LoRa
Primary Unit (EUT)	<input type="checkbox"/> Production <input checked="" type="checkbox"/> Pre-Production <input type="checkbox"/> Engineering
Antenna Manufacturer	SHENZHEN TUKO TECHNOLOGY CO.LTD
Antenna Part Number	TG 03-0930
Antenna Type	Omni-Directional
Antenna Gain	5.0 dBi
Host Brand	Occam Technology Group
Host Model Name	none
Host Model Number	LoRa-Adapter-01

1.3.3 Maximum Conducted Output Power (Peak)

Mode	Frequency Range (MHz)	Output Power (dBm)	Output Power (mW)
LoRa	903 – 927.4	23.92	246.6



1.4 EUT TEST CONFIGURATION

1.4.1 Test Configuration Description

Test Configuration	Description
A	Antenna conducted port test configuration. Direct connection of the antenna port to a spectrum analyzer.
B	Radiated emissions test configuration. EUT transmitting through the integral antenna (mounted on the development board).
C	Radiated emissions test configuration. Antenna port terminated.

1.4.2 EUT Exercise Software


The manufacturer provided an application (Gateway Serial Tool) to configure EUT RF settings.

1.4.3 Support Equipment and I/O cables


Manufacturer	Equipment/Cable	Description
Escort, Inc.	Host Board	LoRa-Adapter-01
Lenovo	Support Laptop for programming EUT	Model B570
-	RF Cable Assembly (EUT antenna port to Spectrum Analyzer)	0.2 meter, SMA Female (Bulkhead) to U.FL

1.4.4 Simplified Test Configuration Diagram

Antenna Conducted Port Test Setup



Radiated Emission Test Setup



For Illustration Purpose Only
Image presented may not represent the
actual EUT, display or support equipment

Configuration not presented is when the EUT is installed inside a representative host. Radiated emissions were performed on the host while the EUT is in Rx and TX mode (worst case).



1.5 DEVIATIONS FROM THE STANDARD

No deviations from the applicable test standards or test plan were made during testing.

1.6 MODIFICATION RECORD

Description of Modification	Modification Fitted By	Date Modification Fitted
Serial Number		
None.		

The table above details modifications made to the EUT during the test programme. The modifications incorporated during each test (if relevant) are recorded on the appropriate test pages.

1.7 TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

For conducted and radiated emissions the equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted according to the Operating Instructions provided by the manufacturer/client.

1.8 TEST FACILITY LOCATION

1.8.1 FCC – Site Registration

The TUV SUD America Inc. (Tampa), test facility has been registered with the Federal Communication Commission as an ISO/IEC 17025 accredited test laboratory and assigned the designation number US1063.

1.8.2 Canadian ISED Site Registration

The TUV SUD America Inc. (Tampa), test facility has been registered with Innovation, Science and Economic Development Canada and assigned the site number 2087A-2.

1.8.3 VCCI Site Registration

The TUV SUD America Inc. (Tampa), test facility has been registered with the VCCI and assigned the registration number A-0256.



SECTION 2

2TEST DETAILS

Radio Testing of the
Microchip Technology, Inc.
Model LG9271



2.1 PEAK OUTPUT POWER

2.1.1 Specification Reference

Part 15 Subpart C §15.247(b)(3)

2.1.2 Standard Applicable

(3) For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

2.1.3 Equipment Under Test and Modification State

Serial No: none / Test Configuration A

2.1.4 Date of Test/Initial of test personnel who performed the test

29. November 2016 / SH

2.1.5 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.1.6 Environmental Conditions

Test performed at TÜV SÜD America Inc. Tampa facility

Ambient Temperature	24 - 26 °C
Relative Humidity	48 - 52 %


2.1.7 Additional Observations

- This is a conducted test (Maximum Peak Conducted Output Power) using direct connection to a spectrum analyzer.
- The cable loss of (0.64) dB was added to the measured value.
- Test methodology is per Clause 9.1.1 of KDB 558074 D01 (DTS Meas Guidance v03r05, April 08, 2016). All conditions under this Clause were satisfied.


2.1.8 Test Results

Channel	Modulation	Measured Peak Power (dBm)	Cable loss (dB)	Actual Peak Power (dBm)	Actual Peak Power (mW)
903 MHz	LoRa SF 12	23.28	0.64	23.92	246.6
914 MHz		22.22	0.64	22.86	193.2
927.5 MHz		23.16	0.64	23.8	239.9


2.1.9 Test Plots



Low Channel Peak Power



Mid Channel Peak Power



High Channel Peak Power



2.2 CONDUCTED EMISSIONS

2.2.1 Specification Reference

Part 15 Subpart C §15.207(a)

2.2.2 Standard Applicable

An intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15–0.5	66 to 56*	56 to 46*
0.5–5	56	46
5–30	60	50

**Decreases with the logarithm of the frequency.*

2.2.3 Equipment Under Test and Modification State

Serial No: 001 /Test Configuration B

2.2.4 Date of Test/Initial of test personnel who performed the test

Not applicable – battery operated

2.2.5 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.2.6 Environmental Conditions

Not applicable as the test was not performed.

2.2.7 Additional Observations

Not applicable as the test was not performed.



2.2.1 Sample Computation (Conducted Emission – Quasi Peak)

Measuring equipment raw measurement (db μ V) @ 150kHz			30.0
Correction Factor (dB)	TEMCO0002 - LISN	0.03	0.11
	Cable 1	0.08	
Reported QuasiPeak Final Measurement (dbμV) @ 150kHz			30.11

2.2.2 Test Results

Not applicable – battery operated



2.3 99% Emission Bandwidth

2.3.1 Specification Reference

RSS-Gen Clause 6.6

2.3.2 Standard Applicable

The emission bandwidth (x dB) is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated x dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth.

When the occupied bandwidth limit is not stated in the applicable RSS or reference measurement method, the transmitted signal bandwidth shall be reported as the 99% emission bandwidth, as calculated or measured.

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- • The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.
- • The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately 3x RBW.

Note: Video averaging is not permitted.

A peak, or peak hold, may be used in place of the sampling detector as this may produce a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold may be necessary to determine the occupied bandwidth if the device is not transmitting continuously.

The trace data points are recovered and are directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded.

The difference between the two recorded frequencies is the 99% occupied bandwidth.

2.3.3 Equipment Under Test and Modification State

Serial No: none / Test Configuration A

2.3.4 Date of Test/Initial of test personnel who performed the test

29. November 2016 / SH

2.3.5 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.



2.3.6 Environmental Conditions

Test performed at TÜV SÜD America Inc. Tampa facility

Ambient Temperature 24 - 26 °C
 Relative Humidity 48 - 52 %


2.3.7 Additional Observations

- This is a conducted test. EUT on normal test mode.
- Span is wide enough to capture the channel transmission.
- RBW is 1% to 5% of the span.
- VBW is 3X RBW.
- Sweep is auto.
- Detector is peak.


2.3.8 Test Results (For reporting purposes only)

Mode	Channel	Measured 99% Bandwidth (kHz)
LoRa	903 MHz	622.5
	914 MHz	620.0
	927 MHz	612.5


2.3.9 Test Plots



LoRa Low Channel



LoRa Mid Channel



LoRa High Channel



2.4 MINIMUM 6 dB RF BANDWIDTH

2.4.1 Specification Reference

Part 15 Subpart C §15.247(a)(2)

2.4.2 Standard Applicable

(2) Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

2.4.3 Equipment Under Test and Modification State

Serial No: none/ Test Configuration A

2.4.4 Date of Test/Initial of test personnel who performed the test

29. November, 2016 / SH

2.4.5 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.4.6 Environmental Conditions

Test performed at TÜV SÜD America Inc. Tampa facility

Ambient Temperature	24 - 26 °C
Relative Humidity	48 - 52 %


2.4.7 Additional Observations

- This is a conducted test.
- Span is wide enough to capture the channel transmission.
- RBW is set to 100 kHz.
- VBW is $\geq 3X$ RBW.
- Sweep is auto.
- Detector is peak.


2.4.8 Test Results

Mode	Channel	Measured Bandwidth (MHz)	Minimum Bandwidth (MHz)	Compliance
Bluetooth LE	903 MHz	0.640	0.500	Complies
	914 MHz	0.600	0.500	Complies
	927 MHz	0.592	0.500	Complies


2.4.9 Test Results Plots



LoRa Low Channel



LoRa Mid Channel



LoRa High Channel



2.5 OUT-OF-BAND EMISSIONS - CONDUCTED

2.5.1 Specification Reference

Part 15 Subpart C §15.247(d)

2.5.2 Standard Applicable

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

2.5.3 Equipment Under Test and Modification State

Serial No: none/ Test Configuration A

2.5.4 Date of Test/Initial of test personnel who performed the test

30. November 2016 / SH

2.5.5 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.5.6 Environmental Conditions


Test performed at TÜV SÜD America Inc. Tampa facility

Ambient Temperature	22 – 24 °C
Relative Humidity	48 – 52%


2.5.7 Additional Observations

- This is a conducted test.
- RBW is 100kHz.VBW is 3X RBW.
- Sweep is auto. Detector is peak. Trace is max hold. Sweep points set to maximum.
- Initial scan was performed to determine the highest level of the desired power within the band. Limit (display line) was drawn 20dB below this level.
- Spectrum was searched from 9 kHz up to 26.5GHz.

2.5.8 Test Results Plots



Conducted Emissions (9 kHz to 30 MHz)



Conducted Emissions (30 MHz to 10 GHz)



2.6 BAND-EDGE COMPLIANCE OF RF CONDUCTED EMISSIONS

2.6.1 Specification Reference

Part 15 Subpart C §15.247(d)

2.6.2 Standard Applicable

See previous test.

2.6.3 Equipment Under Test and Modification State

Serial No: none / Test Configuration A

2.6.4 Date of Test/Initial of test personnel who performed the test

29. November, 2016 / SH

2.6.5 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.6.6 Environmental Conditions

Test performed at TÜV SÜD America Inc. Tampa facility


Ambient Temperature	24 - 26 °C
Relative Humidity	48 - 52 %

2.6.7 Additional Observations


- This is a conducted test.
- RBW is 100kHz.VBW is 3X RBW.
- Sweep is auto. Detector is peak. Trace is max hold.
- Trace was centred on the band-edge frequency.
- Span was set to encompass the band-edge frequency and the peak of the emission.
- Using Marker function, peak of the emission was determined and the delta to the band-edge frequency measured.
- Band-edges were verified ≤ 30 dBc.

2.6.8 Test Results

Complies. See attached plots.



LoRa Low Channel (903 MHz)



LoRa High Channel (927.5 MHz)



2.7 SPURIOUS RADIATED EMISSIONS

2.7.1 Specification Reference

Part 15 Subpart C §15.247(d)

2.7.2 Standard Applicable

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

2.7.3 Equipment Under Test and Modification State

Serial No: 001 / Test Configuration B and C

2.7.4 Date of Test/Initial of test personnel who performed the test

December 08, 2015 and May 19, 2016/FSC

2.7.5 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.7.6 Environmental Conditions

Test performed at TÜV SÜD America Inc. Tampa facility

Ambient Temperature	24 - 26 °C
Relative Humidity	48 - 52 %

2.7.7 Additional Observations

- This is a radiated test. The spectrum was searched from 30MHz to the 10th harmonic.
- There are no emissions found that do not comply to the restricted bands defined in FCC Part 15 Subpart C, 15.205 or Part 15.247(d).
- Only noise floor measurements observed above 18GHz.
- Verification of the EUT while inside a representative host were also performed.
- Measurement was done using EMC32 automated software. Reported level is the actual level with all the correction factors factored in. Correction Factor column is for informational purposes only. See Section 2.6.8 for sample computation.



2.7.1 Sample Computation (Radiated Emission)

Measuring equipment raw measurement (db μ V) @ 30 MHz			20.0
Correction Factor (dB)	Cable 2	0.24	18.94
	TEMCO0011 (antenna)	18.70	
Reported QuasiPeak Final Measurement (db μ V/m) @ 30MHz			38.94

2.7.2 Test Results

See attached plots.

2.7.3 Test Results Below 1GHz





Figure 2.7.3-1 – Radiated Emissions 30 – 1000 MHz Plot



Table 2.7.3-1 – Quasi-Peak Detector Data 30 – 1000 MHz

Frequency (MHz)	Quasi-Peak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
30.000000	30.5	146.0	V	148.0	24.9	9.5	40.0
30.400000	31.0	100.0	V	102.0	24.7	9.0	40.0
209.240000	33.4	100.0	H	104.0	16.6	10.1	43.5
223.480000	31.6	147.0	H	119.0	17.0	14.4	46.0
223.720000	32.6	138.0	H	104.0	17.1	13.4	46.0
344.960000	33.6	100.0	H	225.0	22.3	12.4	46.0
399.000000	42.0	100.0	H	41.0	23.8	4.0	46.0
533.400000	38.2	100.0	V	195.0	26.3	7.8	46.0
534.040000	38.7	100.0	V	212.0	26.3	7.3	46.0
908.000000	86.2	160.0	H	42.0	30.8		

2.7.4 Test Results Above 1GHz (Bluetooth LE Low Channel)



- FCC Part 15 & ICES-003 Class B Radiated 3 m Peak Limit [..EMI radiated]
- FCC Part 15 & ICES-003 Class B Radiated 3 m Average Limit [..]
- Preview Result 1V-PK+ [Preview Result 1V.Result:1]
- Preview Result 1H-PK+ [Preview Result 1H.Result:1]
- ◆ Final Result 1-PK+ [Final Result 1.Result:1]
- ◆ Final Result 2-CAV [Final Result 2.Result:1]

Figure 2.7.4-1 – Radiated Emissions 1 – 10 GHz Plot



Table 2.7.4-1 --Peak Detector Data 1 – 18 GHz

Frequency (MHz)	Peak (dBµV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)
3631.8000	54.3	263.0	V	76.0	4.3	19.7	74.0
4866.6000	47.6	347.0	V	299.0	6.2	26.4	74.0
5711.4000	49.3	137.0	H	195.0	7.9	24.7	74.0
5761.4000	49.9	298.0	H	0.0	8.0	24.1	74.0
6356.2000	54.4	247.0	V	33.0	8.9	19.6	74.0
6615.4000	51.6	126.0	H	121.0	9.1	22.4	74.0
7569.8000	52.7	108.0	V	34.0	11.7	21.3	74.0
7573.8000	53.4	399.0	V	152.0	11.8	20.6	74.0
7787.0000	53.8	298.0	V	107.0	12.7	20.2	74.0
8150.6000	52.1	298.0	V	15.0	13.5	21.9	74.0
9548.6000	56.6	347.0	V	316.0	14.5	17.4	74.0
9655.8000	56.3	172.0	V	345.0	14.7	17.7	74.0

Table 2.7.4-2 --Average Detector Data 1 – 18 GHz

Frequency (MHz)	CAverage (dBµV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)
3631.8000	50.6	263.0	V	76.0	4.3	3.4	54.0
4866.6000	34.8	347.0	V	299.0	6.2	19.2	54.0
5711.4000	37.4	137.0	H	195.0	7.9	16.6	54.0
5761.4000	37.2	298.0	H	0.0	8.0	16.8	54.0
6356.2000	46.5	247.0	V	33.0	8.9	7.5	54.0
6615.4000	38.9	126.0	H	121.0	9.1	15.1	54.0
7569.8000	40.0	108.0	V	34.0	11.7	14.0	54.0
7573.8000	40.4	399.0	V	152.0	11.8	13.6	54.0
7787.0000	40.5	298.0	V	107.0	12.7	13.5	54.0
8150.6000	41.8	298.0	V	15.0	13.5	12.2	54.0
9548.6000	43.6	347.0	V	316.0	14.5	10.4	54.0
9655.8000	43.6	172.0	V	345.0	14.7	10.4	54.0



2.8 POWER SPECTRAL DENSITY

2.8.1 Specification Reference

Part 15 Subpart C §15.247(e)

2.8.2 Standard Applicable

(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

2.8.3 Equipment Under Test and Modification State

Serial No: None / Test Configuration A

2.8.4 Date of Test/Initial of test personnel who performed the test

29. November 2016 / SH

2.8.5 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.8.6 Environmental Conditions

Test performed at TÜV SÜD America Inc. Tampa facility

Ambient Temperature	24 - 26 °C
Relative Humidity	48 - 52 %

2.8.7 Additional Observations


- This is a conducted test.
- Test procedure is per Section 10.8 of KDB 558074 v03r05, (April 08, 2016).
- Detector is Peak.
- Trace Mode is Max hold.
- Sweep time is Auto Couple.
- EUT complies with 3 kHz RBW.
- T= 8.3 mSec (VBW \geq 1/T) (1/T=120 Hz) (VBW set to 300 Hz)
- Number of points in sweep \geq 2 Span / RBW (4,000,000/3,000) =1,333
- Display mode is set to linear




2.8.8 Test Results Summary (PKPSD Method)

Mode	Channel	Marker Reading using 3 kHz RBW (dBm)	Cable loss dB	Linear mode Correction dB	PSD dB	PSD Limit (dBm)	Compliance
LoRa	903 MHz	2.74	0.64	1.0	4.38	8	Complies
	914 MHz	2.10	0.64	1.0	3.74	8	Complies
	927 MHz	2.59	0.64	1.0	4.23	8	Complies


2.8.9 Test Results Plots




Zero Span (T=8.25 mSec)



LoRa Low Channel



LoRa Mid Channel



LoRa High Channel



SECTION 3

3 TEST EQUIPMENT USED



3.1 TEST EQUIPMENT USED

List of absolute measuring and other principal items of test equipment.

ID Number	Test Equipment	Type	Serial Number	Manufacturer	Cal Date	Cal Due Date
Conducted Port Measurement						
NA	High-frequency cable	SMA to N (12) inch	NA	NA	Validated 10/21/2106	
TAME01005	Thermometer	51		Fluke	4/22/2015	4/22/2017
TEMC00093	DVM	87	5920853	Fluke	12/28/2015	12/28/2016
TAME01064	DC Power Supply	HPD 60-5	NA	XANTREX	NCR	
TEMC00091	Spectrum Analyzer	E7402A	US39150137	Agilent	1/21/2016	1/21/2017
NA	Temperature Chamber	EC127	EC0152	Sun Electronics	NCR	
Radiated Emissions						
TEMC00005	Bilog Antenna	6112B	2579	Chase EMC		12/17/2017
TEMC00061	Double-ridged waveguide horn antenna	3117	00109296	ETS Lindgren		2/3/2018
	High-frequency cable					
	High-frequency cable					
TEMC00011	EMI Test Receiver	ESCS30	825788/002	Rhode & Schwarz		12/4/2017
TEMC00012	Spectrum Analyzer	E7404A	MY42000055	Agilent	4/10/2015	4/10/2017
TEMC00013	Pre-amplifier	PA-122	181925	Compower		10/3/2017
Blocking						
TEMC00091	Spectrum Analyzer	E7402A	US39150137	Agilent	1/21/2016	1/21/2017
TEMC00092	Signal Generator	8648C	3619U	Agilent	12/29/2015	12/29/2016
Miscellaneous						
N/A	Test Software	EMC32	V8.54	Rhode & Schwarz	N/A	



3.2 MEASUREMENT UNCERTAINTY

For a 95% confidence level, the measurement uncertainties for defined systems are:

3.2.1 Radiated Emission Measurements (Below 1GHz)

Radiated Measurement 30 - 1000 MHz at a distance of 3 m

	Input Quantity (Contribution) X_i	Value	Prob. Dist.	Divisor	$u(x)$	$u(x)^2$
1	Receiver reading	0.10 dB	Normal, k=1	1.000	0.10	0.01
2	Attenuation: antenna-receiver	0.20 dB	Normal, k=2	2.000	0.10	0.01
3	Antenna factor AF	0.58 dB	Normal, k=2	2.000	0.29	0.08
4	Receiver sinewave accuracy	0.40 dB	Normal, k=2	2.000	0.20	0.04
5	Receiver pulse amplitude	1.50 dB	Rectangular	1.732	0.87	0.75
6	Receiver pulse repetition rate	1.50 dB	Rectangular	1.732	0.87	0.75
7	Noise floor proximity	0.50 dB	Rectangular	1.732	0.29	0.08
8	Mismatch: antenna-receiver	0.95 dB	U-shaped	1.414	0.67	0.45
9	AF frequency interpolation	0.30 dB	Rectangular	1.732	0.17	0.03
10	AF height deviations	0.10 dB	Rectangular	1.732	0.06	0.00
11	Directivity difference at 3 m	3.12 dB	Rectangular	1.732	1.80	3.24
12	Phase center location at 3 m	1.00 dB	Rectangular	1.732	0.58	0.33
13	Cross-polarisation	0.90 dB	Rectangular	1.732	0.52	0.27
14	Balance	0.00 dB	Rectangular	1.732	0.00	0.00
15	Site imperfections	3.85 dB	Triangular	2.449	1.57	2.47
16	Separation distance at 3 m	0.30 dB	Rectangular	1.732	0.17	0.03
17	Effect of setup table material	0.77 dB	Rectangular	1.732	0.44	0.20
18	Table height at 3 m	0.10 dB	Normal, k=2	2.000	0.05	0.00
19	Near-field effects	0.00 dB	Triangular	2.449	0.00	0.00
20	Effect of ambient noise on OATS	0.00 dB				0.00
Combined standard uncertainty				Normal	2.96 dB	
Expanded uncertainty				Normal, k=2	5.92 dB	



3.2.2 Radiated Emission Measurements (Above 1GHz)

Radiated Measurement Above 1 GHz at a distance of 3 m

	Input Quantity (Contribution) X_i	Value		Prob. Dist.	Divisor	$u_i(x)$	$u_i(x)^2$
1	Receiver reading	0.10	dB	Normal, k=1	1.000	0.10	0.01
2	Attenuation: antenna-receiver	0.30	dB	Normal, k=2	2.000	0.15	0.02
3	Preamplifier Gain	0.20	dB	Normal, k=2	2.000	0.10	0.01
4	Antenna factor AF	0.75	dB	Normal, k=2	2.000	0.38	0.14
5	Sinewave accuracy	0.20	dB	Normal, k=2	2.000	0.10	0.01
6	Instability of preamp gain	1.21	dB	Rectangular	1.732	0.70	0.49
7	Noise floor proximity	0.70	dB	Rectangular	1.732	0.40	0.16
8	Mismatch: antenna-preamplifier	1.41	dB	U-shaped	1.414	1.00	0.99
9	Mismatch: preamplifier-receiver	1.30	dB	U-shaped	1.414	0.92	0.85
10	AF frequency interpolation	0.30	dB	Rectangular	1.732	0.17	0.03
11	Directivity difference at 3 m	1.50	dB	Rectangular	1.732	0.87	0.75
12	Phase center location at 3 m	0.30	dB	Rectangular	1.732	0.17	0.03
13	Cross-polarisation	0.90	dB	Rectangular	1.732	0.52	0.27
14	Site imperfections VSWR (Method 2)	2.25	dB	Triangular	2.449	0.92	0.84
15	Effect of setup table material	2.90	dB	Rectangular	1.732	1.67	2.80
16	Separation distance at 3 m	0.30	dB	Rectangular	1.732	0.17	0.03
17	Table height at 3 m	0.00	dB	Normal, k=2	2.000	0.00	0.00
Combined standard uncertainty				Normal	2.73 dB		
Expanded uncertainty				Normal, k=2	5.46 dB		



3.2.3 Conducted Antenna Port Measurement

Antenna Port Conducted Measurements


	Input Quantity (Contribution) X_i	Value	Prob. Dist.	Divisor	$u_i(x)$	$u_i(x)^2$
1	Receiver reading	0.10 dB	Normal, k=1	1.000	0.10	0.01
2	Cable attenuation	1.00 dB	Normal, k=2	2.000	0.50	0.25
3	Receiver sinewave accuracy	0.47 dB	Normal, k=2	2.000	0.24	0.06
4	Receiver pulse amplitude	0.00 dB	Rectangular	1.732	0.00	0.00
5	Receiver pulse repetition rate	0.00 dB	Rectangular	1.732	0.00	0.00
6	Noise floor proximity	0.00 dB	Rectangular	1.732	0.00	0.00
7	Frequency interpolation	0.10 dB	Rectangular	1.732	0.06	0.00
8	Mismatch	0.07 dB	U-shaped	1.414	0.05	0.00
Combined standard uncertainty				Normal	0.57 dB	
Expanded uncertainty				Normal, k=2	1.13 dB	




SECTION 4

4DIAGRAM OF TEST SETUP

4.1 TEST SETUP DIAGRAM



Radiated Emission Test Setup (Below 1GHz)



Radiated Emission Test Setup (Above 1GHz)



SECTION 5

5 ACCREDITATION, DISCLAIMERS AND COPYRIGHT



5.1 ACCREDITATION, DISCLAIMERS AND COPYRIGHT

TÜV SÜD America Inc.'s reports apply only to the specific sample tested under stated test conditions. It is the manufacturer's responsibility to assure the continued compliance of production units of this model. TÜV SÜD America, Inc. shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD America, Inc.'s issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and TÜV SÜD America, Inc., extracts from the test report shall not be reproduced, except in full without TÜV SÜD America, Inc.'s written approval.

This report must not be used to claim product certification, approval, or endorsement by A2LA, NIST, or any agency of the federal government.

TÜV SÜD America, Inc. and its professional staff hold government and professional organization certifications for A2LA, AAMI, ACIL, AEA, ANSI, IEEE, and iNARTE.

