



# Ekahau T201 Wi-Fi Tag

## Benefits

- Locates assets and people in real-time
- Requires no proprietary wireless infrastructure
- Low power consumption and long battery life
- Small size and mounting options enable a wide variety of usage options
- Easy and efficient over-the-air configuration



Ekahau T201 Wi-Fi Tag is a small active radio tag for tracking and finding people and assets. Once attached to an asset or carried by a person the target can be accurately tracked with the Ekahau RTLS platform within the coverage of an 802.11 network. It is most suitable for tracking equipment, personnel or patients in hospitals, manufacturing plants or in any other industry where knowledge of the actual and up-to-date location can improve efficiency and safety.

The T201 tag features an audio buzzer and two red/green LEDs that help to distinguish the tag location. For security applications the call-button enables sending alerts, including the location of the alerter, to security personnel or caregivers. The tag's small size, long battery-life and multiple mounting options make its use care-free in all types of applications. Monitoring continuous, and precise, location information of mobile people and assets has never been this easy.

## Features

- Works with any standard 802.11b infrastructure
- Supports multiple SSID and WEP keys
- Battery life up to several years
- Low battery warning
- Intelligent battery-life management with motion sensor
- Call button/programmable transmitter button
- Customizable audio and LED signals
- RS232 port for configuration
- Multiple mounting options



**Technical Specifications**

Wi-Fi Specification: V1.1  
DSSS (Direct Sequence Spread Spectrum)  
Wi-Fi Standard: 802.11b, 802.11d  
Media Access CSMA/CA  
RCV Sensitivity -82 dBm @ 11 Mb (Typ)  
Output Power 14 dBm +/- 1.0 dBm  
Frequency Range: 2.412-2.484 GHz  
Network Protocol: TCP/IP/DHCP or static  
Security: WEP 64/128 Bit

**Electrical Interface**

DC Power: Internal 1800 mAh Li-Ion rechargeable  
Antenna: Internal, omni-directional  
Configuration: Over-the-air or serial RS-232  
Charger: Output: 5 V/1000 mA, Input: 110-240 V  
Rack charger: Ekahau C201 (optional)

**Battery Life**

Scan-rate Battery life  
10 sec 24 hours  
1 h 1 month\*  
1 d 1 year\*  
External: DC power source (regulated 5V DC/500-600 mA)

**Certifications**

FCC Part 15  
CE Mark  
Telec Mark  
Frequency Band  
Channels 1-11: North America  
Channels 1-13: Global  
Channel 1-14: Japan

**Environment**

Operating: 0 to 50 °C / 32 to 122 °F  
Storage: -10 to 70 °C / 14 to 158 °F  
Humidity: 20 to 95 % non-condensing, relative humidity  
Protection: water splash proof, IP53/NEMA12

**Typical Operating Range**

Open Space: 100 m (330 ft) @ 11Mb  
150 m (500 ft) @ 2Mb  
Closed Office: 40 m (140 ft) @ 11Mb  
60 m (200 ft) @ 2Mb

**Physical**

Dimensions: 49 x 56 x 23 mm / 1.9 x 2.2 x 0.9 in  
Weight: 80 g / 2.8 oz

\*Estimate

Specifications subject to change without prior notice.

[www.ekahau.com](http://www.ekahau.com)  
[sales@ekahau.com](mailto:sales@ekahau.com)  
[info@ekahau.com](mailto:info@ekahau.com)

**West Coast** Ekahau, Inc.  
12930 Saratoga Avenue,  
Suite B-9  
Saratoga, CA 95070  
Tel: 1-866-4EKAHAU  
Fax: 1-408-725 8405  
[sales-americas@ekahau.com](mailto:sales-americas@ekahau.com)

**East Coast** Ekahau, Inc.  
620 Herndon Parkway Suite 200  
Herndon, VA 20170  
Tel: 1-703-481 9861  
Fax: 1-703-481 9834  
[sales-americas@ekahau.com](mailto:sales-americas@ekahau.com)

**Europe** Ekahau, Inc.  
Tammasaarenlaituri 3  
00180 Helsinki, Finland  
Tel: +358 20 743 5910  
Fax: +358 20 743 5919  
[sales-europe@ekahau.com](mailto:sales-europe@ekahau.com)

**Asia** Ekahau, Inc.  
Suite 1002  
Chuang's Tower  
30-32 Connaught Road Central  
Hong Kong  
Tel: +852 3426 4770  
Fax: +852 3426 4061  
[sales-asia@ekahau.com](mailto:sales-asia@ekahau.com)



© 2000-2005 Ekahau, Inc. All rights reserved. Ekahau™, Ekahau Positioning Engine™, Ekahau Site Survey™, Ekahau T201™, Ekahau Finder™ and the Ekahau logo are trademarks or registered trademarks of Ekahau. Other product and company names may be trademarks or trade names of their respective owners.