



Product Service

**Choose certainty.
Add value.**

Report On

FCC and Industry Canada Testing of the
Ericsson RRUS 11 B25 / KRC 131 146/1

COMMERCIAL-IN-CONFIDENCE

FCC ID: TA8AKRC131146-1

IC ID: 287AB-AS1311461

Document 75915268 Report 01 Issue 1

September 2011



Product Service

TÜV SÜD Product Service Ltd, Octagon House, Concorde Way, Segensworth North,
Fareham, Hampshire, United Kingdom, PO15 5RL
Tel: +44 (0) 1489 558100. Website: www.tuvps.co.uk

COMMERCIAL-IN-CONFIDENCE

REPORT ON

FCC and Industry Canada Testing of the
Ericsson RRUS 11 B25 / KRC 131 146/1


Document 75915268 Report 01 Issue 1

September 2011

PREPARED FOR

Ericsson AB
Torshamnsgatan 23
SE-164 80
Stockholm
Sweden

PREPARED BY



X Zhang
Test Engineer

APPROVED BY



M Jenkins
Authorised Signatory


DATED

29 September 2011

ENGINEERING STATEMENT

The measurements shown in this report were made in accordance with the procedures described on test pages. All reported testing was carried out on a sample equipment to demonstrate compliance with FCC CFR 47: Part 24 and Industry Canada RSS-133. The sample tested was found to comply with the requirements defined in the applied rules.

Test Engineer(s);



X Zhang



C Zhang





CONTENTS

Section	Page No
1	REPORT SUMMARY 3
1.1	Introduction 4
1.2	Brief Summary of Results 5
1.3	Declaration of Build Status 7
1.4	Product Information 8
1.5	Test Conditions 13
1.6	Deviations From the Standard 13
1.7	Modification Record 13
1.8	Alternative Test Site 13
2	TEST DETAILS 14
2.1	Maximum Peak Output Power - Conducted 15
2.2	Peak – Average Ratio 17
2.3	Modulation Characteristics 23
2.4	Occupied Bandwidth 26
2.5	Spurious Emissions at Antenna Terminals (± 1 MHz) 29
2.6	Radiated Spurious Emissions 37
2.7	Conducted Spurious Emissions 42
2.8	Frequency Stability Under Temperature Variations 53
2.9	Frequency Stability Under Voltage Variations 55
2.10	Receiver Spurious Emissions 57
3	TEST EQUIPMENT USED 62
3.1	Test Equipment Used 63
3.2	Measurement Uncertainty 64
4	ACCREDITATION, DISCLAIMERS AND COPYRIGHT 65
4.1	Accreditation, Disclaimers and Copyright 66



SECTION 1

REPORT SUMMARY

FCC and Industry Canada Testing of the
Ericsson RRUS 11 B25 / KRC 131 146/1



Product Service

1.1 INTRODUCTION

The information contained in this report is intended to show verification of the Ericsson RRUS 11 B25 / KRC 131 146/1 to the requirements of FCC CFR 47 Part 24 and Industry Canada RSS-133.

Testing was carried out in support of an application for Grant of Equipment Authorisation in the name of RRUS 11 B25 / KRC 131 146/1.

Objective	To perform FCC and Industry Canada Testing to determine the Equipment Under Test's (EUT's) compliance with the Test Specification, for the series of tests carried out.
Manufacturer	Ericsson AB
Product Name	RRUS 11 B25
Part Number	KRC 131 146/1
IC Model Number	AS1311461
Serial Number(s)	C825094639, C825067894
Software Version	CXP9013268%6_R42NA
Hardware Version	R2A
Number of Samples Tested	2
Test Specification/Issue/Date	FCC CFR 47 Part 24: 2010 Industry Canada RSS-133 issue 5: 2009
Incoming Release Date	Declaration of Build Status 08 September 2011
Order Number Date	PTP 05 September 2011
Start of Test	08 September 2011
Finish of Test	28 September 2011
Name of Engineer(s)	X Zhang C Zhang
Related Document(s)	ANSI C63.4: 2009 FCC CFR 47 Part 2: 2010 Industry Canada RSS-GEN Issue 3: 2010



1.2 BRIEF SUMMARY OF RESULTS

A brief summary of results in accordance with FCC CFR 47 Part 24 and Industry Canada RSS-133, is shown below.

Configuration 1 – Radio Equipment							
Section	Spec Clause		Test Description	Mode	Mod State	Result	Comments
	FCC Part 2 and 24	RSS-133 and RSS-GEN					
	24.232 (a)	6.4	Effective Radiated Power	1932.5MHz		N/A	No integral antenna.
				1962.5MHz		N/A	
				1992.5MHz		N/A	
2.1	2.1046, 24.232 (a)	6.4	Maximum Peak Output Power - Conducted	1932.5MHz	0	Pass	-
				1962.5MHz	0	Pass	
				1992.5MHz	0	Pass	
2.2	24.232 (d)	6.4	Peak – Average Ratio	1932.5MHz	0	Pass	-
				1962.5MHz	0	Pass	
				1992.5MHz	0	Pass	
2.3	2.1047 (d)	6.2	Modulation Characteristics	1932.5MHz		N/A	-
				1962.5MHz	0	Pass	
				1992.5MHz		N/A	
2.4	2.1049, 24.238 (b)	RSS-Gen 4.6.1	Occupied Bandwidth	1932.5MHz	0	Pass	-
				1962.5MHz	0	Pass	
				1992.5MHz	0	Pass	
2.5	2.1051, 24.238 (b)	6.5	Spurious Emissions at Antenna Terminals (± 1 MHz)	1932.5MHz	0	Pass	-
				1962.5MHz		N/A	
				1992.5MHz	0	Pass	
2.6	2.1053, 24.238 (a)	6.5	Radiated Spurious Emissions	1932.5MHz	0	Pass	-
				1962.5MHz	0	Pass	
				1992.5MHz	0	Pass	
2.7	2.1051, 24.238 (a)	6.5	Conducted Spurious Emissions	1932.5MHz	0	Pass	-
				1962.5MHz	0	Pass	
				1992.5MHz	0	Pass	



Product Service

Configuration 1 – Radio Equipment							
Section	Spec Clause		Test Description	Mode	Mod State	Result	Comments
	FCC Part 2 and 24	RSS-133 and RSS-GEN					
2.8	2.1055, 24.235	6.3	Frequency Stability Under Temperature Variations	1932.5MHz	0	N/A	-
				1962.5MHz		Pass	
				1992.5MHz		N/A	
2.9	2.1055, 24.235	6.3	Frequency Stability Under Voltage Variations	1932.5MHz	0	N/A	-
				1962.5MHz		Pass	
				1992.5MHz		N/A	
2.10	-	6.6	Receiver Spurious Emissions	1932.5MHz	0	Pass	-
				1962.5MHz	0	Pass	
				1992.5MHz	0	Pass	

N/A – Not Applicable



1.3 DECLARATION OF BUILD STATUS

MAIN EUT	
MANUFACTURING DESCRIPTION	Radio Equipment
MANUFACTURER	Ericsson AB
PRODUCT NAME	RRUS 11 B25
PART NUMBER	KRC 131 146/1
IC Model Number	AS1311461
SERIAL NUMBER	C825094639 C825067894
HARDWARE VERSION	R2A
SOFTWARE VERSION	CXP9013268%6_R42NA
TRANSMITTER OPERATING RANGE	TX: 1930MHz - 1995MHz RX: 1850MHz - 1915MHz
DUPLEXER MODE	FDD
MODULATIONS	QPSK, 16QAM, 64QAM
INTERMEDIATE FREQUENCIES	--
ITU DESIGNATION OF EMISSION	5M00F9W
SUPPORTED CHANNEL BANDWIDTH CONFIGURATION	Only 5MHz according to 3GPP TS 36.141 supported
OUTPUT POWER (RMS) (W or dBm)	2 x 46.0dBm (2 x 40W)
NUMBER OF ANTENNA PORTS	2 TX/RX ports
SUPPORTED CONFIGURATION	Dual Single Carrier. Both RF chains are identical
FCC ID	TA8AKRC131146-1
IC ID	287AB-AS1311461
TECHNICAL DESCRIPTION (a brief description of the intended use and operation)	The equipment is the Radio Part of LTE Base Station.

Signature

Date

19 September 2011

D of B S Serial No

75915268/01

No responsibility will be accepted by TÜV SÜD Product Service as to the accuracy of the information declared in this document by the manufacturer.




1.4 PRODUCT INFORMATION

1.4.1 Technical Description

The Equipment Under Test (EUT) RRUS 11 B25 / KRC 131 146/1 is an Ericsson Radio Equipment working in the public mobile service 1900MHz band which operates in LTE mode. The RRUS 11 B25 / KRC 131 146/1 operates from a -48V DC supply.

The Equipment Under Test (EUT) is shown in the photograph below. A full technical description can be found in the Manufacturers documentation.



Equipment Under Test



Product Service

1.4.2 Test Configuration

Configuration 1: Radio Equipment

The EUT was configured in accordance with FCC CFR 47 Part 24 and Industry Canada RSS-133.

The RRUS 11 B25 / KRC 131 146/1 supports Test Models E-TM1.1, E-TM3.2 and E-TM3.1 at 1900MHz defined in 3GPP TS 36.141. Test Model E-TM1.1 was used to represent QPSK modulation only, Test Model E-TM3.2 was used to represent 16QAM modulation, and Test Model E-TM3.1 was used to represent 64QAM modulation. The EUT only supports 5MHz Occupied Bandwidth.


The EUT has two TX/RX ports and it can be configured to transmit in 1900MHz with both TX are active. All TX measurements were performed on the combined TX/RX output connector RF A. Limited complementary TX measurements were done at connector RF B to verify identical performance for both transmitter chains. RX testing was performed on the RX connector RF B of the EUT when the EUT was set as single Transmitter.

The complete testing was performed with the EUT transmitting at maximum RF power unless otherwise stated.

The EUT was powered by a -48V DC Power supply.



Test Setup, Conducted Measurement:




Test Object	Part Number	Version	Serial Number
Radio Part	RRUS 11 B25 / KRC 131 146/1	R2A	C825094639

No.	Auxiliary Equipment	Part Number / Model Type	Version	Serial Number
1	Computer	DELL LATITUDE D630	--	WQQJ3-6T899-HXPCF-77RM7-H7CT3
2	RBS 6601	BFL 901 009/1	--	--
	DUL 20 01	KDU 137 533/4	R1C	C824321416
	SUP 6601	1/BFL 901 009/1	R3B	BR81477044
3	Switch	TEH108SK	--	S108SK01484801224
4	Attenuator	DTS100G	--	11081901
5	Load	TF150	--	11081910
6	Power Supply	Agilent N5768A	--	US11C3537G
	Power Supply	Agilent N5768A	--	US11C3535G
7	Power Meter	Rohde & Schwarz NRP2	--	101194
	Thermal Power Sensor	Rohde & Schwarz NRP-Z51	--	20-318205
	Spectrum Analyzer	FSQ26	--	100253



Test Setup, Radiated Measurement:



Test Object	Part Number	Version	Serial Number
Radio Part	RRUS 11 B25 / KRC 131 146/1	R2A	C825094639

No.	Auxiliary Equipment	Part Number / Model Type	Version	Serial Number
1	Computer	DELL LATITUDE D630	--	WQQJ3-6T899-HXPCF-77RM7-H7CT3
2	RBS 6601	BFL 901 009/1	--	--
	DUL 20 01	KDU 137 533/4	R1C	C824321416
	SUP 6601	1/BFL 901 009/1	R3B	BR81477044
3	Switch	TEH108SK	--	S108SK01484801224
4	Power Supply	Agilent N5768A	--	US11C3537G
5	Load	TF150	--	11081910
	Load	TF150	--	11081906



Product Service

1.4.3 Modes of Operation

Modes of operation of each EUT during testing were as follows:

Mode 1 : EARFCN 8065: 1932.5MHz (Bottom Channel)

Mode 2 : EARFCN 8365: 1962.5MHz (Middle Channel)

Mode 3 : EARFCN 8665: 1992.5MHz (Top Channel)

Information on the specific test modes utilised are detailed in the test procedure for each individual test.



Product Service

1.5 TEST CONDITIONS

For all tests the EUT was set up in accordance with the relevant test standard and to represent typical operating conditions. Tests were applied with the EUT situated in a shielded enclosure, test laboratories or an open test area as appropriate.

The EUT was powered from a -48V DC supply.

1.6 DEVIATIONS FROM THE STANDARD

No deviations from the applicable test standards or test plan were made during testing.

1.7 MODIFICATION RECORD

No modifications were made to the EUT during testing.

1.8 ALTERNATIVE TEST SITE

Testing has been performed under the following site registrations:

FCC Accreditation 910917:

The State Radio Monitoring Centre, No.80 Beilishi Road Xicheng District Beijing, China.

Industry Canada Accreditation 7308A:

The State Radio Monitoring Centre, No.80 Beilishi Road Xicheng District Beijing, China.



Product Service

SECTION 2

TEST DETAILS

FCC and Industry Canada Testing of the
Ericsson RRUS 11 B25 / KRC 131 146/1



Product Service

2.1 MAXIMUM PEAK OUTPUT POWER - CONDUCTED

2.1.1 Specification Reference

FCC CFR 47 Part 2.1046
FCC CFR 47 Part 24, Clause 24.232 (a)
Industry Canada RSS-133, Clause 6.4

2.1.2 Equipment Under Test

RRUS 11 B25 / KRC 131 146/1, S/N: C825094639

2.1.3 Date of Test and Modification State

08 September 2011 – Modification State 0

2.1.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.1.5 Test Method and Operating Modes

The test was applied in accordance with the test method requirements of FCC CFR 47 Part 2 and Part 24 and Industry Canada RSS-133.

Using a power meter and attenuator(s), the output power of the EUT was measured at the antenna terminal. The carrier power was measured with E-TM1.1, E-TM3.2 and E-TM3.1 test models.

The path loss was measured and entered as a reference level offset.

The test was performed with the EUT in the following configurations and modes of operation:

Configuration 1 - Mode 1
 - Mode 2
 - Mode 3

2.1.6 Environmental Conditions

08 September 2011
Ambient Temperature 23.0°C
Relative Humidity 49.5%



2.1.7 Test Results

For the period of test the EUT met the requirements of FCC CFR 47 Part 2 and Part 24 and Industry Canada RSS-133 for Maximum Peak Output Power.

The test results are shown below

Configuration 1 - Mode 1, 2 and 3

E-TM1.1

UARFCN	Frequency (MHz)	Path Loss (dB)	Result (dBm) RMS	Result (W) RMS
8065 (Bottom)	1932.5	41.5	45.69	37.07
8365 (Middle)	1962.5	41.5	45.62	36.48
8665 (Top)	1992.5	41.5	45.64	36.64

E-TM3.2

UARFCN	Frequency (MHz)	Path Loss (dB)	Result (dBm) RMS	Result (W) RMS
8065 (Bottom)	1932.5	41.5	45.68	36.98
8365 (Middle)	1962.5	41.5	45.62	36.48
8665 (Top)	1992.5	41.5	45.57	36.06

E-TM3.1

UARFCN	Frequency (MHz)	Path Loss (dB)	Result (dBm) RMS	Result (W) RMS
8065 (Bottom)	1932.5	41.5	45.70	37.15
8365 (Middle)	1962.5	41.5	45.67	36.90
8665 (Top)	1992.5	41.5	45.63	36.56

Limit	≤100W or ≤+50dBm
-------	------------------

Remarks

The EUT does not exceed 100W or 50dBm at the measured frequencies.



Product Service

2.2 PEAK – AVERAGE RATIO

2.2.1 Specification Reference

FCC CFR 47 Part 24, Clause 24.232 (d)
Industry Canada RSS-133, Clause 6.4

2.2.2 Equipment Under Test

RRUS 11 B25 / KRC 131 146/1, S/N: C825094639

2.2.3 Date of Test and Modification State

08 September 2011 – Modification State 0

2.2.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.2.5 Test Method and Operating Modes

The test was applied in accordance with the test method requirements of FCC CFR 47 Part 24 and Industry Canada RSS-133.

A peak to average ratio measurement is performed at the conducted port of the EUT. The spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

The path loss measured and entered as a reference level offset.

The test was performed with the EUT in the following configurations and modes of operation:

Configuration 1 - Mode 1
 - Mode 2
 - Mode 3

2.2.6 Environmental Conditions

08 September 2011

Ambient Temperature 23.0°C

Relative Humidity 49.5%



Product Service


2.2.7 Test Results

For the period of test the EUT met the requirements of FCC CFR 47 Part 24 and Industry Canada RSS-133 for Peak – Average Ratio.

The test results are shown below.

E-TM1.1


Configuration 1 - Mode 1



Date: 8.SEP.2011 13:56:46



Configuration 1 - Mode 2




Trace 1
Mean 45.71 dBm
Peak 52.76 dBm
Crest 7.06 dB

10 % 3.72 dB
1 % 6.41 dB
.1 % 6.99 dB
.01 % 7.05 dB

Date: 8.SEP.2011 13:09:00

Configuration 1 - Mode 3



Trace 1
Mean 45.64 dBm
Peak 52.98 dBm
Crest 7.34 dB

10 % 3.72 dB
1 % 6.41 dB
.1 % 6.99 dB
.01 % 7.21 dB


Date: 8.SEP.2011 13:59:51



Product Service


E-TM3.2

Configuration 1 - Mode 1



Date: 8.SEP.2011 13:40:44


Configuration 1 - Mode 2



Date: 8.SEP.2011 13:08:37




Configuration 1 - Mode 3



Date: 8.SEP.2011 14:35:36

E-TM3.1


Configuration 1 - Mode 1



Date: 8.SEP.2011 13:37:03




Configuration 1 - Mode 2



Date: 8.SEP.2011 13:11:16

Configuration 1 - Mode 3



Date: 8.SEP.2011 14:34:16

Limit	13dB
-------	------

Remarks

The Peak – Average ratio does not exceed 13dB at the measured frequencies.



Product Service

2.3 MODULATION CHARACTERISTICS

2.3.1 Specification Reference

FCC CFR 47 Part 2, Clause 2.1047 (d)
Industry Canada RSS-133 Clause 6.2

2.3.2 Equipment Under Test

RRUS 11 B25 / KRC 131 146/1, S/N: C825094639

2.3.3 Date of Test and Modification State

08 September 2011 – Modification State 0

2.3.4 Test Method and Operating Modes

The test was applied in accordance with the test method requirements of FCC CFR 47 Part 2 and Industry Canada RSS-133.

Connect the RF output connector RF A to a spectrum analyzer with an attenuator. The other connector was connected to a match load. The EUT was controlled to transmit maximum power. Measure and record the constellation of the EUT by the spectrum analyzer.

The EUT supports QPSK, 16QAM and 64QAM modulations.

The test was performed with the EUT in the following configurations and modes of operation:

Configuration 1 - Mode 2

2.3.5 Environmental Conditions

	08 September 2011
Ambient Temperature	23.0°C
Relative Humidity	49.5%




2.3.6 Test Result

Plots are shown on the following showing the EUT transmitting with all of the modulations:

The test results are shown below


Configuration 1 - Mode 2

E-TM1.1: EUT transmitting with QPSK modulation in:






E-TM3.2: EUT transmitting with 16QAM modulation:



Date: 8.SEP.2011 13:06:54

E-TM3.1: EUT transmitting with 64QAM modulation:



Date: 8.SEP.2011 13:13:14



Product Service

2.4 OCCUPIED BANDWIDTH

2.4.1 Specification Reference

FCC CFR 47 Part 2, Clause 2.1049 (h)
FCC CFR 47 Part 24, Clause 24.238 (b)
Industry Canada RSS-GEN, Clause 4.6.1

2.4.2 Equipment Under Test

RRUS 11 B25 / KRC 131 146/1, S/N: C825094639

2.4.3 Date of Test and Modification State

08 September 2011 – Modification State 0

2.4.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.4.5 Test Method and Operating Modes

The test was applied in accordance with the test method requirements of FCC CFR 47 Part 2 and Part 24 and Industry Canada RSS-GEN.

The EUT was transmitting at maximum power, modulated using the test model E-TM1.1, E-TM3.2 and E-TM3.1, only the test results of test model E-TM1.1 as the representative are recorded. At least 1% of the emission bandwidths were used for the resolution and video bandwidths.

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission.

The test was performed with the EUT in the following configurations and modes of operation:

Configuration 1 - Mode 1
 - Mode 2
 - Mode 3

2.4.6 Environmental Conditions

08 September 2011
Ambient Temperature 23.0°C
Relative Humidity 49.5%




2.4.7 Test Results

For the period of test the EUT met the requirements of FCC CFR 47 Part 2 and Part 24 and Industry Canada RSS-GEN for Occupied Bandwidth.

The test results are shown below

E-TM1.1


Configuration 1 - Mode 1



Date: 8.SEP.2011 13:55:45




Configuration 1 - Mode 2



Date: 8.SEP.2011 12:36:17

Configuration 1 - Mode 3



Date: 8.SEP.2011 14:02:05



Product Service

2.5 SPURIOUS EMISSIONS AT ANTENNA TERMINALS (± 1 MHz)

2.5.1 Specification Reference

FCC CFR 47 Part 2, Clause 2.1051
 FCC CFR 47 Part 24, Clause 24.238 (b)
 Industry Canada RSS-133 Clause 6.5

2.5.2 Equipment Under Test

RRUS 11 B25 / KRC 131 146/1, S/N: C825094639

2.5.3 Date of Test and Modification State

08 and 28 September 2011 – Modification State 0

2.5.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.5.5 Test Method and Operating Modes

The test was applied in accordance with the test method requirements of FCC CFR 47 Part 2 and Part 24 and Industry Canada RSS-133.

In accordance with 24.238(b), at least 1% of the emission bandwidth was used for the resolution bandwidths up to 1MHz away from the block edge. A resolution bandwidth of 50kHz was used between 1MHz to 5MHz away from the band edge. As the FCC rules specify a RBW of 1MHz for measurements of emissions > 1MHz away from the band edges, the limit was adjusted with -13dB to -26dBm to compensate for the reduced measurement bandwidth. Spectrum analyser detector was set as RMS.

The path loss measured and entered as a reference level offset.

The EUT was tested at its maximum power level.

The test was performed with the EUT in the following configurations and modes of operation:

Configuration 1 - Mode 1
 - Mode 3

2.5.6 Environmental Conditions

	08 September 2011	28 September 2011
Ambient Temperature	23.0°C	23.5°C
Relative Humidity	49.5%	45.8%



Product Service

2.5.7 Test Results

For the period of test the EUT met the requirements of FCC CFR 47 Part 2 and Part 24 and Industry Canada RSS-133 for Spurious Emissions Antenna Terminals (± 1 MHz)

Below are the Frequencies the EUT was tested against along with the tested channels.

ETM1.1

Configuration 1 - Mode 1 and Mode 3

Band Edge Frequency	Bottom 1930 MHz	Top 1995 MHz	RBW / VBW (Hz)
Channel No./Frequencies	Channel: 8065 Frequency: 1932.5 MHz	Channel: 8665 Frequency: 1992.5 MHz	50k / 500k

ETM3.2

Configuration 1 - Mode 1 and Mode 3

Band Edge Frequency	Bottom 1930 MHz	Top 1995 MHz	RBW / VBW (Hz)
Channel No./Frequencies	Channel: 8065 Frequency: 1932.5 MHz	Channel: 8665 Frequency: 1992.5 MHz	50k / 500k

ETM3.1

Configuration 1 - Mode 1 and Mode 3

Band Edge Frequency	Bottom 1930 MHz	Top 1995 MHz	RBW / VBW (Hz)
Channel No./Frequencies	Channel: 8065 Frequency: 1932.5 MHz	Channel: 8665 Frequency: 1992.5 MHz	50k / 500k

The channels shown in the table above are the minimum and maximum channels that can be used in the authorised frequency ranges to maintain compliance.




Product Service


The test results are shown below

E-TM1.1

Configuration 1 - Mode 1




Date: 8.SEP.2011 16:42:25




Date: 8.SEP.2011 16:41:37



Configuration 1 - Mode 3



Date: 8.SEP.2011 17:08:58




Date: 8.SEP.2011 17:09:56




E-TM3.2

Configuration 1 - Mode 1



Date: 8.SEP.2011 16:49:32




Date: 8.SEP.2011 16:51:15




Product Service

Configuration 1 - Mode 3



Date: 8.SEP.2011 17:01:14




Date: 28.SEP.2011 07:19:21




E-TM3.1

Configuration 1 - Mode 1



Date: 8.SEP.2011 16:53:55




Date: 8.SEP.2011 16:52:58




Product Service

Configuration 1 - Mode 3



Date: 8.SEP.2011 16:56:12



Date: 8.SEP.2011 16:58:57

Limit

The power of any emission outside the frequency band shall be attenuated below the transmitter power (P) by at least $43 + 10\log P$ dB.



Product Service

2.6 RADIATED SPURIOUS EMISSIONS

2.6.1 Specification Reference

FCC CFR 47 Part 2, Clause 2.1053
FCC CFR 47 Part 24, Clause 24.238 (a)
Industry Canada RSS-133, Clause 6.5

2.6.2 Equipment Under Test

RRUS 11 B25 / KRC 131 146/1, S/N: C825094639

2.6.3 Date of Test and Modification State

15 and 19 September 2011 – Modification State 0

2.6.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.6.5 Test Method and Operating Modes

The test was applied in accordance with the test method requirements of FCC CFR 47 Part 2 and Part 24 and Industry Canada RSS-133.

A preliminary profile of the Spurious Radiated Emissions was obtained by operating the EUT on a remotely controlled turntable within the chamber. Measurements of emissions from the EUT were obtained with the Measurement Antenna in both Horizontal and Vertical Polarizations.

Emissions identified within the range 30MHz – 25GHz were then formally measured using a Peak detector as the worst case.

In the frequency Range 30MHz – 25GHz, the measurement was performed with a resolution bandwidth of 1MHz.

The measurements were performed at a 3m distance unless otherwise stated.

The limits for Spurious Emissions have been calculated, as shown below using the following formula:

Field Strength of Carrier - $(43 + 10\log(P))$ dB

Where:

Field Strength is measured in dB μ V/m

P is measured Transmitter Power in Watts



Determination of Spurious Emission Limit

As the EUT does not have an integral antenna, the field strength of the carrier has been calculated assuming that the power is to be fed to a half-wave tuned dipoles as per 2.1053 (a).

$$E_{(v/m)} = (30 \times G_i \times P_o)^{0.5} / d$$

Where G_i is the antenna gain of ideal half-wave dipoles,
 P_o is the power out of the transceiver in W,
 d is the measurement distance in meter.

Therefore at 3m measurement distance the field strength using the lowest transceiver output power would be:

$$E_{(v/m)} = (30 \times 1.64 \times 36.06)^{0.5} / 3 = 14.04 \text{V/m} = 143.0 \text{dB}\mu\text{V/m}$$

As per 24.238(a) the spurious emission must be attenuated by $43 + 10 \log (P_o)$ dB this gives:

$$43 + 10 \log(36.06) = 58.6 \text{dB}$$

Therefore the limit at 3m measurement distance is:

$$143.0 - 58.6 = 84.4 \text{dB}\mu\text{V/m}$$

This limit has been used to determine Pass or Fail for the harmonics measured and detailed in the following results.

The test was performed with the EUT operating on all modes in section 1.4.3 and record the result of the following configurations and modes of operation for worst case:

Configuration 1 - Mode 1
 - Mode 2
 - Mode 3

2.6.6 Environmental Conditions

	15 September 2011	19 September 2011
Ambient Temperature	22.0°C	22.3°C
Relative Humidity	55.1%	48.9%



Product Service

2.6.7 Test Results

For the period of test the EUT met the requirements of FCC CFR 47 Part 2 and Part 24 and Industry Canada RSS-133 for Radiated Spurious Emissions.

The test results are shown below

Note: Only the worst case results plots have been included as all of the emissions are greater than 20dB below the limit. A set of plots have been included to show the measurement system noise floor.


E-TM1.1

Configuration 1 - Mode 1

No emissions were detected within 20dB of the limit.


Configuration 1 - Mode 2

30MHz to 1GHz






1GHz to 18GHz



Note: The highest emission near the limit is the operating frequency.

18GHz to 25GHz





Product Service

Configuration 1 - Mode 3

No emissions were detected within 20dB of the limit.

E-TM3.2

Configuration 1 - Mode 2

No emissions were detected within 20dB of the limit.

E-TM3.1

Configuration 1 - Mode 2

No emissions were detected within 20dB of the limit.

Limit	-13dBm
-------	--------

Remarks

The EUT does not exceed -13dBm at the measured frequencies.



Product Service

2.7 CONDUCTED SPURIOUS EMISSIONS

2.7.1 Specification Reference

FCC CFR 47 Part 2, Clause 2.1051
 FCC CFR 47 Part 24, Clause 24.238 (a)
 Industry Canada RSS-133, Clause 6.5

2.7.2 Equipment Under Test

RRUS 11 B25 / KRC 131 146/1, S/N: C825094639

2.7.3 Date of Test and Modification State

08 and 28 September 2011 – Modification State 0

2.7.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.7.5 Test Method and Operating Modes

The test was applied in accordance with the test method requirements of FCC CFR 47 Part 2 and Part 24 and Industry Canada RSS-133.

In accordance with Part 2.1051, the spurious emissions from the antenna terminal were measured. The transmitter output power was attenuated using an attenuator and the frequency spectrum investigated from 9kHz to 25GHz. The EUT was set to transmit on maximum power. The EUT was tested on Bottom, Middle and Top channels for E-TM1.1, E-TM3.2 and E-TM3.1 test models. The resolution was set to 1MHz for 9kHz to 25GHz thus meeting the requirements of Part 24.238 (b). The spectrum analyser detector was set to peak and trace was kept on Max Hold.

The maximum path loss across the measurement band was used as the reference level offset to ensure worst case.

In addition, measurements were made up to the 10th harmonic of the highest internal frequency.

The test was performed with the EUT in the following configurations and modes of operation:

Configuration 1 - Mode 1
 - Mode 2
 - Mode 3

2.7.6 Environmental Conditions


	08 September 2011	28 September 2011
Ambient Temperature	23.0°C	23.5°C
Relative Humidity	49.5%	45.8%



E-TM1.1

Configuration 1 - Mode 1


9kHz to 3GHz



Date: 8.SEP.2011 13:53:09

Note: The emission beyond the limit is the operating frequency.

3GHz to 25GHz




Date: 28.SEP.2011 08:58:29



Product Service

Configuration 1 - Mode 2


9kHz to 3GHz



Date: 8.SEP.2011 12:41:48

Note: The emission beyond the limit is the operating frequency.

3GHz to 25GHz




Date: 28.SEP.2011 08:57:06



Product Service

Configuration 1 - Mode 3


9kHz to 3GHz



Date: 8.SEP.2011 14:05:24

Note: The emission beyond the limit is the operating frequency.

3GHz to 25GHz




Date: 28.SEP.2011 08:46:09



E-TM3.2

Configuration 1 - Mode 1


9kHz to 3GHz



Date: 8.SEP.2011 13:44:41

Note: The emission beyond the limit is the operating frequency.

3GHz to 25GHz




Date: 28.SEP.2011 09:00:18



Configuration 1 - Mode 2


9kHz to 3GHz



Date: 8.SEP.2011 12:56:47

Note: The emission beyond the limit is the operating frequency.

3GHz to 25GHz




Date: 28.SEP.2011 08:55:33



Configuration 1 - Mode 3


9kHz to 3GHz



Date: 8.SEP.2011 14:19:29

Note: The emission beyond the limit is the operating frequency.

3GHz to 25GHz




Date: 28.SEP.2011 08:43:57



E-TM3.1

Configuration 1 - Mode 1


9kHz to 3GHz



Date: 8.SEP.2011 13:31:50

Note: The emission beyond the limit is the operating frequency.

3GHz to 25GHz




Date: 28.SEP.2011 09:03:47



Product Service

Configuration 1 - Mode 2


9kHz to 3GHz



Date: 8.SEP.2011 13:22:09

Note: The emission beyond the limit is the operating frequency.

3GHz to 25GHz




Date: 28.SEP.2011 08:50:25



Product Service

Configuration 1 - Mode 3


9kHz to 3GHz



Date: 8.SEP.2011 14:31:53

Note: The emission beyond the limit is the operating frequency.

3GHz to 25GHz



Date: 28.SEP.2011 08:48:11

Remarks

The EUT does not exceed -13dBm at the frequency range of 9kHz to 25GHz.



Product Service

2.8 FREQUENCY STABILITY UNDER TEMPERATURE VARIATIONS

2.8.1 Specification Reference

FCC CFR 47 Part 2, Clause 2.1055
 FCC CFR 47 Part 24, Clause 24.235
 Industry Canada RSS-133, Clause 6.3

2.8.2 Equipment Under Test

RRUS 11 B25 / KRC 131 146/1, S/N: C825094639

2.8.3 Date of Test and Modification State

13 and 14 September 2011 – Modification State 0

2.8.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.8.5 Test Method and Operating Modes

The test was applied in accordance with the test method requirements of FCC CFR 47 Part 2 and Part 24 and Industry Canada RSS-133.

The EUT was set to transmit on maximum power. A Spectrum Analyser was used to measure the frequency error. The temperature was adjusted between -30°C and +50°C in 10° steps as per 2.1055.

The test was performed with the EUT in the following configurations and modes of operation:

Configuration 1 - Mode 2

2.8.6 Environmental Conditions

	13 September 2011	14 September 2011
Ambient Temperature	25.1°C	23.3°C
Relative Humidity	40.2%	42.0%



Product Service

2.8.7 Test Results

For the period of test the EUT met the requirements of FCC CFR 47 Part 2 and Part 24 and Industry Canada RSS-133 for Frequency Stability Under Temperature Variations.

The test results are shown below

Power Supply: -48V DC

E-TM1.1

Configuration 1 - Mode 2

Temperature Interval (°C)	Deviation (Hz)
-30	-18.98
-20	24.47
-10	13.21
0	-10.31
+10	-10.74
+20	-10.78
+30	-20.10
+40	21.17
+50	-26.30

Limit	±1.0 ppm or ±1.96kHz
-------	----------------------

Remarks

The frequency stability of the EUT is sufficient to keep it within the authorised frequency ranges at any temperature interval across the measured range.



Product Service

2.9 FREQUENCY STABILITY UNDER VOLTAGE VARIATIONS

2.9.1 Specification Reference

FCC CFR 47 Part 2, Clause 2.1055
FCC CFR 47 Part 24, Clause 24.235
Industry Canada RSS-133, Clause 6.3

2.9.2 Equipment Under Test

RRUS 11 B25 / KRC 131 146/1, S/N: C825094639

2.9.3 Date of Test and Modification State

14 September 2011 – Modification State 0

2.9.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.9.5 Test Method and Operating Modes

The test was applied in accordance with the test method requirements of FCC CFR 47 Part 2 and Part 24 and Industry Canada RSS-133.

The EUT was set to transmit on maximum power. A Spectrum Analyser was used to measure the frequency error. The supplied voltage was varied from 85 to 115 percent of the nominal value.

The test was performed with the EUT in the following configurations and modes of operation:

Configuration 1 - Mode 2

2.9.6 Environmental Conditions

	14 September 2011
Ambient Temperature	23.3°C
Relative Humidity	42.0%



Product Service

2.9.7 Test Results

For the period of test the EUT met the requirements of FCC CFR 47 Part 2 and Part 24 and Industry Canada RSS-133 for Frequency Stability Under Voltage Variations.

The test results are shown below

Temperature: 20°C

E-TM1.1

Configuration 1 - Mode 2

DC Voltage (V)	Deviation (Hz)
-40.8	-19.42
-48.0	-10.78
-55.2	-14.60

Limit	±1.0 ppm or ±1.96kHz
-------	----------------------

Remarks

The frequency stability of the EUT is sufficient to keep it within the authorised frequency ranges under voltage variations across the measured range.



Product Service

2.10 RECEIVER SPURIOUS EMISSIONS

2.10.1 Specification Reference

Industry Canada RSS-133, Clause 6.6

2.10.2 Equipment Under Test

RRUS 11 B25 / KRC 131 146/1, S/N: C825067894

2.10.3 Date of Test and Modification State

16 September 2011 – Modification State 0

2.10.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.10.5 Test Method and Operating Modes

The test was applied in accordance with the test method requirements of Industry Canada RSS 133.

In accordance with RSS-Gen Clause 6.2, the receiver spurious emissions from the antenna terminal were measured. Measurements were performed on the receiver antenna connector RF B. The EUT was set to transmitter mode on the TX connector RF A and during the measurement the RF A was terminated with a match load, (50 Ohm).

The resolution bandwidth was set to 120kHz in the frequency range 9kHz to 1GHz, and in the frequency range 1GHz to 13GHz the resolution bandwidth was set to 1MHz thus meeting the requirements of RSS-Gen Clause 4.10, the spectrum analyser detector was set to peak and trace was kept on Max Hold to give the worst case. The limit line was displayed, showing the -57dBm, 2 nanowatts in band 9kHz to 1GHz and above 1GHz, -53dBm, 5 nanowatts.

The maximum path loss across the measurement band was used as the reference level offset to ensure worst case.

In addition, measurements were made from 9kHz up to the 5th harmonic of the highest internal frequency.

The test was performed with the EUT in the following configurations and modes of operation:

Configuration 1 - Mode 1
 - Mode 2
 - Mode 3

2.10.6 Environmental Conditions

	16 September 2011
Ambient Temperature	23.8°C
Relative Humidity	46.5%



Product Service


2.10.7 Test Results

For the period of test the EUT met the requirements of Industry Canada RSS-133 for Receiver Spurious Emissions.

The test results are shown below

Remark:

The emissions at 9kHz on the plots was not generated by the test object. A complementary measurement with a smaller Span showed that it was related to the LO feedthrough.



Date: 16.SEP.2011 14:02:48




Product Service

E-TM1.1


Configuration 1 - Mode 1

9kHz to 1GHz



Date: 16.SEP.2011 14:13:31

1GHz to 13GHz




Date: 16.SEP.2011 14:11:17



Product Service


Configuration 1 - Mode 2

9kHz to 1GHz



Date: 16.SEP.2011 14:14:39

1GHz to 13GHz




Date: 16.SEP.2011 14:06:09




Configuration 1 - Mode 3

9kHz to 1GHz



Date: 16.SEP.2011 14:30:04

1GHz to 13GHz



Date: 16.SEP.2011 14:27:43

Limit	-57dBm (30MHz-1GHz) and -53dBm (above 1GHz)
-------	---

Remarks

The EUT does not exceed -57dBm at the frequency range of 9kHz to 1GHz and does not exceed -53dBm at the frequency range of 1GHz to 13GHz.



Product Service

SECTION 3

TEST EQUIPMENT USED



3.1 TEST EQUIPMENT USED

List of absolute measuring and other principal items of test equipment.

Instrument	Manufacturer	Type No.	Serial No.	Calibration Period (months)	Calibration Due
Section 2.1, 2.2, 2.3, 2.4, 2.6, 2.7 and 2.10 – Maximum Conducted Output Power, Peak – Average Ratio, Modulation Characteristics, Occupied Bandwidth, Spurious Emissions at Antenna Terminals (± 1MHz) , Conducted Spurious Emissions and Receiver Spurious Emissions.					
Spectrum Analyser	Rohde & Schwarz	FSQ26	100253	12	27-Mar-2012
Spectrum Analyser	Rohde & Schwarz	FSQ26	201124	12	09-Jun-2012
Power Meter	Rohde & Schwarz	NRP2	101194	12	11-Aug-2012
Thermal Power Sensor	Rohde & Schwarz	NRP-Z51	20-318205	12	11-Jan-2012
Network Analyzer	Agilent	8720D	US36140166	12	08-Sep-2012
40dB Attenuator	SHX	DTS100G	11081901	-	O/P MON
High pass filter	Salisbury	ULK 904 240/n	23	-	O/P MON
Load	Shanghai Huaxiang	TF150	11081910	-	O/P MON
Power Supply	Agilent	N5768A	US11C3535G	12	11-May-2012
Digital Multi-meter	FLUKE	179	91820401	12	03-Jan-2012
Thermo-hygrometer	AZ Instruments	8705	9151655	12	16-Dec-2011
Section 2.5 – Radiated Spurious Emissions					
Load	Shanghai Huaxiang	TF150	11081910	-	O/P MON
Load	Shanghai Huaxiang	TF150	11081906	-	O/P MON
EMI Receiver	Rohde & Schwarz	ESI 40	100015	12	19-Aug-2012
Ultra log test antenna	Rohde & Schwarz	HL562	100167	12	19-Aug-2012
Double-Ridged Wave-guide Horn Antenna	Rohde & Schwarz	HF 906	100029	12	19-Aug-2012
Pyramidal Horn Antenna	EMCO	3160-09	-	-	-
Antenna master	Frankonia	MA 260	-	-	19-Aug-2012
Relay Switch Unit	Rohde & Schwarz	331.1601.31	338965002	-	TU
Semi Anechoic Chamber	Frankonia	23.18m×16.88m×9.60m	-	12	19-Aug-2012
Power Supply	Agilent	N5768A	US11C3537G	12	11-May-2012
Digital Multimeter	FLUKE	179	91820401	12	03-Jan-2012
Thermo-hygrometer	AZ Instruments	8705	9151655	12	16-Dec-2011
Section 2.8 and 2.9 – Frequency Stability Under Temperature and Voltage Variations					
Spectrum Analyser	Rohde & Schwarz	FSQ26	100253	12	27-Mar-2012
40dB Attenuator	SHX	DTS100G	11081901	-	O/P MON
Temperature Chamber	Zengda	ZTH100U	10080004	-	O/P MON
Power Supply	Agilent	N5768A	US11C3535G	12	11-May-2012
Digital Multimeter	FLUKE	179	91820401	12	03-Jan-2012
Thermo-hygrometer	AZ Instruments	8705	9151655	12	16-Dec-2011

O/P MON Output monitored with calibration equipment
 TU Traceability Unscheduled



Product Service

3.2 MEASUREMENT UNCERTAINTY

For a 95% confidence level, the measurement uncertainties for defined systems are:-

Test Discipline	Frequency / Parameter	MU
Conducted Maximum Peak Output Power	30MHz to 10GHz Amplitude	0.5dB*
Conducted Emissions	30MHz to 40GHz Amplitude	3.0dB*
Frequency Stability	30MHz to 2GHz Amplitude	<1x10 ⁻⁷
Radiated Emissions, Bilog Antenna, AOATS	30MHz to 1GHz Amplitude	5.1dB*
Radiated Emissions, Horn Antenna, AOATS	1GHz to 40GHz Amplitude	6.3dB*
Worst case error for both Time and Frequency measurement 12 parts in 10 ⁶		

* In accordance with CISPR 16-4



Product Service

SECTION 4

ACCREDITATION, DISCLAIMERS AND COPYRIGHT



Product Service

4.1 ACCREDITATION, DISCLAIMERS AND COPYRIGHT



This report relates only to the actual item/items tested.

Our UKAS Accreditation does not cover opinions and interpretations and any expressed are outside the scope of our UKAS Accreditation.

Results of tests not covered by our UKAS Accreditation Schedule are marked NUA (Not UKAS Accredited).

This report must not be reproduced, except in its entirety, without the written permission of TÜV SÜD Product Service Limited

© 2011 TÜV SÜD Product Service Limited