

# Ericsson AB

## RF TEST REPORT

**Report Type:**  
FCC Part 90 RF report

**PRODUCT NAME:**  
Radio 4499 44B26 44B71 C

**REPORT NUMBER:**  
221102038SHA-001

**ISSUE DATE:**  
December 5, 2022

**DOCUMENT CONTROL NUMBER:**  
TTRFFCC Part 90\_V1 © 2018 Intertek



**Applicant:** Ericsson AB  
Isafjordsgatan 10 SE-164 80 Stockholm 16480 Sweden

**Manufacturer:** Ericsson AB  
Isafjordsgatan 10 SE-164 80 Stockholm 16480 Sweden

**FCC ID:** TA8AKRC1610016-1

**IC:** 287AB-AS16100161

**SUMMARY:**

The equipment complies with the requirements according to the following standard(s) or Specification:

FCC CFR 47 Part 90: PRIVATE LAND MOBILE RADIO SERVICES

**PREPARED BY:**

**REVIEWED BY:**

---

Project Engineer  
Victor Yang

---

Reviewer  
Jackson Huang

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

**TEST REPORT**

## Content

<b>REVISION HISTORY</b> .....	<b>4</b>
<b>MEASUREMENT RESULT SUMMARY</b> .....	<b>5</b>
<b>1 GENERAL INFORMATION</b> .....	<b>6</b>
1.1 DESCRIPTION OF EQUIPMENT UNDER TEST (EUT) .....	6
1.2 TECHNICAL SPECIFICATION .....	7
1.3 DESCRIPTION OF TEST FACILITY .....	8
<b>2 TEST SPECIFICATIONS</b> .....	<b>9</b>
2.1 RELATED DOCUMENTS .....	9
2.2 PRODUCT INFORMATION.....	9
2.3 CONFIGURATION DESCRIPTION.....	10
2.4 TEST SETUP.....	13
2.5 TEST ENVIRONMENT CONDITION:.....	15
2.6 INSTRUMENT LIST .....	16
2.7 MEASUREMENT UNCERTAINTY .....	17
<b>3 MAXIMUM OUTPUT POWER AND PEAK TO AVERAGE POWER RATIO AND EIRP</b> .....	<b>18</b>
3.1 LIMIT .....	18
3.2 MEASUREMENT PROCEDURE .....	18
3.3 MEASUREMENT RESULT .....	19
<b>4 OCCUPIED BANDWIDTH</b> .....	<b>27</b>
4.1 MEASUREMENT PROCEDURE .....	27
4.2 MEASUREMENT RESULT .....	28
<b>5 UNWANTED EMISSIONS AT BAND EDGE</b> .....	<b>43</b>
5.1 LIMIT .....	43
5.2 MEASUREMENT PROCEDURE .....	43
5.3 MEASUREMENT RESULT .....	44
<b>6 CONDUCTED UNWANTED EMISSION</b> .....	<b>64</b>
6.1 LIMIT .....	64
6.2 MEASUREMENT PROCEDURE .....	64
6.3 MEASUREMENT RESULT .....	65
<b>7 RADIATED UNWANTED EMISSION</b> .....	<b>96</b>
7.1 LIMIT .....	96
7.2 MEASUREMENT PROCEDURE .....	96
7.3 MEASUREMENT RESULT .....	97
<b>8 FREQUENCY STABILITY</b> .....	<b>130</b>
8.1 LIMIT .....	130
8.2 MEASUREMENT PROCEDURE .....	130
8.3 MEASUREMENT RESULT .....	131

## Revision History

Report No.	Version	Description	Issued Date
221102038SHA-001	Rev. 01	Initial issue of report	December 5, 2022

## Measurement result summary

TEST ITEM	FCC REFERANCE	RESULT
Max Output Power and Peak to Average Power Ratio and EIRP	90.635, 2.1046	Pass
Occupied Bandwidth	2.1049	Pass
Unwanted Emissions at Band Edge	90.210, 2.1051	Pass
Conducted Unwanted Emission	90.210, 2.1051	Pass
Radiated Unwanted Emissions	90.210, 2.1051	Pass
Frequency Stability	90.213, 2.1055	Pass

## 1 GENERAL INFORMATION

### 1.1 Description of Equipment Under Test (EUT)

Description:	Remote Radio Unit
Product name:	Radio 4499 44B26 44B71 C
Product number:	KRC 161 0016/1
HVIN	AS16100161
Serial Number(s)	E2074Y0051
Rating:	-48V DC
Software Version:	PIS: CXP9017316%7_R91LA
Hardware Version:	R1B
Sample received date:	September 8, 2022
Date of test:	September 8, 2022 ~ November 18, 2022

## 1.2 Technical Specification

Frequency Range:	B26: RX: 814MHz-849MHz, TX: 859MHz-894MHz B71: RX: 663MHz-698MHz, TX: 617MHz-652MHz
Number of Antenna ports:	4 TX/RX
Supported RAT:	B26: SRO: WCDMA, LTE, NB-IoT(IB,GB,SA), NR MRO: WCDMA, GSM, LTE with NB-IoT (IB,GB,SA), NR with NB-IoT(IB) B71: SRO/MRO: NR, LTE, NB-IoT(IB,GB,SA), NR with NB-IoT(IB)
Supported other mode:	/
Max RF bandwidth (IBW):	B26: 35MHz B71: 35MHz Note: for narrow channel bandwidth carriers like GSM, NB-IoT standalone, LTE1.4MHz and 3MHz, the IBW is 20MHz.
Supported Number of Carriers:	12 carriers per port; 6 carriers per port per band
Supported modulation:	GSM: GMSK, 8PSK, AQPSK WCDMA: QPSK, 16QAM, 64QAM LTE, NR: QPSK, 16QAM, 64QAM, 256QAM NB-IoT: QPSK
Supported Channel Bandwidth:	B26: LTE: 1.4MHz, 3MHz, 5MHz, 10MHz,15MHz and 20MHz NR: 5MHz, 10MHz,15MHz and 20MHz with SCS 15KHz B71: LTE:5MHz, 10MHz, 15MHz, 20MHz NR: 5MHz,10MHz,15MHz,20MHz with SCS 15kHz
Declaration output power:	Maximum 80W(49dBm) per port. (Maximum 60W(47.8dBm) for B26 per port; Maximum 40W(46dBm) for B71 per port) Note: for narrow channel bandwidth carriers like GSM, LTE1.4MHz and 3MHz, max 20W(43dBm) per carrier; for NB-IoT standalone the max output power is 20W per port; for 5MHz channel bandwidth carriers like WCDMA, LTE, NR, max 40W (46dBm) per carrier.
Antenna Gain:	No dedicated antenna, handled during licensing

### 1.3 Description of Test Facility

Conducted testing:

Name:	Intertek Testing Services Shanghai
Address 1:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Address 2:	No. 5 Lize East Street, Ericsson Tower, Chaoyang District, Beijing 100102 P.R.C.
Telephone:	+86 21 61278200
Telefax:	+86 21 54262353
The test facility is recognized, certified, or accredited by these organizations:	FCC Accredited Lab Designation Number: CN0175, CN1258
	IC Registration Lab CAB identifier.: CN0014
	A2LA Accreditation Lab Certificate Number: 3309.02, 3309.04

Radiated testing:

Name:	BEIJING BOOMWAVE TEST SERVICE CO. LTD.
Address:	EMC Building, No. 1 Wang Jing East Road Chao Yang District, Beijing, 100102 P.R.C.
Telephone:	+86 10 64711866 806
The test facility is recognized, certified, or accredited by these organizations:	FCC Accredited Lab Designation Number: CN1242
	IC Registration Lab CAB identifier.: CN0010
	A2LA Accreditation Lab Certificate Number: 4992.01



## 2 TEST SPECIFICATIONS

### 2.1 Related documents

FCC Part 90 (2021)

FCC Part 2 (2021)

ANSI C63.26:2015

KDB 971168 D01 v03r01

KDB 662911 D01 v02r01

### 2.2 Product Information

The Equipment Under Test (EUT) is an Ericsson Remote Radio Unit working in the wireless communications services 600MHz & 800MHz band which provides communication connections to network in WCDMA / LTE / NB-IoT / NR /GSM modes and MSR modes. The Radio 4499 44B26 44B71 C operates from a -48V DC power supply.

The EUT includes 4 TX/RX ports and it can be configured to transmit in MIMO mode, and MIMO mode was used for measurements as the worst configuration. The complete testing was performed with the EUT transmitting at maximum RF power unless otherwise stated.

A full technical description can be found in the Manufacturer's documentation.

This report is for 859MHz-869MHz, other band is covered in another report (221102037SHA-001 & 221102039SHA-001).

**TEST REPORT**

**2.3 Configuration Description**

The following settings were used to representative for all traffic scenarios when settings with different modulations, channel bandwidths, number for carriers and RF configurations have been tested to find the worst-case setting. The settings below were used for all measurements unless otherwise noted:

**NR**

Configuration	Carrier	NR Carrier BW(MHz)	Carrier Frequency Configuration		
			Bottom	Middle	Top
NR-1C	1	5	861.5	864.0	866.5
		10	-	864.0	-
NR-2C	2	5	-	861.5+866.5	-

**LTE**

Configuration	Carrier	LTE Carrier BW(MHz)	Carrier Frequency Configuration		
			Bottom	Middle	Top
LTE-1C	1	1.4	859.7	864.0	868.3
		3	860.5	864.0	867.5
		5	861.5	864.0	866.5
		10	-	864.0	-
LTE-2C	2	1.4	-	859.7+868.3	-
		3	-	860.5+867.5	-
		5	-	861.5+866.5	-
LTE-6C	6	1.4	-	859.7+861.1+862.5+865.5+866.9+868.3	-

**NB-IoT GB**

Configuration	Carrier	GB Carrier BW(MHz)	Carrier Frequency Configuration		
			Bottom	Middle	Top
GB-1C	1	10	-	864.0	-

**NB-IoT IB**

Configuration	Carrier	IB Carrier BW(MHz)	Carrier Frequency Configuration		
			Bottom	Middle	Top
IB-1C	1	5	861.5	864.0	866.5
		10	-	864.0	-

**NB-IoT SA**

Configuration	Carrier	SA Carrier BW(MHz)	Carrier Frequency Configuration		
			Bottom	Middle	Top
SA-1C	1	0.2	859.2	864.0	868.8
SA-2C	2	0.2	-	859.2+868.8	-