



Product Service

**Choose certainty.
Add value.**

Report On

FCC and Industry Canada Testing of the
Ericsson RRUS 11 B4 / KRC 161 254/1

COMMERCIAL-IN-CONFIDENCE

FCC ID: TA8AKRC161254-1

IC ID: 287AB-AS1612541

Document 75914706 Report 01 Issue 1

August 2011



Product Service

TÜV SÜD Product Service Ltd, Octagon House, Concorde Way, Segensworth North,
Fareham, Hampshire, United Kingdom, PO15 5RL
Tel: +44 (0) 1489 558100. Website: www.tuvps.co.uk

COMMERCIAL-IN-CONFIDENCE

REPORT ON

FCC and Industry Canada Testing of the
Ericsson RRUS 11 B4 / KRC 161 254/1

Document 75914706 Report 01 Issue 1

August 2011

PREPARED FOR

Ericsson AB
Torshamnsgatan 23
SE-164 80
Stockholm
Sweden

PREPARED BY

X Zhang
Test Engineer

APPROVED BY

M J Hardy
Authorised Signatory

DATED

31 August 2011

ENGINEERING STATEMENT

The measurements shown in this report were made in accordance with the procedures described on test pages. All reported testing was carried out on a sample equipment to demonstrate compliance with FCC CFR 47: Part 27 and Industry Canada RSS-139. The sample tested was found to comply with the requirements defined in the applied rules.

Test Engineer(s);

X Zhang

C Zhang





CONTENTS

Section	Page No
1	REPORT SUMMARY 3
1.1	Introduction 4
1.2	Brief Summary of Results 5
1.3	Declaration of Build Status 7
1.4	Product Information 8
1.5	Test Conditions 13
1.6	Deviations From the Standard 13
1.7	Modification Record 13
1.8	Alternative Test Site 13
2	TEST DETAILS 14
2.1	Maximum Peak Output Power - Conducted 15
2.2	Peak – Average Ratio 18
2.3	Modulation Characteristics 27
2.4	Occupied Bandwidth 30
2.5	Spurious Emissions at Antenna Terminals (± 1 MHz) 37
2.6	Radiated Spurious Emissions 52
2.7	Conducted Spurious Emissions 57
2.8	Frequency Stability Under Temperature Variations 65
2.9	Frequency Stability Under Voltage Variations 67
2.10	Receiver Spurious Emissions 69
3	TEST EQUIPMENT USED 77
3.1	Test Equipment Used 78
3.2	Measurement Uncertainty 80
4	ACCREDITATION, DISCLAIMERS AND COPYRIGHT 81
4.1	Accreditation, Disclaimers and Copyright 82



SECTION 1

REPORT SUMMARY

FCC and Industry Canada Testing of the
Ericsson RRUS 11 B4 / KRC 161 254/1



1.1 INTRODUCTION

The information contained in this report is intended to show verification of the Ericsson RRUS 11 B4 / KRC 161 254/1 to the requirements of FCC CFR 47 Part 27 and Industry Canada RSS-139.

Testing was carried out in support of a C2PC application for Grant of RRUS 11 B4 / KRC 161 254/1 for the hardware update.

Objective	To perform FCC and Industry Canada Testing to determine the Equipment Under Test's (EUT's) compliance with the Test Specification, for the series of tests carried out.
Manufacturer	Ericsson AB
Product Name	RRUS 11 B4
Part Number	KRC 161 254/1
IC Model Number	AS1612541
Serial Number(s)	CB4J379552
Software Version	CXP9017316%1_R32LY
Hardware Version	R2C
Number of Samples Tested	1
Test Specification/Issue/Date	FCC CFR 47 Part 27: 2010 Industry Canada RSS-139 Issue 2: 2009
Incoming Release Date	Declaration of Build Status 18 July 2011
Order Number Date	PTP 15 July 2011
Start of Test	18 July 2011
Finish of Test	5 August 2011
Name of Engineer(s)	X Zhang C Zhang
Related Document(s)	ANSI C63.4: 2009 FCC CFR 47 Part 2: 2010 Industry Canada RSS-GEN Issue 3: 2010 3GPP TS 36.141 V9.5.0



1.2 BRIEF SUMMARY OF RESULTS

A brief summary of results in accordance with FCC CFR 47 Part 27 and Industry Canada RSS-139, is shown below.

Configuration 1 – Radio Equipment							
Section	Spec Clause		Test Description	Mode	Mod State	Result	Comments
	FCC Part 2 and 27	RSS-139 and RSS-GEN					
	27.50 (d)	6.4	Effective Radiated Power	2110.7MHz (1.4MHz OBW) / 2120.0MHz (20.0MHz OBW)		N/A	No integral antenna.
				2132.5MHz (1.4MHz, 3.0MHz, 5.0MHz, 10.0MHz, 15.0MHz, 20.0MHz OBW)		N/A	
				2154.3MHz (1.4MHz OBW) / 884.0MHz (20.0MHz OBW)		N/A	
2.1	2.1046, 27.50 (d)	6.4	Maximum Peak Output Power - Conducted	2110.7MHz (1.4MHz OBW) / 2120.0MHz (20.0MHz OBW)	0	Pass	-
				2132.5MHz (1.4MHz, 3.0MHz, 5.0MHz, 10.0MHz, 15.0MHz, 20.0MHz OBW)	0	Pass	
				2154.3MHz (1.4MHz OBW) / 2145.0MHz (20.0MHz OBW)	0	Pass	
2.2	27.50 (i)	-	Peak – Average Ratio	2110.7MHz (1.4MHz OBW) / 2120.0MHz (20.0MHz OBW)	0	Pass	-
				2132.5MHz (1.4MHz, 3.0MHz, 5.0MHz, 10.0MHz, 15.0MHz, 20.0MHz OBW)	0	Pass	
				2154.3MHz (1.4MHz OBW) / 2145.0MHz (20.0MHz OBW)	0	Pass	
2.3	2.1047 (d)	6.2	Modulation Characteristics	2112.5MHz (5.0MHz OBW)		N/A	-
				2132.5MHz (5.0MHz OBW)	0	Pass	
				2152.5MHz (5.0MHz OBW)		N/A	
2.4	2.1049, 27.53 (h)	RSS-Gen 4.6.1	Occupied Bandwidth	2110.7MHz (1.4MHz OBW) / 2120.0MHz (20.0MHz OBW)	0	Pass	-
				2132.5MHz (1.4MHz, 3.0MHz, 5.0MHz, 10.0MHz, 15.0MHz, 20.0MHz OBW)	0	Pass	
				2154.3MHz (1.4MHz OBW) / 2145.0MHz (20.0MHz OBW)	0	Pass	



Configuration 1 – Radio Equipment							
Section	Spec Clause		Test Description	Mode	Mod State	Result	Comments
	FCC Part 2 and 27	RSS-139 and RSS-GEN					
2.5	2.1051, 27.53 (h)	6.5	Spurious Emissions at Antenna Terminals (±1MHz)	2110.7MHz (1.4MHz OBW) / 2111.5MHz (3.0MHz OBW) 2112.5MHz (5.0MHz OBW) / 2115.0MHz (10.0MHz OBW) 2117.5MHz (15.0MHz OBW) / 2120.0MHz (20.0MHz OBW)	0	Pass	-
				2132.5MHz		N/A	
				2154.3MHz (1.4MHz OBW) / 2153.5MHz (3.0MHz OBW) 2152.5MHz (5.0MHz OBW) / 2150.0MHz (10.0MHz OBW) 2147.5MHz (15.0MHz OBW) / 2145.0MHz (20.0MHz OBW)	0	Pass	
2.6	2.1053, 27.53 (h)	6.5	Radiated Spurious Emissions	2110.7MHz (1.4MHz OBW)	0	Pass	-
				2132.5MHz (1.4MHz, 3.0MHz, 5.0MHz, 10.0MHz, 15MHz, 20.0MHz OBW)	0	Pass	
				2154.3MHz (1.4MHz OBW)	0	Pass	
2.7	2.1051, 27.53 (h)	6.5	Conducted Spurious Emissions	2110.7MHz (1.4MHz OBW) / 2120.0MHz (20.0MHz OBW)	0	Pass	-
				2132.5MHz (1.4MHz, 20.0MHz OBW)	0	Pass	
				2154.3MHz (1.4MHz OBW) / 2145.0MHz (20.0MHz OBW)	0	Pass	
2.8	2.1055, 27.54	6.3	Frequency Stability Under Temperature Variations	2112.5MHz (5.0MHz OBW)		N/A	-
				2132.5MHz (5.0MHz OBW)	0	Pass	
				2152.5MHz (5.0MHz OBW)		N/A	
2.9	2.1055, 27.54	6.3	Frequency Stability Under Voltage Variations	2112.5MHz (5.0MHz OBW)		N/A	-
				2132.5MHz (5.0MHz OBW)	0	Pass	
				2152.5MHz (5.0MHz OBW)		N/A	
2.10	-	6.6	Receiver Spurious Emissions	2110.7MHz (1.4MHz OBW) / 2120.0MHz (20.0MHz OBW)	0	Pass	-
				2132.5MHz (1.4MHz, 20.0MHz OBW)	0	Pass	
				2154.3MHz (1.4MHz OBW) / 2145.0MHz (20.0MHz OBW)	0	Pass	

N/A – Not Applicable



1.3 DECLARATION OF BUILD STATUS

MAIN EUT	
MANUFACTURING DESCRIPTION	Radio Equipment
MANUFACTURER	Ericsson AB
PRODUCT NAME	RRUS 11 B4
PART NUMBER	KRC 161 254/1
IC Model Number	AS1612541
SERIAL NUMBER	CB4J379552
HARDWARE VERSION	R2C
SOFTWARE VERSION	CXP9017316%1_R32LY
TRANSMITTER OPERATING RANGE	TX: 2110MHz - 2155MHz RX: 1710MHz - 1755MHz
DUPLEXER MODE	FDD
MODULATIONS	QPSK, 16QAM, 64QAM
INTERMEDIATE FREQUENCIES	--
ITU DESIGNATION OF EMISSION	1M40F9W 3M00F9W 5M00F9W 10M0F9W 15M0F9W 20M0F9W
SUPPORTED CHANNEL BANDWIDTH CONFIGURATION	1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz and 20MHz according to 3GPP TS 36.141
OUTPUT POWER (RMS) (W or dBm)	2 x 44.8dBm (2 x 30W)
NUMBER OF ANTENNA PORTS	2 TX/RX ports
SUPPORTED CONFIGURATION	Dual Single Carrier. Both RF chains are identical
FCC ID	TA8AKRC161254-1
IC ID	287AB-AS1612541
TECHNICAL DESCRIPTION (a brief description of the intended use and operation)	The equipment is the Radio Part of LTE Base Station.

Signature

Date

8 August 2011

D of B S Serial No

75914706/01

No responsibility will be accepted by TÜV SÜD Product Service as to the accuracy of the information declared in this document by the manufacturer.




1.4 PRODUCT INFORMATION

1.4.1 Technical Description

The Equipment Under Test (EUT) RRUS 11 B4 / KRC 161 254/1 is an Ericsson Radio Equipment working in the public mobile service 2100MHz band which operates in LTE mode. The RRUS 11 B4 / KRC 161 254/1 operates from a -48V DC supply.

The Equipment Under Test (EUT) is shown in the photograph below. A full technical description can be found in the Manufacturers documentation.



Equipment Under Test



Product Service

1.4.2 Test Configuration

Configuration 1: Radio Equipment

The EUT was configured in accordance with FCC CFR 47 Part 27 and Industry Canada RSS-139.

The RRUS 11 B4 / KRC 161 254/1 supports Test Models E-TM1.1, E-TM3.2 and E-TM3.1 at 2100MHz defined in 3GPP TS 36.141. Test Model E-TM1.1 was used to represent QPSK modulation only, Test Model E-TM3.2 was used to represent 16QAM modulation, and Test Model E-TM3.1 was used to represent 64QAM modulation.

The settings below were found to be representative for all traffic scenarios when several settings with the different modulations, channel bandwidths were tested to find the worst case setting. These settings were used for all measurements if not otherwise noted:

- Test Model E-TM1.1 in channel bandwidth 1.4MHz and 20MHz.


The EUT has two TX/RX ports and it can be configured to transmit in 2100MHz with both TX are active. All TX measurements were performed on the combined TX/RX output connector RF A. Limited complementary TX measurements were done at connector RF B to verify identical performance for both transmitter chains. RX testing was performed on the RX connector RF B of the EUT when the EUT was set as single Transmitter.

The complete testing was performed with the EUT transmitting at maximum RF power unless otherwise stated.

The EUT was powered by a -48V DC Power supply.



Test Setup, Conducted Measurement:




Test Object	Part Number	Version	Serial Number
Radio Part	RRUS 11 B4 / KRC 161 254/1	R2C	CB4J379552

No.	Auxiliary Equipment	Part Number / Model Type	Version	Serial Number
1	Computer	HP Compaq nc4400	--	CND6460KCL
2	RBS 6601	BFL 901 009/1	--	--
	DUL 2001	KDU 137 533/4	R1C	CB4H365206
	SUP 6601	1/BFL 901 009/1	R3B	BR81237540
3	Switch	TEH1085K	--	S108SK014848011011
4	Attenuator	48-40-43-LIM	--	BR5020
5	Load	TF100	--	09121614
6	Power Supply	DH1716-5D	--	200360033
		DH1716A-14	--	20080401
7	Power Metre	Rohde & Schwarz NRP	--	102624
	Thermal Power Sensor	Rohde & Schwarz NRP-Z51	--	102168
	Spectrum Analyzer	FSQ26	--	20-332960



Test Setup, Radiated Measurement:



Test Object	Part Number	Version	Serial Number
Radio Part	RRUS 11 B4 / KRC 161 254/1	R2C	C824523599

No.	Auxiliary Equipment	Part Number / Model Type	Version	Serial Number
1	Computer	HP Compaq nc4400	--	CND6460KCL
2	RBS 6601	BFL 901 009/1	--	--
	DUL 2001	KDU 137 533/4	R1C	CB4H365206
	SUP 6601	1/BFL 901 009/1	R3B	BR81237540
3	Switch	TEH1085K	--	S108SK014848011011
4	Power Supply	DH1716-5D	--	200360033
		DH1716A-14	--	20080401
5	Load	TF150-3	--	090323433
	Load	TF100	--	09121603



1.4.3 Modes of Operation

Modes of operation of each EUT during testing were as follows:

Bottom Channel :

Mode 1 - 1.4 : EARFCN 1957: 2110.7MHz (1.4MHz Bandwidth)

Mode 1 - 3 : EARFCN 1965: 2111.5MHz (3.0MHz Bandwidth)

Mode 1 - 5 : EARFCN 1975: 2112.5MHz (5.0MHz Bandwidth)

Mode 1 - 10 : EARFCN 2000: 2115.0MHz (10.0MHz Bandwidth)

Mode 1 - 15 : EARFCN 2025: 2117.5MHz (15.0MHz Bandwidth)

Mode 1 - 20 : EARFCN 2050: 2120.0MHz (20.0MHz Bandwidth)

Middle Channel :

Mode 2 : EARFCN 2175: 2132.5MHz

Top Channel :

Mode 3 - 1.4 : EARFCN 2393: 2154.3MHz (1.4MHz Bandwidth)

Mode 3 - 3 : EARFCN 2385: 2153.5MHz (3.0MHz Bandwidth)

Mode 3 - 5 : EARFCN 2375: 2152.5MHz (5.0MHz Bandwidth)

Mode 3 - 10 : EARFCN 2350: 2150.0MHz (10.0MHz Bandwidth)

Mode 3 - 15 : EARFCN 2325: 2147.5MHz (15.0MHz Bandwidth)

Mode 3 - 20 : EARFCN 2300: 2145.0MHz (20.0MHz Bandwidth)

Information on the specific test modes utilised are detailed in the test procedure for each individual test.



Product Service

1.5 TEST CONDITIONS

For all tests the EUT was set up in accordance with the relevant test standard and to represent typical operating conditions. Tests were applied with the EUT situated in a shielded enclosure, test laboratories or an open test area as appropriate.

The EUT was powered from a -48V DC supply.

1.6 DEVIATIONS FROM THE STANDARD

No deviations from the applicable test standards or test plan were made during testing.

1.7 MODIFICATION RECORD

No modifications were made to the EUT during testing.

1.8 ALTERNATIVE TEST SITE

Testing has been performed under the following site registrations:

FCC Accreditation 910917:

The State Radio Monitoring Centre, No.80 Beilishi Road Xicheng District Beijing, China.

Industry Canada Accreditation 7308A:

The State Radio Monitoring Centre, No.80 Beilishi Road Xicheng District Beijing, China.



Product Service

SECTION 2

TEST DETAILS

FCC and Industry Canada Testing of the
Ericsson RRUS 11 B4 / KRC 161 254/1



Product Service

2.1 MAXIMUM PEAK OUTPUT POWER - CONDUCTED

2.1.1 Specification Reference

FCC CFR 47 Part 2.1046
FCC CFR 47 Part 27, Clause 27.50 (d)
Industry Canada RSS-139, Clause 6.4

2.1.2 Equipment Under Test

RRUS 11 B4 / KRC 161 254/1, S/N: CB4J379552

2.1.3 Date of Test and Modification State

18 July 2011 – Modification State 0

2.1.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.1.5 Test Method and Operating Modes

The test was applied in accordance with the test method requirements of FCC CFR 47 Part 2 and Part 27 and Industry Canada RSS-139.

Using a power meter and attenuator(s), the output power of the EUT was measured at the antenna terminal. The carrier power was measured with E-TM1.1, E-TM3.2 and E-TM3.1 test models.

The path loss was measured and entered as a reference level offset.

The test was performed with the EUT in the following configurations and modes of operation:

Configuration 1 - Mode 1 - 1.4, Mode 1 - 20
- Mode 2 (1.4MHz, 3.0MHz, 5.0MHz, 10.0MHz, 15.0MHz, 20MHz OBW)
- Mode 3 - 1.4, Mode 3 - 20

2.1.6 Environmental Conditions

18 July 2011
Ambient Temperature 25.0°C
Relative Humidity 66.5%



2.1.7 Test Results

For the period of test the EUT met the requirements of FCC CFR 47 Part 2 and Part 27 and Industry Canada RSS-139 for Maximum Peak Output Power.

The test results are shown below

E-TM1.1: 1.4MHz Bandwidth

Configuration 1 - Mode 1 - 1.4, Mode 2 and Mode 3 - 1.4

UARFCN	Frequency (MHz)	Path Loss (dB)	Result (dBm) RMS	Result (W) RMS
1957 (Bottom)	2110.7	44.5	44.66	29.24
2175 (Middle)	2132.5	44.5	44.71	29.58
2393 (Top)	2154.3	44.5	44.62	28.97

E-TM1.1: 20.0MHz Bandwidth

Configuration 1 - Mode 1 - 20, Mode 2 and Mode 3 - 20

UARFCN	Frequency (MHz)	Path Loss (dB)	Result (dBm) RMS	Result (W) RMS
2050 (Bottom)	2120.0	44.5	44.50	28.18
2175 (Middle)	2132.5	44.5	44.56	28.58
2300 (Top)	2145.0	44.5	44.48	28.05

E-TM1.1: 3.0MHz, 5.0MHz, 10.0MHz and 15.0MHz Bandwidth

Configuration 1 - Mode 2

UARFCN	Frequency (MHz)	BW Configuration (MHz)	Path Loss (dB)	Result (dBm) RMS	Result (W) RMS
2175 (Middle)	2132.5	3.0	44.5	44.61	28.91
		5.0	44.5	44.62	28.97
		10.0	44.5	44.61	28.91
		15.0	44.5	44.49	28.12



Product Service

E-TM3.2 and E-TM3.1: 1.4MHz Bandwidth

Configuration 1 - Mode 2

UARFCN	Frequency (MHz)	Test Model	Path Loss (dB)	Result (dBm) RMS	Result (W) RMS
2175 (Middle)	2132.5	E-TM3.2	44.5	44.68	29.38
		E-TM3.1	44.5	44.67	29.31

E-TM3.2 and E-TM3.1: 20.0MHz Bandwidth

Configuration 1 - Mode 2

UARFCN	Frequency (MHz)	Test Model	Path Loss (dB)	Result (dBm) RMS	Result (W) RMS
2175 (Middle)	2132.5	E-TM3.2	44.5	44.52	28.31
		E-TM3.1	44.5	44.52	28.31

Limit	$\leq 1640\text{W/MHz}$ or $\leq +62.1\text{dBm/MHz}$
-------	---

Remarks

The EUT does not exceed 1640W/MHz or 62.1dBm/MHz at the measured frequencies.



Product Service

2.2 PEAK – AVERAGE RATIO

2.2.1 Specification Reference

FCC CFR 47 Part 27, Clause 27.50 (i)

2.2.2 Equipment Under Test

RRUS 11 B4 / KRC 161 254/1, S/N: CB4J379552

2.2.3 Date of Test and Modification State

18 July 2011 – Modification State 0

2.2.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.2.5 Test Method and Operating Modes

The test was applied in accordance with the test method requirements of FCC CFR 47 Part 27.

A peak to average ratio measurement is performed at the conducted port of the EUT. The spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

The path loss measured and entered as a reference level offset.

The test was performed with the EUT in the following configurations and modes of operation:

Configuration 1 - Mode 1 - 1.4, Mode 1 - 20
- Mode 2 (1.4MHz, 3.0MHz, 5.0MHz, 10.0MHz, 15.0MHz, 20MHz OBW)
- Mode 3 - 1.4, Mode 3 - 20

2.2.6 Environmental Conditions

18 July 2011

Ambient Temperature 25.0°C

Relative Humidity 66.5%



Product Service

2.2.7 Test Results


For the period of test the EUT met the requirements of FCC CFR 47 Part 27 Peak – Average Ratio.

The test results are shown below.

E-TM1.1

Configuration 1 - Mode 1 - 1.4

1.4MHz Bandwidth



Complementary Cumulative Distribution Function
NOF samples: 100000, Usable BW: 1.7MHz

Trace 1	
Mean	44.40 dBm
Peak	51.10 dBm
Crest	6.71 dB
10 %	3.69 dB
1 %	6.22 dB
.1 %	6.57 dB
.01 %	6.67 dB


Date: 18.JUL.2011 05:35:22



Product Service

Configuration 1 - Mode 1 - 20


20.0MHz Bandwidth



Date: 18.JUL.2011 08:00:01

Configuration 1 - Mode 2


1.4MHz Bandwidth



Date: 18.JUL.2011 05:41:08




3.0MHz Bandwidth



Date: 18.JUL.2011 08:24:01


5.0MHz Bandwidth



Date: 18.JUL.2011 08:27:03




10.0MHz Bandwidth



Date: 18.JUL.2011 08:37:10


15.0MHz Bandwidth



Date: 18.JUL.2011 08:39:43




20.0MHz Bandwidth



Date: 18.JUL.2011 08:48:06

Configuration 1 - Mode 3 - 1.4

1.4MHz Bandwidth




Date: 18.JUL.2011 05:43:45



Product Service

Configuration 1 - Mode 3 - 20

20.0MHz Bandwidth



Complementary Cumulative Distribution Function
 NOF samples: 100000, Usable BW: 23.7MHz


Trace 1	
Mean	44.70 dBm
Peak	51.54 dBm
Crest	6.84 dB
10 %	3.72 dB
1 %	6.25 dB
.1 %	6.63 dB
.01 %	6.79 dB

Date: 18.JUL.2011 08:04:44

E-TM3.2

Configuration 1 - Mode 2

1.4MHz Bandwidth




Complementary Cumulative Distribution Function
 NOF samples: 100000, Usable BW: 1.7MHz

Trace 1	
Mean	44.43 dBm
Peak	51.17 dBm
Crest	6.74 dB
10 %	3.69 dB
1 %	6.31 dB
.1 %	6.60 dB
.01 %	6.73 dB

Date: 18.JUL.2011 08:52:51



20.0MHz Bandwidth




Date: 18.JUL.2011 06:15:21

E-TM3.1

Configuration 1 - Mode 2

1.4MHz Bandwidth




Date: 18.JUL.2011 08:57:39



Product Service

20.0MHz Bandwidth



Date: 18.JUL.2011 07:37:41

Limit	13dB
-------	------

Remarks

The Peak – Average ratio does not exceed 13dB at the measured frequencies.



Product Service

2.3 MODULATION CHARACTERISTICS

2.3.1 Specification Reference

FCC CFR 47 Part 2, Clause 2.1047 (d)
Industry Canada RSS-139 Clause 6.2

2.3.2 Equipment Under Test

RRUS 11 B4 / KRC 161 254/1, S/N: CB4J379552

2.3.3 Date of Test and Modification State

19 July 2011 – Modification State 0

2.3.4 Test Method and Operating Modes

The test was applied in accordance with the test method requirements of FCC CFR 47 Part 2 and Industry Canada RSS-139.

Connect the RF output connector RF A to a spectrum analyzer with an attenuator. The other connector was connected to match load. The EUT was controlled to transmit maximum power. Measure and record the constellation of the EUT by the spectrum analyzer.

The EUT supports QPSK, 16QAM and 64QAM modulations and was tested in 5MHz Bandwidth.

The test was performed with the EUT in the following configurations and modes of operation:

Configuration 1 - Mode 2 (5.0MHz OBW)

2.3.5 Environmental Conditions

	19 July 2011
Ambient Temperature	25.9°C
Relative Humidity	51.8%



2.3.6 Test Results


Plots are shown on the following showing the EUT transmitting with all of the modulations:

The test results are shown below

Configuration 1 - Mode 2


5.0MHz Bandwidth

E-TM1.1: EUT transmitting with QPSK modulation in:






E-TM3.2: EUT transmitting with 16QAM modulation:



Running ...
Date: 19.JUL.2011 07:58:42

E-TM3.1: EUT transmitting with 64QAM modulation:



Running ...
Date: 19.JUL.2011 08:03:40



Product Service

2.4 OCCUPIED BANDWIDTH

2.4.1 Specification Reference

FCC CFR 47 Part 2, Clause 2.1049
 FCC CFR 47 Part 27, Clause 27.53 (h)
 Industry Canada RSS-GEN, Clause 4.6.1

2.4.2 Equipment Under Test

RRUS 11 B4 / KRC 161 254/1, S/N: CB4J379552

2.4.3 Date of Test and Modification State

19, 20 and 28 July 2011 – Modification State 0

2.4.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.4.5 Test Method and Operating Modes

The test was applied in accordance with the test method requirements of FCC CFR 47 Part 2 and Part 27 and Industry Canada RSS-GEN.

The EUT was transmitting at maximum power, modulated using the test model described. The EUT was tested in the 6 supported bandwidths. At least 1% of the emission bandwidths were used for the resolution and video bandwidths.

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission.

The test was performed with the EUT in the following configurations and modes of operation:

Configuration 1 - Mode 1 - 1.4, Mode 1 - 20
 - Mode 2 (1.4MHz, 3.0MHz, 5.0MHz, 10.0MHz, 15.0MHz, 20MHz OBW)
 - Mode 3 - 1.4, Mode 3 - 20

2.4.6 Environmental Conditions

	19 July 2011	20 July 2011	28 July 2011
Ambient Temperature	27.0°C	25.0°C	23.7°C
Relative Humidity	60.0%	61.0%	62.0%



Product Service

2.4.7 Test Results

For the period of test the EUT met the requirements of FCC CFR 47 Part 2 and Part 27 and Industry Canada RSS-GEN for Occupied Bandwidth.

The test results are shown below


Test Model	BW configuration (MHz)	Frequency (MHz) / Channel	Occupied Bandwidth (MHz)
E-TM1.1	1.4	2110.7 (Bottom)	1.09
	20.0	2120.0 (Bottom)	17.95
	1.4	2132.5 (Middle)	1.09
	3.0	2132.5 (Middle)	2.71
	5.0	2132.5 (Middle)	4.47
	10.0	2132.5 (Middle)	8.97
	15.0	2132.5 (Middle)	13.46
	20.0	2132.5 (Middle)	17.95
	1.4	2154.3 (Top)	1.09
	20.0	2145.0 (Top)	17.95



E-TM1.1

Configuration 1 - Mode 1 - 1.4


1.4MHz Bandwidth



Date: 19.JUL.2011 11:06:18

Configuration 1 - Mode 1 - 20

20.0MHz Bandwidth




Date: 20.JUL.2011 03:48:38




Configuration 1 - Mode 2

1.4MHz Bandwidth



Date: 19.JUL.2011 08:13:36


3.0MHz Bandwidth



Date: 19.JUL.2011 08:29:49




5.0MHz Bandwidth



Date: 19.JUL.2011 08:07:14


10.0MHz Bandwidth



Date: 19.JUL.2011 09:04:18




15.0MHz Bandwidth



Date: 19.JUL.2011 09:12:03

20.0MHz Bandwidth




Date: 19.JUL.2011 09:26:34



Configuration 1 - Mode 3 - 1.4


1.4MHz Bandwidth



Date: 28.JUL.2011 09:05:25

Configuration 1 - Mode 3 - 20

20.0MHz Band



Date: 20.JUL.2011 04:10:35



Product Service

2.5 SPURIOUS EMISSIONS AT ANTENNA TERMINALS (± 1 MHz)

2.5.1 Specification Reference

FCC CFR 47 Part 2, Clause 2.1051
 FCC CFR 47 Part 27, Clause 27.53 (h)
 Industry Canada RSS-139 Clause 6.5

2.5.2 Equipment Under Test

RRUS 11 B4 / KRC 161 254/1, S/N: CB4J379552

2.5.3 Date of Test and Modification State

20 and 28 July 2011 – Modification State 0

2.5.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.5.5 Test Method and Operating Modes

The test was applied in accordance with the test method requirements of FCC CFR 47 Part 2 and Part 27 and Industry Canada RSS-139.

In accordance with 27.53(h)(1), at least 1% of the emission bandwidth was used for the resolution and video bandwidths up to 1MHz away from the block edge. A resolution bandwidth of 50kHz was used between 1MHz to 5MHz away from the band edge. As the FCC rules specify a RBW of 1MHz for measurements of emissions > 1MHz away from the band edges, the limit was adjusted with -13dB to -26dBm to compensate for the reduced measurement bandwidth. Spectrum analyser detector was set as RMS.

The path loss measured and entered as a reference level offset.

The EUT was tested at its maximum power level.

The test was performed with the EUT in the following configurations and modes of operation:

Configuration 1 - Mode 1 - 1.4, Mode 1 - 3, Mode 1 - 5,
 Mode 1 - 10, Mode 1 - 15, Mode 1 - 20
 - Mode 3 - 1.4, Mode 3 - 3, Mode 3 - 5,
 Mode 3 - 10, Mode 3 - 15, Mode 3 - 20

2.5.6 Environmental Conditions

	20 July 2011	28 July 2011
Ambient Temperature	25.0°C	23.7°C
Relative Humidity	61.0%	62.0%



2.5.7 Test Results

For the period of test the EUT met the requirements of FCC CFR 47 Part 2 and Part 27 and Industry Canada RSS-139 for Spurious Emissions Antenna Terminals (± 1 MHz)

Below are the Frequencies the EUT was tested against along with the tested channels.

ETM1.1:

1.4MHz Bandwidth

Configuration 1 - Mode 1 -1.4 and Mode 3 - 1.4

Band Edge Frequency	Edge Test with 1.4MHz Bandwidth Channel No./Frequencies	RBW / VBW (Hz)
Bottom 2110 MHz	Channel: 1957 Frequency: 2110.7 MHz	20k / 200k
Top 2155MHz	Channel: 2393 Frequency: 2154.3 MHz	

3.0MHz Bandwidth

Configuration 1 - Mode 1 - 3 and Mode 3 - 3

Band Edge Frequency	Edge Test with 3.0MHz Bandwidth Channel No./Frequencies	RBW / VBW (Hz)
Bottom 2110 MHz	Channel: 1965 Frequency: 2111.5 MHz	30k / 300k
Top 2155MHz	Channel: 2385 Frequency: 2153.5MHz	

5.0MHz Bandwidth

Configuration 1 - Mode 1 - 5 and Mode 3 - 5

Band Edge Frequency	Edge Test with 5.0MHz Bandwidth Channel No./Frequencies	RBW / VBW (Hz)
Bottom 2110 MHz	Channel: 1975 Frequency: 2112.5 MHz	50k / 500k
Top 2155MHz	Channel: 2375 Frequency: 2152.5 MHz	



10.0MHz Bandwidth

Configuration 1 - Mode 1 - 10 and Mode 3 - 10

Band Edge Frequency	Edge Test with 10.0MHz Bandwidth Channel No./Frequencies	RBW / VBW (Hz)
Bottom 2110 MHz	Channel: 2000 Frequency: 2115.0 MHz	100k / 1M
Top 2155MHz	Channel: 2350 Frequency: 2150.0 MHz	

15.0MHz Bandwidth

Configuration 1 - Mode 1 - 15 and Mode 3 - 15

Band Edge Frequency	Edge Test with 15.0MHz Bandwidth Channel No./Frequencies	RBW / VBW (Hz)
Bottom 2110 MHz	Channel: 2025 Frequency: 2117.5 MHz	200k / 2M
Top 2155MHz	Channel: 2325 Frequency: 2147.5 MHz	

20.0MHz Bandwidth

Configuration 1 - Mode 1 - 20 and Mode 3 - 20

Band Edge Frequency	Edge Test with 20.0MHz Bandwidth Channel No./Frequencies	RBW / VBW (Hz)
Bottom 2110 MHz	Channel: 2050 Frequency: 2120.0 MHz	200k / 2M
Top 2155MHz	Channel: 2300 Frequency: 2145.0 MHz	

The channels shown in the table above are the minimum and maximum channels that can be used in the authorised frequency ranges to maintain compliance.




The test results are shown below


E-TM1.1

1.4MHz Bandwidth

Configuration 1 - Mode 1 - 1.4




Date: 20.JUL.2011 04:17:59




Date: 20.JUL.2011 04:20:21



Configuration 1 - Mode 3 - 1.4



Date: 20.JUL.2011 04:28:45




Date: 28.JUL.2011 09:07:44




Product Service

3.0MHz Bandwidth

Configuration 1 - Mode 1 - 3




Date: 20.JUL.2011 05:30:22




Date: 20.JUL.2011 05:23:44



Configuration 1 - Mode 3 - 3



Date: 20.JUL.2011 09:31:16




Date: 20.JUL.2011 09:33:24




5.0MHz Bandwidth

Configuration 1 - Mode 1 - 5




Date: 20.JUL.2011 05:35:54




Date: 20.JUL.2011 05:37:19



Configuration 1 - Mode 3 - 5



Date: 20.JUL.2011 06:01:30




Date: 20.JUL.2011 05:57:52




10.0MHz Bandwidth

Configuration 1 - Mode 1 - 10




Date: 20.JUL.2011 06:17:16




Date: 20.JUL.2011 06:19:34



Configuration 1 - Mode 3 - 10



Date: 20.JUL.2011 07:20:21




Date: 20.JUL.2011 07:17:32




15.0MHz Bandwidth

Configuration 1 - Mode 1 - 15




Date: 20.JUL.2011 07:37:52




Date: 20.JUL.2011 07:36:03



Configuration 1 - Mode 3 - 15



Date: 20.JUL.2011 07:28:27




Date: 20.JUL.2011 07:29:23




20.0MHz Bandwidth

Configuration 1 - Mode 1 - 20



Date: 20.JUL.2011 04:01:17




Date: 20.JUL.2011 04:03:33




Product Service

Configuration 1 - Mode 3 - 20



Date: 20.JUL.2011 04:09:01



Date: 28.JUL.2011 09:22:21

Limit

The power of any emission outside the frequency band shall be attenuated below the transmitter power (P) by at least $43 + 10\log P$ dB.



Product Service

2.6 RADIATED SPURIOUS EMISSIONS

2.6.1 Specification Reference

FCC CFR 47 Part 2, Clause 2.1053
FCC CFR 47 Part 27, Clause 27.53 (h)
Industry Canada RSS-139, Clause 6.5

2.6.2 Equipment Under Test

RRUS 11 B4 / KRC 161 254/1, S/N: CB4J379552

2.6.3 Date of Test and Modification State

4 and 5 August 2011 – Modification State 0

2.6.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.6.5 Test Method and Operating Modes

The test was applied in accordance with the test method requirements of FCC CFR 47 Part 2 and Part 27 and Industry Canada RSS-139.

A preliminary profile of the Spurious Radiated Emissions was obtained by operating the EUT on a remotely controlled turntable within the chamber. Measurements of emissions from the EUT were obtained with the Measurement Antenna in both Horizontal and Vertical Polarizations.

Emissions identified within the range 30MHz – 25GHz were then formally measured using a Peak detector as the worst case.

In the frequency Range 30MHz – 25GHz, the measurement was performed with a resolution bandwidth of 1MHz.

The measurements were performed at a 3m distance unless otherwise stated.

The limits for Spurious Emissions have been calculated, as shown below using the following formula:

Field Strength of Carrier - $(43 + 10\text{Log}(P))$ dB

Where:

Field Strength is measured in dB μ V/m

P is measured Transmitter Power in Watts



Determination of Spurious Emission Limit

As the EUT does not have an integral antenna, the field strength of the carrier has been calculated assuming that the power is to be fed to a half-wave tuned dipoles as per 2.1053 (a).

$$E_{(v/m)} = (30 \times G_i \times P_o)^{0.5} / d$$

Where G_i is the antenna gain of ideal half-wave dipoles,
 P_o is the power out of the transceiver in W,
 d is the measurement distance in meter.

Therefore at 3m measurement distance the field strength using the lowest transceiver output power would be:

$$E_{(v/m)} = (30 \times 1.64 \times 28.05)^{0.5} / 3 = 12.39V/m = 14.9dB\mu V/m$$

As per 27.53(h) the spurious emission must be attenuated by $43 + 10\log(P_o)$ dB this gives:

$$43 + 10\log(28.05) = 57.5dB$$

Therefore the limit at 3m measurement distance is:

$$141.9 - 57.5 = 84.4 \text{ dB}\mu V/m$$

This limit has been used to determine Pass or Fail for the harmonics measured and detailed in the following results.

The test was performed with the EUT in the following configurations and modes of operation:

Configuration 1 - Mode 1 - 1.4
 - Mode 2 (1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20.0MHz OBW)
 - Mode 3 - 1.4

2.6.6 Environmental Conditions

	4 Aug. 2011	5 Aug. 2011
Ambient Temperature	24.0°C	23.6°C
Relative Humidity	55.8%	56.5%



2.6.7 Test Results

For the period of test the EUT met the requirements of FCC CFR 47 Part 2 and Part 27 and Industry Canada RSS-139 for Radiated Spurious Emissions.

The test results are shown below

Note: Only the worst case results plots have been included as all of the emissions are greater than 20dB below the limit. A set of plots have been included to show the measurement system noise floor.

E-TM 1.1: 1.4MHz, 3.0MHz, 5.0MHz, 10MHz, 15MHz, 20MHz Bandwidth

Configuration 1 - Mode 2

No emissions were detected within 20dB of the limit.


E-TM3.2: 1.4MHz Bandwidth

Configuration 1 - Mode 1 - 1.4

No emissions were detected within 20dB of the limit.


Configuration 1 - Mode 2

30MHz to 1GHz






1GHz to 18GHz



MES_20110804-7_pre
LIM 84.4 Field Strength QP Limit

Note: The emission marked is the operating frequency.

18GHz to 25GHz



MES_20110804-12_pre
LIM 84.4 Field Strength QP Limit



Product Service

Configuration 1 - Mode 3 - 1.4

No emissions were detected within 20dB of the limit.

E-TM3.1: 1.4MHz Bandwidth

Configuration 1 - Mode - 2

No emissions were detected within 20dB of the limit.

Limit	-13dBm / 84.4dB μ V/m
-------	---------------------------

Remarks

The EUT does not exceed -13dBm / 84.4dB μ V/m at the measured frequencies.



Product Service

2.7 CONDUCTED SPURIOUS EMISSIONS

2.7.1 Specification Reference

FCC CFR 47 Part 2, Clause 2.1051
 FCC CFR 47 Part 27, Clause 27.53 (h)
 Industry Canada RSS-139, Clause 6.5

2.7.2 Equipment Under Test

RRUS 11 B4 / KRC 161 254/1, S/N: CB4J379552

2.7.3 Date of Test and Modification State

19 and 20 July 2011 – Modification State 0

2.7.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.7.5 Test Method and Operating Modes

The test was applied in accordance with the test method requirements of FCC CFR 47 Part 2 and Part 27 and Industry Canada RSS-139.

In accordance with Part 2.1051, the spurious emissions from the antenna terminal were measured. The transmitter output power was attenuated using an attenuator and the frequency spectrum investigated from 9kHz to 25GHz. The EUT was set to transmit on maximum power. The EUT was tested on Bottom, Middle and Top channels for E-TM1.1 test model in 1.4MHz and 20MHz bandwidth configurations as the representative modes. The resolution was set to 1MHz for 9kHz to 25GHz thus meeting the requirements of Part 27.53(h)(1). The spectrum analyser detector was set to peak and trace was kept on Max Hold.

The maximum path loss across the measurement band was used as the reference level offset to ensure worst case.

In addition, measurements were made up to the 10th harmonic of the highest internal frequency.

The test was performed with the EUT in the following configurations and modes of operation:

Configuration 1 - Mode 1 - 1.4, Mode 1 - 20
 - Mode 2 (1.4MHz, 20.0MHz OBW)
 - Mode 3 - 1.4, Mode 3 - 20

2.7.6 Environmental Conditions

	19 July 2011	20 July 2011
Ambient Temperature	27.0°C	25.0°C
Relative Humidity	60.0%	61.0%




2.7.7 Test Results

For the period of test the EUT met the requirements of FCC CFR 47 Part 2 and Part 27 and Industry Canada RSS-139 for Conducted Spurious Emissions.

The test results are shown below

Remark:

The emissions at 9kHz on the plots was not generated by the test object. A complementary measurement with a smaller Span showed that it was related to the LO feedthrough.



Date: 19.JUL.2011 08:22:29




E-TM1.1

1.4MHz Bandwidth

Configuration 1 - Mode 1 - 1.4


9kHz to 3GHz



Date: 20.JUL.2011 04:14:16

Note: The emission beyond the limit is the operating frequency.

3GHz to 25GHz




Date: 20.JUL.2011 04:15:26



Configuration 1 - Mode 2


9kHz to 3GHz



Date: 19.JUL.2011 08:18:06

Note: The emission beyond the limit is the operating frequency.

3GHz to 25GHz




Date: 19.JUL.2011 08:20:27



Configuration 1 - Mode 3 - 1.4


9kHz to 3GHz



Date: 20.JUL.2011 08:12:05

Note: The emission beyond the limit is the operating frequency.

3GHz to 25GHz




Date: 20.JUL.2011 08:13:19



20MHz Bandwidth

Configuration 1 - Mode 1 - 20


9kHz to 3GHz



Date: 20.JUL.2011 08:45:44

Note: The emission beyond the limit is the operating frequency.

3GHz to 25GHz




Date: 20.JUL.2011 08:46:50



Configuration 1 - Mode 2


9kHz to 3GHz



Date: 19.JUL.2011 09:23:09

Note: The emission beyond the limit is the operating frequency.

3GHz to 25GHz




Date: 19.JUL.2011 09:20:17



Product Service

Configuration 1 - Mode 3 - 20


9kHz to 3GHz



Date: 20.JUL.2011 08:55:32

Note: The emission beyond the limit is the operating frequency.

3GHz to 25GHz



Date: 20.JUL.2011 08:53:04

Limit	-13dBm
-------	--------

Remarks

The EUT does not exceed -13dBm at the frequency range of 9kHz to 25GHz.



Product Service

2.8 FREQUENCY STABILITY UNDER TEMPERATURE VARIATIONS

2.8.1 Specification Reference

FCC CFR 47 Part 2, Clause 2.1055
 FCC CFR 47 Part 27, Clause 27.54
 Industry Canada RSS-139, Clause 6.3

2.8.2 Equipment Under Test

RRUS 11 B4 / KRC 161 254/1, S/N: CB4J379552

2.8.3 Date of Test and Modification State

28 July 2011 – Modification State 0

2.8.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.8.5 Test Method and Operating Modes

The test was applied in accordance with the test method requirements of FCC CFR 47 Part 2 and Part 27 and Industry Canada RSS-139.

The EUT was set to transmit on maximum power. A Spectrum Analyser was used to measure the frequency error. The temperature was adjusted between -30°C and +50°C in 10° steps as per 2.1055.

The EUT was tested with test model E-TM1.1 in 5MHz Bandwidth.

The test was performed with the EUT in the following configurations and modes of operation:

Configuration 1 - Mode 2 (5.0MHz OBW)

2.8.6 Environmental Conditions

	28 July 2011
Ambient Temperature	23.7°C
Relative Humidity	62.0%



2.8.7 Test Results

For the period of test the EUT met the requirements of FCC CFR 47 Part 2 and Part 27 and Industry Canada RSS-139 for Frequency Stability Under Temperature Variations.

The test results are shown below

Power Supply: -48V DC

E-TM1.1: 5MHz Bandwidth

Configuration 1 - Mode 2

Temperature Interval (°C)	Deviation (Hz)
-30	-19.26
-20	-14.25
-10	-15.58
0	-12.79
+10	-5.63
+20	7.00
+30	10.06
+40	-14.74
+50	-19.96

Limit	$\pm (0.05 \text{ ppm} + 12 \text{ Hz})$ or $\pm 118.63 \text{ Hz}^*$
-------	---

Remarks

* Limit according to 3GPP TS 36.141 V9.5.0.

The frequency stability of the EUT is sufficient to keep it within the authorised frequency ranges at any temperature interval across the measured range.



Product Service

2.9 FREQUENCY STABILITY UNDER VOLTAGE VARIATIONS

2.9.1 Specification Reference

FCC CFR 47 Part 2, Clause 2.1055
FCC CFR 47 Part 27, Clause 27.54
Industry Canada RSS-139, Clause 6.3

2.9.2 Equipment Under Test

RRUS 11 B4 / KRC 161 254/1, S/N: CB4J379552

2.9.3 Date of Test and Modification State

28 July 2011 – Modification State 0

2.9.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.9.5 Test Method and Operating Modes

The test was applied in accordance with the test method requirements of FCC CFR 47 Part 2 and Part 27 and Industry Canada RSS-139.

The EUT was set to transmit on maximum power. A Spectrum Analyser was used to measure the frequency error. The supplied voltage was varied from 85 to 115 percent of the nominal value.

The EUT was tested with test model E-TM1.1 in 5MHz Bandwidth.

The test was performed with the EUT in the following configurations and modes of operation:

Configuration 1 - Mode 2 (5.0MHz)

2.9.6 Environmental Conditions

	28 July 2011
Ambient Temperature	23.7°C
Relative Humidity	62.0%



Product Service

2.9.7 Test Results

For the period of test the EUT met the requirements of FCC CFR 47 Part 2 and Part 27 and Industry Canada RSS-139 for Frequency Stability Under Voltage Variations.

The test results are shown below

Temperature: 20°C

E-TM1.1: 5MHz Bandwidth

Configuration 1 - Mode 2

DC Voltage (V)	Deviation (Hz)
-40.8	9.77
-48.0	7.00
-55.2	9.83

Limit	$\pm (0.05 \text{ ppm} + 12 \text{ Hz})$ or $\pm 118.63 \text{ Hz}^*$
-------	---

Remarks

* Limit according to 3GPP TS 36.141 V9.5.0.

The frequency stability of the EUT is sufficient to keep it within the authorised frequency ranges at any temperature interval across the measured range.



2.10 RECEIVER SPURIOUS EMISSIONS

2.10.1 Specification Reference

Industry Canada RSS-139, Clause 6.6

2.10.2 Equipment Under Test

RRUS 11 B4 / KRC 161 254/1, S/N: CB4J379552

2.10.3 Date of Test and Modification State

18 July 2011 – Modification State 0

2.10.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.10.5 Test Method and Operating Modes

The test was applied in accordance with the test method requirements of Industry Canada RSS 139.

In accordance with RSS-Gen Clause 6.2, the receiver spurious emissions from the antenna terminal were measured. Measurements were performed on the receiver antenna connector RF B. The EUT was set to transmitter mode on the TX connector RF A and during the measurement the RF A was terminated with match load, (50 Ohm).

The resolution was set to 1MHz in the frequency range 9kHz to 13GHz thus meeting the requirements of RSS-Gen Clause 4.10, the spectrum analyser detector was set to peak and trace was kept on Max Hold to give the worst case. The limit line was displayed, showing the -57dBm, 2 nanowatts in band 9kHz to 1GHz and above 1GHz, -53dBm, 5 nanowatts.

The maximum path loss across the measurement band was used as the reference level offset to ensure worst case.

In addition, measurements were made from 9kHz up to the 5th harmonic of the highest internal frequency.

The EUT was tested with test model E-TM1.1 in 1.4MHz and 20MHz Bandwidth.

The test was performed with the EUT in the following configurations and modes of operation:

Configuration 1 - Mode 1 - 1.4, Mode 1 - 20
 - Mode 2 (1.4MHz, 20MHz OBW)
 - Mode 3 - 1.4, Mode 3 - 20

2.10.6 Environmental Conditions

18 July 2011

Ambient Temperature 25.0°C

Relative Humidity 66.5%




2.10.7 Test Results

For the period of test the EUT met the requirements of Industry Canada RSS-139 for Receiver Spurious Emissions.

The test results are shown below

Remark:

The emissions at 9kHz on the plots was not generated by the test object. A complementary measruement with a smaller Span showed that it was related to the LO feedthrough.



Date: 18.JUL.2011 10:14:40




Product Service

E-TM1.1

1.4MHz Bandwidth


Configuration 1 - Mode 1 - 1.4

9kHz to 1GHz



Date: 18.JUL.2011 10:22:22

1GHz to 13GHz




Date: 18.JUL.2011 10:20:56




Configuration 1 - Mode 2

9kHz to 1GHz



Date: 18.JUL.2011 10:12:13

1GHz to 13GHz




Date: 18.JUL.2011 10:17:28




Configuration 1 - Mode 3 - 1.4

9kHz to 1GHz



Date: 18.JUL.2011 10:24:58

1GHz to 13GHz



Date: 18.JUL.2011 10:26:06




Product Service

20MHz Bandwidth


Configuration 1 - Mode 1 - 20

9kHz to 1GHz



Date: 18.JUL.2011 10:34:48

1GHz to 13GHz




Date: 18.JUL.2011 10:35:50




Configuration 1 - Mode 2

9kHz to 1GHz



Date: 18.JUL.2011 10:31:20

1GHz to 13GHz




Date: 18.JUL.2011 10:30:22



Product Service


Configuration 1 - Mode 3 - 20

9kHz to 1GHz



Date: 18.JUL.2011 10:43:34

1GHz to 13GHz



Date: 18.JUL.2011 10:39:25

Limit	-57dBm (30MHz-1GHz) and -53dBm (above 1GHz)
-------	---

Remarks

The EUT does not exceed -57dBm at the frequency range of 9kHz to 1GHz and does not exceed -53dBm at the frequency range of 1GHz to 13GHz.



Product Service

SECTION 3

TEST EQUIPMENT USED



3.1 TEST EQUIPMENT USED

List of absolute measuring and other principal items of test equipment.

Instrument	Manufacturer	Type No.	Serial No.	Calibration Period (months)	Calibration Due
Section 2.1, 2.2, 2.3, 2.4, 2.5, 2.7 and 2.10 – Maximum Conducted Output Power, Peak – Average Ratio, Modulation Characteristics, Occupied Bandwidth, Spurious Emissions at Antenna Terminals (± 1MHz) , Conducted Spurious Emissions and Receiver Spurious Emissions.					
Spectrum Analyser	Rohde & Schwarz	FSQ26	20-332960	12	08-May-2012
Power Meter	Rohde & Schwarz	NRP	102624	12	27-Mar-2012
Thermal Power Sensor	Rohde & Schwarz	NRP-Z51	102168	12	24-Aug-2011
Network Analyzer	Agilent	8720D	US38431317	12	24-Aug-2011
40dB Attenuator	Aeroflex / Weinschel	48-40-43-LIM	BR5020	-	O/P MON
40dB Attenuator	SHX	DTS 100	04051203	-	O/P MON
Load	Shanghai Huaxiang	TF100	09121614	-	O/P MON
Power Supply	Dahua	DH1716-5D	200360033	-	O/P MON
Power Supply	Dahua	DH1716A-14	20080401	-	O/P MON
Digital Multi-meter	FLUKE	179	91820401	12	03-Jan-2012
Thermo-hygrometer	AZ Instruments	8705	9151655	12	16-Dec-2011
Section 2.6 – Radiated Spurious Emissions					
Load	Shanghai Huaxiang	TF150-3	090323433	-	O/P MON
Load	Shanghai Huaxiang	TF100	09121603	-	O/P MON
EMI Receiver	Rohde & Schwarz	ESI 40	100015	12	19-Aug-2011
Ultra log test antenna	Rohde & Schwarz	HL562	100167	12	19-Aug-2011
Double-Ridged Wave-guide Horn Antenna	Rohde & Schwarz	HF 906	100029	12	19-Aug-2011
Pyramidal Horn Antenna	EMCO	3160-09	-	-	-
Antenna master	Frankonia	MA 260	-	-	19-Aug-2011
Relay Switch Unit	Rohde & Schwarz	331.1601.31	338965002	-	TU
Semi Anechoic Chamber	Frankonia	23.18m×16.88m×9.60m	-	12	19-Aug-2011
Power Supply	Dahua	DH1716-5D	200360033	-	O/P MON
Power Supply	Dahua	DH1716A-14	20080401	-	O/P MON
Digital Multimeter	FLUKE	179	91820401	12	03-Jan-2012
Thermo-hygrometer	AZ Instruments	8705	9151655	12	16-Dec-2011



Product Service

Section 2.8 and 2.9 – Frequency Stability Under Temperature and Voltage Variations					
Spectrum Analyser	Rohde & Schwarz	FSQ26	20-332960	12	08-May-2012
40dB Attenuator	Aeroflex / Weinschel	48-40-43-LIM	BR5020	-	O/P MON
Temperature Chamber	Weiss-Voetsch	C1000-70	54686070200 30	12	08-Jun-2012
Power Supply	Dahua	DH1716-5D	200360033	-	O/P MON
Power Supply	Dahua	DH1716A-14	20080401	-	O/P MON
Digital Multimeter	FLUKE	179	91820401	12	03-Jan-2012
Thermo-hygrometer	AZ Instruments	8705	9151655	12	16-Dec-2011

O/P MON Output monitored with calibration equipment
 TU Traceability Unscheduled



3.2 MEASUREMENT UNCERTAINTY

For a 95% confidence level, the measurement uncertainties for defined systems are:-

Test Discipline	Frequency / Parameter	MU
Conducted Maximum Peak Output Power	30MHz to 10GHz Amplitude	0.5dB*
Conducted Emissions	30MHz to 40GHz Amplitude	3.0dB*
Frequency Stability	30MHz to 2GHz Amplitude	$<1 \times 10^{-7}$
Radiated Emissions, Bilog Antenna, AOATS	30MHz to 1GHz Amplitude	5.1dB*
Radiated Emissions, Horn Antenna, AOATS	1GHz to 40GHz Amplitude	6.3dB*
Worst case error for both Time and Frequency measurement 12 parts in 10^6		

* In accordance with CISPR 16-4



Product Service

SECTION 4

ACCREDITATION, DISCLAIMERS AND COPYRIGHT



Product Service

4.1 ACCREDITATION, DISCLAIMERS AND COPYRIGHT



This report relates only to the actual item/items tested.

Our UKAS Accreditation does not cover opinions and interpretations and any expressed are outside the scope of our UKAS Accreditation.

Results of tests not covered by our UKAS Accreditation Schedule are marked NUA
(Not UKAS Accredited).

This report must not be reproduced, except in its entirety, without the written permission of
TÜV SÜD Product Service Limited

© 2011 TÜV SÜD Product Service Limited