

Confidentiality Class	External Confidentiality Label	Document Type	Sheet
Ericsson Internal			1 (6)
Prepared By (Subject Responsible)	Approved By (Document Responsible)		Checked
EHUAYAN	Hua Yang		
Document Number	Revision	Date	Reference
TA8AKRC161711-1	A	2020-04-07	



## External Antenna List

Ericsson AB requests to authorize additional antennas for Part 96 operations with the FCC Hardware Certified Part 96 CBSD radio device.

**Radio Vendor:** Ericsson AB  
**Radio Product Name:** Radio 2208 B48  
**Radio Model Number:** KRC 161 711/1  
**Radio FCC ID:** TA8AKRC161711-1

### Radio dynamic range:

- Maximum linear conducted power rating at output connector into 50 ohms that meets all OOB requirements [zero additional attenuation, highest power setting allowed, for use with lowest gain external antennas] (dBm): 40dBm per port or 43 dBm total power
- Minimum linear conducted power rating at output connector into 50 ohms that meets all OOB requirements [maximum additional linear attenuation, lowest power setting allowed, for use with highest gain external antennas] (dBm): 10dBm per port or 13 dBm total power
- Note: use of an external cable introduces additional losses that may be compensated appropriately by increasing the radio's power level (reducing the attenuator setting). This cable compensation may be achieved during radio setup.

The Original Equipment Manufacturer (OEM) vendor of the radio states that the use of the following listed external antennas meets all requirements for Part 96 operations. The following specific external antennas may be used in conjunction with this model radio at the appropriate listed power settings.

These antennas will allow this radio to meet the appropriate Part 96 requirements for Maximum EIRP, at below:

- 30 dBm EIRP (for Category A operations), or
- 47 dBm/10MHz EIRP (for Category B operations).

Confidentiality Class Ericsson Internal	External Confidentiality Label	Document Type	Sheet 2 (6)
Prepared By (Subject Responsible) EHUAYAN	Approved By (Document Responsible) Hua Yang		Checked
Document Number TA8AKRC161711-1	Revision A	Date 2020-04-07	Reference



Total conducted power is shown, for each antenna, with varying signal operating bandwidths.

**Table: CBRS Band 48 External antennas authorized by the Original Equipment Manufacturer for use with this radio:**

Antenna Configuration	Antenna Vendor	Antenna Model Number	Antenna Main Beam Peak Gain [dBi]	LTE Carrier Bandwidth [MHz]	Maximum Total Conducted Power [dBm]	EIRP [dBm/10MHz]	EIRP per Bandwidth [dBm]	Operational Category [A / B]
1	JMA	CX14OMI236-1C	5	10	42	47	47	B
				20	43	45	48	
2	JMA	CX16OMI236-1C	5	10	42	47	47	B
				20	43	45	48	
3	JMA	CX16OMI224-1H	6.1	10	40.9	47	47	B
				20	43	46.1	49.1	
4	JMA	CX16OMI218-1P	5.3	10	41.7	47	47	B
				20	43	45.3	48.3	
5	JMA	DX10FRO260-00 or 06	15.5	10	31.5	47	47	B
				20	34.5	47	50	
6	JMA	DX12FRO260-20 or 26	14.8	10	32.2	47	47	B
				20	35.2	47	50	
7	JMA	CX04OMI336-1C	12	10	35	47	47	B
				20	38	47	50	
8	JMA	MX02FIT365-01	17.8	10	29.2	47	47	B
				20	32.2	47	50	
9	JMA	MX04FIT365-01	17.8	10	29.2	47	47	B
				20	32.2	47	50	

Confidentiality Class Ericsson Internal	External Confidentiality Label	Document Type	Sheet 3 (6)
Prepared By (Subject Responsible) EHUAYAN	Approved By (Document Responsible) Hua Yang	Checked	
Document Number TA8AKRC161711-1	Revision A	Date 2020-04-07	Reference



10	Amphenol	C2U3MT360X06Fxys0	8.1	10	38.9	47	47	B
				20	41.9	47	50	
11	Amphenol	2C2U3MT360X06Fxys0	5.8	10	41.2	47	47	B
				20	43	45.8	48.8	
12	Amphenol	4U4MT360X06Fxys0	5.7	10	41.3	47	47	B
				20	43	45.7	48.7	
13	Amphenol	2C4U3MT360X06Fwxys0	5.9	10	41.3	47	47	B
				20	43	45.7	48.7	
14	Amphenol	2U3MX065X06Fxys0	11.6	10	35.4	47	47	B
				20	38.4	47	50	
15	Amphenol	4U4MX065X06Fxys0	11.3	10	35.7	47	47	B
				20	38.7	47	50	
16	Amphenol	2C4U3MX065X06Fwxys0	8.9	10	38.1	47	47	B
				20	41.1	47	50	
17	Kathrein	84010555 / 84010556	7	10	40	47	47	B
				20	43	47	50	
18	Kathrein	84010557 / 84010558	6.3	10	40.7	47	47	B
				20	43	46.3	49.3	
19	Kathrein	84010603 / 84010604	6.5	10	40.5	47	47	B
				20	43	46.5	49.5	
20	Kathrein	84010564	11.5	10	35.5	47	47	B
				20	38.5	47	50	
21	Kathrein	80010922	18	10	29	47	47	B
				20	32	47	50	
22	Kathrein	800250911	16.1	10	30.9	47	47	B

Confidentiality Class Ericsson Internal	External Confidentiality Label	Document Type	Sheet 4 (6)
Prepared By (Subject Responsible) EHUAYAN	Approved By (Document Responsible) Hua Yang	Checked	
Document Number TA8AKRC161711-1	Revision A	Date 2020-04-07	Reference



				20	33.9	47	50	
23	Kathrein	84010601 / 84010602	7.2	10	39.8	47	47	B
				20	42.8	47	50	
24	Kathrein	80010249	2	10	43	45	45	B
				20	43	42	45	
25	Kathrein	80010430	2	10	43	45	45	B
				20	43	42	45	
26	CommScope	VVSSP-360S-F	4.9	10	42.1	47	47	B
				20	43	44.9	47.9	
27	CommScope	NNVVSSP-360S-FM	5.7	10	41.3	47	47	B
				20	43	45.7	48.7	
28	CommScope	V4SSPP-360S-F	5.4	10	41.6	47	47	B
				20	43	45.4	48.4	
29	CommScope	VVSSP-65S-R1B (Canister)	9.8	10	37.2	47	47	B
				20	40.2	47	50	
30	CommScope	VVSSP-65S-R1BV2 (Panel)	10.4	10	36.6	47	47	B
				20	39.6	47	50	
31	CommScope	SSPX31OR-V2	18.1	10	28.9	47	47	B
				20	31.9	47	50	
32	CommScope	S-65M-R1	18.1	10	28.9	47	47	B
				20	31.9	47	50	
33	CommScope	SS-360S-F	11.3	10	35.7	47	47	B
				20	38.7	47	50	
34	MobileMark	EDN32-3700	5	10	42	47	47	B
				20	43	45	48	

Confidentiality Class Ericsson Internal	External Confidentiality Label	Document Type	Sheet 5 (7)
Prepared By (Subject Responsible) EHUAYAN	Approved By (Document Responsible) Hua Yang	Checked	
Document Number TA8AKRC161711-1	Revision A	Date 2020-04-07	Reference



35	Rosenberger	CA-AEOIOITJTVEX360F-JS06	9	10	38	47	47	B
				20	41	47	50	
36	Rosenberger	BA-T8T8X65V-01	18	10	29	47	47	B
				20	32	47	50	
37	Rosenberger	BA-T8X65V-01	18	10	29	47	47	B
				20	32	47	50	
38	Alpha	AW3014	18	10	29	47	47	B
				20	32	47	50	
39	Alpha	AW3023	18	10	29	47	47	B
				20	32	47	50	
40	Alpha	AW3056	19.5	10	27.5	47	47	B
				20	30.5	47	50	
41	Alpha	AW3089	11	10	36	47	47	B
				20	39	47	50	
42	Alpha	AW3159	17.3	10	29.7	47	47	B
				20	32.7	47	50	
43	Alpha	AW3161	17.9	10	29.1	47	47	B
				20	32.1	47	50	
44	Alpha	AW3523	18.6	10	28.4	47	47	B
				20	31.4	47	50	
45	Alpha	AW3625	8.5	10	38.5	47	47	B
				20	41.5	47	50	
46	Alpha	AW3647	19.5	10	27.5	47	47	B
				20	30.5	47	50	
47	Alpha	AW3672	8.5	10	38.5	47	47	B

Confidentiality Class Ericsson Internal	External Confidentiality Label	Document Type	Sheet 6 (6)
Prepared By (Subject Responsible) EHUAYAN	Approved By (Document Responsible) Hua Yang	Checked	
Document Number TA8AKRC161711-1	Revision A	Date 2020-04-07	Reference



				20	41.5	47	50	
48	Alpha	AW3711	20.2	10	26.8	47	47	B
				20	29.8	47	50	
49	CellMax	12004v	19.9	10	27.1	47	47	B
				20	30.1	47	50	
50	CellMax	13006v	21.1	10	25.9	47	47	B
				20	28.9	47	50	
51	CellMax	12010v	19.9	10	27.1	47	47	B
				20	30.1	47	50	
52	CellMax	13011v	21.1	10	25.9	47	47	B
				20	28.9	47	50	
53	PCTEL	SP3338-17XP65	17	10	30	47	47	B
				20	33	47	50	
54	PCTEL	SP3338-16QP90	16	10	31	47	47	B
				20	34	47	50	
55	Denki Kogyo	DK16WDYKDP-10R86F	5	10	42	47	47	B
				20	43	45	48	
56	Denki Kogyo	DK18BDYKDP-8R54F	5	10	42	47	47	B
				20	43	45	48	
57	Denki Kogyo	DKOBDYKDP-7R45F	3	10	43	46	46	B
				20	43	43	46	
58	Galtronics	EXTENT™ P6612	8.5	10	38.5	47	47	B
				20	41.5	47	50	