FRICSSON					
		EXHIBIT 13			
Prepared (Subject resp)		No.			
ESAVMIK		287AB-AS901060			
Approved (Document resp)	Checked	Date	Rev	Reference	

Approved (Document resp) LMF/TXA (Mika Savilakso)

Industry Canada Certification and Engineering Bureau 3701 Carling Avenue, Bldg.94 P.O. Box 11490, Station "H" Ottawa, Ontario K2H 8S2 Canada TÜV SÜD BABT Octagon House, Concorde Way Segensworth North,|Fareham, Hampshire PO15 5RL United Kingdom

А

2015-06-08

1 (3)

April 24, 2015

Subject: Certification for IC ID: 287AB-AS901060

To Whom It May Concern:

Ericsson AB requests a Grant of Certification (Type Acceptance) for the above mentioned IC Identifier.

This base station transceiver (Radio Base Station – RBS 6402) is designed for use in LTE cellular telephone system. The transmitter will operate from 1930 MHz to 1990 MHz, from 1930 to 1995 MHz, from 2110 to 2155 MHz and from 2620 to 2690 MHz. The receiver circuit supports from 1850 to 1910 MHz, form 1850 to 1915 MHz, from 1710 to 1755 MHz, from 2500 to 2570 MHz. It supports channel bandwidths of 5, 10, 15 and 20 MHz for LTE. This Radio Base Station supports modulation type and QPSK, 16QAM and 64QAM for LTE. The base station operates in the Cellular band as per RSS-130. It meets the requirements of Third Generation Partnership Project (3GPP) for operation in LTE cellular systems.

This base station transceiver (Radio Base Station – RBS 6402) will in normal mode operate at a nominal power out of 250 milliwats at the output connectors, to feed an Integrated omni antenna.

This RBS 6402 is has two a dual-TX radio units where two RF chains are identical. Can be configured to two 2x2 MIMO per radio or CA inter-band CA, intra band CA with two radio cards and 4x4 MIMO with two radio cards. Table 1 is illustrate HW configuration.

This RBS 6402 supports two Radio Modules of which both have two identical down-link and up-link signal paths.

Function Designation	Product nr.	FCC ID:	IC:	IC MODEL NO:
KRD 901 060/1 = One radio module, include Band 2, Band 25, Band 4, Band 7	KRD 901 060/1	TA8AKRD901060	287AB-AS901060	AS9010601
KRD 901 060/2 = Two radio module, include Band 2, Band 25, Band 4, Band 7	KRD 901 060/2	TA8AKRD901060	287AB-AS901060	AS9010602
KRD 901 060/7 = One radio module, include Band 2, Band 25	KRD 901 060/7	TA8AKRD901060	287AB-AS901060	AS9010607
KRD 901 060/8 = One radio module, include Band 4	KRD 901 060/8	TA8AKRD901060	287AB-AS901060	AS9010608
KRD 901 060/9 = One radio module, include Band 7	KRD 901 060/9		287AB-AS901060	AS9010609

Table 1 RBS 6402 HW configuration

This Permissive Change request for this Radio Base Station (RBS 6402 B2, B25, B4, B7) is to include following, specified in Exhibit 12 Circuit Description:

1) Modifications according to Exhibit 12 Circuit Description Modification

The Exhibit 8 user manuals submitted with this application is generic and may cover multiple products.

This application is only valid for the model specified in the Exhibit 12 circuit description.

Ericsson AB requests confidentiality pursuant to RSP-100 Section 6.4 according to attached letter.

ERICSSON	1
----------	---

ERICSSON >		EXHIBIT 13			2 (3)
Prepared (Subject resp)		No.			
ESAVMIK		287AB-AS901060			
Approved (Document resp)	Checked	Date	Rev	Reference	
LMF/TXA (Mika Savilakso)		2015-06-08	А		

ERICSSON	
----------	--

•		EXHIBIT 13			3 (3)
Prepared (Subject resp)		No.			
ESAVMIK		287AB-AS901060			
Approved (Document resp)	Checked	Date	Rev	Reference	
LMF/TXA (Mika Savilakso)		2015-06-08	А		

If additional information is needed, please contact me on the below listed number.

Mika Savilakso Senior Developer Ericsson AB FCC Registration Number (FRN): 0013476155 Isafjordsgatan 10 SE-164 80 Stockholm, Sweden Telephone No.: +358 9 299 3714 e-mail: <u>mika.savilakso@ericsson.com</u>