



# REPORT

issued by an FCC listed Laboratory Reg. no. 93866.  
The test site complies with RSS-Gen, file no: IC 3482A

Contact person

Andreas Johnson  
Electronics  
+46 10 516 57 86  
Andreas.Johnson@sp.se

Date

2014-06-26

Reference

4P04484-02-MPE

Page

1 (2)

Ericsson AB  
Weil Ma  
PDU HW  
164 80 Stockholm

## MPE test on Ericsson RBS 6501 B12

(3 appendices)

### Test object

Product name: RBS 6501 B12

Product number: KRD 901 112/X, see appendix 1 for details.

See appendix 1 for the tested hardware configuration and general information.

See appendix 3 for photos.

### Summary

Standard	Compliant	Appendix	Remarks
FCC 47 CFR 2.1091 Radiofrequency radiation exposure evaluation: mobile devices	Yes	2	-
RSS-102 Radio Frequency Exposure compliance of Radio communication Apparatus, Issue 4	Yes	2	-
OET Bulletin 65/KDB447498 D01 v05r02	Yes	2	-

## SP Technical Research Institute of Sweden Electronics - EMC

Performed by

Signed by: Andreas Johnson  
Reason: I am the author of this document.  
Date & Time: 2014-06-26 14:27:19 +02:00

Andreas Johnson

Examined by

Signed by: Anders Nordlöf  
Reason: I have reviewed this document  
Date & Time: 2014-06-26 14:46:18 +02:00

Anders Nordlöf

---

### SP Technical Research Institute of Sweden

Postal address

SP  
Box 857  
SE-501 15 BORÅS  
Sweden

Office location

Västeråsen  
Brinellgatan 4  
SE-504 62 BORÅS

Phone / Fax / E-mail

+46 10 516 50 00  
+46 33 13 55 02  
info@sp.se

This document may not be reproduced other than in full, except with the prior written approval of SP.

**Table of contents**

Measurement equipment	Appendix 1
Uncertainties	Appendix 1
Purpose of test	Appendix 1
Description of the test object	Appendix 1
Delivery of test object	Appendix 1
Test facility	Appendix 1
Reservation	Appendix 1
Test engineers	Appendix 1
Test participant	Appendix 1
Operational test mode	Appendix 1
Tested configuration	Appendix 1
Purpose of test	Appendix 1
Description of the test object	Appendix 1
RF exposure evaluation	Appendix 2
Photos of test object	Appendix 3

## Appendix 1

### Measurement equipment

	Calibration Due	SP number
Test site Tesla	2017-01	503 881
Measurement software: Antennkalibrering V1.20	-	-
Calculation software: EMF 1.2	-	-
Laser probe AR FL7006	2014-07	901 492
Testo 625 Temperature and humidity meter	2014-06	504 188

### Uncertainties

Measurement and test instrument uncertainties are described in the quality assurance documentation "SP-QD 10885". The measurement uncertainties can be found in the table below. The uncertainties are calculated with a coverage factor  $k=2$  (95% level of confidence).

Standard	Method	Uncertainty
FCC 47 CFR 2.1091 and RSS-102	RF exposure evaluation	10 %, Note

Note: Stated uncertainty refers to the calculated distance.

Compliance evaluation is based on a shared risk principle with respect to the measurement uncertainty.

### Purpose of test

The tests were performed to verify that the radiofrequency exposure of the RBS 6501 meets the requirements of 47 CFR 2.1091 and RSS-102.

### Description of the test object

The test object is a Radio Base Station configured in Single RAT mode for LTE designed to provide mobile users with a connection to a mobile network.

The test scope covers the following models of test objects:

Product number: KRD 901 112/1, 100-250 VAC integrated antenna

Product number: KRD 901 112/2, -48 VDC integrated antenna

Product number: KRD 901 112/3, 100-250 VAC no integrated antenna

Product number: KRD 901 112/4, -48 VDC no integrated antenna

FCC ID: TA8AKRD901112

IC ID: 287AB-AS901112

IC model numbers:

IC MODEL NO: AS9011121

IC MODEL NO: AS9011122

IC MODEL NO: AS9011123

IC MODEL NO: AS9011124

## Appendix 1

### **Delivery of test object**

The test object was delivered: 2014-06-10.

### **Test facility**

The used test site (503 881) is compliant with the requirements of section 2.948 of the FCC rules and listed, registration number 93866, as a facility accepted for certification under parts 15 and 18. The site complies with RSS-Gen, Issue 3 and is accepted by Industry Canada for the performance of radiated measurements, file no: IC 3482A-1.

### **Reservation**

The test results in this report apply only to the particular test object as declared in the report.

### **Test engineers**

Tomas Isbring, Andreas Johnson, Benyamin Mashouf and Kexin Chen, SP.

### **Test participant**

None.

## Appendix 1

**Tested configuration**

RF A configuration: 1x 37.0 dBm (5 W)  
RF B configuration: 1x 37.0 dBm (5 W)  
Communication: IP via electrical interface  
Power configuration: 120 VAC/ 60 Hz

**Operational test mode**

The RBS 6501 unit was activated for maximum transmit power transmitting test model E-TM1.1 as defined in ETSI TS 136 141/ 3GPP TS 36.141.


The test object was configured in MIMO mode with both RF paths allocated to the following EARFCN:

EARFCN Downlink	Frequency [MHz]	Comment
5035	731.5	Single carrier TX bottom frequency in 5 MHz BW configuration
5090	737.0	Single carrier TX mid frequency in 5 MHz BW configuration
5145	742.5	Single carrier TX top frequency in 5 MHz BW configuration

All RX frequencies were configured 30 MHz below the corresponding TX frequency according to the applicable duplex offset for the operating band.

Appendix 1

Test setup:



1.	RBS 6501 B12 AC, KR D 901 112/1, rev. R1A, s/n: CB4T818581 Software CXP 901 3268/9, rev. R51TB
----	---

**Functional test equipment:**

2.	Computer HP EliteBook 8540w BAMS – 1001052042
3.	Switch Netgear GS108E
4.	GPS Active Antenna, KRE 101 2082/1

**Integrated antenna**

Directional antenna, KRE 101 2134/1, rev. R1C, s/n: T89U200079

Representing version: KR D 901 112/1 and KR D 901 112/2

**Semi-integrated omni antenna**

VPol Omni 694-894, KRE 101 2245/1, s/n: DEG4843265, Type no. 80010846

VPol Omni 694-894, KRE 101 2245/1, s/n: DEG4843302, Type no. 80010846

Representing version: KR D 901 112/3 and KR D 901 112/4

Appendix 1

<b>Interface:</b>	<b>Type of port:</b>
Power: 120 VAC/ 60 Hz	AC Power
TNA, RJ45 interface	Telecom
TNB, Optical interface	Telecom
EC bus and Ext Alarm	Signal
GPS	Signal
Ground wire	Ground

**RBS software**

<b>Software</b>	<b>Revision</b>
CXP 102 051/19	R37AL

Appendix 2

**RF exposure evaluation: 2.1091 Mobile devices / RSS-102 4.2**

Date	Temperature	Humidity
2014-06-16	22 °C ± 3 °C	49 % ± 5 %
2014-06-17	23 °C ± 3 °C	32 % ± 5 %
2014-06-18	23 °C ± 3 °C	40 % ± 5 %

**Procedure**

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

**Test setup and procedure**

1. The test object is measured in twelve directions (in 30° steps) with the field probe continuously scanning from 0.1 – 2.0 m in height.
2. Measuring distance was 20 cm from the centre of the test object, step 1 is repeated with a distance increment of 20 cm until the measured field strength is compliant.

The distance for compliance for Adult is derived from spatial average over the full scan height. The distance for compliance for Child is derived from spatial average over ± 45 cm from the height where the highest level was detected.

The calculation were adjusted according to:

1. measured output power with tolerance of ± 1 dB.
2. field probe characteristics with respect to the modulated signal LTE BW 5 MHz at different levels of the field strength.

The nominal power stated by the manufacturer is 2x 5 W (2x 37 dBm), with a tolerance of ± 1 dB. The measured output power was as follows:

Bottom frequency: 4.7 W (36.7 dBm)  
 Mid frequency: 4.8 W (36.8 dBm)  
 Top frequency: 4.8 W (36.8 dBm)

The calculation was therefore adjusted by the following corrections to cover the highest possible output power:


Bottom frequency: 1.3 dBm  
 Mid frequency: 1.2 dBm  
 Top frequency: 1.2 dBm

The measurement were made with an Integrated antenna and a Semi-integrated omni antenna.




## Appendix 2

Test setup orientation 1, Integrated antenna:




Test setup orientation 2, Integrated antenna:



## Appendix 2


Test setup orientation 2, Semi-integrated omni antenna:



Appendix 2

**Results**

Orientation 1, Integrated antenna, worst case: TX bottom frequency




Note: The test object was placed with the front side facing 0° and the rear side facing 180° as shown in the test setup photo.

Direction	Distance for compliance (cm).	
	Adult	Child
0°	74.0	93.4
30°	59.3	78.7
60°	20.0	36.3
90°	20.0	20.0
120°	20.0	20.0
150°	20.0	20.0
180°	20.0	20.0
210°	20.0	20.0
240°	20.0	20.0
270°	20.0	20.0
300°	20.0	20.0
330°	40.7	69.7

Note: The distance for compliance of every direction in the table above is calculated from the chassis of the test object.

Appendix 2

Orientation 2, Integrated antenna, worst case: TX mid frequency




Note: The test object was placed with the front side facing 0° and the cable inlet facing 90° as shown in the test setup photo.

Direction	Distance for compliance (cm).	
	Adult	Child
0°	75.4	101.5
30°	43.8	64.2
60°	20.0	20.0
90°	20.0	20.0
120°	20.0	20.0
150°	20.0	20.0
180°	20.0	20.0
210°	20.0	20.0
240°	20.0	20.0
270°	20.0	20.0
300°	20.0	30.8
330°	63.8	83.7

Note: The distance for compliance of every direction in the table above is calculated from the chassis of the test object.

Appendix 2

Orientation 2, Semi-integrated omni antenna, worst case: TX Bottom frequency



Note: The test object was placed with the front side facing 0° and the cable inlet facing 90° as shown in the test setup photo.

Direction	Distance for compliance (cm).	
	Adult	Child
0°	20.0	40.2
30°	20.0	31.1
60°	20.0	28.7
90°	20.0	24.8
120°	20.0	23.3
150°	20.0	20.0
180°	20.0	25.9
210°	20.0	21.9
240°	20.0	26.7
270°	20.0	30.7
300°	20.0	35.2
330°	20.0	36.5

Note: The distance for compliance of every direction in the table above is calculated from the chassis of the test object.

Appendix 2

**Limits**

According to 47 CFR 1.1310.

**(B) Limits for General Population/Uncontrolled Exposure**

Frequency range (MHz)	Electric field strength [E] (V/m)	Magnetic field strength [H] (A/m)	Power density [S] (mW/cm <sup>2</sup> )	Averaging time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
300-1500	-	-	0.5 (f/1500)	(Note 1)

According to RSS-102 4.2

**RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)**

Frequency range (MHz)	Electric field strength [E] (V/m)	Magnetic field strength [H] (A/m)	Power density [S] (W/m <sup>2</sup> )	Averaging time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
300-1500	-	-	5 (f/150)	(Note 1)

Note 1: The test was executed with the test object configured for continuous transmission with maximum output power setting to represent worst case. Therefore no averaging time measurement was made.


Complies?	Yes
-----------	-----



## Appendix 3

### Photos of test object

Front side with cover:



Front side without cover:



Front side without Integrated antenna and without cover:



Back side:



### Appendix 3

Right side without Integrated antenna and without cover:



Left side without Integrated antenna and without cover:



Front side with Semi-integrated omni antenna





Appendix 3

Labels:

RBS 6501 B12:



Integrated antenna:



Semi-integrated omni antennas

Antenna 1



Antenna 2

