



Add value.  
Inspire trust.

FCC Testing of the  
Ericsson Remote Radio Unit Dot 4455/4465 B77DB25B66 KRY 901  
523/1, KRY 901 523/2 NR (3700-3980 MHz) Base Station in  
accordance with FCC CFR 47 Part 2, FCC CFR 47 Part 27

COMMERCIAL-IN-CONFIDENCE

FCC: TA8AKRY901523-1 & TA8AKRY901523-2

PREPARED BY

Handwritten signature of Glen Westwell.

Glen Westwell  
Senior Test Engineer

APPROVED BY

Handwritten signature of Scott Drysdale.

Scott Drysdale  
Authorised Signatory

DATED

07-November-2022

Document 75956591 Report 01 Issue 2

02-November-2022



## CONTENTS

Section	Page No
<b>1</b>	<b>REPORT INFORMATION ..... 2</b>
1.1	Report Details ..... 3
1.2	Brief Summary of Results ..... 4
1.3	Test Rationale..... 5
1.4	Configuration Description ..... 6
1.5	Declaration of Build Status ..... 8
1.6	Product Information ..... 10
1.7	Test Setup ..... 11
1.8	Deviation From The Standard ..... 13
1.9	Modification Record ..... 13
1.10	Additional Information ..... 13
<b>2</b>	<b>TEST DETAILS ..... 14</b>
2.1	Maximum Peak Output Power and Peak to Average Ratio - Conducted..... 15
2.2	Occupied Bandwidth..... 46
2.3	Band Edge ..... 53
2.4	Transmitter Spurious Emissions ..... 76
2.5	Frequency Stability ..... 91
<b>3</b>	<b>TEST EQUIPMENT USED ..... 93</b>
3.1	Test Equipment Used ..... 94
3.2	Measurement Uncertainty ..... 95
<b>4</b>	<b>ACCREDITATION, DISCLAIMERS AND COPYRIGHT ..... 96</b>
4.1	Accreditation, Disclaimers and Copyright..... 97
<b>ANNEX A</b>	<b>Module Lists.....A.2</b>



## **SECTION 1**

### **REPORT INFORMATION**



## 1.1 REPORT DETAILS

Manufacturer	Ericsson
Address	Torshamnsgatan 23 Kista SE-16480 Stockholm Sweden
Product Name & Product Number	Dot 4465 B77D - KRY 901 523/2
Serial Number(s)	TD3W340089
Software Version	CXP2030045/26
Hardware Version	R1A modified as a R1B
Non-Tested Variant (See Section 1.10 Additional Information)	Dot 4455 B77DB25B66 - KRY 901 523/1
Test Specification/Issue/Date	FCC CFR 47 Part 2: 2021 FCC CFR 47 Part 27: 2021
Test Plan	TP_RA-FCC_Dot_4465_B77DB25B66
Start of Test	3-October-2021
Finish of Test	7-October-2022
Name of Engineer(s)	Glen Westwell
Related Document(s)	KDB 971168 D01 v02r02 KDB 662911 D01 v02r01 ANSI C63.26-2015

---

### ENGINEERING STATEMENT

The measurements shown in this report were made in accordance with the procedures described on test pages. All reported testing was carried out on a sample equipment to demonstrate compliance with and FCC CFR 47 Part 2: 2021, FCC CFR 47 Part 27: 2021. The sample tested was found to comply with the requirements defined in the applied rules.

Test Engineer(s);

---

Glen Westwell



## 1.2 BRIEF SUMMARY OF RESULTS

A brief summary of results for each configuration, in accordance with FCC CFR 47 Part 2, FCC CFR 47 Part 27 is shown below.

Section	Specification Clause		Test Description	Result
	FCC CFR 47 Part 2	FCC CFR 47 Part 27		
2.1	2.1046	27.50	Maximum Peak Output Power and Peak to Average Ratio - Conducted	Pass
2.2	2.1049	27.53	Occupied Bandwidth	Pass
2.3	2.1051	27.53	Band Edge	Pass
2.4	2.1051	27.53	Transmitter Spurious Emissions	Pass
2.5	2.1055	27.54	Frequency Stability	Pass



### **1.3 TEST RATIONALE**

The tests that have been selected are detailed in the customer Test Plan as defined in section 1.1 of this report. The Test Plan is based on the TÜV SÜD FCC Test Plan Rationale, available on request.



#### 1.4 CONFIGURATION DESCRIPTION

Configuration A					
RAT	No. of Carriers	Carrier Bandwidth	Carrier Frequency Configuration (MHz)		
			Bottom	Middle	Top
NR	1	10 MHz	3705.0	3840.0	3975.0
		15 MHz	3707.5	3840.0	3972.5
		20 MHz	3710.0	3840.0	3970.0
		30 MHz	3715.0	3840.0	3965.0
		40 MHz	3720.0	3840.0	3960.0
		50 MHz	3725.0	3840.0	3955.0
		60 MHz	3730.0	3840.0	3950.0
		70 MHz	3735.0	3840.0	3945.0
		80 MHz	3740.0	3840.0	3940.0
		90 MHz	3745.0	3840.0	3935.0
		100 MHz	3750.0	3840.0	3930.0

Configuration B Contiguous Channel Allocations					
RAT	No. of Carriers	Carrier Bandwidth	Carrier Frequency Configuration (MHz)		
			Bottom	Middle	Top
NR	2	10+10 MHz	3705.0+3715.0	3835.0+3845.0	3965.0+3975.0
		100+100 MHz	3750 + 3850	3790 +3890	3830 +3930

Configuration B Non-Contiguous Channel Allocations					
RAT	No. of Carriers	Carrier Bandwidth	Carrier Frequency Configuration (MHz)		
			Bottom	Middle	Top
NR	2	10+10 MHz	3705.0+3895.0	3745.0+3935.0	3785.0+3975.0
		90+90 MHz	3745.0+3855.0	3785.0+3895.0	3825.0+3935.0



<b>Configuration C Contiguous Channel Allocations</b>					
RAT	No. of Carriers	Carrier BW	Carrier Frequency Configuration (MHz)		
			Bottom	Middle	Top
NR	6	10 MHz	3705+3715+3725+	3815+3825+3835+	3925+3935+3945+
			3735+3745+3755	3845+3855+3865	3955+3965+3975
NR	6	20 MHz	3710+3730+3750+	3790+3810+3830+	3870+3890+3910+
			3770+3790+3810	3850+3870+3890	3930+3950+3970

<b>Configuration C Non-Contiguous Channel Allocations</b>					
RAT	No. of Carriers	Carrier BW	Carrier Frequency Configuration (MHz)		
			Bottom	Middle	Top
NR	6	10 MHz	3705+3715+3725+	3745+3755+3765+	3785+3795+3805+
			3875+3885+3895	3915+3925+3935	3955+3965+3975
NR	6	20 MHz	3710+3730+3750+	3750+3770+3790	3790+3810+3830+
			3850+3870+3890	3890+3910+3930	3930+3950+3970





## 1.5 DECLARATION OF BUILD STATUS

<b>MAIN EUT</b>	
<b>MANUFACTURING DESCRIPTION</b>	Radio Dot
<b>MANUFACTURER</b>	Ericsson
<b>TYPE</b>	Remote Radio Base Station
<b>PART NUMBER</b>	KRY 901 523/1 and KRY 901 523/2
<b>SERIAL NUMBER</b>	TD3W340089
<b>HARDWARE VERSION</b>	R1A modified as R1B
<b>SOFTWARE VERSION</b>	CXP 203 0045/26 - R14BX12
<b>TRANSMITTER OPERATING RANGE</b>	B77D: 3700-3980 MHz B25: 1930-1995MHz B66: 2110-2200MHz
<b>RECEIVER OPERATING RANGE</b>	B77D: 3700-3980 MHz B25: 1850-1915MHz B66: 1710-1780MHz
<b>COUNTRY OF ORIGIN</b>	China
<b>INTERMEDIATE FREQUENCIES</b>	None
<b>EMISSION DESIGNATOR(S): (i.e. G1D, GXW)</b>	B77D NR: 10M0F9W, 15M0F9W, 20M0F9W, 30M0F9W, 40M0F9W, 50M0F9W, 60M0F9W, 70M0F9W 80M0F9W, 90M0F9W, 100M0F9W  B25 NR: 10M0F9W, 15M0F9W, 20M0F9W +NBloT  B25 NR: 5M00F9W, 25M0F9W, 30M0F9W, 40M0F9W  B25 LTE: 5M00W7D, 10M0W7D, 15M0W7D, 20M0W7D +NBloT  B66 NR: 10M0F9W, 15M0F9W, 20M0F9W +NBloT  B66 NR: 5M00F9W, 25M0F9W, 30M0F9W, 40M0F9W  B66 LTE: 5M00W7D, 10M0W7D, 15M0W7D, 20M0W7D +NBloT
<b>MODULATION TYPES: (i.e. GMSK, QPSK)</b>	NR: QPSK, 16QAM, 64QAM, 256QAM LTE: QPSK, 16QAM, 64QAM, 256QAM
<b>HIGHEST INTERNALLY GENERATED FREQUENCY</b>	3.98 GHz
<b>OUTPUT POWER (W or dBm)</b>	B77D: 4 x 0.4W (26dBm) (1 carrier limited to 24dBm) B25: 2 x 0.2W (23dBm) B66: 2 x 0.2W (23dBm)
<b>Antenna gain (dBi)</b>	B77D: 4.3 dBi B25: 4.2 dBi B66: 4.3 dBi
<b>FCC ID</b>	TA8AKRY901523-1 & TA8AKRY901523-2
<b>INDUSTRY CANADA ID</b>	NA



<b>TECHNICAL DESCRIPTION (a brief description of the intended use and operation)</b>	The Dot 4455 B77DB25B66 (KRY 901 523/1) and the Dot 4465 B77DB25B66 (KRY 901 523/2) are Remote Radio Units forming part of the Ericsson Radio Base Station (RBS) equipment. The Dot provides radio access for mobile and fixed devices and is intended for the indoor environment. The radio operates over 8 Transmit ports in MRO (NR+LTE); Single, Multi-Carrier, and MIMO transmission with a maximum rated RF Output up to 0.4W per port over an operational temperature of 5°C to +40°C. The unit is designed to be ceiling or wall mounted. The 4455 and 4465 radios are identical except that Dot 4455 has internal antennas and Dot 4465 has external RF ports.
--	---

**Signature**

**Denis Lalonde**

**Date: 3 November 2022**

**Declaration of Build Status Serial Number: TD3W340089**



## 1.6 PRODUCT INFORMATION

### 1.6.1 Technical Description

The Equipment Under Test (EUT) Dot 4465 B77DB25B66 - KRY 901 523/2 is an Ericsson AB Radio Unit working in the public mobile service Band 77D band which provides communication connections to Band 77D, Band 25, and Band 66 5G networks.

The EUT is declared as operating from a nominal -48V DC supply.

The Equipment Under Test (EUT) is shown in the photograph below. A full technical description can be found in the Manufacturer's documentation.



#### Equipment Under Test






## 1.7 TEST SETUP

### Conducted Test Set Up





### Conducted Test Set Up – Frequency Stability



Dashed line indicates equipment inside the Temperature Chamber for testing



## Test Conditions

For all tests the EUT was set up in accordance with the relevant test standard and to represent typical operating conditions. Tests were applied with the EUT situated as described in the Test Method for each Test.

The EUT was powered from a -54V DC supply unless otherwise stated.

FCC Measurement Facility Registration Number  
CA4810 TUV SUD Canada, 1280 Teron Rd., Kanata On.

Under our A2LA Accreditation, TÜV SÜD Canada conducted the following tests Ericsson, Ottawa Laboratory: 349 Terry Fox Dr, Kanata, ON.

Test Name	Name of Engineer(s)
Maximum Peak Output Power and Peak to Average Ratio - Conducted	Glen Westwell
Occupied Bandwidth	Glen Westwell
Band Edge	Glen Westwell
Transceiver Spurious Emissions	Glen Westwell
Freq. Stab.	Glen Westwell

### 1.8 DEVIATION FROM THE STANDARD

No deviations from the applicable test standards or test plan were made during testing.

### 1.9 MODIFICATION RECORD

The R1A unit under test was modified to be identical to the R1B build of this product

1. The C62T3A8 component was changed
  - a. from a RJC 545 1110/4C, 0.4pF +/-0.1pF 0201 100V HQ C0/CAPACITOR
  - b. To a REG 724 5182/33PJ, 33nH 5% 0201/INDUCTOR
2. The C62T4A8 component was changed
  - a. from a RJC 545 1110/4C, 0.4pF +/-0.1pF 0201 100V HQ C0/CAPACITOR
  - b. To a REG 724 5182/33PJ, 33nH 5% 0201/INDUCTOR
3. Added RF Absorber Material (2/MPP 901 158/2) inside EMC cover

### 1.10 ADDITIONAL INFORMATION

Ericsson will limit this product through the software from operating across the whole of Band 77, it will be limited to Band 77D (3700-3980MHz).

1. This filing is for a Radio Certification for use in the USA under the following ID's:

FCC ID: TA8AKRY901523-1 & TA8AKRY901523-2

2. Transmitter performance was measured for top, mid & bottom channels for contiguous and non-contiguous (NC) operation, where applicable, across all antenna ports as presented in the average power measurement tables. Typical performance is presented. All configuration data is on file and available upon request.



## **SECTION 2**

### **TEST DETAILS**



## **2.1 MAXIMUM PEAK OUTPUT POWER AND PEAK TO AVERAGE RATIO - CONDUCTED**

### **2.1.1 Specification Reference**

FCC CFR 47 Part 27, Clause 27.50  
FCC CFR 47 Part 2, Clause 2.1046

### **2.1.2 Date of Test and Modification State**

04-October-2022 - Modification State 0

### **2.1.3 Test Equipment Used**

The major items of test equipment used for the above tests are identified in Section 3.1.

### **2.1.4 Environmental Conditions**

Ambient Temperature	24.3°C
Relative Humidity	31.0%

### **2.1.5 Test Method**

All measurements were made in accordance with FCC KDB 971168 D01, clause 5.2.1 and summed in accordance with FCC KDB 662911 D01.





## 2.1.6 Test Results

Configuration A

Maximum Output Power 24.00 dBm / Port

Antenna Gain (dBi)	Modulation	Carrier Bandwidth	Peak to Average Ratio (PAR) / Output Power				
			PAR (dB)	Channel Position B			
				Average Power			
Antenna Port				dBm	EIRP (dBm)	dBm/MHz	EIRP dBm/MHz
4.30							
A	NR: QPSK	10.0 MHz	-	23.91	28.21	14.47	18.77
B	NR: QPSK	10.0 MHz	-	23.99	28.29	14.47	18.77
C	NR: QPSK	10.0 MHz	-	24.00	28.30	14.47	18.77
D	NR: QPSK	10.0 MHz	9.65	24.10	28.40	14.47	18.77
Total			-	30.02	34.32	20.49	24.79
A	NR: QPSK	15.0 MHz	-	23.51	27.81	13.66	17.96
B	NR: QPSK	15.0 MHz	-	24.06	28.36	13.66	17.96
C	NR: QPSK	15.0 MHz	-	24.39	28.69	13.66	17.96
D	NR: QPSK	15.0 MHz	9.74	24.38	28.68	13.66	17.96
Total			-	30.12	34.42	19.68	23.98
A	NR: QPSK	20.0 MHz	-	24.21	28.51	12.40	16.70
B	NR: QPSK	20.0 MHz	-	24.09	28.39	12.40	16.70
C	NR: QPSK	20.0 MHz	-	23.50	27.80	12.40	16.70
D	NR: QPSK	20.0 MHz	9.39	23.55	27.85	12.40	16.70
Total			-	29.87	34.17	18.42	22.72
A	NR: QPSK	30.0 MHz	-	23.69	27.99	10.74	15.04
B	NR: QPSK	30.0 MHz	-	23.57	27.87	10.74	15.04
C	NR: QPSK	30.0 MHz	-	23.52	27.82	10.74	15.04
D	NR: QPSK	30.0 MHz	9.26	23.61	27.91	10.74	15.04
Total			-	29.62	33.92	16.76	21.06
A	NR: QPSK	40.0 MHz	-	23.54	27.84	9.28	13.58
B	NR: QPSK	40.0 MHz	-	23.38	27.68	9.28	13.58
C	NR: QPSK	40.0 MHz	-	23.75	28.05	9.28	13.58
D	NR: QPSK	40.0 MHz	9.27	23.86	28.16	9.28	13.58
Total			-	29.66	33.96	15.30	19.60
A	NR: QPSK	50.0 MHz	-	23.81	28.11	8.35	12.65
B	NR: QPSK	50.0 MHz	-	23.80	28.10	8.35	12.65
C	NR: QPSK	50.0 MHz	-	23.86	28.16	8.35	12.65
D	NR: QPSK	50.0 MHz	9.34	23.75	28.05	8.35	12.65
Total			-	29.83	34.13	14.37	18.67
A	NR: QPSK	60.0 MHz	-	23.55	27.85	7.54	11.84
B	NR: QPSK	60.0 MHz	-	23.60	27.90	7.54	11.84
C	NR: QPSK	60.0 MHz	-	23.65	27.95	7.54	11.84
D	NR: QPSK	60.0 MHz	9.37	23.66	27.96	7.54	11.84
Total			-	29.64	33.94	13.56	17.86
A	NR: QPSK	70.0 MHz	-	23.60	27.90	6.94	11.24
B	NR: QPSK	70.0 MHz	-	23.63	27.93	6.94	11.24
C	NR: QPSK	70.0 MHz	-	23.71	28.01	6.94	11.24
D	NR: QPSK	70.0 MHz	9.50	23.86	28.16	6.94	11.24
Total			-	29.72	34.02	12.96	17.26



Antenna Gain (dBi)	Modulation	Carrier Bandwidth	Peak to Average Ratio (PAR) / Output Power				
			Channel Position B				
Antenna Port			PAR (dB)	Average Power			EIRP dBm/MHz
	dBm	EIRP (dBm)		dBm/MHz			
4.30							
A	NR: QPSK	80.0 MHz	-	23.63	27.93	6.14	10.44
B	NR: QPSK	80.0 MHz	-	23.56	27.86	6.14	10.44
C	NR: QPSK	80.0 MHz	-	23.83	28.13	6.14	10.44
D	NR: QPSK	80.0 MHz	9.37	23.90	28.20	6.14	10.44
Total			-	29.75	34.05	12.16	16.46
A	NR: QPSK	90.0 MHz	-	23.60	27.90	5.64	9.94
B	NR: QPSK	90.0 MHz	-	23.65	27.95	5.64	9.94
C	NR: QPSK	90.0 MHz	-	23.75	28.05	5.64	9.94
D	NR: QPSK	90.0 MHz	9.51	23.80	28.10	5.64	9.94
Total			-	29.72	34.02	11.66	15.96
A	NR: QPSK	100.0 MHz	-	23.62	27.92	5.05	9.35
B	NR: QPSK	100.0 MHz	-	23.60	27.90	5.05	9.35
C	NR: QPSK	100.0 MHz	-	23.81	28.11	5.05	9.35
D	NR: QPSK	100.0 MHz	9.47	23.85	28.15	5.05	9.35
Total			-	29.74	34.04	11.07	15.37



Antenna Gain (dBi)	Modulation	Carrier Bandwidth	Peak to Average Ratio (PAR) / Output Power					
			Antenna Port	PAR (dB)	Channel Position M			
					Average Power			
4.30				dBm	EIRP (dBm)	dBm/MHz	EIRP dBm/MHz	
A	NR: QPSK	10.0 MHz	-	24.16	28.46	14.78	19.08	
B	NR: QPSK	10.0 MHz	-	24.08	28.38	14.78	19.08	
C	NR: QPSK	10.0 MHz	-	24.18	28.48	14.78	19.08	
D	NR: QPSK	10.0 MHz	9.56	24.22	28.52	14.78	19.08	
Total			-	30.18	34.48	20.80	25.10	
A	NR: QPSK	15.0 MHz	-	24.23	28.53	13.52	17.82	
B	NR: QPSK	15.0 MHz	-	24.35	28.65	13.52	17.82	
C	NR: QPSK	15.0 MHz	-	24.46	28.76	13.52	17.82	
D	NR: QPSK	15.0 MHz	9.98	24.45	28.75	13.52	17.82	
Total			-	30.39	34.69	19.54	23.84	
A	NR: QPSK	20.0 MHz	-	23.51	27.81	12.14	16.44	
B	NR: QPSK	20.0 MHz	-	23.68	27.98	12.14	16.44	
C	NR: QPSK	20.0 MHz	-	23.59	27.89	12.14	16.44	
D	NR: QPSK	20.0 MHz	9.53	24.36	28.66	12.14	16.44	
Total			-	29.82	34.12	18.16	22.46	
A	NR: QPSK	30.0 MHz	-	23.42	27.72	10.47	14.77	
B	NR: QPSK	30.0 MHz	-	23.74	28.04	10.47	14.77	
C	NR: QPSK	30.0 MHz	-	23.89	28.19	10.47	14.77	
D	NR: QPSK	30.0 MHz	9.71	23.91	28.21	10.47	14.77	
Total			-	29.76	34.06	16.49	20.79	
A	NR: QPSK	40.0 MHz	-	23.77	28.07	9.09	13.39	
B	NR: QPSK	40.0 MHz	-	23.91	28.21	9.09	13.39	
C	NR: QPSK	40.0 MHz	-	23.94	28.24	9.09	13.39	
D	NR: QPSK	40.0 MHz	9.33	23.82	28.12	9.09	13.39	
Total			-	29.88	34.18	15.11	19.41	
A	NR: QPSK	50.0 MHz	-	23.82	28.12	8.10	12.40	
B	NR: QPSK	50.0 MHz	-	23.81	28.11	8.10	12.40	
C	NR: QPSK	50.0 MHz	-	23.95	28.25	8.10	12.40	
D	NR: QPSK	50.0 MHz	9.50	23.87	28.17	8.10	12.40	
Total			-	29.88	34.18	14.12	18.42	
A	NR: QPSK	60.0 MHz	-	23.62	27.92	7.33	11.63	
B	NR: QPSK	60.0 MHz	-	23.67	27.97	7.33	11.63	
C	NR: QPSK	60.0 MHz	-	23.70	28.00	7.33	11.63	
D	NR: QPSK	60.0 MHz	9.33	23.69	27.99	7.33	11.63	
Total			-	29.69	33.99	13.35	17.65	
A	NR: QPSK	70.0 MHz	-	23.63	27.93	6.69	10.99	
B	NR: QPSK	70.0 MHz	-	23.62	27.92	6.69	10.99	
C	NR: QPSK	70.0 MHz	-	23.74	28.04	6.69	10.99	
D	NR: QPSK	<b>70.0 MHz</b>	9.62	23.79	28.09	6.69	10.99	
Total			-	29.72	34.02	12.71	17.01	
A	NR: QPSK	80.0 MHz	-	23.68	27.98	5.91	10.21	
B	NR: QPSK	80.0 MHz	-	23.69	27.99	5.91	10.21	
C	NR: QPSK	80.0 MHz	-	23.77	28.07	5.91	10.21	
D	NR: QPSK	80.0 MHz	9.54	23.80	28.10	5.91	10.21	
Total			-	29.76	34.06	11.93	16.23	



Antenna Gain (dBi)	Modulation	Carrier Bandwidth	Peak to Average Ratio (PAR) / Output Power				
			Channel Position M				
Antenna Port			PAR (dB)	Average Power			
	dBm	EIRP (dBm)		dBm/MHz	EIRP dBm/MHz		
4.30							
A	NR: QPSK	90.0 MHz	-	23.66	27.96	5.42	9.72
B	NR: QPSK	90.0 MHz	-	23.66	27.96	5.42	9.72
C	NR: QPSK	90.0 MHz	-	23.71	28.01	5.42	9.72
D	NR: QPSK	90.0 MHz	9.42	23.81	28.11	5.42	9.72
Total			-	29.73	34.03	11.44	15.74
A	NR: QPSK	100.0 MHz	-	23.53	27.83	4.94	9.24
B	NR: QPSK	100.0 MHz	-	23.58	27.88	4.94	9.24
C	NR: QPSK	100.0 MHz	-	23.78	28.08	4.94	9.24
D	NR: QPSK	100.0 MHz	9.45	23.73	28.03	4.94	9.24
Total			-	29.68	33.98	10.96	15.26



Antenna Gain (dBi)	Modulation	Carrier Bandwidth	Peak to Average Ratio (PAR) / Output Power				
			Channel Position T				
			PAR (dB)	Average Power			
dBm	EIRP (dBm)	dBm/MHz		EIRP dBm/MHz			
4.30							
Antenna Port							
A	NR: QPSK	10.0 MHz	-	23.87	28.17	14.95	19.25
B	NR: QPSK	10.0 MHz	-	23.76	28.06	14.95	19.25
C	NR: QPSK	10.0 MHz	-	23.99	28.29	14.95	19.25
D	NR: QPSK	10.0 MHz	9.69	24.07	28.37	14.95	19.25
Total			-	29.94	34.24	20.97	25.27
A	NR: QPSK	15.0 MHz	-	24.21	28.51	13.84	18.14
B	NR: QPSK	15.0 MHz	-	24.85	29.15	13.84	18.14
C	NR: QPSK	15.0 MHz	-	24.15	28.45	13.84	18.14
D	NR: QPSK	15.0 MHz	9.62	23.86	28.16	13.84	18.14
Total			-	30.30	34.60	19.86	24.16
A	NR: QPSK	20.0 MHz	-	23.75	28.05	12.65	16.95
B	NR: QPSK	20.0 MHz	-	23.70	28.00	12.65	16.95
C	NR: QPSK	20.0 MHz	-	23.67	27.97	12.65	16.95
D	NR: QPSK	20.0 MHz	9.31	24.44	28.74	12.65	16.95
Total			-	29.92	34.22	18.67	22.97
A	NR: QPSK	30.0 MHz	-	23.66	27.96	10.77	15.07
B	NR: QPSK	30.0 MHz	-	23.60	27.90	10.77	15.07
C	NR: QPSK	30.0 MHz	-	23.73	28.03	10.77	15.07
D	NR: QPSK	30.0 MHz	9.73	23.82	28.12	10.77	15.07
Total			-	29.72	34.02	16.79	21.09
A	NR: QPSK	40.0 MHz	-	23.76	28.06	9.70	14.00
B	NR: QPSK	40.0 MHz	-	23.88	28.18	9.70	14.00
C	NR: QPSK	40.0 MHz	-	23.86	28.16	9.70	14.00
D	NR: QPSK	40.0 MHz	9.63	23.98	28.28	9.70	14.00
Total			-	29.89	34.19	15.72	20.02
A	NR: QPSK	50.0 MHz	-	23.73	28.03	8.63	12.93
B	NR: QPSK	50.0 MHz	-	23.52	27.82	8.63	12.93
C	NR: QPSK	50.0 MHz	-	23.78	28.08	8.63	12.93
D	NR: QPSK	50.0 MHz	9.38	23.92	28.22	8.63	12.93
Total			-	29.76	34.06	14.65	18.95
A	NR: QPSK	60.0 MHz	-	23.60	27.90	8.16	12.46
B	NR: QPSK	60.0 MHz	-	23.69	27.99	8.16	12.46
C	NR: QPSK	60.0 MHz	-	23.68	27.98	8.16	12.46
D	NR: QPSK	60.0 MHz	9.51	23.96	28.26	8.16	12.46
Total			-	29.76	34.06	14.18	18.48
A	NR: QPSK	70.0 MHz	-	23.53	27.83	7.52	11.82
B	NR: QPSK	70.0 MHz	-	23.59	27.89	7.52	11.82
C	NR: QPSK	70.0 MHz	-	23.68	27.98	7.52	11.82
D	NR: QPSK	70.0 MHz	9.28	23.96	28.26	7.52	11.82
Total			-	29.71	34.01	13.54	17.84
A	NR: QPSK	80.0 MHz	-	23.59	27.89	6.78	11.08
B	NR: QPSK	80.0 MHz	-	23.61	27.91	6.78	11.08
C	NR: QPSK	80.0 MHz	-	23.73	28.03	6.78	11.08
D	NR: QPSK	80.0 MHz	9.24	23.96	28.26	6.78	11.08
Total			-	29.75	34.05	12.80	17.10



Antenna Gain (dBi)	Modulation	Carrier Bandwidth	Peak to Average Ratio (PAR) / Output Power				
			Channel Position M				
Antenna Port			PAR (dB)	Average Power			
	dBm	EIRP (dBm)		dBm/MHz	EIRP dBm/MHz		
4.30							
A	NR: QPSK	90.0 MHz	-	23.47	27.77	6.19	10.49
B	NR: QPSK	90.0 MHz	-	23.48	27.78	6.19	10.49
C	NR: QPSK	90.0 MHz	-	23.63	27.93	6.19	10.49
D	NR: QPSK	90.0 MHz	9.63	23.84	28.14	6.19	10.49
Total			-	29.63	33.93	12.21	16.51
A	NR: QPSK	100.0 MHz	-	23.56	27.86	5.59	9.89
B	NR: QPSK	100.0 MHz	-	23.59	27.89	5.59	9.89
C	NR: QPSK	100.0 MHz	-	23.71	28.01	5.59	9.89
D	NR: QPSK	100.0 MHz	9.25	23.90	28.20	5.59	9.89
Total			-	29.71	34.01	11.61	15.91



Remarks


1. Transmitter performance has been presented for top, mid, bottom channels across all antenna ports as represented in the following tables.
2. Typical performance and measurement plot data has been presented for reference.
3. All contiguous and non-contiguous (NC) plot data is on file and available upon request.

Antenna Port D Carrier Power - Modulation NR: QPSK - Carrier Bandwidth 10.0 MHz - Channel Position B





Antenna Port D Pk-Av Ratio - Modulation NR: QPSK - Carrier Bandwidth 10.0 MHz - Channel Position B







Antenna Port D PSD - Modulation NR: QPSK - Carrier Bandwidth 10.0 MHz - Channel Position B




Antenna Port D Carrier Power - Modulation NR: QPSK - Carrier Bandwidth 15.0 MHz - Channel Position B





Antenna Port D Pk-Av Ratio - Modulation NR: QPSK - Carrier Bandwidth 15.0 MHz - Channel Position B



Antenna Port D PSD - Modulation NR: QPSK - Carrier Bandwidth 15.0 MHz - Channel Position B






Antenna Port D Carrier Power - Modulation NR: QPSK - Carrier Bandwidth 20.0 MHz - Channel Position B



Antenna Port D Pk-Av Ratio - Modulation NR: QPSK - Carrier Bandwidth 20.0 MHz - Channel Position B






Antenna Port D PSD - Modulation NR: QPSK - Carrier Bandwidth 20.0 MHz - Channel Position B




Antenna Port D Carrier Power - Modulation NR: QPSK - Carrier Bandwidth 30.0 MHz - Channel Position B





Antenna Port D Pk-Av Ratio - Modulation NR: QPSK - Carrier Bandwidth 30.0 MHz - Channel Position B




Antenna Port D PSD - Modulation NR: QPSK - Carrier Bandwidth 30.0 MHz - Channel Position B






Antenna Port D Carrier Power - Modulation NR: QPSK - Carrier Bandwidth 40.0 MHz - Channel Position B



Antenna Port D Pk-Av Ratio - Modulation NR: QPSK - Carrier Bandwidth 40.0 MHz - Channel Position B





Antenna Port D PSD - Modulation NR: QPSK - Carrier Bandwidth 40.0 MHz - Channel Position B




Antenna Port D Carrier Power - Modulation NR: QPSK - Carrier Bandwidth 50.0 MHz - Channel Position B






Antenna Port D Pk-Av Ratio - Modulation NR: QPSK - Carrier Bandwidth 50.0 MHz - Channel Position B




Antenna Port D PSD - Modulation NR: QPSK - Carrier Bandwidth 50.0 MHz - Channel Position B








Antenna Port D Carrier Power - Modulation NR: QPSK - Carrier Bandwidth 60.0 MHz - Channel Position B



Antenna Port D Pk-Av Ratio - Modulation NR: QPSK - Carrier Bandwidth 60.0 MHz - Channel Position B





Antenna Port D PSD - Modulation NR: QPSK - Carrier Bandwidth 60.0 MHz - Channel Position B



Antenna Port D Carrier Power - Modulation NR: QPSK - Carrier Bandwidth 70.0 MHz - Channel Position B





Antenna Port D Pk-Av Ratio - Modulation NR: QPSK - Carrier Bandwidth 70.0 MHz - Channel Position B




Antenna Port D PSD - Modulation NR: QPSK - Carrier Bandwidth 70.0 MHz - Channel Position B






Antenna Port D Carrier Power - Modulation NR: QPSK - Carrier Bandwidth 80.0 MHz - Channel Position B



Antenna Port D Pk-Av Ratio - Modulation NR: QPSK - Carrier Bandwidth 80.0 MHz - Channel Position B





Antenna Port D PSD - Modulation NR: QPSK - Carrier Bandwidth 80.0 MHz - Channel Position B




Antenna Port D Carrier Power - Modulation NR: QPSK - Carrier Bandwidth 90.0 MHz - Channel Position B





Antenna Port D Pk-Av Ratio - Modulation NR: QPSK - Carrier Bandwidth 90.0 MHz - Channel Position B



Antenna Port D PSD - Modulation NR: QPSK - Carrier Bandwidth 90.0 MHz - Channel Position B






Antenna Port D Carrier Power - Modulation NR: QPSK - Carrier Bandwidth 100.0 MHz - Channel Position B



Antenna Port D Pk-Av Ratio - Modulation NR: QPSK - Carrier Bandwidth 100.0 MHz - Channel Position B





Antenna Port D PSD - Modulation NR: QPSK - Carrier Bandwidth 100.0 MHz - Channel Position B







## Configuration B

Maximum Output Power 26.00 dBm / Port

Antenna Gain (dBi)	Antenna Port	Modulation	Carrier Bandwidth	Output Power		Output Power		Output Power	
				Channel Position B		Channel Position M		Channel Position T	
				Average Power (dBm)		Average Power (dBm)		Average Power (dBm)	
				dBm	EIRP (dBm)	dBm	EIRP (dBm)	dBm	EIRP (dBm)
4.30									
	A	NR10: QPSK	NR10.0+NR10.0 MHz	25.98	30.28	26.10	30.40	26.19	30.49
	B	NR10: QPSK	NR10.0+NR10.0 MHz	25.94	30.24	26.20	30.50	26.18	30.48
	C	NR10: QPSK	NR10.0+NR10.0 MHz	26.03	30.33	26.33	30.63	26.16	30.46
	D	NR10: QPSK	NR10.0+NR10.0 MHz	26.21	30.51	26.20	30.50	26.28	30.58
	Total			32.06	36.36	32.23	36.53	32.22	36.52
	A	NR100: QPSK	NR100.0+NR100.0 MHz	25.58	29.88	25.35	29.65	25.31	29.61
	B	NR100: QPSK	NR100.0+NR100.0 MHz	25.49	29.79	25.36	29.66	25.39	29.69
	C	NR100: QPSK	NR100.0+NR100.0 MHz	25.62	29.92	25.54	29.84	25.38	29.68
	D	NR100: QPSK	NR100.0+NR100.0 MHz	25.43	29.73	25.54	29.84	25.47	29.77
	Total			31.55	35.85	31.47	35.77	31.41	35.71
	A	NR10: QPSK (NC)	NR10.0+NR10.0 MHz	25.31	29.61	25.25	29.55	25.63	29.93
	B	NR10: QPSK (NC)	NR10.0+NR10.0 MHz	25.35	29.65	25.46	29.76	25.41	29.71
	C	NR10: QPSK (NC)	NR10.0+NR10.0 MHz	25.47	29.77	25.71	30.01	25.59	29.89
	D	NR10: QPSK (NC)	NR10.0+NR10.0 MHz	25.49	29.79	25.72	30.02	25.56	29.86
	Total			31.43	35.73	31.56	35.86	31.57	35.87
	A	NR90: QPSK (NC)	NR90.0+NR90.0 MHz	25.36	29.66	25.28	29.58	25.42	29.72
	B	NR90: QPSK (NC)	NR90.0+NR90.0 MHz	25.14	29.44	25.49	29.79	25.40	29.70
	C	NR90: QPSK (NC)	NR90.0+NR90.0 MHz	25.45	29.75	25.59	29.89	25.70	30.00
	D	NR90: QPSK (NC)	NR90.0+NR90.0 MHz	25.64	29.94	25.68	29.98	25.73	30.03
	Total			31.42	35.72	31.53	35.83	31.59	35.89

### Remarks


1. The table results are measured at all antenna ports. 2. The plot results represent typical radio performance across all channels. 3. Plot data performance for all transmitter ports and channels for both contiguous and non-contiguous (NC) operation are available on request.



Antenna Port D Carrier Power - Modulation NR10: QPSK - Carrier Bandwidth NR10.0+NR10.0 MHz - Channel Position M




Antenna Port D Carrier Power - Modulation NR100: QPSK - Carrier Bandwidth NR100.0+NR100.0 MHz - Channel Position M






Antenna Port D Carrier Power - Modulation NR10: QPSK (NC) - Carrier Bandwidth NR10.0+NR10.0 MHz - Channel Position M



Antenna Port D Carrier Power - Modulation NR90: QPSK (NC) - Carrier Bandwidth NR90.0+NR90.0 MHz - Channel Position M





Configuration C

Maximum Output Power 26.00 dBm / Port


Antenna Gain (dBi)	Modulation	Carrier Bandwidth	Output Power		Output Power		Output Power	
			Channel Position B		Channel Position M		Channel Position T	
			Average Power (dBm)		Average Power (dBm)		Average Power (dBm)	
			dBm	EIRP (dBm)	dBm	EIRP (dBm)	dBm	EIRP (dBm)
4.30								
Antenna Port								
A	NR10: QPSK	10+10+10+10+10+10 MHz	25.79	30.09	25.88	30.18	25.93	30.23
B	NR10: QPSK	10+10+10+10+10+10 MHz	25.82	30.12	25.98	30.28	26.01	30.31
C	NR10: QPSK	10+10+10+10+10+10 MHz	25.90	30.20	25.90	30.20	26.16	30.46
D	NR10: QPSK	10+10+10+10+10+10 MHz	26.09	30.39	25.92	30.22	26.31	30.61
Total			31.92	36.22	31.94	36.24	32.13	36.43
A	NR20: QPSK	20+20+20+20+20+20 MHz	25.39	29.69	25.44	29.74	25.46	29.76
B	NR20: QPSK	20+20+20+20+20+20 MHz	25.39	29.69	25.65	29.95	25.48	29.78
C	NR20: QPSK	20+20+20+20+20+20 MHz	25.82	30.12	25.65	29.95	25.61	29.91
D	NR20: QPSK	20+20+20+20+20+20 MHz	25.73	30.03	25.72	30.02	25.79	30.09
Total			31.61	35.91	31.64	35.94	31.61	35.91
A	NR10: QPSK (NC)	10+10+10+10+10+10 MHz	25.30	29.60	25.47	29.77	25.73	30.03
B	NR10: QPSK (NC)	10+10+10+10+10+10 MHz	25.39	29.69	25.54	29.84	25.60	29.90
C	NR10: QPSK (NC)	10+10+10+10+10+10 MHz	25.50	29.80	25.79	30.09	25.66	29.96
D	NR10: QPSK (NC)	10+10+10+10+10+10 MHz	25.52	29.82	25.76	30.06	25.68	29.98
Total			31.45	35.75	31.66	35.96	31.69	35.99
A	NR20: QPSK (NC)	20+20+20+20+20+20 MHz	25.39	29.69	25.43	29.73	25.43	29.73
B	NR20: QPSK (NC)	20+20+20+20+20+20 MHz	25.31	29.61	25.49	29.79	25.29	29.59
C	NR20: QPSK (NC)	20+20+20+20+20+20 MHz	25.17	29.47	25.36	29.66	25.84	30.14
D	NR20: QPSK (NC)	20+20+20+20+20+20 MHz	25.44	29.74	26.23	30.53	25.76	30.06
Total			31.35	35.65	31.66	35.96	31.61	35.91

Remarks


1. The table results are measured at all antenna ports. 2. The plot results represent typical radio performance across all channels. 3. Plot data performance for all transmitter ports and channels for both contiguous and non-contiguous (NC) operation are available on request.



Antenna Port D Carrier Power - Modulation NR10: QPSK - Carrier Bandwidth 10+10+10+10+10+10 MHz - Channel Position M




Antenna Port D Carrier Power - Modulation NR20: QPSK - Carrier Bandwidth 20+20+20+20+20+20 MHz - Channel Position M






Antenna Port D Carrier Power - Modulation NR10: QPSK (NC) - Carrier Bandwidth 10+10+10+10+10+10 MHz - Channel Position M



Antenna Port D Carrier Power - Modulation NR20: QPSK (NC) - Carrier Bandwidth 20+20+20+20+20+20 MHz - Channel Position M





## 2.2 OCCUPIED BANDWIDTH

### 2.2.1 Specification Reference

FCC CFR 47 Part 27, Clause 27.53  
 FCC CFR 47 Part 2, Clause 2.1049

### 2.2.2 Date of Test and Modification State

04-October-2022 - Modification State 0

### 2.2.3 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

### 2.2.4 Environmental Conditions

Ambient Temperature 24.3°C  
 Relative Humidity 31.0%

### 2.2.5 Test Method

All measurements were made in accordance with FCC KDB 971168 D01, Clause 4.2 and 4.3. The Spectrum Analyser RBW was configured to be at least 1% of the channel bandwidth of the carrier to be measured.

### 2.2.6 Test Results

Configuration A

Maximum Output Power 24.00 dBm / Port


Modulation	Carrier Bandwidth	Result (MHz)
		Channel Bandwidth
		99% Occupied Bandwidth
NR: QPSK	NR: 10.0 MHz	8.6295
NR: QPSK	NR: 15.0 MHz	13.5740
NR: QPSK	NR: 20.0 MHz	18.2270
NR: QPSK	NR: 30.0 MHz	27.9080
NR: QPSK	NR: 40.0 MHz	37.8150
NR: QPSK	NR: 50.0 MHz	47.4010
NR: QPSK	NR: 60.0 MHz	57.7540
NR: QPSK	NR: 70.0 MHz	67.3930
NR: QPSK	NR: 80.0 MHz	77.2850
NR: QPSK	NR: 90.0 MHz	87.2510
NR: QPSK	NR: 100.0 MHz	97.2410

#### Remarks


Representative occupied bandwidth performance results presented. Plot data performance for all transmitter ports and channel positions are on file and available on request.



Antenna D - Modulation NR: QPSK - LTE Carrier Bandwidth NR: 10.0 MHz - Channel Position B




Antenna D - Modulation NR: QPSK - LTE Carrier Bandwidth NR: 15.0 MHz - Channel Position B








Antenna D - Modulation NR: QPSK - LTE Carrier Bandwidth NR: 20.0 MHz - Channel Position B




Antenna D - Modulation NR: QPSK - LTE Carrier Bandwidth NR: 30.0 MHz - Channel Position B






Antenna D - Modulation NR: QPSK - LTE Carrier Bandwidth NR: 40.0 MHz - Channel Position B




Antenna D - Modulation NR: QPSK - LTE Carrier Bandwidth NR: 50.0 MHz - Channel Position B






Antenna D - Modulation NR: QPSK - LTE Carrier Bandwidth NR: 60.0 MHz - Channel Position B




Antenna D - Modulation NR: QPSK - LTE Carrier Bandwidth NR: 70.0 MHz - Channel Position B






Antenna D - Modulation NR: QPSK - LTE Carrier Bandwidth NR: 80.0 MHz - Channel Position B




Antenna D - Modulation NR: QPSK - LTE Carrier Bandwidth NR: 90.0 MHz - Channel Position B





Antenna D - Modulation NR: QPSK - LTE Carrier Bandwidth NR: 100.0 MHz - Channel Position B





## **2.3 BAND EDGE**

### **2.3.1 Specification Reference**

FCC CFR 47 Part 27, Clause 27.53  
FCC CFR 47 Part 2, Clause 2.1051

### **2.3.2 Date of Test and Modification State**

04-October-2022 - Modification State 0

### **2.3.3 Test Equipment Used**

The major items of test equipment used for the above tests are identified in Section 3.1.

### **2.3.4 Environmental Conditions**

Ambient Temperature 24.3°C  
Relative Humidity 31.0%

### **2.3.5 Test Method**

All measurements were made in accordance with FCC KDB 971168 D01, Clause 6.0.

Band Edge measurements were done using an Integration Bandwidth of 1% or greater of the measured 26dB Bandwidth.

All 4 antenna ports have been declared as being equivalent, therefore measurements were made on one antenna port only (worst-case). To account for this, the limit was integrated by  $10 * \text{Log}(N)$ , where N is equal to the number of MIMO antenna ports as per below.

For multi-port, the limit was calculated as being  $-13 \text{ dBm} - 10 * \text{Log}(4) = -19 \text{ dBm}$ .

### **2.3.6 Test Results**

Configuration A

Maximum Output Power 24.00 dBm / Port




Antenna Port A	Modulation	Carrier Bandwidth	Band Edge (MHz)	
			Channel Position B	Channel Position T
A	NR: QPSK	NR: 10.0 MHz	3,705.0	3,840.0
A	NR: QPSK	NR: 15.0 MHz	3,707.5	3,972.5
A	NR: QPSK	NR: 20.0 MHz	3,710.0	3,970.0
A	NR: QPSK	NR: 30.0 MHz	3,715.0	3,965.0
A	NR: QPSK	NR: 40.0 MHz	3,720.0	3,960.0
A	NR: QPSK	NR: 50.0 MHz	3,725.0	3,955.0
A	NR: QPSK	NR: 60.0 MHz	3,730.0	3,950.0
A	NR: QPSK	NR: 70.0 MHz	3,735.0	3,945.0
A	NR: QPSK	NR: 80.0 MHz	3,740.0	3,940.0
A	NR: QPSK	NR: 90.0 MHz	3,745.0	3,935.0
A	NR: QPSK	NR: 100.0 MHz	3,750.0	3,930.0

Remarks

1. Bandedge data was captured from the transmit port with maximum measured power. 2. Worst case bandedge data presented.



Antenna Port D - Modulation NR: QPSK - Carrier Bandwidth NR: 10.0 MHz - Channel Position B




Antenna Port D - Modulation NR: QPSK - Carrier Bandwidth NR: 10.0 MHz - Channel Position T







Antenna Port D - Modulation NR: QPSK - Carrier Bandwidth NR: 15.0 MHz - Channel Position B




Antenna Port D - Modulation NR: QPSK - Carrier Bandwidth NR: 15.0 MHz - Channel Position T





Antenna Port D - Modulation NR: QPSK - Carrier Bandwidth NR: 20.0 MHz - Channel Position B



Antenna Port D - Modulation NR: QPSK - Carrier Bandwidth NR: 20.0 MHz - Channel Position T





Antenna Port D - Modulation NR: QPSK - Carrier Bandwidth NR: 30.0 MHz - Channel Position B




Antenna Port D - Modulation NR: QPSK - Carrier Bandwidth NR: 30.0 MHz - Channel Position T





Antenna Port D - Modulation NR: QPSK - Carrier Bandwidth NR: 40.0 MHz - Channel Position B



Antenna Port D - Modulation NR: QPSK - Carrier Bandwidth NR: 40.0 MHz - Channel Position T





Antenna Port D - Modulation NR: QPSK - Carrier Bandwidth NR: 50.0 MHz - Channel Position B



Antenna Port D - Modulation NR: QPSK - Carrier Bandwidth NR: 50.0 MHz - Channel Position T





Antenna Port D - Modulation NR: QPSK - Carrier Bandwidth NR: 60.0 MHz - Channel Position B



Antenna Port D - Modulation NR: QPSK - Carrier Bandwidth NR: 60.0 MHz - Channel Position T





Antenna Port D - Modulation NR: QPSK - Carrier Bandwidth NR: 70.0 MHz - Channel Position B



Antenna Port D - Modulation NR: QPSK - Carrier Bandwidth NR: 70.0 MHz - Channel Position T





Antenna Port D - Modulation NR: QPSK - Carrier Bandwidth NR: 80.0 MHz - Channel Position B



Antenna Port D - Modulation NR: QPSK - Carrier Bandwidth NR: 80.0 MHz - Channel Position T







Antenna Port D - Modulation NR: QPSK - Carrier Bandwidth NR: 90.0 MHz - Channel Position B



Antenna Port D - Modulation NR: QPSK - Carrier Bandwidth NR: 90.0 MHz - Channel Position T






Antenna Port D - Modulation NR: QPSK - Carrier Bandwidth NR: 100.0 MHz - Channel Position B



Antenna Port D - Modulation NR: QPSK - Carrier Bandwidth NR: 100.0 MHz - Channel Position T





Configuration B

Maximum Output Power 26.00 dBm / Port

Antenna	Modulation	Carrier Bandwidth	Band Edge (MHz)	
			Channel Position B	Channel Position T
A	NR10: QPSK	NR10.0+NR10.0 MHz	3705.0+3715.0	3965.0+3975.0
A	NR100: QPSK	NR100.0+NR100.0 MHz	3750.0+3850.0	3830.0+3930.0
A	NR10: QPSK (NC)	NR10.0+NR10.0 MHz	3705.0+3895.0	3785.0+3975.0
A	NR90: QPSK (NC)	NR90.0+NR90.0 MHz	3745.0+3855.0	3825.0+3935.0

Remarks

The plot results represent typical radio performance.



Antenna Port A A - Modulation NR10: QPSK - Carrier Bandwidth NR10.0+NR10.0 MHz - Channel Position B




Antenna Port A A - Modulation NR10: QPSK - Carrier Bandwidth NR10.0+NR10.0 MHz - Channel Position T






Antenna Port A A - Modulation NR100: QPSK - Carrier Bandwidth NR100.0+NR100.0 MHz - Channel Position B



Antenna Port A A - Modulation NR100: QPSK - Carrier Bandwidth NR100.0+NR100.0 MHz - Channel Position T






Antenna Port A A - Modulation NR10: QPSK (NC) - Carrier Bandwidth NR10.0+NR10.0 MHz - Channel Position B



Antenna Port A A - Modulation NR10: QPSK (NC) - Carrier Bandwidth NR10.0+NR10.0 MHz - Channel Position T





Antenna Port A A - Modulation NR90: QPSK (NC) - Carrier Bandwidth NR90.0+NR90.0 MHz - Channel Position B



Antenna Port A A - Modulation NR90: QPSK (NC) - Carrier Bandwidth NR90.0+NR90.0 MHz - Channel Position T





Configuration C

Maximum Output Power 26.00 dBm / Port

Antenna	Modulation	Carrier Bandwidth	Band Edge (MHz)	
			Channel Position B	Channel Position T
D	NR10: QPSK	10+10+10+10+10+10 MHz	3705+3715+3725+3735+3745+3755	3925+3935+3945+3955+3965+3975
D	NR20: QPSK	20+20+20+20+20+20 MHz	3710+3730+3750+3770+3790+3810	3870+3890+3910+3930+3950+3970
D	NR10: QPSK (NC)	10+10+10+10+10+10 MHz	3705+3715+3725+3775+3785+3795	3885+3895+3905+3955+3965+3975
D	NR20: QPSK (NC)	20+20+20+20+20+20 MHz	3710+3730+3750+3850+3870+3890	3790+3810+3830+3930+3950+3970


Antenna Port A D - Modulation NR10: QPSK - Carrier Bandwidth 10+10+10+10+10+10 MHz - Channel Position B







Antenna Port A D - Modulation NR10: QPSK - Carrier Bandwidth 10+10+10+10+10+10 MHz - Channel Position T





Antenna Port A D - Modulation NR20: QPSK - Carrier Bandwidth 20+20+20+20+20 MHz - Channel Position B



Antenna Port A D - Modulation NR20: QPSK - Carrier Bandwidth 20+20+20+20+20 MHz - Channel Position T





Antenna Port A D - Modulation NR10: QPSK (NC) - Carrier Bandwidth 10+10+10+10+10 MHz - Channel Position B




Antenna Port A D - Modulation NR10: QPSK (NC) - Carrier Bandwidth 10+10+10+10+10 MHz - Channel Position T






Antenna Port A D - Modulation NR20: QPSK (NC) - Carrier Bandwidth 20+20+20+20+20+20 MHz - Channel Position B



Antenna Port A D - Modulation NR20: QPSK (NC) - Carrier Bandwidth 20+20+20+20+20+20 MHz - Channel Position T



Limit	-19 dBm
-------	---------



## 2.4 TRANSMITTER SPURIOUS EMISSIONS

### 2.4.1 Specification Reference

FCC CFR 47 Part 27, Clause 27.53  
FCC CFR 47 Part 2, Clause 2.1051

### 2.4.2 Date of Test and Modification State

05-October-2022 - Modification State 0

### 2.4.3 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

### 2.4.4 Environmental Conditions

Ambient Temperature 23.9°C  
Relative Humidity 32.0%

### 2.4.5 Test Method

All measurements were made in accordance with FCC KDB 971168 D01, Clause 6.1.

All 4 antenna ports have been declared as being equivalent, therefore measurements were made on one antenna port only (worst-case). To account for this, the limit was integrated by  $10 * \text{Log}(N)$ , where N is equal to the number of MIMO antenna ports as per below.

For multi-port, the limit was calculated as being  $-13 \text{ dBm} - 10 * \text{Log}(4) = -19 \text{ dBm}$ .

### 2.4.6 Test Results

Configuration A


Maximum Output Power 24.00 dBm / Port

#### Remarks


1. Transceiver spurious emissions have been searched for all channel bandwidths and antenna ports.
2. Representative spurious emissions performance using the worst-case channel bandwidth has been presented for all modulations.
3. Plot data performance for all channel bandwidths, and channel positions for both contiguous and non-contiguous (NC) operation are on file and available on request.



Antenna D - Modulation NR: QPSK - Carrier Bandwidth 20.0 MHz - Channel Position M - Band 1 - Range 0.009 to 4000 MHz



Antenna D - Modulation NR: QPSK - Carrier Bandwidth 20.0 MHz - Channel Position M - Band 2 - Range 4000 to 12000 MHz





Antenna D - Modulation NR: QPSK - Carrier Bandwidth 20.0 MHz - Channel Position M - Band 3 - Range 12000 to 18000 MHz



Antenna D - Modulation NR: QPSK - Carrier Bandwidth 20.0 MHz - Channel Position M - Band 4 - Range 18000 to 39800 MHz





## Configuration B

Maximum Output Power 26.00 dBm / Port


### Remarks

1. Transceiver spurious emissions have been searched for all channel bandwidths and antenna ports.
2. Representative spurious emissions performance using the worst-case channel bandwidth has been presented for all modulations.
3. Plot data performance for all channel bandwidths, and channel positions for both contiguous and non-contiguous (NC) operation are on file and available on request.






Antenna A - Modulation NR10: QPSK - Carrier Bandwidth NR10.0+NR10.0 MHz - Channel Position B - Band 1 - Range 0.009 to 4000 MHz



Antenna A - Modulation NR10: QPSK - Carrier Bandwidth NR10.0+NR10.0 MHz - Channel Position B - Band 2 - Range 4000 to 12000 MHz






Antenna A - Modulation NR10: QPSK - Carrier Bandwidth NR10.0+NR10.0 MHz - Channel Position B - Band 3 - Range 12000 to 22000 MHz



Antenna A - Modulation NR10: QPSK - Carrier Bandwidth NR10.0+NR10.0 MHz - Channel Position B - Band 4 - Range 22000 to 39800 MHz






Antenna A - Modulation NR10: QPSK (NC) - Carrier Bandwidth NR10.0+NR10.0 MHz - Channel Position B - Band 1 - Range 0.009 to 4000 MHz




Antenna A - Modulation NR10: QPSK (NC) - Carrier Bandwidth NR10.0+NR10.0 MHz - Channel Position B - Band 2 - Range 4000 to 12000 MHz






Antenna A - Modulation NR10: QPSK (NC) - Carrier Bandwidth NR10.0+NR10.0 MHz - Channel Position B - Band 3 - Range 12000 to 22000 MHz




Antenna A - Modulation NR10: QPSK (NC) - Carrier Bandwidth NR10.0+NR10.0 MHz - Channel Position B - Band 4 - Range 22000 to 39800 MHz






Antenna A - Modulation NR10: QPSK (NC) - Carrier Bandwidth NR10.0+NR10.0 MHz - Channel Position B - Band 1 - Range 0.009 to 4000 MHz




Antenna A - Modulation NR10: QPSK (NC) - Carrier Bandwidth NR10.0+NR10.0 MHz - Channel Position B - Band 2 - Range 4000 to 12000 MHz





Antenna A - Modulation NR10: QPSK (NC) - Carrier Bandwidth NR10.0+NR10.0 MHz - Channel Position B - Band 3 - Range 12000 to 22000 MHz



Antenna A - Modulation NR10: QPSK (NC) - Carrier Bandwidth NR10.0+NR10.0 MHz - Channel Position B - Band 4 - Range 22000 to 39800 MHz





## Configuration C

Maximum Output Power 26.00 dBm / Port

### Remarks


1. Transceiver spurious emissions have been searched for all channel bandwidths and antenna ports.
2. Representative spurious emissions performance using the worst-case channel bandwidth has been presented for all modulations.
3. Plot data performance for all channel bandwidths, and channel positions for both contiguous and non-contiguous (NC) operation are on file and available on request.



Antenna D - Modulation NR10: QPSK - Carrier Bandwidth 10+10+10+10+10+10 MHz - Channel Position B - Band 1 - Range 0.009 to 4000 MHz



Antenna D - Modulation NR10: QPSK - Carrier Bandwidth 10+10+10+10+10+10 MHz - Channel Position B - Band 2 - Range 4000 to 12000 MHz







Antenna D - Modulation NR10: QPSK - Carrier Bandwidth 10+10+10+10+10+10 MHz - Channel Position B - Band 3 - Range 12000 to 20000 MHz



Antenna D - Modulation NR10: QPSK - Carrier Bandwidth 10+10+10+10+10+10 MHz - Channel Position B - Band 4 - Range 20000 to 38900 MHz






Antenna D - Modulation NR10: QPSK (NC) - Carrier Bandwidth 10+10+10+10+10+10 MHz - Channel Position B - Band 1 - Range 0.009 to 4000 MHz



Antenna D - Modulation NR10: QPSK (NC) - Carrier Bandwidth 10+10+10+10+10+10 MHz - Channel Position B - Band 2 - Range 4000 to 12000 MHz






Antenna D - Modulation NR10: QPSK (NC) - Carrier Bandwidth 10+10+10+10+10+10 MHz - Channel Position B - Band 3 - Range 12000 to 20000 MHz



Antenna D - Modulation NR10: QPSK (NC) - Carrier Bandwidth 10+10+10+10+10+10 MHz - Channel Position B - Band 4 - Range 20000 to 38900 MHz



Limit FCC Part 27.53 (a – j)

Limit	The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) db.
-------	---



## 2.5 FREQUENCY STABILITY

### 2.5.1 Specification Reference

FCC CFR 47 Part 2, Clause 2.1051

### 2.5.2 Date of Test and Modification State

6-October-2022 - Modification State 0

### 2.5.3 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

### 2.5.4 Environmental Conditions

Ambient Temperature 24.6°C  
Relative Humidity 30.8%

### 2.5.5 Test Method

All measurements were made in accordance with FCC KDB 971168 D01, Clause 9 and ANSI C63.26 Clause 5.6

### 2.5.6 Test Results

Configuration A

Temperature	Voltage	Frequency Error (Hz)
		Channel Position B (3 840 000 000 Hz)
-30°C	-48.0 V DC	Turns OFF
-20°C	-48.0 V DC	Turns OFF
-10°C	-48.0 V DC	2.700
0°C	-48.0 V DC	-1.7500
+10°C	-48.0 V DC	-4.8500
+20°C	-40.5 V DC	-1.6700
+20°C	-48.0 V DC	-1.8800
+20°C	-57.5 V DC	-1.1100
+30°C	-48.0 V DC	-3.1500
+40°C	-48.0 V DC	-1.2300
+50°C	-48.0 V DC	-2.7500

#### Remarks

Worst Case deviation at 4.8500 Hz = 0.001263 ppm



Limit	The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.
-------	---



### **SECTION 3**

#### **TEST EQUIPMENT USED**



### 3.1 TEST EQUIPMENT USED

Instrument	Manufacturer	Type No.	TE No.	Calibration Period (months)	Calibration Due
Spectrum Analyzer	Keysight	PXA N9030B	MY57144347	12	25-Mar-2023
Thermometer / Refrigeration	VWR	89094-746	210697579	24	13-Aug-2023
PSU	Xantrex	XKW60-50	E00109862	N/A	O/P Mon
Attenuator (20dB)	Mini-Circuits	BW-K10-2W44+	-	N/A	O/P Mon
Climate Chamber	Burnsco	RTC-37P-3-3	-07-07	N/A	O/P Mon

N/A – Not Applicable

O/P Mon – Output Monitored with Calibrated Equipment



### 3.2 MEASUREMENT UNCERTAINTY

For a 95% confidence level, the measurement uncertainties for defined systems are:-

Test Discipline	Frequency / Parameter	MU	
Conducted Maximum Peak Output Power	30 MHz to 20 GHz Amplitude	± 0.7 dB	
Conducted Emissions	30 MHz to 20 GHz Amplitude	± 2.1 dB	
Frequency Stability	30 MHz to 2 GHz	± 5.0 Hz	
Occupied Bandwidth	Up to 20 MHz Bandwidth	5 MHz Bandwidth	± 11547 Hz
		10 MHz Bandwidth	± 23094 Hz
		15 MHz Bandwidth	± 34641 Hz
		20 MHz Bandwidth	± 46188 Hz
Band Edge	30 MHz to 20 GHz Amplitude	±0.8 dB	
Radiated Spurious Emissions	30 MHz to 1 GHz	± 5.2 dB	
	1 GHz to 40GHz	± 6.3 dB	

#### Measurement Uncertainty Decision Rule

Determination of conformity with the specification limits is based on the results of the compliance measurement and does not take into account measurement instrumentation uncertainty as defined in ANSI C63.26:2015 Clause 1.3.

Risk: The uncertainty of measurement about the measured result is negligible with regard to the final pass/fail decision. The measurement result can be directly compared with the test limit to determine conformance with the requirement (compare IEC Guide 115). The level of risk to falsely accept and falsely reject items is further described in ILAC-G8





## **SECTION 4**

### **ACCREDITATION, DISCLAIMERS AND COPYRIGHT**



#### 4.1 ACCREDITATION, DISCLAIMERS AND COPYRIGHT



This report relates only to the actual item/items tested.

Our A2LA Accreditation does not cover opinions and interpretations and any expressed are outside the scope of our A2LA Accreditation.

© 2022 TÜV SÜD  
TÜV SÜD  
TUV SUD Canada, 1280 Teron Rd., Kanata On.

## **ANNEX A**

### **MODULE LIST**

Configuration A/B/C			
Product	Product No	R-State	Serial No
DOT 4465 B77DB25B66 (EUT)	KRY 901 523/2	R1A modified as R1B	TD3W340089
CT11	LPC 102 494/1	R2A	T01G495060
IRU 1648	KRC 161 842/1	R1D	TD3F105259
IRU 1649	KRC 161 842/2	R1E	TD3F109016
Software Version:	CXP 203 0045/26	Revision:	R14BX12