



## RF Exposure Compliance Requirement

### 1. Standard requirement

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

#### (a) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm <sup>2</sup> )	Averaging Times  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	F/300	6
1500-100000	--	--	5	6

#### (b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm <sup>2</sup> )	Averaging Times  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	F/1500	30
1500-100000	--	--	1.0	30

Note: f=frequency in MHz; \*Plane-wave equivalent power density



# SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch

Application No.: GZEM160700448001

Page: 2 of 3

FCC ID: TAPMD-TC6006W

## 2. MPE Calculation Method

$$E (V/m) = (30 \cdot P \cdot G)^{0.5} / d \quad \text{Power Density: } Pd(W/m^2) = E^2 / 377$$

E=Electric Field (V/m)

P=Peak RF output Power (W)

G=EUT Antenna numeric gain (numeric)

d= Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = (30 \cdot P \cdot G) / (377 \cdot d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

## 3. Calculated Result and Limit

(1) 802.11b 11Mbps data rate:

Frequency (MHz)	Antenna Gain (Numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
2412	1.585	20.91	123.31	0.03888	1	Complies
2442	1.585	22.03	159.58	0.05032	1	Complies
2462	1.585	21.50	141.25	0.04454	1	Complies

(2) 802.11g 54Mbps data rate:

Frequency (MHz)	Antenna Gain (Numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
2412	1.585	20.19	104.472	0.03294	1	Complies
2442	1.585	21.20	131.826	0.04156	1	Complies
2462	1.585	21.27	133.968	0.04224	1	Complies



**SGS-CSTC Standards Technical Services Co., Ltd.**  
**Guangzhou Branch**

Application No.: GZEM160700448001

Page: 3 of 3

FCC ID: TAPMD-TC6006W

3) 802.11n HT20 65Mbps data rate:

Frequency (MHz)	Antenna Gain (Numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
2412	1.585	19.40	87.096	0.02746	1	Complies
2442	1.585	20.12	102.802	0.03241	1	Complies
2462	1.585	19.66	92.470	0.02916	1	Complies

3) 802.11n HT40 135Mbps data rate:

Frequency (MHz)	Antenna Gain (Numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
2422	1.585	18.87	77.090	0.02431	1	Complies
2442	1.585	19.62	91.622	0.02889	1	Complies
2452	1.585	18.11	64.714	0.02040	1	Complies