

Maximum Permissible Exposure (MPE)

Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended to comply with Section Part 22, subpart H and Part 24, subpart E of the FCC CFR 47 Rules. For 47 CFR 1.1310 Radio frequency Radiation Exposure requirement.

Special Accessories

Not available for this EUT intended for grant.

Equipment Modifications

Not available for this EUT intended for grant.

Limitation

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-15000	/	/	1.0	30

F = frequency in MHz

* = Plane-wave equipment power density

Maximum Permissible Exposure (MPE) Evaluation

In this application we seek approval to the GST8000. Based on the FCC OET Bulletin 65 Supplement C and 47 CFR §2.1091, we have concluded that the SIM340 module will comply with the FCC rules on RF exposure for mobile devices in cellular band and PCS band. The following analysis will demonstrate such compliance. The analysis will be done in two US bands.

Operation in cellular band (824 – 849 MHz)

The GSM 850 band is 27.61dBm max at GSM/GPRS mode. The resulted power density at a distance of 20 cm can be deducted as follows:

EUT Mode	Frequency (MHz)	CH	EUT Pol.	Antenna Pol.	SPA Reading (dBuV)	S.G. Output (dBm)	Antenna Gain (dBd)	Cable Loss (dB)	ERP (dBm)	Limit (dBm)
GPRS 850	824.20	1013	H	V	119.46	33.08	-10.01	3.62	19.44	38.45
				H	125.38	39.11	-10.01	3.62	25.48	38.45
	836.60	384	H	V	118.25	31.99	-10.01	3.65	18.33	38.45
				H	124.75	38.52	-10.01	3.65	24.86	38.45
	848.80	777	H	V	119.37	33.24	-10.01	3.68	19.56	38.45
				H	124.98	38.78	-10.01	3.68	25.10	38.45

$$\text{ERP} = 25.48 \text{ dBm}$$

$$\text{ERP} = 25.48 \text{ dBm} + 2.14 = 578.10 \text{ mW}$$

$$\begin{aligned} \text{Power Density} &= \text{ERP} * \text{Duty Cycle} / (4 \pi R^2) \\ &= 578.1 * 0.25 / (4 * \pi * 20^2) = 0.0288 \text{ mW/cm}^2 \end{aligned}$$

where Duty Cycle is 0.25 for GPRS operation (class 10) and R is 20 cm.

The MPE limit for General Population/Uncontrolled Exposure is shown in the FCC OET Bulletin 65 Supplement C and can be calculated as follows:

$$\text{MPE limit} = 824/1500 = 0.55 \text{ mW/cm}^2$$

As we can see the resulted power density is below the MPE limit, therefore GST8000 in cellular band is compliant with the FCC rules on RF exposure.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。 This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms_and_conditions.htm) and Terms and Conditions for Electronic Documents (www.sgs.com/terms_e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/authentication. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.

Operation in PCS band (1850 – 1910 MHz)

The EIRP of GST8000 in PCS band is 23.52 dBm max. The resulted EIRP can be expressed as follows:

EUT Mode	Frequency (MHz)	CH	EUT Pol.	Antenna Pol.	SPA Reading (dBuV)	S.G. Output (dBm)	Antenna Gain (dBi)	Cable Loss (dB)	EIRP (dBm)	Limit (dBm)
GPRS 1900	1850.20	512	H	V	118.96	14.57	9.90	5.56	18.91	33.00
				H	122.93	18.75	9.90	5.56	23.09	33.00
	1880.00	661	H	V	119.24	14.88	9.99	5.61	19.26	33.00
				H	123.29	19.15	9.99	5.61	23.52	33.00
	1909.80	810	H	V	116.41	12.08	10.07	5.66	16.50	33.00
				H	121.87	17.76	10.07	5.66	22.17	33.00

$$\text{EIRP} = 23.52 \text{ dBm} = 224.91 \text{ mW}$$

$$\begin{aligned} \text{Power Density} &= \text{EIRP} \cdot \text{Duty Cycle} / (4 \pi R^2) \\ &= 224.91 \cdot 0.25 / (4 \cdot \pi \cdot 20^2) = 0.0112 \text{ mW/cm}^2 \end{aligned}$$

where Duty Cycle is 0.25 for GPRS operation (class 10) and R is 20 cm.

The MPE limit for General Population/Uncontrolled Exposure is shown in the FCC OET Bulletin 65 Supplement C and can be calculated as follows:

$$\text{MPE limit} = 1.0 \text{ mW/cm}^2$$

As we can see the resulted power density is below the MPE limit, therefore GST8000 in PCS band is compliant with the FCC rules on RF exposure.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。 This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms_and_conditions.htm) and Terms and Conditions for Electronic Documents (www.sgs.com/terms_e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/authentication. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.