

Recognized by the  
Federal Communications Commission and Industry Canada  
Anechoic chamber registration No.: 90462 (FCC)  
Anechoic chamber registration No.: 3463 (IC)  
TCB ID: DE0001



Accredited by the  
German Accreditation Council  
DAR-Registration Number  
DAT-P-176/94-D1



Independent ETSI  
compliance test house



Test report No. 2-4236-01-05/06

Applicant: Bircher Reglomat AG

Type: Mars /31, Impulse

FCC ID: TBZ-RAD00

IC: 5904A-RAD00

Test standard: FCC Part 15 / IC RSS-210, Issue 6, Annex 7

## Table of contents

Page

1	General information.....	3
1.1	Notes.....	3
1.2	Testing laboratory.....	4
1.3	Details of applicant.....	4
1.4	Application details.....	4
1.5	Test item (EUT).....	5
1.6	Technical data.....	5
1.7	Operation conditions .....	5
1.8	Equipment under test.....	5
1.9	Test standards.....	6
2	Technical test.....	8
2.1	Summary of test results .....	8
2.2	Test environment.....	8
2.3	Measurement and test set-up .....	8
2.4	Test equipment utilized and test set-up .....	9
2.4.1	Field strength measurement of fundamental and spurious in the frequency range 0.9 GHz to 33 GHz .....	9
2.4.2	Field strength and spurious radiation in the frequency range 33 GHz to 110 GHz .....	10
2.4.3	Field strength and spurious radiation in the frequency range 9 kHz to 12 GHz .....	11
2.5	Test results.....	12
2.5.1	Test results overview .....	12
2.5.2	Remarks on methods of measurements.....	12
2.5.3	Test results in details.....	13
3	Measurement results .....	15
4	Photographs .....	26

## 1 General information

### 1.1 Notes

The test results of this test report relate exclusively to the test item specified in 1.5. CETECOM ICT Services GmbH does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of the CETECOM ICT Services GmbH.

*Tester:*

Date	Name	Signature
2006-05-23	Karsten Gerald	
2006-11-10	Manfred Paschwitz	

*Technical responsibility for area of testing:*

Date	Name	Signature
2006-11-10	Harro Ames	



## 1.2 Testing laboratory

CETECOM ICT Services GmbH  
Untertürkheimerstraße 6–10  
D-66117 Saarbrücken  
Germany

CETECOM ICT Services GmbH  
P.O. Box 10 04 45  
D-66004 Saarbrücken  
Germany

Telephone : + 49 (0) 681 598–0  
Fax : + 49 (0) 681 598–9075  
e-mail : [info@ict.cetecom.de](mailto:info@ict.cetecom.de)  
Internet : <http://www.cetecom-ict.de>

## Accredited testing laboratory

Accredited by : Regulierungsbehörde für Telekommunikation und Post (RegTP)  
Listed by : Federal Communications Commission (FCC)  
Industry Canada (IC)

Authority	Identification/Registration No.
RegTP	DAT-P-176/94-D1
FCC	90462
IC	3463

Testing location, if different from CETECOM ICT Services GmbH: (not applicable)

## 1.3 Details of applicant

Name : Bircher Reglomat AG  
Street : Hauptstrasse 22  
Town : 9042 Speicher  
Country : Switzerland  
Phone : +41-71-343-83 83  
Fax : +41-71-343-83 80

### Contact person

Name : Mr. François Cosandey  
Phone : +41-71-343-83 77  
Fax : +41-71-343-83 10  
E-Mail : [francois.cosandey@bircher.com](mailto:francois.cosandey@bircher.com)

## 1.4 Application details

Date of receipt of application : 2006-04-19  
Date of receipt of test item : 2006-05-09  
Date of test : 2006-05-16 and 22  
Person(s) who have been present during the tests : -/-

## 1.5 Test item (EUT)

Description : Field disturbance Sensor  
Type designation : Mars /31, Impulse

Manufacturer

Name : Bircher Reglomat AG  
Street : Hauptstrasse 22  
Town : 9042 Speicher  
Country : Switzerland

## 1.6 Technical data

Frequency range : 24.075 GHz ... 24.175 GHz  
Operational frequency : 24.125 GHz  
Field strength : 305 mV/m @ 3m  
Type of modulation : 142KN0N  
Microwave modules : Tx/Rx-Module with integral horn antenna  
Power supply range (U nom) : 12 - 36 VDC / 12 - 28 VAC

## 1.7 Operation conditions

Operation : As soon as the equipment is powered on, Tx and Rx start operating  
Purpose of operation : Microwave Motion Detector for door openers

## 1.8 Equipment under test

Mars /31, Impulse, Serial Number 032414

Mars / 31 and Impulse are exactly the same microwave motion detectors. They differ in labels and user manual.

## 1.9 Test standards

## Code of Federal Regulations (CFR 47) Federal Communications Commission (FCC)

## FCC Part 15 Radio Frequency Devices (04/2006)

## SECTION 15.209

### Radiation emission limits, general requirements

## SECTION 15.245

### Operation within the band 24.075 GHz to 24.175 GHz

Industrie Canada RSS-210, Issue 6, Annex 7

## Test Report Cover Sheet/Performance Test Data

TEST REPORT NUMBER: **2-4236-01-05/06**

EQUIPMENT MODEL NUMBER: **Mars /31, Impulse**

CERTIFICATION NO:

MANUFACTURER : **Bircher Reglomat AG  
Hauptstrasse 22  
9042 Speicher  
Switzerland  
Mr. Francois Cosandey  
+41 71 343 8377  
Francois.cosandey@reglomat.com**

TESTED TO RADIO STANDARDS SPECIFICATION NO. : **RSS210 Issue 6**

OPEN AREA TEST SITE INDUSTRY CANADA NUMBER: **3463**

FREQUENCY RANGE (or fixed frequency): **24.125 GHz**

FIELD STRENGTH: **305 mV/m @ 3m**

OCCUPIED BANDWIDTH (99% BW): **142 kHz (CW carrier)  
depending on RBW, here 3 kHz**

TYPE OF MODULATION: **CW**

EMISSION DESIGNATOR (TRC-43): **142KN0N**

TRANSMITTER SPURIOUS (worst case): **6.7 mV/m @ 3m (1. Harmonics)**

RECEIVER SPURIOUS (worst case): **not applicable**

ANTENNA TYPE: **horn antenna**

### ATTESTATION:

**DECLARATION OF COMPLIANCE:** I declare that the testing was performed or supervised by me; that the test measurements were made in accordance with the above-mentioned Industry Canada standard(s); and that the equipment identified in this application has been subjected to all the applicable test conditions specified in the Industry Canada standards and all of the requirements of the standard have been met.

**Signature:**

**Date: 2006-11-10**

**Manfred Paschwitz**



## 2 Technical test

### 2.1 Summary of test results

- No deviations from the technical specification (s) were ascertained in the course of the performed tests.
- The deviations as specified in 2.5 were ascertained in the course of the performed tests.

This test report:

- describes the first test
- describes an additional test
- is a verification of documents
- is only valid with the test report no.

### 2.2 Test environment


The environmental conditions are documented especially for each test.

### 2.3 Measurement and test set-up

The measurement and test set-up is defined in the technical specification.

## 2.4 Test equipment utilized and test set-up

### 2.4.1 Field strength measurement of fundamental and spurious in the frequency range 0.9 GHz to 33 GHz



Frequency f [GHz]	Distance d [m]	Antenna factor k [dB(1/m)]	Amp. gain g [dB]	Cable loss a(c) [dB]
0.9 to 2.0	3.0	23.45	32.0	0.5 ... 0.7
2.0 to 4.0	3.0	23.68	32.0	0.7 ... 0.8
4.0 to 6.0	3.0	27.31	32.0	0.8 ... 1.2
6.0 to 8.0	3.0	30.06	32.0	1.2 ... 1.6
8.0 to 12.0	3.0	33.70	32.0	1.6 ... 2.0
12.0 to 18.0	3.0	33.97	32.0	2.0 ... 2.7
18.0 to 26.5	3.0	36.73	32.0	2.7 ... 3.0
26.5 to 33.0	3.0	40.29	32.0 to 28.0	3.0 ... 3.2


Calculation: Field strength = analyser reading + cable loss - amplifier gain + antenna factor  
 $e [\text{dB}(\mu\text{V}/\text{m})] = u [\text{dB}(\mu\text{V})] + a [\text{dB}] - g [\text{dB}] + k [\text{dB}(1/\text{m})]$

Test equipment	Manufacturer	Type	CETECOM reference
Spectrum Analyser	HP	HP 8565E	300000916
SGH 1.0 to 2.0 GHz	flann	0624-10	300000225
SGH 2.0 to 4.0 GHz	narda	644	300000769
SGH 4.0 to 6.0 GHz	narda	643	300002447
SGH 6.0 to 8.0 GHz	narda	642	300000767
SGH 8.0 to 12.5 GHz	narda	640	300000784
SGH 12.0 to 18.0 GHz	narda	639	300000787
SGH 18.0 to 26.5 GHz	flann	2024-20	300001968
SGH 26.5 to 40.0 GHz	flann	2224-20	300001973
Amplifier 0.1 to 26.5 GHz	HP	HP 83017A	300002267
Climatic chamber	Vötsch	VUK 04/500	300000297
DC Power supply	HP	HP 6038A	300001174
RF-cable	Insulated Wire Inc.	KPS-1533-590	300002290

## Measurement uncertainty

Test parameter	Measurement uncertainty
DC Power supply	$\pm 0.5 \text{ V}$
Temperature	$\pm 0.2 \text{ }^\circ\text{C}$
Frequency	$\pm 0.01 \text{ ppm}$
eirp	$\pm 1.5 \text{ dB}$

## 2.4.2 Field strength and spurious radiation in the frequency range 33 GHz to 110 GHz



Frequency range [GHz]	Distance d [m]	Distance correction dc (3 m/X m) [dB]	Antenna factor k [dB 1/m]
33.0 ..... 50.0	0.250	-21.60	39.00
50.0 ..... 75.0	0.125	-27.60	40.70
75.0 ... 110.0	0.125	-27.60	45.10

Calculation: Field strength = analyser reading + antenna factor - distance correction  
 $e [\text{dB}(\mu\text{V}/\text{m})] = u [\text{dB}(\mu\text{V})] + k [\text{dB}(1/\text{m})] - d [\text{dB}]$

Remark: Cable loss is automatically taken into account if the S.A. is operating with external mixers.


Test equipment	Manufacturer	Type	CETECOM reference
Spectrum Analyser	HP	HP 8565E	300000916
Power supply	HP	HP 6038A	300001174
SGH 33 ... 50 GHz	Thomson	COR 33_50	300000812
Mixer 33 ... 50 GHz	HP	11970Q	300000781j
SGH 50 ... 75 GHz	Thomson	COR 50_75	300000789k
Mixer 50 ... 75 GHz	HP	11970V	300000871o
SGH 75 ... 110 GHz	Thomson	COR 75_110	300000789m
Mixer 75 ... 110 GHz	HP	11970W	300000871v

### Measurement uncertainty

Test parameter	Measurement uncertainty
Power supply	$\pm 0.1 \text{ VDC}$
Temperature	$\pm 0.2 \text{ }^\circ\text{C}$
Frequency	$\pm 0.01 \text{ ppm}$
Field strength <50 GHz	$\pm 1.0 \text{ dB}$
Field strength >50 GHz	$\pm 3.0 \text{ dB}$

### 2.4.3 Field strength and spurious radiation in the frequency range 9 kHz to 12 GHz

#### Set-up for radiated measurements



Test equipment	Manufacturer	Type	Serial No.
Spectrum analyser	HP	HP 85660B	2478A05306
Analyser display	HP	HP 85662A	2816A16541
Quasi peak adapter	HP	HP 85650A	2811A01131
RF-preselector	HP	HP 85685A	2833A00768
Loop Antenna A 0	R&S	HFH 2-Z2	881 058/42
Biconical antenna A 1	Emco	3104	3758
Log.-per.-antenna A 2	Emco	3146	2304
Double ridge horn ant. A 3	Emco	3115	3007
Relay switch	R&S	RSU	375 339/002
High pass filter	FSY Microwave	HM 985955	001
Amplifier	Tron-Tech	P42-GA29	B2302
DC Power supply	HP	HP 6038A	300001174
RF-cable	HP	5061-5359	P36303

#### Measurement uncertainty

Test parameter	Measurement uncertainty
Power supply	$\pm 0.5$ V
Temperature	$\pm 0.2$ °C
Frequency	$\pm 0.01$ ppm
RF-power	$\pm 1.5$ dB
Field strength >50 GHz	$\pm 3.0$ dB

## 2.5 Test results

### 2.5.1 Test results overview

This test was performed:

- in addition to the test report no.

Verification of EUT:

- EUT is in accordance with the technical description
- EUT is not in accordance with the technical description
- The equipment is compliant to FCC requirement

### 2.5.2 Remarks on methods of measurements

The EUT is positioned in a non-conductive test fixture and can be rotated and tilted in all angles and in all planes.

The radiated measurements are performed in vertical and horizontal plane in the frequency range from 9 kHz to 110 GHz in semi-anechoic chambers. The EUT is positioned on a non-conductive support with a height of 0.80 m above a conductive ground plane that covers the whole chamber. The receiving antennas are conform with specifications ANSI C63.2-1987 clause 15 and ANSI C63.4-1992 clause 4.1.5. These antennas can be moved over the height range between 1.0 m and 4.0 m in order to search for maximum field strength emitted from EUT. The measurement distances between EUT and receiving antennas are indicated in the test set-ups for the various frequency ranges. For each measurement, the EUT is rotated in all three axes until the maximum field strength is received.

The wanted and unwanted emissions are received by spectrum analysers where the detector modes and resolution bandwidths (RBW) over various frequency ranges are set according to requirement ANSI C63.4-1992 clause 4.2.

#### 1. Measurements of ERP/EIRP at fundamental and spurious frequencies

Spurious frequencies are produced by transmitter and receiver when the EUT is active. According to FCC requirements 15.209, spurious emissions have to be investigated as maximum field strength values in the frequency range from 9 kHz to 960 MHz. Where possible, the measurement distance shall be 3 m. If other distances are used, the distance correction is added to the test result.

In the low frequency range (9 kHz to 30 MHz), the receiving antenna is an active loop antenna which is positioned at 3 m distance in a shielded, anechoic chamber (see page 8). In case of required measuring distances > 3 m, a distance correction factor is used to calculate the received field strength.

Spurious EIRP measurements in the frequency range 960 MHz to 4 GHz are carried out in a shielded semi-anechoic test chamber. The measurement distance is 3.0 m.

In the frequency range 4 GHz to 40 GHz, spurious EIRP measurements are performed in a shielded fully anechoic chamber with rectangular SGHs. The measurement distances are indicated underneath each plot, and a calculation for field strength is added, where all relevant factors like cable losses, antenna factors, etc are taken into account.

**2.5.3 Test results in details**

Equipment under test (EUT): see page 5

Ambient temperature: 21 °C

Relative humidity: 45 %

**TRANSMITTER PARAMETERS****SECTION 15.245**

Fundamental frequency and harmonics

Microwave module: Mars /31, operating in N0N

Test condition t = 21 °C	TRANSMITTER FIELD STRENGTH			
EUT operating: TX / RX on DC power supply	Frequency f [GHz]	S.A. e [dBμV] @ 0.3 m	Field strength e [dBμV/m] @ 3 m	See plot no.:
U = 24.0 VDC (CW-mode)	24.131	89.7	109.7	1
	48.258	56.5	76.5	2
	72.385	54.8	74.8	3
	96.250	noise	noise	4

Note:

The values are recalculated from a test distance of 0.3 m to 3 m with 20 dB/decade according to the FCC requirements.

REFERENCE OF TEST EQUIPMENT USED: see test set-up on page 8 / 9

LIMITS:

**SECTION 15.245**

Frequency range (MHz)	Measurement distance [m]	Field strength e [dBμV/m] @ 3 m	Field strength E [mV/m]
24,075 to 24,175	3	128.0	2,500
Harmonics	3	88.0	25

Verdict: Field strength limits are kept

Equipment under test (EUT): see page 5

Ambient temperature: 21 °C

Relative humidity: 45 %

**TRANSMITTER PARAMETERS**  
**Spurious Frequencies**
**SECTION 15.245**  
**SECTION 15.209**

Microwave module: Mars /31 operating in N0N

Test condition t = 21 °C		TRANSMITTER SPURIOUS FIELD STRENGTH		
Frequency range [GHz]	Spurious frequencies [GHz]	SA u [dBµV/m]	E [µV/m]	See plot no.:
0.009 to 30.0 MHz (h + v) horizontal and vertical plane	noise	n.a.	< limit	5
0.030 to 4.0 (h + v)	noise	n.a.	< limit	6
4.0 to 12.0 (h + v)	noise	n.a.	< limit	7
12.0 to 24.0 (h + v)	noise	n.a.	< limit	8
> 24.0	fundamental and harmonics		< limit	1 - 4
25.0 to 50.0 (h + v)	noise	n.a.	< limit	9
50.0 to 75.0 (h + v)	noise	n.a.	< limit	10
75.0 to 110.0 (h + v)	noise	n.a.	< limit	11

Note:

9 kHz to 150 kHz : 200 Hz ResBw/VideoBw

150 kHz to 30 MHz : 9 kHz ResBw/VideoBw

30 MHz to 1 GHz : 100 kHz ResBw/VideoBw

above 1 GHz : 1 MHz ResBw/VideoBw

LIMITS:


**SECTION 15.209 / 15.245**

Frequency range (MHz)	Measurement distance [m]	Field strength e [dBµV/m] @ 3 m	Field strength E [µV/m]
0.009 – 0.490	300	88.5 ... 53.8	2400/F(kHz)
0.490 – 1.705	30	53.8 ... 43.0	24000/F(kHz)
1.705 – 30.0	30	49.5	30
30.0 – 88.0	3	40.0	100
88.0 – 216.0	3	43.5	150
216.0 – 960.0	3	46.0	200
> 960.0	3	54.0 (AV)	500
> 960.0	3	74.0 (PK)	5,000
2nr/rd harmonic	3	88.0	25,000

Verdict:	Field strength limits are kept.
----------	---------------------------------

### 3 Measurement results

Plot no. 1:



Note:

The values are recalculated from a test distance of 0.3 m to 3 m with 20 dB/decade according to the FCC requirements.

$P_{\text{Analyser}}$  = 89.6 dB $\mu$ V (The 20 dB/decade according is not calculated in the analyser reading)


$P_{\text{Spurious Emission}}$  = 109.6 dB $\mu$ V

LIMITS:

SECTION 15.209 / 15.245

Frequency range (MHz)	Measurement distance [m]	Field strength e [dB $\mu$ V/m] @ 3 m	Field strength E [ $\mu$ V/m]
0.009 – 0.490	300	88.5 ... 53.8	2400/F(kHz)
0.490 – 1.705	30	53.8 ... 43.0	24000/F(kHz)
1.705 – 30.0	30	49.5	30
30.0 – 88.0	3	40.0	100
88.0 – 216.0	3	43.5	150
216.0 – 960.0	3	46.0	200
> 960.0	3	54.0 (AV)	500
> 960.0	3	74.0 (PK)	5,000
2nr/rd harmonic	3	88.0	25,000

Plot no. 2:



Note:

The values are recalculated from a test distance of 0.3 m to 3 m with 20 dB/decade according to the FCC requirements.

$P_{\text{Analyser}}$  = 56.5 dB $\mu$ V (The 20 dB/decade according is not calculated in the analyser reading)


$P_{\text{Spurious Emission}}$  = 76.5 dB $\mu$ V

LIMITS:

SECTION 15.209 / 15.245

Frequency range (MHz)	Measurement distance [m]	Field strength $e$ [dB $\mu$ V/m] @ 3 m	Field strength $E$ [ $\mu$ V/m]
0.009 – 0.490	300	88.5 ... 53.8	2400/F(kHz)
0.490 – 1.705	30	53.8 ... 43.0	24000/F(kHz)
1.705 – 30.0	30	49.5	30
30.0 – 88.0	3	40.0	100
88.0 – 216.0	3	43.5	150
216.0 – 960.0	3	46.0	200
> 960.0	3	54.0 (AV)	500
> 960.0	3	74.0 (PK)	5,000
2nr/rd harmonic	3	88.0	25,000

Plot no. 3:




LIMITS:

SECTION 15.209 / 15.245

Frequency range (MHz)	Measurement distance [m]	Field strength e [dB $\mu$ V/m] @ 3 m	Field strength E [ $\mu$ V/m]
0.009 – 0.490	300	88.5 ... 53.8	2400/F(kHz)
0.490 – 1.705	30	53.8 ... 43.0	24000/F(kHz)
1.705 – 30.0	30	49.5	30
30.0 – 88.0	3	40.0	100
88.0 – 216.0	3	43.5	150
216.0 – 960.0	3	46.0	200
> 960.0	3	54.0 (AV)	500
> 960.0	3	74.0 (PK)	5,000
2nr/rd harmonic	3	88.0	25,000

Plot no. 4:




## LIMITS:

## SECTION 15.209 / 15.245


Frequency range (MHz)	Measurement distance [m]	Field strength $E$ [dB $\mu$ V/m] @ 3 m	Field strength $E$ [ $\mu$ V/m]
0.009 – 0.490	300	88.5 ... 53.8	2400/F(kHz)
0.490 – 1.705	30	53.8 ... 43.0	24000/F(kHz)
1.705 – 30.0	30	49.5	30
30.0 – 88.0	3	40.0	100
88.0 – 216.0	3	43.5	150
216.0 – 960.0	3	46.0	200
> 960.0	3	54.0 (AV)	500
> 960.0	3	74.0 (PK)	5,000
2nr/rd harmonic	3	88.0	25,000

Plot no. 5:


**Note:**

The limit lines were recalculated from a test distance of 300 m/30 m to 3 m with 40 dB/decade according to the FCC requirements.


Plot no. 6:



Plot no. 7:



Plot no. 8:




LIMITS:

SECTION 15.209 / 15.245

Frequency range (MHz)	Measurement distance [m]	Field strength e [dB $\mu$ V/m] @ 3 m	Field strength E [ $\mu$ V/m]
0.009 – 0.490	300	88.5 ... 53.8	2400/F(kHz)
0.490 – 1.705	30	53.8 ... 43.0	24000/F(kHz)
1.705 – 30.0	30	49.5	30
30.0 – 88.0	3	40.0	100
88.0 – 216.0	3	43.5	150
216.0 – 960.0	3	46.0	200
> 960.0	3	54.0 (AV)	500
> 960.0	3	74.0 (PK)	5,000
2nr/rd harmonic	3	88.0	25,000


Plot no. 9: 25 to 50 GHz



Measured at 0.3 m

To recalculate to 3.0 m we add 20dB / decade according to FCC requirement.  
The maximum value is 49.1 dB $\mu$ V/m at 3m.

Plot no. 10: 50 to 75 GHz



Tested with ext. Mixer


Measured at 0.3 m

Note:

The values are recalculated from a test distance of 0.3 m to 3 m with 20 dB/decade according to the FCC requirements.

$P_{\text{Analyser}} = 42.83 \text{ dB}\mu\text{V}$  (The 20 dB/decade according is calculated in the analyser reading)

Plot no. 11: 75 to 110 GHz



Tested with ext. Mixer

Measured at 0.3 m

### Note:

The values are recalculated from a test distance of 0.3 m to 3 m with 20 dB/decade according to the FCC requirements.

P Analyser = 43.10 dB $\mu$ V (The 20 dB/decade according is calculated in the analyser reading)

## **4 Photographs**

Photo no. 1



Photo no. 2




Photo no. 3




Photo no. 4




Photo no. 5




Photo no. 6



Photo no. 7

