

August 17, 2022

Roku, Inc.  
1155 Coleman Ave  
San Jose  
CA 95110 USA

Dear Thien,

Enclosed is the EMC Wireless test report for compliance testing of the Roku, Inc., WiFi Remote Control as tested to the requirements of 15.407 for Intentional Radiators.

Thank you for using the services of Eurofins Electrical and Electronic Testing NA, Inc. If you have any questions regarding these results or if Eurofins Electrical and Electronic Testing NA, Inc. can be of further service to you, please feel free to contact me.

*Gary Chou*

Documentation Department  
Eurofins Electrical and Electronic Testing NA, Inc.

Reference: WIR119780-ROKU-FCC-DFS



Certificates and reports shall not be reproduced except in full, without the written permission of Eurofins Electrical and Electronic Testing NA, Inc. While use of the A2LA logo in this report reflects Eurofins Electrical and Electronic Testing NA, Inc. accreditation under these programs, the report must not be used by the client to claim product certification, approval, or endorsement by A2LA, or any agency of the Federal Government. This letter of transmittal is not a part of the attached report.

Eurofins Electrical and Electronic Testing NA, Inc. is part of the Eurofins Electrical & Electronics (E&E) global compliance network.

## **FCC DFS Test Report**

**Applicant name: Roku, Inc.**

**Product: WiFi Remote Control**

**Report: WIR119780-ROKU-ISED-DFS**

### **Applicant Address:**

**1155 Coleman Ave., San Jose, CA 95110 USA**

### **Manufacturer Address:**

**1155 Coleman Ave., San Jose, CA 95110 USA**

**Prepared By:**  
**Eurofins Electrical and Electronic Testing NA, Inc.**  
3162 Belick St.  
Santa Clara CA, 95054

## FCC DFS Test Report

**Applicant name: Roku, Inc.**

**Product: WiFi Remote Control**

**Standard  
FCC 15.407**

*Christopher Martin*

Christopher Martin Test Engineer, Wireless Laboratory

**Engineering Statement:** The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements FCC Rules under normal use and maintenance.

*Gary Chou*

Gary Chou  
Wireless Engineering Manager, Wireless Laboratory

**Table of Contents**

Release Control Record.....	5
1 General Description of EUT .....	6
2. U-NII DFS Rule Requirements .....	7
2.1 Working Modes and Required Test Items .....	7
2.2 Test Limits and Radar Signal Parameters.....	8
2.3 Test Channel List.....	11
2.4 Test Setup Configuration .....	12
3 Summary of Test Results .....	13
3.1 Test Instruments .....	13
3.2 Modification Record.....	14
4 General Information .....	15
4.1 Description of Test Modes .....	15
4.2 Description of Support Units .....	16
4.3 General Description of Applied Standards .....	17
5 In-Service Monitoring: Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period	18

**Release Control Record**

<b>Issue No.</b>	<b>Description</b>	<b>Date Issued</b>
WIR119780-ROKU-FCC-DFS	Original Release	08/30/2022

## 1 General Description of EUT

<b>Product:</b>	WiFi Remote Control		
<b>Brand:</b>	Roku		
<b>Model(s) Tested:</b>	RC-MC1F, RC-MC5F		
<b>Series Model:</b>	N/A		
<b>Sample Status:</b>	Original		
<b>4.09EUT Specifications:</b>	Primary Power:	5Vdc powered by Adaptor/ 3.8Vdc powered by battery	
	Voltage Frequency:	N/A	
	Technology / Type of Modulations:	256QAM, 64QAM, 16QAM, QPSK, BPSK for OFDM	
	Operating Frequency :	5180 MHz~5240MHz, 5260 MHz~5320 MHz 5500 MHz~5725 MHz 5745 MHz~5825MHz	
	FCC ID:	TC2-R1049	
	Antenna Type:	Chip Antenna	5150 MHz: 5.18 dBi 5500 MHz: 5.04 dBi 5850 MHz: 4.09 dBi
	Antenna connector:	N/A	
	<b>Analysis:</b>	The results obtained relate only to the item(s) tested.	
<b>Environmental Test Conditions:</b>	Temperature: 20.3° C		
	Relative Humidity: 47.5%		
	Barometric Pressure: 860-1060 mbar		
<b>Evaluated by:</b>	Christopher Martin		
<b>Issue Date(s):</b>	August 31, 2022		

NOTE: The following modules can be chosen to be configured in the EUT.

	Model No.	FCC ID	Note
-	-	-	-
-	-	-	-

## 2. U-NII DFS Rule Requirements

### 2.1 Working Modes and Required Test Items

This is a DFS test report.

The manufacturer shall state whether the UUT is capable of operating as a Client. If the UUT is capable of operating in more than one operating mode then each operating mode shall be tested separately. See tables 6 and 7 for the applicability of DFS requirements for each of the operational modes.

Table 6: Applicability of DFS Requirements Prior To Use a Channel

Requirement	Operational Mode		
	Master	Client without radar detection	Client with radar detection
Non-Occupancy Period	✓	✓ <small>note</small>	✓
DFS Detection Threshold	✓	Not required	✓
Channel Availability Check Time	✓	Not required	Not required
U-NII Detection Bandwidth	✓	Not required	✓

Note: Per KDB 905462 D03 UNII Clients Without Radar Detection New Rules v01r02 section (b)(5/6),  
If the client moves with the master, the device is considered compliant if nothing appears in the client non-occupancy period test. For devices that shut down (rather than moving channels), no beacons should appear. An analyzer plot that contains a single 30-minute sweep on the original channel.

Table 7: Applicability of DFS Requirements During Normal Operation.

Requirement	Operational Mode	
	Master or Client with radar detection	Client without radar detection
DFS Detection Threshold	✓	Not required
Channel Closing Transmission Time	✓	✓
Channel Move Time	✓	✓
U-NII Detection Bandwidth	✓	Not required

Additional requirements for devices with multiple bandwidth modes	Master or Client with radar detection	Client without radar detection
U-NII Detection Bandwidth and Statistical Performance Check	All BW modes must be tested	Not required
Channel Move Time and Channel Closing Transmission Time	Test using widest BW mode available	Test using the widest BW mode available for the link
All other tests	Any single BW mode	Not required

Note: Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency.

## 2.2 Test Limits and Radar Signal Parameters

### Detection Threshold Values

Table 8: DFS Detection Thresholds for Master Devices and Client Devices With Radar Detection

Maximum Transmit Power	Value (See Notes 1, 2, and 3)
EIRP $\geq$ 200 milliwatt	-64 dBm
EIRP < 200 milliwatt and power spectral density < 10 dBm/MHz	-62 dBm
EIRP < 200 milliwatt that do not meet the power spectral density requirement	-64 dBm

Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna.  
 Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response.  
 Note3: EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01.

Table 9: DFS Response Requirement Values

Parameter	Value
Non-occupancy period	Minimum 30 minutes
Channel Availability Check Time	60 seconds
Channel Move Time	10 seconds See Note 1.
Channel Closing Transmission Time	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.
U-NII Detection Bandwidth	Minimum 100% of the U-NII 99% transmission power bandwidth. See Note 3

Note 1: Channel Move Time and the Channel Closing Transmission Time should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst.  
 Note 2: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.  
 Note 3: During the U-NII Detection Bandwidth detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.



### Parameters of DFS Test Signals

Step intervals of 0.1 microsecond for Pulse Width, 1 microsecond for PRI, 1 MHz for chirp width and 1 for the number of pulses will be utilized for the random determination of specific test waveforms.

Table 10: Short Pulse Radar Test Waveforms

Radar Type	Pulse Width (μsec)	PRI (μsec)	Number of Pulses	Minimum Percentage of Successful Detection	Minimum Number of Trials
0	1	1428	18	See Note 1	See Note 1
1	1	Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in Table 5a	Roundup $\left\{ \begin{array}{l} \left( \frac{1}{360} \right) \cdot \\ \left( \frac{19 \cdot 10^6}{\text{PRI}_{\mu\text{sec}}} \right) \end{array} \right\}$	60%	30
		Test B: 15 unique PRI values randomly selected within the range of 518-3066 μsec, with a minimum increment of 1 μsec, excluding PRI values selected in Test A			
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120
Note 1: Short Pulse Radar Type 0 should be used for the detection bandwidth test, channel move time, and channel closing time tests.					

Table 11: Long Pulse Radar Test Waveform

Radar Type	Pulse Width (µsec)	Chirp Width (MHz)	PRI (µsec)	Number Of Pulses Per Burst	Number Of Bursts	Minimum Percentage Of Successful Detection	Minimum Number Of Trials
5	50-100	5-20	1000-2000	1-3	8-20	80%	30

Three subsets of trials will be performed with a minimum of ten trials per subset. The subset of trials differ in where the Long Pulse Type 5 Signal is tuned in frequency.

- a) the Channel center frequency
- b) tuned frequencies such that 90% of the Long Pulse Type 5 frequency modulation is within the low edge of the UUT Occupied Bandwidth
- c) tuned frequencies such that 90% of the Long Pulse Type 5 frequency modulation is within the high edge of the UUT Occupied Bandwidth

It include 10 trails for every subset, the formula as below,

For subset case 1: the center frequency of the signal generator will remain fixed at the center of the UUT Channel.

For subset case 2: to retain 90% frequency overlap between the radar signal and the UUT Occupied Bandwidth, the center frequency of the signal generator will vary for each of the ten trials in subset case 2. The center frequency of the signal generator for each trial is calculated by:

$$FL + (0.4 * \text{Chirp Width [in MHz]})$$

For subset case 3: to retain 90% frequency overlap between the radar signal and the UUT Occupied Bandwidth, the center frequency of the signal generator will vary for each of the ten trials in subset case 3. The center frequency of the signal generator for each trial is calculated by:

$$FH - (0.4 * \text{Chirp Width [in MHz]})$$

Table 12: Frequency Hopping Radar Test Waveform

Radar Type	Pulse Width (µsec)	PRI (µsec)	Pulses per Hop	Hopping Rate (kHz)	Hopping Sequence Length (msec)	Minimum Percentage Of Successful Detection	Minimum Number Of Trials
6	1	333	9	0.333	300	70%	30


### 2.3 Test Channel List

#### 802.11n (HT20) mode

Test Parameter	Test channel
Radar Detection Performance	5300, 5500

## 2.4 Test Setup Configuration

### Radiated Setup Configuration of DFS Measurement System



The UUT is a RLAN device operating in Client mode. Radar test signals are injected into the UUT.

### 3 Summary of Test Results

The EUT has been tested according to the following specifications:

FCC 15.407/ RSS 247		
Clause	Test Parameter	Results
4.2.6	DFS	Pass

#### 3.1 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Spectrum Analyzer Keysight	N9030B	MY58141486	08/08/2021	08/08/2022
Splitter/Combiner (Mini-Circuit)	ZFSC-2-9G+	S F030000719	N/A	N/A
Splitter/Combiner (Mini-Circuit)	ZFSC-2-9G+	S F030000718	N/A	N/A
Signal Generator Keysight	MXG N5172B	MY59100287	08/07/2021	08/07/2022

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

Test Method	Typical Expanded Uncertainty	K	Confidence Level
<b>RF Frequencies</b>	$\pm 4.52$ Hz	2	95%
<b>RF Power Conducted Emissions</b>	$\pm 2.32$ dB	2	95%
<b>RF Power Conducted Spurious Emissions</b>	$\pm 2.25$ dB	2	95%
<b>RF Power Radiated Emissions</b>	$\pm 3.01$ dB	2	95%

### 3.2 Modification Record

There were no modifications required for compliance.

## 4 General Information

### 4.1 Description of Test Modes

#### FOR 5180 ~ 5320MHz

1 channels are provided for 802.11a, 802.11n (HT20):

Channel	Frequency
60	5300 MHz

#### FOR 5500 ~ 5700MHz

1 channels are provided for 802.11a, 802.11n (HT20):

Channel	Frequency
100	5500 MHz

#### 4.2 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Switch	TP-LINK	AX3000	2224282000899	2AXJ4AX3000PRO	N/A
B.	Laptop	Acer	Aspire A315-51	N/A	N/A	N/A
C.	Switching Power Adapter for Switch	Zebra	FSP025-DYAA3	N/A	N/A	N/A
D.	Switching Power Adapter for EUT	FSP	FSP045-D3MR3	H00000093	N/A	N/A

Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Items E~F acted as communication partners to transfer data.

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	-	-	-	-	0	-

Note: The core(s) is(are) originally attached to the cable(s).



#### 4.3 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standard:

##### **FCC 15.407**

All test items have been performed and recorded as per the above standard.

## 5 In-Service Monitoring: Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period

### 5.1 Limit of In-Service Monitoring

The EUT has In-Service Monitoring function to continuously monitor the radar signals, If radar is detected, it must leave the channel (Shutdown). The Channel Move Time to cease all transmissions on the current Channel upon detection of a Radar Waveform above the DFS Detection Threshold within 10 sec. The total duration of *Channel Closing Transmission Time* is comprised of 200 milliseconds starting at the beginning of the *Channel Move Time* plus any additional intermittent control signals required to facilitate *Channel* changes (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

Non-Occupancy Period time is 30 minute during which a Channel will not be utilized after a Radar Waveform is detected on that Channel. The non-associated Client Beacon Test is during the 30 minutes observation time. The EUT should not make any transmissions in the DFS band after EUT power up.

### 5.2 Test Procedures

1. The radar pulse generator is setup to provide a pulse at frequency that the Master and Client are operating. A type 0 radar pulse with a 1us pulse width and a 1428 us PRI is used for the testing.
2. The vector signal generator is adjusted to provide the radar burst (18 pulses) at a level of approximately -62dBm at the antenna of the Master device.
3. A trigger is provided from the pulse generator to the DFS monitoring system in order to capture the traffic and the occurrence of the radar pulse.
4. A U-NII device operating as a Client Device will associate with the Master at Channel. The MPEG file "TestFile.mpg" specified by the FCC is streamed from the "file computer" through the Master to the Client Device and played in full motion video using Media Player Classic Ver. 6.4.8.6 in order to properly load the network for the entire period of the test.
5. When a radar Burst with a level equal to the DFS Detection Threshold + 1dB is generated on the Operating Channel of the U-NII device. At time T0 the Radar Waveform generator sends a Burst of pulse of the radar waveform at Detection Threshold + 1dB.
6. Observe the transmissions of the EUT at the end of the radar Burst on the Operating Channel. Measure and record the transmissions from the EUT during the observation time (Channel Move Time). One 12 seconds plot is reported for the Short Pulse Radar Types 0. The plot for the Short Pulse Radar Types start at the end of the radar burst. The Channel Move Time will be calculated based on the zoom in 600ms plot of the Short Pulse Radar Type.
7. Measurement of the aggregate duration of the Channel Closing Transmission Time method. With the spectrum analyzer set to zero span tuned to the center frequency of the EUT operating channel at the radar simulated frequency, peak detection, and max hold, the dwell time per bin is given by: **Dwell (0.4ms) = S (12000ms) / B (30000)**; where Dwell is the dwell time per spectrum analyzer sampling bin, S is the sweep time and B is the number of spectrum analyzer sampling bins. An upper bound of the aggregate duration of the intermittent control signals of Channel Closing Transmission Time is calculated by: **C (ms) = N X Dwell (0.4 ms)**; where C

is the ClosingTime, N is the number of spectrum analyzer sampling bins (intermittent control signals) showing a U-NII transmission and Dwell is the dwell time per bin.

8. Measure the EUT for more than 30 minutes following the channel move time to verify that no transmissions or beacons occur on this Channel.
9. The test frequency , bandwidth and data rate as following table:

BW / Channel	Test Data Rate
20 MHz / 5300MHz (CH60)	MCS0
20 MHz / 5500MHz (CH140)	MCS0

### 5.3 Result of Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period for Client Beacon Test


BW / Channel	Test Item	Test Result	Limit	Pass/Fail
20MHz / 5300MHz (CH60)	Channel Move Time	643ms	< 10s	Pass
	Channel Closing Transmission Time	200ms + 29.2 ms	< 260ms	Pass
	Non-Occupancy Period	≥ 30	≥ 30 min	Pass
BW / Channel	Test Item	Test Result	Limit	Pass/Fail
20MHz / 5500MHz (CH100)	Channel Move Time	686.4ms	< 10s	Pass
	Channel Closing Transmission Time	200ms + 26 ms	< 260ms	Pass
	Non-Occupancy Period	≥ 30	≥ 30 min	Pass

**Note:** The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 seconds period. The aggregate duration of control signals will not count quiet periods in between transmissions.

**5.4 Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period for Client Beacon Test Plots**



**<20 MHz / 5300MHz (CH60)> In-Service Monitoring**

**Channel Move Time & Channel Closing Transmission Time**



**Non-Occupancy Period**

**Non-associated test Master was off. (beacon test)**




**Note:**

Dwell (0.4 ms) = Sweep Time (12000 ms) / Sweep Point Bins (30000)

Channel Closing Transmission Time (200 + 29.2 ms) = 200 + Number (73) X Dwell (0.4 ms) < 260ms

<20 MHz / 5500MHz (CH100)> In-Service Monitoring

Channel Move Time & Channel Closing Transmission Time



Non-Occupancy Period

Non-associated test Master was off. (beacon test)




Note:

Dwell (0.4 ms) = Sweep Time (12000 ms) / Sweep Point Bins (30000)


Channel Closing Transmission Time (200 + 26 ms) = 200 + Number (65) X Dwell (0.4 ms) < 260ms

EUT Data Traffic

<20 MHz / 5300MHz (CH60)> Data traffic



<20 MHz / 5500MHz (CH100)> Data traffic



--- END ---