



SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	TP-LINK TECHNOLOGIES CO., LTD.
Applicant Address	Building 24 (floors 1,3,4,5) and 28 (floors1-4) Central Science and Technology Park, Nanshan, Shenzhen, 518057 China
FCC ID	TE7AD7200
Manufacturer's company	TP-LINK TECHNOLOGIES CO., LTD.
Manufacturer Address	Building 24 (floors 1,3,4,5) and 28 (floors1-4) Central Science and Technology Park, Nanshan, Shenzhen, 518057 China

Product Name	AD7200 Multi-Band Wi-Fi Router
Brand Name	TP-LINK
Model No.	AD7200
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz
Received Date	Oct. 19, 2015
Final Test Date	May 27, 2016
Submission Type	Original Equipment

Statement

Test result included is only for the IEEE 802.11b/g, IEEE 802.11n and IEEE 802.11a/ac of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2013, 47 CFR FCC Part 15 Subpart C, KDB558074 D01 v03r04 and KDB 662911 D01 v02r01, KDB644545 D01 v01r02.**

The test equipment used to perform the test is calibrated and traceable to NML/ROC.





Table of Contents

1. VERIFICATION OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	4
3.3. Table for Filed Antenna.....	5
3.4. Table for Carrier Frequencies	6
3.5. Table for Test Modes.....	7
3.6. Table for Testing Locations.....	9
3.7. Table for Supporting Units	10
3.8. Table for Parameters of Test Software Setting	11
3.9. EUT Operation during Test	11
3.10. Duty Cycle.....	12
3.11. Test Configurations	13
4. TEST RESULT	17
4.1. AC Power Line Conducted Emissions Measurement.....	17
4.2. Maximum Conducted Output Power Measurement.....	21
4.3. Power Spectral Density Measurement	23
4.4. 6dB Spectrum Bandwidth Measurement	38
4.5. Radiated Emissions Measurement	47
4.6. Emissions Measurement	72
4.7. Antenna Requirements	98
5. LIST OF MEASURING EQUIPMENTS	99
6. MEASUREMENT UNCERTAINTY	101
APPENDIX A. TEST PHOTOS	A1 ~ A4
APPENDIX B. RADIATED EMISSION CO-LOCATION REPORT	B1 ~ B3




History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR5O1802AA	Rev. 01	Initial issue of report.	Mar. 17, 2016
FR5O1802AA	Rev. 02	Adding bridge mode.	Jun. 15, 2016

1. VERIFICATION OF COMPLIANCE

Product Name : AD7200 Multi-Band WI-FI Router
Brand Name : TP-LINK
Model No. : AD7200
Applicant : TP-LINK TECHNOLOGIES CO., LTD.
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Oct. 19, 2015 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Sam Chen

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	12.54 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	0.11 dB
4.3	15.247(e)	Power Spectral Density	Complies	1.85 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	2.06 dB
4.6	15.247(d)	Band Edge Emissions	Complies	0.14 dB
4.7	15.203	Antenna Requirements	Complies	-

3. GENERAL INFORMATION

3.1. Product Details

Items	Description
Product Type	WLAN (4TX, 4RX)
Radio Type	Intentional Transceiver
Power Type	From power adapter
Modulation	IEEE 802.11b: DSSS IEEE 802.11g: OFDM IEEE 802.11n/ac: see the below table
Data Modulation	IEEE 802.11b: DSSS (BPSK / QPSK / CCK) IEEE 802.11g/n: OFDM (BPSK / QPSK / 16QAM / 64QAM) IEEE 802.11ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)
Data Rate (Mbps)	IEEE 802.11b: DSSS (1/ 2/ 5.5/11) IEEE 802.11g: OFDM (6/9/12/18/24/36/48/54) IEEE 802.11n/ac: see the below table
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11 for 20MHz bandwidth ; 7 for 40MHz bandwidth
Channel Band Width (99%)	<u>For non-beamforming function:</u> IEEE 802.11b: 13.72 MHz IEEE 802.11g: 16.24 MHz IEEE 802.11ac MCS0/Nss1 (VHT20): 17.11 MHz IEEE 802.11ac MCS0/Nss1 (VHT40): 36.61 MHz <u>For beamforming function:</u> IEEE 802.11ac MCS1/Nss1 (VHT20): 17.80 MHz IEEE 802.11ac MCS0/Nss1 (VHT40): 36.47 MHz
Maximum Conducted Output Power	<u>For non-beamforming function:</u> IEEE 802.11b: 29.89 dBm IEEE 802.11g: 29.65 dBm IEEE 802.11ac MCS0/Nss1 (VHT20): 29.70 dBm IEEE 802.11ac MCS0/Nss1 (VHT40): 27.46 dBm <u>For beamforming function:</u> IEEE 802.11ac MCS1/Nss1 (VHT20): 27.96 dBm IEEE 802.11ac MCS0/Nss1 (VHT40): 27.07 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Note: This device contains 60GHz transmitter module FCC ID: PPD-QCA9008-SBD1.

Items	Description	
Beamforming Function	<input checked="" type="checkbox"/> With beamforming	<input type="checkbox"/> Without beamforming
	The product has beamforming function for 802.11ac.	

Antenna and Band width

Antenna	Four (TX)	
Band width Mode	20 MHz	40 MHz
IEEE 802.11b	V	X
IEEE 802.11g	V	X
IEEE 802.11n	V	V
IEEE 802.11ac	V	V

IEEE 11n/ac Spec.

Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS	
For non-beamforming function:	802.11n (HT20)	4	MCS 0-31
	802.11n (HT40)	4	MCS 0-31
	802.11ac (VHT20)	4	MCS 0-9/Nss1-4
	802.11ac (VHT40)	4	MCS 0-9/Nss1-4
For beamforming function:	802.11ac (VHT20)	4	MCS 1-9/Nss1-4
	802.11ac (VHT40)	4	MCS 0-9/Nss1-4

Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput).
Then EUT supports HT20 and HT40.

Note 2: IEEE Std. 802.11ac modulation consists of VHT20, VHT40, VHT80 and VHT160 (VHT: Very High Throughput). Then EUT supports VHT20, VHT40 for 2.4GHz.

Note 3: Modulation modes consist of below configuration: HT20/HT40: IEEE 802.11n, VHT20/VHT40: IEEE 802.11ac.

3.2. Accessories

Power	Brand	Model No.	Rating
Adapter	TP-LINK	T120420 (T120420-2B1)	Input: 100-240Vac, 50/60Hz, 1.2A Output: 12Vdc, 4.2A
Other			
Plug*1			

3.3. Table for Filed Antenna

Ant.	Brand	Product Number	Antenna Type	Connector	Gain (dBi)	Remark
1	TP-LINK	3101500712	Dipole Antenna	I-PEX	1.1	2.4GHz TX/RX
2	TP-LINK	3101500711	Dipole Antenna	I-PEX	1.6	2.4GHz TX/RX
3	TP-LINK	3101500710	Dipole Antenna	I-PEX	3.0	2.4GHz TX/RX
4	TP-LINK	3101500713	Dipole Antenna	I-PEX	1.5	2.4GHz TX/RX
5	TP-LINK	3101500707	Dipole Antenna	I-PEX	2.7	5GHz TX/RX
6	TP-LINK	3101500709	Dipole Antenna	I-PEX	3.4	5GHz TX/RX
7	TP-LINK	3101500708	Dipole Antenna </td <td>I-PEX</td> <td>3.3</td> <td>5GHz TX/RX</td>	I-PEX	3.3	5GHz TX/RX
8	TP-LINK	3101500706	Dipole Antenna	I-PEX	2.6	5GHz TX/RX

Note: The EUT has eight antennas.

Then Ant. 1, Ant. 2, Ant. 3 and Ant. 4 supports 2.4GHz WLAN function / Ant. 5, Ant. 6, Ant. 7 and Ant. 8 supports 5GHz WLAN function.

For 2.4GHz WLAN function (4TX/4RX):


Chain 1, Chain 2, Chain 3 and Chain 4 could transmit/receive simultaneously.

Chain 1: Connect to Ant. 1, Chain 2: Connect to Ant. 2, Chain 3: Connect to Ant. 3, Chain 4: Connect to Ant. 4.

For 5GHz WLAN function (4TX/4RX):

Chain 1, Chain 2, Chain 3 and Chain 4 could transmit/receive simultaneously.

Chain 1: Connect to Ant. 5, Chain 2: Connect to Ant. 6, Chain 3: Connect to Ant. 7, Chain 4: Connect to Ant. 8.



3.4. Table for Carrier Frequencies

There are two bandwidth systems.

For 20MHz bandwidth systems, use Channel 1~Channel 11.

For 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Chain
AC Power Line Conducted Emissions	Normal Link	-	-	-
Maximum Conducted Output Power	<u>For non-beamforming function:</u>			
	11b/CCK	1 Mbps	1/6/11	1+2+3+4
	11g/BPSK	6 Mbps	1/6/11	1+2+3+4
	11ac VHT20	MCS0/Nss1	1/6/11	1+2+3+4
	11ac VHT40	MCS0/Nss1	3/6/9	1+2+3+4
	<u>For beamforming function:</u>			
	11ac VHT20	MCS1/Nss1	1/6/11	1+2+3+4
	11ac VHT40	MCS0/Nss1	3/6/9	1+2+3+4
Power Spectral Density	<u>For non-beamforming function:</u>			
	11b/CCK	1 Mbps	1/6/11	1+2+3+4
	11g/BPSK	6 Mbps	1/6/11	1+2+3+4
	11ac VHT20	MCS0/Nss1	1/6/11	1+2+3+4
	11ac VHT40	MCS0/Nss1	3/6/9	1+2+3+4
	<u>For beamforming function:</u>			
	11ac VHT20	MCS1/Nss1	1/6/11	1+2+3+4
	11ac VHT40	MCS0/Nss1	3/6/9	1+2+3+4
6dB Spectrum Bandwidth	<u>For non-beamforming function:</u>			
	11b/CCK	1 Mbps	1/6/11	1+2+3+4
	11g/BPSK	6 Mbps	1/6/11	1+2+3+4
	11ac VHT20	MCS0/Nss1	1/6/11	1+2+3+4
	11ac VHT40	MCS0/Nss1	3/6/9	1+2+3+4
	<u>For beamforming function:</u>			
	11ac VHT20	MCS1/Nss1	1/6/11	1+2+3+4
	11ac VHT40	MCS0/Nss1	3/6/9	1+2+3+4
Radiated Emissions 9kHz~1GHz	Normal Link	-	-	-

Radiated Emissions 1GHz~10 th Harmonic	<u>For non-beamforming function:</u>			
	11b/CCK	1 Mbps	1/6/11	1+2+3+4
	11g/BPSK	6 Mbps	1/6/11	1+2+3+4
	11ac VHT20	MCS0/Nss1	1/6/11	1+2+3+4
	11ac VHT40	MCS0/Nss1	3/6/9	1+2+3+4
	<u>For beamforming function:</u>			
	11ac VHT20	MCS1/Nss1	1/6/11	1+2+3+4
	11ac VHT40	MCS0/Nss1	3/6/9	1+2+3+4
Band Edge Emissions	<u>For non-beamforming function:</u>			
	11b/CCK	1 Mbps	1/6/11	1+2+3+4
	11g/BPSK	6 Mbps	1/6/11	1+2+3+4
	11ac VHT20	MCS0/Nss1	1/6/11	1+2+3+4
	11ac VHT40	MCS0/Nss1	3/6/9	1+2+3+4
	<u>For beamforming function:</u>			
	11ac VHT20	MCS1/Nss1	1/6/11	1+2+3+4
	11ac VHT40	MCS0/Nss1	3/6/9	1+2+3+4

Note: 1. VHT20/VHT40 covers HT20/HT40, due to same modulation. The power setting for 802.11n HT20 and HT40 are the same or lower than 802.11ac VHT20 and VHT40.

2. There are two modes of EUT, one is beamforming mode, and the other is non-beamforming mode for 802.11ac. All test results were recorded in this report.

The following test modes were performed for all tests:

For AC Power Line Conducted Emissions test:

Mode 1. Normal Link - Router mode

Mode 2. Normal Link - Bridge mode<2.4GHz>

Mode 2. Normal Link - Bridge mode<5GHz>

Mode 3 generated the worst test result, so it was recorded in this report.

For Radiated Emission below 1 GHz:

There are two modes of EUT, one EUT Y axis, and the other is EUT Z axis for Radiated emission below 1 GHz test, after evaluating, EUT Z axis has been evaluated to be the worst case, so it was selected to test and record in this test report.

Mode 1. Normal Link - EUT Z axis_Router mode

Mode 2. Normal Link - EUT Z axis_Bridge mode<2.4GHz>

Mode 3. Normal Link - EUT Z axis_Bridge mode<5GHz>

Mode 1 generated the worst test result, so it was recorded in this report.

For Radiated Emission above 1 GHz test:

Mode 1. CTX - EUT Y axis + Antenna folded

Mode 2. CTX - EUT Z axis + Antenna folded

Mode 3. CTX - EUT Y axis + Antenna in 90°

Mode 4. CTX - EUT Z axis + Antenna in 90°

Mode 4 has been evaluated to be the worst case, so it was selected to test and record in this test report.

For Radiated Emission Co-location test:

There are two modes of EUT, one EUT Y axis, and the other is EUT Z axis for Radiated emission below 1 GHz test, after evaluating, EUT Z axis has been evaluated to be the worst case, so it was selected to test and record in this test report.

For Co-location MPE and Radiated Emission Co-location test:

The EUT could be applied with 2.4GHz WLAN function, 5GHz WLAN function and 60GHz function; therefore Co-location Maximum Permissible Exposure (Please refer to FA5O1802) and Radiated Emission Co-location (please refer to Appendix B) tests are added for simultaneously transmit between 2.4GHz WLAN function, 5GHz WLAN function and 60GHz function.

3.6. Table for Testing Locations

Test Site Location				
Address:	No.8, Lane 724, Bo-ai St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C.			
TEL:	886-3-656-9065			
FAX:	886-3-656-9085			
Test Site No.	Site Category	Location	FCC Designation No.	IC File No.
03CH01-CB	SAC	Hsin Chu	TW0006	IC 4086D
CO01-CB	Conduction	Hsin Chu	TW0006	IC 4086D
TH01-CB	OVEN Room	Hsin Chu	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

3.7. Table for Supporting Units

For Test Site No: 03CH01-CB (below 1 GHz)

Support Unit	Brand	Model	FCC ID
Notebook*4	DELL	E4300	DoC
Notebook	Apple	Mac Book	DoC
Flash disk3.0*2	Silicon Power	B06	DoC
AD7200 Multi-Band Wi-Fi Router (Device)	TP-LINK	AD7200	TE7AD7200

For Test Site No: 03CH01-CB (above 1 GHz)

For non-beamforming function:

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E4300	DoC

For beamforming function:

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E4300	DoC
Notebook	Apple	Mac Book	DoC
AD7200 Multi-Band Wi-Fi Router (RX Device)	TP-LINK	AD7200	TE7AD7200

For Test Site No: CO01-CB

Support Unit	Brand	Model	FCC ID
Notebook*5	DELL	E6430	DoC
AD7200 Multi-Band Wi-Fi Router (Device)*2	TP-LINK	AD7200	TE7AD7200
Flash disk3.0*2	Transcend	JetFlash-700	DoC
PC	DELL	T3400	DoC
LCD Monitor	DELL	1704FPT†	DoC
Keyboard	iCooky	SK068	DoC
Mouse	HP	FM100	DoC
Modem	ACEEX	DM1414	IFAXDM1414
Printer	EPSON	LQ-300+	N/A

For Test Site No: TH01-CB

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E4300	DoC

3.8. Table for Parameters of Test Software Setting

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

For non-beamforming function:

Test Software Version	QCARCT Version3.0.136.0					
Mode	Test Frequency (MHz)					
	NCB: 20MHz			NCB: 40MHz		
	2412 MHz	2437 MHz	2462 MHz	2422 MHz	2437 MHz	2452 MHz
802.11b	23.5	23.5	23.5	-	-	-
802.11g	21	24	22	-	-	-
802.11ac MCS0/Nss1 VHT20	20.5	24	22.5	-	-	-
802.11ac MCS0/Nss1 VHT40	-	-	-	16	21	20

For beamforming function:

Test Software Version	QCARCT Version3.0.136.0					
Mode	Test Frequency (MHz)					
	NCB: 20MHz			NCB: 40MHz		
	2412 MHz	2437 MHz	2462 MHz	2422 MHz	2437 MHz	2452 MHz
802.11ac MCS1/Nss1 VHT20	25.5	28	27	-	-	-
802.11ac MCS0/Nss1 VHT40	-	-	-	25	26.5	25.5

3.9. EUT Operation during Test

For non-beamforming function:

The EUT was programmed to be in continuously transmitting mode.

For beamforming function:

For Conducted Mode:

The EUT was programmed to be in continuously transmitting mode.

For Radiated Mode:

During the test, the following programs under WIN 7 were executed.

The program was executed as follows:

1. During the test, the EUT operation to normal function.
2. Executed command fixed test channel under DOS.
3. Executed "Lantest.exe" to link with the remote workstation to receive and transmit packet by RX Device and transmit duty cycle no less 98%

3.10. Duty Cycle

For non-beamforming function:


Mode	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)	Duty Factor (dB)	1/T Minimum VBW (kHz)
802.11b	1.000	1.000	100.00	0.00	0.01
802.11g	2.040	2.100	97.14	0.13	0.49
802.11ac MCS0/Nss1 VHT20	4.966	5.018	98.96	0.05	0.01
802.11ac MCS0/Nss1 VHT40	2.380	2.496	95.35	0.21	0.42

For beamforming function:

Mode	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)	Duty Factor (dB)	1/T Minimum VBW (kHz)
802.11ac MCS1/Nss1 VHT20	1.164	1.302	89.40	0.49	0.86
802.11ac MCS0/Nss1 VHT40	1.620	1.800	90.00	0.46	0.62

3.11. Test Configurations


3.11.1. AC Power Line Conduction Emissions Test Configuration



Item	Connection	Shielded	Length
1	Power cable	No	1.5m
2	RJ-45 cable*3	No	1.5m
3	RJ-45 cable	No	10m
4	RJ-45 cable	No	1.5m
5	VGA cable	Yes	1.8m
6	USB cable	Yes	1.8m
7	USB cable	Yes	1.8m
8	USB cable	Yes	1.8m
9	RS232 cable	Yes	1.8m
10	RJ-45 cable	No	1.5m
11	USB cable	Yes	1.8m
12	USB cable	Yes	1.8m
13	RJ-45 cable	No	1.5m

3.11.2. Radiation Emissions Test Configuration


Test Configuration: 30MHz~1GHz



Item	Connection	Shielded	Length
1	Power cable	No	1.5m
2	RJ-45 cable*3	No	1.5m
3	RJ-45 cable	No	10m
4	RJ-45 cable	No	10m
5	RJ-45 cable	No	1.5m


Test Configuration: above 1GHz

For non-beamforming function:



Item	Connection	Shielded	Length
1	Power cable	No	1.5m
2	RJ-45 cable	No	10m

For beamforming function:



Item	Connection	Shielded	Length
1	Power cable	No	1.5m
2	RJ-45 cable	No	10m
3	RJ-45 cable	No	1.5m

4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 kHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
 - (3.1) All other equipment powered from additional LISN(s).
 - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	20°C	Humidity	53%
Test Engineer	Deven Huang	Phase	Line
Configuration	Normal Link	Test Mode	Mode 3



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.1548	35.74	-20.00	55.74	25.70	10.02	0.02	LINE	Average
2	0.1548	47.76	-17.98	65.74	37.72	10.02	0.02	LINE	QP
3	0.1607	35.92	-19.51	55.43	25.88	10.02	0.02	LINE	Average
4	0.1607	47.33	-18.10	65.43	37.29	10.02	0.02	LINE	QP
5	0.1884	33.43	-20.68	54.11	23.49	9.92	0.02	LINE	Average
6	0.1884	42.15	-21.96	64.11	32.21	9.92	0.02	LINE	QP
7	0.6075	33.37	-12.63	46.00	23.40	9.93	0.04	LINE	Average
8	0.6075	40.21	-15.79	56.00	30.24	9.93	0.04	LINE	QP
9	1.9697	26.86	-19.14	46.00	16.84	9.96	0.06	LINE	Average
10	1.9697	34.40	-21.60	56.00	24.38	9.96	0.06	LINE	QP
11	21.3725	26.67	-23.33	50.00	16.06	10.35	0.26	LINE	Average
12	21.3725	33.81	-26.19	60.00	23.20	10.35	0.26	LINE	QP

Temperature	20°C	Humidity	53%
Test Engineer	Deven Huang	Phase	Neutral
Configuration	Normal Link	Test Mode	Mode 3



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.1540	36.17	-19.61	55.78	26.13	10.02	0.02	NEUTRAL	Average
2	0.1540	49.10	-16.68	65.78	39.06	10.02	0.02	NEUTRAL	QP
3	0.1607	36.70	-18.73	55.43	26.66	10.02	0.02	NEUTRAL	Average
4	0.1607	48.72	-16.71	65.43	38.68	10.02	0.02	NEUTRAL	QP
5	0.1884	33.50	-20.61	54.11	23.56	9.92	0.02	NEUTRAL	Average
6	0.1884	43.08	-21.03	64.11	33.14	9.92	0.02	NEUTRAL	QP
7	0.6140	33.46	-12.54	46.00	23.49	9.93	0.04	NEUTRAL	Average
8	0.6140	39.84	-16.16	56.00	29.87	9.93	0.04	NEUTRAL	QP
9	2.2486	25.95	-20.05	46.00	15.93	9.96	0.06	NEUTRAL	Average
10	2.2486	33.04	-22.96	56.00	23.02	9.96	0.06	NEUTRAL	QP
11	23.0181	29.34	-20.66	50.00	18.68	10.39	0.27	NEUTRAL	Average
12	23.0181	36.20	-23.80	60.00	25.54	10.39	0.27	NEUTRAL	QP

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. Maximum Conducted Output Power Measurement

4.2.1. Limit

The limit for output power is 30dBm.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Bandwidth	50MHz bandwidth is greater than the EUT emission bandwidth
Detector	Average

4.2.3. Test Procedures

1. Test procedures refer KDB558074 D01 v03r04 section 9.2.3.2 Measurement using a power meter (PM).
2. Multiple antenna systems was performed in accordance with KDB 662911 D01 v02r01 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
3. This procedure provides an alternative for determining the RMS output power using a broadband RF average power meter with a thermocouple detector.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Conducted Output Power

Temperature	24°C	Humidity	55%
Test Engineer	Clemens Fang / Peter Wu	Test Date	Feb. 15, 2016

For non-beamforming function:

Mode	Frequency	Conducted Power (dBm)					Max. Limit (dBm)	Result
		Chain 1	Chain 2	Chain 3	Chain 4	Total		
802.11b	2412 MHz	23.96	23.75	23.70	23.62	29.78	30.00	Complies
	2437 MHz	23.69	24.01	24.06	23.71	29.89	30.00	Complies
	2462 MHz	23.66	23.93	23.72	23.95	29.84	30.00	Complies
802.11g	2412 MHz	19.93	20.39	20.32	20.12	26.21	30.00	Complies
	2437 MHz	23.63	23.74	23.50	23.63	29.65	30.00	Complies
	2462 MHz	21.53	21.67	21.57	21.82	27.67	30.00	Complies
802.11ac MCS0/Nss1 VHT20	2412 MHz	19.26	19.56	19.51	19.36	25.44	30.00	Complies
	2437 MHz	23.51	23.92	23.75	23.53	29.70	30.00	Complies
	2462 MHz	21.74	21.93	21.66	22.11	27.88	30.00	Complies
802.11ac MCS0/Nss1 VHT40	2422 MHz	16.23	16.56	16.12	16.21	22.30	30.00	Complies
	2437 MHz	21.43	21.57	21.42	21.35	27.46	30.00	Complies
	2452 MHz	20.53	20.39	20.35	20.85	26.56	30.00	Complies

For beamforming function:

Mode	Frequency	Conducted Power (dBm)					Max. Limit (dBm)	Result
		Chain 1	Chain 2	Chain 3	Chain 4	Total		
802.11ac MCS1/Nss1 VHT20	2412 MHz	18.35	18.53	19.15	18.23	24.60	28.15	Complies
	2437 MHz	21.83	21.92	21.96	22.05	27.96	28.15	Complies
	2462 MHz	20.27	20.58	20.46	20.42	26.45	28.15	Complies
802.11ac MCS0/Nss1 VHT40	2422 MHz	19.82	19.89	19.15	19.43	25.60	28.15	Complies
	2437 MHz	21.10	21.23	20.98	20.90	27.07	28.15	Complies
	2452 MHz	20.02	19.91	19.96	20.48	26.12	28.15	Complies

Note: $Directional\ Gain = 10 \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{K=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 7.85 \text{dBi} > 6 \text{dBi}$, so limit = $30 - (7.85 - 6) = 28.15 \text{dBm}$.

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS channel bandwidth.
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100\text{kHz}$
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto couple

4.3.3. Test Procedures

1. Test was performed in accordance with KDB558074 D01 v03r04 for Performing Compliance Measurements on Digital Transmission Systems (DTS) - section 10.2 Method PKPSD (peak PSD) and KDB 662911 D01 v02r01 section In-Band Power Spectral Density (PSD) Measurements option (b) Measure and sum spectral maximal across the outputs.
2. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
3. Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span}/\text{RBW}$ (use of a greater number of measurement points than this minimum requirement is recommended).
4. Use the peak marker function to determine the maximum level in any 3 kHz band segment within the fundamental EBW.
5. The resulting PSD level must be $\leq 8 \text{ dBm}$.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

Temperature	24°C	Humidity	55%
Test Engineer	Clemens Fang / Peter Wu		

For non-beamforming function:

Mode	Frequency	Power Density (dBm/3kHz)					Power Density Limit (dBm/3kHz)	Result
		Chain 1	Chain 2	Chain 3	Chain 4	Total		
802.11b	2412 MHz	-1.76	-1.59	-2.41	-1.39	4.25	6.15	Complies
	2437 MHz	-2.04	-2.39	-0.05	-2.99	4.30	6.15	Complies
	2462 MHz	-3.14	-2.86	-1.35	-2.27	3.67	6.15	Complies
802.11g	2412 MHz	-8.02	-8.18	-8.00	-6.79	-1.69	6.15	Complies
	2437 MHz	-2.50	-2.40	-3.47	-2.65	3.29	6.15	Complies
	2462 MHz	-7.30	-6.78	-6.46	-6.75	-0.79	6.15	Complies
802.11ac MCS0/Nss1 VHT20	2412 MHz	-10.14	-8.16	-7.79	-8.37	-2.51	6.15	Complies
	2437 MHz	-4.12	-3.62	-2.87	-3.28	2.57	6.15	Complies
	2462 MHz	-7.28	-7.71	-6.44	-7.37	-1.15	6.15	Complies
802.11ac MCS0/Nss1 VHT40	2422 MHz	-15.02	-14.71	-14.53	-13.47	-8.37	6.15	Complies
	2437 MHz	-11.02	-9.96	-10.67	-10.78	-4.57	6.15	Complies
	2452 MHz	-11.77	-12.27	-11.77	-10.86	-5.62	6.15	Complies

Note: $Directional\ Gain = 10 \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{K=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 7.85 \text{dBi} > 6 \text{dBi}$, so limit = $8 - (7.85 - 6) = 6.15 \text{dBm/3kHz}$.

For beamforming function:

Mode	Frequency	Power Density (dBm/3kHz)					Power Density Limit (dBm/3kHz)	Result
		Chain 1	Chain 2	Chain 3	Chain 4	Total		
802.11ac MCS1/Nss1 VHT20	2412 MHz	-6.75	-6.38	-6.81	-6.32	-0.54	6.15	Complies
	2437 MHz	-4.88	-4.21	-4.84	-4.28	1.48	6.15	Complies
	2462 MHz	-5.82	-5.61	-5.72	-4.31	0.70	6.15	Complies
802.11ac MCS0/Nss1 VHT40	2422 MHz	-7.88	-9.04	-8.68	-8.12	-2.39	6.15	Complies
	2437 MHz	-6.28	-6.53	-7.35	-6.84	-0.71	6.15	Complies
	2452 MHz	-7.12	-7.64	-7.86	-7.97	-1.61	6.15	Complies


Note: $Directional\ Gain = 10 \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{K=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 7.85 \text{dBi} > 6 \text{dBi}$, so limit = $8 - (7.85 - 6) = 6.15 \text{dBm/3kHz}$.

Note: All the test values were listed in the report.


For plots, only the channel with worse result was shown.

For non-beamforming function:


Power Density Plot on Configuration IEEE 802.11b / 2437 MHz / Chain 1




Power Density Plot on Configuration IEEE 802.11b / 2437 MHz / Chain 2




Power Density Plot on Configuration IEEE 802.11b / 2437 MHz / Chain 3




Power Density Plot on Configuration IEEE 802.11b / 2437 MHz / Chain 4




Power Density Plot on Configuration IEEE 802.11g / 2437 MHz / Chain 1



Power Density Plot on Configuration IEEE 802.11g / 2437 MHz / Chain 2




Power Density Plot on Configuration IEEE 802.11g / 2437 MHz / Chain 3




Date: 25.OCT.2015 13:02:02

Power Density Plot on Configuration IEEE 802.11g / 2437 MHz / Chain 4




Date: 25.OCT.2015 13:01:20


Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 2437 MHz / Chain 1




Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 2437 MHz / Chain 2




Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 2437 MHz / Chain 3




Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 2437 MHz / Chain 4




Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2437 MHz / Chain 1




Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2437 MHz / Chain 2



Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2437 MHz / Chain 3




Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2437 MHz / Chain 4




For beamforming function:

Power Density Plot on Configuration IEEE 802.11ac MCS1/Nss1 VHT20 / 2437 MHz / Chain 1




Date: 21.JAN.2016 21:00:00

Power Density Plot on Configuration IEEE 802.11ac MCS1/Nss1 VHT20 / 2437 MHz / Chain 2




Date: 21.JAN.2016 20:59:24

Power Density Plot on Configuration IEEE 802.11ac MCS1/Nss1 VHT20 / 2437 MHz / Chain 3




Date: 21.JAN.2016 20:58:54

Power Density Plot on Configuration IEEE 802.11ac MCS1/Nss1 VHT20 / 2437 MHz / Chain 4




Date: 21.JAN.2016 20:58:12

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2437 MHz / Chain 1




Date: 21.JAN.2016 20:42:56

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2437 MHz / Chain 2




Date: 21.JAN.2016 20:44:37

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2437 MHz / Chain 3



Date: 21.JAN.2016 20:45:05

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2437 MHz / Chain 4



Date: 21.JAN.2016 20:46:27

4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

4.4.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the Spectrum Analyzer.

6dB Spectrum Bandwidth	
Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RBW	100kHz
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto
99% Occupied Bandwidth	
Spectrum Parameters	Setting
Span	1.5 times to 5.0 times the OBW
RBW	1 % to 5 % of the OBW
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold

4.4.3. Test Procedures

For Radiated 6dB Bandwidth Measurement:

1. The transmitter was radiated to the spectrum analyzer in peak hold mode.
2. Test was performed in accordance with KDB558074 D01 v03r04 for Performing Compliance Measurements on Digital Transmission Systems (DTS) - section 8.0 DTS bandwidth = > 8.1 Option 1.
3. Multiple antenna system was performed in accordance with KDB 662911 D01 v02r01 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. Measured the spectrum width with power higher than 6dB below carrier.

4.4.4. Test Setup Layout

For Radiated 6dB Bandwidth Measurement:

This test setup layout is the same as that shown in section 4.5.4.

4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	24°C	Humidity	55%
Test Engineer	Clemens Fang / Peter Wu		

For non-beamforming function:

Mode	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
802.11b	2412 MHz	3.59	10.33	500	Complies
	2437 MHz	8.52	13.72	500	Complies
	2462 MHz	5.04	10.59	500	Complies
802.11g	2412 MHz	15.30	16.24	500	Complies
	2437 MHz	6.03	15.98	500	Complies
	2462 MHz	6.61	15.89	500	Complies
802.11ac MCS0/Nss1 VHT20	2412 MHz	12.81	17.11	500	Complies
	2437 MHz	6.38	16.85	500	Complies
	2462 MHz	6.90	16.76	500	Complies
802.11ac MCS0/Nss1 VHT40	2422 MHz	35.71	36.47	500	Complies
	2437 MHz	35.71	36.61	500	Complies
	2452 MHz	35.71	36.47	500	Complies

For beamforming function:


Mode	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
802.11ac MCS1/Nss1 VHT20	2412 MHz	17.28	17.80	500	Complies
	2437 MHz	16.29	17.71	500	Complies
	2462 MHz	17.33	17.80	500	Complies
802.11ac MCS0/Nss1 VHT40	2422 MHz	32.00	36.18	500	Complies
	2437 MHz	35.13	36.32	500	Complies
	2452 MHz	35.13	36.47	500	Complies

Note: All the test values were listed in the report.

For plots, only the channel with worse result was shown.


For non-beamforming function:

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2412 MHz / Chain 1 + Chain 2 + Chain 3 + Chain 4




Date: 15.FEB.2016 20:34:03

99% Occupied Bandwidth Plot on Configuration IEEE 802.11b / 2437 MHz / Chain 1 + Chain 2 + Chain 3 + Chain 4




Date: 15.FEB.2016 21:06:55


6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2437 MHz / Chain 1 + Chain 2 + Chain 3 + Chain 4



99% Occupied Bandwidth Plot on Configuration IEEE 802.11g / 2412 MHz / Chain 1 + Chain 2 + Chain 3 + Chain 4




6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 2437 MHz / Chain 1 + Chain 2 + Chain 3 + Chain 4




Date: 15.FEB.2016 20:43:54

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 2412 MHz / Chain 1 + Chain 2 + Chain 3




Date: 15.FEB.2016 21:00:29

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2422 MHz /
Chain 1 + Chain 2 + Chain 3 + Chain 4



Date: 15.FEB.2016 20:48:05

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2437 MHz /
Chain 1 + Chain 2 + Chain 3 + Chain 4




Date: 15.FEB.2016 20:57:34

For beamforming function:

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS1/Nss1 VHT20 / 2437 MHz /

Chain 1 + Chain 2 + Chain 3 + Chain 4




99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS1/Nss1 VHT20 / 2412 MHz /

Chain 1 + Chain 2 + Chain 3 + Chain 4



6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2422 MHz /
Chain 1 + Chain 2 + Chain 3 + Chain 4



Date: 15.FEB.2016 21:27:00

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2452 MHz /
Chain 1 + Chain 2 + Chain 3 + Chain 4



Date: 15.FEB.2016 21:22:35

4.5. Radiated Emissions Measurement

4.5.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 1/T for Average
RBW / VBW (Emission in non-restricted band)	100kHz / 300kHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RBW 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RBW 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 1m & 3m far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 m to 4 m) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 1/T VBW for average reading in spectrum analyzer.
7. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
8. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
9. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout


For Radiated Emissions: 9kHz ~30MHz



For Radiated Emissions: 30MHz~1GHz



For Radiated Emissions: Above 1GHz



4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

For non-beamforming function:

The EUT was programmed to be in continuously transmitting mode.

For beamforming function:

The EUT was programmed to be in beamforming transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	24°C	Humidity	55%
Test Engineer	Eason Chen / Gino Huang / Brian Sun / Lucke Hsieh	Configurations	Normal Link
Test Date	Feb. 15, 2016		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	24°C	Humidity	55%
Test Engineer	Eason Chen / Gino Huang / Brian Sun / Lucke Hsieh	Configurations	Normal Link

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	218.18	37.47	46.00	-8.53	50.48	1.18	16.10	30.29	150	215	Peak	HORIZONTAL
2	359.80	38.81	46.00	-7.19	44.98	1.47	21.14	28.78	150	9	Peak	HORIZONTAL
3	503.36	40.67	46.00	-5.33	42.15	1.77	23.76	27.01	100	68	Peak	HORIZONTAL
4	647.89	41.74	46.00	-4.26	42.38	2.01	25.28	27.93	150	92	Peak	HORIZONTAL
5	791.45	37.10	46.00	-8.90	35.81	2.27	26.43	27.41	150	39	Peak	HORIZONTAL
6	935.98	39.78	46.00	-6.22	36.25	2.42	27.69	26.58	125	84	Peak	HORIZONTAL

Vertical



	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	30.97	36.90	40.00	-3.10	36.52	0.53	24.69	24.84	100	291	Peak	VERTICAL
2	51.34	36.64	40.00	-3.36	46.49	0.61	14.03	24.49	100	49	Peak	VERTICAL
3	359.80	35.31	46.00	-10.69	41.48	1.47	21.14	28.78	150	168	Peak	VERTICAL
4	503.36	41.75	46.00	-4.25	43.23	1.77	23.76	27.01	125	194	Peak	VERTICAL
5	647.89	39.26	46.00	-6.74	39.90	2.01	25.28	27.93	125	358	Peak	VERTICAL
6	935.98	37.19	46.00	-8.81	33.66	2.42	27.69	26.58	100	1	Peak	VERTICAL

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)

Temperature	24°C	Humidity	55%
Test Engineer	Eason Chen / Gino Huang / Brian Sun / Lucke Hsieh	Configurations	IEEE 802.11b CH 1 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Dec. 20, 2015	Test Function	Non-beamforming function

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4823.90	46.31	74.00	-27.69	43.09	7.18	32.58	36.54	128	262	HORIZONTAL	Peak
2	4823.93	36.57	54.00	-17.43	33.35	7.18	32.58	36.54	128	262	HORIZONTAL	Average

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4823.96	49.56	74.00	-24.44	46.34	7.18	32.58	36.54	158	328	VERTICAL	Peak
2	4824.01	43.39	54.00	-10.61	40.17	7.18	32.58	36.54	158	328	VERTICAL	Average

Temperature	24°C	Humidity	55%
Test Engineer	Eason Chen / Gino Huang / Brian Sun / Lucke Hsieh	Configurations	IEEE 802.11b CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Dec. 20, 2015	Test Function	Non-beamforming function

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4873.94	36.34	54.00	-17.66	33.07	7.12	32.68	36.53	121	53	HORIZONTAL	Average
2	4873.98	45.94	74.00	-28.06	42.67	7.12	32.68	36.53	121	53	HORIZONTAL	Peak
3	7310.02	51.71	74.00	-22.29	41.75	8.74	37.24	36.02	150	255	HORIZONTAL	Peak
4	7310.05	38.79	54.00	-15.21	28.83	8.74	37.24	36.02	150	255	HORIZONTAL	Average

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4873.91	49.86	74.00	-24.14	46.59	7.12	32.68	36.53	154	21	VERTICAL	Peak
2	4873.97	44.72	54.00	-9.28	41.45	7.12	32.68	36.53	154	21	VERTICAL	Average
3	7309.79	54.46	74.00	-19.54	44.50	8.74	37.24	36.02	116	171	VERTICAL	Peak
4	7310.27	45.37	54.00	-8.63	35.41	8.74	37.24	36.02	116	171	VERTICAL	Average

Temperature	24°C	Humidity	55%
Test Engineer	Eason Chen / Gino Huang / Brian Sun / Lucke Hsieh	Configurations	IEEE 802.11b CH 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Dec. 20, 2015	Test Function	Non-beamforming function

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4923.94	47.61	74.00	-26.39	44.31	7.05	32.78	36.53	112	130	HORIZONTAL	Peak
2	4924.01	39.01	54.00	-14.99	35.71	7.05	32.78	36.53	112	130	HORIZONTAL	Average
3	7385.98	52.14	74.00	-21.86	42.17	8.63	37.35	36.01	147	231	HORIZONTAL	Peak
4	7386.47	39.46	54.00	-14.54	29.49	8.63	37.35	36.01	147	231	HORIZONTAL	Average

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4923.84	49.19	74.00	-24.81	45.89	7.05	32.78	36.53	164	15	VERTICAL	Peak
2	4923.99	42.99	54.00	-11.01	39.69	7.05	32.78	36.53	164	15	VERTICAL	Average
3	7384.98	55.64	74.00	-18.36	45.67	8.63	37.35	36.01	100	172	VERTICAL	Peak
4	7386.71	46.89	54.00	-7.11	36.92	8.63	37.35	36.01	100	172	VERTICAL	Average

Temperature	24°C	Humidity	55%
Test Engineer	Eason Chen / Gino Huang / Brian Sun / Lucke Hsieh	Configurations	IEEE 802.11g CH 1 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Dec. 20, 2015	Test Function	Non-beamforming function

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4823.06	44.48	74.00	-29.52	41.26	7.18	32.58	36.54	160	55	HORIZONTAL	Peak
2	4824.31	31.57	54.00	-22.43	28.35	7.18	32.58	36.54	160	55	HORIZONTAL	Average

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4823.42	44.48	74.00	-29.52	41.26	7.18	32.58	36.54	173	319	VERTICAL	Peak
2	4823.92	32.70	54.00	-21.30	29.48	7.18	32.58	36.54	173	319	VERTICAL	Average

Temperature	24°C	Humidity	55%
Test Engineer	Eason Chen / Gino Huang / Brian Sun / Lucke Hsieh	Configurations	IEEE 802.11g CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Dec. 20, 2015	Test Function	Non-beamforming function

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4873.97	31.29	54.00	-22.71	28.02	7.12	32.68	36.53	170	70	HORIZONTAL Average
2	4874.25	44.00	74.00	-30.00	40.73	7.12	32.68	36.53	170	70	HORIZONTAL Peak
3	7311.68	51.39	74.00	-22.61	41.43	8.74	37.24	36.02	160	215	HORIZONTAL Peak
4	7311.80	38.29	54.00	-15.71	28.33	8.74	37.24	36.02	160	215	HORIZONTAL Average

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4874.07	33.15	54.00	-20.85	29.88	7.12	32.68	36.53	141	352	VERTICAL Average
2	4874.24	46.97	74.00	-27.03	43.70	7.12	32.68	36.53	141	352	VERTICAL Peak
3	7310.06	38.89	54.00	-15.11	28.93	8.74	37.24	36.02	150	160	VERTICAL Average
4	7311.87	51.63	74.00	-22.37	41.67	8.74	37.24	36.02	150	161	VERTICAL Peak

Temperature	24°C	Humidity	55%
Test Engineer	Eason Chen / Gino Huang / Brian Sun / Lucke Hsieh	Configurations	IEEE 802.11g CH 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Dec. 20, 2015	Test Function	Non-beamforming function

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	cm	deg		
1	4924.27	44.81	74.00	-29.19	41.51	7.05	32.78	155	98	HORIZONTAL	Peak
2	4924.94	32.21	54.00	-21.79	28.91	7.05	32.78	155	98	HORIZONTAL	Average
3	7385.86	39.00	54.00	-15.00	29.03	8.63	37.35	164	173	HORIZONTAL	Average
4	7386.19	52.19	74.00	-21.81	42.22	8.63	37.35	164	173	HORIZONTAL	Peak

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	cm	deg		
1	4923.24	45.13	74.00	-28.87	41.84	7.07	32.75	161	325	VERTICAL	Peak
2	4924.04	32.56	54.00	-21.44	29.26	7.05	32.78	161	325	VERTICAL	Average
3	7385.95	51.78	74.00	-22.22	41.81	8.63	37.35	156	259	VERTICAL	Peak
4	7386.91	39.06	54.00	-14.94	29.09	8.63	37.35	156	259	VERTICAL	Average

Temperature	24°C	Humidity	55%
Test Engineer	Eason Chen / Gino Huang / Brian Sun / Lucke Hsieh	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 1 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Dec. 20, 2015	Test Function	Non-beamforming function

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4823.54	31.83	54.00	-22.17	28.61	7.18	32.58	36.54	135	255	HORIZONTAL Average
2	4824.30	45.30	74.00	-28.70	42.08	7.18	32.58	36.54	135	255	HORIZONTAL Peak

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4823.72	44.73	74.00	-29.27	41.51	7.18	32.58	36.54	163	360	VERTICAL Peak
2	4824.02	32.50	54.00	-21.50	29.28	7.18	32.58	36.54	163	360	VERTICAL Average

Temperature	24°C	Humidity	55%
Test Engineer	Eason Chen / Gino Huang / Brian Sun / Lucke Hsieh	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Dec. 20, 2015	Test Function	Non-beamforming function

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4873.83	31.23	54.00	-22.77	27.96	7.12	32.68	36.53	165	175	HORIZONTAL Average
2	4874.35	44.40	74.00	-29.60	41.13	7.12	32.68	36.53	165	175	HORIZONTAL Peak
3	7311.89	51.26	74.00	-22.74	41.30	8.74	37.24	36.02	150	112	HORIZONTAL Peak
4	7311.92	38.22	54.00	-15.78	28.26	8.74	37.24	36.02	150	112	HORIZONTAL Average

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4874.26	31.75	54.00	-22.25	28.48	7.12	32.68	36.53	141	111	VERTICAL Average
2	4874.59	44.83	74.00	-29.17	41.56	7.12	32.68	36.53	141	111	VERTICAL Peak
3	7311.69	50.73	74.00	-23.27	40.77	8.74	37.24	36.02	160	201	VERTICAL Peak
4	7311.98	38.43	54.00	-15.57	28.47	8.74	37.24	36.02	160	201	VERTICAL Average

Temperature	24°C	Humidity	55%
Test Engineer	Eason Chen / Gino Huang / Brian Sun / Lucke Hsieh	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Dec. 20, 2015	Test Function	Non-beamforming function

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4923.84	44.48	74.00	-29.52	41.18	7.05	32.78	36.53	178	163	HORIZONTAL Peak
2	4923.94	32.20	54.00	-21.80	28.90	7.05	32.78	36.53	178	163	HORIZONTAL Average
3	7385.95	38.88	54.00	-15.12	28.91	8.63	37.35	36.01	156	77	HORIZONTAL Average
4	7386.48	51.99	74.00	-22.01	42.02	8.63	37.35	36.01	156	77	HORIZONTAL Peak

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4924.07	32.36	54.00	-21.64	29.06	7.05	32.78	36.53	166	284	VERTICAL Average
2	4924.57	45.60	74.00	-28.40	42.30	7.05	32.78	36.53	166	284	VERTICAL Peak
3	7385.79	39.01	54.00	-14.99	29.04	8.63	37.35	36.01	146	190	VERTICAL Average
4	7385.86	52.26	74.00	-21.74	42.29	8.63	37.35	36.01	146	190	VERTICAL Peak

Temperature	24°C	Humidity	55%
Test Engineer	Eason Chen / Gino Huang / Brian Sun / Lucke Hsieh	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 3 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Dec. 14, 2015	Test Function	Non-beamforming function

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4843.16	48.05	74.00	-25.95	42.48	7.11	33.47	35.01	Peak	142	122	HORIZONTAL
2	4845.52	35.45	54.00	-18.55	29.88	7.11	33.47	35.01	Average	142	122	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4843.95	40.09	54.00	-13.91	34.52	7.11	33.47	35.01	Average	146	343	VERTICAL
2	4844.20	52.46	74.00	-21.54	46.89	7.11	33.47	35.01	Peak	146	343	VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Eason Chen / Gino Huang / Brian Sun / Lucke Hsieh	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Dec. 14, 2015	Test Function	Non-beamforming function

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4874.84	58.53	74.00	-15.47	52.89	7.12	33.53	35.01	Peak	140	232	HORIZONTAL
2	4875.94	45.55	54.00	-8.45	39.91	7.12	33.53	35.01	Average	140	232	HORIZONTAL
3	7306.42	50.82	74.00	-23.18	40.99	8.72	36.39	35.28	Peak	123	129	HORIZONTAL
4	7307.26	38.13	54.00	-15.87	28.30	8.72	36.39	35.28	Average	123	129	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4873.42	51.94	54.00	-2.06	46.30	7.12	33.53	35.01	Average	101	196	VERTICAL
2	4873.78	65.93	74.00	-8.07	60.29	7.12	33.53	35.01	Peak	101	196	VERTICAL
3	7306.56	52.14	74.00	-21.86	42.31	8.72	36.39	35.28	Peak	111	339	VERTICAL
4	7315.50	41.76	54.00	-12.24	31.93	8.72	36.39	35.28	Average	111	339	VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Eason Chen / Gino Huang / Brian Sun / Lucke Hsieh	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 9 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Dec. 14, 2015	Test Function	Non-beamforming function

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4903.28	44.75	54.00	-9.25	39.04	7.13	33.59	35.01	Average	112	2	HORIZONTAL
2	4904.78	58.16	74.00	-15.84	52.45	7.13	33.59	35.01	Peak	112	2	HORIZONTAL
3	7351.26	39.01	54.00	-14.99	29.02	8.80	36.48	35.29	Average	142	249	HORIZONTAL
4	7356.56	53.04	74.00	-20.96	43.05	8.80	36.48	35.29	Peak	142	249	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4904.90	50.78	54.00	-3.22	45.07	7.13	33.59	35.01	Average	116	198	VERTICAL
2	4906.20	63.77	74.00	-10.23	58.06	7.13	33.59	35.01	Peak	116	198	VERTICAL
3	7356.36	39.13	54.00	-14.87	29.14	8.80	36.48	35.29	Average	147	212	VERTICAL
4	7358.36	52.12	74.00	-21.88	41.99	8.89	36.53	35.29	Peak	147	212	VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Eason Chen / Gino Huang / Brian Sun / Lucke Hsieh	Configurations	IEEE 802.11ac MCS1/Nss1 VHT20 CH 1 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Dec. 19, 2015	Test Function	Beamforming function

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4823.97	37.10	54.00	-16.90	28.81	8.11	33.11	32.93	102	136	Average	HORIZONTAL
2	4824.62	48.57	74.00	-25.43	40.28	8.11	33.11	32.93	102	136	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4823.11	49.22	74.00	-24.78	40.93	8.11	33.11	32.93	104	123	Peak	VERTICAL
2	4823.91	37.91	54.00	-16.09	29.62	8.11	33.11	32.93	104	123	Average	VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Eason Chen / Gino Huang / Brian Sun / Lucke Hsieh	Configurations	IEEE 802.11ac MCS1/Nss1 VHT20 CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Dec. 19, 2015	Test Function	Beamforming function

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4873.97	46.08	54.00	-7.92	37.84	7.94	33.23	32.93	106	155	Average	HORIZONTAL
2	4873.98	53.85	74.00	-20.15	45.61	7.94	33.23	32.93	106	155	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4873.91	47.85	54.00	-6.15	39.61	7.94	33.23	32.93	104	142	Average	VERTICAL
2	4874.46	53.81	74.00	-20.19	45.57	7.94	33.23	32.93	104	142	Peak	VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Eason Chen / Gino Huang / Brian Sun / Lucke Hsieh	Configurations	IEEE 802.11ac MCS1/Nss1 VHT20 CH 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Dec. 19, 2015	Test Function	Beamforming function

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4924.19	49.36	74.00	-24.64	41.15	7.78	33.35	32.92	106	178	Peak	HORIZONTAL
2	4924.21	37.49	54.00	-16.51	29.28	7.78	33.35	32.92	106	178	Average	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4924.00	41.62	54.00	-12.38	33.41	7.78	33.35	32.92	108	166	Average	VERTICAL
2	4924.05	49.77	74.00	-24.23	41.56	7.78	33.35	32.92	108	166	Peak	VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Eason Chen / Gino Huang / Brian Sun / Lucke Hsieh	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 3 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Dec. 19, 2015	Test Function	Beamforming function

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4843.32	35.55	54.00	-18.45	27.28	8.03	33.17	32.93	119	201	Average	HORIZONTAL
2	4844.42	51.46	74.00	-22.54	43.19	8.03	33.17	32.93	119	201	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4844.08	49.16	74.00	-24.84	40.89	8.03	33.17	32.93	116	192	Peak	VERTICAL
2	4844.25	35.79	54.00	-18.21	27.52	8.03	33.17	32.93	116	192	Average	VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Eason Chen / Gino Huang / Brian Sun / Lucke Hsieh	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Dec. 19, 2015	Test Function	Beamforming function

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4874.42	35.89	54.00	-18.11	27.65	7.94	33.23	32.93	107	26	Average	HORIZONTAL
2	4874.54	49.72	74.00	-24.28	41.48	7.94	33.23	32.93	107	26	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4874.07	35.54	54.00	-18.46	27.30	7.94	33.23	32.93	109	298	Average	VERTICAL
2	4874.32	50.55	74.00	-23.45	42.31	7.94	33.23	32.93	109	298	Peak	VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Eason Chen / Gino Huang / Brian Sun / Lucke Hsieh	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 9 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Dec. 19, 2015	Test Function	Beamforming function

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4903.26	48.44	74.00	-25.56	40.21	7.86	33.29	32.92	102	234	Peak	HORIZONTAL
2	4904.84	35.26	54.00	-18.74	27.03	7.86	33.29	32.92	102	234	Average	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4904.13	35.37	54.00	-18.63	27.14	7.86	33.29	32.92	110	67	Average	VERTICAL
2	4904.25	48.44	74.00	-25.56	40.21	7.86	33.29	32.92	110	67	Peak	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Emissions Measurement

4.6.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RBW / VBW (Emission in restricted band)	1 MHz / 3MHz for Peak, 1 MHz / 1/T for Average
RBW / VBW (30dBc in any 100 kHz bandwidth emission)	100 kHz / 300 kHz for Peak

4.6.3. Test Procedures

For Radiated band edges Measurement:

1. The test procedure is the same as section 4.5.3.

For Radiated Out of Band Emission Measurement:

1. Test was performed in accordance with KDB558074 D01 v03r04 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 10.1 Unwanted Emissions into Non-Restricted Frequency Bands Measurement Procedure.

4.6.4. Test Setup Layout

For Radiated band edges Measurement:

This test setup layout is the same as that shown in section 4.5.4.

For Radiated Out of Band Emission Measurement:

This test setup layout is the same as that shown in section 4.5.4.

4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

For non-beamforming function:

The EUT was programmed to be in continuously transmitting mode.

For beamforming function:

The EUT was programmed to be in beamforming transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	24°C	Humidity	55%
Test Engineer	Eason Chen / Gino Huang / Brian Sun / Lucke Hsieh	Configurations	IEEE 802.11b CH 1, 6, 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Dec. 20, 2015 / Dec. 28, 2015	Test Function	Non-beamforming function

Channel 1

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2386.80	60.20	74.00	-13.80	27.78	4.52	27.90	0.00	307	70 VERTICAL	Peak
2	2389.20	50.00	54.00	-4.00	17.58	4.52	27.90	0.00	307	70 VERTICAL	Average
3	2412.80	118.42			85.99	4.55	27.88	0.00	307	70 VERTICAL	Average
4	2413.00	122.46			90.03	4.55	27.88	0.00	307	70 VERTICAL	Peak

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2387.80	57.81	74.00	-16.19	25.39	4.52	27.90	0.00	232	306 VERTICAL	Peak
2	2388.20	47.38	54.00	-6.62	14.96	4.52	27.90	0.00	232	306 VERTICAL	Average
3	2438.60	120.52			88.09	4.57	27.86	0.00	232	306 VERTICAL	Peak
4	2438.80	116.98			84.55	4.57	27.86	0.00	232	306 VERTICAL	Average
5	2486.40	46.69	54.00	-7.31	14.27	4.61	27.81	0.00	232	306 VERTICAL	Average
6	2486.40	58.51	74.00	-15.49	26.09	4.61	27.81	0.00	232	306 VERTICAL	Peak

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2461.20	116.72			84.84	4.05	27.83	0.00	318	109 VERTICAL	Average
2	2463.00	123.00			91.12	4.05	27.83	0.00	318	109 VERTICAL	Peak
3	2484.80	51.46	54.00	-2.54	19.58	4.07	27.81	0.00	318	109 VERTICAL	Average
4	2485.60	61.65	74.00	-12.35	29.77	4.07	27.81	0.00	318	109 VERTICAL	Peak

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	24°C	Humidity	55%
Test Engineer	Eason Chen / Gino Huang / Brian Sun / Lucke Hsieh	Configurations	IEEE 802.11g CH 1, 6, 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Dec. 20, 2015	Test Function	Non-beamforming function

Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	2389.40	67.22	74.00	-6.78	34.80	4.52	27.90	0.00	312	256	VERTICAL	Peak
2	2390.00	53.56	54.00	-0.44	21.14	4.52	27.90	0.00	312	256	VERTICAL	Average
3	2409.20	110.30			77.87	4.55	27.88	0.00	312	256	VERTICAL	Average
4	2409.60	121.77			89.34	4.55	27.88	0.00	312	256	VERTICAL	Peak

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	2390.00	47.93	54.00	-6.07	15.51	4.52	27.90	0.00	221	317	VERTICAL	Average
2	2390.00	60.34	74.00	-13.66	27.92	4.52	27.90	0.00	221	317	VERTICAL	Peak
3	2435.80	123.41			90.98	4.57	27.86	0.00	221	317	VERTICAL	Peak
4	2436.20	112.42			79.99	4.57	27.86	0.00	221	317	VERTICAL	Average
5	2483.50	47.83	54.00	-6.17	15.41	4.61	27.81	0.00	221	317	VERTICAL	Average
6	2483.50	59.33	74.00	-14.67	26.91	4.61	27.81	0.00	221	317	VERTICAL	Peak

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	2459.00	107.25			74.82	4.59	27.84	0.00	341	1	HORIZONTAL	Average
2	2460.00	118.22			85.79	4.59	27.84	0.00	341	1	HORIZONTAL	Peak
3	2483.50	53.55	54.00	-0.45	21.13	4.61	27.81	0.00	341	1	HORIZONTAL	Average
4	2483.50	66.36	74.00	-7.64	33.94	4.61	27.81	0.00	341	1	HORIZONTAL	Peak

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	24°C	Humidity	55%
Test Engineer	Eason Chen / Gino Huang / Brian Sun / Lucke Hsieh	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 1, 6, 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Dec. 20, 2015	Test Function	Non-beamforming function

Channel 1

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2388.20	65.94	74.00	-8.06	33.52	4.52	27.90	0.00	311	260	VERTICAL Peak
2	2390.00	53.69	54.00	-0.31	21.27	4.52	27.90	0.00	311	260	VERTICAL Average
3	2409.00	119.82			87.39	4.55	27.88	0.00	311	260	VERTICAL Peak
4	2409.20	108.57			76.14	4.55	27.88	0.00	311	260	VERTICAL Average

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2378.20	58.33	74.00	-15.67	25.91	4.51	27.91	0.00	221	316	VERTICAL Peak
2	2390.00	47.70	54.00	-6.30	15.28	4.52	27.90	0.00	221	316	VERTICAL Average
3	2435.80	121.57			89.14	4.57	27.86	0.00	221	316	VERTICAL Peak
4	2436.20	110.81			78.38	4.57	27.86	0.00	221	316	VERTICAL Average
5	2483.50	47.63	54.00	-6.37	15.21	4.61	27.81	0.00	221	316	VERTICAL Average
6	2483.50	59.26	74.00	-14.74	26.84	4.61	27.81	0.00	221	316	VERTICAL Peak

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2459.20	105.99			73.56	4.59	27.84	0.00	303	0	HORIZONTAL Average
2	2460.20	118.60			86.17	4.59	27.84	0.00	303	0	HORIZONTAL Peak
3	2483.50	52.98	54.00	-1.02	20.56	4.61	27.81	0.00	303	0	HORIZONTAL Average
4	2485.00	67.02	74.00	-6.98	34.60	4.61	27.81	0.00	303	0	HORIZONTAL Peak

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	24°C	Humidity	55%
Test Engineer	Eason Chen / Gino Huang / Brian Sun / Lucke Hsieh	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 3, 6, 9 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Dec. 14, 2015 / Dec. 28, 2015	Test Function	Non-beamforming function

Channel 3

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	2389.60	65.80	74.00	-8.20	33.93	3.97	27.90	0.00	301	291	VERTICAL	Peak
2	2390.00	53.52	54.00	-0.48	21.65	3.97	27.90	0.00	301	291	VERTICAL	Average
3	2410.00	104.38			72.51	3.99	27.88	0.00	301	291	VERTICAL	Average
4	2411.20	115.11			83.23	4.00	27.88	0.00	301	291	VERTICAL	Peak

Item 3, 4 are the fundamental frequency at 2422 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	2384.60	66.37	74.00	-7.63	33.20	4.96	28.21	0.00	Peak	252	287	VERTICAL
2	2385.80	52.40	54.00	-1.60	19.23	4.96	28.21	0.00	Average	252	287	VERTICAL
3	2424.20	117.11			83.84	5.00	28.27	0.00	Peak	252	287	VERTICAL
4	2425.40	106.03			72.74	5.01	28.28	0.00	Average	252	287	VERTICAL
5	2483.80	68.22	74.00	-5.78	34.78	5.06	28.38	0.00	Peak	252	287	VERTICAL
6	2484.20	53.77	54.00	-0.23	20.33	5.06	28.38	0.00	Average	252	287	VERTICAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 9

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	2440.40	117.22			83.89	5.02	28.31	0.00	Peak	245	283	VERTICAL
2	2440.80	106.72			73.39	5.02	28.31	0.00	Average	245	283	VERTICAL
3	2491.60	68.75	74.00	-5.25	35.29	5.07	28.39	0.00	Peak	245	283	VERTICAL
4	2499.20	53.86	54.00	-0.14	20.38	5.08	28.40	0.00	Average	245	283	VERTICAL

Item 1, 2 are the fundamental frequency at 2452 MHz.

Temperature	24°C	Humidity	55%
Test Engineer	Eason Chen / Gino Huang / Brian Sun / Lucke Hsieh	Configurations	IEEE 802.11ac MCS1/Nss1 VHT20 CH 1, 6, 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Dec. 19, 2015	Test Function	Beamforming function

Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	2390.00	72.01	74.00	-1.99	38.69	5.01	28.31	0.00	274	61	Peak	VERTICAL
2	2390.00	53.65	54.00	-0.35	20.33	5.01	28.31	0.00	274	61	Average	VERTICAL
3	2410.80	117.82			84.43	5.04	28.35	0.00	274	61	Peak	VERTICAL
4	2411.00	108.62			75.23	5.04	28.35	0.00	274	61	Average	VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	2390.00	72.59	74.00	-1.41	39.27	5.01	28.31	0.00	261	116	Peak	VERTICAL
2	2390.00	52.37	54.00	-1.63	19.05	5.01	28.31	0.00	261	116	Average	VERTICAL
3	2433.80	120.27			86.81	5.07	28.39	0.00	261	116	Peak	VERTICAL
4	2436.20	113.49			80.03	5.07	28.39	0.00	261	116	Average	VERTICAL
5	2483.50	50.36	54.00	-3.64	16.76	5.12	28.48	0.00	261	116	Average	VERTICAL
6	2483.90	68.37	74.00	-5.63	34.77	5.12	28.48	0.00	261	116	Peak	VERTICAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	2456.40	116.63			83.11	5.09	28.43	0.00	278	298	Peak	VERTICAL
2	2463.20	111.00			77.46	5.10	28.44	0.00	278	298	Average	VERTICAL
3	2483.50	72.23	74.00	-1.77	38.63	5.12	28.48	0.00	278	298	Peak	VERTICAL
4	2483.50	53.64	54.00	-0.36	20.04	5.12	28.48	0.00	278	298	Average	VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	24°C	Humidity	55%
Test Engineer	Eason Chen / Gino Huang / Brian Sun / Lucke Hsieh	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 3, 6, 9 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Dec. 19, 2015	Test Function	Beamforming function

Channel 3

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	2386.80	73.50	74.00	-0.50	40.18	5.01	28.31	0.00	271	116	Peak	VERTICAL
2	2389.20	53.65	54.00	-0.35	20.33	5.01	28.31	0.00	271	116	Average	VERTICAL
3	2409.20	105.42			72.03	5.04	28.35	0.00	271	116	Average	VERTICAL
4	2426.00	114.03			80.59	5.06	28.38	0.00	271	116	Peak	VERTICAL

Item 3, 4 are the fundamental frequency at 2422 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	2387.80	71.19	74.00	-2.81	37.87	5.01	28.31	0.00	278	323	Peak	HORIZONTAL
2	2390.00	51.01	54.00	-2.99	17.69	5.01	28.31	0.00	278	323	Average	HORIZONTAL
3	2424.40	114.27			80.85	5.05	28.37	0.00	278	323	Peak	HORIZONTAL
4	2426.20	107.54			74.10	5.06	28.38	0.00	278	323	Average	HORIZONTAL
5	2483.50	47.69	54.00	-6.31	14.09	5.12	28.48	0.00	278	323	Average	HORIZONTAL
6	2486.80	66.35	74.00	-7.65	32.75	5.12	28.48	0.00	278	323	Peak	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 9

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	2462.80	108.88			75.34	5.10	28.44	0.00	267	296	Average	VERTICAL
2	2464.00	113.41			79.87	5.10	28.44	0.00	267	296	Peak	VERTICAL
3	2485.60	70.19	74.00	-3.81	36.59	5.12	28.48	0.00	267	296	Peak	VERTICAL
4	2486.80	52.18	54.00	-1.82	18.58	5.12	28.48	0.00	267	296	Average	VERTICAL

Item 1, 2 are the fundamental frequency at 2452 MHz.

Note:


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

For Emission not in Restricted Band


For non-beamforming function:

Plot on Configuration IEEE 802.11b / Reference Level




Date: 20.DEC.2015 15:01:44

Plot on Configuration IEEE 802.11b / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 20.DEC.2015 15:02:48

Plot on Configuration IEEE 802.11b / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 20.DEC.2015 15:03:22

Plot on Configuration IEEE 802.11b / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 20.DEC.2015 15:04:41

Plot on Configuration IEEE 802.11b / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 20.DEC.2015 15:04:19

Plot on Configuration IEEE 802.11g / Reference Level




Date: 20.DEC.2015 15:09:42

Plot on Configuration IEEE 802.11g / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 20.DEC.2015 15:10:49

Plot on Configuration IEEE 802.11g / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 20.DEC.2015 15:11:24

Plot on Configuration IEEE 802.11g / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 20.DEC.2015 15:12:44

Plot on Configuration IEEE 802.11g / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 20.DEC.2015 15:12:13

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Reference Level




Date: 20.DEC.2015 15:16:43

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 20.DEC.2015 15:18:01

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 20.DEC.2015 15:18:48

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 20.DEC.2015 15:20:27

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 20.DEC.2015 15:22:36

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Reference Level




Date: 14.DEC.2015 19:40:34

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / CH 3 / 30MHz~2400MHz (down 30dBc)




Date: 14.DEC.2015 19:42:08

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / CH 3 / 2500MHz~26500MHz (down 30dBc)




Date: 14.DEC.2015 19:43:00

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / CH 9 / 30MHz~2400MHz (down 30dBc)



Date: 14.DEC.2015 19:44:37


Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / CH 9 / 2500MHz~26500MHz (down 30dBc)



Date: 14.DEC.2015 19:44:03


For beamforming function:

Plot on Configuration IEEE 802.11ac MCS1/Nss1 VHT20 / Reference Level




Date: 19.JAN.2016 22:03:21

Plot on Configuration IEEE 802.11ac MCS1/Nss1 VHT20 / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 19.JAN.2016 22:06:31

Plot on Configuration IEEE 802.11ac MCS1/Nss1 VHT20 / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 19.JAN.2016 22:06:55

Plot on Configuration IEEE 802.11ac MCS1/Nss1 VHT20 / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 19.JAN.2016 22:08:33

Plot on Configuration IEEE 802.11ac MCS1/Nss1 VHT20 / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 19.JAN.2016 22:10:18

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Reference Level




Date: 19.JAN.2016 22:12:23

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / CH 3 / 30MHz~2400MHz (down 30dBc)




Date: 19.JAN.2016 22:14:54

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / CH 3 / 2500MHz~26500MHz (down 30dBc)




Date: 19.JAN.2016 22:16:01

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / CH 9 / 30MHz~2400MHz (down 30dBc)



Date: 19.JAN.2016 22:17:55

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / CH 9 / 2500MHz~26500MHz (down 30dBc)



Date: 19.JAN.2016 22:17:28

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100355	9kHz ~ 2.75GHz	Apr. 22, 2015	Conduction (CO01-CB)
EMI Receiver	Agilent	N9038A	My52260123	9kHz ~ 8.45GHz	Jan. 27, 2016	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Dec. 08, 2015	Conduction (CO01-CB)
LISN	Schwarzbeck	NSLK 8127	8127647	9kHz ~ 30MHz	Dec. 23, 2015	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	150kHz ~ 30MHz	May 25, 2015	Conduction (CO01-CB)
Software	Audix	E3	6.120210n	-	N.C.R.	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	37880	20MHz ~ 2GHz	Sep. 03, 2015	Radiation (O3CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz ~ 18GHz	Oct. 22, 2015	Radiation (O3CH01-CB)
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Jul. 21, 2015	Radiation (O3CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Feb. 24, 2015	Radiation (O3CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Mar. 15, 2016	Radiation (O3CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Jan. 12, 2015	Radiation (O3CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Jan. 18, 2016	Radiation (O3CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26GHz ~ 40GHz	Nov.13, 2015	Radiation (O3CH01-CB)
Spectrum Analyzer	R&S	FSP40	100056	9kHz ~ 40GHz	Oct. 27, 2015	Radiation (O3CH01-CB)
EMI Receiver	Agilent	N9038A	MY52260123	9kHz ~ 8.4GHz	Jan. 21, 2015	Radiation (O3CH01-CB)
EMI Test	R&S	ESCS	100355	9kHz ~ 2.75GHz	May 16, 2016	Radiation (O3CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz ~ 1 GHz	Nov. 02, 2015	Radiation (O3CH01-CB)
RF Cable-high	Woken	High Cable-16	N/A	1 GHz ~ 18 GHz	Nov. 02, 2015	Radiation (O3CH01-CB)
RF Cable-high	Woken	High Cable-17	N/A	1 GHz ~ 18 GHz	Nov. 02, 2015	Radiation (O3CH01-CB)
RF Cable-high	Woken	High Cable-40G-1	N/A	18GHz ~ 40 GHz	Nov. 02, 2015	Radiation (O3CH01-CB)
RF Cable-high	Woken	High Cable-40G-2	N/A	18GHz ~ 40 GHz	Nov. 02, 2015	Radiation (O3CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9kHz - 30 MHz	Mar. 12, 2015*	Radiation (O3CH01-CB)
Spectrum analyzer	R&S	FSV40	100979	9kHz~40GHz	Dec. 12, 2014	Conducted (TH01-CB)
Spectrum analyzer	R&S	FSV40	100979	9kHz~40GHz	Dec. 09, 2015	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-7	1 GHz – 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-7	1 GHz – 26.5 GHz	Nov. 02, 2015	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-8	1 GHz – 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-8	1 GHz – 26.5 GHz	Nov. 02, 2015	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-9	1 GHz – 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-9	1 GHz – 26.5 GHz	Nov. 02, 2015	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-10	1 GHz – 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-10	1 GHz – 26.5 GHz	Nov. 02, 2015	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-6	1 GHz – 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-6	1 GHz – 26.5 GHz	Nov. 02, 2015	Conducted (TH01-CB)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Power Sensor	Agilent	U2021XA	MY53410001	50MHz~18GHz	Nov. 02, 2015	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

“*” Calibration Interval of instruments listed above is two years.

N.C.R. means Non-Calibration required.

6. MEASUREMENT UNCERTAINTY

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	3.2 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	3.6 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	3.7 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	3.5 dB	Confidence levels of 95%
Conducted Emission	1.7 dB	Confidence levels of 95%