

RF Exposure Report

Report No.: SA150408C04A

FCC ID: TE7AP500

Test Model: AP500

Received Date: Apr. 08, 2015

Test Date: Aug. 18 to 21, 2015

Issued Date: Nov. 02, 2015

Applicant: TP-LINK TECHNOLOGIES CO., LTD.

Address: Building 24 (floors 1,3,4,5) and 28 (floors1-4) Central Science and Technology Park,Shennan Rd, Nanshan, Shenzhen,China

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan R.O.C.

Test Location (1): No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan R.O.C.

Test Location (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan R.O.C.

Test Location (3): E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.



Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits For Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Antenna Gain	5
4 Calculation Result Of Maximum Conducted Power	6



A D T

Release Control Record

Issue No.	Description	Date Issued
SA150408C04A	Original release.	Nov. 02, 2015

1 Certificate of Conformity

Product: AC1900 Wireless Gigabit Access Point

Brand: TP-LINK

Test Model: AP500

Sample Status: PROTOTYPE

Applicant: TP-LINK TECHNOLOGIES CO., LTD.

Test Date: Aug. 18 to 21, 2015


Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D03

IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : , **Date:** Nov. 02, 2015
Elsie Hsu / Specialist

Approved by : , **Date:** Nov. 02, 2015
May Chen / Manager

2 RF Exposure

2.1 Limits For Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 26cm away from the body of the user.

So, this device is classified as **Mobile Device**.

3 Antenna Gain

Transmitter Circuit	Brand	Model	Antenna Gain (dBi)	Frequency range (GHz to GHz)	Antenna Type	Connector Type
Chain (0)	NA	NA	1.59	2.4-2.4835	Dipole	RP-SMA-F
			1.03	5.15-5.25		
			1.43	5.725-5.850		
Chain (1)	NA	NA	1.59	2.4-2.4835	Dipole	RP-SMA-F
			1.03	5.15-5.25		
			1.43	5.725-5.850		
Chain (2)	NA	NA	1.59	2.4-2.4835	Dipole	RP-SMA-F
			1.03	5.15-5.25		
			1.43	5.725-5.850		

4 Calculation Result Of Maximum Conducted Power

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2412-2462	985.832	6.36	26	0.50193	1
5180-5240	129.773	5.8	26	0.05808	1
5745-5825	941.704	6.2	26	0.46212	1

NOTE:

For 2412-2462MHz: Directional gain = 1.59dBi + 10log(3) = 6.36dBi

For 5180-5240MHz: Directional gain = 1.03dBi + 10log(3) = 5.8dBi

For 5745-5825MHz: Directional gain = 1.43dBi + 10log(3) = 6.2dBi

Conclusion:

Both of the 2.4GHz/5GHz can transmit simultaneously, the formula of calculated the MPE is

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

Therefore, the worst-case situation is $0.50193 / 1 + 0.46212 / 1 = 0.964$, which is less than "1". This confirmed that the device comply with FCC 1.1310 MPE limit.

--- END ---