



SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	TP-LINK TECHNOLOGIES CO., LTD.
Applicant Address	Building 24 (floors 1,3,4,5) and 28 (floors1-4) Central Science and Technology Park, Shennan Rd, Nanshan, Shenzhen, China
FCC ID	TE7C3150
Manufacturer's company	TP-LINK TECHNOLOGIES CO., LTD.
Manufacturer Address	Building 24 (floors 1,3,4,5) and 28 (floors1-4) Central Science and Technology Park, Shennan Rd, Nanshan, Shenzhen, China

Product Name	AC3150 Wireless MU-MIMO Gigabit Router
Brand Name	TP-LINK
Model No.	Archer C3150
Test Rule Part(s)	47 CFR FCC Part 15 Subpart E § 15.407
Test Freq. Range	5150 ~ 5250MHz
Received Date	Oct. 28, 2015
Final Test Date	Nov. 06, 2015
Submission Type	Original Equipment

Statement

Test result included is for the IEEE 802.11n and IEEE 802.11a/ac of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2013, 47 CFR FCC Part 15 Subpart E, KDB789033 D02 v01, KDB662911 D01 v02r01, KDB644545 D03 v01.**

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Table of Contents

1. VERIFICATION OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	4
3.3. Table for Filed Antenna.....	5
3.4. Table for Carrier Frequencies	6
3.5. Table for Test Modes	7
3.6. Table for Testing Locations.....	9
3.7. Table for Supporting Units	9
3.8. Table for Parameters of Test Software Setting	10
3.9. EUT Operation during Test	10
3.10. Duty Cycle.....	10
3.11. Test Configurations	11
4. TEST RESULT	13
4.1. AC Power Line Conducted Emissions Measurement.....	13
4.2. 26dB Bandwidth and 99% Occupied Bandwidth Measurement.....	17
4.3. Maximum Conducted Output Power Measurement.....	24
4.4. Power Spectral Density Measurement	27
4.5. Radiated Emissions Measurement	32
4.6. Band Edge Emissions Measurement	48
4.7. Frequency Stability Measurement	53
4.8. Antenna Requirements	57
5. LIST OF MEASURING EQUIPMENTS	58
6. MEASUREMENT UNCERTAINTY	59
APPENDIX A. TEST PHOTOS	A1 ~ A5
APPENDIX B. RADIATED EMISSION CO-LOCATION REPORT	B1 ~ B3



History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR5O1803AB	Rev. 01	Initial issue of report	Nov. 18, 2015

1. VERIFICATION OF COMPLIANCE

Product Name : AC3150 Wireless MU-MIMO Gigabit Router
Brand Name : TP-LINK
Model No. : Archer C3150
Applicant : TP-LINK TECHNOLOGIES CO., LTD.
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart E § 15.407

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Oct. 28, 2015 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Sam Chen

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart E				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	16.15 dB
4.2	15.407(a)	26dB Spectrum Bandwidth and 99% Occupied Bandwidth	Complies	-
4.3	15.407(a)	Maximum Conducted Output Power	Complies	3.03 dB
4.4	15.407(a)	Power Spectral Density	Complies	0.06 dB
4.5	15.407(b)	Radiated Emissions	Complies	3.37 dB
4.6	15.407(b)	Band Edge Emissions	Complies	0.02 dB
4.7	15.407(g)	Frequency Stability	Complies	-
4.8	15.203	Antenna Requirements	Complies	-

3. GENERAL INFORMATION

3.1. Product Details

Items	Description
Product Type	WLAN (4TX, 4RX)
Radio Type	Intentional Transceiver
Power Type	From power adapter
Modulation	IEEE 802.11a: OFDM IEEE 802.11n/ac: see the below table
Data Modulation	IEEE 802.11a/n: OFDM (BPSK / QPSK / 16QAM / 64QAM) IEEE 802.11ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM, 1024QAM)
Data Rate (Mbps)	IEEE 802.11a: OFDM (6/9/12/18/24/36/48/54) IEEE 802.11n/ac: see the below table
Frequency Range	5150 ~ 5250MHz
Channel Number	4 for 20MHz bandwidth ; 2 for 40MHz bandwidth 1 for 80MHz bandwidth
Channel Band Width (99%)	IEEE 802.11a: 17.28 MHz IEEE 802.11ac MCS0/Nss1 (VHT20): 18.23 MHz ; IEEE 802.11ac MCS0/Nss1 (VHT40): 36.76 MHz ; IEEE 802.11ac MCS0/Nss1 (VHT80): 74.38 MHz
Maximum Conducted Output Power	IEEE 802.11a: 26.97 dBm IEEE 802.11ac MCS0/Nss1 (VHT20): 26.96 dBm ; IEEE 802.11ac MCS0/Nss1 (VHT40): 25.18 dBm ; IEEE 802.11ac MCS0/Nss1 (VHT80): 22.67 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Items	Description
Communication Mode	<input checked="" type="checkbox"/> IP Based (Load Based) <input type="checkbox"/> Frame Based
Beamforming Function	<input type="checkbox"/> With beamforming <input checked="" type="checkbox"/> Without beamforming
Operating Mode	<input type="checkbox"/> Outdoor access point
	<input checked="" type="checkbox"/> Indoor access point
	<input type="checkbox"/> Fixed point-to-point access points
	<input type="checkbox"/> Mobile and portable client devices

Antenna and Band width

Antenna	Four (TX)		
	20 MHz	40 MHz	80 MHz
Band width Mode			
IEEE 802.11a	V	X	X
IEEE 802.11n	V	V	X
IEEE 802.11ac	V	V	V

IEEE 11n/ac Spec.

Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS
802.11n (HT20)	4	MCS0-31
802.11n (HT40)	4	MCS0-31
802.11ac (VHT20)	4	MCS 0-11/Nss1-4
802.11ac (VHT40)	4	MCS 0-11/Nss1-4
802.11ac (VHT80)	4	MCS 0-11/Nss1-4

Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput).
Then EUT supports HT20 and HT40.

Note 2: IEEE Std. 802.11ac modulation consists of VHT20, VHT40, VHT80 and VHT160 (VHT: Very High Throughput). Then EUT supports VHT20, VHT40 and VHT80.

Note 3: Modulation modes consist of below configuration:
HT20/HT40: IEEE 802.11n, VHT20/VHT40/VHT80: IEEE 802.11ac

3.2. Accessories


Power	Brand	Model No.	Rating	Remark
Adapter	Huntkey	HKA06012050-7C	Input: 100-240Vac, 50/60Hz, 1.5A Output: 12.0Vdc, 5.0A	Cable (Non-shielded, 1.6m)
Other				
Power cable*1: Non-shielded, 1.5m				

3.3. Table for Filed Antenna

Ant.	Brand	Model No.	Product Number	Antenna Type	Connector	Gain (dBi)	
						2.4GHz	5GHz
1	TP-LINK	T3060-NU000 1.0	3101500587	Dipole Antenna	RF-SMA-F	2	3
2	TP-LINK	T3060-NU000 1.0	3101500587	Dipole Antenna	RF-SMA-F	2	3
3	TP-LINK	T3060-NU000 1.0	3101500587	Dipole Antenna	RF-SMA-F	2	3
4	TP-LINK	T3060-NU000 1.0	3101500587	Dipole Antenna	RF-SMA-F	2	3

Note: The EUT has four antennas.

Chain 1, Chain 2, Chain 3 and Chain 4 could transmit/receive simultaneously.



3.4. Table for Carrier Frequencies

There are three bandwidth systems.

For 20MHz bandwidth systems, use Channel 36, 40, 44, 48.

For 40MHz bandwidth systems, use Channel 38, 46.

For 80MHz bandwidth systems, use Channel 42.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5150~5250 MHz Band 1	36	5180 MHz	44	5220 MHz
	38	5190 MHz	46	5230 MHz
	40	5200 MHz	48	5240 MHz
	42	5210 MHz	-	-

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode		Data Rate	Channel	Chain
AC Power Conducted Emission	CTX		-	-	-
Max. Conducted Output Power	11a/BPSK	Band 1	6Mbps	36/40/48	1+2+3+4
	11ac VHT20	Band 1	MCS0/Nss1	36/40/48	1+2+3+4
	11ac VHT40	Band 1	MCS0/Nss1	38/46	1+2+3+4
	11ac VHT80	Band 1	MCS0/Nss1	42	1+2+3+4
Power Spectral Density	11a/BPSK	Band 1	6Mbps	36/40/48	1+2+3+4
	11ac VHT20	Band 1	MCS0/Nss1	36/40/48	1+2+3+4
	11ac VHT40	Band 1	MCS0/Nss1	38/46	1+2+3+4
	11ac VHT80	Band 1	MCS0/Nss1	42	1+2+3+4
26dB Spectrum Bandwidth 99% Occupied Bandwidth Measurement	11a/BPSK	Band 1	6Mbps	36/40/48	1+2+3+4
	11ac VHT20	Band 1	MCS0/Nss1	36/40/48	1+2+3+4
	11ac VHT40	Band 1	MCS0/Nss1	38/46	1+2+3+4
	11ac VHT80	Band 1	MCS0/Nss1	42	1+2+3+4
Radiated Emission Below 1GHz	CTX		-	-	-
Radiated Emission Above 1GHz	11a/BPSK	Band 1	6Mbps	36/40/48	1+2+3+4
	11ac VHT20	Band 1	MCS0/Nss1	36/40/48	1+2+3+4
	11ac VHT40	Band 1	MCS0/Nss1	38/46	1+2+3+4
	11ac VHT80	Band 1	MCS0/Nss1	42	1+2+3+4
Band Edge Emission	11a/BPSK	Band 1	6Mbps	36/40/48	1+2+3+4
	11ac VHT20	Band 1	MCS0/Nss1	36/40/48	1+2+3+4
	11ac VHT40	Band 1	MCS0/Nss1	38/46	1+2+3+4
	11ac VHT80	Band 1	MCS0/Nss1	42	1+2+3+4
Frequency Stability	20 MHz	Band 1	-	40	1
	40 MHz	Band 1	-	38	1
	80 MHz	Band 1	-	42	1

Note: VHT20/VHT40 covers HT20/HT40, due to same modulation. The power setting for 802.11n HT20 and HT40 are the same or lower than 802.11ac VHT20 and VHT40.

The following test modes were performed for all tests:

AC Power Line Conducted Emissions	
Test Mode	Description
1	2.4GHz WLAN function
2	5GHz WLAN function

Mode 1 is the worst case, so it was selected to record in this test report.

Radiated Emissions Below 1GHz	
"EUT in Z axis" generated the worst test result for Radiated emission above 1GHz test, thus the measurement for Radiated emission below 1GHz test will follow this same test configuration.	
Test Mode	Description
1	EUT in Z axis (2.4GHz WLAN function)
2	EUT in Z axis (5GHz WLAN function)

Mode 2 is the worst case, so it was selected to record in this test report.

Radiated Emissions Above 1GHz	
Test Mode	Description
1	EUT in Y axis
2	EUT in Z axis

Mode 2 has been evaluated to be the worst case after evaluating. Consequently, measurement will follow this same test mode.

Co-location MPE and Radiated Emission Co-location
The EUT could be applied with 2.4GHz WLAN function and 5GHz WLAN function; therefore Co-location Maximum Permissible Exposure (Please refer to FA5O1803) and Radiated Emission Co-location (please refer to Appendix B) tests are added for simultaneously transmit between 2.4GHz WLAN function and 5GHz WLAN function.

3.6. Table for Testing Locations

Test Site Location					
Address:	No.8, Lane 724, Bo-ai St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C.				
TEL:	886-3-656-9065				
FAX:	886-3-656-9085				
Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D	-
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D	-
TH01-CB	OVEN Room	Hsin Chu	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

3.7. Table for Supporting Units

For Test Site No: 03CH01-CB and TH01-CB

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E4300	DoC

For Test Site No: CO01-CB

Support Unit	Brand	Model	FCC ID
NB	DELL	E6430	DoC
Flash disk	ADATA	C103	DoC
Flash disk	Silicon	I-Series	DoC

3.8. Table for Parameters of Test Software Setting

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Test Software Version	Mtool 2.0.2.7		
Mode	Test Frequency (MHz)		
	NCB: 20MHz		
	5180 MHz	5200 MHz	5240 MHz
802.11a	84	88	88
802.11ac MCS0/Nss1 VHT20	74	88	88
Mode	NCB: 40MHz		
	5190 MHz	5230 MHz	
802.11ac MCS0/Nss1 VHT40	64	80	
Mode	NCB: 80MHz		
	5210 MHz		
802.11ac MCS0/Nss1 VHT80	67		

3.9. EUT Operation during Test


The EUT was programmed to be in continuously transmitting mode.

3.10. Duty Cycle

Mode	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)	Duty Factor (dB)	1/T Minimum VBW (kHz)
802.11a	2.061	2.097	98.28	0.08	0.01
802.11ac MCS0/Nss1 VHT20	1.927	1.968	97.92	0.09	0.52
802.11ac MCS0/Nss1 VHT40	0.960	0.984	97.56	0.11	1.04
802.11ac MCS0/Nss1 VHT80	0.460	0.489	94.07	0.27	2.17


3.11. Test Configurations

3.11.1. AC Power Line Conduction Emissions Test Configuration



Item	Connection	Shielded	Length
1	Power cable	No	3.1m
2	RJ-45 cable	No	10m
3	RJ-45 cable*4	No	1.5m

3.11.2. Radiation Emissions Test Configuration



Item	Connection	Shielded	Length
1	Power cable	No	3.1m
2	RJ-45 cable	No	10m

4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product that is designed to connect to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 kHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
 - (3.1) All other equipment powered from additional LISN(s).
 - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	25°C	Humidity	60%
Test Engineer	Da Deng	Phase	Line
Configuration	CTX	Test Mode	Mode 1



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.1582	20.53	-35.03	55.56	10.58	9.93	0.02	LINE	Average
2	0.1582	41.94	-23.62	65.56	31.99	9.93	0.02	LINE	QP
3	0.2007	12.75	-40.83	53.58	2.80	9.93	0.02	LINE	Average
4	0.2007	33.18	-30.40	63.58	23.23	9.93	0.02	LINE	QP
5	0.2616	16.26	-35.12	51.38	6.30	9.93	0.03	LINE	Average
6	0.2616	29.40	-31.98	61.38	19.44	9.93	0.03	LINE	QP
7	0.4686	28.51	-18.03	46.54	18.53	9.94	0.04	LINE	Average
8	0.4686	32.69	-23.85	56.54	22.71	9.94	0.04	LINE	QP
9	1.2960	11.90	-34.10	46.00	1.88	9.97	0.05	LINE	Average
10	1.2960	19.49	-36.51	56.00	9.47	9.97	0.05	LINE	QP
11	3.3281	15.37	-30.63	46.00	5.30	10.01	0.06	LINE	Average
12	3.3281	20.86	-35.14	56.00	10.79	10.01	0.06	LINE	QP

Temperature	25°C	Humidity	60%
Test Engineer	Da Deng	Phase	Neutral
Configuration	CTX	Test Mode	Mode 1



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.1540	22.59	-33.19	55.78	12.79	9.78	0.02	NEUTRAL	Average
2	0.1540	41.90	-23.88	65.78	32.10	9.78	0.02	NEUTRAL	QP
3	0.1758	30.89	-23.79	54.68	21.08	9.79	0.02	NEUTRAL	Average
4	0.1758	43.70	-20.98	64.68	33.89	9.79	0.02	NEUTRAL	QP
5	0.2139	29.02	-24.03	53.05	19.21	9.79	0.02	NEUTRAL	Average
6	0.2139	40.11	-22.94	63.05	30.30	9.79	0.02	NEUTRAL	QP
7	0.4686	30.39	-16.15	46.54	20.56	9.79	0.04	NEUTRAL	Average
8	0.4686	34.14	-22.40	56.54	24.31	9.79	0.04	NEUTRAL	QP
9	1.4409	14.64	-31.36	46.00	4.75	9.83	0.06	NEUTRAL	Average
10	1.4409	21.56	-34.44	56.00	11.67	9.83	0.06	NEUTRAL	QP
11	3.0576	16.11	-29.89	46.00	6.20	9.86	0.05	NEUTRAL	Average
12	3.0576	21.26	-34.74	56.00	11.35	9.86	0.05	NEUTRAL	QP

Note:

Level = Read Level + LISN Factor + Cable Loss

4.2. 26dB Bandwidth and 99% Occupied Bandwidth Measurement

4.2.1. Limit

No restriction limits.

4.2.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

26dB Bandwidth	
Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 26dB Bandwidth
RBW	Approximately 1% of the emission bandwidth
VBW	VBW > RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto
99% Occupied Bandwidth	
Spectrum Parameters	Setting
Span	1.5 times to 5.0 times the OBW
RBW	1 % to 5 % of the OBW
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold

4.2.3. Test Procedures

For Radiated 26dB Bandwidth and 99% Occupied Bandwidth Measurement:

1. The transmitter was radiated to the spectrum analyzer in peak hold mode.
2. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

4.2.4. Test Setup Layout

For Radiated 26dB Bandwidth and 99% Occupied Bandwidth Measurement:

This test setup layout is the same as that shown in section 4.5.4.

4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test


The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of 26dB Bandwidth and 99% Occupied Bandwidth

Temperature	25°C	Humidity	45%
Test Engineer	Eddie Weng		


Mode	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
802.11a	5180 MHz	20.70	16.93
	5200 MHz	21.30	17.11
	5240 MHz	21.13	17.28
802.11ac MCS0/Nss1 VHT20	5180 MHz	21.48	18.15
	5200 MHz	21.30	18.23
	5240 MHz	21.57	18.15
802.11ac MCS0/Nss1 VHT40	5190 MHz	40.58	36.76
	5230 MHz	40.58	36.47
802.11ac MCS0/Nss1 VHT80	5210 MHz	80.00	74.38

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5180 MHz




Date: 9.NOV.2015 13:58:11

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5200 MHz




Date: 9.NOV.2015 13:59:31

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5240 MHz




Date: 9.NOV.2015 13:59:52

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5180 MHz




Date: 9.NOV.2015 14:01:19

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5200 MHz




Date: 9.NOV.2015 14:01:47

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5240 MHz




Date: 9.NOV.2015 14:02:21

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5190 MHz




Date: 9.NOV.2015 14:03:28

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5230 MHz



Date: 9.NOV.2015 14:03:49

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5210 MHz



Date: 9.NOV.2015 14:04:45

4.3. Maximum Conducted Output Power Measurement

4.3.1. Limit

Frequency Band		Limit
5.15~5.25 GHz		
Operating Mode		
<input type="checkbox"/>	Outdoor access point	The maximum conducted output power over the frequency band of operation shall not exceed 1 W (30dBm) provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).
<input checked="" type="checkbox"/>	Indoor access point	The maximum conducted output power over the frequency band of operation shall not exceed 1 W (30dBm) provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
<input type="checkbox"/>	Fixed point-to-point access points	The maximum conducted output power over the frequency band of operation shall not exceed 1 W (30dBm). Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi.
<input type="checkbox"/>	Mobile and portable client devices	The maximum conducted output power over the frequency band of operation shall not exceed 250 mW (24dBm) provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Detector	AVERAGE

4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the power meter.
2. Test was performed in accordance with KDB789033 D02 v01 for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - section (E) Maximum conducted output power =>3. Measurement using a Power Meter (PM) =>b) Method PM-G (Measurement using a gated RF average power meter).
3. Multiple antenna systems was performed in accordance with KDB662911 D01 v02r01 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. When measuring maximum conducted output power with multiple antenna systems, add every result of the values by mathematic formula.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Maximum Conducted Output Power

Temperature	25°C	Humidity	45%
Test Engineer	Eddie Weng	Test Date	Oct. 30, 2015~Nov. 09, 2015

Mode	Frequency	Conducted Power (dBm)					Max. Limit (dBm)	Result
		Chain 1	Chain 2	Chain 3	Chain 4	Total		
802.11a	5180 MHz	19.72	20.01	19.68	20.09	25.90	30.00	Complies
	5200 MHz	20.72	20.79	21.02	21.06	26.92	30.00	Complies
	5240 MHz	21.12	20.75	21.05	20.88	26.97	30.00	Complies
802.11ac MCS0/Nss1 VHT20	5180 MHz	18.01	18.11	18.27	18.71	24.30	30.00	Complies
	5200 MHz	20.84	20.88	20.87	20.99	26.92	30.00	Complies
	5240 MHz	21.14	20.77	21.11	20.74	26.96	30.00	Complies
802.11ac MCS0/Nss1 VHT40	5190 MHz	15.75	16.02	15.61	16.13	21.90	30.00	Complies
	5230 MHz	19.27	19.02	18.47	19.76	25.18	30.00	Complies
802.11ac MCS0/Nss1 VHT80	5210 MHz	16.44	16.38	16.41	17.31	22.67	30.00	Complies

4.4. Power Spectral Density Measurement

4.4.1. Limit

The following table is power spectral density limits and decrease power density limit rule refer to section 4.3.1.

Frequency Band		Limit
5.15~5.25 GHz		
Operating Mode		
<input type="checkbox"/>	Outdoor access point	17 dBm/MHz
<input checked="" type="checkbox"/>	Indoor access point	17 dBm/MHz
<input type="checkbox"/>	Fixed point-to-point access points	17 dBm/MHz
<input type="checkbox"/>	Mobile and portable client devices	11 dBm/MHz

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RBW	1000 kHz
VBW	3000 kHz
Detector	RMS
Trace	AVERAGE
Sweep Time	Auto
Trace Average	100 times

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected RF switch to the spectrum analyzer.
2. Test was performed in accordance with KDB789033 D02 v01 for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - section (F) Maximum Power Spectral Density (PSD).
3. Multiple antenna systems was performed in accordance KDB662911 D01 v02r01 in-Band Power Spectral Density (PSD) Measurements (a) Measure and sum the spectra across the outputs.
4. When measuring first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3 and so on up to the Nth output to obtain the value for the first frequency bin of the summed spectrum. The summed spectrum value for each of the other frequency bins is computed in the same way.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of Power Spectral Density

Temperature	25°C	Humidity	45%
Test Engineer	Eddie Weng	Test Date	Oct. 30, 2015~Nov. 09, 2015


Mode	Frequency	Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
802.11a	5180 MHz	12.74	13.98	Complies
	5200 MHz	13.83	13.98	Complies
	5240 MHz	13.92	13.98	Complies
802.11ac MCS0/Nss1 VHT20	5180 MHz	11.13	13.98	Complies
	5200 MHz	13.84	13.98	Complies
	5240 MHz	13.74	13.98	Complies
802.11ac MCS0/Nss1 VHT40	5190 MHz	5.73	13.98	Complies
	5230 MHz	8.99	13.98	Complies
802.11ac MCS0/Nss1 VHT80	5210 MHz	3.45	13.98	Complies

Note: $Directional\ Gain = 10 \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 9.02 \text{dBi} > 6 \text{dBi}$, so limit = $17 - (9.02 - 6) = 13.98 \text{dBm/MHz}$.


Note: All the test values were listed in the report.

For plots, only the channel with worse result was shown.


Power Density Plot on Configuration IEEE 802.11a / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5240 MHz




Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5200 MHz



Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5230 MHz



Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5210 MHz



4.5. Radiated Emissions Measurement

4.5.1. Limit

For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

In addition, In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micovolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	40 GHz
RBW / VBW (Emission in restricted band)	1 MHz / 3MHz for Peak, 1 MHz / 1/T for Average
RBW / VBW (Emission in non-restricted band)	1 MHz / 3MHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RBW 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RBW 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 1m & 3m far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 1/T VBW for average reading in spectrum analyzer.
7. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
8. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
9. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout


For Radiated Emissions: 9kHz ~30MHz



For Radiated Emissions: 30MHz~1GHz



For Radiated Emissions: Above 1GHz



4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	24°C	Humidity	51%
Test Engineer	Lucke Hsieh	Configurations	CTX
Test Date	Oct. 30, 2015	Test Mode	Mode 2

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	24°C	Humidity	51%
Test Engineer	Lucke Hsieh	Configurations	CTX
Test Mode	Mode 2		

Horizontal



	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	30.00	27.19	40.00	-12.81	38.85	0.64	20.10	32.40	125	353	Peak	HORIZONTAL
2	217.21	39.42	46.00	-6.58	59.72	1.30	10.72	32.32	125	0	Peak	HORIZONTAL
3	243.40	38.62	46.00	-7.38	57.13	1.37	12.43	32.31	150	329	Peak	HORIZONTAL
4	340.40	30.81	46.00	-15.19	46.46	1.60	15.05	32.30	100	66	Peak	HORIZONTAL
5	657.59	29.87	46.00	-16.13	40.53	2.11	19.61	32.38	100	84	Peak	HORIZONTAL
6	823.46	32.47	46.00	-13.53	41.21	2.33	21.05	32.12	300	337	Peak	HORIZONTAL

Vertical



	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	42.61	36.63	40.00	-3.37	55.74	0.68	12.62	32.41	100	0 Peak	VERTICAL
2	64.92	30.56	40.00	-9.44	55.31	0.80	6.85	32.40	100	141 Peak	VERTICAL
3	243.40	34.80	46.00	-11.20	53.31	1.37	12.43	32.31	200	110 Peak	VERTICAL
4	277.35	32.92	46.00	-13.08	50.24	1.44	13.53	32.29	150	330 Peak	VERTICAL
5	758.47	31.82	46.00	-14.18	41.40	2.24	20.47	32.29	125	33 Peak	VERTICAL
6	852.56	32.45	46.00	-13.55	40.74	2.37	21.32	31.98	150	6 Peak	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~40GHz)

Temperature	24°C	Humidity	51%
Test Engineer	Lucke Hsieh	Configurations	IEEE 802.11a CH 36 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Nov. 03, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	15540.54	58.15	74.00	-15.85	44.33	10.77	38.25	35.20	Peak	168	147	HORIZONTAL
2	15541.00	44.83	54.00	-9.17	31.01	10.77	38.25	35.20	Average	168	147	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	15540.54	57.15	74.00	-16.85	43.33	10.77	38.25	35.20	Peak	168	147	VERTICAL
2	15541.00	43.79	54.00	-10.21	29.97	10.77	38.25	35.20	Average	168	147	VERTICAL

Temperature	24°C	Humidity	51%
Test Engineer	Lucke Hsieh	Configurations	IEEE 802.11a CH 40 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Oct. 28, 2015		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	15599.65	58.85	74.00	-15.15	45.44	9.81	38.29	34.69	213	146	Peak	HORIZONTAL
2	15600.70	46.00	54.00	-8.00	32.59	9.81	38.29	34.69	213	146	Average	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	15599.38	45.83	54.00	-8.17	32.42	9.81	38.29	34.69	175	139	Average	VERTICAL
2	15599.54	58.79	74.00	-15.21	45.38	9.81	38.29	34.69	175	139	Peak	VERTICAL

Temperature	24°C	Humidity	51%
Test Engineer	Lucke Hsieh	Configurations	IEEE 802.11a CH 48 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Oct. 28, 2015		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	deg	cm		
1	15720.78	58.46	74.00	-15.54	44.86	9.88	38.50	217	154	Peak	HORIZONTAL
2	15720.89	45.52	54.00	-8.48	31.92	9.88	38.50	217	154	Average	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	deg	cm		
1	15719.83	45.73	54.00	-8.27	32.13	9.88	38.50	113	149	Average	VERTICAL
2	15720.62	57.77	74.00	-16.23	44.17	9.88	38.50	113	149	Peak	VERTICAL

Temperature	24°C	Humidity	51%
Test Engineer	Lucke Hsieh	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 36 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Oct. 28, 2015		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	15539.12	45.49	54.00	-8.51	32.19	9.76	38.16	34.62	312	119 Average	HORIZONTAL
2	15540.77	58.18	74.00	-15.82	44.88	9.76	38.16	34.62	312	119 Peak	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	15539.97	58.16	74.00	-15.84	44.86	9.76	38.16	34.62	287	136 Peak	VERTICAL
2	15541.00	45.46	54.00	-8.54	32.16	9.76	38.16	34.62	287	136 Average	VERTICAL

Temperature	24°C	Humidity	51%
Test Engineer	Lucke Hsieh	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 40 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Oct. 28, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	15599.04	45.83	54.00	-8.17	32.42	9.81	38.29	34.69	356	147	Average	HORIZONTAL
2	15600.52	58.96	74.00	-15.04	45.55	9.81	38.29	34.69	356	147	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	15600.35	59.56	74.00	-14.44	46.15	9.81	38.29	34.69	318	150	Peak	VERTICAL
2	15600.85	45.78	54.00	-8.22	32.37	9.81	38.29	34.69	318	150	Average	VERTICAL

Temperature	24°C	Humidity	51%
Test Engineer	Lucke Hsieh	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 48 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Oct. 28, 2015		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	15719.66	45.38	54.00	-8.62	31.78	9.88	38.50	34.78	86	149 Average	HORIZONTAL
2	15719.97	58.55	74.00	-15.45	44.95	9.88	38.50	34.78	86	149 Peak	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	15719.40	45.36	54.00	-8.64	31.76	9.88	38.50	34.78	125	166 Average	VERTICAL
2	15720.56	58.25	74.00	-15.75	44.65	9.88	38.50	34.78	125	166 Peak	VERTICAL

Temperature	24°C	Humidity	51%
Test Engineer	Lucke Hsieh	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 38 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Oct. 28, 2015		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	15569.14	58.87	74.00	-15.13	45.51	9.78	38.22	34.64	133	158	Peak	HORIZONTAL
2	15569.36	45.67	54.00	-8.33	32.31	9.78	38.22	34.64	133	158	Average	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	15569.44	45.74	54.00	-8.26	32.38	9.78	38.22	34.64	96	152	Average	VERTICAL
2	15570.14	58.32	74.00	-15.68	44.96	9.78	38.22	34.64	96	152	Peak	VERTICAL

Temperature	24°C	Humidity	51%
Test Engineer	Lucke Hsieh	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 46 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Oct. 28, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	15690.29	58.26	74.00	-15.74	44.71	9.86	38.44	34.75	96	141	Peak	HORIZONTAL
2	15690.75	45.62	54.00	-8.38	32.07	9.86	38.44	34.75	96	141	Average	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	15690.58	45.79	54.00	-8.21	32.24	9.86	38.44	34.75	144	148	Average	VERTICAL
2	15690.74	59.01	74.00	-14.99	45.46	9.86	38.44	34.75	144	148	Peak	VERTICAL



Temperature	24°C	Humidity	51%
Test Engineer	Lucke Hsieh	Configurations	IEEE 802.11ac MCS0/Nss1 VHT80 CH 42 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Oct. 28, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	15629.58	45.92	54.00	-8.08	32.45	9.83	38.35	34.71	197	160	Average	HORIZONTAL
2	15630.70	59.12	74.00	-14.88	45.65	9.83	38.35	34.71	197	160	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	15629.77	45.90	54.00	-8.10	32.43	9.83	38.35	34.71	178	164	Average	VERTICAL
2	15630.01	58.87	74.00	-15.13	45.40	9.83	38.35	34.71	178	164	Peak	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Band Edge Emissions Measurement

4.6.1. Limit

For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

In addition, In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RBW / VBW (Emission in restricted band)	1 MHz / 3MHz for Peak, 1 MHz / 1/T for Average
RBW / VBW (Emission in non-restricted band)	1 MHz / 3MHz for Peak

4.6.3. Test Procedures

The test procedure is the same as section 4.5.3.

4.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.5.4.

4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	24°C	Humidity	51%
Test Engineer	Lucke Hsieh	Configurations	IEEE 802.11a CH 36, 40, 48 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Oct. 28, 2015 / Nov. 03, 2015 / Nov. 05, 2015		

Channel 36

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	5135.13	53.98	54.00	-0.02	48.85	6.12	34.01	35.00 Average	199	20	VERTICAL
2	5141.38	66.90	74.00	-7.10	61.73	6.13	34.04	35.00 Peak	199	20	VERTICAL
3	5174.23	112.92			107.68	6.15	34.09	35.00 Average	199	20	VERTICAL
4	5174.39	121.95			116.71	6.15	34.09	35.00 Peak	199	20	VERTICAL

Item 3, 4 are the fundamental frequency at 5180 MHz.

Channel 40

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	5116.00	53.58	54.00	-0.42	46.80	6.14	33.69	33.05 Average	225	20	VERTICAL
2	5142.40	66.66	74.00	-7.34	59.80	6.17	33.74	33.05 Peak	225	20	VERTICAL
3	5196.80	113.94			106.90	6.27	33.82	33.05 Average	225	20	VERTICAL
4	5196.80	124.39			117.35	6.27	33.82	33.05 Peak	225	20	VERTICAL

Item 3, 4 are the fundamental frequency at 5200 MHz.

Channel 48

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	5132.00	66.45	74.00	-7.55	61.84	5.84	33.24	34.47 Peak	335	229	VERTICAL
2	5150.00	53.98	54.00	-0.02	49.34	5.84	33.27	34.47 Average	335	229	VERTICAL
3	5242.40	127.13			122.37	5.78	33.45	34.47 Peak	335	229	VERTICAL
4	5243.00	117.08			112.32	5.78	33.45	34.47 Average	335	229	VERTICAL
5	5356.40	52.77	54.00	-1.23	47.88	5.73	33.63	34.47 Average	335	229	VERTICAL
6	5370.20	65.13	74.00	-8.87	60.21	5.73	33.66	34.47 Peak	335	229	VERTICAL

Item 3, 4 are the fundamental frequency at 5240 MHz.

Temperature	24°C	Humidity	51%
Test Engineer	Lucke Hsieh	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 36, 40, 48 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Oct. 28, 2015 / Nov. 05, 2015		

Channel 36

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	5147.20	53.54	54.00	-0.46	46.64	6.21	33.74	33.05	200	19	Average	VERTICAL
2	5147.60	68.15	74.00	-5.85	61.25	6.21	33.74	33.05	200	19	Peak	VERTICAL
3	5172.40	107.41			100.45	6.24	33.77	33.05	200	19	Average	VERTICAL
4	5177.60	118.13			111.15	6.24	33.79	33.05	200	19	Peak	VERTICAL

Item 3, 4 are the fundamental frequency at 5180 MHz.

Channel 40

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	5112.40	52.92	54.00	-1.08	46.14	6.14	33.69	33.05	200	334	Average	VERTICAL
2	5122.40	65.85	74.00	-8.15	59.04	6.17	33.69	33.05	200	334	Peak	VERTICAL
3	5202.80	123.06			116.02	6.27	33.82	33.05	200	334	Peak	VERTICAL
4	5208.00	112.97			105.90	6.27	33.85	33.05	200	334	Average	VERTICAL

Item 3, 4 are the fundamental frequency at 5200 MHz.

Channel 48

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	5144.60	66.53	74.00	-7.47	61.89	5.84	33.27	34.47	337	228	Peak	VERTICAL
2	5150.00	53.81	54.00	-0.19	49.17	5.84	33.27	34.47	337	228	Average	VERTICAL
3	5242.40	127.16			122.40	5.78	33.45	34.47	337	228	Peak	VERTICAL
4	5242.40	117.00			112.24	5.78	33.45	34.47	337	228	Average	VERTICAL
5	5350.00	52.48	54.00	-1.52	47.59	5.73	33.63	34.47	337	228	Average	VERTICAL
6	5353.00	64.68	74.00	-9.32	59.79	5.73	33.63	34.47	337	228	Peak	VERTICAL

Item 3, 4 are the fundamental frequency at 5240 MHz.

Temperature	24°C	Humidity	51%
Test Engineer	Lucke Hsieh	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 38, 46 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Oct. 28, 2015 / Nov. 05, 2015		

Channel 38

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	5147.20	53.83	54.00	-0.17	46.93	6.21	33.74	33.05	200	19 Average	VERTICAL
2	5147.60	68.45	74.00	-5.55	61.55	6.21	33.74	33.05	200	19 Peak	VERTICAL
3	5197.60	113.07			106.03	6.27	33.82	33.05	200	19 Peak	VERTICAL
4	5207.60	101.53			94.46	6.27	33.85	33.05	200	19 Average	VERTICAL

Item 3, 4 are the fundamental frequency at 5190 MHz.

Channel 46

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	deg	cm		
1	5138.00	64.73	74.00	-9.27	60.12	5.84	33.24	34.47	25	211 Peak	VERTICAL
2	5147.20	53.83	54.00	-0.17	49.19	5.84	33.27	34.47	25	211 Average	VERTICAL
3	5242.80	111.34			106.58	5.78	33.45	34.47	25	211 Average	VERTICAL
4	5247.60	120.69			115.93	5.78	33.45	34.47	25	211 Peak	VERTICAL

Item 3, 4 are the fundamental frequency at 5230 MHz.

Temperature	24°C	Humidity	51%
Test Engineer	Lucke Hsieh	Configurations	IEEE 802.11ac MCS0/Nss1 VHT80 CH 42 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Oct. 28, 2015		

Channel 42

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	deg	cm		
1	5142.00	53.91	54.00	-0.09	49.27	5.84	33.27	34.47	23	225 Average	VERTICAL
2	5147.00	65.41	74.00	-8.59	60.77	5.84	33.27	34.47	23	225 Peak	VERTICAL
3	5208.00	102.98			98.26	5.80	33.39	34.47	23	225 Average	VERTICAL
4	5223.00	111.67			106.95	5.80	33.39	34.47	23	225 Peak	VERTICAL
5	5363.00	48.91	54.00	-5.09	43.99	5.73	33.66	34.47	23	225 Average	VERTICAL
6	5380.00	60.18	74.00	-13.82	55.24	5.72	33.69	34.47	23	225 Peak	VERTICAL

Item 3, 4 are the fundamental frequency at 5210 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

4.7. Frequency Stability Measurement

4.7.1. Limit

In-band emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

The transmitter center frequency tolerance shall be ± 20 ppm maximum for the 5 GHz band (IEEE 802.11n specification).

4.7.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Entire absence of modulation emissions bandwidth
RBW	10 kHz
VBW	10 kHz
Sweep Time	Auto

4.7.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings.
5. f_c is declaring of channel frequency. Then the frequency error formula is $(f_c - f) / f_c \times 10^6$ ppm and the limit is less than ± 20 ppm (IEEE 802.11n specification).
6. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 minutes.
7. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
8. Extreme temperature is $0^\circ\text{C} \sim 40^\circ\text{C}$.

4.7.4. Test Setup Layout



4.7.5. Test Deviation

There is no deviation with the original standard.

4.7.6. EUT Operation during Test

The EUT was programmed to be in continuously un-modulation transmitting mode.

4.7.7. Test Result of Frequency Stability

Temperature	25°C	Humidity	45%
Test Engineer	Eddie Weng	Test Date	Oct. 30, 2015~Nov. 09, 2015

Mode: 20 MHz / Chain 1

Voltage vs. Frequency Stability

Voltage (V)	Measurement Frequency (MHz)			
	5200 MHz			
	0 Minute	2 Minute	5 Minute	10 Minute
126.50	5199.9903	5199.9889	5199.9871	5199.9850
110.00	5199.9891	5199.9878	5199.9862	5199.9843
93.50	5199.9877	5199.9866	5199.9854	5199.9832
Max. Deviation (MHz)	0.0123	0.0134	0.0146	0.0168
Max. Deviation (ppm)	2.37	2.58	2.81	3.23
Result	Complies			

Temperature vs. Frequency Stability

Temperature (°C)	Measurement Frequency (MHz)			
	5200 MHz			
	0 Minute	2 Minute	5 Minute	10 Minute
0	5199.9916	5199.9904	5199.9885	5199.9863
10	5199.9903	5199.9890	5199.9875	5199.9857
20	5199.9891	5199.9878	5199.9862	5199.9843
30	5199.9877	5199.9866	5199.9852	5199.9836
40	5199.9861	5199.9846	5199.9830	5199.9810
Max. Deviation (MHz)	0.0139	0.0154	0.0170	0.0190
Max. Deviation (ppm)	2.67	2.96	3.27	3.65
Result	Complies			

Mode: 40 MHz / Chain 1

Voltage vs. Frequency Stability

Voltage	Measurement Frequency (MHz)			
(V)	5190 MHz			
	0 Minute	2 Minute	5 Minute	10 Minute
126.50	5189.9920	5189.9906	5189.9888	5189.9867
110.00	5189.9908	5189.9895	5189.9879	5189.9860
93.50	5189.9894	5189.9883	5189.9871	5189.9849
Max. Deviation (MHz)	0.0106	0.0117	0.0129	0.0151
Max. Deviation (ppm)	2.04	2.25	2.49	2.91
Result	Complies			

Temperature vs. Frequency Stability

Temperature	Measurement Frequency (MHz)			
(°C)	5190 MHz			
	0 Minute	2 Minute	5 Minute	10 Minute
0	5189.9933	5189.9921	5189.9902	5189.9880
10	5189.9920	5189.9907	5189.9892	5189.9874
20	5189.9908	5189.9895	5189.9879	5189.9860
30	5189.9894	5189.9883	5189.9869	5189.9853
40	5189.9878	5189.9863	5189.9847	5189.9827
Max. Deviation (MHz)	0.0122	0.0137	0.0153	0.0173
Max. Deviation (ppm)	2.35	2.64	2.95	3.33
Result	Complies			

Mode: 80 MHz / Chain 1

Voltage vs. Frequency Stability

Voltage	Measurement Frequency (MHz)			
(V)	5210 MHz			
	0 Minute	2 Minute	5 Minute	10 Minute
126.50	5209.9920	5209.9906	5209.9888	5209.9867
110.00	5209.9908	5209.9895	5209.9879	5209.9860
93.50	5209.9894	5209.9883	5209.9871	5209.9849
Max. Deviation (MHz)	0.0106	0.0117	0.0129	0.0151
Max. Deviation (ppm)	2.03	2.25	2.48	2.90
Result	Complies			

Temperature vs. Frequency Stability

Temperature	Measurement Frequency (MHz)			
(°C)	5210 MHz			
	0 Minute	2 Minute	5 Minute	10 Minute
0	5209.9933	5209.9921	5209.9902	5209.9880
10	5209.9920	5209.9907	5209.9892	5209.9874
20	5209.9908	5209.9895	5209.9879	5209.9860
30	5209.9894	5209.9883	5209.9869	5209.9853
40	5209.9878	5209.9863	5209.9847	5209.9827
Max. Deviation (MHz)	0.0122	0.0137	0.0153	0.0173
Max. Deviation (ppm)	2.34	2.63	2.94	3.32
Result	Complies			

4.8. Antenna Requirements

4.8.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.8.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100355	9kHz ~ 2.75GHz	Apr. 22, 2015	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Dec. 02, 2014	Conduction (CO01-CB)
LISN	Schwarzbeck	NSLK 8127	8127647	9kHz ~ 30MHz	Dec. 02, 2014	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	150kHz ~ 30MHz	Dec. 03, 2014	Conduction (CO01-CB)
Software	Audix	E3	6.120210n	-	N.C.R.	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	May 06, 2015	Radiation (O3CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz ~ 18GHz	Oct. 22, 2015	Radiation (O3CH01-CB)
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Jul. 21, 2015	Radiation (O3CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Feb. 24, 2015	Radiation (O3CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Jan. 12, 2015	Radiation (O3CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26GHz ~ 40GHz	Nov. 25, 2014	Radiation (O3CH01-CB)
Spectrum Analyzer	R&S	FSP40	100056	9kHz ~ 40GHz	Oct. 27, 2015	Radiation (O3CH01-CB)
EMI Receiver	Agilent	N9038A	MY52260123	9kHz ~ 8.4GHz	Jan. 21, 2015	Radiation (O3CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz ~ 1 GHz	Nov. 15, 2014	Radiation (O3CH01-CB)
RF Cable-high	Woken	High Cable-40G-1	N/A	1 GHz ~ 40 GHz	Nov. 15, 2014	Radiation (O3CH01-CB)
RF Cable-high	Woken	High Cable-40G-2	N/A	1 GHz ~ 40 GHz	Nov. 15, 2014	Radiation (O3CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9kHz - 30 MHz	Mar. 12, 2015*	Radiation (O3CH01-CB)
Spectrum analyzer	R&S	FSV40	100979	9kHz~40GHz	Dec. 12, 2014	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	Jun. 02, 2015	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-7	1 GHz – 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-8	1 GHz – 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-9	1 GHz – 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-10	1 GHz – 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-6	1 GHz – 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
Power Sensor	Agilent	U2021XA	MY53410001	50MHz~18GHz	Nov. 03, 2014	Conducted (TH01-CB)
Power Sensor	Agilent	U2021XA	MY53410002	50MHz~18GHz	Nov. 02, 2015	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

“*” Calibration Interval of instruments listed above is two years.

N.C.R. means Non-Calibration required.

6. MEASUREMENT UNCERTAINTY

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	3.2 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	3.6 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	3.7 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	3.5 dB	Confidence levels of 95%
Conducted Emission	1.7 dB	Confidence levels of 95%