




RF TEST REPORT



Report No.: Q181023S005-FCC-R2

Supersede Report No.: N/A

Applicant	TP-LINK Technologies Co., Ltd.	
Product Name	C5 Plus smartphone	
Model No.	TP7031C	
Serial No.	TP7031CXYZZ	
Test Standard	FCC Part 15.247, ANSI C63.10: 2013	
Test Date	Nov. 06 to Nov. 20, 2018	
Issue Date	Nov. 22, 2018	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification <input checked="" type="checkbox"/>		
Equipment did not comply with the specification <input type="checkbox"/>		
		
Aaron Liang Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report No.	Q181023S005-FCC-R2
Page	3 of 51

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY.....	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION	6
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	7
5. TEST SUMMARY	9
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	10
6.1 ANTENNA REQUIREMENT.....	10
6.2 DTS (6 DB&20 DB) CHANNEL BANDWIDTH.....	11
6.3 MAXIMUM OUTPUT POWER	18
6.4 POWER SPECTRAL DENSITY.....	22
6.5 BAND-EDGE & UNWANTED EMISSIONS INTO RESTRICTED FREQUENCY BANDS	26
6.6 AC POWER LINE CONDUCTED EMISSIONS.....	32
6.7 RADIATED SPURIOUS EMISSIONS & RESTRICTED BAND	38
ANNEX A. TEST INSTRUMENT	46
ANNEX B. TEST SETUP AND SUPPORTING EQUIPMENT	47
ANNEX C. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST/ DECLARATION OF SIMILARITY.....	51

1. Report Revision History

Report No.	Report Version	Description	Issue Date
Q181023S005-FCC-R2	NONE	Original	Nov. 22, 2018

2. Customer information

Applicant Name	TP-LINK Technologies Co., Ltd.
Applicant Add	Building 24-1F/3F/4F/5F, 28-1F/2F/3F/4F Science and Technology Park, Shennan Road, Nanshan District, Shenzhen City, Guangdong Province, P.R. China
Manufacturer	TP-LINK Technologies Co.,Ltd
Manufacturer Add	Building 24-1F/3F/4F/5F, 28-1F/2F/3F/4F Science and Technology Park, Shennan Road, Nanshan District, Shenzhen City, Guangdong Province, P.R. China

3. Test site information

Test Lab A:

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	535293
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

Test Lab B:

Lab performing tests	SIEMIC (Nanjing-China) Laboratories
Lab Address	2-1 Longcang Avenue Yuhua Economic and Technology Development Park, Nanjing, China
FCC Test Site No.	694825
IC Test Site No.	4842B-1
Test Software	EZ_EMG(ver.lcp-03A1)

Note: We just perform Radiated Spurious Emission above 18GHz in the test Lab. B.

4. Equipment under Test (EUT) Information

Description of EUT:	C5 Plus smartphone
Main Model:	TP7031C
	TP7031CXYZZ
	(Model Difference
	Description of Model Name Differentiation:
	X=2 , indicates Grey ; X=4 , indicates Gold ; X=7 , indicates Blue ;
Serial Model:	X=8 , indicates Red ;
	Y=0 , indicates the memory is 512MB RAM + 8GB Flash; Y=1 , indicates the memory is 1GB RAM + 8GB Flash; Y=2 , indicates the memory is 1GB RAM + 16GB Flash;
	Z=' A' to ' Z' , ZZ indicates different regions or customers.
	All models are same with electrical parameters and internal circuit structure.)
Date EUT received:	Nov. 05, 2018
Test Date(s):	Nov. 06 to Nov. 20, 2018
Equipment Category :	DTS
Antenna Gain:	WIFI: -0.5dBi
Antenna Type:	PIFA Antenna
Type of Modulation:	802.11b/g/n: DSSS, OFDM
RF Operating Frequency (ies):	WIFI: 802.11b/g/n(20M): 2412-2462 MHz
	WIFI: 802.11n(40M): 2422-2452 MHz

Max. Output Power:	802.11b: 17.25 dBm
	802.11g: 14.41 dBm
	802.11n(20M): 14.47 dBm
	802.11n(40M): 13.43 dBm
Number of Channels:	WIFI :802.11b/g/n(20M): 11CH
	WIFI :802.11n(40M): 7CH
Port:	Please refer to the user' s manual
Input Power:	Adapter :
	Model: A8-501000
	Input: AC100-240V~50/60Hz,0.2A Max
	Output: DC 5.0V, 1.0A
	Battery :
	Model: NBL-40A2150
	Spec: 3.8V, 2150mAh from Li-ion
	Limited charge voltage: 4.35V
	Rating:3.8V/2150mAh/8.17Wh
Trade Name :	Typical3.8V/2200mAh/8.36Wh
	neffos
FCC ID:	TE7C5PLUSV1

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247 (a)(2)	DTS (6 dB&20 dB) CHANNEL BANDWIDTH	Compliance
§15.247(b)(3)	Conducted Maximum Output Power	Compliance
§15.247(e)	Power Spectral Density	Compliance
§15.247(d)	Band-Edge & Unwanted Emissions into Restricted Frequency Bands	Compliance
§15.207 (a),	AC Power Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions & Unwanted Emissions into Restricted Frequency Bands	Compliance

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band-Edge & Unwanted Emissions into Restricted Frequency Bands and Radiated Emissions & Unwanted Emissions into Restricted Frequency Bands	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. Measurements, Examination And Derived Results

6.1 Antenna Requirement

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has 2 antennas:

A permanently attached PIFA antenna for Bluetooth/BLE/WIFI/GPS, the gain is -0.5dBi for Bluetooth/BLE, the gain is -0.5dBi for WIFI, the gain is -0.5dBi for GPS.


A permanently attached PIFA antenna for GSM/PCS/UMTS, the gain is 0dBi for GSM850, 0dBi for PCS1900, 0dBi for UMTS-FDD Band V, -0.5dBi for UMTS-FDD Band II.

The antenna meets up with the ANTENNA REQUIREMENT.

Result: Compliance.

6.2 DTS (6 dB&20 dB) Channel Bandwidth

Temperature	22 °C
Relative Humidity	54%
Atmospheric Pressure	1021mbar
Test date :	Nov. 21, 2018
Tested By :	Aaron Liang

Spec	Item	Requirement	Applicable
§ 15.247(a)(2) RSS Gen(4.6.1)	a)	6dB BW ≥ 500kHz;	<input checked="" type="checkbox"/>
	b)	99% BW: For FCC reference only; required by IC.	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Spectrum Analyzer EUT</p>		
Test Procedure	<p>558074 D01 DTS MEAS Guidance v03r03, 8.1 DTS bandwidth</p> <p><u>6dB bandwidth</u></p> <ol style="list-style-type: none"> Set RBW = 100 kHz. Set the video bandwidth (VBW) ≥ 3 × RBW. Detector = Peak. Trace mode = max hold. Sweep = auto couple. Allow the trace to stabilize. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission. <p><u>20dB bandwidth</u></p> <p>C63.10 Occupied Bandwidth (OBW=20dB bandwidth)</p> <ol style="list-style-type: none"> Set RBW = 1%-5% OBW. Set the video bandwidth (VBW) ≥ 3 x RBW. Set the span range between 2 times and 5 times of the OBW. Sweep time=Auto, Detector=PK, Trace=Max hold. Once the reference level is established, the equipment is conditioned with typical modulating signals to produce the worst- 		

	case (i.e., the widest) bandwidth. Unless otherwise specified for an unlicensed wireless device, measure the bandwidth at the 20 dB levels with respect to the reference level.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A


Measurement result


Test mode	CH	Freq (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	10.032	≥ 0.5
	Mid	2437	10.022	≥ 0.5
	High	2462	9.619	≥ 0.5
802.11g	Low	2412	15.437	≥ 0.5
	Mid	2437	15.261	≥ 0.5
	High	2462	14.612	≥ 0.5
802.11n (20M)	Low	2412	16.886	≥ 0.5
	Mid	2437	15.149	≥ 0.5
	High	2462	15.253	≥ 0.5
802.11n (40M)	Low	2422	35.353	≥ 0.5
	Mid	2437	34.127	≥ 0.5
	High	2452	35.227	≥ 0.5

Test mode	CH	Freq (MHz)	20dB Bandwidth (MHz)
802.11b	Low	2412	15.141
	Mid	2437	15.195
	High	2462	13.214
802.11g	Low	2412	18.730
	Mid	2437	19.045
	High	2462	18.944
802.11n (20M)	Low	2412	19.285
	Mid	2437	19.333
	High	2462	19.204
802.11n (40M)	Low	2422	39.514
	Mid	2437	39.715
	High	2452	39.638


Test Plots

6dB Bandwidth measurement result







802.11n20 6dB Bandwidth - Low CH 2412




802.11n20 6dB Bandwidth - Mid CH 2437




802.11n20 6dB Bandwidth - High CH 2462



802.11n40 6dB Bandwidth - Low CH 2422





802.11n40 6dB Bandwidth - Mid CH 2437




802.11n40 6dB Bandwidth - High CH 2452


20 dB Bandwidth measurement result




802.11b 20dB Bandwidth - Low CH 2412




802.11b 20dB Bandwidth - Mid CH 2437



802.11b 20dB Bandwidth - High CH 2462




802.11g 20dB Bandwidth - Low CH 2412




802.11g 20dB Bandwidth - Mid CH 2437


802.11g 20dB Bandwidth - High CH 2462




802.11n20 20dB Bandwidth - Low CH 2412




802.11n20 20dB Bandwidth - Mid CH 2437




802.11n20 20dB Bandwidth - High CH 2462



802.11n40 20dB Bandwidth - Low CH 2422



802.11n40 20dB Bandwidth - Mid CH 2437




802.11n40 20dB Bandwidth - High CH 2452

6.3 Maximum Output Power

Temperature	22 °C
Relative Humidity	54%
Atmospheric Pressure	1021mbar
Test date :	Nov. 21, 2018
Tested By :	Aaron Liang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b) (3),RSS210 (A8.4)	a)	FHSS in 2400-2483.5MHz with ≥ 75 channels: ≤ 1 Watt	<input type="checkbox"/>
	b)	FHSS in 5725-5850MHz: ≤ 1 Watt	<input type="checkbox"/>
	c)	For all other FHSS in the 2400-2483.5MHz band: ≤ 0.125 Watt.	<input type="checkbox"/>
	d)	FHSS in 902-928MHz with ≥ 50 channels: ≤ 1 Watt	<input type="checkbox"/>
	e)	FHSS in 902-928MHz with ≥ 25 & <50 channels: ≤ 0.25 Watt	<input type="checkbox"/>
	f)	DTS in 902-928MHz, 2400-2483.5MHz: ≤ 1 Watt	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Spectrum Analyzer EUT</p>		
Test Procedure	<p>558074 D01 DTS MEAS Guidance v03r03, 9.1.2 Integrated band power method Maximum output power measurement procedure</p> <ul style="list-style-type: none"> - a) Set span to at least 1.5 times the OBW. - b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz. - c) Set VBW $\geq 3 \times$ RBW. - d) Number of points in sweep $\geq 2 \times$ span / RBW. (This gives bin-to-bin spacing \leq RBW/2, so that narrowband signals are not lost between frequency bins.) - e) Sweep time = auto. - f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode. - g) If transmit duty cycle $< 98\%$, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum 		

	<p>power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle $\geq 98\%$, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run".</p> <ul style="list-style-type: none"> - h) Trace average at least 100 traces in power averaging (i.e., RMS) mode. - i) Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A


Output Power measurement result

Type	Test mode	CH	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Result
Output power	802.11b	Low	2412	17.01	30	Pass
		Mid	2437	16.86	30	Pass
		High	2462	17.25	30	Pass
	802.11g	Low	2412	12.86	30	Pass
		Mid	2437	14.41	30	Pass
		High	2462	13.43	30	Pass
	802.11n (20M)	Low	2412	12.77	30	Pass
		Mid	2437	14.47	30	Pass
		High	2462	13.40	30	Pass
	802.11n (40M)	Low	2422	10.02	30	Pass
		Mid	2437	13.43	30	Pass
		High	2452	10.72	30	Pass


Test Plots

The Average Power







802.11n20 - AV Output power - Low CH 2412




802.11n20 - AV Output power - Mid CH 2437




802.11n20 - AV Output power - High CH 2462



802.11n40 - AV Output power - Low CH 2422




802.11n40 - AV Output power - Mid CH 2437



802.11n40 - AV Output power - High CH 2452

6.4 Power Spectral Density

Temperature	22°C
Relative Humidity	51%
Atmospheric Pressure	1009mbar
Test date :	Nov. 09, 2018
Tested By :	Aaron Liang

Spec	Item	Requirement	Applicable
§15.247(e)	a)	The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Spectrum Analyzer EUT</p>		
Test Procedure	<p>558074 D01 DTS MEAS Guidance v03r03, 10.2 power spectral density method power spectral density measurement procedure</p> <ul style="list-style-type: none"> - a) Set analyzer center frequency to DTS channel center frequency. - b) Set the span to 1.5 times the DTS bandwidth. - c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$. - d) Set the VBW $\geq 3 \times \text{RBW}$. - e) Detector = peak. - f) Sweep time = auto couple. - g) Trace mode = max hold. - h) Allow trace to fully stabilize. - i) Use the peak marker function to determine the maximum amplitude level within the RBW. - j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat. 		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		


Test Data ☒ Yes ☐ N/A
 Test Plot ☒ Yes (See below) ☐ N/A


Power Spectral Density measurement result

Type	Test mode	CH	Freq (MHz)	PSD	Limit (dBm)	Result
				(dBm)		
PSD	802.11b	Low	2412	-4.06	8	Pass
		Mid	2437	-2.62	8	Pass
		High	2462	-5.63	8	Pass
	802.11g	Low	2412	-10.36	8	Pass
		Mid	2437	-9.78	8	Pass
		High	2462	-11.84	8	Pass
	802.11n (20M)	Low	2412	-10.19	8	Pass
		Mid	2437	-8.64	8	Pass
		High	2462	-8.50	8	Pass
	802.11n (40M)	Low	2422	-16.32	8	Pass
		Mid	2437	-13.90	8	Pass
		High	2452	-16.95	8	Pass


Test Plots

Power Spectral Density measurement result







PSD - Low CH 2412 - 802.11n20




PSD - Mid CH 2437 - 802.11n20




PSD - High CH 2472 - 802.11n20



PSD - Low CH 2422 - 802.11n40



PSD - Mid CH 2437 - 802.11n40



PSD - High CH 2452 - 802.11n40

6.5 Band-Edge & Unwanted Emissions into Restricted Frequency Bands

Temperature	23°C
Relative Humidity	52%
Atmospheric Pressure	1010mbar
Test date :	Nov. 10&15&16, 2018
Tested By :	Aaron Liang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(d)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	<input checked="" type="checkbox"/>

Test Setup	
------------	--


Test Procedure	<p>Radiated Method Only</p> <ul style="list-style-type: none"> 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator. 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
----------------	---

	<ul style="list-style-type: none"> - 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below: <ul style="list-style-type: none"> a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency. - 5. Repeat above procedures until all measured frequencies were complete.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail


Test Data ☒ Yes ☐ N/A
 Test Plot ☒ Yes (See below) ☐ N/A

Test Plots


Band Edge measurement result



Note: Both Horizontal and vertical polarities were investigated



Date: 10.NOV.2018 08:24:07




Date: 15.NOV.2018 04:22:56

Band Edge, Left Side (Peak) - 802.11g


Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz

Band Edge, Right Side (Peak) - 802.11g

Note: F1 is frequency 2483.5MHz



Date: 10.NOV.2018 08:24:33



Date: 15.NOV.2018 04:23:37


Band Edge, Left Side (Average) - 802.11g

Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz


Band Edge, Right Side (Average) - 802.11g

Note: F1 is frequency 2483.5MHz


Note: Both Horizontal and vertical polarities were investigated




Band Edge, Left Side (Peak) - 802.11n20
Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz



Band Edge, Right Side (Peak) - 802.11n20
Note: F1 is frequency 2483.5MHz




Band Edge, Left Side (Average) - 802.11n20
Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz




Band Edge, Right Side (Average) - 802.11n20
Note: F1 is frequency 2483.5MHz


Note: Both Horizontal and vertical polarities were investigated




Band Edge, Left Side (Peak) - 802.11n40
Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz



Band Edge, Right Side (Peak) - 802.11n40
Note: F1 is frequency 2483.5MHz



Band Edge, Left Side (Average) - 802.11n40
Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz



Band Edge, Right Side (Average) - 802.11n40
Note: F1 is frequency 2483.5MHz


Note: Both Horizontal and vertical polarities were investigated

6.6 AC Power Line Conducted Emissions

Temperature	25°C
Relative Humidity	50%
Atmospheric Pressure	1008mbar
Test date :	Nov. 08, 2018
Tested By :	Aaron Liang

Requirement(s):

Spec	Item	Requirement	Applicable		
47CFR§15.207, RSS210 (A8.1)	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu] H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.	<div><input checked="" type="checkbox"/></div>		
		Frequency ranges (MHz)		Limit (dBµV)	
				QP	Average
		0.15 ~ 0.5		66 – 56	56 – 46
		0.5 ~ 5		56	46
5 ~ 30	60	50			

Test Setup	 <p>Note: 1. Support units were connected to second LISN. 2. Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.</p>
------------	---


Procedure	<ol style="list-style-type: none"> The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table. The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss
-----------	---

	<p>coaxial cable.</p> <ol style="list-style-type: none"> 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Mode: Transmitting Mode




Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)
1	L1	0.1812	37.26	QP	10.03	47.29	64.43	-17.14
2	L1	0.1812	17.47	AVG	10.03	27.50	54.43	-26.93
3	L1	0.2436	33.76	QP	10.03	43.79	61.97	-18.18
4	L1	0.2436	15.10	AVG	10.03	25.13	51.97	-26.84
5	L1	0.5205	29.00	QP	10.03	39.03	56.00	-16.97
6	L1	0.5205	20.79	AVG	10.03	30.82	46.00	-15.18
7	L1	1.6710	25.03	QP	10.04	35.07	56.00	-20.93
8	L1	1.6710	11.56	AVG	10.04	21.60	46.00	-24.40
9	L1	2.8566	27.42	QP	10.05	37.47	56.00	-18.53
10	L1	2.8566	13.94	AVG	10.05	23.99	46.00	-22.01
11	L1	23.6427	14.37	QP	10.37	24.74	60.00	-35.26
12	L1	23.6427	0.52	AVG	10.37	10.89	50.00	-39.11

Test Mode: Transmitting Mode




Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)
1	N	0.1851	34.08	QP	10.02	44.10	64.25	-20.15
2	N	0.1851	15.92	AVG	10.02	25.94	54.25	-28.31
3	N	0.4620	29.37	QP	10.02	39.39	56.66	-17.27
4	N	0.4620	21.47	AVG	10.02	31.49	46.66	-15.17
5	N	1.0041	22.02	QP	10.03	32.05	56.00	-23.95
6	N	1.0041	6.01	AVG	10.03	16.04	46.00	-29.96
7	N	2.4003	23.81	QP	10.04	33.85	56.00	-22.15
8	N	2.4003	12.46	AVG	10.04	22.50	46.00	-23.50
9	N	4.7628	21.58	QP	10.07	31.65	56.00	-24.35
10	N	4.7628	9.66	AVG	10.07	19.73	46.00	-26.27
11	N	23.2527	22.39	QP	10.31	32.70	60.00	-27.30
12	N	23.2527	4.41	AVG	10.31	14.72	50.00	-35.28

Test Mode: Transmitting Mode




Test Data

Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)
1	L1	0.1734	39.74	QP	10.03	49.77	64.80	-15.03
2	L1	0.1734	17.80	AVG	10.03	27.83	54.80	-26.97
3	L1	0.2553	31.32	QP	10.03	41.35	61.58	-20.23
4	L1	0.2553	15.16	AVG	10.03	25.19	51.58	-26.39
5	L1	0.4698	34.26	QP	10.03	44.29	56.52	-12.23
6	L1	0.4698	20.02	AVG	10.03	30.05	46.52	-16.47
7	L1	1.0938	29.32	QP	10.03	39.35	56.00	-16.65
8	L1	1.0938	19.23	AVG	10.03	29.26	46.00	-16.74
9	L1	1.4370	25.50	QP	10.04	35.54	56.00	-20.46
10	L1	1.4370	17.12	AVG	10.04	27.16	46.00	-18.84
11	L1	2.6082	30.03	QP	10.05	40.08	56.00	-15.92
12	L1	2.6082	14.54	AVG	10.05	24.59	46.00	-21.41

Test Mode: Transmitting Mode



Test Data

Phase Neutral Plot at 240Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)
1	N	0.3840	37.60	QP	10.02	47.62	58.19	-10.57
2	N	0.3840	27.57	AVG	10.02	37.59	48.19	-10.60
3	N	0.4971	39.39	QP	10.02	49.41	56.05	-6.64
4	N	0.4971	31.63	AVG	10.02	41.65	46.05	-4.40
5	N	0.5595	32.08	QP	10.02	42.10	56.00	-13.90
6	N	0.5595	15.69	AVG	10.02	25.71	46.00	-20.29
7	N	0.9807	34.28	QP	10.03	44.31	56.00	-11.69
8	N	0.9807	22.09	AVG	10.03	32.12	46.00	-13.88
9	N	2.6343	35.71	QP	10.05	45.76	56.00	-10.24
10	N	2.6343	24.56	AVG	10.05	34.61	46.00	-11.39
11	N	4.0140	34.84	QP	10.06	44.90	56.00	-11.10
12	N	4.0140	21.28	AVG	10.06	31.34	46.00	-14.66



6.7 Radiated Spurious Emissions & Restricted Band

Temperature	22 °C
Relative Humidity	54%
Atmospheric Pressure	1021mbar
Test date :	Nov. 21, 2018
Tested By :	Aaron Liang

Requirement(s):

Spec	Item	Requirement	Applicable																
47CFR§15.247(d), RSS210 (A8.5)	a)	Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges	<input checked="" type="checkbox"/>																
		<table><tr><th>Frequency range (MHz)</th><th>Field Strength (μV/m)</th></tr><tr><td>0.009~0.490</td><td>2400/F(KHz)</td></tr><tr><td>0.490~1.705</td><td>24000/F(KHz)</td></tr><tr><td>1.705~30.0</td><td>30</td></tr><tr><td>30 – 88</td><td>100</td></tr><tr><td>88 – 216</td><td>150</td></tr><tr><td>216 960</td><td>200</td></tr><tr><td>Above 960</td><td>500</td></tr></table>		Frequency range (MHz)	Field Strength (μV/m)	0.009~0.490	2400/F(KHz)	0.490~1.705	24000/F(KHz)	1.705~30.0	30	30 – 88	100	88 – 216	150	216 960	200	Above 960	500
		Frequency range (MHz)		Field Strength (μV/m)															
		0.009~0.490		2400/F(KHz)															
		0.490~1.705		24000/F(KHz)															
		1.705~30.0		30															
		30 – 88		100															
		88 – 216		150															
		216 960		200															
	Above 960	500																	
b)	For non-restricted band, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB or 30dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, determined by the measurement method on output power to be used. Attenuation below the general limits specified in § 15.209(a) is not required <input checked="" type="checkbox"/> 20 dB down <input type="checkbox"/> 30 dB down	<input checked="" type="checkbox"/>																	
	c)		or restricted band, emission must also comply with the radiated emission limits specified in 15.209	<input checked="" type="checkbox"/>															

Test Setup



Procedure

1. The EUT was switched on and allowed to warm up to its normal operating condition.
2. The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner:
 - a. Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen.
 - b. The EUT was then rotated to the direction that gave the maximum emission.
 - c. Finally, the antenna height was adjusted to the height that gave the maximum emission.
3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi Peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz.

Test Report No.	Q181023S005-FCC-R2
Page	40 of 51

	<p>The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz.</p> <p>5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.</p>
Remark	Different RF configuration has been evaluated but not much difference was found. The data presented here is the worst case data with EUT under 802.11n – HT20-2437MHz mode.
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Result:

Test Mode:	Transmitting Mode
------------	-------------------

Frequency range: 9KHz - 30MHz

Freq.	Detection	Factor	Reading	Result	Limit@3m	Margin
(MHz)	value	(dB/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dB)
--	--	--	--	--	--	>20
--	--	--	--	--	--	>20

Note:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.

Test Mode: Transmitting Mode

30MHz -1GHz




Test Data

Horizontal Polarity Plot @3m

No.	P/L	Frequency	Reading	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)	(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	H	790.6188	29.89	21.29	21.17	2.94	32.95	46.00	-13.05	100	322
2	H	399.0302	26.80	15.68	22.01	2.01	22.48	46.00	-23.52	100	141
3	H	207.8501	27.57	11.99	22.37	1.57	18.76	43.50	-24.74	100	102
4	H	121.5486	27.83	13.80	22.36	1.17	20.44	43.50	-23.06	100	210
5	H	85.5977	31.17	7.82	22.36	1.06	17.69	40.00	-22.31	100	304
6	H	69.6005	28.95	7.78	22.38	0.97	15.32	40.00	-24.68	100	4

30MHz -1GHz



Test Data

Vertical Polarity Plot @3m

N o.	P/ L	Frequency (MHz)	Reading (dBuV/m)	Ant_F (dB/m)	PA_G (dB)	Cab_L (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degr ee ()
1	V	207.8501	27.99	11.99	22.37	1.57	19.18	43.50	-24.32	100	50
2	V	166.6514	26.74	12.07	22.26	1.37	17.92	43.50	-25.58	200	350
3	V	125.0066	27.17	13.57	22.37	1.18	19.55	43.50	-23.95	100	140
4	V	87.7248	34.03	7.91	22.34	1.00	20.60	40.00	-19.40	100	316
5	V	54.6429	38.20	7.89	22.39	0.78	24.48	40.00	-15.52	100	36
6	V	39.4372	31.40	14.31	22.28	0.79	24.22	40.00	-15.78	100	337

Above 1GHz

Test Mode:	Transmitting Mode
------------	-------------------

Low Channel (2412 MHz) (b mode worst case)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4824	45.57	AV	V	33.39	7.22	48.46	37.72	54	-16.28
4824	43.02	AV	H	33.39	7.22	48.46	35.17	54	-18.83
4824	65.62	PK	V	33.39	7.22	48.46	57.77	74	-16.23
4824	63.41	PK	H	33.39	7.22	48.46	55.56	74	-18.44
10331	26.66	AV	V	38.78	10.13	47.5	28.07	54	-25.93
10331	20.59	AV	H	38.78	10.13	47.5	22	54	-32
10331	45.86	PK	V	38.78	10.13	47.5	47.27	74	-26.73
10331	48.28	PK	H	38.78	10.13	47.5	49.69	74	-24.31

Middle Channel (2437 MHz) (b mode worst case)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4874	44.15	AV	V	33.62	7.53	48.36	36.94	54	-17.06
4874	42.18	AV	H	33.62	7.53	48.36	34.97	54	-19.03
4874	69	PK	V	33.62	7.53	48.36	61.79	74	-12.21
4874	64	PK	H	33.62	7.53	48.36	56.79	74	-17.21
10126	29.05	AV	V	38.69	10.28	47.54	30.48	54	-23.52
10126	27.08	AV	H	38.69	10.28	47.54	28.51	54	-25.49
10126	41.38	PK	V	38.69	10.28	47.54	42.81	74	-31.19
10126	47.04	PK	H	38.69	10.28	47.54	48.47	74	-25.53

High Channel (2462 MHz) (b mode worst case)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4924	49.36	AV	V	33.74	7.78	48.34	42.54	54	-11.46
4924	43.48	AV	H	33.74	7.78	48.34	36.66	54	-17.34
4924	66.62	PK	V	33.74	7.78	48.34	59.8	74	-14.2
4924	68.53	PK	H	33.74	7.78	48.34	61.71	74	-12.29
17778	11.39	AV	V	43.87	18.73	43.52	30.47	54	-23.53
17778	5.13	AV	H	43.87	18.73	43.52	24.21	54	-29.79
17778	33	PK	V	43.87	18.73	43.52	52.08	74	-21.92
17778	26.91	PK	H	43.87	18.73	43.52	45.99	74	-28.01

Note:

- 1, The testing has been conformed to $10 \times 2462 \text{ MHz} = 24,620 \text{ MHz}$
- 2, All other emissions more than 30 dB below the limit
- 3, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.
- 4, The radiated spurious test above 18GHz is subcontracted to SIEMIC (Nanjing-China) Laboratories. and found 30dB below the limit at least.

Annex A. TEST INSTRUMENT

The product was tested in accordance with the following specifications.


All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Please refer to 17021127-FCC-R1
§15.247(a)(1)	Channel Separation	Please refer to 17021127-FCC-R1
§15.247(a)(1)	20 dB Bandwidth	Please refer to 17021127-FCC-R1
§15.247(b)(1)	Peak Output Power	Please refer to 17021127-FCC-R1
§15.247(a)(1)(iii)	Number of Hopping Channel	Please refer to 17021127-FCC-R1
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Please refer to 17021127-FCC-R1
§15.247(d)	Band Edge& Restricted Band	Please refer to 17021127-FCC-R1
§15.207(a)	AC Line Conducted Emissions	Please refer to 17021127-FCC-R1
§15.205, §15.209, §15.247(d)	Radiated Emissions& Restricted Band	Please refer to 17021127-FCC-R1


Annex B. TEST SETUP AND SUPPORTING EQUIPMENT

Annex B.i. TEST SET UP BLOCK


Block Configuration Diagram for AC Line Conducted Emissions



Block Configuration Diagram for Radiated Emissions (Below 1GHz) .



Block Configuration Diagram for Radiated Emissions (Above 1GHz) .



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Dongguan Aohai Power Technology Co.,Ltd.	Adapter	A8-501000	N/A
Dong guan Tenji Technology Industrial Co., Ltd.	Earphone	TJ101891E	N/A

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	1m	N/A

Annex C. User Manual / Block Diagram / Schematics / Partlist/ DECLARATION OF SIMILARITY

TP-LINK TECHNOLOGIES CO., LTD.

Building 24 (floors 1,3,4,5) and 28 (floors 1-4)
Central Science and Technology Park, Shennan Rd, Nanshan, Shenzhen, China

Product Change Description

We, TP-LINK TECHNOLOGIES CO., LTD. ,declare on our sole responsibility that the product,

[TP7031CXYZZ]

is the variant of the initial certified product,

[TP7031C]

Except the following changes on the latest MODEL: [TP7031CXYZZ]

Series Name TP7031CXYZZ

Model Difference

Description of Model Name Differentiation:

X=2, indicates Grey; X=4, indicates Gold; X=7, indicates Blue;

X=8, indicates Red;

Y=0, indicates the memory is 512MB RAM + 8GB Flash; Y=1, indicates

the memory is 1GB RAM + 8GB Flash; Y=2, indicates the memory is

1GB RAM + 16GB Flash;

Z='A' to 'Z', ZZ indicates different regions or customers.

All models are same with electrical parameters and internal circuit structure.

HARDWARE MODIFICATION:

Power Amplifier changes: NO

Antenna changes: NO

PCB Layout changes: NO

LCD changes: NO

Speaker changes: NO

Camera changes: NO

Vibrator changes: NO Bluetooth

changes: NO

FM changes: NO

Other changes: NO

MECHANICAL MODIFICATIONS:

Use new metal front/back cover or keypad: NO

Mechanical shell changes: NO

Other changes detailed: NO

Signature:



Name: Huang Jing

Designation: Regulatory Compliance Manager

Date: 2018-11-29