



中国认可
国际互认
检测
TESTING
CNAS L5313



RF Exposure Evaluation Declaration

Product Name : AC1750 Wireless Dual Band
Gigabit Router

Model No. : Archer C8

FCC ID : TE7C8V2

Applicant : TP-LINK TECHNOLOGIES CO., LTD.

Address : Building 24 (floors 1,3,4,5) and 28 (floors1-4) Central
Science and Technology Park,Shennan Rd,
Nanshan,
Shenzhen,China

Date of Receipt : Mar. 03, 2016

Issued Date : May. 27, 2016

Report No. : 1632027R-RF-US-P20V01

Report Version : V1.0

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of Quietek Corporation.

Test Report Certification

Issued Date : May. 27, 2016

Report No. : 1632027R-RF-US-P20V01



Product Name : AC1750 Wireless Dual Band Gigabit Router
Applicant : TP-LINK TECHNOLOGIES CO., LTD.
Address : Building 24 (floors 1,3,4,5) and 28 (floors1-4) Central
Science and Technology Park,Shennan Rd, Nanshan,
Shenzhen,China
Manufacturer : TP-LINK TECHNOLOGIES CO., LTD
Address : Building 24 (floors 1,3,4,5) and 28 (floors1-4) Central
Science and Technology Park,Shennan Rd, Nanshan,
Shenzhen,China
Model No. : Archer C8
FCC ID : TE7C8V2
Brand Name : AC 100-240V, 50/60Hz
EUT Voltage : TP-LINK
Applicable Standard : KDB 447498D01V06
FCC Part1.1310(b)
Test Result : Complied
Performed Location : Quietek Corporation - Suzhou EMC Laboratory
No.99 Hongye Rd., Suzhou Industrial Park, Suzhou,
215006, Jiangsu, China
TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098
FCC Registration Number: 800392

Documented By :

Alice Ni

(Senior Adm. Specialist: Alice Ni)

Reviewed By :

Frank He

(Senior Engineer: Frank He)

Approved By :

Harry Zhao

(Engineering Manager : Harry Zhao)

Laboratory Information

We, **Quietek Corporation**, are an independent EMC and safety consultancy that was established the whole facility in our laboratories. The test facility has been accredited/accepted(audited or listed) by the following related bodies in compliance with ISO 17025, EN 45001 and specified testing scope:

Taiwan R.O.C.	:	BSMI, NCC, TAF
USA	:	FCC
Japan	:	VCCI
China	:	CNAS

The related certificate for our laboratories about the test site and management system can be downloaded from Quietek Corporation's Web Site : <http://www.quietek.com/english/about/certificates.aspx?bval=5>
The address and introduction of Quietek Corporation's laboratories can be founded in our Web site : http://www.quietek.com/index_en.aspx

If you have any comments, Please don't hesitate to contact us. Our contact information is as below:

HsinChu Testing Laboratory :

No.75-2, 3rd Lin, Wangye Keng, Yonghxing Tsuen, Qionglin Shiang, Hsinchu County 307, Taiwan, R.O.C.
TEL:+886-3-592-8858 / FAX:+886-3-592-8859 E-Mail : service@quietek.com

LinKou Testing Laboratory :

No.5-22, Ruishukeng, Linkou Dist., New Taipei City 24451, Taiwan, R.O.C.
TEL : 886-2-8601-3788 / FAX : 886-2-8601-3789 E-Mail : service@quietek.com

Suzhou Testing Laboratory :

No.99 Hongye Rd., Suzhou Industrial Park, Suzhou, 215006, Jiangsu, China
TEL : +86-512-6251-5088 / FAX : 86-512-6251-5098 E-Mail : service@quietek.com

History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
1632027R-RF-US-P20V01	V1.0	Initial Issued Report	May. 27, 2016

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18 and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product	:	AC1750 Wireless Dual Band Gigabit Router
Test Item	:	RF Exposure Evaluation
Test Site	:	AC-6

2.4G Antenna :

Model No.		N/A								
Antenna manufacturer		TP-LINK								
Antenna Delivery		<input type="checkbox"/>	1*TX+1*RX		<input type="checkbox"/>	2*TX+2*RX		<input checked="" type="checkbox"/>	3*TX+3*RX	
Antenna technology		<input type="checkbox"/>	SISO							
		<input checked="" type="checkbox"/>	MIMO	<input type="checkbox"/>	Basic					
				<input checked="" type="checkbox"/>	CDD					
				<input type="checkbox"/>	Beam-forming					
Antenna Type		<input checked="" type="checkbox"/>	External	<input checked="" type="checkbox"/>	Dipole					
		<input type="checkbox"/>	Internal	<input type="checkbox"/>	PIFA					
				<input type="checkbox"/>	PCB					
				<input type="checkbox"/>	Ceramic Chip Antenna					
				<input type="checkbox"/>	Metal plate type F antenna					
Antenna Technology		Ant Gain (dBi)					Directional Gain (dBi)			
							For Power		For PSD	
<input checked="" type="checkbox"/>	CDD	Ant 0: 2.1 Ant 1: 2.1 Ant 2: 2.1					2.1		6.87	
<input type="checkbox"/>	Beam-forming	N/A					N/A		N/A	

5G Antenna :

Antenna Model	PIFA Antenna					
Antenna Manufacturer	TPlink					
Antenna Delivery	<input type="checkbox"/>	1*TX+1*RX	<input type="checkbox"/>	2*TX+2*RX	<input checked="" type="checkbox"/>	3*TX+3*RX
Antenna Technology	<input type="checkbox"/>	SISO				
	<input checked="" type="checkbox"/>	MIMO	<input type="checkbox"/>	Basic methodology with NANT transmit antennas		
			<input type="checkbox"/>	Sectorized antenna systems		
			<input type="checkbox"/>	Cross-polarized antennas		
			<input type="checkbox"/>	Unequal antenna gains, with equal transmit powers		
			<input checked="" type="checkbox"/>	Spatial Multiplexing		
			<input checked="" type="checkbox"/>	Cyclic Delay Diversity (CDD)		
Antenna Type	Dipole					
Antenna Gain						
Antenna Technology		Ant Gain			Directional Gain	
					For Power	For PSD
<input checked="" type="checkbox"/>	CDD	Ant0: 1.7	Ant1: 1.7	Ant2:1.7	1.7	6.47
<input checked="" type="checkbox"/>	Beam-forming	Ant0: 1.7	Ant1: 1.7	Ant2:1.7	6.47	6.47

- Output Power into Antenna & RF Exposure Evaluation Distance:

Standalone modes

2.4GHz:

Test Mode	Frequency Band (MHz)	Maximum Output Power to Antenna (dBm)	Directional Gain (dBi)	Power Density at R = 25 cm (mW/cm ²)
802.11b/g/n(20MHz)	2412 - 2462	29.36	6.87	0.5345
802.11n(40MHz)	2422 - 2452	18.71	6.87	0.0460

5GHz:

Test Mode	Frequency Band (MHz)	Maximum Output Power to Antenna (dBm)	Directional Gain (dBi)	Power Density at R = 25 cm (mW/cm ²)
802.11a/n(20MHz)/ac(20MHz) with CDD	5180 - 5240 5745 - 5825	26.84	6.47	0.2728
802.11n(40MHz)/ac(40MHz) with CDD	5190 - 5230 5755 - 5795	26.85	6.47	0.2735
802.11ac(80MHz) with CDD	5210	15.67	6.47	0.0326
802.11a/n(20MHz) /ac(20MHz) with Beam-forming	5180 - 5240 5745 - 5825	27.42	6.47	0.3118
802.11n(40MHz) /ac(40MHz) with Beam-forming	5190 - 5230 5755 - 5795	28.87	6.47	0.4354
802.11ac(80MHz) with Beam-forming	5210	16.55	6.47	0.0399

Simultaneous transmission:

Test Mode	Frequency Band (MHz)	Maximum Output Power to Antenna (dBm)	Directional Gain (dBi)	Power Density at R = 25 cm (mW/cm ²)
802.11b/g/n(20MHz)	2412 - 2462	29.36	6.87	0.5345
802.11n(40MHz) /ac(40MHz) with Beam-forming	5190 - 5230 5755 - 5795	28.87	6.47	0.4354
Simultaneous transmission power density				0.9699

So according to transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$ and the power density limit according to KDB 447498D01V06 and FCC Part1.1310(b), the limit is 1mW/cm²

Safety Distance Calculation Formula:

The power flux:

$$S = \frac{P \cdot G_{(\theta, \phi)}}{4 \cdot \pi \cdot r^2}$$

So safety distance as following:

$$r = \sqrt{\frac{P \cdot G}{4 \cdot \pi \cdot S}}$$

P = input power of the antenna

G = antenna gain relative to an isotropic antenna

θ, ϕ = elevation and azimuth angles.

r = distance from the antenna to the point of investigation

Test Mode	Frequency Range (MHz)	Maximum EIRP (dBm)	Limit of Power Density S(mW/cm ²)	Safety Distance r(cm)
802.11b/g/n(20MHz)	2412 - 2462	36.23	1	18.28
802.11n(40MHz) /ac(40MHz) with Beam-forming	5190 - 5230 5755 - 5795	35.34	1	

Note: The safety distance is 25cm for AC1750 Wireless Dual Band Gigabit Router without any other radio equipment.

_____ The End _____