

FCC RF EXPOSURE REPORT

FCC ID: TE7EAP235WALL

Project No. : 1909C126
Equipment : AC1200 Wireless MU-MIMO Gigabit Wall Plate Access Point
Brand Name : tp-link
Test Model : EAP235-Wall
Series Model : N/A
Applicant : TP-Link Technologies Co., Ltd.
Address : Building 24(floors1,3,4,5) and 28(floors1-4) Central Science and Technology Park, Shennan Rd, Nanshan, Shenzhen, China
Manufacturer : TP-Link Technologies Co., Ltd.
Address : Building 24(floors1,3,4,5) and 28(floors1-4) Central Science and Technology Park, Shennan Rd, Nanshan, Shenzhen, China
Date of Receipt : Sep. 20, 2019
Date of Test : Sep. 20, 2019 ~ Nov. 06, 2019
Issued Date : Nov. 22, 2019
Report Version : R00
Test Sample : Engineering Sample No.: DG2019092092
Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091
FCC Title 47 Part 2.1091, OET Bulletin 65 Supplement C

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Vincent Tan

Prepared by : Vincent Tan

Ethan Ma

Approved by : Ethan Ma



Certificate #5123.02

Add: No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China.

Tel: +86-769-8318-3000

Web: www.newbtl.com

REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Original Issue	Nov. 22, 2019

1. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi^2} = \frac{EIRP}{4\pi^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna:

For 2.4GHz:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	PCB	N/A	2.68
2	N/A	N/A	PCB	N/A	2.83

Note:

This EUT supports CDD, and antenna gains are not equal, so Directional gain = $10\log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / N]$ dBi, that is Directional gain = $10\log[(10^{2.68/20} + 10^{2.83/20})^2 / 2]$ dBi = 5.77.

For 5GHz:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	PCB	N/A	2.44
2	N/A	N/A	PCB	N/A	2.94

This EUT supports CDD, and antenna gains are not equal, so.

(1) For Non Beamforming Function:

Directional gain = $10\log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / N]$ dBi, that is Directional gain = $10\log[(10^{2.44/20} + 10^{2.94/20})^2 / 2]$ dBi = 5.70.

(2) For With Beamforming Function:

Beamforming Gain: 3 dB. So Directional gain = 2.94 + 3 = 5.94.

2. TEST RESULTS

For 2.4GHz:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Average Output Power (dBm)	Max. Average Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
5.77	3.7757	23.30	213.7962	0.16068	1	Complies

For 5GHz UNII-1 Non Beamforming:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Average Output Power (dBm)	Max. Average Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
5.70	3.7154	23.90	245.4709	0.18153	1	Complies

For 5GHz UNII-3 Non Beamforming:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Average Output Power (dBm)	Max. Average Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
5.70	3.7154	23.90	245.4709	0.18153	1	Complies

For 5GHz UNII-1 With Beamforming:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Average Output Power (dBm)	Max. Average Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
5.94	3.9264	23.86	243.2204	0.19009	1	Complies

For 5GHz UNII-3 With Beamforming:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Average Output Power (dBm)	Max. Average Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
5.94	3.9264	23.85	242.6610	0.18965	1	Complies

For the max simultaneous transmission MPE:

Power Density (S) (mW/cm ²)	Power Density (S) (mW/cm ²)	Total	Limit of Power Density (S) (mW/cm ²)	Test Result
2.4GHz	5GHz			
0.16068	0.19009	0.35077	1	Complies

Note: The calculated distance is 20 cm.
Output power including tune up tolerance.

End of Test Report