

# RF EXPOSURE REPORT

Applicant	TP-Link Technologies Co., Ltd.
Address	Building 24(floors1,3,4,5) and 28(floors1-4) Central Science and Technology Park, Shennan Rd, Nanshan, Shenzhen, China

Manufacturer or Supplier	TP-Link Technologies Co., Ltd.
Address	Building 24(floors1,3,4,5) and 28(floors1-4) Central Science and Technology Park, Shennan Rd, Nanshan, Shenzhen, China
Product	Smart Wi-Fi Power Strip, 6-Outlet
Brand Name	tp-link
Model	HS300
Additional Model & Model Difference	N/A
Date of tests	Mar. 29, 2018 ~ Mar. 09, 2018

- **⊠** IEEE C95.1

#### CONCLUSION: The submitted sample was found to **COMPLY** with the test requirement

Tested by Harry Li	Approved by Glyn He
Project Engineer/ EMC Department	Supervisor / EMC Department

Date: April. 09, 2018

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie Town, Dongguan City, Guangdong 523942, China Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



## **TABLE OF CONTENTS**

REL	EASE CONTROL RECORD	3
1.	CERTIFICATION	4
	RF EXPOSURE LIMIT	
3.	MPE CALCULATION FORMULA	5
4.	CLASSIFICATION	5
5.	ANTENNA GAIN	6
6	CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	6

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



### **RELEASE CONTROL RECORD**

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FS180129N023	Original release	April. 09, 2018

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



### 1. CERTIFICATION

FCC ID:	TE7HS300		
PRODUCT:	Smart Wi-Fi Power Strip, 6-Outlet		
BRAND NAME:	tp-link		
MODEL NO.:	: HS300		
ADDITIONAL NO.:	: N/A		
TEST SAMPLE: Engineering Sample			
APPLICANT:	CANT: TP-Link Technologies Co., Ltd.		
STANDARDS:	FCC Part 2 (Section 2.1091)		
	KDB 447498 D01		
	IEEE C95.1		

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



#### 2. RF EXPOSURE LIMIT

#### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm²)	AVERAGE TIME (minutes)	
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE					
300-1500			F/1500	30	
1500-100,000			1.0	30	

F = Frequency in MHz

#### 3. MPE CALCULATION FORMULA

 $Pd = (Pout*G) / (4*pi*r^2)$ 

where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

#### 4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com

Page 5 of 6



### 5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Peak Gain (dBi)		Antenna Type	
Chain 0	1.90	PIFA antenna	

#### 6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

FREQUENCY BAND (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm²)	LIMIT (mW/cm²)
2412-2462	85.50667	1.90	20	0.026347	1.0

--- END ---

Tel: +86 769 8593 5656