



中国认可
国际互认
检测
TESTING
CNAS L5313



DEKRA

RF Exposure Evaluation Declaration

Product Name : Kasa Cam
Model No. : KC120
FCC ID : TE7KC120

Applicant : TP-Link Technologies Co., Ltd.
Address : Building 24(floors1,3,4,5) and 28(floors1-4) Central
Science and Technology Park, Shennan Rd,
Nanshan, Shenzhen, China

Date of Receipt : Feb. 10th, 2017
Test Date : Feb. 10th, 2017~ Apr. 25th, 2017
Issued Date : July. 14th, 2017
Report No. : 1722031R-RF-US-P20V01
Report Version : V1.0

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF, CNAS or any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing and Certification (Suzhou) Co., Ltd.


Test Report Certification

Issued Date : July. 14th, 2017


Report No. : 1722031R-RF-US-P20V01




Product Name : Kasa Cam
Applicant : TP-Link Technologies Co., Ltd.
Address : Building 24(floors1,3,4,5) and 28(floors1-4) Central
Science and Technology Park, Shennan Rd, Nanshan,
Shenzhen, China
Manufacturer : TP-Link Technologies Co., Ltd.
Address : Building 24(floors1,3,4,5) and 28(floors1-4) Central
Science and Technology Park, Shennan Rd, Nanshan,
Shenzhen, China
Model No. : KC120
FCC ID : TE7KC120
EUT Voltage : DC 5V,1A
Test Voltage : AC 120V/60Hz
Brand Name : tp-link
Applicable Standard : KDB 447498D01V06
FCC Part1.1310
Test Result : Complied
Performed Location : DEKRA Testing and Certification (Suzhou) Co., Ltd.
No.99 Hongye Rd., Suzhou Industrial Park, Suzhou,
215006, Jiangsu, China
TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098
FCC Registration Number: 800392

Documented By : 

(Adm. Specialist: Kitty Li)

Reviewed By : 

(Senior Engineer: Frank He)

Approved By : 

(Engineering Manager : Harry Zhao)

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18 and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product	:	Kasa Cam
Test Item	:	RF Exposure Evaluation
Test Site	:	AC-6

Antenna Information:

2.4G:

Antenna manufacturer	N/A		
Antenna Delivery	<input checked="" type="checkbox"/> 1*TX+1*RX	<input type="checkbox"/> 2*TX+2*RX	<input type="checkbox"/> 3*TX+3*RX
Antenna technology	<input checked="" type="checkbox"/> SISO		
	<input type="checkbox"/> MIMO	<input type="checkbox"/> Basic	
		<input type="checkbox"/> Sectorized antenna systems	
		<input type="checkbox"/> Cross-polarized antennas	
		<input type="checkbox"/> Unequal antenna gains, with equal transmit powers	
		<input type="checkbox"/> Spatial Multiplexing	
		<input type="checkbox"/> CDD	
		<input type="checkbox"/> Beam-forming	
Antenna Type	<input type="checkbox"/> External	<input type="checkbox"/> Dipole	
	<input checked="" type="checkbox"/> Internal	<input checked="" type="checkbox"/> PIFA	
		<input type="checkbox"/> PCB	
		<input type="checkbox"/> Ceramic Chip Antenna	
		<input type="checkbox"/> Metal plate type F antenna	
		<input type="checkbox"/> Cross-polarize Antenna	
Antenna Gain #0	4.42dBi		

5G :

Antenna Model No.	N/A		
Antenna Manufacturer	tp-link		
Antenna Delivery	<input checked="" type="checkbox"/> 1*TX+1*RX	<input type="checkbox"/> 2*TX+2*RX	<input type="checkbox"/> 3*TX+4*RX
Antenna Technology	<input checked="" type="checkbox"/> SISO		
	<input type="checkbox"/> MIMO	<input type="checkbox"/> Basic methodology with NANT transmit antennas	
		<input type="checkbox"/> Sectorized antenna systems	
		<input type="checkbox"/> Cross-polarized antennas	
		<input type="checkbox"/> Unequal antenna gains, with equal transmit powers	
		<input type="checkbox"/> Spatial Multiplexing	
	<input type="checkbox"/> Cyclic Delay Diversity (CDD)		
Antenna Type	PIFA Antenna		
Antenna Gain			
Antenna Technology	Ant Gain (dBi)		
<input type="checkbox"/> Basic MIMO	Ant1: 4.77		

- Output Power into Antenna & RF Exposure Evaluation Distance
- Standalone modes

Test Mode	Frequency Band (MHz)	Maximum Output Power to Antenna (dBm)	Directional Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Power Density Limit at R = 20 cm (mW/cm ²)
802.11b/g/n(20MHz)	2412 ~ 2462 MHz	22.35	4.42	0.0946	1.0
802.11n(40MHz)	2422 ~ 2452 MHz	16.06	4.42	0.0222	1.0
802.11a/n/ac(20MHz)	5180-5240MHz 5745-5825 MHz	23.43	4.77	0.1314	1.0
802.11n/ac (40MHz)	5190-5230MHz 5755-5795 MHz	23.27	4.77	0.1267	1.0
802.11ac(80MHz)	5210MHz 5775MHz	17.41	4.77	0.0329	1.0

Simultaneous transmission:

Frequency Band (MHz)	Maximum Output Power to Antenna (dBm)	Directional Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Power Density Limit at R = 20 cm (mW/cm ²)
2412 ~ 2462	22.35	4.42	0.0946	1.0
5180-5240 5745-5825	23.43	4.77	0.1314	1.0
Simultaneous transmission power density			0.2260	1.0

Note: The simultaneous transmission power density is 0.2260mW/cm² for Kasa Cam without any other radio equipment.

_____ The End _____