



# TEST REPORT

**Reference No.**..... : WTF20F07043252-1W  
**FCC ID** ..... : TE7KL1X0  
**Applicant**..... : TP-Link Technologies Co., Ltd.  
**Address**..... : Building 24(floors1,3,4,5) and 28(floors1-4) Central Science and Technology Park, Shennan Rd, Nanshan, Shenzhen, China  
**Manufacturer** ..... : The same as above  
**Address**..... : The same as above  
**Product Name**..... : Kasa Smart Light Bulb, Dimmable  
Kasa Smart Light Bulb, Multicolor  
**Model No.**..... : KL110, KL130  
**Standards**..... : FCC CFR47 Part 15 Subpart C (Section 15.247): 2019  
**Date of Receipt sample** .... : 2020-07-08  
**Date of Test** ..... : 2020-08-05  
**Date of Issue**..... : 2020-08-26  
**Test Result**..... : **Pass**

**Remarks:**

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

**Prepared By:**

**Waltek Testing Group (Foshan) Co., Ltd.**

Address: No.13-19, 2/F., 2nd Building, Sunlink International Machinery City,  
Chencun, Shunde District, Foshan, Guangdong, China

Tel:+86-757-23811398 Fax:+86-757-23811381 E-mail:info@waltek.com.cn

Compiled by:

Roy Hong / Project Engineer

Approved by:

Danny Zhou / Manager



## 1 Revision History

Test Report No.	Date of Issue	Description	Status
WTF20F07043252-1W	2020-08-05	Original	Valid





## 2 Contents

	<b>Page</b>
<b>1 REVISION HISTORY</b> .....	<b>2</b>
<b>2 CONTENTS</b> .....	<b>3</b>
<b>3 GENERAL INFORMATION</b> .....	<b>4</b>
3.1 GENERAL DESCRIPTION OF E.U.T .....	4
3.2 TECHNICAL CHARACTERISTICS OF EUT .....	4
3.3 STANDARDS APPLICABLE FOR TESTING .....	5
3.4 TEST FACILITY .....	5
3.5 SUBCONTRACTED .....	6
3.6 ABNORMALITIES FROM STANDARD CONDITIONS .....	6
<b>4 EUT SETUP AND TEST MODE</b> .....	<b>7</b>
<b>5 EQUIPMENT USED DURING TEST</b> .....	<b>8</b>
5.1 EQUIPMENT LIST .....	8
5.2 SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT .....	9
5.3 MEASUREMENT UNCERTAINTY .....	9
<b>6 SUMMARY OF TEST RESULT</b> .....	<b>10</b>
6.1 ANTENNA REQUIREMENT .....	11
6.2 RF EXPOSURE REQUIREMENT .....	12
6.3 RADIATED SPURIOUS EMISSIONS .....	13
6.4 POWER SPECTRAL DENSITY .....	25
6.5 DTS BANDWIDTH.....	31
6.6 RF OUTPUT POWER.....	37
6.7 BAND EDGE MEASUREMENT .....	43
6.8 CONDUCTED EMISSIONS.....	49
<b>7 PHOTOGRAPHS TEST SETUP</b> .....	<b>54</b>
7.1 PHOTOGRAPHS - RADIATED EMISSION TEST SETUP .....	54
7.2 PHOTOGRAPHS - CONDUCTED EMISSION TEST SETUP .....	55
<b>8 PHOTOGRAPHS - CONSTRUCTIONAL DETAILS</b> .....	<b>56</b>
8.1 EUT - EXTERNAL VIEW .....	56
8.2 EUT - INTERNAL VIEW.....	62



### 3 General Information

#### 3.1 General Description of E.U.T

<b>Product Name</b> .....	:	Kasa Smart Light Bulb, Dimmable Kasa Smart Light Bulb, Multicolor
<b>Model No.</b> .....	:	KL110, KL130
<b>Model Description</b> .....	:	Product name Kasa Smart Light Bulb, Dimmable for model KL110. Product name Kasa Smart Light Bulb, Multicolor for model KL130. Two models with same RF module but different electric circuit. Therefore the full tests were performed on model KL110, additional DV and Spurious Emission were performed on model KL130.
<b>Rated Voltage</b> .....	:	AC 120V, 60Hz, 9W
<b>Battery Capacity</b> .....	:	---
<b>Power Adapter</b> .....	:	---

#### 3.2 Technical Characteristics of EUT

<b>Support Standards</b> .....	:	802.11b, 802.11g, 802.11n
<b>Frequency Range</b> .....	:	2412-2462MHz for 802.11b/g/n(HT20)
<b>RF Output Power</b> .....	:	18.24dBm (Conducted )
<b>Modulation</b> .....	:	DBPSK,BPSK,DQPSK,QPSK,16QAM,64QAM
<b>Data Rate</b> .....	:	1-11Mbps, 6-54Mbps, MCS0-MCS7
<b>Quantity of Channels</b> .....	:	11
<b>Channel Separation</b> .....	:	5MHz
<b>Type of Antenna</b> .....	:	PCB Printed Antenna
<b>Antenna Gain</b> .....	:	1.5dBi
<b>Lowest Oscillation</b> .....	:	40MHz



### 3.3 Standards Applicable for Testing

The tests were performed according to following standards:

FCC Rules Part 15.247	Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz
558074 D01 15.247 Meas Guidance v05r02	Guidance For Compliance Measurements On Digital Transmission System, Frequency Hopping Spread Spectrum System, And Hybrid System Devices Operating Under Section 15.247 Of The FCC Rules
662911 D01 Multiple Transmitter Output v02r01	Emissions Testing of Transmitters with Multiple Outputs in the Same Band
ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

### 3.4 Test Facility

The test facility has a test site registered with the following organizations:

- **IC – Registration No.: 21895-1**

Waltek Testing Group (Foshan) Co., Ltd. has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files. Registration IC number:21895-1, Nov. 14, 2016.

- **FCC – Registration No.: 820106**

Waltek Testing Group (Foshan) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 820106, August 16, 2018

- **FCC – Designation No.: CN5034**

Waltek Testing Group (Foshan) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation No. CN5034.

- **NVLAP – Lab Code: 600191-0**

Waltek Services (Foshan) Co., Ltd. EMC Laboratory is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 600191-0.

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.



### 3.5 Subcontracted

Whether parts of tests for the product have been subcontracted to other labs:

Yes       No

If Yes, list the related test items and lab information:

Test items: ---

Lab information: ---

### 3.6 Abnormalities from Standard Conditions

None.



# WALTEK



## 4 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

**Test Mode List**

Test Mode	Description	Remark
TM1	802.11b	Low:2412MHz, Middle:2437MHz, High:2462MHz
TM2	802.11g	Low:2412MHz, Middle:2437MHz, High:2462MHz
TM3	802.11n-HT20	Low:2412MHz, Middle:2437MHz, High:2462MHz

**Test Conditions**

Temperature:	22~25°C
Relative Humidity:	50~55%
Atmospheric pressure:	101.9kPa

# WALTEK



## 5 Equipment Used during Test

### 5.1 Equipment List

Conducted Emissions						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal Date	Cal Due Date
1.	EMI Test Receiver	R&S	ESR3	102423	2020-01-09	2021-01-08
2.	LISN	R&S	ENV216	101343	2020-01-09	2021-01-08
3.	Cable	HUBER+SUHNER	CBL2-NN-6M	223NN624	2020-01-09	2021-01-08
4.	Test Software	FARATRONIC	EZ-EMC	-	-	-
5.	Shielding Room	Zhongshuo	8mx4mx3m	-	2018-04-26	2021-04-25
3m Semi-anechoic Chamber for Radiation Emissions						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal Date	Cal Due Date
1.	EMI Test Receiver	RS	ESR7	101566	2020-01-09	2021-01-08
2.	EMC Analyzer	Agilent	N9020A	MY48011796	2020-01-09	2021-01-08
3.	Active Loop Antenna	SCHWARZBECK	FMZB1519B	00004	2020-01-09	2021-01-08
4.	Trilog Broadband Antenna	SCHWARZBECK	VULB 9162	9162-117	2020-01-09	2021-01-08
5.	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	01561	2020-01-09	2021-01-08
6.	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9170	335	2020-01-09	2021-01-08
7.	Amplifier	Lunar E M	LNA1G18-40	20160501002	2020-01-09	2021-01-08
8.	Coaxial Cable (below 1GHz)	H+S	CBL3-NN-12+3 m	214NN320	2020-01-09	2021-01-08
9.	Coaxial Cable (above 1GHz)	Times-Microwave	CBL5-NN	-	2020-01-09	2021-01-08
10.	Test Software	FARATRONIC	EZ-EMC RA-03A1-1	-	-	-
11.	966 Semi-anechoic Chamber	CHANGCHUANG	9mx6mx6m	-	2018-03-14	2021-03-13
RF Conducted Testing						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal Date	Cal Due Date
1.	Spectrum Analyzer	Agilent	N9020A	MY48011796	2020-01-09	2021-01-08
2.	Spectrum Analyzer	R&S	FSP40	100501	2020-01-09	2021-01-08
3.	Vector Signal Generator	Agilent	N5182A	MY50141533	2020-01-09	2021-01-08
4.	Analog Signal Generator	Agilent	N5181A	MY48180720	2020-01-09	2021-01-08
5.	Environmental Chamber	KSON	THS-D4C-100	5244K	2020-01-09	2021-01-08
6.	RF Control Unit	CHANGCHUANG	JS0806-2	-	2020-01-09	2021-01-08
7.	Shielding Room	CHANGCHUANG	5mx4mx3m	-	2018-01-11	2021-01-10





## 5.2 Special Accessories and Auxiliary Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.
1.	/	/	/	/

## 5.3 Measurement Uncertainty

Parameter	Uncertainty
RF Output Power	$\pm 0.95\text{dB}$
Occupied Bandwidth	$\pm 1.5\%$
Conducted Spurious Emission	$\pm 2.7\text{dB}$
Conducted Emission	$\pm 2.7\text{dB}$
Transmitter Spurious Emission	$\pm 3.8\text{dB}$ (for 25MHz-1GHz)
	$\pm 5.0\text{dB}$ (for 1GHz-18GHz)

# WALTEK



## 6 Summary of Test Result

Test Items	FCC Rules	Result
Antenna Requirement	§15.203; §15.247(b)(4)(i)	Compliance
Restricted Band of Operation	§15.205	Compliance
Conducted Emissions	§15.207(a)	Compliance
Radiated Spurious Emissions	§15.209(a)	Compliance
Power Spectral Density	§15.247(e)	Compliance
DTS Bandwidth	§ 15.247(a)(2)	Compliance
RF Output Power	§15.247(b)(3)	Compliance
Band edge (Out of Band Emissions)	§15.247(d)	Compliance
RF Exposure	§2.1093	Compliance

Remark:

- Pass Test item meets the requirement  
Fail Test item does not meet the requirement  
N/A Test case does not apply to the test object

# WALTEK




## 6.1 Antenna Requirement

### 6.1.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

### 6.1.2 Evaluation Information

The EUT has an PCB Printed Antenna, the gain is 1.5dBi, fulfil the requirement of this section.





## **6.2 RF Exposure Requirement**

### **6.2.1 Standard Applicable**

According to §1.1307 and §2.1093, the portable transmitter must comply the RF exposure requirements.

### **6.2.2 Test Result**

This product complied with the requirement of the RF exposure, please see the RF Exposure Report WTF20F07043252-2W.



# WALTEK



## 6.3 Radiated Spurious Emissions

### 6.3.1 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

### 6.3.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.


The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

The test setup for emission measurement below 30MHz.






The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.





### 6.3.3 Spectrum Analyzer Setup

#### 9KHz-30MHz

RBW=10kHz

VBW=30kHz

Sweep time=Auto

Trace=Max hold

Detector function=peak

#### 30MHz-1GHz

RBW=120kHz

VBW=300kHz

Sweep time=Auto

Trace=Max hold

Detector function=peak, QP

#### Above 1GHz

RBW=1MHz

VBW=3MHz(Peak), 10MHz(AV)

Sweep time=Auto

Trace=Max hold

Detector function=peak, AV

### 6.3.4 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Corr. Factor}$$

$$\text{Corr. Factor} = \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

# WALTEK



### 6.3.5 Test Results

Note: All test modes (different data rate and different modulation) are performed, but only the worst case is recorded in this report.

**Test Frequency: 30MHz ~ 18GHz**

Frequency (MHz)	Receiver Reading (dBμV/m)	Detector (PK/QP/AVG)	Turn table Angle (°)	RX Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247	
				Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
<b>KL110_802.11b_Low Channel</b>									
30.40	10.70	QP	170	1.6	H	11.17	21.87	40	-18.13
30.40	10.10	QP	117	1.8	V	11.17	21.27	40	-18.73
1834.25	50.77	PK	144	1.8	H	-12.62	38.15	74	-35.85
1834.25	40.93	AVG	100	1.3	H	-12.62	28.31	54	-25.69
4824.75	57.33	PK	134	1.3	V	-3.41	53.92	74	-20.08
4824.75	49.16	AVG	126	1.4	V	-3.41	45.75	54	-8.25
5970.25	46.67	PK	220	1.3	H	-0.72	45.95	74	-28.05
5970.25	36.91	AVG	217	1.3	H	-0.72	36.19	54	-17.81
7227.50	38.45	PK	274	1.8	V	2.98	41.43	74	-12.57
7227.50	46.73	AVG	255	1.6	V	2.98	49.71	54	-24.29
8461.25	47.46	PK	207	1.7	H	4.23	51.69	74	-22.31
8461.25	38.43	AVG	109	1.3	H	4.23	42.66	54	-11.31

Frequency (MHz)	Receiver Reading (dBμV/m)	Detector (PK/QP/AVG)	Turn table Angle (°)	RX Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247	
				Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
<b>KL110_802.11b_Middle Channel</b>									
40.15	5.94	QP	159	1.5	H	12.91	18.85	40	-21.15
40.15	6.75	QP	248	1.6	V	12.91	19.66	40	-20.34
1951.75	50.67	PK	150	1.4	H	-12.15	38.52	74	-35.48
1951.75	40.94	AVG	273	1.8	H	-12.15	28.79	54	-25.21
4243.00	46.91	PK	210	1.1	V	-4.97	41.94	74	-32.06
4243.00	38.6	AVG	102	1.8	V	-4.97	33.63	54	-20.37
4874.75	56.51	PK	179	1.4	H	-3.27	53.24	74	-20.76
4874.75	54.11	AVG	260	1.3	H	-3.27	50.84	54	-3.16
5547.25	46.82	PK	189	1.7	V	-1.93	44.89	74	-29.11
5547.25	37.64	AVG	184	1.6	V	-1.93	35.71	54	-18.29
6757.50	48.33	PK	128	1.1	H	1.83	50.16	74	-23.84
6757.50	37.72	AVG	226	1.4	H	1.83	39.55	54	-14.45





Frequency (MHz)	Receiver Reading (dB $\mu$ V/m)	Detector (PK/QP/AVG)	Turn table Angle (°)	RX Antenna		Corrected Factor (dB)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part 15.247	
				Height (m)	Polar (H/V)			Limit (dB $\mu$ V/m)	Margin (dB)
<b>KL110_802.11b_High Channel</b>									
47.74	4.94	QP	110	1.1	H	13.56	18.5	40	-21.50
47.74	7.77	QP	206	1.7	V	13.56	21.33	40	-18.67
1329.00	54.00	PK	124	1.5	H	-14.90	39.10	74	-34.90
1329.00	48.23	AVG	254	1.5	H	-14.90	33.33	54	-20.67
3385.25	49.44	PK	169	1.9	V	-7.43	42.01	74	-31.99
3385.25	39.80	AVG	252	1.7	V	-7.43	32.37	54	-21.63
4924.50	57.23	PK	167	1.8	H	-3.14	54.09	74	-19.91
4924.50	48.63	AVG	179	1.7	H	-3.14	45.49	54	-8.51
6087.75	45.92	PK	219	1.2	V	-0.36	45.56	74	-28.44
6087.75	37.21	AVG	165	1.9	V	-0.36	36.85	54	-17.15
7580.00	47.92	PK	192	1.5	H	3.48	51.40	74	-22.60
7580.00	38.76	AVG	108	1.1	H	3.48	42.24	54	-11.76

Frequency (MHz)	Receiver Reading (dB $\mu$ V/m)	Detector (PK/QP/AVG)	Turn table Angle (°)	RX Antenna		Corrected Factor (dB)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part 15.247	
				Height (m)	Polar (H/V)			Limit (dB $\mu$ V/m)	Margin (dB)
<b>KL110_802.11g_Low Channel</b>									
77.84	17.26	QP	225	1.6	H	10.13	27.39	40	-12.61
77.84	16.24	QP	120	1.5	V	10.13	26.37	40	-13.63
1317.25	54.40	PK	276	1.4	H	-14.96	39.44	74	-34.56
1317.25	43.33	AVG	290	1.4	H	-14.96	28.37	54	-25.63
3843.50	48.14	PK	160	1.1	V	-6.10	42.04	74	-31.96
3843.50	39.21	AVG	139	1.4	V	-6.10	33.11	54	-20.89
4824.75	56.85	PK	233	1.4	H	-3.41	53.44	74	-20.56
4824.75	49.20	AVG	222	1.3	H	-3.41	45.79	54	-8.21
5993.75	46.19	PK	177	1.5	V	-0.66	45.53	74	-28.47
5993.75	37.00	AVG	199	1.6	V	-0.66	36.34	54	-17.66
7227.50	47.56	PK	282	1.4	H	2.98	50.54	74	-23.46
7227.50	38.30	AVG	283	1.8	H	2.98	41.28	54	-12.72



Frequency (MHz)	Receiver Reading (dB $\mu$ V/m)	Detector (PK/QP/AVG)	Turn table Angle (°)	RX Antenna		Corrected Factor (dB)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part 15.247	
				Height (m)	Polar (H/V)			Limit (dB $\mu$ V/m)	Margin (dB)
<b>KL110_802.11g_Middle Channel</b>									
94.63	13.81	QP	163	1.5	H	11.11	24.92	43.5	-18.58
94.63	17.21	QP	246	1.3	V	11.11	28.32	43.5	-15.18
1329.00	53.66	PK	157	1.1	H	-14.90	38.76	74	-35.24
1329.00	48.38	AVG	268	1.4	H	-14.90	33.48	54	-20.52
3902.25	47.99	PK	141	1.5	V	-5.91	42.08	74	-31.92
3902.25	39.35	AVG	169	1.5	V	-5.91	33.44	54	-20.56
4865.75	68.25	PK	278	1.3	H	-3.30	64.95	74	-9.05
4865.75	54.24	AVG	109	1.6	H	-3.30	50.94	54	-3.06
6781.00	47.10	PK	156	1.4	V	1.91	49.01	74	-24.99
6781.00	37.66	AVG	178	1.8	V	1.91	39.57	54	-14.43
7309.75	51.03	PK	289	1.3	H	3.10	54.13	74	-19.87
7309.75	45.84	AVG	134	1.8	H	3.10	48.94	54	-5.06

Frequency (MHz)	Receiver Reading (dB $\mu$ V/m)	Detector (PK/QP/AVG)	Turn table Angle (°)	RX Antenna		Corrected Factor (dB)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part 15.247	
				Height (m)	Polar (H/V)			Limit (dB $\mu$ V/m)	Margin (dB)
<b>KL110_802.11g_High Channel</b>									
35.33	-0.66	QP	224	1.8	H	13.21	12.55	40	-27.45
35.33	-0.85	QP	165	1.6	V	13.21	12.36	40	-27.64
1329.00	53.65	PK	155	1.1	H	-14.90	38.75	74	-35.25
1329.00	47.92	AVG	237	1.2	H	-14.90	33.02	54	-20.98
4196.00	47.60	PK	260	1.6	V	-5.09	42.51	74	-31.49
4196.00	38.55	AVG	236	1.5	V	-5.09	33.46	54	-20.54
4924.50	56.39	PK	184	1.2	H	-3.14	53.25	74	-20.75
4924.50	48.94	AVG	227	1.6	H	-3.14	45.80	54	-8.20
6170.00	46.38	PK	232	1.4	V	-0.10	46.28	74	-27.72
6170.00	37.58	AVG	277	1.4	V	-0.10	37.48	54	-16.52
7368.50	47.78	PK	269	1.3	H	3.20	50.98	74	-23.02
7368.50	38.63	AVG	229	1.9	H	3.20	41.83	54	-12.17



Frequency (MHz)	Receiver Reading (dB $\mu$ V/m)	Detector (PK/QP/AVG)	Turn table Angle (°)	RX Antenna		Corrected Factor (dB)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part 15.247	
				Height (m)	Polar (H/V)			Limit (dB $\mu$ V/m)	Margin (dB)
<b>KL110_802.11n20_Low Channel</b>									
35.77	-0.29	QP	173	1.8	H	13.23	12.94	40	-27.06
35.77	-0.57	QP	212	1.6	V	13.23	12.66	40	-27.34
1317.25	55.14	PK	254	1.4	H	-14.96	40.18	74	-33.82
1317.25	43.36	AVG	166	1.8	H	-14.96	28.40	54	-25.60
3103.25	50.24	PK	172	1.2	V	-7.80	42.44	74	-31.56
3103.25	39.36	AVG	278	1.5	V	-7.80	31.56	54	-22.44
4824.75	56.12	PK	249	1.4	H	-3.41	52.71	74	-21.29
4824.75	47.33	AVG	218	1.7	H	-3.41	43.92	54	-10.08
6076.00	46.29	PK	272	1.7	V	-0.40	45.89	74	-28.11
6076.00	36.75	AVG	248	1.8	V	-0.40	36.35	54	-17.65
7227.50	49.76	PK	155	1.2	H	2.98	52.74	74	-21.26
7227.50	39.30	AVG	230	1.6	H	2.98	42.28	54	-11.72

Frequency (MHz)	Receiver Reading (dB $\mu$ V/m)	Detector (PK/QP/AVG)	Turn table Angle (°)	RX Antenna		Corrected Factor (dB)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part 15.247	
				Height (m)	Polar (H/V)			Limit (dB $\mu$ V/m)	Margin (dB)
<b>KL110_802.11n20_Middle Channel</b>									
52.43	3.35	QP	173	1.5	H	13.66	17.01	40	-22.99
52.43	2.24	QP	107	1.4	V	13.66	15.9	40	-24.10
1329.00	54.24	PK	127	1.7	H	-14.90	39.34	74	-34.66
1329.00	44.05	AVG	268	1.4	H	-14.90	29.15	54	-24.85
3890.50	48.84	PK	271	1.2	V	-5.94	42.90	74	-31.10
3890.50	39.35	AVG	104	1.3	V	-5.94	33.41	54	-20.59
4865.75	68.80	PK	238	1.6	H	-3.30	65.50	74	-8.50
4865.75	54.12	AVG	245	1.9	H	-3.30	50.82	54	-3.18
6205.25	45.94	PK	140	1.2	V	0.02	45.96	74	-28.04
6205.25	37.32	AVG	288	1.8	V	0.02	37.34	54	-16.66
7309.75	52.79	PK	289	1.5	H	3.10	55.89	74	-18.11
7309.75	45.88	AVG	241	1.6	H	3.10	48.98	54	-5.02



Frequency (MHz)	Receiver Reading (dB $\mu$ V/m)	Detector (PK/QP/AVG)	Turn table Angle (°)	RX Antenna		Corrected Factor (dB)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part 15.247	
				Height (m)	Polar (H/V)			Limit (dB $\mu$ V/m)	Margin (dB)
<b>KL110_802.11n20_High Channel</b>									
234.33	3.94	QP	280	1.6	H	14.41	18.35	43.5	-25.15
234.33	2.34	QP	186	1.7	V	14.41	16.75	43.5	-26.75
2104.50	50.11	PK	283	1.3	H	-11.56	38.55	74	-35.45
2104.50	41.19	AVG	289	1.7	H	-11.56	29.63	54	-24.37
3737.75	48.05	PK	281	1.7	V	-6.56	41.49	74	-32.51
3737.75	39.15	AVG	222	1.9	V	-6.56	32.59	54	-21.41
4924.75	51.09	PK	229	1.2	H	-3.30	47.79	74	-26.21
4924.75	38.20	AVG	279	1.7	H	-3.30	34.90	54	-19.10
6029.00	47.16	PK	274	1.2	V	-1.05	46.11	74	-27.89
6029.00	37.19	AVG	151	1.2	V	-1.05	36.14	54	-17.86
6863.25	46.99	PK	161	1.2	H	2.09	49.08	74	-24.92
6863.25	38.24	AVG	114	1.6	H	2.09	40.33	54	-13.67

Frequency (MHz)	Receiver Reading (dB $\mu$ V/m)	Detector (PK/QP/AVG)	Turn table Angle (°)	RX Antenna		Corrected Factor (dB)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part 15.247	
				Height (m)	Polar (H/V)			Limit (dB $\mu$ V/m)	Margin (dB)
<b>KL130_802.11b_Low Channel</b>									
60.68	7.18	QP	179	1.6	H	12.61	19.79	40	-20.21
60.68	11.04	QP	184	1.4	V	12.61	23.65	40	-16.35
2034.00	49.28	PK	108	1.7	H	-11.83	37.45	74	-36.55
2034.00	38.07	AVG	210	1.2	H	-11.83	26.24	54	-27.76
3232.50	50.26	PK	198	2.0	V	-7.95	42.31	74	-31.69
3232.50	40.43	AVG	117	1.7	V	-7.95	32.48	54	-21.52
4824.75	60.77	PK	154	1.6	H	-3.54	57.23	74	-16.77
4824.75	51.32	AVG	280	1.4	H	-3.54	47.78	54	-6.22
6134.75	46.29	PK	273	1.3	V	-0.73	45.56	74	-28.44
6134.75	37.65	AVG	148	1.3	V	-0.73	36.92	54	-17.08
7533.00	47.23	PK	270	1.2	H	3.55	50.78	74	-23.22
7533.00	38.75	AVG	217	1.8	H	3.55	42.30	54	-11.70



Frequency (MHz)	Receiver Reading (dB $\mu$ V/m)	Detector (PK/QP/AVG)	Turn table Angle (°)	RX Antenna		Corrected Factor (dB)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part 15.247	
				Height (m)	Polar (H/V)			Limit (dB $\mu$ V/m)	Margin (dB)
<b>KL130_802.11b_Middle Channel</b>									
82.91	9.40	QP	119	1.8	H	10.39	19.79	40	-20.21
82.91	11.12	QP	233	1.3	V	10.39	21.51	40	-18.49
1799.00	50.05	PK	274	1.6	H	-12.55	37.50	74	-36.50
1799.00	41.93	AVG	101	1.1	H	-12.55	29.38	54	-24.62
3925.75	48.34	PK	255	1.1	V	-5.99	42.35	74	-31.65
3925.75	38.94	AVG	110	1.1	V	-5.99	32.95	54	-21.05
4865.75	54.75	PK	210	2.0	H	-3.45	51.30	74	-22.70
4865.75	41.93	AVG	228	1.0	H	-3.45	38.48	54	-15.52
5676.50	47.26	PK	140	1.9	V	-1.86	45.40	74	-28.60
5676.50	37.96	AVG	147	1.3	V	-1.86	36.10	54	-17.90
6922.00	46.32	PK	223	1.3	H	2.38	48.70	74	-25.30
6922.00	38.14	AVG	199	2.0	H	2.38	40.52	54	-13.48

Frequency (MHz)	Receiver Reading (dB $\mu$ V/m)	Detector (PK/QP/AVG)	Turn table Angle (°)	RX Antenna		Corrected Factor (dB)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part 15.247	
				Height (m)	Polar (H/V)			Limit (dB $\mu$ V/m)	Margin (dB)
<b>KL130_802.11b_High Channel</b>									
105.98	6.37	QP	286	1.6	H	12.40	18.77	43.5	-24.73
105.98	9.79	QP	108	1.5	V	12.40	22.19	43.5	-21.31
1940.00	50.76	PK	101	1.3	H	-12.14	38.62	74	-35.38
1940.00	40.77	AVG	223	1.9	H	-12.14	28.63	54	-25.37
3878.75	48.29	PK	107	1.1	V	-6.14	42.15	74	-31.85
3878.75	39.43	AVG	175	1.1	V	-6.14	33.29	54	-20.71
4924.75	51.63	PK	117	1.2	H	-3.30	48.33	74	-25.67
4924.75	38.58	AVG	113	1.4	H	-3.30	35.28	54	-18.72
6334.50	46.57	PK	220	1.2	V	-0.13	46.44	74	-27.56
6334.50	36.97	AVG	144	1.9	V	-0.13	36.84	54	-17.16
7650.50	47.52	PK	144	1.6	H	3.73	51.25	74	-22.75
7650.50	38.14	AVG	101	1.3	H	3.73	41.87	54	-12.13



Frequency (MHz)	Receiver Reading (dB $\mu$ V/m)	Detector (PK/QP/AVG)	Turn table Angle (°)	RX Antenna		Corrected Factor (dB)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part 15.247	
				Height (m)	Polar (H/V)			Limit (dB $\mu$ V/m)	Margin (dB)
<b>KL130_802.11g_Low Channel</b>									
338.88	8.96	QP	132	1.2	H	16.75	25.71	43.5	-17.79
338.88	6.26	QP	100	1.5	V	16.75	23.01	43.5	-20.49
1857.75	52.56	PK	265	1.1	H	-12.38	40.18	74	-33.82
1857.75	41.11	AVG	181	2.0	H	-12.38	28.73	54	-25.27
3361.75	49.02	PK	221	1.8	V	-7.64	41.38	74	-32.62
3361.75	40.02	AVG	169	1.4	V	-7.64	32.38	54	-21.62
4824.75	60.55	PK	116	1.9	H	-3.54	57.01	74	-16.99
4824.75	51.28	AVG	170	1.3	H	-3.54	47.74	54	-6.26
6087.75	45.82	PK	245	2.0	V	-0.88	44.94	74	-29.06
6087.75	37.58	AVG	127	1.1	V	-0.88	36.70	54	-17.30
7603.50	46.97	PK	209	1.6	H	3.65	50.62	74	-23.38
7603.50	38.32	AVG	270	1.3	H	3.65	41.97	54	-12.03

Frequency (MHz)	Receiver Reading (dB $\mu$ V/m)	Detector (PK/QP/AVG)	Turn table Angle (°)	RX Antenna		Corrected Factor (dB)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part 15.247	
				Height (m)	Polar (H/V)			Limit (dB $\mu$ V/m)	Margin (dB)
<b>KL130_802.11g_Middle Channel</b>									
44.74	-3.25	QP	108	1.9	H	15.30	12.05	40	-27.95
44.74	1.03	QP	193	1.8	V	15.30	16.33	40	-23.67
1893.00	50.11	PK	236	1.9	H	-12.27	37.84	74	-36.16
1893.00	42.00	AVG	150	2.0	H	-12.27	29.73	54	-24.27
3279.50	48.90	PK	219	2.0	V	-7.83	41.07	74	-32.93
3279.50	40.57	AVG	107	1.1	V	-7.83	32.74	54	-21.26
4865.75	54.09	PK	104	1.8	H	-3.45	50.64	74	-23.36
4865.75	42.27	AVG	243	1.3	H	-3.45	38.82	54	-15.18
6076.00	45.92	PK	246	1.3	V	-0.92	45.00	74	-29.00
6076.00	37.58	AVG	180	1.5	V	-0.92	36.66	54	-17.34
7309.75	46.72	PK	185	2.0	H	3.20	49.92	74	-24.08
7309.75	38.43	AVG	153	2.0	H	3.20	41.63	54	-12.37



Frequency (MHz)	Receiver Reading (dB $\mu$ V/m)	Detector (PK/QP/AVG)	Turn table Angle (°)	RX Antenna		Corrected Factor (dB)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part 15.247	
				Height (m)	Polar (H/V)			Limit (dB $\mu$ V/m)	Margin (dB)
<b>KL130_802.11g_High Channel</b>									
41.60	-1.66	QP	249	1.2	H	14.98	13.32	40	-26.68
41.60	-4.29	QP	278	1.9	V	14.98	10.69	40	-29.31
1329.00	52.17	PK	268	1.1	H	-13.92	38.25	74	-35.75
1329.00	43.06	AVG	300	1.2	H	-13.92	29.14	54	-24.86
3867.00	48.47	PK	237	1.5	V	-6.18	42.29	74	-31.71
3867.00	39.32	AVG	172	1.4	V	-6.18	33.14	54	-20.86
4924.50	52.50	PK	137	1.8	H	-3.31	49.19	74	-24.81
4924.50	38.90	AVG	229	1.1	H	-3.31	35.59	54	-18.41
5359.25	47.74	PK	269	1.8	V	-2.50	45.24	74	-28.76
5359.25	38.12	AVG	182	1.0	V	-2.50	35.62	54	-18.38
7333.25	47.98	PK	264	1.6	H	3.25	51.23	74	-22.77
7333.25	38.11	AVG	276	1.0	H	3.25	41.36	54	-12.64

Frequency (MHz)	Receiver Reading (dB $\mu$ V/m)	Detector (PK/QP/AVG)	Turn table Angle (°)	RX Antenna		Corrected Factor (dB)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part 15.247	
				Height (m)	Polar (H/V)			Limit (dB $\mu$ V/m)	Margin (dB)
<b>KL130_802.11n20_Low Channel</b>									
72.72	18.81	QP	115	1.7	H	9.76	28.57	40	-11.43
72.72	10.58	QP	222	1.6	V	9.76	20.34	40	-19.66
1834.25	49.70	PK	216	1.6	H	-12.45	37.25	74	-36.75
1834.25	40.89	AVG	285	1.6	H	-12.45	28.44	54	-25.56
3620.25	48.86	PK	171	1.7	V	-6.93	41.93	74	-32.07
3620.25	39.36	AVG	170	1.1	V	-6.93	32.43	54	-21.57
4824.75	58.71	PK	269	1.9	H	-3.54	55.17	74	-18.83
4824.75	51.19	AVG	135	1.9	H	-3.54	47.65	54	-6.35
6358.00	44.92	PK	108	2.0	V	-0.06	44.86	74	-29.14
6358.00	37.51	AVG	131	1.4	V	-0.06	37.45	54	-16.55
7345.00	46.93	PK	251	1.9	H	3.25	50.18	74	-23.82
7345.00	38.93	AVG	235	1.6	H	3.25	42.18	54	-11.82



Frequency (MHz)	Receiver Reading (dB $\mu$ V/m)	Detector (PK/QP/AVG)	Turn table Angle (°)	RX Antenna		Corrected Factor (dB)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part 15.247	
				Height (m)	Polar (H/V)			Limit (dB $\mu$ V/m)	Margin (dB)
<b>KL130_802.11n20_Middle Channel</b>									
176.27	12.60	QP	279	1.6	H	11.15	23.75	43.5	-19.75
176.27	8.50	QP	263	1.1	V	11.15	19.65	43.5	-23.85
1317.25	52.49	PK	144	1.9	H	-13.95	38.54	74	-35.46
1317.25	42.60	AVG	194	1.1	H	-13.95	28.65	54	-25.35
3878.75	48.32	PK	118	1.4	V	-6.14	42.18	74	-31.82
3878.75	39.53	AVG	133	2.0	V	-6.14	33.39	54	-20.61
4865.75	54.31	PK	260	1.9	H	-3.45	50.86	74	-23.14
4865.75	41.86	AVG	288	1.4	H	-3.45	38.41	54	-15.59
5958.50	46.72	PK	230	2.0	V	-1.23	45.49	74	-28.51
5958.50	37.40	AVG	278	1.9	V	-1.23	36.17	54	-17.83
7803.25	48.00	PK	122	1.7	H	3.97	51.97	74	-22.03
7803.25	38.42	AVG	296	1.7	H	3.97	42.39	54	-11.61

Frequency (MHz)	Receiver Reading (dB $\mu$ V/m)	Detector (PK/QP/AVG)	Turn table Angle (°)	RX Antenna		Corrected Factor (dB)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part 15.247	
				Height (m)	Polar (H/V)			Limit (dB $\mu$ V/m)	Margin (dB)
<b>KL130_802.11n20_High Channel</b>									
95.06	11.71	QP	143	1.2	H	11.82	23.53	43.5	-19.97
95.06	8.59	QP	220	1.5	V	11.82	20.41	43.5	-23.09
1329.00	55.09	PK	114	1.4	H	-14.90	40.19	74	-33.81
1329.00	47.72	AVG	113	2.0	H	-14.90	32.82	54	-21.18
3867.00	49.22	PK	191	1.1	V	-6.03	43.19	74	-30.81
3867.00	39.32	AVG	277	1.8	V	-6.03	33.29	54	-20.71
4924.50	56.52	PK	194	1.8	H	-3.14	53.38	74	-20.62
4924.50	48.79	AVG	128	1.9	H	-3.14	45.65	54	-8.35
5782.25	46.66	PK	180	1.0	V	-1.26	45.40	74	-28.60
5782.25	37.71	AVG	197	1.6	V	-1.26	36.45	54	-17.55
6675.25	47.46	PK	174	1.5	H	1.56	49.02	74	-24.98
6675.25	38.06	AVG	124	1.4	H	1.56	39.62	54	-14.38

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.





## 6.4 Power Spectral Density

### 6.4.1 Standard Applicable

According to 15.247(a)(1)(iii), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### 6.4.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.10.3, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d) Set VBW  $\geq 3 \times \text{RBW}$ .
- e) Detector = power averaging (RMS) or sample detector (when RMS not available).
- f) Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span}/\text{RBW}$ .
- g) Sweep time = auto couple.
- h) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).

# WALTEK




### 6.4.3 Test Result

Test Mode	Test Channel(MHz)	Test Result (dBm/3kHz)	Limit (dBm/3kHz)
802.11b	2412	-11.55	8
	2437	-11.71	8
	2462	-10.92	8
802.11g	2412	-13.45	8
	2437	-12.8	8
	2462	-11.36	8
802.11n-HT20	2412	-12.66	8
	2437	-13.42	8
	2462	-12.32	8


#### Test Plots:

#### 802.11b\_Low Channel






### 802.11b\_Middle Channel




### 802.11b\_High Channel






### 802.11g\_Low Channel




### 802.11g\_Middle Channel






### 802.11g\_High Channel




### 802.11n(HT20)\_Low Channel






### 802.11n(HT20)\_Middle Channel



### 802.11n(HT20)\_High Channel





## 6.5 DTS Bandwidth

### 6.5.1 Standard Applicable

According to 15.247(a)(2). Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### 6.5.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.2 and ANSI C63.10-2013 Subclause 11.8.1, the test method of DTS Bandwidth as below:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



# WALTEK



### 6.5.3 Test Result

Test Mode	Test Channel(MHz)	Test Result (MHz)	Limit kHz
802.11b	2412	9.120	≥500
	2437	9.640	≥500
	2462	8.640	≥500
802.11g	2412	16.400	≥500
	2437	16.400	≥500
	2462	16.360	≥500
802.11n-HT20	2412	17.360	≥500
	2437	17.640	≥500
	2462	17.600	≥500

#### Test Plots:


802.11b\_Low Channel








### 802.11b\_Middle Channel




### 802.11b\_High Channel






### 802.11g\_Low Channel




### 802.11g\_Middle Channel






### 802.11g\_High Channel




### 802.11n(HT20)\_Low Channel





### 802.11n(HT20)\_Middle Channel



### 802.11n(HT20)\_High Channel





## 6.6 RF Output Power

### 6.6.1 Standard Applicable

According to 15.247(b)(3). For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

### 6.6.2 Test Procedure

According to the KDB-558074 D01 v05r02 Subclause 8.3.2.2 and ANSI C63.10-2013 Subclause 11.9.2.2, when this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth

- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- c) Set VBW  $\geq 3 \times$  RBW.
- d) Number of points in sweep  $\geq 2 \times$  span / RBW. (This gives bin-to-bin spacing  $\geq$ RBW/2, so that narrowband signals are not lost between frequency bins.)
- e) Sweep time = auto.
- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- g) If transmit duty cycle < 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle  $\geq$  98 %, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run”.
- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.




### 6.6.3 Test Result

Modulation	Test Channel (MHz)	Power Setting	Reading (dBm)	Output Power (mW)	Limit (mW)
802.11b	2412	1E	18.24	66.68	1000
	2437	1F	18.13	65.01	1000
	2462	20	18.07	64.12	1000
802.11g	2412	21	18.09	64.42	1000
	2437	22	17.65	58.21	1000
	2462	23	18.16	65.46	1000
802.11n-HT20	2412	22	17.49	56.10	1000
	2437	23	17.45	55.59	1000
	2462	24	17.85	60.95	1000


#### Test Plots:

#### 802.11b\_Low Channel






### 802.11b\_Middle Channel




### 802.11b\_High Channel






### 802.11g\_Low Channel




### 802.11g\_Middle Channel








### 802.11g\_High Channel




### 802.11n(HT20)\_Low Channel






802.11n(HT20)\_Middle Channel



802.11n(HT20)\_High Channel





## 6.7 Band Edge Measurement

### 6.7.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

### 6.7.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.11, the Emissions in nonrestricted frequency bands test method as follows:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW  $\geq [3 \times \text{RBW}]$ .
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

According to the KDB 558074 D01 v05r02 Subclause 8.5 and ANSI C63.10-2013 Subclause 11.12, the Emissions in restricted frequency bands test method as follows:

#### A. Radiated emission measurements:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge,

as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz

for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge. Enable the marker-delta function, and then use the marker-to-peak function to move the marker to the peak of the in-band emission.

Waltek Testing Group (Foshan) Co., Ltd.

<http://www.waltek.com.cn>



Those emissions must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated band edge measurements.

#### B. Antenna-port conducted measurements

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 9/
- b) VBW  $\geq [3 \times \text{RBW}]$ .
- c) Detector = peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

**Table 9—RBW as a function of frequency**

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1000 MHz	100 kHz to 120 kHz
>1000 MHz	1 MHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1.

# WALTEK




### 6.7.3 Test Result

Test Mode	Channel (MHz)	Ref Level (dBm)	Result (dBm)	Limit (dBm)	Verdict
802.11b	2412	6.81	-38.58	<=-23.19	Pass
	2462	8.05	-48.61	<=-21.95	Pass
802.11g	2412	3.37	-35.08	<=-26.63	Pass
	2462	4.43	-35.52	<=-25.57	Pass
802.11n-HT20	2412	1.89	-29.64	<=-28.11	Pass
	2462	2.64	-40.25	<=-27.37	Pass


#### Test Plots:

#### 802.11b\_Low Channel






### 802.11b\_High Channel




### 802.11g\_Low Channel






### 802.11g\_High Channel




### 802.11n(HT20)\_Low Channel





802.11n(HT20)\_High Channel








## 6.8 Conducted Emissions

### 6.8.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

### 6.8.2 Basic Test Setup Block Diagram



### 6.8.3 10.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:


Start Frequency.....	150 kHz
Stop Frequency.....	30 MHz
Sweep Speed.....	Auto
IF Bandwidth.....	10 kHz
Quasi-Peak Adapter Bandwidth.....	9 kHz
Quasi-Peak Adapter Mode.....	Normal



### 6.8.4 Test Result

#### Model KL110


Test Mode      Communication mode(AC 120V/60Hz)      Polarity      Line



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1740	50.92	9.64	60.56	64.77	-4.21	QP	
2	*	0.1740	41.73	9.64	51.37	54.77	-3.40	AVG	
3		0.2060	48.94	9.64	58.58	63.37	-4.79	QP	
4		0.2060	37.93	9.64	47.57	53.37	-5.80	AVG	
5		0.2420	46.59	9.64	56.23	62.03	-5.80	QP	
6		0.2420	34.52	9.64	44.16	52.03	-7.87	AVG	
7		0.3780	40.53	9.65	50.18	58.32	-8.14	QP	
8		0.3780	26.72	9.65	36.37	48.32	-11.95	AVG	
9		0.6419	36.62	9.65	46.27	56.00	-9.73	QP	
10		0.6419	27.43	9.65	37.08	46.00	-8.92	AVG	
11		0.8460	33.69	9.67	43.36	56.00	-12.64	QP	
12		0.8460	23.64	9.67	33.31	46.00	-12.69	AVG	



Test Mode Communication mode(AC 120V/60Hz) Polarity Neutral



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1731	51.05	9.61	60.66	64.81	-4.15	QP	
2	*	0.1731	41.94	9.61	51.55	54.81	-3.26	AVG	
3		0.2072	48.07	9.61	57.68	63.32	-5.64	QP	
4		0.2072	37.93	9.61	47.54	53.32	-5.78	AVG	
5		0.2404	46.56	9.61	56.17	62.08	-5.91	QP	
6		0.2404	34.73	9.61	44.34	52.08	-7.74	AVG	
7		0.4588	38.39	9.63	48.02	56.71	-8.69	QP	
8		0.4588	24.10	9.63	33.73	46.71	-12.98	AVG	
9		0.5940	33.20	9.63	42.83	56.00	-13.17	QP	
10		0.5940	23.59	9.63	33.22	46.00	-12.78	AVG	
11		0.8220	34.13	9.64	43.77	56.00	-12.23	QP	
12		0.8220	24.56	9.64	34.20	46.00	-11.80	AVG	




Model KL130

Test Mode

Communication mode(AC 120V/60Hz)

Polarity


Line



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1500	41.76	9.64	51.40	66.00	-14.60	QP	
2		0.1500	21.04	9.64	30.68	56.00	-25.32	AVG	
3		0.1825	39.74	9.64	49.38	64.37	-14.99	QP	
4		0.1825	27.25	9.64	36.89	54.37	-17.48	AVG	
5		0.2460	28.58	9.64	38.22	61.89	-23.67	QP	
6		0.2460	15.37	9.64	25.01	51.89	-26.88	AVG	
7		0.8100	8.94	9.67	18.61	56.00	-37.39	QP	
8		0.8100	0.74	9.67	10.41	46.00	-35.59	AVG	
9		2.1580	6.96	9.72	16.68	56.00	-39.32	QP	
10		2.1580	-0.90	9.72	8.82	46.00	-37.18	AVG	
11		16.5540	5.31	10.06	15.37	60.00	-44.63	QP	
12		16.5540	-1.22	10.06	8.84	50.00	-41.16	AVG	



Test Mode Communication mode(AC 120V/60Hz) Polarity Neutral



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1500	41.81	9.61	51.42	66.00	-14.58	QP	
2		0.1500	21.09	9.61	30.70	56.00	-25.30	AVG	
3		0.1835	39.74	9.61	49.35	64.33	-14.98	QP	
4		0.1835	27.38	9.61	36.99	54.33	-17.34	AVG	
5		0.2460	28.53	9.61	38.14	61.89	-23.75	QP	
6		0.2460	14.25	9.61	23.86	51.89	-28.03	AVG	
7		1.3099	0.25	9.64	9.89	56.00	-46.11	QP	
8		1.3099	-4.62	9.64	5.02	46.00	-40.98	AVG	
9		4.6220	11.29	9.73	21.02	56.00	-34.98	QP	
10		4.6220	-3.25	9.73	6.48	46.00	-39.52	AVG	
11		16.8620	8.61	10.14	18.75	60.00	-41.25	QP	
12		16.8620	0.84	10.14	10.98	50.00	-39.02	AVG	



## 7 Photographs Test Setup

### 7.1 Photographs - Radiated Emission Test Setup

30MHz-1GHz



Above 1GHz





## 7.2 Photographs - Conducted Emission Test Setup





## 8 Photographs - Constructional Details

### 8.1 EUT - External View

Model KL110











**Model KL130**














## 8.2 EUT - Internal View

Model KL110











Model KL130











====End of Report====



# WALTEK