

FCC RF EXPOSURE REPORT

FCC ID: TE7KP200V2

Project No. : 1908C106

Equipment: Smart Wi-Fi Outlet

Brand Name : tp-link
Test Model : KP200
Series Model : N/A

Applicant: TP-Link Technologies Co., Ltd.

Address : Building 24(floors1,3,4,5) and 28(floors1-4) Central Science and

Technology Park, Shennan Rd, Nanshan, Shenzhen, China

Manufacturer: TP-Link Technologies Co., Ltd.

Address: Building 24(floors1,3,4,5) and 28(floors1-4) Central Science and

Technology Park, Shennan Rd, Nanshan, Shenzhen, China

Date of Receipt : Aug. 14, 2019

Date of Test : Aug. 15, 2019 ~ Sep. 02, 2019

Issued Date : Oct. 14, 2019

Report Version: R00

Test Sample : Engineering Sample No.: DG19081430

Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part

2.1091

FCC Title 47 Part 2.1091, OET Bulletin 65 Supplement C

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Prepared by : Rose Liu

Rose.Liu

Approved by: Ethan Ma

IAC-MRA ACCREDITED

Certificate #5123.02

Add: No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China.

Tel: +86-769-8318-3000 Web: www.newbtl.com



REPORT ISSUED HISTORY

Report Version	Description	Issued Date	
R00	Original Issue	Oct. 14, 2019	





1. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator R = distance to the center of radiation of the antenna

Table for Filed Antenna

Ant.	Brand	P/N	Antenna Type	Connector	Gain (dBi)	
1 TP-LINK°		3101502179	Internal	I-PEX	2.81	



2. TEST RESULTS

Tune up tolerance(dBm)			
2.4G			
± 0.5 dB			

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (mW)	Power Density (S) (mW/cm²)	Limit of Power Density (S) (mW/cm²)	Test Result
2.81	1.9099	27.23	528.4453	0.20089	1	Complies

Note: The calculated distance is 20 cm.

Output power including tune up tolerance.

End of Test Report