

## RF Exposure Report

**Report No.:** SA150112C13A

**FCC ID:** TE7NC250

**IC:** 8853A-NC250

**Test Model:** NC250

**Received Date:** Jan. 12, 2015

**Test Date:** Jan. 15 ~ Jul. 29, 2015

**Issued Date:** Jul. 31, 2015

**Applicant:** TP-LINK TECHNOLOGIES CO., LTD.

**Address:** Building 24 (floors 1,3,4,5) and 28 (floors1-4) Central Science and Technology Park, Shennan Rd, Nanshan, Shenzhen, China

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan, R.O.C.

**Test Location:** No.19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



## Table of Contents

<b>Release Control Record</b> .....	<b>3</b>
<b>1 Certificate of Conformity</b> .....	<b>4</b>
<b>2 RF Exposure</b> .....	<b>5</b>
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula .....	6
2.3 Classification .....	6
<b>3 Calculation Result of Maximum Conducted Power</b> .....	<b>7</b>



A D T

**Release Control Record**

Issue No.	Description	Date Issued
SA150112C13A	Original release	Jul. 31, 2015



A D T

## 1 Certificate of Conformity

**Product:** HD Day/Night Cloud Camera,300Mbps Wi-Fi

**Brand:** TP-LINK

**Test Model:** NC250

**Sample Status:** Prototype

**Applicant:** TP-LINK TECHNOLOGIES CO., LTD.

**Test Date:** Jan. 15 ~ Jul. 29, 2015

**Standards:** FCC Part 2 (Section 2.1091)

KDB 447498 D03

IEEE C95.1

RSS-102 Issue 5 (2015-03)

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :** Sunt Lee, **Date:** Jul. 31, 2015  
Sunt Lee / Specialist

**Approved by :** Ken Liu, **Date:** Jul. 31, 2015  
Ken Liu / Senior Manager

## 2 RF Exposure

### 2.1 Limits for Maximum Permissible Exposure (MPE)

#### FCC:

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

#### IC:

Per RSS-102 issue 5, section 2.5.2 as reproduced below:

#### 2.5.2 Exemption from Routine Evaluation Limits – RF Exposure Evaluation

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $22.48/f^{0.5}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

Frequency Range (MHz)	Electric Field Strength (V/m rms)	Magnetic Field Strength (A/m rms)	Power Density (W/m <sup>2</sup> )	Reference Period (minutes)
Limits For General Population / Uncontrolled Exposure				
0.003-10 <sup>21</sup>	83	90	-	Instantaneous*
0.1-10	-	0.73/ $f$	-	6**
1.1-10	87/ $f^{0.5}$	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ $f^{0.25}$	0.1540/ $f^{0.25}$	8.944/ $f^{0.5}$	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 $f^{0.3417}$	0.008335 $f^{0.3417}$	0.02619 $f^{0.6834}$	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ $f^{1.2}$
150000-300000	0.158 $f^{0.5}$	4.21 x 10 <sup>-4</sup> $f^{0.5}$	6.67 x 10 <sup>-5</sup> $f$	616000/ $f^{1.2}$

Note:  $f$  is frequency in MHz.

\*Based on nerve stimulation (NS).

\*\* Based on specific absorption rate (SAR).

## 2.2 MPE Calculation Formula

### FCC:

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm

### IC:

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

$P_d$  = power density in W/m<sup>2</sup>

$P_{out}$  = output power to antenna in W

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in m

## 2.3 Classification

### FCC:

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as Mobile Device.

### IC:

The antenna of this product, under normal use condition, is at least 0.2m away from the body of the user. So, this device is classified as Mobile Device.

### 3 Calculation Result of Maximum Conducted Power

#### FCC:

Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
2412-2462	23.47	5.87	20	0.171	1

Note: 2412-2462MHz Directional gain = 2.86dBi + 10log(2) = 5.87dBi

#### IC:

Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (m)	Power Density (W/m <sup>2</sup> )	Limit (W/m <sup>2</sup> )
2412-2462	23.47	5.87	0.2	1.709	5.366

Note: 2412-2462MHz Directional gain = 2.86dBi + 10log(2) = 5.87dBi

--- END ---