


Site: WZ-AC2	Time: 2020/08/31 - 17:08
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT20 at Channel 5240MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5241.760	102.516	102.521	N/A	N/A	-0.005	AV
2			5350.000	43.359	43.278	-10.641	54.000	0.081	AV

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 17:10
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT20 at Channel 5240MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5238.560	108.113	108.193	N/A	N/A	-0.080	PK
2			5350.000	55.365	55.284	-18.635	74.000	0.081	PK
3			5351.520	56.773	56.682	-17.227	74.000	0.091	PK

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 17:09
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT20 at Channel 5240MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5241.040	98.205	98.227	N/A	N/A	-0.022	AV
2			5350.000	43.163	43.082	-10.837	54.000	0.081	AV

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 17:18
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT20 at Channel 5320MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5318.280	111.414	111.482	N/A	N/A	-0.068	PK
2			5350.000	70.000	69.919	-4.000	74.000	0.081	PK
3			5350.760	73.230	73.144	-0.770	74.000	0.086	PK

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 17:25
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT20 at Channel 5320MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5317.800	101.304	101.362	N/A	N/A	-0.058	AV
2			5350.000	53.332	53.251	-0.668	54.000	0.081	AV
3			5350.280	53.537	53.454	-0.463	54.000	0.083	AV

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 17:29
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT20 at Channel 5320MHz	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5317.400	107.115	107.162	N/A	N/A	-0.047	PK
2			5350.000	64.614	64.533	-9.386	74.000	0.081	PK
3			5350.520	69.156	69.072	-4.844	74.000	0.085	PK

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 17:28
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT20 at Channel 5320MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5317.320	96.927	96.972	N/A	N/A	-0.044	AV
2			5350.000	49.829	49.748	-4.171	54.000	0.081	AV

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 17:35
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT20 at Channel 5500MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5460.000	57.225	56.946	-16.775	74.000	0.279	PK
2			5469.690	66.497	66.239	-1.703	68.200	0.258	PK
3			5470.000	64.197	63.940	-4.003	68.200	0.257	PK
4		*	5498.535	110.020	109.762	N/A	N/A	0.258	PK

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 17:38
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT20 at Channel 5500MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5460.000	45.431	45.152	-8.569	54.000	0.279	AV
2			5470.000	48.122	47.865	-5.878	54.000	0.257	AV
3		*	5498.625	99.847	99.590	N/A	N/A	0.257	AV

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 17:40
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT20 at Channel 5500MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5460.000	55.424	55.145	-18.576	74.000	0.279	PK
2			5468.115	62.832	62.571	-5.368	68.200	0.261	PK
3			5470.000	59.472	59.215	-8.728	68.200	0.257	PK
4		*	5498.805	107.028	106.771	N/A	N/A	0.257	PK

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 17:39
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT20 at Channel 5500MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5460.000	44.182	43.903	-9.818	54.000	0.279	AV
2			5470.000	45.984	45.727	-8.016	54.000	0.257	AV
3		*	5498.715	96.795	96.538	N/A	N/A	0.258	AV

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 17:55
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT20 at Channel 5700MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5698.000	108.591	107.385	N/A	N/A	1.205	PK
2			5725.000	66.601	65.168	-1.599	68.200	1.433	PK
3			5725.592	66.835	65.409	-1.365	68.200	1.426	PK

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 17:58
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT20 at Channel 5700MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5698.553	105.663	104.441	N/A	N/A	1.221	PK
2			5725.000	59.738	58.305	-8.462	68.200	1.433	PK
3			5725.853	62.799	61.376	-5.401	68.200	1.423	PK

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 18:24
Limit: FCC_Part15.407_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT20 at Channel 5745MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5606.683	59.663	58.722	-8.537	68.200	0.941	PK
2			5650.000	57.239	55.866	-10.961	68.200	1.373	PK
3			5699.083	71.840	70.603	-32.684	104.524	1.237	PK
4			5700.000	70.235	68.971	-34.965	105.200	1.264	PK
5			5719.790	84.360	82.898	-26.381	110.741	1.462	PK
6			5720.000	83.588	82.126	-27.212	110.800	1.462	PK
7			5724.822	92.028	90.593	-29.766	121.794	1.435	PK
8			5725.000	90.377	88.944	-31.823	122.200	1.433	PK
9		*	5743.303	113.990	112.605	N/A	N/A	1.386	PK

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 18:34
Limit: FCC_Part15.407_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT20 at Channel 5745MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5648.098	58.703	57.370	-9.497	68.200	1.334	PK
2			5650.000	57.059	55.686	-11.141	68.200	1.373	PK
3			5692.812	67.338	66.283	-32.563	99.901	1.055	PK
4			5700.000	67.158	65.894	-38.042	105.200	1.264	PK
5			5716.325	81.023	79.554	-28.749	109.772	1.469	PK
6			5720.000	79.191	77.729	-31.609	110.800	1.462	PK
7			5723.750	89.998	88.550	-29.353	119.351	1.448	PK
8			5725.000	85.004	83.571	-37.196	122.200	1.433	PK
9			5746.107	110.435	108.984	N/A	N/A	1.451	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 18:39
Limit: FCC_Part15.407_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT20 at Channel 5825MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5824.598	113.427	111.845	N/A	N/A	1.581	PK
2			5850.000	84.990	83.197	-37.210	122.200	1.792	PK
3			5850.240	85.674	83.881	-35.978	121.653	1.793	PK
4			5855.000	80.965	79.163	-29.835	110.800	1.802	PK
5			5856.480	82.712	80.907	-27.673	110.385	1.805	PK
6			5875.000	69.242	67.371	-35.958	105.200	1.872	PK
7			5876.175	71.231	69.356	-33.096	104.327	1.875	PK
8			5925.000	58.624	56.555	-9.576	68.200	2.069	PK
9		*	5928.045	59.599	57.528	-8.601	68.200	2.071	PK

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 18:43
Limit: FCC_Part15.407_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT20 at Channel 5825MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5826.158	111.458	109.890	N/A	N/A	1.568	PK
2			5850.000	80.543	78.750	-41.657	122.200	1.792	PK
3			5850.922	82.895	81.101	-37.202	120.097	1.795	PK
4			5855.000	77.649	75.847	-33.151	110.800	1.802	PK
5			5858.333	80.615	78.807	-29.250	109.865	1.808	PK
6			5875.000	62.474	60.603	-42.726	105.200	1.872	PK
7			5876.663	69.511	67.635	-34.453	103.964	1.876	PK
8			5925.000	57.876	55.807	-10.324	68.200	2.069	PK
9		*	5963.145	59.790	57.854	-8.410	68.200	1.936	PK

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 19:10
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT40 at Channel 5190MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5144.000	68.063	67.715	-5.937	74.000	0.348	PK
2			5150.000	64.001	63.599	-9.999	74.000	0.402	PK
3		*	5186.450	105.503	105.195	N/A	N/A	0.308	PK

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 19:15
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT40 at Channel 5190MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5150.000	49.003	48.601	-4.997	54.000	0.402	AV
2		*	5191.450	95.192	94.904	N/A	N/A	0.289	AV

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 19:18
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT40 at Channel 5190MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5144.500	63.434	63.081	-10.566	74.000	0.353	PK
2			5150.000	58.632	58.230	-15.368	74.000	0.402	PK
3		*	5192.250	101.117	100.832	N/A	N/A	0.285	PK

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 19:19
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT40 at Channel 5190MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5149.600	46.807	46.409	-7.193	54.000	0.398	AV
2			5150.000	46.463	46.061	-7.537	54.000	0.402	AV
3		*	5187.250	90.111	89.806	N/A	N/A	0.305	AV

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 19:23
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT40 at Channel 5230MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5228.450	111.697	111.916	N/A	N/A	-0.219	PK
2			5350.000	59.607	59.526	-14.393	74.000	0.081	PK
3			5355.350	62.752	62.667	-11.248	74.000	0.085	PK

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 19:37
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT40 at Channel 5230MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5228.810	101.066	101.288	N/A	N/A	-0.222	AV
2			5350.000	47.249	47.168	-6.751	54.000	0.081	AV

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 19:42
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT40 at Channel 5230MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5227.370	105.954	106.165	N/A	N/A	-0.211	PK
2			5350.000	58.043	57.962	-15.957	74.000	0.081	PK
3			5352.290	59.676	59.582	-14.324	74.000	0.094	PK

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 19:45
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT40 at Channel 5230MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5227.370	96.499	96.710	N/A	N/A	-0.211	AV
2			5350.000	46.092	46.011	-7.908	54.000	0.081	AV

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 20:06
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT40 at Channel 5310MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5308.650	106.673	106.489	N/A	N/A	0.184	PK
2			5350.000	70.197	70.116	-3.803	74.000	0.081	PK
3			5351.950	70.343	70.249	-3.657	74.000	0.095	PK

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 20:08
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT40 at Channel 5310MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5311.450	96.070	95.956	N/A	N/A	0.114	AV
2			5350.000	49.082	49.001	-4.918	54.000	0.081	AV

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 20:10
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT40 at Channel 5310MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5308.550	101.774	101.588	N/A	N/A	0.185	PK
2			5350.000	65.193	65.112	-8.807	74.000	0.081	PK
3			5352.250	65.394	65.300	-8.606	74.000	0.094	PK

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 20:12
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT40 at Channel 5310MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5308.750	91.783	91.601	N/A	N/A	0.181	AV
2			5350.000	46.318	46.237	-7.682	54.000	0.081	AV
3			5350.600	46.702	46.617	-7.298	54.000	0.085	AV

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 20:24
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT40 at Channel 5510MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5454.650	61.572	61.281	-12.428	74.000	0.291	PK
2			5460.000	60.107	59.828	-13.893	74.000	0.279	PK
3			5464.350	65.288	65.019	-2.912	68.200	0.269	PK
4			5470.000	62.967	62.710	-5.233	68.200	0.257	PK
5		*	5512.200	106.117	105.646	N/A	N/A	0.471	PK

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 20:45
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT40 at Channel 5510MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5460.000	45.344	45.065	-8.656	54.000	0.279	AV
2		*	5508.450	95.774	95.420	N/A	N/A	0.354	AV

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 20:50
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT40 at Channel 5510MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5457.600	58.601	58.317	-15.399	74.000	0.284	PK
2			5460.000	55.666	55.387	-18.334	74.000	0.279	PK
3			5468.800	61.453	61.193	-6.747	68.200	0.260	PK
4			5470.000	58.321	58.064	-9.879	68.200	0.257	PK
5		*	5508.150	101.103	100.758	N/A	N/A	0.345	PK

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 20:52
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT40 at Channel 5510MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5460.000	44.164	43.885	-9.836	54.000	0.279	AV
2		*	5508.300	91.417	91.068	N/A	N/A	0.349	AV

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 21:30
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT40 at Channel 5670MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5668.400	108.774	107.461	N/A	N/A	1.312	PK
2			5725.000	64.424	62.991	-3.776	68.200	1.433	PK
3			5725.100	67.761	66.329	-0.439	68.200	1.432	PK

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 21:32
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT40 at Channel 5670MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5665.850	104.461	103.125	N/A	N/A	1.335	PK
2			5725.000	62.728	61.295	-5.472	68.200	1.433	PK

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 21:59
Limit: FCC_Part15.407_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT40 at Channel 5755MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5649.087	65.193	63.839	-3.007	68.200	1.354	PK
2			5650.000	61.186	59.813	-7.014	68.200	1.373	PK
3			5700.000	77.874	76.610	-27.326	105.200	1.264	PK
4			5720.000	89.057	87.595	-21.743	110.800	1.462	PK
5			5725.000	91.164	89.731	-31.036	122.200	1.433	PK
6			5753.562	111.634	110.008	N/A	N/A	1.626	PK

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 22:01
Limit: FCC_Part15.407_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT40 at Channel 5755MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5645.850	61.341	60.055	-6.859	68.200	1.286	PK
2			5650.000	58.294	56.921	-9.906	68.200	1.373	PK
3			5700.000	74.088	72.824	-31.112	105.200	1.264	PK
4			5720.000	83.858	82.396	-26.942	110.800	1.462	PK
5			5725.000	85.867	84.434	-36.333	122.200	1.433	PK
6			5748.400	107.657	106.152	N/A	N/A	1.504	PK

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 22:10
Limit: FCC_Part15.407_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT40 at Channel 5795MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5797.388	111.331	109.705	N/A	N/A	1.626	PK
2			5850.000	82.964	81.171	-39.236	122.200	1.792	PK
3			5855.000	80.552	78.750	-30.248	110.800	1.802	PK
4			5875.000	73.817	71.946	-31.383	105.200	1.872	PK
5			5925.000	64.647	62.578	-3.553	68.200	2.069	PK
6		*	5928.000	64.706	62.635	-3.494	68.200	2.071	PK

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 22:16
Limit: FCC_Part15.407_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT40 at Channel 5795MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5792.437	108.902	107.264	N/A	N/A	1.639	PK
2			5850.000	78.700	76.907	-43.500	122.200	1.792	PK
3			5855.000	77.058	75.256	-33.742	110.800	1.802	PK
4			5875.000	71.455	69.584	-33.745	105.200	1.872	PK
5			5925.000	60.806	58.737	-7.394	68.200	2.069	PK
6		*	5927.212	62.258	60.188	-5.942	68.200	2.070	PK

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 22:41
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT80 at Channel 5210MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5147.425	68.548	68.167	-5.452	74.000	0.381	PK
2			5150.000	64.155	63.753	-9.845	74.000	0.402	PK
3		*	5197.375	101.674	101.409	N/A	N/A	0.265	PK

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 22:45
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT80 at Channel 5210MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5150.000	51.490	51.088	-2.510	54.000	0.402	AV
2		*	5212.075	91.348	91.339	N/A	N/A	0.009	AV

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 22:46
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT80 at Channel 5210MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5137.750	63.611	63.322	-10.389	74.000	0.289	PK
2			5150.000	58.593	58.191	-15.407	74.000	0.402	PK
3		*	5206.750	96.544	96.428	N/A	N/A	0.115	PK

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 22:52
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT80 at Channel 5210MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5150.000	48.074	47.672	-5.926	54.000	0.402	AV
2		*	5208.400	86.848	86.765	N/A	N/A	0.083	AV

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 23:06
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT80 at Channel 5290MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5286.970	103.795	103.563	N/A	N/A	0.232	PK
2			5350.000	62.162	62.081	-11.838	74.000	0.081	PK
3			5361.990	68.949	68.884	-5.051	74.000	0.065	PK

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 23:08
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT80 at Channel 5290MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5288.400	92.589	92.335	N/A	N/A	0.254	AV
2			5350.000	51.467	51.386	-2.533	54.000	0.081	AV

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 23:10
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT80 at Channel 5290MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5295.110	98.387	98.070	N/A	N/A	0.318	PK
2			5350.000	62.679	62.598	-11.321	74.000	0.081	PK
3			5354.400	63.536	63.448	-10.464	74.000	0.088	PK

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 23:11
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT80 at Channel 5290MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5287.520	87.623	87.382	N/A	N/A	0.241	AV
2			5350.000	47.689	47.608	-6.311	54.000	0.081	AV

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 23:28
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT80 at Channel 5530MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5457.065	68.615	68.330	-5.385	74.000	0.285	PK
2			5460.000	65.209	64.930	-8.791	74.000	0.279	PK
3			5464.655	67.750	67.481	-0.450	68.200	0.269	PK
4			5470.000	64.455	64.198	-3.745	68.200	0.257	PK
5		*	5527.330	103.553	102.770	N/A	N/A	0.783	PK

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 23:33
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT80 at Channel 5530MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5460.000	50.637	50.358	-3.363	54.000	0.279	AV
2		*	5528.595	92.729	91.944	N/A	N/A	0.786	AV

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 23:35
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT80 at Channel 5530MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5455.915	63.195	62.907	-10.805	74.000	0.288	PK
2			5460.000	58.865	58.586	-15.135	74.000	0.279	PK
3			5465.460	64.866	64.599	-3.334	68.200	0.267	PK
4			5470.000	60.705	60.448	-7.495	68.200	0.257	PK
5		*	5523.075	98.507	97.730	N/A	N/A	0.777	PK

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 23:37
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT80 at Channel 5530MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5460.000	46.747	46.468	-7.253	54.000	0.279	AV
2		*	5525.950	88.552	87.771	N/A	N/A	0.781	AV

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 23:49
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT80 at Channel 5610MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5612.155	105.832	104.796	N/A	N/A	1.036	PK
2			5725.000	66.077	64.644	-2.123	68.200	1.433	PK
3			5725.015	66.557	65.124	-1.643	68.200	1.433	PK

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/08/31 - 23:52
Limit: FCC_Part15.209_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT80 at Channel 5610MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5607.025	102.068	101.122	N/A	N/A	0.945	PK
2			5725.000	59.888	58.455	-8.312	68.200	1.433	PK
3			5728.530	63.468	62.057	-4.732	68.200	1.410	PK

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/09/01 - 00:09
Limit: FCC_Part15.407_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT80 at Channel 5775MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5648.600	67.878	66.534	-0.322	68.200	1.344	PK
2			5650.000	64.480	63.107	-3.720	68.200	1.373	PK
3			5700.000	79.872	78.608	-25.328	105.200	1.264	PK
4			5720.000	84.001	82.539	-26.799	110.800	1.462	PK
5			5725.000	83.777	82.344	-38.423	122.200	1.433	PK
6			5771.200	105.884	104.104	N/A	N/A	1.780	PK
7			5850.000	78.701	76.908	-43.499	122.200	1.792	PK
8			5855.000	78.288	76.486	-32.512	110.800	1.802	PK
9			5875.000	71.332	69.461	-33.868	105.200	1.872	PK
10			5925.000	62.653	60.584	-5.547	68.200	2.069	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: WZ-AC2	Time: 2020/09/01 - 00:12
Limit: FCC_Part15.407_RE(3m)	Engineer: Hyde Yu
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Note: Transmit by 802.11ac-VHT80 at Channel 5775MHz	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5650.000	63.438	62.065	-4.762	68.200	1.373	PK
2			5700.000	76.207	74.943	-28.993	105.200	1.264	PK
3			5720.000	79.519	78.057	-31.281	110.800	1.462	PK
4			5725.000	79.070	77.637	-43.130	122.200	1.433	PK
5			5768.200	102.562	100.782	N/A	N/A	1.780	PK
6			5850.000	73.703	71.910	-48.497	122.200	1.792	PK
7			5855.000	72.345	70.543	-38.455	110.800	1.802	PK
8			5875.000	67.989	66.118	-37.211	105.200	1.872	PK
9			5925.000	58.008	55.939	-10.192	68.200	2.069	PK
10			5931.800	60.889	58.829	-7.311	68.200	2.060	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

6.10. AC Conducted Emissions Measurement


6.10.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dB μ V)	Average (dB μ V)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.


Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

6.10.2. Test Setup



6.10.3. Test Result

Site: SR2	Time: 2020/11/06 - 10:05
Limit: FCC_Part15.207_CE_AC Power	Engineer: Dillon Diao
Probe: ENV216_101683_Filter On	Polarity: Line
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11a at Channel 5180MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV)	Factor (dB)	Type
1			0.230	34.573	24.928	-27.877	62.450	9.645	QP
2			0.230	20.376	10.731	-32.074	52.450	9.645	AV
3			0.354	36.790	27.121	-22.078	58.868	9.670	QP
4			0.354	21.723	12.054	-27.145	48.868	9.670	AV
5			0.662	42.829	33.110	-13.171	56.000	9.719	QP
6		*	0.662	33.758	24.039	-12.242	46.000	9.719	AV
7			1.306	32.227	22.473	-23.773	56.000	9.754	QP
8			1.306	19.993	10.239	-26.007	46.000	9.754	AV
9			2.482	29.118	19.340	-26.882	56.000	9.777	QP
10			2.482	18.484	8.706	-27.516	46.000	9.777	AV
11			6.734	25.543	15.600	-34.457	60.000	9.943	QP
12			6.734	15.545	5.602	-34.455	50.000	9.943	AV

Note: Measure Level (dBμV) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB)

Site: SR2	Time: 2020/11/06 - 10:08
Limit: FCC_Part15.207_CE_AC Power	Engineer: Dillon Diao
Probe: ENV216_101683_Filter On	Polarity: Neutral
EUT: AC750 Wi-Fi Range Extender	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11a at Channel 5180MHz	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV)	Factor (dB)	Type
1			0.158	39.648	30.041	-25.920	65.568	9.607	QP
2			0.158	24.849	15.242	-30.719	55.568	9.607	AV
3			0.482	37.488	27.804	-18.817	56.305	9.683	QP
4			0.482	26.826	17.143	-19.478	46.305	9.683	AV
5		*	0.658	45.752	36.043	-10.248	56.000	9.709	QP
6			0.658	35.239	25.530	-10.761	46.000	9.709	AV
7			1.326	35.792	26.045	-20.208	56.000	9.747	QP
8			1.326	21.895	12.148	-24.105	46.000	9.747	AV
9			2.466	32.328	22.553	-23.672	56.000	9.776	QP
10			2.466	20.597	10.822	-25.403	46.000	9.776	AV
11			12.858	28.179	18.051	-31.821	60.000	10.128	QP
12			12.858	15.927	5.799	-34.073	50.000	10.128	AV

Note: Measure Level (dBμV) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB)

7. CONCLUSION

The data collected relate only the item(s) tested and show that the device is in compliance with Part 15E of the FCC rules.

————— The End —————

Appendix A - Test Setup Photograph

Refer to "2008RSU036-UT" file.

Appendix B - EUT Photograph

Refer to "2008RSU036-UE" file.