



RF Exposure Evaluation Report

APPLICANT : TP-Link Technologies Co., Ltd.
EQUIPMENT : AC1200 Wi-Fi Range Extender with Smart Plug
BRAND NAME : TP-Link
MODEL NAME : RE370K
FCC ID : TE7RE370K
STANDARD : 47 CFR Part 2.1091

We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091, and pass the limit. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.

Prepared by: Mark Qu / Manager

Approved by: Jones Tsai / Manager

SPORTON INTERNATIONAL (SHENZHEN) INC.

**1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town,
Nanshan District, Shenzhen, Guangdong, P. R. China**



Table of Contents

1. ADMINISTRATION DATA	4
1.1. Testing Laboratory	4
2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	5
3. MAXIMUM RF AVERAGE OUTPUT POWER AMONG PRODUCTION UNITS	6
4. RF EXPOSURE LIMIT INTRODUCTION	7
5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	8
5.1. Standalone Power Density Calculation	8



Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA692804	Rev. 01	Initial issue of report	Nov. 22, 2016



1. Administration Data

1.1. Testing Laboratory

Testing Site	
Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.
Test Site Location	1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595

Applicant	
Company Name	TP-Link Technologies Co., Ltd.
Address	Building 24 (floors 1,3,4,5) and 28 (floors1-4) Central Science and Technology Park, Shennan Rd, Nanshan, Shenzhen, China

Manufacturer	
Company Name	TP-Link Technologies Co., Ltd.
Address	Building 24 (floors 1,3,4,5) and 28 (floors1-4) Central Science and Technology Park, Shennan Rd, Nanshan, Shenzhen, China

2. Description of Equipment Under Test (EUT)

Product Feature & Specification										
EUT Type	AC1200 Wi-Fi Range Extender with Smart Plug									
Brand Name	TP-Link									
Model Name	RE370K									
FCC ID	TE7RE370K									
Wireless Technology and Frequency Range	WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5700 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz									
Mode	<ul style="list-style-type: none"> · WLAN 2.4GHz 802.11b/g/n HT20/HT40 · WLAN 5GHz 802.11a/n HT20/HT40 · WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 									
Antenna Type	Dipole Antenna									
Antenna Function for Transmitter	<table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th></th> <th>Chain Port 1</th> <th>Chain Port 2</th> </tr> </thead> <tbody> <tr> <td>802.11 a/b/g/n/ac SISO</td> <td>√</td> <td>√</td> </tr> <tr> <td>802.11 a/b/g/n/ac MIMO</td> <td>√</td> <td>√</td> </tr> </tbody> </table>		Chain Port 1	Chain Port 2	802.11 a/b/g/n/ac SISO	√	√	802.11 a/b/g/n/ac MIMO	√	√
	Chain Port 1	Chain Port 2								
802.11 a/b/g/n/ac SISO	√	√								
802.11 a/b/g/n/ac MIMO	√	√								
EUT Stage	Production Unit									
Remark: <ol style="list-style-type: none"> 1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description. 2. WLAN operation in 5600 MHz ~ 5650 MHz is notched. 3. Since each SISO antenna power is less than per chain MIMO antenna power, we only evaluate MPE in MIMO antenna mode for WLAN 2.4/5GHz. 										



3. Maximum RF average output power among production units

<WLAN 2.4GHz Antenna 1+2>

	Mode	Maximum Average Power (dBm)
2.4GHz	802.11b	23.5
	802.11g	22.5
	802.11n-HT20	22.5
	802.11n-HT40	20.5

<WLAN 5GHz Antenna 1+2>

	Mode	Maximum Average Power (dBm)
5.2GHz	802.11a	28.0
	802.11n-HT20	28.0
	802.11n-HT40	26.5
	802.11ac-VHT20	28.0
	802.11ac-VHT40	26.0
	802.11ac-VHT80	19.5
5.3GHz	802.11a	22.0
	802.11n-HT20	22.5
	802.11n-HT40	24.0
	802.11ac-VHT20	22.0
	802.11ac-VHT40	24.0
	802.11ac-VHT80	19.5
5.5GHz	802.11a	22.0
	802.11n-HT20	22.0
	802.11n-HT40	24.0
	802.11ac-VHT20	22.0
	802.11ac-VHT40	24.0
	802.11ac-VHT80	18.0
5.8GHz	802.11a	28.0
	802.11n-HT20	28.0
	802.11n-HT40	28.0
	802.11ac-VHT20	28.0
	802.11ac-VHT40	28.0
	802.11ac-VHT80	25.0



4. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna



5. Radio Frequency Radiation Exposure Evaluation

5.1. Standalone Power Density Calculation

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Maximum EIRP (W)	Average EIRP (mW)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)
WLAN2.4GHz 802.11b	2412.0	4.94	23.50	28.44	0.70	698.23	0.14	1.00
WLAN2.4GHz 802.11g	2412.0	4.94	22.50	27.44	0.55	554.63	0.11	1.00
WLAN2.4GHz 802.11n-HT20	2412.0	4.94	22.50	27.44	0.55	554.63	0.11	1.00
WLAN2.4GHz 802.11n-HT40	2422.0	4.94	20.50	25.44	0.35	349.95	0.07	1.00
WLAN5.2GHz 802.11a	5180.0	4.91	28.00	32.91	1.95	1954.34	0.39	1.00
WLAN5.2GHz 802.11n-HT20	5180.0	4.91	28.00	32.91	1.95	1954.34	0.39	1.00
WLAN5.2GHz 802.11n-HT40	5190.0	4.91	26.50	31.41	1.38	1383.57	0.28	1.00
WLAN5.2GHz 802.11ac-VHT20	5180.0	4.91	28.00	32.91	1.95	1954.34	0.39	1.00
WLAN5.2GHz 802.11ac-VHT40	5190.0	4.91	26.00	30.91	1.23	1233.10	0.25	1.00
WLAN5.2GHz 802.11ac-VHT80	5210.0	4.91	19.50	24.41	0.28	276.06	0.05	1.00
WLAN5.3GHz 802.11a	5260.0	4.95	22.00	26.95	0.50	495.45	0.10	1.00
WLAN5.3GHz 802.11n-HT20	5260.0	4.95	22.50	27.45	0.56	555.90	0.11	1.00
WLAN5.3GHz 802.11n-HT40	5270.0	4.95	24.00	28.95	0.79	785.24	0.16	1.00
WLAN5.3GHz 802.11ac-VHT20	5260.0	4.95	22.00	26.95	0.50	495.45	0.10	1.00
WLAN5.3GHz 802.11ac-VHT40	5270.0	4.95	24.00	28.95	0.79	785.24	0.16	1.00
WLAN5.3GHz 802.11ac-VHT80	5290.0	4.95	19.50	24.45	0.28	278.61	0.06	1.00
WLAN5.5GHz 802.11a	5500.0	4.93	22.00	26.93	0.49	493.17	0.10	1.00
WLAN5.5GHz 802.11n-HT20	5500.0	4.93	22.00	26.93	0.49	493.17	0.10	1.00
WLAN5.5GHz 802.11n-HT40	5510.0	4.93	24.00	28.93	0.78	781.63	0.16	1.00
WLAN5.5GHz 802.11ac-VHT20	5500.0	4.93	22.00	26.93	0.49	493.17	0.10	1.00
WLAN5.5GHz 802.11ac-VHT40	5510.0	4.93	24.00	28.93	0.78	781.63	0.16	1.00
WLAN5.5GHz 802.11ac-VHT80	5530.0	4.93	18.00	22.93	0.20	196.34	0.04	1.00
WLAN5.8GHz 802.11a	5745.0	4.97	28.00	32.97	1.98	1981.53	0.39	1.00
WLAN5.8GHz 802.11n-HT20	5745.0	4.97	28.00	32.97	1.98	1981.53	0.39	1.00
WLAN5.8GHz 802.11n-HT40	5755.0	4.97	28.00	32.97	1.98	1981.53	0.39	1.00
WLAN5.8GHz 802.11ac-VHT20	5745.0	4.97	28.00	32.97	1.98	1981.53	0.39	1.00
WLAN5.8GHz 802.11ac-VHT40	5755.0	4.97	28.00	32.97	1.98	1981.53	0.39	1.00
WLAN5.8GHz 802.11ac-VHT80	5775.0	4.97	25.00	29.97	0.99	993.12	0.20	1.0

Note: 1. For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band .

2. In the above table have assessed WLAN 2.4GHz and WLAN 5GHz by referring to their maximum CDD gain and maximum output power.

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.